

Interactive Logic Programming via Choice-Disjunctive Clauses

Keehang Kwon

Dept. of Computer Engineering, DongA University
Busan 604-714, Korea
khkwon@dau.ac.kr

Abstract: Adding interaction to logic programming is an essential task. Expressive logics such as linear logic provide a theoretical basis for such a mechanism. Unfortunately, none of the existing linear logic languages can model interactions with the user. This is because they use provability as the sole basis for computation.

We propose to use the game semantics instead of provability as the basis for computation to allow for more active participation from the user. We illustrate our idea via Prolog_{\oplus} , an extension of Prolog with choice-disjunctive clauses.

keywords: interaction, logic programming, linear logic, computability logic.

1 Introduction

Representing interactive objects (lottery tickets, vending machines) in logic and logic programming requires interactive knowledgebases or interactive clauses. An interactive knowledgebase must be able to allow the user to select one among many alternatives. Expressive logics such as linear logic provide a theoretical basis for such a mechanism.

Unfortunately, none of the existing linear logic languages can model decision steps from the user. This deficiency is an outcome of using provability as the sole basis for executing logic programs. In the operational semantics based on provability such as uniform provability [3, 4, 5], solving a goal G from the additive-disjunctive clause $D_0 \oplus D_1$ simply *terminates* with a success if G is solvable from both D_0 and D_1 . This semantics, pv , is shown below:

$$pv(D_0 \oplus D_1, G) \text{ if } pv(D_0, G) \text{ and } pv(D_1, G)$$

This is unsatisfactory, as the action of choosing either D_0 or D_1 by the user – the declarative reading of \oplus – is not present in this operational semantics.

Our approach in this paper involves a change of the operational semantics to allow for more active participation from the user. This is inspired by the game semantics of Japaridze [1]. Solving a goal G from the choice-disjunctive clause $D_0 \oplus D_1$ now has the following operational semantics:

$$ex(D_0 \oplus D_1, G) \text{ if } read(k) \text{ and } ex(D_i, G) \text{ and } pv(D_j, G)$$

where i ($= 0$ or 1) is chosen by the user (and stored in k) and j is $(i + 1) \bmod 2$. In the above semantics, the system requests the user to choose i and then proceeds with solving both the chosen goal, G_i , and the unchosen goal, G_j . Both executions must succeed. It is worth noting that solving G_j must proceed using pv rather than ex to disallow further interactions with the user. It can be easily seen that our new semantics has the advantage over the old semantics: the former respects the declarative reading of $\&$ without losing completeness.

As an illustration of this approach, let us consider a BMW car dealer web page where you can get the information for BMW models you choose. For an engine, you can have a gasoline model or a diesel one. For a doortype, you can have a 2door or a 4door. This is provided by the following definition:

!2door \oplus !4door.
!diesel \oplus !gas.
! bmw(120d) : – 2door \otimes diesel.
! bmw(120) : – 2door \otimes gas.
! bmw(320d) : – 4door \otimes diesel.
! bmw(320) : – 4door \otimes gas.

Here, $: -$ represents reverse implication. The definition above consists of reusable resources, denoted by $!$. As a particular example, consider a goal task $\exists x \text{ bmw}(x)$. This goal would simply terminate with no interactions from the user in the context of [3] as this goal is solvable. However, in our context, execution proceeds as follows: the system requests the user to select a particular engine model and a doortype. After they – say, 2door, diesel – is selected, execution eventually terminates with $x = 120d$.

As seen from the example above, choice-disjunctive clauses can be used to model interactive decision tasks.

To present our idea as simple as possible, this paper focuses on muprolog, which is a variant of a subset of Lolli[3]. The former can be obtained from

the latter by (a) disallowing linear context and $\&$ in the clauses, (b) allowing only \otimes in goal formulas, and (c) allowing \oplus in the clauses. Prolog_{\oplus} can also be seen as an extension of Prolog with choice-disjunctive clauses, as \otimes in Prolog_{\oplus} corresponds to \wedge of Prolog.

In this paper we present the syntax and semantics of this extended language, show some examples of its use. The remainder of this paper is structured as follows. We describe Prolog_{\oplus} based on a first-order clauses in the next section and Section 3. In Section 4, we present some examples of Prolog_{\oplus} . Section 6 concludes the paper.

2 Prolog_{\oplus} and Its Proof Procedure

The extended language is a version of Horn clauses with choice-disjunctive clauses. It is described by G -, C - and D -formulas given by the syntax rules below:

$$G ::= A \mid G \otimes G \mid \exists x G$$

$$C ::= A \mid G \supset A \mid \forall x C$$

$$D ::= !C \mid D \oplus D$$

In the rules above, A represents an atomic formula. A C -formula is called a Horn clause and a D -formula is called a choice-disjunctive clause.

In the transition system to be considered, G -formulas will function as queries and a list of D -formulas will constitute a program. We will present a proof procedure for this language as sequent system. The rules for proving queries in our language are based on two different phases. The first phase is that of processing choice-disjunctive clauses, while the second phase is that of proving traditional Prolog based on uniform provability [3, 5]. Note that choice-disjunctive clauses are processed first via pv_D^{\uparrow} . Then, execution in the second phase proceeds just like traditional logic programming. To be specific, execution in the second phase alternates between two subphases: the goal reduction subphase via pv_G (one without a distinguished clause) and the backchaining subphase via pv_D^{\downarrow} (one with a distinguished clause). Below in the notation $pv_D^{\downarrow}(D, \mathcal{P}, G)$, the D formula is a distinguished formula (marked for backchaining). The symbol $::$ is a list constructor.

Definition 1. Let G be a goal and let Δ be a list of D -formulas and let \mathcal{P}

be a set of Horn clauses. Then the task of proving G from $\Delta - pv(\Delta, G)$ – is defined as follows:

- (1) $pv(\Delta, G)$ if $pv_D^\uparrow(nil, \Delta, G)$.
- (2) $pv_D^\uparrow(\mathcal{P}, !C :: \Delta, G)$ if $pv_D^\uparrow(\{!C\} \cup \mathcal{P}, \Delta, G)$.
- (3) $pv_D^\uparrow(\mathcal{P}, (D_0 \oplus D_1) :: \Delta, G)$ if $pv_D^\uparrow(\mathcal{P}, D_0 :: \Delta, G)$ and $pv_D^\uparrow(\mathcal{P}, D_1 :: \Delta, G)$.
- (4) $pv_D^\uparrow(\mathcal{P}, nil, G)$ if $pv_G(\mathcal{P}, G)$. % switch to goal reduction mode
- (5) $pv_D^\downarrow(A, \mathcal{P}, A)$. % This is a success.
- (6) $pv_D^\downarrow((G_0 \supset A), \mathcal{P}, A)$ if $pv_G(\mathcal{P}, G_0)$.
- (7) $pv_D^\downarrow(\forall x D, \mathcal{P}, A)$ if $pv_D^\downarrow([t/x]D, \mathcal{P}, A)$.
- (8) $pv_G(\mathcal{P}, A)$ if $D \in \mathcal{P}$ and $pv_D^\downarrow(D, \mathcal{P}, A)$. % switch to backchaining mode
- (9) $pv_G(\mathcal{P}, G_0 \otimes G_1)$ if $pv_G(\mathcal{P}, G_0)$ and $pv_G(\mathcal{P}, G_1)$.
- (10) $pv_G(\mathcal{P}, \exists x G_0)$ if $pv_G(\mathcal{P}, [t/x]G_0)$.

The notion of proof defined above is intuitive enough. The following theorem – whose proof is rather obvious from the discussion in [3] and from the completeness of the focused proof system – shows the connection to linear logic.

Theorem 1 *Let Δ be a program and G be a goal in $Prolog_\oplus$. The procedure $pv(\Delta, G)$ is a success if and only if G follows from $!\Delta$ in intuitionistic linear logic.*

3 An Execution Model for $Prolog_\oplus$

We now present an execution model for $Prolog_\oplus$. This execution model is identical to the proof procedure in the previous section, except for the way choice-disjunctive clauses are handled (Rule 3 below).

In the transition system to be considered, G -formulas will function as queries and a list of D -formulas will constitute a program. We will present an operational semantics for this language as before.

Definition 2. Let G be a goal and let Δ be a list of D -formulas and let \mathcal{P} be a set of Horn clauses. Then the task of executing G from $\Delta - ex(\Delta, G) -$ is defined as follows:

- (1) $ex(\Delta, G)$ if $ex_D^\uparrow(nil, \Delta, G)$.
- (2) $ex_D^\uparrow(\mathcal{P}, !C :: \Delta, G)$ if $ex_D^\uparrow(\{!C\} \cup \mathcal{P}, \Delta, G)$.
- (3) $ex_D^\uparrow(\mathcal{P}, (D_0 \oplus D_1) :: \Delta, G)$ if $read(i)$ and $ex_D^\uparrow(\mathcal{P}, D_i :: \Delta, G)$ and $pv_D^\uparrow(\mathcal{P}, D_j :: \Delta, G)$ where i ($= 0$ or 1) is chosen by the user and j is $(i + 1) \bmod 2$.
- (4) $ex_D^\uparrow(\mathcal{P}, nil, G)$ if $ex_G(\mathcal{P}, G)$. % switch to traditional logic programming
- (5) $ex_D^\downarrow(A, \mathcal{P}, A)$. % This is a success.
- (6) $ex_D^\downarrow((G_0 \supset A), \mathcal{P}, A)$ if $ex_G(\mathcal{P}, G_0)$.
- (7) $ex_D^\downarrow(\forall x D, \mathcal{P}, A)$ if $ex_D^\downarrow([t/x]D, \mathcal{P}, A)$.
- (8) $ex_G(\mathcal{P}, A)$ if $D \in \mathcal{P}$ and $ex_D^\downarrow(D, \mathcal{P}, A)$.
- (9) $ex_G(\mathcal{P}, G_0 \otimes G_1)$ if $ex_G(\mathcal{P}, G_0)$ and $ex_G(\mathcal{P}, G_1)$.
- (10) $ex_G(\mathcal{P}, \exists x G_0)$ if $ex_G(\mathcal{P}, [t/x]G_0)$.

In the above rules, the symbol \oplus provides choice operations.

The following theorem – whose proof is easily obtained from the fact that the modified rule does not affect the soundness and completeness and can be shown using an induction on the length of derivations – shows the connection between our operational semantics and linear logic.

Theorem 2 *Let Δ be a program and G be a goal in $Prolog_\oplus$. Executing $\langle \Delta, G \rangle - ex(\Delta, G) -$ terminates with a success if and only if G follows from $!\delta$ in*

4 Examples

As an example, let us consider the following interactive database which contains tuition information for some university. The following tuition charges are in effect for this year: \$40K for medical students, \$30K for engineering and \$20K for economics.

$!med \oplus !eng \oplus !eco.$

$!tuition(40K) : -med.$

$!tuition(30K) : -eng.$

$!tuition(20K) : -eco.$

Consider a goal $\exists x \text{ tuition}(x)$. The system in Section 3 requests the user to select the current major. After the major – say, med – is selected, the system eventually produces the amount, *i.e.*, $x = 40K$.

5 An Alternative Operational Semantics

Our execution model in the previous section, although efficient, has a serious drawback: it requests the user to perform some actions in advance even when an execution leads to a failure. Fixing this problem requires fundamental changes to our execution model and adds additional complexity to the model.

To be precise, the new execution model – adapted from [1] – now requires two phases:

- (1) the proof phase: This phase builds a proof tree. This proof tree encodes all the possible execution sequences.
- (2) the execution phase: This phase requests the user to choose one execution sequence among all the possible execution sequences.

Given a program Δ and a goal G , a proof tree of $nil; ; \Delta \supset G$ is a list of tuples of the form $\langle E, i \rangle$ or $\langle E, (i, j) \rangle$ where E is a proof formula (a formula + execution mode) and i, j are the distances to F 's children in the proof tree. Below the execution mode $pv_D^\uparrow(\mathcal{P}, \Delta, G)$ is represented by a proof formula of

the form $\mathcal{P};; \Delta \supset G$, $pv_D^\downarrow(D, \mathcal{P}, A)$ by $D; \mathcal{P} \supset A$ and $pv_G(\mathcal{P}, G)$ by $\mathcal{P} \supset G$. In addition, $a_1 :: \dots :: a_n :: nil$ represents a list of n elements.

Definition 3. Let G be a goal and let \mathcal{P}, Δ be a program that consists of only reusable clauses. In addition, assume that \mathcal{P} consists of only Horn clauses. Then the task of proving $\mathcal{P};; \Delta \supset G$ and returning its proof tree L – written as $pv(\mathcal{P};; \Delta \supset G, L)$ – is defined as follows:

- (1) $pv(E, \langle E, 1 \rangle :: L)$ if $pv(\{!C\} \cup \mathcal{P};; \Delta \supset G, L)$ where E is $\mathcal{P};; (!C :: \Delta) \supset G$ % process a Horn clause in D^\uparrow mode
- (2) $pv(E, \langle E, (m+1, 1) \rangle :: L_2)$ if $pv(\mathcal{P};; (D_0 :: \Delta) \supset G, L_0)$ and $pv(\mathcal{P};; (D_1 :: \Delta) \supset G, L_1)$ and $append(L_0, L_1, L_2)$ and $length(L_1, m)$. where E is $\mathcal{P};; ((D_0 \oplus D_1) :: \Delta) \supset G$ % process a choice-disjunctive clause in D^\uparrow mode
- (3) $pv(E, \langle E, 1 \rangle :: L)$ if $pv(\mathcal{P} \supset G, L)$. where E is $\mathcal{P};; nil \supset G$ % switch from D^\uparrow mode to goal processing mode
- (4) $pv(E, \langle E, - \rangle :: nil)$ where E is $A; \mathcal{P} \supset A$. % This is a leaf node in D^\downarrow mode
- (5) $pv(E, \langle E, 1 \rangle :: L)$ if $pv(\mathcal{P} \supset G_0, L)$ where E is $(G_0 \supset A); \mathcal{P} \supset A$. % backchaining in D^\downarrow mode
- (6) $pv(E, \langle E, 1 \rangle :: L)$ if $pv([t/x]D; \mathcal{P} \supset A, L)$ where E is $\forall x D; \mathcal{P} \supset A$. % in D^\downarrow mode
- (7) $pv(E, \langle E, 1 \rangle :: L)$ if $D \in \mathcal{P}$ and $pv(D; \mathcal{P} \supset A, L)$ where E is $\mathcal{P} \supset A$. % proving an atomic goal
- (8) $pv(E, \langle E, (m+1, 1) \rangle :: L_2)$ if $pv(\mathcal{P} \supset G_0, L_0)$ and $pv(\mathcal{P} \supset G_1, L_1)$ and $append(L_0, L_1, L_2)$ and $length(L_1, m)$. where E is $\mathcal{P} \supset G_0 \otimes G_1$. % proving a conjunctive goal
- (9) $pv(E, \langle E, 1 \rangle :: L)$ if $pv(\mathcal{P} \supset [t/x]G, L)$ where E is $\mathcal{P} \supset \exists x G$.

Here, \mathcal{P} is initialized to an empty list.

Once a proof tree is built, the execution phase actually solves the goal relative to the program using the proof tree. Below A *choose* B means that

the machine must choose a successful one between the task A and the task B.

Definition 4. Let i be an index and let L be a proof tree. Then executing L_i (the i element in L) – written as $exec(i, L)$ – is defined as follows:

- (1) $exec(i, L)$ if $L_i = (E, -)$. % success
- (2) $exec(i, L)$ if $L_i = (\mathcal{P} \supset G_0 \otimes G_1, (n, m))$ and $exec(i-n, L)$ and $exec(i-m, L)$. % the case of two children
- (3) $exec(i, L)$ if $L_i = (\mathcal{P}; (D_0 \oplus D_1) :: \Delta \supset G, (n, m))$ and $read(k)$ and $((k == 0$ and $exec(i-n, L))$ choose $(k == 1$ and $exec(i-m, L))$). % In the case of choice disjunctive clauses, the machine requests the user to choose one between D_0 and D_1 and then executes the chosen path.
- (4) $exec(i, L)$ if $L_i = (E, 1)$ and $exec(i-1, L)$. % the remaining cases

Now given a program Δ and a goal G , L is initialized to the proof tree of $nil; \Delta \supset G$ and n is initialized to the length of L .

6 Conclusion

In this paper, we have considered an extension to Prolog with choice-disjunctive clauses in linear logic. This extension allows clauses of the form $D_0 \oplus D_1$ where D_0, D_1 are Horn clauses. In particular, these clauses make it possible for Prolog to model decision steps from the user.

At this stage, clauses of more complex forms such as $!(D \oplus D)$ or $(D \wedge D)$ are not allowed in our language. We plan to allow them in the future. We also plan to connect our execution model to Japaridze’s expressive Computability Logic [1, 2] in the near future.

References

- [1] G. Japaridze, “Introduction to computability logic”, Annals of Pure and Applied Logic, vol.123, pp.1–99, 2003.
- [2] G. Japaridze, “Sequential operators in computability logic”, Information and Computation, vol.206, No.12, pp.1443-1475, 2008.

- [3] J. Hodas and D. Miller, “Logic Programming in a Fragment of Intuitionistic Linear Logic”, *Information and Computation*, vol.110, No.2, pp.327-365, 1994.
- [4] D. Miller, “A logical analysis of modules in logic programming”, *Journal of Logic Programming*, vol.6, pp.79–108, 1989.
- [5] D. Miller, G. Nadathur, F. Pfenning, and A. Scedrov, “Uniform proofs as a foundation for logic programming”, *Annals of Pure and Applied Logic*, vol.51, pp.125–157, 1991.