# Fully Dynamic k-Median with Near-Optimal Update Time and Recourse

Sayan Bhattacharya University of Warwick s.bhattacharya@warwick.ac.uk

Martín Costa University of Warwick martin.costa@warwick.ac.uk

Ermiya Farokhnejad University of Warwick ermiya.farokhnejad@warwick.ac.uk

#### Abstract

In metric  $k$ -clustering, we are given as input a set of  $n$  points in a general metric space, and we have to pick k centers and cluster the input points around these chosen centers, so as to minimize an appropriate objective function. In recent years, significant effort has been devoted to the study of metric k-clustering problems in a dynamic setting, where the input keeps changing via updates (point insertions/deletions), and we have to maintain a good clustering throughout these updates [Fichtenberger, Lattanzi, Norouzi-Fard and Svensson, SODA'21; Bateni, Esfandiari, Fichtenberger, Henzinger, Jayaram, Mirrokni and Weise, SODA'23; Lacki, Haeupler, Grunau, Rozhon and Jayaram, SODA'24; Bhattacharya, Costa, Garg, Lattanzi and Parotsidis, FOCS'24; Forster and Skarlatos, SODA'25]. The performance of such a dynamic algorithm is measured in terms of three parameters: (i) Approximation ratio, which signifies the quality of the maintained solution, (ii) Recourse, which signifies how stable the maintained solution is, and (iii) Update time, which signifies the efficiency of the algorithm.

We consider a textbook metric k-clustering problem, metric k-median, where the objective is the sum of the distances of the points to their nearest centers. We design the first dynamic algorithm for this problem with near-optimal guarantees across all three performance measures (up to a constant factor in approximation ratio, and polylogarithmic factors in recourse and update time). Specifically, we obtain a  $O(1)$ -approximation algorithm for dynamic metric kmedian with  $\hat{O}(1)$  recourse and  $\hat{O}(k)$  update time. Prior to our work, the state-of-the-art here was the recent result of [Bhattacharya, Costa, Garg, Lattanzi and Parotsidis, FOCS'24], who obtained  $O(\epsilon^{-1})$ -approximation ratio with  $\tilde{O}(k^{\epsilon})$  recourse and  $\tilde{O}(k^{1+\epsilon})$  update time.

We achieve our results by carefully synthesizing the concept of *robust centers* introduced in [Fichtenberger, Lattanzi, Norouzi-Fard and Svensson, SODA'21] along with the randomized local search subroutine from [Bhattacharya, Costa, Garg, Lattanzi and Parotsidis, FOCS'24], in addition to several key technical insights of our own.

# Contents







# 17 Obtaining  $\tilde{O}(k)$  [Amortized Update Time](#page-72-1) 69

# <span id="page-4-0"></span>Part I Extended Abstract

# <span id="page-4-1"></span>1 Introduction

Consider a metric space  $(\mathcal{P}, d)$  over a set  $\mathcal P$  of n points, with a distance function  $d : \mathcal{P} \times \mathcal{P} \to \mathbb{R}^{\geq 0}$ , and a positive integer  $k \leq n$ . In the *metric k-median* problem, we have to pick a set  $\mathcal{U} \subseteq \mathcal{P}$  of k centers, so as to minimize the objective function  $\text{Cost}(\mathcal{U}, \mathcal{P}) := \sum_{p \in \mathcal{P}} d(p, \mathcal{U})$ , where  $d(p, \mathcal{U}) :=$  $\min_{q \in \mathcal{U}} d(p,q)$  denotes the distance between a point p and its nearest center in U. We assume that we have access to the function d via a distance oracle, which returns the value of  $d(p, q)$  for any two points  $p, q \in \mathcal{P}$  in  $O(1)$  time. We further assume that  $1 \leq d(p, q) \leq \Delta$  for all  $p, q \in \mathcal{P}, p \neq q$ , where  $\Delta$  is an upper bound on the *aspect ratio* of the metric space.

Metric k-median is a foundational problem in clustering, is known to be NP-hard, and approximation algorithms for this problem are taught in standard textbooks [\[WS11\]](#page-75-1). In particular, it has a  $O(1)$  $O(1)$  $O(1)$ -approximation algorithm that runs in  $\tilde{O}(kn)$  time [\[MP02\]](#page-75-2),<sup>1</sup> and it is known that we *cannot* have any  $O(1)$ -approximation algorithm for metric k-median with  $o(kn)$  runtime [\[BCIS05\]](#page-74-1).

In recent years, substantive effort have been devoted to the study of this problem in a *dynamic* setting, when the underlying input changes over time  $[UV17, CHP<sup>+</sup>19, FLNS21, HK20, BCLP23,$  $[UV17, CHP<sup>+</sup>19, FLNS21, HK20, BCLP23,$ [DHS24,](#page-75-5)  $BCG^+24$  $BCG^+24$ . To be more specific, here the input changes by a sequence of updates; each update inserts/deletes a point in  $P$ . Throughout these updates, we have to maintain a set of k centers  $U \subseteq \mathcal{P}$  which form an approximate k-median solution to the current input  $\mathcal{P}$ . Such a dynamic algorithm's performance is measured in terms of its: (i) Approximation ratio, (ii) Recourse, which is the number of changes (i.e., point insertions/deletions) in the maintained solution  $\mathcal{U}$  per update, and (iii) Update time, which is the time taken by the algorithm to process an update. In a sense, approximation ratio and recourse respectively measures the "quality" and the "stability" of the maintained solution, whereas update time measures the "efficiency" of the algorithm.

<span id="page-4-4"></span>We design a dynamic algorithm for this problem with almost optimal performance guarantees with respect to all these measures. Our main result is summarized in the theorem below.

Theorem 1.1. There is a randomized dynamic algorithm for the metric k-median problem that has  $O(1)$ -approximation ratio,  $O(\log^2 \Delta)$  $O(\log^2 \Delta)$  $O(\log^2 \Delta)$  recourse and  $\tilde{O}(k)$  update time, w.h.p.<sup>2</sup>

Remarks. A few important remarks are in order. First, note that there cannot exist a dynamic  $O(1)$ -approximation algorithm for our problem with  $o(k)$  update time, for otherwise we would get a *static* algorithm for metric k-median with  $O(1)$ -approximation ratio and  $o(kn)$  runtime: Simply let the dynamic algorithm handle a sequence of  $n$  insertions corresponding to the points in the static input, and return the solution maintained by the dynamic algorithm at the end of this update sequence. This would contradict the  $\Omega(kn)$  lower bound on the runtime of any such static algorithm, derived in [\[BCIS05\]](#page-74-1). Furthermore, it is easy to verify that we cannot achieve  $o(1)$ recourse in the fully dynamic setting, and hence, our dynamic algorithm is almost optimal (up to a  $O(1)$  factor in approximation ratio and polylogarithmic factors in recourse and update time).

Second, in this extended abstract we focus the unweighted metric k-median problem, only to ease notations. In the full version (see Part [III\)](#page-35-0), we show that Theorem [1.1](#page-4-4) seamlessly extends to the weighted setting, where each point  $p \in \mathcal{P}$  has a weight  $w(p) > 0$  associated with it, and we have

<span id="page-4-2"></span><sup>&</sup>lt;sup>1</sup>Throughout this paper, we use the  $\tilde{O}(\cdot)$  notation to hide polylogarithmic factors in k, n and  $\Delta$ .

<span id="page-4-3"></span><sup>2</sup>Both our recourse and update time bounds are amortized. Throughout the paper, we do not make any distinction between amortized vs worst-case bounds.

to maintain a set U of k centers that (approximately) minimizes  $\sum_{p\in\mathcal{P}} w(p) \cdot d(p, \mathcal{U})$ . Moreover, our result extends to the related *metric k-means* problem as well, where we have to pick a set  $\mathcal{U} \subseteq \mathcal{P}$  of k centers so as to minimize  $\sum_{p \in \mathcal{P}} (d(p, \mathcal{U}))^2$ . We can get a dynamic  $O(1)$ -approximation algorithm for (weighted) metric k-means that has  $\tilde{O}(1)$  recourse and  $\tilde{O}(k)$  update time, w.h.p.

Finally, Table [1](#page-5-1) compares our result against prior state-of-the-art. Until very recently, all known algorithms  $\text{CHP}^+19$ , [HK20,](#page-75-4) BCLP23 for fully dynamic metric k-median had a trivial recourse bound of  $\Omega(k)$ , which can be obtained by computing a new set of k centers from scratch after every update (at the expense of  $\Omega(kn)$  update time). Then, in FOCS 2024, [\[BCG](#page-74-0)+24] took a major step towards designing an almost optimal algorithm for this problem, by achieving  $O(\epsilon^{-1})$ approximation ratio,  $\tilde{O}(k^{1+\epsilon})$  update time and  $\tilde{O}(k^{\epsilon})$  recourse. To achieve truly polylogarithmic recourse and  $\tilde{O}(k)$  update time using the algorithm of [\[BCG](#page-74-0)<sup>+</sup>24], we have to set  $\epsilon = O\left(\frac{\log \log k}{\log k}\right)$  $\frac{\log \log k}{\log k}$ . This, however, increases the approximation guarantee to  $\Omega\left(\frac{\log k}{\log \log k}\right)$  $\frac{\log k}{\log \log k}$ . In contrast, we achieve  $O(1)$ -approximation ratio,  $\tilde{O}(k)$  update time and  $\tilde{O}(1)$  recourse.

Approximation Ratio	Update Time	Recourse	Paper
O(1)	$O(n+k^2)$	O(k)	$[CHP+19]$
O(1)	$\tilde{O}(k^2)$	O(k)	[HK20]
O(1)	$\tilde{O}(k^2)$	O(k)	$[BCLP23]$ <sup>3</sup>
$O(\epsilon^{-1})$	$\tilde{O}(k^{1+\epsilon})$	$\tilde{O}(k^{\epsilon})$	$[BCG+24]$
O(1)	$\tilde{O}(k)$	$O(\log^2 \Delta)$	Our Result

<span id="page-5-1"></span>Table 1: State-of-the-art for fully dynamic metric  $k$ -median. The table for fully dynamic metric k-means is identical, except that the approximation ratio of  $[BCG^+24]$  is  $O(\epsilon^{-2})$ .

Related Work. In addition to metric k-median, two related clustering problems have been exten-sively studied in the dynamic setting: (i) metric k-center [\[CGS18,](#page-74-4) [BEF](#page-74-5)<sup>+</sup>23, [LHG](#page-75-6)<sup>+</sup>24, [BCG](#page-74-0)<sup>+</sup>24, [FS25,](#page-75-7) BCLP24 and (ii) metric facility location  $\lbrack \text{CHP+19, BLP22} \rbrack$ . Both these problems are relatively well-understood by now. For example, it is known how to simultaneously achieve  $O(1)$ approximation ratio,  $O(1)$  recourse and  $O(k)$  update time for dynamic metric k-center [\[BCLP24\]](#page-74-6). They have also been studied under special classes of metrics, such as Euclidean spaces  $\lbrack \text{GHL}^+21 \rbrack$ , [BEF](#page-74-5)<sup>+</sup>23, [BGJ](#page-74-8)<sup>+</sup>24], or shortest-path metrics in graphs undergoing edge-updates [\[CFG](#page-74-9)<sup>+</sup>24].

There is another line of work on dynamic metric k-center and metric k-median, which considers the incremental (insertion only) setting, and achieves total recourse guarantees that are sublinear in the total number of updates [\[LV17,](#page-75-3) [FLNS21\]](#page-75-0). However, the update times of these algorithms are large polynomials in n. Section [2.2](#page-7-0) contains a detailed discussion on the algorithm of [\[FLNS21\]](#page-75-0).

## <span id="page-5-0"></span>2 Technical Overview

In Sections [2.1](#page-6-0) and [2.2,](#page-7-0) we summarize the technical contributions of two relevant papers  $[BCG^+24,$ [FLNS21\]](#page-75-0). We obtain our algorithm via carefully synthesizing the techniques from both these papers, along with some key, new insights of our own. In Section [2.3,](#page-8-0) we outline the major technical challenges we face while trying to prove Theorem [1.1,](#page-4-4) and how we overcome them.

<span id="page-5-2"></span><sup>&</sup>lt;sup>3</sup>We remark that [\[BCLP23\]](#page-74-3) actually maintain a  $O(1)$  approximate "sparsifier" of size  $\tilde{O}(k)$  in  $\tilde{O}(k)$  update time, and they need to run the static algorithm of [\[MP00\]](#page-75-9) on top of this sparsifier after every update. This leads to an update time of  $\tilde{O}(k^2)$  for the dynamic k-median and k-means problems.

## <span id="page-6-0"></span>2.1 The Fully Dynamic Algorithm of  $[BCG^+24]$

<span id="page-6-1"></span>There are two main technical contributions in  $[BCG^+24]$ ; we briefly review each of them below.

#### 2.1.1 A Hierarchical Approach to Dynamic k-Median

This approach allows the authors to obtain  $O(\epsilon^{-1})$ -approximation ratio with  $\tilde{O}(k^{\epsilon})$  recourse, and works as follows. We maintain a hierarchy of nested subsets of centers  $S_0 \supseteq \cdots \supseteq S_{\ell+1}$ , where  $\ell = 1/\epsilon$  and  $|S_i| = k + \lfloor k^{1-i\epsilon} \rfloor$  for each  $i \in [0, \ell + 1]$ . We refer to  $s_i := \lfloor k^{1-i\epsilon} \rfloor$  as the slack at layer i of the hierarchy. The set  $S_{\ell+1}$  has size exactly k and is the k-median solution maintained by the algorithm. We always maintain the following invariant.

<span id="page-6-4"></span>**Invariant 2.1.** Cost  $(S_0, \mathcal{P}) = O(1) \cdot \text{OPT}_k(\mathcal{P})$ , and Cost  $(S_i, \mathcal{P}) \leq \text{Cost}(S_{i-1}, \mathcal{P}) + O(1) \cdot \text{OPT}_k(\mathcal{P})$ for each  $i \in [1, \ell]$ . Here,  $\text{OPT}_k(\mathcal{P})$  is the optimal k-median objective w.r.t. the input point-set  $\mathcal{P}$ .

Given this invariant, we infer that  $\text{Cost}(S_{\ell+1}) = O(\ell) \cdot \text{OPT}_k(\mathcal{P}) = O(1/\epsilon) \cdot \text{OPT}_k(\mathcal{P})$ . Thus, the approximation guarantee is proportional to the number of layers in this hierarchy.

The hierarchy is maintained by periodically reconstructing each of the sets  $S_i$ . To be more specific, each set  $S_i$  (along with the sets  $S_{i+1}, \ldots, S_{\ell+1}$ ) is reconstructed from scratch every  $s_i$ many updates, without modifying the sets  $S_0, \ldots, S_{i-1}$ . In between these updates, the subset  $S_i$ is maintained lazily: Whenever a point p is inserted into P, we set  $S_i \leftarrow S_i \cup \{p\}$ , and whenever a point is deleted from  $P$ , no changes are made to  $S_i$ .<sup>[4](#page-6-3)</sup>

To analyze the recourse, consider the solution  $S_{\ell+1}$  before and after an update during which  $S_i$ is reconstructed. Let  $S'_{\ell+1}$  and  $S''_{\ell+1}$  denote the status of the solution before and after the update, respectively. Observe that the total recourse incurred in the solution  $S_{\ell+1}$  during this update, i.e. the value  $|S'_{\ell+1}\oplus S''_{\ell+1}|$ , is  $O(s_{i-1})$ . This follows immediately from the fact that  $S'_{\ell+1}$  and  $S''_{\ell+1}$ are both subsets of size k of the set  $S_{i-1}$ , which has size  $\leq k+2s_{i-1}$ . We can amortize this recourse over the  $s_i$  many lazy updates performed since the last time that  $S_i$  was reconstructed. This implies that the amortized recourse of  $S_{\ell+1}$  which is caused by reconstructing  $S_i$  is  $O(s_{i-1}/s_i) = O(k^{\epsilon})$ . Summing over all  $i \in [0, \ell+1]$ , we get an overall amortized recourse bound of  $O((\ell+2) \cdot k^{\epsilon}) = O(k^{\epsilon}/\epsilon)$ .

Barrier towards achieving  $O(1)$ -approximation with  $O(1)$  recourse. If we want to use this hierarchy to obtain a recourse of  $\tilde{O}(1)$ , then we need to ensure that  $s_i = \Omega(s_{i-1})$  (i.e., we need the slacks at the layers to decrease by at most a  $\tilde{O}(1)$  factor between the layers). If this is not the case, then the amortized recourse in  $S_{\ell+1}$  caused by reconstructing  $S_i$  will be  $\Omega(s_{i-1}/s_i) = \tilde{\omega}(1)$ . Unfortunately, to have such a guarantee, the number of layers needs to be  $\Omega(\log k / \log \log k)$ ; and since the approximation ratio of the algorithm is proportional to the number of layers (see Invariant [2.1\)](#page-6-4), this leads to an approximation ratio of  $\omega(1)$ . Thus, it is not at all clear if this approach can be used to obtain  $O(1)$ -approximation and  $O(1)$  recourse simultaneously.

# <span id="page-6-2"></span>2.1.2 Achieving  $\tilde{O}(k^{1+\epsilon})$  Update Time via Randomized Local Search

The second technical contribution in  $[BCG^+24]$  is to show that the hierarchy from Section [2.1.1](#page-6-1) can be maintained in  $\tilde{O}(k^{1+\epsilon})$  update time, using a specific type of *randomized local search*.

To be more specific, consider a set of n points P, a set of k centers U, and an integer  $s \in$ [1, k – 1]. Suppose that we want to compute a subset  $\mathcal{U}' \subseteq \mathcal{U}$  of  $(k - s)$  centers, so as to minimize Cost  $(U', \mathcal{P})$ . In [\[BCG](#page-74-0)<sup>+</sup>24], the authors present a O(1)-approximation algorithm for this problem

<span id="page-6-3"></span><sup>&</sup>lt;sup>4</sup>We can afford to handle the *deletions* in this lazy manner if we consider the improper  $k$ -median problem, where we are allowed to open a center at a point that got deleted. See the discussion in the beginning of Section [3.](#page-10-1)

using randomized local search, that runs in only  $\ddot{O}(ns)$  time, assuming the algorithm has access to some "auxiliary data structures" to begin with (see Lemma [6.1\)](#page-20-3).

Morally, the important message here is that the runtime of randomized local search (when given access to some auxiliary data structures) is proportional to the slack s, and independent of k. In  $[BCG^+24]$  $[BCG^+24]$ , the authors call this procedure as a subroutine while reconstructing a set  $S_i$  (along with the sets  $S_{i+1}, \ldots, S_{\ell+1}$  in the hierarchy from scratch, after every  $s_i$  many updates. Although our algorithm does not use a hierarchical approach while bounding the approximation ratio and recourse, we use randomized local search to achieve fast update time (see Section [2.3\)](#page-8-0).

## <span id="page-7-0"></span>2.2 The Incremental Algorithm of [\[FLNS21\]](#page-75-0)

In [\[FLNS21\]](#page-75-0), the authors obtain  $O(k)$  total recourse, while maintaining a  $O(1)$ -approximate kmedian solution over a sequence of  $n$  point insertions (starting from an empty input). Note that in this incremental setting, the total recourse is sublinear in the number of updates; this is achieved by using a technique known as *Myerson sketch* [\[Mey01\]](#page-75-10). Since it is not possible to achieve such a sublinear total recourse bound in the fully dynamic setting (the focus of our paper), in Theorem [2.2](#page-7-2) we summarize the main result of [\[FLNS21\]](#page-75-0) without invoking Myerson sketch. We emphasize that the update time in  $[FLNS21]$  is already prohibitively high (some large polynomial in n) for our purpose. Accordingly, to highlight the main ideas in the rest of this section, we will outline a variant of the algorithm in [\[FLNS21\]](#page-75-0) with *exponential* update time.

<span id="page-7-2"></span>**Theorem 2.2** ([\[FLNS21\]](#page-75-0)). Suppose that the input  $P$  undergoes a sequence of point-insertions. Then, we can maintain a  $O(1)$ -approximate k-median solution to  $P$  with  $O(1)$  amortized recourse.

A major technical insight in [\[FLNS21\]](#page-75-0) was to introduce the notion of robust centers. Informally, a set of centers U is robust w.r.t. a point-set P, iff each  $u \in U$  is a good approximate 1-median solution at every "distance-scale" w.r.t. the points in  $P$  that are sufficiently close to u. See Section [3.2](#page-11-1) for a formal definition. Below, we present our interpretation of the incremental algorithm in [\[FLNS21\]](#page-75-0). We start with a key lemma summarizing an important property of robust centers.

Consider any integer  $0 \leq \ell \leq k$ . We say that a set of k centers U is maximally  $\ell$ -stable w.r.t. a point-set  $\mathcal P$  iff  $\mathrm{OPT}_{k-\ell}^{\mathcal U}(\mathcal P)\le c\cdot{\sf Cost}\left(\mathcal U,\mathcal P\right)$  and  $\mathrm{OPT}_{k-(\ell+1)}^{\mathcal U}(\mathcal P)>c\cdot{\sf Cost}\left(\mathcal U,\mathcal P\right),$  where  $c=456000$ is an absolute constant, and  $\mathrm{OPT}_t^{\mathcal{U}}(\mathcal{P}) := \min_{Z \subseteq \mathcal{U}: |Z| \leq t} \mathsf{Cost}(Z, \mathcal{P})$  is the objective of the optimal t-median solution subject to the restriction that all the centers must be from the set  $\mathcal{U}$ . This means that we can afford to remove  $\ell$  centers from  $\mathcal U$  without increasing the objective value by more than a  $O(1)$  factor, but not more than  $\ell$  centers. We defer the proof of Lemma [2.3](#page-7-1) to Section [9.](#page-34-1)

<span id="page-7-1"></span>**Lemma 2.3** ([\[FLNS21\]](#page-75-0)). Consider any two point-sets  $\mathcal{P}_{init}$  and  $\mathcal{P}_{final}$  with  $|\mathcal{P}_{init} \oplus \mathcal{P}_{final}| \leq \ell+1$ , for  $\ell \in [0,k]$ .<sup>[5](#page-7-3)</sup> W.r.t.  $\mathcal{P}_{\text{init}}$ , let  $\mathcal{U}_{\text{init}}$  be any set of k centers that is robust and maximally  $\ell$ -stable. Let V be any set of k centers such that  $Cost(V, \mathcal{P}_{init}) \leq 18 \cdot Cost(\mathcal{U}_{init}, \mathcal{P}_{init})$ . Then, there is a set of k centers  $W^*$ , such that  $|W^* \oplus \mathcal{U}_{init}| \leq 5\ell + 5$  and  $Cost(W^*, \mathcal{P}_{final}) \leq 3 \cdot Cost(V, \mathcal{P}_{final})$ .

The algorithm works in  $O(1)$  many *phases*, where each phase consists of a sequence of consecutive updates (only insertions) such that the optimal objective value, given by  $\text{OPT}_k(\mathcal{P})$ , does not increase by more than a factor of 18 within any given phase. The algorithm restarts whenever one phase terminates and the next phase begins, and computes a new k-median solution to the current input from scratch. Within each phase, the algorithm incurs  $O(n)$  total recourse, and this implies the amortized recourse guarantee of  $O(1)$ . Each phase is further partitioned into *epochs*, as follows.

<span id="page-7-3"></span> ${}^{5}$ Here, the notation  $\oplus$  denotes the symmetric difference between two sets.

By induction hypothesis, we start an epoch with an 100-approximate k-median solution  $\mathcal{U}_{\text{init}}$ that is robust and also maximally  $\ell$ -stable, for some  $\ell \in [0, k]$ , w.r.t. the current input  $\mathcal{P}_{\text{init}}$ . Let  $\lambda_{\text{init}} := \text{OPT}_k(\mathcal{P}_{\text{init}})$  denote the optimal objective value at this point in time. We then compute a subset  $\mathcal{U} \subseteq \mathcal{U}_{\text{init}}$  of  $(k - \ell)$  centers, such that Cost  $(\mathcal{U}, \mathcal{P}_{\text{init}}) \leq c \cdot \text{Cost}(\mathcal{U}_{\text{init}}, \mathcal{P}_{\text{init}}) \leq$  $100c \cdot \text{OPT}_k(\mathcal{P}_{\text{init}}) = 100c \cdot \lambda_{\text{init}}$ . The epoch lasts for the next  $(\ell+1)$  updates.

The algorithm *lazily* handles the first  $\ell$  updates in the epoch, incurring a worst-case recourse of one per update: Whenever a point p gets inserted into P, it sets  $\mathcal{U} \leftarrow \mathcal{U} \cup \{p\}$ . Since initially  $|U| = k - \ell$ , the set U never grows large enough to contain more than k centers. Further, the objective of the maintained solution  $\mathcal U$  does not increase due to these  $\ell$  updates, and remains

<span id="page-8-2"></span>
$$
Cost(\mathcal{U}, \mathcal{P}) \le 100c \cdot \lambda_{\text{init}} \le 200c \cdot \text{OPT}_k(\mathcal{P}),\tag{1}
$$

where the last inequality holds because  $\text{OPT}_k(\mathcal{P})$  is almost monotone as P undergoes pointinsertions (more precisely, it can decrease by at most a factor of 2).

While handling the last (i.e.,  $(\ell + 1)^{th}$ ) update in the epoch, our goal is to come up with a k-median solution  $U_{final}$  such that: (i) the induction hypothesis holds w.r.t.  $U_{final}$  and  $P_{final}$ (where  $\mathcal{P}_{\texttt{final}}$  is the state of the input at the end of the epoch), and (ii) the recourse remains small, i.e.,  $|\mathcal{U}_{\text{final}} \oplus \mathcal{U}_{\text{init}}| = O(\ell+1)$ . We can assume that  $\text{OPT}_k(\mathcal{P}_{\text{final}}) \leq 18 \cdot \lambda_{\text{init}}$ , for otherwise we would initiate a new phase at this point in time.

We find the set  $\mathcal{U}_{\text{final}}$  as follows. Let V be an optimal k-median solution w.r.t.  $\mathcal{P}_{\text{final}}$ , so that:

<span id="page-8-3"></span>
$$
\text{Cost}\left(\mathcal{V}, \mathcal{P}_{\text{init}}\right) \leq \text{Cost}\left(\mathcal{V}, \mathcal{P}_{\text{final}}\right) = \text{OPT}_k(\mathcal{P}_{\text{final}}) \leq 18\cdot \text{OPT}_k(\mathcal{P}_{\text{init}}) \leq 18\cdot \text{Cost}\left(\mathcal{U}_{\text{init}}, \mathcal{P}_{\text{init}}\right). \tag{2}
$$

Applying Lemma [2.3,](#page-7-1) we find a set of k centers  $\mathcal{W}^*$  such that

<span id="page-8-4"></span>
$$
|\mathcal{W}^{\star}\oplus\mathcal{U}_{\mathtt{init}}|\leq 5\ell+5\ \mathrm{and}\ \mathsf{Cost}\,(\mathcal{W}^{\star},\mathcal{P}_{\mathtt{final}})\leq 3\cdot\mathsf{Cost}\,(\mathcal{V},\mathcal{P}_{\mathtt{final}})=3\cdot\mathrm{OPT}_k(\mathcal{P}_{\mathtt{final}}). \tag{3}
$$

Next, we call a subroutine ROBUSTIFY $(W^*)$  which returns a set of k robust centers  $\mathcal{U}_{\text{final}}$  such that  $\textsf{Cost}\left(\mathcal{U}_{\texttt{final}}, \mathcal{P}_{\texttt{final}}\right) \leq (3/2) \cdot \textsf{Cost}\left(\mathcal{W}^\star, \mathcal{P}_{\texttt{final}}\right) = (9/2) \cdot \textsf{OPT}_k(\mathcal{P}_{\texttt{final}}) \leq 100 \cdot \textsf{OPT}_k(\mathcal{P}_{\texttt{final}})$  (see Lemma [3.7\)](#page-12-3). This restores the induction hypothesis for the next epoch, w.r.t.  $\mathcal{U}_{\text{final}}$  and  $\mathcal{P}_{\text{final}}$ . We can show that the subroutine ROBUSTIFY works in such a manner that the step where we transition from  $W^*$  to  $\mathcal{U}_{\text{final}}$  incurs at most  $\tilde{O}(1)$  recourse, amortized over the entire sequence of updates within a phase (spanning across multiple epochs). This implies Theorem [2.2.](#page-7-2)

#### <span id="page-8-0"></span>2.3 Our Approach

At a high level, we achieve our result in two parts. First, we generalize the framework of [\[FLNS21\]](#page-75-0) to achieve  $O(1)$ -approximation and  $O(1)$  recourse in the fully dynamic setting. Second, we use the randomized local search procedure to implement our algorithm in  $O(k)$  update time. In addition, both these parts require us to come up with important and new technical insights of our own. Below, we explain three significant challenges and outline how we overcome them. Challenge I and Challenge II refers to the first part (approximation and recourse guarantees), whereas Challenge III refers to the third part (update time guarantee).

#### <span id="page-8-1"></span>2.3.1 Challenge I: Double-sided Stability

In Section [2.2,](#page-7-0) we crucially relied on the observation that the optimal  $k$ -median objective is (almost) monotonically increasing as more and more points get inserted into  $P$ . This allowed us to derive Equation [\(1\)](#page-8-2), which guarantees that the maintained solution  $\mathcal U$  remains  $O(1)$ -approximate while we lazily handle the first  $\ell$  updates within the epoch. This guarantee, however, breaks down in the fully dynamic setting: If points can get deleted from  $P$ , then within an epoch we might end up in a situation where  $\text{OPT}_k(\mathcal{P}) \ll \lambda_{\text{init}}$ . To address this issue, we derive a new *double-sided* stability property in the fully dynamic setting (see Lemma [4.1\)](#page-13-3). Informally, this implies that if  $\text{OPT}_{k-\ell}(\mathcal{P}_{\text{init}}) = \Theta(1) \cdot \text{OPT}_k(\mathcal{P}_{\text{init}})$  (which follows from the hypothesis at the start of an epoch), then for some  $\Theta(\ell) = r \leq \ell$  we have  $\text{OPT}_{k+r}(\mathcal{P}_{\text{init}}) = \Theta(1) \cdot \text{OPT}_k(\mathcal{P}_{\text{init}})$ . Furthermore, we have  $|\mathcal{P} \oplus \mathcal{P}_{\text{init}}| \leq r$  throughout the first r updates in the epoch, which gives us:  $\text{OPT}_k(\mathcal{P}) \geq$  $\text{OPT}_{k+r}(\mathcal{P}_{\text{init}})$  (see Lemma [3.11\)](#page-13-7). It follows that for the first r updates in the epoch, we have  $\text{OPT}_k(\mathcal{P}) \geq \text{OPT}_{k+r}(\mathcal{P}_{\text{init}}) = \Theta(1) \cdot \text{OPT}_k(\mathcal{P}_{\text{init}}) = \Theta(1) \cdot \lambda_{\text{init}}$ . Accordingly, we truncate the epoch to last for only  $r + 1$  updates, and now we can rule out the scenario where  $\text{OPT}_k(\mathcal{P})$  drops significantly below  $\lambda_{\text{init}}$  during the epoch. But since  $r = \Omega(\ell)$ , the epoch remains sufficiently long, so that we can still manage to generalize the recourse analysis from Section [2.2.](#page-7-0)

#### <span id="page-9-0"></span>2.3.2 Challenge II: Getting Rid of the Phases

To derive Equation [\(2\)](#page-8-3), we need to have  $\text{OPT}_k(\mathcal{P}_{\text{final}}) \leq 18 \cdot \text{OPT}_k(\mathcal{P}_{\text{init}})$ . This is precisely the reason why the algorithm in [\[FLNS21\]](#page-75-0) works in *phases*, so that  $\text{OPT}_k(\mathcal{P})$  increases by at most a  $O(1)$  factor within each phase. Further, the analysis in [\[FLNS21\]](#page-75-0) crucially relies on showing that we incur  $O(n)$  total recourse within a phase. This, combined with the fact that there are  $O(1)$ phases overall in the incremental setting, implies the amortized recourse guarantee.

From the preceding discussion, it becomes apparent that we cannot hope to extend such an argument in the fully dynamic setting, because it is not possible to argue that we have at most  $O(1)$  phases when the value of  $\text{OPT}_k(\mathcal{P})$  can fluctuate in either direction (go up or down) over a sequence of fully dynamic updates. To circumvent this obstacle, we make the following subtle but important change to the framework of [\[FLNS21\]](#page-75-0). Recall Equation [\(3\)](#page-8-4). Note that we can find the set  $W^*$  by solving the following computational task:<sup>[6](#page-9-1)</sup> Compute the set  $W^*$  of k centers, which minimizes the k-median objective w.r.t.  $\mathcal{P}_{final}$ , subject to the constraint that it can be obtained by adding/removing  $\Theta(\ell+1)$  points in  $\mathcal{U}_{\text{init}}$ . Informally, in our algorithm, we replace this task by three separate (and new) tasks, which we perform one after another (see Step 4 in Section [5.1\)](#page-14-1).

- Task (i). Find a set of  $k + \Theta(\ell + 1)$  centers  $\mathcal{U}^*$ , which minimizes the  $(k + \ell + 1)$ -median objective w.r.t.  $\mathcal{P}_{\text{init}}$ , such that  $\mathcal{U}^*$  is obtained by adding  $\Theta(\ell+1)$  many centers to  $\mathcal{U}_{\text{init}}$ .
- Task (ii). Set  $\mathcal{V}^* \leftarrow \mathcal{U}^* \cup (\mathcal{P}_{\text{final}} \setminus \mathcal{P}_{\text{init}}).$
- Task (iii). Find a set of k centers  $W^*$ , which minimizes the k-median objective w.r.t.  $P_{final}$ , such that  $W^*$  is obtained by removing  $\Theta(\ell+1)$  many centers from  $V^*$ .

Thus, while adding centers in Task (i), we optimize the  $(k + \ell + 1)$ -median objective w.r.t.  $\mathcal{P}_{init}$ . On the other hand, while removing centers in Task (iii), we optimize the  $k$ -median objective w.r.t.  $P_{final}$ . This is in sharp contrast to the approach in [\[FLNS21\]](#page-75-0), where we need to optimize the k-median objective w.r.t.  $\mathcal{P}_{final}$ , both while adding centers and while removing centers. Strikingly, we show that this modification allows us to get rid of the concept of phases altogether. In particular, our algorithm can be cast in the classical periodic recomputation framework: We work in epochs. Within an epoch we handle the updates lazily, and at the end of the epoch we reinitialize our maintained solution so that we get ready to handle the next epoch. See Section [5.3](#page-18-0) for details.

<span id="page-9-1"></span><sup>&</sup>lt;sup>6</sup>For now, we ignore any consideration about keeping the update time of our algorithm low, or even polynomial.

#### <span id="page-10-0"></span>2.3.3 Challenge III: Achieving Fast Update Time

As mentioned previously, the update time of the algorithm in [\[FLNS21\]](#page-75-0) is prohibitively large. This occurs because of the following computationally expensive steps at the start and at the end of an epoch.<sup>[7](#page-10-2)</sup> (1) At the start of an epoch, [\[FLNS21\]](#page-75-0) computes the value of  $\ell$ , by solving an LP for the  $(k - s)$ -median problem with potential centers  $\mathcal{U}_{\text{init}}$ , for each  $s \in [0, k - 1]$ . (2) Next, to initialize the subset  $\mathcal{U} \subseteq \mathcal{U}_{\text{init}}$  of  $(k - \ell)$  centers at the start of the epoch, [\[FLNS21\]](#page-75-0) again invokes an algorithm for the  $(k - \ell)$ -median problem from scratch. (3) At the end of the epoch, [\[FLNS21\]](#page-75-0) solves another LP and applies a rounding procedure, to get an approximation of the desired set  $W^{\star}$  (see Equation [\(3\)](#page-8-4)). (4) Finally, at the end of the epoch, the call to the ROBUSTIFY subroutine also takes a prohibitively long time for our purpose.

In contrast, we take alternative approaches while performing the above steps. At the start of an epoch, we implement Steps (1) and (2) via randomized local search (see Section [2.1.2\)](#page-6-2). For Step (3), we compute (an approximation) of the set  $\mathcal{W}^*$  by solving the three tasks outlined in Section [2.3.2.](#page-9-0) One of our contributions is to design a new algorithm for Task (i) that runs in  $O(n \cdot (\ell + 1))$  time, assuming it has access to some auxiliary data structures (see Lemma [6.2\)](#page-21-1). It is trivial to perform Task (ii). For Task (iii), we again invoke the randomized local search procedure (see Section [2.1.2\)](#page-6-2).

Finally, for step (4), we need to efficiently implement the calls to ROBUSTIFY( $\cdot$ ). See Section [6.2.1](#page-22-0) for a more detailed discussion on this challenge, and how we overcome it (we defer the discussion to Section [6.2.1](#page-22-0) because it requires an understanding of the inner workings of the ROBUSTIFY( $\cdot$ ) subroutine, which we have not described until now).

## <span id="page-10-1"></span>3 Preliminaries

We now define some basic notations, and recall some relevant results from the existing literature. For the sake of completeness, we provide self-contained proofs for most of the lemmas stated in this section, but defer those proofs (since we do *not* take any credit for them) to Section [8.](#page-29-1)

Consider a set of points **P** and a distance function  $d: \mathbf{P} \times \mathbf{P} \to \mathbb{R}^+$  that together form a metric space. The input to our dynamic algorithm is a subset  $P \subseteq P$ , which changes by means of updates. Let n be an upper bound on the maximum size of  $P$  throughout these updates. Each update either inserts a point  $p \in \mathbf{P} \setminus \mathcal{P}$  into  $\mathcal{P}$ , or deletes a point  $p \in \mathcal{P}$  from  $\mathcal{P}$ . At all times, we have to maintain a set  $\mathcal{U} \subseteq \mathbf{P}$  of at most k "centers", so as to minimize the objective function

Cost 
$$
(U, \mathcal{P}) := \sum_{p \in \mathcal{P}} d(p, U)
$$
, where  $d(p, U) := \min_{q \in U} d(p, q)$  is the distance from p to the set U.

We will refer to this as the dynamic **improper**  $k$ -median problem. Our goal is to design an algorithm for this problem that has: (1) good approximation ratio, (2) small update time, which is the time it takes to process an update in  $P$ , and (3) small recourse, which is the number of changes (point insertions/deletions) in the maintained solution  $\mathcal U$  per update. What makes this setting distinct from the standard k-median problem is this: Here, we are allowed to open centers at locations that are not part of the current input, i.e., we can have  $U \cap (\mathbf{P} \setminus \mathcal{P}) \neq \emptyset$ . Nevertheless, in a black-box manner we can convert any dynamic algorithm for improper k-median into a dynamic algorithm for  $k$ -median, with essentially the same guarantees (see Lemma [3.1\)](#page-10-3). Accordingly, for the rest of this paper, we focus on designing a dynamic algorithm for improper k-median.

<span id="page-10-3"></span><span id="page-10-2"></span><sup>&</sup>lt;sup>7</sup>Note that it is straightforward to lazily handle the updates within the epoch.

**Lemma 3.1** ([\[BCG](#page-74-0)<sup>+</sup>24]). Given an  $\alpha$ -approximation algorithm for dynamic improper k-median, we can get a  $2\alpha$ -approximation algorithm for dynamic k-median, with an extra  $O(1)$  multiplicative factor overhead in the recourse, and an extra  $O(n)$  additive factor overhead in the update time.

Remark. At this point, the reader might get alarmed by the fact that Lemma [3.1](#page-10-3) incurs an additive overhead of  $O(n)$  update time. To assuage this concern, in Section [6.3,](#page-24-1) we explain how to bring down the update time from  $O(n)$  to  $O(k)$ , using standard sparsification techniques.

### <span id="page-11-0"></span>3.1 Basic Notations

By a simple scaling, we can assume that all of the distances in the metric space lie in the range [1,  $\Delta$ ], where  $\Delta$  is the *aspect ratio*. Throughout the paper, we use the symbol **P** to denote the underlying metric space with distance function  $d: \mathbf{P} \times \mathbf{P} \to \mathbb{R}^{\geq 0}$ , and  $\mathcal{P} \subseteq \mathbf{P}$  to denote the current input. For simplicity, for each set S and element p, we denote  $S \cup \{p\}$  and  $S \setminus \{p\}$  by  $S + p$  and  $S - p$ respectively. For two sets of points S and S', we use  $S \oplus S'$  to denote their symmetric difference.

For each  $S \subseteq \mathbf{P}$ , we define  $\pi_S : \mathbf{P} \to S$  to be the projection function onto S, i.e.,  $\pi_S(x) :=$ arg min<sub>s∈S</sub>  $d(x, s)$ , breaking the ties arbitrarily. For each  $\mathcal{U} \subseteq \mathbf{P}$  and  $S \subseteq \mathcal{P}$ , we also define

$$
\text{AverageCost}(\mathcal{U}, S) := \frac{\text{Cost}(\mathcal{U}, S)}{|S|} = \frac{\sum_{p \in S} d(p, \mathcal{U})}{|S|} = \frac{\sum_{p \in S} \min_{q \in \mathcal{U}} d(p, q)}{|S|}.
$$

Consider any subset of points  $C \subseteq P$ . For every  $k \geq 1$ , we let  $\text{OPT}_k^{\mathcal{C}}(\mathcal{P})$  denote the cost of the optimum k-median solution for  $\mathcal{P} \subseteq \mathbf{P}$ , where we can only open centers from C. Thus, we have

$$
\mathrm{OPT}^{\mathcal{C}}_k(\mathcal{P}) = \min_{\mathcal{U} \subseteq \mathcal{C}, |\mathcal{U}| \leq k} \mathsf{Cost}(\mathcal{U}, \mathcal{P})\,.
$$

When  $C = \mathbf{P}$ , we slightly abuse the notation and write  $\text{OPT}_k(\mathcal{P})$  instead of  $\text{OPT}_k^{\mathcal{C}}(\mathcal{P})$ . Next, for each  $U \subseteq \mathbf{P}$  and  $u \in U$ , we define  $C_u(U, \mathcal{P}) := \{p \in \mathcal{P} \mid \pi_U(p) = u\}$  to be the set of points in  $\mathcal{P}$  that are "assigned to" the center u in the solution U (breaking ties arbitrarily). For each point  $p \in \mathbf{P}$ and value  $r \geq 0$ , let  $\text{Ball}_r^{\mathcal{P}}(p) := \{q \in \mathcal{P} \mid d(p,q) \leq r\}$  denote the ball of radius r around p. Note that if  $p \in \mathbf{P} \setminus \mathcal{P}$ , then p itself is not part of the ball  $\text{Ball}_r^{\mathcal{P}}(p)$ . Finally, throughout the paper we use a sufficiently large constant parameter  $\gamma = 4000$ .

#### <span id="page-11-1"></span>3.2 Robust Centers

We will use the notion of *robust centers* [\[FLNS21\]](#page-75-0). Morally, a point  $p \in \mathbf{P}$  is *t*-robust for an integer  $t \geq 1$  iff it satisfies the following condition for all  $i \in [1, t]$ : Let  $B_i = \text{Ball}_{10^i}^{\mathcal{P}}(p)$ , and consider any point  $q \in \mathcal{P}$  with  $d(p,q) \ll 10^i$ , i.e., q is sufficiently close to p compared to the radius of  $B_i$ . Then Cost  $(p, S) \leq O(1)$  · Cost  $(q, S)$  for all  $B_i \subseteq S \subseteq P$ . In words, the point p is a good approximate 1-median solution, compared to any other nearby point, at every "distance scale" up to  $10<sup>t</sup>$ .

The above definition, however, is too strong, in the sense that there might not exist any  $t$ -robust point under this definition.<sup>[8](#page-11-2)</sup> Instead, the actual definition that we will use is stated below (see Definition [3.2\)](#page-11-3), along with the relevant properties that follow from it (see Lemma [3.3](#page-12-0) and Lemma [3.4\)](#page-12-1). Conceptually, here the key difference from the idealized definition is that the balls  ${B_i}_i$  are centered around different points  ${p_i}_i$ , with  $p_0 = p$  and  $d(p, p_i) \ll 10^i$  for all  $i \in [1, t]$ .

<span id="page-11-3"></span><span id="page-11-2"></span><sup>&</sup>lt;sup>8</sup>For instance, it might be the case that there are (say)  $\lambda$  many points in  $B_i$ , and all of them (except p) are in the exact same location as q, i.e.,  $d(p', q) = 0$  for all  $p' \in B_i - p$ . Then, the condition Cost  $(p, B_i) \leq O(1)$ . Cost  $(q, B_i)$ clearly does not hold, since the LHS is  $(\lambda - 1) \cdot d(p, q)$ , whereas the RHS is only  $d(p, q)$ .

**Definition 3.2.** Let  $(p_0, p_1, \ldots, p_t)$  be a sequence of  $t + 1$  points in **P**, and let  $B_i = \text{Ball}_{10^i}^{\mathcal{P}}(p_i)$  for each  $i \in [0, t]$ . We refer to  $(p_0, p_1, \ldots, p_t)$  as a t-robust sequence iff for every  $i \in [1, t]$ :

$$
p_{i-1} = \begin{cases} p_i & \text{if AverageCost } (p_i, B_i) \ge 10^i / 5; \\ q_i & \text{otherwise, where } q_i = \arg \min_{q \in B_i + p_i} \text{Cost } (q, B_i) \,. \end{cases}
$$

<span id="page-12-0"></span>We say that a point  $p \in \mathbf{P}$  is t-robust iff there exists a t-robust sequence  $(p_0, p_1, \ldots, p_t)$  with  $p_0 = p$ .

**Lemma 3.3** ([\[FLNS21\]](#page-75-0)). Let  $(p_0, p_1, \ldots, p_t)$  be a t-robust sequence and let  $B_i = Ball_{10^i}^{\mathcal{P}}(p_i)$  for all  $i \in [0, t]$ . Then, for all  $i \in [1, t]$ , we have  $d(p_{i-1}, p_i) \leq 10^i/2$ ,  $B_{i-1} \subseteq B_i$  and  $d(p_0, p_i) \leq 10^i/2$ .

<span id="page-12-1"></span>**Lemma 3.4** ([\[FLNS21\]](#page-75-0)). Let  $(p_0, p_1, \ldots, p_t)$  be a t-robust sequence and let  $B_i = Ball_{10^i}^{\mathcal{P}}(p_i)$  for all  $i \in [0,t]$ . Then, for every  $i \in [0,t]$  and every  $B_i \subseteq S \subseteq \mathcal{P}$ , we have  $\mathsf{Cost}\,(p_0,S) \leq (3/2) \cdot \mathsf{Cost}\,(p_i,S)$ .

<span id="page-12-6"></span>We next define the concept of a *robust collection of centers*.

**Definition 3.5.** A set of centers  $W \subseteq \mathbf{P}$  is robust iff the following holds for every  $w \in W$ :

<span id="page-12-4"></span>w is t-robust, where t is the smallest integer satisfying  $10^t \ge d(w, W - w)/200$ . (4)

Suppose that we have a set of centers  $W \subseteq \mathbf{P}$  that is not robust. A natural way to convert them into a robust set of centers is to call the subroutine ROBUSTIFY $(W)$ , as described below.

Algorithm 1: ROBUSTIFY $(W)$ 

<span id="page-12-11"></span><span id="page-12-9"></span><span id="page-12-5"></span>1 while there exist a  $w \in \mathcal{W}$  violating  $\mathcal{L}$  do 2  $t \leftarrow$  Smallest integer satisfying  $10^t \geq d(w, W - w)/100$ .  $\mathbf{3} \quad w_0 \leftarrow \text{MAKE-ROBUST}(w, t).$ 4  $W \leftarrow W - w + w_0$ .

<span id="page-12-10"></span><span id="page-12-7"></span>Algorithm 2: MAKE-ROBUST $(p, t)$ 

1  $p_t \leftarrow p$ . 2 for  $i = t$  down to 1 do  $\mathbf{3} \quad B_i \leftarrow \text{Ball}_{10^i}^{\mathcal{P}}(p_i).$  $4$  | if AverageCost  $(p_i,B_i) \geq 10^i/5$  then 5  $p_{i-1} \leftarrow p_i$ . 6 else  $7 \quad | \quad p_{i-1} \leftarrow \arg\min_{q \in B_i + p_i} \textsf{Cost}(q, B_i).$ 8 return  $p_0$ .

<span id="page-12-8"></span>During a call to  $M$ AKE-ROBUST $(p, t)$ , we simply apply the rule from Definition [3.2](#page-11-3) to obtain a t-robust sequence  $(p_0, p_1, \ldots, p_t)$  with  $p_t = p$ , and then return the point  $p_0$ . Further, Line [2](#page-12-5) of the subroutine ROBUSTIFY(W) considers the inequality  $10^t \ge d(w, W - w)/100$ , whereas [\(4\)](#page-12-4) refers to the inequality  $10^t \geq d(w, W - w)/200$ . This discrepancy in the constants on the right hand side (100 vs 200) of these two inequalities is intentional, and plays a crucial role in deriving Lemma [3.6.](#page-12-2)

<span id="page-12-2"></span>**Lemma 3.6** ([\[FLNS21\]](#page-75-0)). Consider any call to ROBUSTIFY(W), and suppose that it sets  $w_0 \leftarrow$  $\text{MAKE-ROBUST}(w, t)$  during some iteration of the while loop. Then in subsequent iterations of the while loop in the same call to ROBUSTIFY(W), we will not make any call to MAKE-ROBUST( $w_0, \cdot$ ).

<span id="page-12-3"></span>**Lemma 3.7** ([\[FLNS21\]](#page-75-0)). If U is the output of ROBUSTIFY(W), then Cost  $(U, \mathcal{P}) \leq \frac{3}{2}$  $\frac{3}{2}$   $\cdot$  Cost  $(\mathcal{W}, \mathcal{P})$  .

#### <span id="page-13-0"></span>3.3 Well-Separated Pairs

We will also use the notion of a well-separated pair of points [\[FLNS21\]](#page-75-0), defined as follows.

**Definition 3.8.** Consider any  $\mathcal{U}, \mathcal{V} \subseteq \mathbf{P}$ . A pair  $(u, v) \in \mathcal{U} \times \mathcal{V}$  is well-separated w.r.t.  $(\mathcal{U}, \mathcal{V})$  iff

$$
d(u, \mathcal{U} - u) \geq \gamma \cdot d(u, v)
$$
 and  $d(v, \mathcal{V} - v) \geq \gamma \cdot d(u, v)$ .

Using triangle inequality, it is easy to verify that each point  $u \in \mathcal{U}$  either forms a well-separated pair with a unique  $v \in V$ , or it does not form a well-separated pair with any  $v \in V$ . The next lemma implies that if U is robust, then we can replace every center  $v \in V$  that is well-separated by its counterpart in  $\mathcal{U}$ , and this will increase the cost of the solution  $\mathcal{V}$  by at most a constant factor.

<span id="page-13-5"></span>**Lemma 3.9** ([\[FLNS21\]](#page-75-0)). Consider any two sets of centers  $U, V \subseteq P$  such that U is robust. Then, for every well-separated pair  $(u, v) \in \mathcal{U} \times \mathcal{V}$ , we have  $\text{Cost}(u, C_v(\mathcal{V}, \mathcal{P})) \leq 3 \cdot \text{Cost}(v, C_v(\mathcal{V}, \mathcal{P}))$ .

#### <span id="page-13-1"></span>3.4 Projection Lemma and Lazy-Updates Lemma

We conclude by recalling two lemmas that are folklore in the literature on clustering  $[BCG^+24]$ .

Intuitively, the projection lemma says that if we have a set  $\mathcal U$  of more than k centers, then the cost of the best possible k-median solution, subject to the constraint that all of the  $k$  centers must be picked from  $\mathcal{U}$ , is not too large compared to  $\mathsf{Cost}(\mathcal{U}, \mathcal{P})$ .

<span id="page-13-6"></span>**Lemma 3.10** (Projection Lemma [\[BCG](#page-74-0)<sup>+</sup>24]). Consider any set of centers  $\mathcal{U} \subseteq \mathbf{P}$  of size  $|\mathcal{U}| \geq k$ , where k is a positive integer. Then we have  $\text{OPT}_k^{\mathcal{U}}(\mathcal{P}) \leq \text{Cost}(\mathcal{U}, \mathcal{P}) + 2 \cdot \text{OPT}_k(\mathcal{P})$ .

The lazy updates lemma, stated below, is derived from the following observation. Suppose that whenever a new point gets inserted into  $P$ , we create a center at the position of the newly inserted point; and whenever a point gets deleted from  $P$ , we do not make any changes to the set of centers. Then this *lazy rule* for handling updates ensures that the cost of the solution we maintain does not increase over time (although the solution might consist of more than  $k$  centers).

<span id="page-13-7"></span>**Lemma 3.11** (Lazy-Updates Lemma [\[BCG](#page-74-0)<sup>+</sup>24]). Consider any two sets of input points  $P, P' \subseteq P$ such that  $|\mathcal{P} \oplus \mathcal{P}'| \leq s$ . Then for every  $k \geq 1$ , we have  $\text{OPT}_{k+s}(\mathcal{P}') \leq \text{OPT}_k(\mathcal{P})$ .

# <span id="page-13-2"></span>4 Two Key Lemmas

<span id="page-13-3"></span>We now state two key lemmas that will be used in the design and analysis of our dynamic algorithm. We defer the formal proofs of these two lemmas to Section [7.](#page-25-0)

**Lemma 4.1** (Double-Sided Stability Lemma). Consider any  $r \in [0, k-1]$  and any  $\eta \geq 1$ . If  $\text{OPT}_{k-r}(\mathcal{P}) \leq \eta \cdot \text{OPT}_k(\mathcal{P})$ , then we must have  $\text{OPT}_k(\mathcal{P}) \leq 4 \cdot \text{OPT}_{k+|r/(12\eta)|}(\mathcal{P})$ .

<span id="page-13-4"></span>To interpret Lemma [4.1,](#page-13-3) first note that  $\text{OPT}_k(\mathcal{P})$  is a monotonically non-increasing function of k, since the objective value can only drop if we open extra centers. Now, suppose there is a sufficiently large integer  $r \in [0, k-1]$  such that  $\text{OPT}_{k-r}(\mathcal{P}) \leq \Theta(1) \cdot \text{OPT}_k(\mathcal{P})$ . Then, Lemma [4.1](#page-13-3) guarantees that  $\text{OPT}_k(\mathcal{P}) \leq \Theta(1) \cdot \text{OPT}_{k+r'}(\mathcal{P})$  for some integer  $r' = \Theta(r)$ . In other words, if the optimal objective remains stable as we *decrease* the number of centers by some additive  $r$ , then it also remains stable as we increase the number of centers by roughly the same amount. Conceptually, this holds because of two reasons: (i) the optimal objective of the fractional version of the k-median problem (encoded by its standard LP-relaxation) is convex as a function of  $k$ , and (ii) the concerned LP-relaxation has  $\Theta(1)$ -integrality gap.

**Lemma 4.2** (Generalization of Lemma 7.3 in the arXiv version of [\[FLNS21\]](#page-75-0)). Let  $r \geq 0$  and  $m \in [0, k]$ . Consider any two sets of centers  $\mathcal{U}, \mathcal{V} \subseteq \mathbf{P}$  such that  $|\mathcal{U}| = k$  and  $|\mathcal{V}| = k + r$ . If the number of well-separated pairs w.r.t.  $(\mathcal{U}, \mathcal{V})$  is  $k - m$ , then there exists a subset  $\mathcal{U} \subseteq \mathcal{U}$  of size at  $most\; k - \lfloor (m-r)/4 \rfloor \; such\; that\; \mathsf{Cost}\left(\tilde{\mathcal{U}}, \mathcal{P}\right) \leq 6\gamma \cdot (\mathsf{Cost}\left(\mathcal{U}, \mathcal{P}\right) + \mathsf{Cost}\left(\mathcal{V}, \mathcal{P}\right)).$ 

Intuitively, think of U as the k-median solution maintained by our algorithm, and let V be another set of  $k + r$  centers such that  $Cost(\mathcal{V}, \mathcal{P}) \leq \Theta(1) \cdot OPT_k(\mathcal{P})$ . The above lemma implies that if  $m \gg r$  (i.e., the number of well-separated pairs w.r.t.  $(\mathcal{U}, \mathcal{V})$  is sufficiently small), then we can delete  $|(m - r)/4| = \Omega(r)$  centers from U without significantly increasing the objective  $Cost(\mathcal{U}, \mathcal{P}).$ 

# <span id="page-14-0"></span>5 Achieving  $O(1)$  Approximation Ratio and  $O(\log^2 \Delta)$  Recourse

In this section, we focus only on achieving good approximation ratio and recourse bounds. We prove the following theorem, without any concern for the update time of the algorithm. In particular, to keep the exposition as simple as possible, we present an algorithm with exponential update time.

**Theorem 5.1.** There is a deterministic  $O(1)$ -approximation algorithm for dynamic metric kmedian with  $O(\log^2 \Delta)$  recourse.

## <span id="page-14-1"></span>5.1 Description of the Algorithm

<span id="page-14-4"></span>Our algorithm works in **epochs**; each epoch lasts for some consecutive updates in P. Let  $\mathcal{U} \subseteq \mathbf{P}$ denote the maintained solution (set of  $k$  centers). We satisfy the following invariant.

**Invariant 5.2.** At the start of an epoch, the set U is robust and  $\text{Cost}(\mathcal{U}, \mathcal{P}) \leq 8 \cdot \text{OPT}_k(\mathcal{P})$ .

We now describe how our dynamic algorithm works in a given epoch, in four steps.

Step 1: Determining the length of the epoch. At the start of an epoch, we compute the maximum  $\ell^* \geq 0$  such that  $\text{OPT}_{k-\ell^*}(\mathcal{P}) \leq 54\gamma \cdot \text{OPT}_k(\mathcal{P})$ , and set  $\ell \leftarrow \lfloor \ell^* / (12 \cdot 54\gamma) \rfloor$ . Since  $\ell \leq \ell^*$ , it follows that  $\text{OPT}_{k-\ell}(\mathcal{P}) \leq \text{OPT}_{k-\ell^*}(\mathcal{P})$ . Thus, by setting  $\eta = 54\gamma$  and  $r = \ell^*$  in Lemma [4.1,](#page-13-3) at the start of the epoch we have:

<span id="page-14-5"></span>
$$
\frac{\text{OPT}_{k-\ell}(\mathcal{P})}{54\gamma} \le \text{OPT}_k(\mathcal{P}) \le 4 \cdot \text{OPT}_{k+\ell}(\mathcal{P}).\tag{5}
$$

The epoch will last for the next  $\ell+1$  updates.<sup>[10](#page-14-3)</sup> From now on, we will use the superscript  $t \in [0, \ell+1]$ to denote the status of some object after our algorithm has finished processing the  $t^{th}$  update in the epoch. For example, at the start of the epoch we have  $P = P^{(0)}$ .

Step 2: Preprocessing at the start of the epoch. Let  $\mathcal{U}_{init} \leftarrow \mathcal{U}$  be the solution maintained by the algorithm after it finished processing the last update in the previous epoch. Before handling the very first update in the current epoch, we initialize the maintained solution by setting

$$
\mathcal{U}^{(0)} \leftarrow \arg\min_{\mathcal{U}' \subseteq \mathcal{U}_{\text{init}} : |\mathcal{U}'| = k - \ell} \text{Cost}\left(\mathcal{U}', \mathcal{P}^{(0)}\right). \tag{6}
$$

Thus, at this point in time, we have  $\mathsf{Cost}\left(\mathcal{U}^{(0)},\mathcal{P}^{(0)}\right) = \mathrm{OPT}^{\mathcal{U}_\mathrm{init}}_{k-\ell}\left(\mathcal{P}^{(0)}\right) \leq \mathsf{Cost}\left(\mathcal{U}_\mathrm{init},\mathcal{P}^{(0)}\right) + 2 \cdot \mathsf{Cost}\left(\mathcal{U}_\mathrm{init},\mathcal{P}^{(0)}\right)$  $\text{OPT}_{k-\ell}(\mathcal{P}^{(0)}) \leq 8 \cdot \text{OPT}_k(\mathcal{P}^{(0)}) + 2 \cdot \text{OPT}_{k-\ell}(\mathcal{P}^{(0)}) \leq (32 + 432\gamma) \cdot \text{OPT}_{k+\ell}(\mathcal{P}^{(0)}),$  where the

<sup>&</sup>lt;sup>9</sup>Recall  $\gamma$  from Section [3.1](#page-11-0)

<span id="page-14-3"></span><span id="page-14-2"></span><sup>&</sup>lt;sup>10</sup>Note that we might very well have  $\ell = 0$ .

first inequality follows from Lemma [3.10,](#page-13-6) the second inequality follows from Invariant [5.2,](#page-14-4) and the last inequality follows from [\(5\)](#page-14-5). To summarize, we get:

<span id="page-15-0"></span>
$$
\text{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) \le (32 + 432\gamma) \cdot \text{OPT}_{k+\ell}\left(\mathcal{P}^{(0)}\right) \text{ and } \left|\mathcal{U}^{(0)}\right| \le k - \ell. \tag{7}
$$

In words, before we deal with the very first update in the epoch, the maintained solution  $\mathcal{U}^{(0)}$  is a  $(32+432\gamma) = \Theta(1)$ -approximation of  $\text{OPT}_{k+\ell}(\mathcal{P}^{(0)})$ , and consists of at most  $(k-\ell)$  centers. Both these properties will be crucially exploited while handling the updates within the epoch.

Step 3: Handling the updates within the epoch. Consider the  $t^{th}$  update in the epoch, for  $t \in [1, \ell+1]$ . We handle this update in a lazy manner, as follows. If the update involves the deletion of a point from P, then we do not change our maintained solution, and set  $\mathcal{U}^{(t)} \leftarrow \mathcal{U}^{(t-1)}$ . (The maintained solution remains valid, since we are considering the improper k-median problem). In contrast, if the update involves the insertion of a point p into P, then we set  $\mathcal{U}^{(t)} \leftarrow \mathcal{U}^{(t-1)} + p$ .

It is easy to verify that this lazy way of dealing with an update does not increase the objective, and increases the number of centers in the maintained solution by at most one. Thus, we have  $\text{Cost}(\mathcal{U}^{(t)}, \mathcal{P}^{(t)}) \leq \text{Cost}(\mathcal{U}^{(t-1)}, \mathcal{P}^{(t-1)})$  and  $|\mathcal{U}^{(t)}| \leq |\mathcal{U}^{(t-1)}| + 1$ . From [\(7\)](#page-15-0), we now derive that

<span id="page-15-1"></span>
$$
\mathsf{Cost}\left(\mathcal{U}^{(t)}, \mathcal{P}^{(t)}\right) \le \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) \text{ and } \left|\mathcal{U}^{(t)}\right| \le k - \ell + t, \text{ for all } t \in [1, \ell + 1].\tag{8}
$$

Step 4: Post-processing at the end of the epoch. By [\(8\)](#page-15-1), the set  $\mathcal{U}^{(t)}$  remains a valid solution for the improper k-median problem, for all  $t \in [1, \ell]$ . After the very last update in the epoch, however, the set  $\mathcal{U}^{(\ell+1)}$  might have more than k centers. At this point in time, we do some post-processing, and compute another set  $\mathcal{U}_{\text{final}} \subseteq \mathbf{P}$  of at most k centers (i.e.,  $|\mathcal{U}_{\text{final}}| \leq k$ ) that satisfies Invariant [5.2.](#page-14-4) We then initiate the next epoch, with  $\mathcal{U} \leftarrow \mathcal{U}_{\text{final}}$  being the current solution. The post-processing is done as follows.

We first add  $O(\ell+1)$  extra centers to the set  $\mathcal{U}_{\text{init}}$ , while minimizing the cost of the resulting solution w.r.t.  $\mathcal{P}^{(0)}$ . This gives us the set of centers  $\mathcal{U}^*$ . Note that  $|\mathcal{U}^*| = k + O(\ell+1)$ .

<span id="page-15-2"></span>
$$
\mathcal{F}^{\star} \leftarrow \arg\min_{\mathcal{F} \subseteq \mathbf{P}: |\mathcal{F}| \leq 2700\gamma \cdot (\ell+1)} \text{Cost}\left(\mathcal{U}_{\text{init}} + \mathcal{F}, \mathcal{P}^{(0)}\right), \text{ and } \mathcal{U}^{\star} \leftarrow \mathcal{U}_{\text{init}} + \mathcal{F}^{\star}.\tag{9}
$$

We next add the newly inserted points within the epoch to the set of centers, so as to obtain the set  $\mathcal{V}^*$ . Since the epoch lasts for  $\ell+1$  updates, we have  $|\mathcal{V}^*|=k+O(\ell+1)$ . Next, we identify the subset  $\mathcal{W}^{\star} \subseteq \mathcal{V}^{\star}$  of k centers that minimizes the k-median objective w.r.t.  $\mathcal{P}^{(\ell+1)}$ .

<span id="page-15-3"></span>
$$
\mathcal{V}^{\star} \leftarrow \mathcal{U}^{\star} + \left(\mathcal{P}^{(\ell+1)} - \mathcal{P}^{(0)}\right), \text{ and } \mathcal{W}^{\star} \leftarrow \arg\min_{\mathcal{W} \subseteq \mathcal{V}^{\star}: |\mathcal{W}| = k} \text{Cost}\left(\mathcal{W}, \mathcal{P}^{(\ell+1)}\right). \tag{10}
$$

Finally, we call ROBUSTIFY( $W^*$ ) and let  $\mathcal{U}_{\text{final}}$  be the set of k centers returned by this subroutine. Before starting the next epoch, we set  $\mathcal{U} \leftarrow \mathcal{U}_{\text{final}}$ .

<span id="page-15-4"></span>
$$
\mathcal{U}_{\text{final}} \leftarrow \text{ROBUSTIFY}(\mathcal{W}^{\star}).\tag{11}
$$

It is easy to verify that we always maintain a set  $\mathcal{U} \subseteq \mathbf{P}$  of k centers. In Section [5.2,](#page-16-0) we show that  $U = U_{final}$  satisfies Invariant [5.2](#page-14-4) at the end of Step 4, and analyze the approximation ratio of the overall algorithm. Finally, Section [5.3](#page-18-0) bounds the recourse of the algorithm. We conclude this section with a corollary that will play an important role in our recourse analysis.

<span id="page-15-5"></span>Corollary 5.3. We have  $|W^* \oplus \mathcal{U}_{init}| = O(\ell+1)$ .

Proof. From [\(9\)](#page-15-2) and [\(10\)](#page-15-3), we infer that  $|\mathcal{V}^* \oplus \mathcal{U}_{\text{init}}| \leq |\mathcal{V}^* \oplus \mathcal{U}^*| + |\mathcal{U}^* \oplus \mathcal{U}_{\text{init}}| \leq |\mathcal{P}^{(\ell+1)} - \mathcal{P}^{(0)}| + |\mathcal{I}^* \oplus \mathcal{U}_{\text{init}}| \leq (2789 \text{ s} \cdot (\ell + 1)) \cdot (\ell + 1) \cdot \mathcal{O}(\ell + 1) \cdot \mathcal{O}(\ell + 1)$  $|\mathcal{F}^{\star}| \leq (2700\gamma \cdot (\ell+1)) + (\ell+1) = O(\ell+1)$ . Next, recall that  $|\mathcal{V}^{\star}| = k + O(\ell+1)$ , and  $\mathcal{W}^{\star}$  is a subset of  $\mathcal{V}^*$  of size k. Thus, we get:  $|\mathcal{W}^* \oplus \mathcal{U}_{\text{init}}| \leq |\mathcal{W}^* \oplus \mathcal{V}^*| + |\mathcal{V}^* \oplus \mathcal{U}_{\text{init}}| = O(\ell+1) + O(\ell+1) = O(\ell+1).$ This concludes the proof.  $\Box$ 

## <span id="page-16-0"></span>5.2 Analyzing the Approximation Ratio

Consider any  $t \in [0, \ell]$ , and note that  $|\mathcal{P}^{(t)} \oplus \mathcal{P}^{(0)}| \leq t \leq \ell$ . Thus, by Lemma [3.11,](#page-13-7) we have:

<span id="page-16-3"></span>
$$
\text{OPT}_{k+\ell}\left(\mathcal{P}^{(0)}\right) \le \text{OPT}_k\left(\mathcal{P}^{(t)}\right). \tag{12}
$$

From  $(7)$ ,  $(8)$  and  $(12)$ , we now infer that:

$$
\text{Cost}\left(\mathcal{U}^{(t)}, \mathcal{P}^{(t)}\right) \le (32 + 432\gamma) \cdot \text{OPT}_k\left(\mathcal{P}^{(t)}\right) \text{ and } \left|\mathcal{U}^{(t)}\right| \le k, \text{ for all } t \in [0, \ell].\tag{13}
$$

In other words, at all times within an epoch, the set  $\mathcal{U}^{(t)}$  maintained by our algorithm remains a valid  $\Theta(1)$ -approximate solution to the improper k-median problem on the current input  $\mathcal{P}^{(t)}$ . It remains to show that the algorithm successfully restores Invariant [5.2](#page-14-4) when the epoch terminates after the  $(\ell+1)^{th}$  update. Accordingly, we devote the rest of this section to the proof of Lemma [5.4.](#page-16-4)

<span id="page-16-4"></span>**Lemma 5.4.** At the end of Step 4 in Section [5.1,](#page-14-1) the set  $\mathcal{U} = \mathcal{U}_{final}$  satisfies Invariant [5.2.](#page-14-4)

<span id="page-16-1"></span>The claim below bounds the cost of the solution  $\mathcal{U}^*$  w.r.t. the point-set  $\mathcal{P}^{(0)}$ .

Claim 5.5. We have  $\text{Cost}(\mathcal{U}^*, \mathcal{P}^{(0)}) \leq 3 \cdot \text{OPT}_{k+\ell+1}(\mathcal{P}^{(0)})$ .

Before proving Claim [5.5,](#page-16-1) we explain how it implies Lemma [5.4.](#page-16-4) Towards this end, note that:

<span id="page-16-5"></span>Cost 
$$
(\mathcal{U}_{\text{final}}, \mathcal{P}^{(\ell+1)}) \leq \frac{3}{2} \cdot \text{Cost} \left(\mathcal{W}^{\star}, \mathcal{P}^{(\ell+1)}\right) = \frac{3}{2} \cdot \text{OPT}_{k}^{\mathcal{V}^{\star}} \left(\mathcal{P}^{(\ell+1)}\right)
$$
 (14)

$$
\leq \frac{3}{2} \cdot \text{Cost}\left(\mathcal{V}^{\star}, \mathcal{P}^{(\ell+1)}\right) + 3 \cdot \text{OPT}_k\left(\mathcal{P}^{(\ell+1)}\right) \tag{15}
$$

$$
\leq \frac{3}{2} \cdot \text{Cost}\left(\mathcal{U}^{\star}, \mathcal{P}^{(0)}\right) + 3 \cdot \text{OPT}_k\left(\mathcal{P}^{(\ell+1)}\right) \tag{16}
$$

$$
\leq \frac{9}{2} \cdot \text{OPT}_{k+\ell+1} \left( \mathcal{P}^{(0)} \right) + 3 \cdot \text{OPT}_k \left( \mathcal{P}^{(\ell+1)} \right) \tag{17}
$$

$$
\leq \frac{9}{2} \cdot \text{OPT}_k \left( \mathcal{P}^{(\ell+1)} \right) + 3 \cdot \text{OPT}_k \left( \mathcal{P}^{(\ell+1)} \right) \tag{18}
$$

$$
\leq 8 \cdot \text{OPT}_k \left( \mathcal{P}^{(\ell+1)} \right). \tag{19}
$$

In the above derivation, the first step  $(14)$  follows from  $(10)$ ,  $(11)$  and Lemma [3.7.](#page-12-3) The second step  $(15)$  follows from Lemma [3.10.](#page-13-6) The third step  $(16)$  follows from  $(10)$ . The fourth step  $(17)$ follows from Claim [5.5.](#page-16-1) The fifth step [\(18\)](#page-16-5) follows from Lemma [3.11](#page-13-7) and the observation that  $\left|\mathcal{P}^{(\ell+1)}\oplus\mathcal{P}^{(0)}\right| \leq \ell+1$ . From [\(19\)](#page-16-5), we infer that at the start of the next epoch Cost  $(\mathcal{U},\mathcal{P}) \leq$  $8 \cdot \text{OPT}_k(\mathcal{P})$ , and the set U is robust because of [\(11\)](#page-15-4). This implies Lemma [5.4.](#page-16-4)

#### <span id="page-16-2"></span>5.2.1 Proof of Claim [5.5](#page-16-1)

<span id="page-16-7"></span>Let  $V \subseteq \mathbf{P}$  be an optimal improper  $(k+\ell+1)$ -median solution for the point-set  $\mathcal{P}^{(0)}$ , i.e.,  $|V| =$  $k+\ell+1$  and  $\textsf{Cost}\left(\mathcal{V},\mathcal{P}^{(0)}\right) = \text{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right)$ . Let  $m \in [0,k]$  be the unique integer such that there are  $(k-m)$  well-separated pairs w.r.t.  $(\mathcal{U}_{init}, \mathcal{V})$ . Let  $\{(u_1, v_1), (u_2, v_2), \ldots, (u_{k-m}, v_{k-m})\} \subseteq$  $U_{\text{init}} \times V$  denote the collection of  $(k - m)$  well-separated pairs w.r.t.  $(U_{\text{init}}, V)$ . Define the set  $\tilde{\mathcal{F}} := \mathcal{V} \setminus \{v_1, \ldots, v_{k-m}\}.$  It is easy to verify that:

<span id="page-16-6"></span>
$$
\left|\tilde{\mathcal{F}}\right| = |\mathcal{V}| - (k - m) = m + \ell + 1. \tag{20}
$$

<span id="page-17-0"></span>**Claim 5.6.** We have  $m \leq 2600\gamma \cdot (\ell+1)$ .

Claim 5.7. We have  $\text{Cost}(\mathcal{U}_{\text{init}} + \tilde{\mathcal{F}}, \mathcal{P}^{(0)}) \leq 3 \cdot \text{OPT}_{k+\ell+1}(\mathcal{P}^{(0)})$ .

By [\(20\)](#page-16-6), Claim [5.6](#page-16-7) and Claim [5.7,](#page-17-0) there exists a set  $\tilde{\mathcal{F}} \subseteq \mathbf{P}$  of  $m + \ell + 1 \leq 2700\gamma \cdot (\ell + 1)$ centers such that  $\textsf{Cost}\left( \mathcal{U}_\mathtt{init} + \tilde{\mathcal{F}}, \mathcal{P}^{(0)} \right) \leq 3 \cdot \text{OPT}_{k+\ell+1}\left( \mathcal{P}^{(0)} \right)$ . Accordingly, from [\(9\)](#page-15-2), we get  $\textsf{Cost}\left(\mathcal{U}_\texttt{init}+\mathcal{F}^\star,\mathcal{P}^{(0)}\right)\leq \textsf{Cost}\left(\mathcal{U}_\texttt{init}+\tilde{\mathcal{F}},\mathcal{P}^{(0)}\right)\leq 3\cdot \text{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right)\text{, which implies Claim 5.5.}$  $\textsf{Cost}\left(\mathcal{U}_\texttt{init}+\mathcal{F}^\star,\mathcal{P}^{(0)}\right)\leq \textsf{Cost}\left(\mathcal{U}_\texttt{init}+\tilde{\mathcal{F}},\mathcal{P}^{(0)}\right)\leq 3\cdot \text{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right)\text{, which implies Claim 5.5.}$  $\textsf{Cost}\left(\mathcal{U}_\texttt{init}+\mathcal{F}^\star,\mathcal{P}^{(0)}\right)\leq \textsf{Cost}\left(\mathcal{U}_\texttt{init}+\tilde{\mathcal{F}},\mathcal{P}^{(0)}\right)\leq 3\cdot \text{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right)\text{, which implies Claim 5.5.}$ It now remains to prove Claim [5.6](#page-16-7) and Claim [5.7.](#page-17-0)

### Proof of Claim [5.6](#page-16-7)

We apply Lemma [4.2,](#page-13-4) by setting  $r = \ell + 1$ ,  $\mathcal{U} = \mathcal{U}_{\text{init}}$  and  $\mathcal{P} = \mathcal{P}^{(0)}$ . This implies the existence of a set  $\tilde{\mathcal{U}} \subseteq \mathcal{U}_{\text{init}}$  of at most  $(k - b)$  centers, with  $b = \lfloor (m - \ell - 1)/4 \rfloor$ , such that

$$
\begin{array}{lcl} \textsf{Cost}\left(\tilde{\mathcal{U}}, \mathcal{P}^{(0)}\right) & \leq & 6\gamma\cdot\left(\textsf{Cost}\left(\mathcal{U}_{\mathtt{init}}, \mathcal{P}^{(0)}\right) + \textsf{Cost}\left(\mathcal{V}, \mathcal{P}^{(0)}\right)\right) \\ \\ & \leq & 6\gamma\cdot\left(8\cdot\mathrm{OPT}_k\left(\mathcal{P}^{(0)}\right) + \mathrm{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right)\right) \leq 54\gamma\cdot\mathrm{OPT}_k\left(\mathcal{P}^{(0)}\right). \end{array}
$$

In the above derivation, the second inequality follows from Invariant [5.2,](#page-14-4) and the last inequality holds because  $\text{OPT}_{k+\ell+1}\left(\mathcal{P}^{(0)}\right) \leq \text{OPT}_k(\mathcal{P}^{(0)})$ . Since  $\text{OPT}_{k-b}\left(\mathcal{P}^{(0)}\right) \leq \text{Cost}\left(\tilde{\mathcal{U}},\mathcal{P}^{(0)}\right)$ , we get

<span id="page-17-1"></span>
$$
\text{OPT}_{k-b}\left(\mathcal{P}^{(0)}\right) \leq 54\gamma \cdot \text{OPT}_{k}\left(\mathcal{P}^{(0)}\right). \tag{21}
$$

Recall the way we defined  $\ell, \ell^*$  at Step 1 in Section [5.1.](#page-14-1) From [\(21\)](#page-17-1), it follows that  $b \leq \ell^*$ . Since  $b \geq \frac{m-\ell-1}{4} - 1 = \frac{m-\ell-5}{4}$  and  $\ell \geq \frac{\ell^2}{12 \cdot 54\gamma} - 1$ , we get  $\frac{m-\ell-5}{4} \leq 12 \cdot 54\gamma \cdot (\ell+1)$ , and hence  $m \leq$  $(2592\gamma + 1)(\ell + 1) + 4 \leq 2600\gamma \cdot (\ell + 1)$ . This concludes the proof of the claim.

#### Proof of Claim [5.7](#page-17-0)

We define assignment  $\sigma: \mathcal{P}^{(0)} \to \mathcal{U}_{\text{init}} + \tilde{\mathcal{F}}$ , as follows.<sup>[11](#page-17-2)</sup> Consider any point  $p \in \mathcal{P}^{(0)}$ .

- If  $p \in C_{v_i}(\mathcal{V}, \mathcal{P}^{(0)})$  for some  $i \in [1, k m]$ , then  $\sigma(p) := u_i$ .
- Otherwise,  $\sigma(p) := \pi_{\mathcal{V}}(p)$ .

In words, for every well-separated pair  $(u_i, v_i) \in \mathcal{U}_{\text{init}} \times \mathcal{V}$  all the points in the cluster of  $v_i$  get reassigned to the center  $u_i$ , and the assignment of all other points remain unchanged (note that their assigned centers are present in  $\mathcal{U}_{\text{init}} + \tilde{\mathcal{F}}$  as well as  $\mathcal{V}$ ). Now, recall that the set of centers  $U_{\text{init}}$  is robust (see Invariant [5.2\)](#page-14-4). Hence, by applying Lemma [3.9,](#page-13-5) we infer that

$$
\mathsf{Cost}\left(\mathcal{U}_{\mathtt{init}}+\tilde{\mathcal{F}},\mathcal{P}^{(0)}\right) \leq \sum_{p \in \mathcal{P}^{(0)}} d(p,\sigma(p)) \leq 3 \cdot \mathsf{Cost}\left(\mathcal{V},\mathcal{P}^{(0)}\right).
$$

The claim follows since  $\text{Cost}(\mathcal{V}, \mathcal{P}^{(0)}) = \text{OPT}_{k+\ell+1}(\mathcal{P}^{(0)})$  by definition.

<span id="page-17-2"></span><sup>&</sup>lt;sup>11</sup>Recall the notations  $C_u(\mathcal{U}, \mathcal{P})$  and  $\pi_{\mathcal{U}}(p)$  from Section [3.1.](#page-11-0)

### <span id="page-18-0"></span>5.3 Analyzing the Recourse

Recall the description of our algorithm from Section [5.1,](#page-14-1) and consider a given epoch (say)  $\mathcal E$  of length  $(\ell + 1)$ . The total recourse incurred by the algorithm during this epoch is

<span id="page-18-1"></span>
$$
R_{\mathcal{E}} \leq \left| \mathcal{U}_{\text{init}} \oplus \mathcal{U}^{(0)} \right| + \left( \sum_{t=1}^{\ell+1} \left| \mathcal{U}^{(t)} \oplus \mathcal{U}^{(t-1)} \right| \right) + \left| \mathcal{U}^{(\ell+1)} \oplus \mathcal{U}_{\text{final}} \right|.
$$
 (22)

We will now bound each term on the right hand side of  $(22)$ . Towards this end, recall that  $\mathcal{U}^{(0)}$ is obtained by deleting  $\ell$  centers from  $\mathcal{U}_{\text{init}}$ , and hence we have  $|\mathcal{U}_{\text{init}} \oplus \mathcal{U}^{(0)}| = \ell$ . Next, it is easy to verify that in Step 3 (see Section [5.1\)](#page-14-1) we incur a worst-case recourse of at most one per update. Specifically, we have  $|\mathcal{U}^{(t)} \oplus \mathcal{U}^{(t-1)}| \leq 1$  for all  $t \in [1, \ell + 1]$ , and hence  $|\mathcal{U}^{(\ell+1)} \oplus \mathcal{U}_{\text{init}}| \leq$  $|\mathcal{U}^{(\ell+1)}\oplus\mathcal{U}^{(0)}|+|\mathcal{U}^{(0)}\oplus\mathcal{U}_{\text{init}}| \leq (\ell+1)+\ell=2\ell+1$ . Thus, from [\(22\)](#page-18-1) we get:

<span id="page-18-2"></span>
$$
R_{\mathcal{E}} \leq \ell + (\ell + 1) + \left| \mathcal{U}^{(\ell+1)} \oplus \mathcal{U}_{\text{final}} \right|
$$
  
\n
$$
\leq (2\ell + 1) + \left| \mathcal{U}^{(\ell+1)} \oplus \mathcal{U}_{\text{init}} \right| + |\mathcal{U}_{\text{init}} \oplus \mathcal{U}_{\text{final}}|
$$
  
\n
$$
\leq (4\ell + 2) + |\mathcal{U}_{\text{init}} \oplus \mathcal{W}^{\star}| + |\mathcal{W}^{\star} \oplus \mathcal{U}_{\text{final}}|
$$
  
\n
$$
= O(\ell + 1) + |\mathcal{W}^{\star} \oplus \mathcal{U}_{\text{final}}|.
$$
 (23)

In the above derivation, the last step follows from Corollary [5.3.](#page-15-5)

Since the epoch lasts for  $\ell+1$  updates, the  $O(\ell+1)$  term in the right hand side of [\(23\)](#page-18-2) contributes an amortized recourse of  $O(1)$ . Moreover, the term  $|\mathcal{W}^* \oplus \mathcal{U}_{\text{final}}|$  is proportional to the number of MAKE-ROBUST( $\cdot$ , $\cdot$ ) calls made while computing  $\mathcal{U}_{\text{final}} \leftarrow \text{RobUSTIFY}(\mathcal{W}^*)$ . So, the recourse of our algorithm is dominated by the number of calls made to the MAKE-ROBUST $(\cdot, \cdot)$  subroutine, and Lemma [5.8](#page-18-3) implies that our algorithm has an amortized recourse of  $O(\log^2 \Delta)$ .

<span id="page-18-3"></span>**Lemma 5.8.** The dynamic algorithm from Section [5.1](#page-14-1) makes at most  $O(\log^2 \Delta)$  many calls to MAKE-ROBUST $(\cdot, \cdot)$ , amortized over the entire sequence of updates (spanning multiple epochs).

We devote the rest of this section towards proving Lemma [5.8.](#page-18-3)

Contaminated vs Clean Centers. Focus on the scenario at the start of a given epoch (see Section [5.1\)](#page-14-1). By Invariant [5.2,](#page-14-4) the set  $\mathcal{U}_{\text{init}}$  is robust w.r.t.  $\mathcal{P}^{(0)}$ . For each center  $u \in \mathcal{U}_{\text{init}}$ , we maintain an integer  $t[u]$  such that: (i) u is  $t[u]$  robust w.r.t.  $\mathcal{P}^{(0)}$ , and (ii)  $10^{t[u]} \geq d(u, \mathcal{U}_{\text{init}} - u)/200$ . The existence of  $t[u]$  is guaranteed by Definition [3.5.](#page-12-6)<sup>[12](#page-18-4)</sup> Let  $(p_0(u), p_1(u), \ldots, p_{t[u]}(u))$  be the  $t[u]$ robust sequence w.r.t.  $\mathcal{P}^{(0)}$  corresponding to u (i.e.,  $u = p_0(u)$ ), and for each  $i \in [1, t[u]]$ , let  $B_i(u) = \text{Ball}_{10^i}^{\mathcal{P}^{(0)}}(p_i(u))$ . Recall that by Lemma [3.3,](#page-12-0) we have  $B_1(u) \subseteq B_2(u) \subseteq \cdots \subseteq B_{t[u]}(u)$ .

Now, consider any  $j \in [1, \ell + 1]$ , and let  $q_j \in \mathbf{P}$  denote the point being inserted/deleted in P during the j<sup>th</sup> update in the epoch, i.e.,  $\mathcal{P}^{(j)} \oplus \mathcal{P}^{(j-1)} = \{q_j\}$ . We say that this j<sup>th</sup> update contaminates a center  $u \in \mathcal{U}_{\text{init}}$  iff  $d(q_j, p_{t[u]}(u)) \leq 10^{t[u]}$ . Intuitively, this means that if this  $j^{th}$ update were taken into account while defining the balls  ${B_i(u)}_i$  at the start of the epoch, then it might have impacted our decision to classify u as being  $t[u]$ -robust at that time. Furthermore, we say that the center  $u \in \mathcal{U}_{\text{init}}$  is **clean** at the end of the epoch if no update  $j \in [1, \ell+1]$  contaminated it (i.e.  $B_{t[u]}(u)$  and accordingly all of the balls  $B_i(u)$  remain intact during the updates in this epoch); otherwise we say that the center  $u$  is **contaminated** at the end of the epoch.

<span id="page-18-5"></span>In the two claims below, we summarize a few key properties of clean and contaminated centers. We defer the proof of Claim [5.10](#page-19-0) to Section [5.3.1.](#page-20-0)

<span id="page-18-4"></span><sup>&</sup>lt;sup>12</sup>We use t[u] only for the sake of analyzing recourse. Here, the actual algorithm remains the same as in Section [5.1.](#page-14-1) But, we make use of these integers in Section [6](#page-20-1) to get fast update time.

**Claim 5.9.** If  $u \in \mathcal{U}_{\text{init}}$  is clean at the end of the epoch, then u is t[u]-robust w.r.t.  $\mathcal{P}^{(\ell+1)}$ .

*Proof.* Let  $u \in \mathcal{U}_{\text{init}}$  be a clean center at the end of the epoch. So, during the epoch no point was inserted into/deleted from  $B_{t[u]}$ . As  $B_1(u) \subseteq B_2(u) \subseteq \cdots \subseteq B_{t[u]}(u)$  by Lemma [3.3,](#page-12-0) this implies that during the epoch no point was inserted into/deleted from any of the balls  $B_1(u), B_2(u), \ldots, B_{t[u]}(u)$ . Thus, we have  $\text{Ball}_{10^i}^{\mathcal{P}^{(0)}}(p_i(u)) = \text{Ball}_{10^i}^{\mathcal{P}^{(\ell+1)}}(p_i(u))$  for all  $i \in [0, \ell+1]$ .  $\Box$ 

<span id="page-19-0"></span>The claim now follows from Definition [3.2.](#page-11-3)

Claim 5.10. Each update during the epoch contaminates at most  $O(\log \Delta)$  centers in  $\mathcal{U}_{\text{init}}$ .

At the end of the epoch, we set  $\mathcal{U}_{\text{final}} \leftarrow \text{ROBUSTIFY}(\mathcal{W}^{\star})$ . By Lemma [3.6,](#page-12-2) the subroutine ROBUSTIFY  $(W^*)$  makes at most one call to MAKE-ROBUST $(w, \cdot)$  for each point  $w \in W^*$ , and zero call to MAKE-ROBUST $(w, \cdot)$  for each point  $w \in \mathbf{P} \setminus \mathcal{W}^*$ . Accordingly, we can partition the calls to MAKE-ROBUST $(\cdot, \cdot)$  that are made by ROBUSTIFY  $(\mathcal{W}^{\star})$  into the following three types.

Type I. A call to MAKE-ROBUST $(w, \cdot)$  for some  $w \in \mathcal{W}^* \setminus \mathcal{U}_{init}$ . The total number of such calls is at most  $|W^* \setminus \mathcal{U}_{\text{init}}| \leq |W^* \oplus \mathcal{U}_{\text{init}}| = O(\ell+1)$  (see Corollary [5.3\)](#page-15-5). Since the epoch lasts for  $(\ell+1)$  updates, the amortized number of Type I calls to MAKE-ROBUST $(\cdot, \cdot)$ , per update, is  $O(1)$ .

Type II. A call to MAKE-ROBUST $(w, \cdot)$  for some  $w \in \mathcal{W}^* \cap \mathcal{U}_{init}$  that is contaminated at the end of the epoch. By Claim [5.10,](#page-19-0) the amortized number of such Type II MAKE-ROBUST $(\cdot, \cdot)$  calls, per update, is  $O(\log \Delta)$ .

Type III. A call to MAKE-ROBUST $(w, \cdot)$  for some  $w \in \mathcal{W}^* \cap \mathcal{U}_{\text{init}}$  that is clean at the end of the epoch. Recall that the center w was  $t[w]$ -robust w.r.t.  $\mathcal{P}^{(0)}$  at the start of the epoch, and by Claim [5.9](#page-18-5) it remains  $t[w]$ -robust w.r.t.  $\mathcal{P}^{(\ell+1)}$  at the end of the epoch. Furthermore, note that if a center is t'-robust, then it is also t''-robust for all  $t'' \leq t'$ . Thus, at the end of the epoch, the call to  $\text{MAKE-ROBUST}(w, t)$  could have been made for only one reason: The subroutine ROBUSTIFY  $(W^*)$  wanted to ensure that w was t-robust w.r.t.  $\mathcal{P}^{(\ell+1)}$  for some  $t > t[w]$ , but it was not the case. Suppose that  $w' \leftarrow \text{MAKE-ROBUST}(w, t)$  was the center returned by this call to MAKE-ROBUST( $\cdot$ ,  $\cdot$ ). Then at the end of this call, we set  $t[w'] \leftarrow t$ . Clearly, we have  $t[w'] > t[w]$ .

To bound the amortized number of Type III calls, we need to invoke a more "global" argument, that spans across multiple epochs. Consider a maximal "chain" of  $j$  many Type III calls (possibly spanning across multiple different epochs), in increasing order of time:

$$
w_1 \leftarrow \text{MAKE-ROBUST}(w_0, t[w_1]), w_2 \leftarrow \text{MAKE-ROBUST}(w_1, t[w_2]),
$$
  
...,  $w_j \leftarrow \text{MAKE-ROBUST}(w_{j-1}, t[w_j]).$ 

Note that the calls in the above chain can be interspersed with other Type I, Type II or Type III calls that are not part of the chain. Still, from the above discussion, we get  $0 \le t[w_0] < t[w_1] < \cdots <$  $t[w_i] \leq [\log \Delta]$ . So, the chain has length at most  $O(\log \Delta)$ . Also, for the chain to start in the first place, we must have had a Type I or Type II call to MAKE-ROBUST $(\cdot, \cdot)$  which returned the center  $w_0$ . We can thus "charge" the length (total number of Type III calls) in this chain to the Type I or Type II call that triggered it (by returning the center  $w_0$ ). In other words, the total number of Type III calls ever made is at most  $O(\log \Delta)$  times the total number of Type I plus Type II calls. Since the amortized number of Type I and Type II calls per update is  $O(\log \Delta)$ , the amortized number of Type III calls per update is  $O(\log^2 \Delta)$ . This concludes the proof of Lemma [5.8.](#page-18-3)

#### <span id="page-20-0"></span>5.3.1 Proof of Claim [5.10](#page-19-0)

Assume  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(\ell+1)}$  is an updated point during the epoch. Let  $u \in \mathcal{U}_{\text{init}}$  be contaminated by  $p, \text{ i.e., } d(p, p_{t[u]}(u)) \leq 10^{t[u]}$ . According to Lemma [3.3,](#page-12-0)  $d(p_{t[u]}(u), u) = d(p_{t[u]}(u), p_0(u)) \leq 10^{t[u]} / 2$ , which concludes

<span id="page-20-4"></span>
$$
d(p, u) \le d(p, p_{t[u]}(u)) + d(p_{t[u]}(u), u) \le 10^{t[u]} + 10^{t[u]} / 2 \le 2 \cdot 10^{t[u]}.
$$
\n(24)

Let  $\{u_1, u_2, \ldots, u_\mu\} \subseteq \mathcal{U}_{\text{init}}$  be all centers contaminated by p ordered in decreasing order by the time they were added to the main solution via a call to MAKE-ROBUST( $\cdot$ , $\cdot$ ). So, when  $u_i$  is added to the main solution U,  $u_{i+1}$  was already present in U, which concludes  $10^{t[u_i]} \leq d(u_i, u_{i+1})/10$ , for every  $i \in [1, \mu - 1]$  (by the choice of  $t[u_i]$  in MAKE-ROBUST at that time). Hence,

$$
10^{t[u_{i+1}]}\geq d(p,u_{i+1})/2\geq (d(u_i,u_{i+1})-d(p,u_i))/2\geq 5\cdot 10^{t[u_i]}-10^{t[u_i]}=4\cdot 10^{t[u_i]}.
$$

The first and last inequalities hold by [\(24\)](#page-20-4) for  $u = u_{i+1}, u_i$ . Finally, this concludes  $t[u_\mu] > \cdots >$  $t[u_2] > t[u_1]$ . Since distances between any two point in the space is between 1 and  $\Delta$ , we know  $0 \leq t[u_i] \leq \lceil \log \Delta \rceil$  for each  $i \in [1, \mu]$ , which concludes  $\mu = O(\log \Delta)$ .

# <span id="page-20-1"></span>6 Achieving  $\tilde{O}(k)$  Update Time

We first outline how to implement the algorithm from Section [5.1](#page-14-1) in  $\tilde{O}(n)$  update time, by incurring only a  $O(1)$  multiplicative overhead in approximation ratio and recourse (*n* is an upper bound on the size of the input  $\mathcal{P} \subseteq \mathbf{P}$ , throughout the sequence of updates). In Section [6.3,](#page-24-1) we show how to further improve the update time from  $O(n)$  to  $O(k)$  using standard sparsification techniques.

Disclaimer. In this section, we often use asymptotic notations and informal arguments without proofs. The reader can find the correct values of the parameters together with complete formal proofs for the statements of this section in Part [III](#page-35-0) (full version).

#### <span id="page-20-2"></span>6.1 Auxiliary Data Structure and Randomized Local Search

Recall that  $U \subseteq P$  is the solution (set of k centers) maintained by our algorithm, and  $P \subseteq P$ denotes the current input. For each point  $p \in \mathcal{P} \cup \mathcal{U}$ , we maintain a BST (balanced search tree)  $\mathcal{T}_p$  that stores the centers U in increasing order of their distances to p. Note that after every change (insertion/deletion of a center) in the set U, we can update all these BSTs in  $O(|\mathcal{P}| +$  $|\mathcal{U}| = \tilde{O}(n + k) = \tilde{O}(n)$  time. Similarly, after the insertion/deletion of a point  $p \in \mathcal{P}$ , we can construct/destroy the relevant BST  $\mathcal{T}_p$  in  $O(|\mathcal{U}|) = O(k) = O(n)$  time. In other words, if the algorithm from Section [5.1](#page-14-1) incurs a total recourse of  $\tau$  while handling a sequence of  $\mu$  updates, then we spend  $\tilde{O}(n \cdot (\tau + \mu))$  total time on maintaining this auxiliary data structure (collection of BSTs) over the same update-sequence. Since  $\tau = O(\mu \cdot \log^2 \Delta)$  (see Section [5.3\)](#page-18-0), this incurs an amortized update time of  $\tilde{O}(n)$ , which is within our budget.

<span id="page-20-3"></span>We will use the randomized local search algorithm, developed in  $[BCG^+24]$  and summarized in the lemma below, as a crucial subroutine.

**Lemma 6.1** (Randomized Local Search  $[BCG^+24]$ ). Suppose that we have access to the auxiliary data structure described above. Then, given any integer  $s \in [0, k-1]$ , in  $\tilde{O}(ns)$  time we can find a subset  $\mathcal{U}^{\star} \subseteq \mathcal{U}$  of  $(k-s)$  centers such that  $\text{Cost}(\mathcal{U}^{\star}, \mathcal{P}) \leq O(1) \cdot \text{OPT}_{k-s}^{\mathcal{U}}(\mathcal{P})$ .

## <span id="page-21-0"></span>6.2 Implementing Our Dynamic Algorithm

Henceforth, we focus on a given epoch of our dynamic algorithm that lasts for  $(\ell + 1)$  updates (see Section [5.1\)](#page-14-1), and outline how to implement the algorithm in such a manner that it spends  $O(n \cdot (\ell+1))$  total time during the whole epoch, except the call to ROBUSTIFY (see Equation [\(11\)](#page-15-4)). For ROBUSTIFY, we provide an implementation that takes an amortized time of  $O(n)$ , over the entire sequence of updates (spanning multiple epochs). This implies an overall amortized update time of  $O(n)$ . Below, we first show how to implement each of Steps 1 - 4, as described in Section [5.1,](#page-14-1) one after another. Then, we provide the implementation of ROBUSTIFY in Section [6.2.1.](#page-22-0)

#### Implementing Step 1.

Our task here is to compute an estimate of the value of  $\ell^*$ . For each  $i \in [0, \log_2 k]$  define  $s_i := 2^i$ , and let  $s_{-1} := 0$ . We now run a **for** loop, as described below.



After finding  $\hat{\ell}$ , we set the length of the epoch to be  $\ell + 1$  where  $\ell \leftarrow \frac{\hat{\ell}}{12.6}$  $\frac{\hat{\ell}}{12\cdot\Theta(\gamma)}$ . With some extra calculations, we can show that  $\ell + 1 = \Omega(\hat{\ell} + 1) = \Omega(\ell^* + 1)$  and

$$
\frac{\mathop{\rm{OPT}}\nolimits_{k-\ell}(\mathcal{P}^{(0)})}{\Theta(\gamma)} \leq \mathop{\rm{OPT}}\nolimits_k(\mathcal{P}^{(0)}) \leq 4 \cdot \mathop{\rm{OPT}}\nolimits_{k+\ell}(\mathcal{P}^{(0)}).
$$

The running time of this for loop is  $\tilde{O}\left(n \sum_{j=0}^{i^*} s_j\right) = \tilde{O}(ns_{i^*})$ , where  $i^*$  is the index s.t.  $s_{i^*-1} = \hat{\ell}$ . Thus, we have  $s_{i^*} = O(\hat{\ell}) = O(\ell+1)$ , and hence we can implement Step 1 in  $\tilde{O}(n \cdot (\ell+1))$  time.

### Implementing Step 2.

Instead of finding the optimum set of  $(k - \ell)$  centers within  $\mathcal{U}_{init}$ , we approximate it using Lemma [6.1:](#page-20-3) We compute a set of  $(k - \ell)$  centers  $\mathcal{U}^{(0)} \subseteq \mathcal{U}_{\text{init}}$  such that Cost  $(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}) \leq$  $O(1) \cdot \text{OPT}_{k-\ell}^{\mathcal{U}_{\text{init}}}(\mathcal{P}^{(0)})$ . With the same arguments as before, we get  $\text{Cost}(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}) \leq O(1)$ . OPT<sub>k+ $\ell$ </sub>( $\mathcal{P}^{(0)}$ ). Note that the running time for this step is also  $\tilde{O}(n \cdot (\ell+1)).$ 

#### Implementing Step 3.

Trivially, we can implement each of these updates in constant time.

## Implementing Step 4.

<span id="page-21-1"></span>We first need to add  $O(\ell+1)$  centers to  $\mathcal{U}_{\text{init}}$ , while minimizing the cost of the solution w.r.t.  $\mathcal{P}^{(0)}$ . We compute an approximation of  $\mathcal{U}^*$ , by setting  $\mathcal{U} = \mathcal{U}_{\text{init}}$ ,  $\mathcal{P} = \mathcal{P}^{(0)}$  and  $s = \Theta(\gamma \cdot (\ell + 1))$  in Lemma [6.2](#page-21-1) below (see Equation [\(9\)](#page-15-2)). This also takes  $\tilde{O}(n \cdot (\ell+1))$  time. We defer the proof sketch of Lemma [6.2](#page-21-1) to Section [6.2.2.](#page-24-0)

Lemma 6.2. Suppose that we have access to the auxiliary data structure described above (see Section [6.1\)](#page-20-2). Then, given any integer  $s \geq 1$ , in  $\tilde{O}(ns)$  time we can find a superset  $\mathcal{U}^* \supseteq \mathcal{U}$  of  $(k+s)$  centers such that  $\text{Cost}(\mathcal{U}^*, \mathcal{P}) \leq O(1) \cdot \min_{\mathcal{F} \subseteq \mathbf{P}:|\mathcal{F}| \leq s} \text{Cost}(\mathcal{U} + \mathcal{F}, \mathcal{P}).$ 

At this stage, we compute  $\mathcal{V}^* := \mathcal{U}^* + (\mathcal{P}^{(\ell+1)} - \mathcal{P}^{(0)})$  as in Equation [\(10\)](#page-15-3), in only  $\tilde{O}(\ell+1)$ time. Next, we compute an approximation of  $W^*$  (see Equation [\(10\)](#page-15-3)) using Lemma [6.1,](#page-20-3) which again takes  $\tilde{O}(n \cdot (\ell+1))$  time. It follows that Cost  $(\mathcal{W}^\star, \mathcal{P}^{(\ell+1)}) \leq O(1) \cdot \text{OPT}_k(\mathcal{P}^{(\ell+1)})$ . Finally, we explain below how we implement the call to ROBUSTIFY $(\mathcal{W}^{\star})$  (see Equation [\(11\)](#page-15-4)).

#### <span id="page-22-0"></span>6.2.1 Implementing the calls to Robustify( $\cdot$ ) subroutine

Recall Algorithm [1](#page-12-7) and Algorithm [2](#page-12-8) from Section [3.2.](#page-11-1) In the static setting, there are known  $O(1)$ approximation algorithms for 1-median with  $O(n)$  runtime [\[MP02\]](#page-75-2). Using any such 1-median algorithm, it is relatively straightforward to (approximately) implement a call to MAKE-ROBUST $(\cdot, \cdot)$ in  $O(n)$  time (see Line [3](#page-12-9) in Algorithm [1\)](#page-12-7). Using the auxiliary data structure (see Section [6.1\)](#page-20-2), it is easy to implement each invocation of Line [2](#page-12-5) in Algorithm [1](#page-12-7) in  $O(1)$  time, whereas Line [4](#page-12-10) in Algorithm [1](#page-12-7) trivially takes  $O(1)$  time. By Lemma [5.8,](#page-18-3) our dynamic algorithm makes  $O(1)$  many amortized calls to MAKE-ROBUST( $\cdot, \cdot$ ), per update. Thus, it follows that we spend  $O(n)$  amortized time per update on implementing Lines [2](#page-12-5) to [4](#page-12-10) in Algorithm [1.](#page-12-7)

There remains a significant challenge: We might have to iterate over  $|\mathcal{W}| = k$  centers in Line [1](#page-12-11) in Algorithm [1,](#page-12-7) before we find a center  $w \in \mathcal{W}$  that violates Equation [\(4\)](#page-12-4). Let us refer to this operation as "testing a center w"; this occurs when we check whether w violates Equation  $(4)$ . In other words, we need to perform  $O(k)$  many such tests in Line [1,](#page-12-11) before we execute a MAKE-ROBUST $(\cdot, \cdot)$  call in Line [3](#page-12-9) in Algorithm [1.](#page-12-7) Note that because of Lemma [5.8,](#page-18-3) we perform  $O(k)$  many tests, on average, per update. Thus, if we could hypothetically perform each test in  $O(1)$  time, then we would incur an additive overhead of  $O(k)$  in our amortized update time, and everything would be fine.

The issue, however, is that testing a center can be prohibitively expensive. This is because Equation  $(4)$  consists of two conditions. The second condition (which finds the value of t) requires us to know the value of  $d(w, W - w)$ , and this can indeed be implemented in  $O(1)$  time using our auxiliary data structure (see Section [6.1\)](#page-20-2). The first condition asks us to check whether  $w$  is t-robust, and there does not seem to be *any* efficient way in which we can implement this check (see Definition [3.2\)](#page-11-3). To address this significant challenge, we modify the execution of a call to ROBUSTIFY $(W^*)$  at the end of an epoch, as described below.

## Modified version of the call to Robustify $(W^*)$ .

At the end of an epoch, the call to ROBUSTIFY( $W^*$ ) is supposed to return the set  $\mathcal{U}_{\text{final}}$  (see Equation [\(11\)](#page-15-4)). We replace this call to ROBUSTIFY( $W^*$ ) by the procedure in Algorithm [4](#page-23-0) below.

To appreciate what Algorithm [4](#page-23-0) does, recall the recourse analysis in Section [5.3;](#page-18-0) in particular, the distinction between *contaminated* vs *clean* centers in  $U_{\text{init}}$ , and the three types of calls to the MAKE-ROBUST( $\cdot$ , $\cdot$ ) subroutine. Note that in Lines [1](#page-23-1) to [3](#page-23-2) in Algorithm [4,](#page-23-0) the sets  $W_1, W_2$  and  $W_3$ respectively correspond to those centers w that might *potentially* be the sources of Type I, Type II and Type III calls to MAKE-ROBUST $(w, \cdot)$ . We refer to the centers in  $\mathcal{W}_1, \mathcal{W}_2$  and  $\mathcal{W}_3$  respectively as Type I, Type II and Type III centers.

The key difference between Algorithm [4](#page-23-0) and the previous version of ROBUSTIFY( $W^*$ ) is this: In Algorithm [4,](#page-23-0) we proactively make calls to MAKE-ROBUST $(w, \cdot)$  without even checking the first condition in Equation [\(4\)](#page-12-4), which was the main bottleneck in achieving efficient update time. To be more specific, we proactively call MAKE-ROBUST $(w, \cdot)$  for every Type I and Type II center w (see Line [7\)](#page-23-3). In contrast, for a Type III center w, we call MAKE-ROBUST $(w, \cdot)$  whenever we observe that  $t > t[w]$ , where t is the smallest integer satisfying  $10^t \ge d(w, W - w)/200$  (see Lines [12](#page-23-4) and [15\)](#page-23-5). Note that if  $t \leq t[w]$  in Line [13,](#page-23-6) then by Claim [5.9](#page-18-5) the center w does not violate Equation [\(4\)](#page-12-4).

Algorithm 4: Modified version of the call to ROBUSTIFY( $W^*$ ) at the end of an epoch.

<span id="page-23-9"></span><span id="page-23-8"></span><span id="page-23-7"></span><span id="page-23-3"></span><span id="page-23-2"></span><span id="page-23-1"></span>1  $W_1 \leftarrow W^* \setminus \mathcal{U}_{\text{init}}$ 2  $W_2 \leftarrow \{w \in \mathcal{W}^{\star} \cap \mathcal{U}_{\text{init}} : w \text{ is contaminated}\}\$  $\mathbf{3} \ \mathcal{W}_3 \leftarrow \{w \in \mathcal{W}^\star \cap \mathcal{U}_{\text{init}} : w \text{ is clean}\}\$ // The set  $W^*$  is partitioned into the subsets  $W_1, W_2, W_3$ 4  $W \leftarrow W^*$ 5 for each center  $w \in \mathcal{W}_1 \cup \mathcal{W}_2$  do 6  $t \leftarrow$  Smallest integer satisfying  $10^t \geq d(w, W - w)/100$ 7  $w_0 \leftarrow \text{MAKE-ROBUST}(w, t)$  $\mathbf{8} \quad W \leftarrow \mathcal{W} - w + w_0$ 9 Save  $t[w_0] \leftarrow t$  and  $p_{t[w_0]}(w_0) \leftarrow w$  (see Section [5.3\)](#page-18-0) together with  $w_0$ 10 while true do 11 **for** each center  $w \in \mathcal{W}_3$  do 12  $t \leftarrow$  Smallest integer satisfying  $10^t \ge d(w, W - w)/200$ 13 if  $t > t[w]$  then  $\begin{array}{c|c|c|c|c} \hline \end{array}$  t  $t'$  ← Smallest integer satisfying  $10^t \ge d(w, W - w)/100$ 15  $w_0 \leftarrow \text{MAKE-ROBUST}(w, t')$ 16  $\bigcup \mathcal{W} \leftarrow \mathcal{W} - w + w_0$ 17 Save  $t[w_0] \leftarrow t'$  and  $p_{t[w_0]}(w_0) \leftarrow w$  (see Section [5.3\)](#page-18-0) together with  $w_0$ 18 | | | go back to Line [10.](#page-23-7) 19 return  $\mathcal{U}_{\text{final}} \leftarrow \mathcal{W}$ .

<span id="page-23-13"></span><span id="page-23-12"></span><span id="page-23-11"></span><span id="page-23-10"></span><span id="page-23-6"></span><span id="page-23-5"></span><span id="page-23-4"></span><span id="page-23-0"></span>**Lemma 6.3** (Informal). Lemma [5.8](#page-18-3) continues to hold even after the call to ROBUSTIFY( $W^*$ ) at the end of every epoch is replaced by the procedure in Algorithm  $\ddot{4}$ .

Proof. (Sketch) The lemma holds because the procedure in Algorithm [4](#page-23-0) is perfectly aligned with the recourse analysis in Section [5.3.](#page-18-0) In other words, the recourse analysis accounts for the scenario where we make proactive calls to MAKE-ROBUST $(\cdot, \cdot)$ , precisely in the manner specified by Algorithm [4.](#page-23-0) For example, the recourse analysis bounds the number of Type I and Type II calls to MAKE-ROBUST $(\cdot, \cdot)$ , by pretending that every Type I or Type II center makes such a call, regardless of whether or not it violates Equation [\(4\)](#page-12-4).  $\Box$ 

Bounding the Update Time. First, note that we can implement each invocation of Lines [1](#page-23-1) to [4](#page-23-8) in Algorithm [4](#page-23-0) in  $O(k \cdot (\ell + 1))$  time, which gets amortized over the length of the epoch, as an epoch lasts for  $(\ell + 1)$  updates. Specifically, to compute the sets  $\mathcal{W}_2$  and  $\mathcal{W}_3$ , we iterate over all  $w \in \mathcal{W}^* \cap \mathcal{U}_{\text{init}}$  and  $q \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(\ell+1)}$ , and check whether the update involving q contaminates w, using the value  $t[w]$  and the point  $p_{t[w]}(w)$ . Moreover, Lines [1](#page-23-1) and [4](#page-23-8) trivially take  $O(k)$  time.

Using the auxiliary data structure (see Section [6.1\)](#page-20-2), we can implement each invocation of Lines  $6$ , [12](#page-23-4) and [14](#page-23-10) in  $O(1)$  time. Next, say that an iteration of the **for** loop in Line [11](#page-23-11) is uninterrupted if we find that  $t \leq t[w]$  in Line [13](#page-23-6) (and accordingly do not execute any line within the if block) and *interrupted* otherwise. Each uninterrupted iteration of the **for** loop takes  $O(1)$  time. Furthermore, there can be at most  $|\mathcal{W}_3| = O(k)$  many consecutive uninterrupted iterations of the for loop in Line [11:](#page-23-11) Any such chain of uninterrupted iterations is broken (i) either by an interrupted iteration,

which involves a call to  $\text{MAKE-ROBUST}(w, t')$  in Line [15,](#page-23-5) (ii) or by the termination of the procedure in Line [19](#page-23-12) (this can happen only once in an epoch).

From the preceding discussion, it follows that total time spent on the remaining lines in Al-gorithm [4](#page-23-0) is dominated by the time spent on the calls to MAKE-ROBUST $(\cdot, \cdot)$ . Recall that at the start of Section [6.2.1,](#page-22-0) we have already explained that we spend  $O(n)$  time to implement each call to MAKE-ROBUST( $\cdot$ , $\cdot$ ). Finally, Lemmas [5.8](#page-18-3) and [6.3](#page-23-13) imply that we make  $O(1)$  amortized calls to MAKE-ROBUST( $\cdot$ ,  $\cdot$ ), per update. This gives us an overall amortized update time of  $O(n)$ .

#### <span id="page-24-0"></span>6.2.2 Algorithm for Lemma [6.2](#page-21-1)

Since we have a set of fixed k centers  $\mathcal U$  that must be contained in  $\mathcal U^*$ , if we can treat these fixed centers as a single center instead of a set of k centers, we might be able to reduce the problem to a  $(s + 1)$ -median problem. So, we contract all of the points U to a single point  $u^*$  and define a new space  $\mathcal{P}' = (\mathcal{P} - \mathcal{U}) + u^*$  with a new metric d' as follows.

<span id="page-24-2"></span>
$$
\begin{cases} d'(x, u^*) := d(x, \mathcal{U}) & \forall x \in \mathcal{P} \\ d'(x, y) := \min\{d'(x, u^*) + d'(y, u^*), d(x, y)\} & \forall x, y \in \mathcal{P} \end{cases}
$$
(25)

This function d' defines a metric on  $\mathcal{P}'$ . A simple way to verify this is that d' is the metric derived from the shortest path in a complete graph where weight of edges between any two nodes in  $\mathcal{U}$  is zero and the weight of the other edges is the d distance of their endpoints (you can find a complete proof in Claim [11.2\)](#page-46-1). We also define weights for each  $x \in \mathcal{P}'$ . We define the weight of all  $x \in \mathcal{P}'-u^*$ to be 1 and the weight of  $u^*$  to be very large denoted by  $\infty$  to enforce any constant approximate solution for  $(s + 1)$ -median in  $\mathcal{P}'$  to open center  $u^*$ .

In order to have access to metric  $d'$ , we can simply construct an oracle  $D'$  to compute it. This is because we have access to sorted distances of any  $p \in \mathcal{P}$  to U through  $\mathcal{T}_p$  in our auxiliary data structure. Combining with the definition of d', it is easy to see that we can compute  $d'(x, y)$  in  $O(1)$  time for each  $x, y \in \mathcal{P}'$ .

Next, we run the algorithm of [\[MP02\]](#page-75-2) for  $(s + 1)$ -median problem on  $\mathcal{P}'$  w.r.t. metric d' to find a F of size at most  $(s + 1)$  which is a constant approximation for  $\text{OPT}_{s+1}(\mathcal{P}')$  in a total of  $\tilde{O}(|\mathcal{P}'| \cdot (s+1)) = \tilde{O}(n \cdot (\ell+1))$  time. Finally, we let  $\mathcal{U}^* \leftarrow \mathcal{U} + (\mathcal{F} - u^*)$ . Note that  $\mathcal{F} - u^* \subseteq \mathcal{P}$  and its size is at most s since  $u^* \in \mathcal{F}$ . This set  $\mathcal{U} + (\mathcal{F} - u^*)$  is going to be a good solution w.r.t. metric d as well as  $d'$  (see Lemma [11.3\)](#page-48-0).

Algorithm 5: Computing an approximation of the optimum  $\mathcal{U}^* \supseteq \mathcal{U}$  of size  $(k + s)$ .

1  $\mathcal{P}' \leftarrow (\mathcal{P} - \mathcal{U}) + u^*$ .

- 2  $w(u^*) \leftarrow \infty, w(x) \leftarrow 1 \ \forall x \in \mathcal{P}' u^*$ .
- **3** Consider  $D'$  as an oracle to the metric  $d'$  defined in Equation  $(25)$ .
- 4 Compute any  $O(1)$  approximate solution  $\mathcal{F} \subseteq \mathcal{P}'$  for  $(s+1)$ -median problem on weighted metric space  $\mathcal{P}'$  in  $\tilde{O}(|\mathcal{P}'| \cdot (s+1))$  time using [\[MP02\]](#page-75-2) with access to distance oracle D'. 5 return  $\leftarrow U + (\mathcal{F} - u^*)$ .

## <span id="page-24-1"></span>6.3 Improving the Update Time to  $\tilde{O}(k)$

Extension to Weighted Case. First, we argue that our algorithm can be extended to the weighted case defined as follows. We have a metric space  $P$  with positive weights  $w(p)$  for each  $p \in \mathcal{P}$  and distance function d. Denote this weighted space by  $(\mathcal{P}, w, d)$ . The cost of a collection U of  $k$  centers is defined as  $\mathsf{Cost}\,(\mathcal{U},\mathcal{P})=\sum_{p\in\mathcal{P}}w(p)\cdot d(p,\mathcal{U})$  and subsequently  $\mathsf{AverageCost}\,(\mathcal{U},S)=$ 

Cost  $(U, S) / (\sum_{p \in S} w(p))$  for all  $S \subseteq \mathcal{P}$ . We can extend our algorithm and all of the arguments for weighted case.

**Sparsification.** Note that parameter n in our algorithm is the maximum size of the space at any time during the total sequence of updates (it is **not** the size of the underlying ground metric space **P**). As a result, if we make sure that the size of the space P is at most  $O(k)$  at any point in time, then the amortized running time of the algorithm would be  $\tilde{O}(k)$  as desired.

We use the result of [\[BCLP23\]](#page-74-3) to sparsify the input. A simple generalization of this result is presented in Section 10 of  $[BCG+24]$  which extends this sparsifier to weighted metric spaces. The authors provided an algorithm to sparsify the space to  $O(k)$  weighted points. More precisely, given a dynamic metric space  $(\mathcal{P}, w, d)$  and parameter  $k \in \mathbb{N}$ , there is an algorithm that maintains a dynamic metric space  $(\mathcal{P}', w', d)$  in  $\tilde{O}(k)$  amortized update time such that the following holds.

- $\mathcal{P}' \subseteq \mathcal{P}$  and the size of  $\mathcal{P}'$  at any time is  $\tilde{O}(k)$ .
- A sequence of T updates in  $(\mathcal{P}, w, d)$ , leads to a sequence of  $O(T)$  updates in  $(\mathcal{P}', w', d)$ .<sup>[13](#page-25-2)</sup>
- Every  $\alpha$  approximate solution to the k-median problem in the metric space  $(\mathcal{P}', w', d)$  is also a  $O(\alpha)$  approximate solution to the k-median problem in the metric space  $(\mathcal{P}, w, d)$  with probability at least  $1 - \tilde{O}(1/n^c)$ .

Now, suppose that we are given a sequence of updates  $\sigma_1, \sigma_2, \ldots, \sigma_T$  in a dynamic metric space  $(\mathcal{P}, w, d)$ . Instead of feeding the metric space  $(\mathcal{P}, w, d)$  directly to our algorithm, we can perform this dynamic sparsification to obtain a sequence of updates  $\sigma'_1, \sigma'_2, \ldots, \sigma'_{T'}$  for a metric space  $(\mathcal{P}', w', d)$ , where  $T' = O(T)$ , and feed the metric space  $(\mathcal{P}', w', d)$  to our dynamic algorithm instead. Since our algorithm maintains a  $O(1)$  approximate solution U to the k-median problem in  $(\mathcal{P}', w', d)$ , then U is also a  $O(1)$  approximate solution for the k-median problem in  $(\mathcal{P}, w, d)$  with high probability.

Since the length of the stream is multiplied by  $O(1)$ , we would have a multiplicative overhead of  $O(1)$  in the amortized update time and recourse (amortized w.r.t. the original input stream).

# <span id="page-25-1"></span><span id="page-25-0"></span>7 Missing Proofs From Section [4](#page-13-2)

### 7.1 Proof of Lemma [4.1:](#page-13-3) Double-Sided Stability Lemma

Consider the LP relaxation for improper k-median problem on  $P$  for each k as follows.

$$
\min \sum_{p \in \mathcal{P}} \sum_{c \in \mathbf{P}} d(c, p) \cdot x_{cp}
$$
\n
$$
\text{s.t.} \quad x_{cp} \le y_c
$$
\n
$$
\sum_{c \in \mathbf{P}} x_{cp} \ge 1 \qquad \forall c \in \mathbf{P}, p \in \mathcal{P}
$$
\n
$$
\sum_{c \in \mathbf{P}} y_c \le k
$$
\n
$$
x_{cp}, y_c \ge 0 \qquad \forall c \in \mathbf{P}, p \in \mathcal{P}
$$

Denote the cost of the optimal fractional solution for this LP by  $\text{FOPT}_k$ . Since space  $\mathcal P$  is fixed here, we denote  $\text{OPT}_k(\mathcal{P})$  by  $\text{OPT}_k$ . It is known that the integrality gap of this relaxation is at

<span id="page-25-2"></span><sup>&</sup>lt;sup>13</sup>This guarantee follows from a slightly more refined analysis of the recourse of this sparsifier which is presented in [\[BCLP24\]](#page-74-6) (see Lemma 3.4 of [\[BCLP24\]](#page-74-6)).

most 3 [\[CS11\]](#page-74-10). So, for every k we have

<span id="page-26-1"></span>
$$
\text{FOPT}_k \le \text{OPT}_k \le 3 \cdot \text{FOPT}_k. \tag{26}
$$

**Claim 7.1.** For every  $k_1$ ,  $k_2$  and  $0 \leq \alpha, \beta \leq 1$  such that  $\alpha + \beta = 1$ , we have

$$
\text{FOPT}_{\alpha k_1 + \beta k_2} \leq \alpha \cdot \text{FOPT}_{k_1} + \beta \cdot \text{FOPT}_{k_2}.
$$

*Proof.* Assume optimal fractional solutions  $(x_1^*, y_1^*)$  and  $(x_2^*, y_2^*)$  to be an optimal solution for above LP for fractional  $k_1$  and  $k_2$ -median problems respectively. It is easy to verify that their convex combination  $(\alpha x_1^* + \beta x_2^*, \alpha y_1^* + \beta y_2^*)$  is a feasible solution for LP relaxation of  $(\alpha k_1 + \beta k_2)$ -median problem whose cost is  $\alpha$  FOPT<sub>k<sub>1</sub></sub> +  $\beta$  FOPT<sub>k<sub>2</sub></sub> which concludes the claim.  $\Box$ 

Now, plug  $k_1 = k - r$ ,  $k_2 = k + r/(12\eta)$ ,  $\alpha = 1/(12\eta)$  and  $\beta = 1 - \alpha$  in the claim. We have

$$
\alpha k_1 + \beta k_2 = \frac{1}{12\eta} (k - r) + \left( 1 - \frac{1}{12\eta} \right) \left( k + \frac{r}{12\eta} \right) = k - \frac{r}{(12\eta)^2} \le k.
$$

As a result,  $\text{FOPT}_k \leq \text{FOPT}_{\alpha k_1 + \beta k_2} \leq \alpha \text{FOPT}_{k_1} + \beta \text{FOPT}_{k_2}$ . Together with Equation [\(26\)](#page-26-1), we have  $OPT_k \leq 3\alpha \cdot OPT_{k_1} + 3\beta \cdot OPT_{k_2}$ . We also have the assumption that  $OPT_{k_1} = OPT_{k-r} \leq$  $\eta \cdot \text{OPT}_k$ , which implies  $\text{OPT}_k \leq 3\alpha\eta \cdot \text{OPT}_k + 3\beta \cdot \text{OPT}_{k_2}$ . Finally,

$$
\text{OPT}_k \le \left(\frac{3\beta}{1-3\alpha\eta}\right) \cdot \text{OPT}_{k_2} \le 4 \cdot \text{OPT}_{k_2} \le 4 \cdot \text{OPT}_{k+ \lfloor r/(12\eta) \rfloor}.
$$

The second inequality holds since

$$
\frac{3\beta}{1 - 3\alpha\eta} \le \frac{3}{1 - 3\alpha\eta} = \frac{3}{1 - 1/4} = 4.
$$

## <span id="page-26-0"></span>7.2 Proof of Lemma [4.2](#page-13-4)

Consider the standard LP relaxation for the weighted k-median problem as follows.

$$
\min \sum_{p \in \mathcal{P}} \sum_{u \in \mathcal{U}} d(u, p) \cdot x_{up}
$$
\n
$$
\text{s.t.} \quad x_{up} \le y_u
$$
\n
$$
\sum_{u \in \mathcal{U}} x_{up} \ge 1 \qquad \forall u \in \mathcal{U}, p \in \mathcal{P}
$$
\n
$$
\sum_{u \in \mathcal{U}} y_u \le k - (m - r)/4
$$
\n
$$
x_{up}, y_u \ge 0 \qquad \forall u \in \mathcal{U}, p \in \mathcal{P}
$$

We consider the set of potential centers to open is U, and we want to open at most  $k - (m - r)/4$ many centers. Since the integrality gap of this LP is known to be at most 3 [\[CS11\]](#page-74-10), it suffices to show the existence of a fractional solution whose cost is at most  $2\gamma \cdot (Cost(\mathcal{U}, \mathcal{P}) + Cost(\mathcal{V}, \mathcal{P}))$  and this solution opens at most  $k - (m - r)/4$  centers. Now, we explain how to construct a fractional solution for this LP.

**Fractional Opening of Centers.** Consider the projection  $\pi_{\mathcal{U}} : \mathcal{V} \to \mathcal{U}$  function. Assume  $U = U_I + U_F$  is a partition of U where  $U_I$  contains those centers  $u \in U$  satisfying at least one of the following conditions:

- u forms a well-separated pair with one center in  $\mathcal V$ .
- $\bullet$   $|\pi^{-1}_{\mathcal{U}}$  $\frac{1}{\mathcal{U}}(u) \geq 2.$

For every  $u \in \mathcal{U}_I$ , set  $y_u = 1$  and for every  $u \in \mathcal{U}_F$  set  $y_u = 1/2$ . Each center  $u \in \mathcal{U}$  that forms a well-separated pair with a center  $v \in V$  has  $|\pi_{\mathcal{U}}^{-1}|$  $\mathcal{U}^{-1}(u)$   $\geq 1$  since u must be the closest center to v in U. Since the number of well-separated pairs is  $k - m$ , we have

$$
k + r = |\mathcal{V}| = \sum_{u \in \mathcal{U}} |\pi_{\mathcal{U}}^{-1}(u)| \geq \sum_{u \in \mathcal{U}_I} |\pi_{\mathcal{U}}^{-1}(u)| \geq 1 \cdot (k - m) + 2 \cdot (|\mathcal{U}_I| - (k - m)).
$$

Hence,  $|\mathcal{U}_I| \le \frac{k+r+(k-m)}{2} = k - \frac{m-r}{2}$  $\frac{r-r}{2}$ . Finally, we conclude

$$
\sum_{u \in \mathcal{U}} y_u = \sum_{u \in \mathcal{U}_I} y_u + \sum_{u \in \mathcal{U}_F} y_u \le 1 \cdot \left( k - \frac{m - r}{2} \right) + \frac{1}{2} \cdot \frac{m - r}{2} = k - \frac{m - r}{4}.
$$

**Fractional Assignment of Points.** For every  $p \in \mathcal{P}$ , assume  $v_p = \pi_v(p)$  is the closest center to p in V and  $u_p = \pi_{\mathcal{U}}(v_p)$  is the closest center in U to  $v_p$ . We have three cases:

- If  $y_{u_p} = 1$ , then set  $x_{u_p} = 1$ . The cost of this assignment would be  $d(u_p, p)$ .
- If  $y_{u_p} = 1/2$  and there is a center  $u'_p \in \mathcal{U} u_p$  such that  $d(u_p, u'_p) \leq \gamma \cdot d(u_p, v_p)$ , then set  $x_{u_p p} = x_{u'_p p} = 1/2$ . Note that  $u'_p \neq u_p$  which means this solution is feasible to the LP. The cost of this assignment would be

$$
\frac{1}{2} \cdot (d(p, u_p) + d(p, u'_p)) \leq \frac{1}{2} \cdot (d(p, u_p) + d(p, u_p) + d(u'_p, u_p))
$$
  

$$
\leq d(p, u_p) + \frac{\gamma}{2} \cdot d(u_p, v_p).
$$

• If  $y_{u_p} = 1/2$  and the previous case does not hold, then since  $(u_p, v_p)$  is not a well-separated pair, there is a center  $v'_p \in V - v_p$  such that  $d(v_p, v'_p) \leq \gamma \cdot d(u_p, v_p)$ . Let  $u'_p = \pi_{\mathcal{U}}(v'_p)$  and set  $x_{u_p p} = x_{u'_p p} = 1/2$ . First, we show that  $u'_p \neq u_p$ . Since  $y_{u_p} = 1/2$ , we have  $u_p \in U_F$ which concludes  $|\pi_{\mathcal{U}}^{-1}|$  $\vert u^{-1}(u_p) \vert \leq 1$ . We also know that  $\pi_{\mathcal{U}}(v_p) = u_p$ . So,  $v_p$  is the only center in V mapped to  $u_p$  which implies  $\pi_{\mathcal{U}}(v'_p) \neq u_p$  or  $u'_p \neq u_p$  (note that  $v'_p \neq v_p$ ). So, point p is assigned one unit to centers. The cost of this assignment would be

$$
\frac{1}{2} \cdot (d(p, u_p) + d(p, u'_p)) \leq \frac{1}{2} \cdot (d(p, u_p) + d(p, u_p) + d(u_p, v'_p) + d(v'_p, u'_p))
$$
\n
$$
\leq \frac{1}{2} \cdot (d(p, u_p) + d(p, u_p) + d(u_p, v'_p) + d(v'_p, u_p))
$$
\n
$$
= d(p, u_p) + d(u_p, v'_p)
$$
\n
$$
\leq d(p, u_p) + d(u_p, v_p) + d(v_p, v'_p)
$$
\n
$$
\leq d(p, u_p) + (\gamma + 1) \cdot d(u_p, v_p).
$$

The second inequality is because of the choice of  $u'_p = \pi_{\mathcal{U}}(v'_p)$  and the last inequality is because  $d(v_p, v'_p) \leq \gamma \cdot d(u_p, v_p).$ 

**Bounding the Cost.** Assume  $u_p^* = \pi_{\mathcal{U}}(p)$  for each  $p \in \mathcal{P}$ . We have

$$
d(u_p, v_p) \le d(u_p^*, v_p) \le d(u_p^*, p) + d(p, v_p).
$$

The first inequality is by the choice of  $u_p = \pi_{\mathcal{U}}(v_p)$ . As a result,

<span id="page-28-0"></span>
$$
\sum_{p \in \mathcal{P}} d(u_p, v_p) \le \sum_{p \in \mathcal{P}} \left( d(u_p^*, p) + d(p, v_p) \right) = \text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P}). \tag{27}
$$

In each of the cases of fractional assignments of points to centers, the cost of assigning a point  $p \in C_v(\mathcal{V}, \mathcal{P})$  is at most  $d(p, u_p) + (\gamma + 1) \cdot d(u_p, v_p)$ . As a result, the total cost of this assignment is upper bounded by

$$
\sum_{p \in P} (d(p, u_p) + (\gamma + 1) \cdot d(u_p, v_p)) \leq \sum_{p \in P} (d(p, v_p) + (\gamma + 2) \cdot d(u_p, v_p))
$$
  
\n
$$
\leq \text{Cost}(\mathcal{V}, \mathcal{P}) + (\gamma + 2) \cdot (\text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P}))
$$
  
\n
$$
\leq 2\gamma \cdot (\text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P})).
$$

The second inequality follows by Equation [\(27\)](#page-28-0).

# <span id="page-29-0"></span>Part II Proofs That Follow From Prior Work

# <span id="page-29-2"></span><span id="page-29-1"></span>8 Missing Proofs From Section [3](#page-10-1)

## 8.1 Proof of Lemma [3.3](#page-12-0)

The lemma is obvious if AverageCost  $(p_j, B_j) \ge 10^j/5$ , because  $p_j = p_{j-1}$  which means  $d(p_{j-1}, p_j) =$ 0. Now, assume AverageCost  $(p_j, B_j)$  <  $10^j/5$ . By the definition of a t-robust sequence, we know Cost  $(p_{j-1}, B_j) \leq$  Cost  $(p_j, B_j)$ . Hence,

$$
d(p_j, p_{j-1}) = \frac{1}{|B_j|} \cdot \sum_{p \in B_j} d(p_j, p_{j-1}) \le \frac{1}{|B_j|} \cdot \sum_{p \in B_j} (d(p_j, p) + d(p_{j-1}, p))
$$
  
= AverageCost  $(p_j, B_j)$  + AverageCost  $(p_{j-1}, B_j)$   
 $\le 2 \cdot AverageCost (p_j, B_j) \le \frac{2}{5} \cdot 10^j$ .

For every  $p \in B_{j-1}$  we have  $d(p, p_j) \leq d(p, p_{j-1}) + d(p_{j-1}, p_j) \leq 10^{j-1} + \frac{2}{5} \cdot 10^j \leq 10^j$ , which implies  $B_{j-1} \subseteq B_j$ . Finally,

$$
d(p_0, p_j) \le \sum_{i=1}^j d(p_{i-1}, p_i) \le \frac{2}{5} \cdot \sum_{i=1}^j 10^i = \frac{2}{5} \cdot \frac{10^{j+1} - 2}{9} \le 10^j / 2.
$$

## <span id="page-29-3"></span>8.2 Proof of Lemma [3.4](#page-12-1)

Since  $(p_0, p_1, \ldots, p_t)$  is t-robust, for every  $1 \leq j \leq t$ , we know

<span id="page-29-4"></span>
$$
Cost(p_j, B_j) \ge Cost(p_{j-1}, B_j).
$$
\n(28)

Assume  $q \in \mathcal{P} \setminus B_j$ . Then, by Lemma [3.3,](#page-12-0)  $d(q, p_j) \geq 10^j \geq 2 \cdot d(p_0, p_j)$ . Hence,

$$
\frac{3}{2} \cdot d(q, p_j) = d(q, p_j) + \frac{1}{2} \cdot d(q, p_j) \ge d(q, p_j) + d(p_0, p_j) \ge d(q, p_0),
$$

which means

<span id="page-29-5"></span>
$$
d(q, p_j) \ge \frac{2}{3} \cdot d(q, p_0). \tag{29}
$$

Finally, Since  $B_1 \subseteq \cdots \subseteq B_i \subseteq S$  (by Lemma [3.3\)](#page-12-0) we can apply Equation [\(28\)](#page-29-4) and Equation [\(29\)](#page-29-5) repeatedly to get

Cost 
$$
(p_i, S)
$$
 = Cost  $(p_i, B_i)$  + Cost  $(p_i, S \setminus B_i)$   $\ge$  Cost  $(p_{i-1}, B_i)$  +  $\frac{2}{3}$  · Cost  $(p_0, S \setminus B_i)$   
\n= Cost  $(p_{i-1}, B_{i-1})$  + Cost  $(p_{i-1}, B_i \setminus B_{i-1})$  +  $\frac{2}{3}$  · Cost  $(p_0, S \setminus B_i)$   
\n $\ge$  Cost  $(p_{i-2}, B_{i-1})$  +  $\frac{2}{3}$  Cost  $(p_0, B_i \setminus B_{i-1})$  +  $\frac{2}{3}$  · Cost  $(p_0, S \setminus B_i)$   
\n= Cost  $(p_{i-2}, B_{i-1})$  +  $\frac{2}{3}$  · Cost  $(p_0, S \setminus B_{i-1})$   
\n:  
\n $\ge$  Cost  $(p_0, B_1)$  +  $\frac{2}{3}$  · Cost  $(p_0, S \setminus B_1)$   $\ge$   $\frac{2}{3}$  · Cost  $(p_0, S)$ .

#### <span id="page-30-0"></span>8.3 Proof of Lemma [3.6](#page-12-2)

Assume a MAKE-ROBUST call to a center  $w \in \mathcal{W}$  is made and it is replaced by  $w_0$ . Let  $\mathcal{W}_1$  be the set of centers just before this call to MAKE-ROBUST is made on  $w$ . At this point of time,  $t[w_0]$  is the smallest integer satisfying  $10^{t[w_0]} \geq d(w, \mathcal{W}_1 - w)/100$  (note that  $t[w_0] \geq 0$ , otherwise the algorithm should not have called MAKE-ROBUST duo to line 10 in the ROBUSTIFY). For the sake of contradiction, assume that another call to MAKE-ROBUST is made on  $w_0$ . We assume that this pair w, w<sub>0</sub> is the first pair for which this occurs. Let  $w' = \pi_{\mathcal{W}_1-w}(w)$  which means  $d(w, W_1 - w) = d(w, w')$ . Then,  $10^{t[w_0]} \ge d(w, w')/100$  and  $10^{t[w_0]} < d(w, w')/10$  by definition of  $t[w_0]$ . So, by Lemma [10.3,](#page-37-0) we have

<span id="page-30-2"></span>
$$
d(w_0, w) \le 10^{t[w_0]}/2 \le d(w, w')/20.
$$
\n(30)

Assume  $\mathcal{W}_2$  is the set of centers just after the call to MAKE-ROBUST is made on  $w_0$ . Since we assumed  $w, w_0$  is the first pair that another call to MAKE-ROBUST on  $w_0$  is made, we have one of the two following cases.

•  $w' \in \mathcal{W}_2$ . In this case, we have

$$
d(w_0, \mathcal{W}_2 - w_0) \le d(w_0, w') \le d(w_0, w) + d(w, w') \le \frac{21}{20} \cdot d(w, w') \le 2 \cdot d(w, w').
$$

The last inequality holds by Equation [\(30\)](#page-30-2). This is in contradiction with the assumption that a call to MAKE-ROBUST on  $w_0$  is made, because  $w_0$  is  $t[w_0]$ -robust where  $10^{t[w_0]} \ge$  $d(w, w')/100 \geq d(w_0, \mathcal{W}_2 - w_0)/200$ . So, w<sub>0</sub> must not be selected to be added to S in ROBUSTIFY.

• There is  $w'_0 \in W_2$  that replaced w' by a single call to MAKE-ROBUST. When MAKE-ROBUST is called on w', the algorithm picks integer  $t[w'_0]$  that satisfies  $10^{t[w'_0]} \leq d(w', w_0)/10$  (otherwise, it should have picked  $t[w'_0] - 1$  instead of  $t[w'_0]$ ). Hence,

<span id="page-30-3"></span>
$$
d(w'_0, w') \le 10^{t[w'_0]}/2 \le d(w', w_0)/20 \le (d(w_0, w) + d(w, w'))/20 \le d(w, w')/10.
$$
 (31)

The first inequality holds by Lemma [10.3](#page-37-0) and the last inequality is Equation [\(30\)](#page-30-2). As a result,

$$
d(w_0, \mathcal{W}_2 - w_0) \le d(w_0, w'_0) \le d(w_0, w) + d(w, w') + d(w', w'_0)
$$
  
\n
$$
\le d(w, w')/20 + d(w, w') + d(w, w')/10
$$
  
\n
$$
= \frac{23}{20} \cdot d(w, w') \le 2 \cdot d(w, w').
$$

The last inequality holds by Equation [\(30\)](#page-30-2) and Equation [\(31\)](#page-30-3). This leads to the same contradiction.

### <span id="page-30-1"></span>8.4 Proof of Lemma [3.7](#page-12-3)

By Lemma [3.6,](#page-12-2) ROBUSTIFY calls MAKE-ROBUST on each center at most once. Let  $r$  be the number of centers in W for which a call to MAKE-ROBUST has happened. Assume  $W = \{w_1, \ldots, w_k\}$  is an ordering by the time that MAKE-ROBUST is called on the centers  $w_1, w_2, \ldots, w_r$  and the last elements are ordered arbitrarily. Assume also that  $\mathcal{U} = \{w'_1, \ldots, w'_k\}$  where  $w'_i$  is obtained by the call MAKE-ROBUST on  $w_i$  for each  $1 \leq i \leq r$  and  $w'_i = w_i$  for each  $r + 1 \leq i \leq k$ . For every  $1 \leq j \leq r$ , integer  $t[w'_j]$  is the smallest integer satisfying

$$
10^{t[w'_j]} \ge d(w_j, \{w'_1, \ldots, w'_{j-1}, w_{j+1}, \ldots, w_k\})/100.
$$

Hence,

<span id="page-31-1"></span>
$$
10^{t[w'_j]} \le d(w_j, w'_i)/10 \quad \forall i < j \tag{32}
$$

and

<span id="page-31-2"></span>
$$
10^{t[w'_j]} \le d(w_j, w_i)/10 \quad \forall i > j.
$$
\n(33)

Now, for every  $1 \leq i < j \leq r$ , we conclude

$$
10 \cdot 10^{t[w'_j]} \le d(w'_i, w_j) \le d(w_i, w_j) + d(w_i, w'_i) \le d(w_i, w_j) + 10^{t[w'_i]} / 2 \le \frac{11}{10} \cdot d(w_i, w_j).
$$

The first inequality holds by Equation [\(32\)](#page-31-1), the third one holds by Lemma [3.3](#page-12-0) (note that  $w_i' =$ MAKE-ROBUST $(w_i)$ ) and the last one holds by Equation [\(33\)](#page-31-2) (by exchanging i and j in this equation since  $i < j$ ). This concludes for each  $i < j$ , we have  $d(w_i, w_j) > 2 \cdot 10^{t[w'_j]}$ . The same inequality holds for each  $i > j$  by Equation [\(33\)](#page-31-2). As a result,  $d(w_i, w_j) > 2 \cdot 10^{t[w'_j]}$  for all  $i \neq j$ . This concludes

$$
\text{Ball}^{\mathcal{P}}_{10^{t[w'_j]}}(w_j) \subseteq C_{w_j}(\mathcal{W}, \mathcal{P}),
$$

for every  $1 \leq j \leq r$ . Then, we can apply Lemma [3.4,](#page-12-1) we have

<span id="page-31-3"></span>
$$
\mathsf{Cost}\left(w'_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \le \frac{3}{2} \cdot \mathsf{Cost}\left(w_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \quad \forall 1 \le j \le r. \tag{34}
$$

Finally, since  $C_{w_j}(\mathcal{W}, \mathcal{P})$  for  $1 \leq j \leq k$  form a partition of  $\mathcal{P}$ , we conclude

$$
\begin{array}{lcl} \mathsf{Cost}\left(\mathcal{U}, \mathcal{P}\right) & = & \displaystyle \sum_{j=1}^k \mathsf{Cost}\left(\mathcal{U}, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \leq \sum_{j=1}^k \mathsf{Cost}\left(w_j', C_{w_j}(\mathcal{W}, \mathcal{P})\right) \\ \\ & = & \displaystyle \sum_{j=1}^r \mathsf{Cost}\left(w_j', C_{w_j}(\mathcal{W}, \mathcal{P})\right) + \sum_{j=r+1}^k \mathsf{Cost}\left(w_j', C_{w_j}(\mathcal{W}, \mathcal{P})\right) \\ \\ & \leq & \displaystyle \frac{3}{2} \cdot \sum_{j=1}^r \mathsf{Cost}\left(w_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) + \sum_{j=r+1}^k \mathsf{Cost}\left(w_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \\ \\ & \leq & \displaystyle \frac{3}{2} \cdot \sum_{j=1}^k \mathsf{Cost}\left(w_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) = \frac{3}{2} \cdot \mathsf{Cost}\left(\mathcal{W}, \mathcal{P}\right). \end{array}
$$

The second inequality holds by Equation [\(34\)](#page-31-3).

### <span id="page-31-0"></span>8.5 Proof of Lemma [3.9](#page-13-5)

Since, the point-set P is fixed, denote  $C_v(\mathcal{V}, \mathcal{P})$  by  $C_v$  for simplicity. If  $d(u, v) = 0$ , the statement is trivial. Now assume  $d(u, v) \geq 1$ . Since U is robust, then u is t-robust where t is the smallest integer such that  $10^t \geq d(u, U - u)/200 \geq (\gamma/200) \cdot d(u, v) = 20 \cdot d(u, v)$ . The second inequality is because  $(u, v)$  is well-separated pair and the equality is because  $\gamma = 4000$ . Assume  $t^*$  is the integer satisfying

<span id="page-31-4"></span>
$$
20 \cdot d(u, v) \le 10^{t^*} < 10 \cdot 20 \cdot d(u, v). \tag{35}
$$

<span id="page-31-5"></span>Note that  $t^* \geq 1$ . Since  $t^* \leq t$  and u is t-robust, then it is also  $t^*$ -robust which means there is a t<sup>\*</sup>-robust sequence  $(p_0, p_1, \ldots, p_{t^*})$  such that  $p_0 = u$ . For Simplicity, assume  $B_i = \text{Ball}_{10^i}^{\mathcal{P}}(p_i)$  for  $0 \leq i \leq t^*$ .

**Claim 8.1.** For each  $0 \le i \le t^*$ , we have  $B_i \subseteq C_v$ .

*Proof.* Assume  $q \in B_i$ . Then,

$$
d(q, v) \leq d(q, p_i) + d(p_i, u) + d(u, v) = d(q, p_i) + d(p_i, p_0) + d(u, v)
$$
  
 
$$
\leq 10^i + 10^i/2 + 10^{i*}/20 \leq 2 \cdot 10^{i*}.
$$

For the second inequality, we used  $q \in B_i$ , Lemma [3.3](#page-12-0) and Equation [\(35\)](#page-31-4). Now, for every  $v' \in V - v$ we have  $d(v, v') \geq d(v, v - v) \geq 4 \cdot 10^3 \cdot d(u, v) > 10^{t^*+1} \geq 2 \cdot d(q, v)$ . The second inequality is by  $(u, v)$  being well-separated (and  $\gamma = 4000$ ), the third one is by Equation [\(35\)](#page-31-4). This concludes  $d(q, v') \geq d(v, v') - d(q, v) > d(q, v)$  which means v is the closest center to q in V. So,  $q \in B_i$  and finally  $B_i \subseteq C_v$ . □

Now, according to the definition of t-robust sequence we have two cases. **Case 1:** AverageCost  $(p_{t^*}, B_{t^*}) \ge 10^{t^*}/5$ . In this case, we have  $p_{t^*-1} = p_{t^*}$  and

$$
d(v, p_{t^*}) = d(v, p_{t^*-1}) \le d(v, p_0) + d(p_0, p_{t^*-1}) = d(v, u) + d(p_0, p_{t^*-1})
$$
  
 
$$
\le 10^{t^*}/20 + 10^{t^*-1}/2 = 10^{t^*}/10.
$$

The second inequality holds by Lemma [3.3](#page-12-0) and Equation [\(35\)](#page-31-4). So,

<span id="page-32-0"></span>
$$
d(v, p_{t^*}) \le 10^{t^*} / 10. \tag{36}
$$

For every  $q \in C_v - B_{t^*}$ , we have  $d(q, v) \geq d(p_{t^*}, q) - d(v, p_{t^*}) \geq 10^{t^*} - d(v, p_{t^*}) \geq d(v, p_{t^*})$ . The second inequality follows by  $q \in C_v - B_{t^*}$  and the last inequality follows by Equation [\(36\)](#page-32-0). So,  $d(q, v) \ge (d(q, v) + d(v, p_{t^*}))/2 \ge d(q, p_{t^*})/2$ , which implies

<span id="page-32-2"></span>Cost 
$$
(v, C_v - B_{t^*}) \ge \frac{\text{Cost}(p_{t^*}, C_v - B_{t^*})}{2}
$$
. (37)

We also have

<span id="page-32-1"></span>
$$
\text{AverageCost}(p_{t^*}, B_{t^*}) \ge 10^{t^*} / 5 \ge 2 \cdot d(v, p_{t^*}),\tag{38}
$$

by the assumption of this case and Equation [\(36\)](#page-32-0). Now, we conclude

Cost 
$$
(v, C_v)
$$
 = Cost  $(v, B_{t^*})$  + Cost  $(v, C_v - B_{t^*})$   
\n=  $|B_{t^*}|$  · AverageCost  $(v, B_{t^*})$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq |B_{t^*}|$  · (AverageCost  $(p_{t^*}, B_{t^*}) - d(v, p_{t^*}))$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq |B_{t^*}|$  ·  $\frac{\text{AverageCost}(p_{t^*}, B_{t^*})}{2}$  + Cost  $(v, C_v - B_{t^*})$   
\n $= \frac{\text{Cost}(p_{t^*}, B_{t^*})}{2}$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq \frac{\text{Cost}(p_{t^*}, B_{t^*})}{2}$  +  $\frac{\text{Cost}(p_{t^*}, C_v - B_{t^*})}{2}$  =  $\frac{\text{Cost}(p_{t^*}, C_v)}{2}$ .

The first inequality is triangle inequality, the second inequality holds by Equation [\(38\)](#page-32-1) and the last inequality holds by Equation [\(37\)](#page-32-2). Finally, since  $B_{t^*} \subseteq C_v$  (by Claim [8.1\)](#page-31-5), we can apply Lemma [3.4](#page-12-1) to get

$$
\mathsf{Cost}\left(u,C_v\right) = \mathsf{Cost}\left(p_0,C_v\right) \leq \frac{3}{2} \cdot \mathsf{Cost}\left(p_{t^*},C_v\right) \leq \frac{3}{2} \cdot 2 \cdot \mathsf{Cost}\left(v,C_v\right) = 3 \cdot \mathsf{Cost}\left(v,C_v\right).
$$

**Case 2:** AverageCost  $(p_{t^*}, B_{t^*}) < 10^{t^*}/5$ . In this case, for every  $q \in C_v - B_{t^*}$ ,

$$
d(q, p_{t^*-1}) \ge d(q, p_{t^*}) - d(p_{t^*}, p_{t^*-1}) \ge 10^{t^*} - 10^{t^*}/2 = 10^{t^*}/2.
$$

The second inequality holds by  $q \in C_v - B_{t^*}$  and Lemma [3.3.](#page-12-0) So,

<span id="page-33-1"></span>
$$
d(q, p_{t^*-1}) \ge 10^{t^*}/2. \tag{39}
$$

We also have

$$
d(v, p_{t^*-1}) \le d(v, u) + d(u, p_{t^*-1}) = d(v, u) + d(p_0, p_{t^*-1}) \le 10^{t^*} / 20 + 10^{t^*-1} / 2 = 10^{t^*} / 10.
$$

The second inequality holds by Equation [\(35\)](#page-31-4) and Lemma [3.3.](#page-12-0) So,

<span id="page-33-2"></span>
$$
d(v, p_{t^*-1}) \le 10^{t^*} / 10. \tag{40}
$$

Combining Equation [\(39\)](#page-33-1) and Equation [\(40\)](#page-33-2), we have

$$
d(v, p_{t^*-1}) \le 10^{t^*}/10 = \frac{1}{5} \cdot 10^{t^*}/2 \le \frac{1}{5} \cdot d(q, p_{t^*-1}),
$$

which concludes

$$
\frac{d(q, p_{t^*-1})}{d(q, v)} \le \frac{d(q, p_{t^*-1})}{d(q, p_{t^*-1}) - d(p_{t^*-1}, v)} \le \frac{d(q, p_{t^*-1})}{d(q, p_{t^*-1}) - \frac{1}{5} \cdot d(q, p_{t^*-1})} = 5/4 \le 2.
$$

So, we have  $d(q, p_{t^*-1}) \leq 2 \cdot d(q, v)$ . Using this inequality for all  $q \in C_v - B_{t^*}$ , we conclude

<span id="page-33-3"></span>Cost 
$$
(p_{t^*-1}, C_v - B_{t^*}) \le 2 \cdot \text{Cost}(v, C_v - B_{t^*})
$$
. (41)

We also have

<span id="page-33-4"></span>Cost 
$$
(p_{t^*-1}, B_{t^*}) = \text{OPT}_1^{B_{t^*} + p_{t^*}}(B_{t^*}) \le 2 \cdot \text{OPT}_1(B_{t^*}) \le 2 \cdot \text{Cost}(v, B_{t^*}).
$$
 (42)

The equality holds by the definition of  $p_{t^*-1}$  in a t<sup>\*</sup>-robust sequence, the first inequality holds by Lemma [3.10](#page-13-6) and  $\text{Cost}(B_{t^*} + p_{t^*}, B_{t^*}) = 0$  (we need this argument since we do not know if v is inside the current space  $P$ ). Hence,

$$
\begin{array}{rcl}\n\text{Cost}(p_{t^*-1}, C_v) & = & \text{Cost}(p_{t^*-1}, B_{t^*}) + \text{Cost}(p_{t^*-1}, C_v - B_{t^*}) \\
& \leq & 2 \cdot \text{Cost}(v, B_{t^*}) + 2 \cdot \text{Cost}(v, C_v - B_{t^*}) = 2 \cdot \text{Cost}(v, C_v)\,. \n\end{array}
$$

The equality holds since  $B_{t^*} \subseteq C_v$  (by Claim [8.1\)](#page-31-5) and the first inequality holds by Equation [\(41\)](#page-33-3) and Equation [\(42\)](#page-33-4). Finally, applying Lemma [3.4](#page-12-1) implies

Cost 
$$
(u, C_v)
$$
 = Cost  $(p_0, C_v) \leq \frac{3}{2} \cdot \text{Cost}(p_{t^*-1}, C_v) \leq \frac{3}{2} \cdot 2 \cdot \text{Cost}(v, C_v) = 3 \cdot \text{Cost}(u, C_v)$ .

In both cases, we showed that  $\text{Cost}(u, C_v) \leq 3 \cdot \text{Cost}(v, C_v)$  which completes the proof.

### <span id="page-33-0"></span>8.6 Proof of Lemma [3.10](#page-13-6)

Let  $\mathcal{V}^* \subseteq \mathbf{P}$  be of size k such that  $\text{Cost}(\mathcal{V}^*, \mathcal{P}) = \text{OPT}_k(\mathcal{P})$ . Assume  $\mathcal{V} = \pi_{\mathcal{U}}(\mathcal{V}^*)$ . Obviously  $\mathcal{V}$  is of size at most k and  $\text{OPT}_k^{\mathcal{U}}(\mathcal{P}) \leq \text{Cost}(\mathcal{V}, \mathcal{P})$ . For each  $p \in \mathcal{P}$ , let  $v_p^*$  and  $u_p$  be the projection of p onto  $\mathcal{V}^*$  and  $\mathcal{U}$  respectively. Also assume  $v_p = \pi_{\mathcal{U}}(v_p^*)$ . Hence,  $d(p, v_p) \leq d(p, v_p^*) + d(v_p^*, v_p) \leq$  $d(p, v_p^{\star}) + d(v_p^{\star}, u_p) \leq d(p, v_p^{\star}) + d(v_p^{\star}, p) + d(p, u_p) = d(p, \mathcal{U}) + 2 \cdot d(p, \mathcal{V}^{\star})$ . Now, assign each p to  $v_p$ in solution  $V$ , which concludes

Cost 
$$
(V, \mathcal{P}) \leq \sum_{p \in \mathcal{P}} d(p, V) \leq \sum_{p \in \mathcal{P}} (d(p, \mathcal{U}) + 2 \cdot d(p, V^*)) = \text{Cost}(\mathcal{U}, \mathcal{P}) + 2 \cdot \text{Cost}(V^*, \mathcal{P}).
$$

Hence,  $\mathrm{OPT}^{\mathcal{U}}_k(\mathcal{P}) \leq \mathsf{Cost}\,(\mathcal{V},\mathcal{P}) \leq \mathsf{Cost}\,(\mathcal{U},\mathcal{P}) + 2 \cdot \mathrm{OPT}_k(\mathcal{P}).$ 

#### <span id="page-34-0"></span>8.7 Proof of Lemma [3.11](#page-13-7)

Assume  $\mathcal{U} \subseteq \mathbf{P}$  of size at most k is such that  $\text{Cost}(\mathcal{U}, \mathcal{P}) = \text{OPT}_k(\mathcal{P})$ . Define  $\mathcal{U}' = \mathcal{U} + (\mathcal{P} \oplus \mathcal{P}')$ . Obviously,  $\mathcal{U}'$  is a feasible solution for the  $(k + s)$ -median problem on  $\mathcal{P}'$  and since  $\mathcal{U}'$  contains  $P \oplus P'$ , we conclude

$$
\text{OPT}_{k+s}(\mathcal{P}')\leq \text{Cost}\left(\mathcal{U}',\mathcal{P}'\right)=\text{Cost}\left(\mathcal{U}+(\mathcal{P}\oplus \mathcal{P}'),\mathcal{P}'\right)\leq \text{Cost}\left(\mathcal{U},\mathcal{P}\right)=\text{OPT}_k(\mathcal{P}).
$$

## <span id="page-34-1"></span>9 Proof of Lemma [2.3](#page-7-1)

Assume the number of well-separated pairs w.r.t.  $(\mathcal{U}_{init}, \mathcal{V})$  is  $k - m$  for some  $m \in [0, k]$ . We call a  $u \in \mathcal{U}_{\text{init}}$  good if

- u forms a well-separated pair with a  $v \in \mathcal{V}$ ; and
- $v$  is not the closest center to any inserted point in the epoch, i.e., all of the points assigned to v in  $\mathcal{P}_{\text{final}}$  (denoted by  $C_v(\mathcal{V}, \mathcal{P}_{\text{final}})$ ) are in  $\mathcal{P}_{\text{init}}$ .

Assume we have g many good centers in  $\mathcal{U}_{\text{init}}$  and consider orderings  $\mathcal{U}_{\text{init}} = \{u_1, u_2, \dots, u_k\}$  and  $\mathcal{V} = \{v_1, v_2, \dots, v_k\}$ , such that for all  $i \in [1, g]$ , the center  $u_i$  is good and  $v_i$  is such that  $(u_i, v_i)$  is a well-separated pair. Since  $|\mathcal{P}_{\text{final}} \oplus \mathcal{P}_{\text{init}}| \leq \ell + 1$ , there are at most  $\ell + 1$  many centers v such that  $C_v(\mathcal{V}, \mathcal{P}_{\text{final}}) \nsubseteq \mathcal{P}_{\text{init}}$ . So, we have at most  $m + \ell + 1$  centers in  $\mathcal{U}_{\text{init}}$  that are not good.

Now, assume  $\mathcal{W}^* = \{u_1, \ldots, u_q, v_{q+1}, \ldots, v_k\}$  is derived by swapping at most  $k - g \leq m + \ell + 1$ many centers in  $U_{\text{init}}$ . According to Lemma [3.9](#page-13-5) for  $P = P_{\text{init}}$  and  $U = U_{\text{init}}$ , we have

$$
Cost(\mathcal{W}^*, \mathcal{P}_{\text{final}}) \leq \sum_{i=1}^{g} Cost(u_i, C_v(\mathcal{V}, \mathcal{P}_{\text{final}})) + \sum_{i=g+1}^{k} Cost(v_i, C_v(\mathcal{V}, \mathcal{P}_{\text{final}}))
$$
  

$$
\leq \sum_{i=1}^{g} 3 \cdot Cost(v_i, C_v(\mathcal{V}, \mathcal{P}_{\text{final}})) + \sum_{i=g+1}^{k} Cost(v_i, C_v(\mathcal{V}, \mathcal{P}_{\text{final}}))
$$
  

$$
\leq 3 \cdot Cost(\mathcal{V}, \mathcal{P}_{\text{final}})
$$

As a result, there exist a set of k centers  $W^*$  such that  $Cost(W^*, \mathcal{P}_{final}) \leq 3 \cdot Cost(V, \mathcal{P}_{final})$  and  $|W^{\star}\oplus\mathcal{U}_{\text{init}}| \leq m+\ell+1$ . In order to complete the proof of lemma, it suffices to show  $m \leq 4\cdot(\ell+1)$ .

According to Lemma [4.2](#page-13-4) for  $P = P_{\text{init}}$ ,  $U = U_{\text{init}}$  and  $r = 0$ , there exist a  $\tilde{U} \subseteq U_{\text{init}}$  of size at most  $k - \lfloor m/4 \rfloor$  such that  $\mathsf{Cost}\left(\tilde{\mathcal{U}}, \mathcal{P}_{\mathtt{init}}\right) \leq 6\gamma \cdot (\mathsf{Cost}\left(\mathcal{U}_{\mathtt{init}}, \mathcal{P}_{\mathtt{init}}) + \mathsf{Cost}\left(\mathcal{V}, \mathcal{P}_{\mathtt{init}}\right)).$  By hypothesis we have  $Cost(V, \mathcal{P}_{init}) \leq 18$ . Cost  $(\mathcal{U}_{init}, \mathcal{P}_{init})$ . Hence,

$$
\begin{array}{lcl} \textsf{Cost}\left(\mathcal{U}', \mathcal{P}_{\textsf{init}}\right) & \leq & 6\gamma \cdot \left(\textsf{Cost}\left(\mathcal{U}_{\textsf{init}}, \mathcal{P}_{\textsf{init}}\right) + \textsf{Cost}\left(\mathcal{V}, \mathcal{P}_{\textsf{init}}\right)\right) \\ & \leq & 6\gamma \cdot \left(1 + 18\right) \cdot \textsf{Cost}\left(\mathcal{U}_{\textsf{init}}, \mathcal{P}_{\textsf{init}}\right) \\ & = & 456000 \cdot \textsf{Cost}\left(\mathcal{U}_{\textsf{init}}, \mathcal{P}_{\textsf{init}}\right). \end{array}
$$

Finally, since we assumed that  $\mathcal{U}_{\text{init}}$  is maximally lestable, we conclude that  $|m/4| \leq \ell$  which shows  $m \leq 4 \cdot (\ell + 1)$ .

# <span id="page-35-0"></span>Part III Full Version

# <span id="page-35-2"></span><span id="page-35-1"></span>10 Preliminaries

## 10.1 Problem Setting

Assume we have a ground metric space P with distance function d together with a subset  $\mathcal{P} \subseteq \mathbf{P}$ which contains the current present weighted points. In the k-median problem on  $P$ , we want to find  $\mathcal{U} \subseteq \mathcal{P}$  of size k (called centers) so as to minimize the objective function  $\sum_{p \in \mathcal{P}} w(p) \cdot d(p, \mathcal{U}),$ where  $w(p) > 0$  is the weight of p and  $d(p, U) = \min_{q \in \mathcal{U}} d(p,q)$  is the distance of p to U. In the dynamic setting, the current space  $\mathcal P$  is changing. Each update is either deleting a point of  $\mathcal P$ , or inserting a points of  $\mathbf{P} - \mathcal{P}$  into  $\mathcal{P}$  and assign a weight to it. The aim is to maintain a set  $\mathcal{U} \subseteq \mathcal{P}$ of k centers that is a good approximation of the optimum k-median in the current space  $\mathcal{P}$  at each point in time.

We consider the **improper** dynamic k-median problem, which means even if a point is not present in  $P$ , we can pick it as a center in our main solution (i.e. open it as a center). In order to have an algorithm for the **proper** k-median problem that opens centers only present in the current set of points  $P$  at any time, we use the following result of [\[BCG](#page-74-0)<sup>+</sup>24].

**Lemma 10.1** (Lemma 9.1 in  $[BCG+24]$ ). Given any fully dynamic  $(k, p)$ -clustering algorithm that maintains an  $\alpha$ -approximate improper solution, we can maintain a 2 $\alpha$ -approximate proper solution while incurring a  $O(1)$  factor in the recourse and an additive  $O(n)$  factor in the update time.

In  $[BCG^+24]$ , the authors achieved this result by providing a projection scheme that for every set of improper centers  $U$  returns a proper subset of current set of points. We refer the reader to Section 9 of  $[BCG^+24]$  to see the complete procedure.

## <span id="page-35-3"></span>10.2 Notations

By a simple scaling, we can assume that all of the distances in the metric space are between 1 and a parameter  $\Delta$ . We use **P** for the points of the ground metric space and  $\mathcal P$  for the set of current present points. For simplicity, for each set S and element p, we denote  $S \cup \{p\}$  and  $S \setminus \{p\}$  by  $S + p$ and  $S - p$  respectively. Each  $p \in \mathcal{P}$  has a weight denoted by  $w(p)$  and for every  $S \subseteq \mathcal{P}$ , we define

$$
w(S) := \sum_{p \in S} w(p).
$$

For two point sets P and  $\mathcal{P}'$ , we use  $\mathcal{P} \oplus \mathcal{P}'$  for their symmetric difference. Note that if a point p is present in both P and P', but its weight is different in these two sets, we also consider  $p \in \mathcal{P} \oplus \mathcal{P}'$ . We assume the same for  $\mathcal{P} - \mathcal{P}'$ . For each  $S \subseteq \mathbf{P}$ , we define  $\pi_S : \mathbf{P} \to S$  to be the projection function onto S. For each  $p \in \mathbf{P}$  and  $S \subseteq \mathbf{P}$ , we define  $d(p, S) := d(p, \pi_S(p))$ . For each  $\mathcal{U} \subseteq \mathbf{P}$  and  $S \subseteq \mathcal{P}$ , we use

$$
\mathsf{Cost}\,(\mathcal{U}, S) := \sum_{p \in S} w(p) \, d(p, \mathcal{U}).
$$

We also define

$$
\mathsf{AverageCost}\left(\mathcal{U}, S\right) := \frac{\mathsf{Cost}\left(\mathcal{U}, S\right)}{w(S)}.
$$
Assume  $\mathcal{P}, \mathcal{C} \subseteq \mathbf{P}$ . For any integer  $m \geq 0$ , we denote the cost of the optimum m-median solution for  $P$  where we can only open centers from  $C$ , by  $\mathrm{OPT}_{m}^{\mathcal{C}}(\mathcal{P})$ , i.e.

$$
\text{OPT}^{\mathcal{C}}_m(\mathcal{P}) = \min_{\substack{\mathcal{U} \subseteq \mathcal{C}, \\ |\mathcal{U}| \leq m}} \text{Cost}(\mathcal{U}, \mathcal{P}).
$$

Whenever we do not use the superscript  $\mathcal{C}$ , we consider  $\mathcal{C}$  is the underlying ground metric space  $\mathbf{P}$ , i.e.

$$
\text{OPT}_m(\mathcal{P}) = \min_{\substack{\mathcal{U} \subseteq \mathbf{P}, \\ |\mathcal{U}| \leq m}} \text{Cost}(\mathcal{U}, \mathcal{P}) .
$$

Note that  $U$  is a subset of the ground set **P**, but its cost is computed w.r.t.  $P$ .

For each  $\mathcal{U} \subseteq \mathbf{P}$  and  $u \in \mathcal{U}$ , we define

$$
C_u(\mathcal{U}, \mathcal{P}) := \{ p \in \mathcal{P} \mid \pi_{\mathcal{U}}(p) = u \}
$$

to be the points of  $P$  assigned to the center u in the solution  $U$  (breaking ties arbitrarily). For each point  $p \in \mathbf{P}$  and value  $r \geq 0$ , we define  $\text{Ball}_r^{\mathcal{P}}(p)$  to be the points in  $\mathcal{P}$  whose distances from p are at most  $r$ , i.e.

$$
\text{Ball}_r^{\mathcal{P}}(p) := \{ q \in \mathcal{P} \mid d(p, q) \le r \}.
$$

Note that p itself might not be in  $\text{Ball}_r^{\mathcal{P}}(p)$  since we only consider points of  $\mathcal{P}$  in this ball.

### <span id="page-36-1"></span>10.2.1 Constant Parameters

Throughout the paper we use constant parameters  $\beta, \gamma$  and C for convenience.  $\beta = O(1)$  is the constant approximation of the algorithm for static k-median on  $\mathcal P$  in [\[MP02\]](#page-75-0) that runs in  $O(|\mathcal P| \cdot k)$ time. The final values of  $\gamma$  and C are as follows.

$$
\gamma = 4000, \text{ and } C = 12 \cdot 3 \cdot 10^5 \gamma \beta^2
$$

### 10.3 Robustness

In this section we describe the notion of robustness. This notion is first defined in [\[FLNS21\]](#page-75-1). We change the definition in order to be able to get linear update time while the main good properties derived from the previous definition remain correct up to a constant overhead in approximation parts.

**Definition 10.2** (*t*-robust sequence). Assume  $(p_0, p_1, \ldots, p_t)$  is a sequence of  $t + 1$  points. Let  $\mathcal{P} \subseteq \mathbf{P}$  and  $B_i=Ball_{10^i}^{\mathcal{P}}(p_i)$  for each  $0 \leq i \leq t$ . We call this sequence, t-robust w.r.t.  $\mathcal{P}$  if for every  $1 \leq i \leq t$ ,

$$
p_{i-1} = \begin{cases} p_i & \text{if AverageCost } (p_i, B_i) \ge 10^i / 5 \\ q_i & \text{Otherwise} \end{cases}
$$

where  $q_i \in B_i + p_i$  must satisfy

$$
\mathsf{Cost}\left(q_i,B_i\right) \leq \min\{3\; \text{OPT}_1(B_i), \mathsf{Cost}\left(p_i,B_i\right)\}^{.14}
$$

<span id="page-36-0"></span><sup>&</sup>lt;sup>14</sup> $q_i$  might be equal to  $p_i$  itself.

Note that in this definition, points  $p_i$  need not necessarily be inside  $P$ . But, the balls  $B_i =$  $\text{Ball}_{10^i}^{\mathcal{P}}(p_i)$  are considered as a subset of current  $\mathcal{P}$ . Also note that  $q_i$  is picked from  $B_i + p_i$ , but its cost is compared to the optimum improper solution for 1-median problem in  $B_i$ , i.e.  $\text{OPT}_1(B_i)$ .

<span id="page-37-0"></span>**Lemma 10.3.** Let  $(p_0, p_1, \ldots, p_t)$  be a t-robust sequence and assume  $B_j = \text{Ball}_{10^j}^{\mathcal{P}}(p_j)$ . Then, for every  $1 \leq j \leq t$ , we have

$$
d(p_{j-1}, p_j) \le 10^j/2
$$
,  $B_{j-1} \subseteq B_j$  and  $d(p_0, p_j) \le 10^j/2$ .

*Proof.* The first part is trivial if AverageCost $(p_j, B_j) \geq 10^j/5$  since  $p_j = p_{j-1}$ . Now, assume AverageCost  $(p_j, B_j) < 10^j/5$ . By the definition of a t-robust sequence, we know Cost  $(p_{j-1}, B_j) \le$ Cost  $(p_j, B_j)$ . Hence,

$$
d(p_j, p_{j-1}) = \sum_{p \in B_j} \frac{w(p)}{w(B_j)} d(p_j, p_{j-1})
$$
  
\n
$$
\leq \sum_{p \in B_j} \frac{w(p)}{w(B_j)} (d(p_j, p) + d(p_{j-1}, p))
$$
  
\n
$$
= \text{AverageCost}(p_j, B_j) + \text{AverageCost}(p_{j-1}, B_j)
$$
  
\n
$$
\leq 2 \text{ AverageCost}(p_j, B_j)
$$
  
\n
$$
\leq \frac{2}{5} \cdot 10^j.
$$

For the second part, if  $p \in B_{j-1}$ , we have

$$
d(p, p_j) \le d(p, p_{j-1}) + d(p_{j-1}, p_j) \le 10^{j-1} + \frac{2}{5} \cdot 10^j \le 10^j,
$$

which implies  $B_{j-1} \subseteq B_j$ . For the last part,

$$
d(p_0, p_j) \le \sum_{i=1}^j d(p_{i-1}, p_i) \le \frac{2}{5} \sum_{i=1}^j 10^i = \frac{2}{5} \cdot \frac{10^{j+1} - 2}{9} \le 10^j / 2.
$$

<span id="page-37-2"></span>**Lemma 10.4.** Let  $(p_0, p_1, \ldots, p_t)$  be a t-robust sequence and assume  $B_j = \text{Ball}_{10^j}^{\mathcal{P}}(p_j)$ . Then, for every  $0 \leq i \leq t$  and every  $S \subseteq \mathcal{P}$  containing  $B_i$  (i.e.  $B_i \subseteq S$ ), we have

$$
\mathsf{Cost}\left(p_0,S\right) \leq \frac{3}{2}\,\, \mathsf{Cost}\left(p_i,S\right)
$$

*Proof.* Since  $(p_0, p_1, \ldots, p_t)$  is *t*-robust, for every  $1 \leq j \leq t$ , we know

<span id="page-37-1"></span>
$$
Cost(p_j, B_j) \ge Cost(p_{j-1}, B_j). \tag{43}
$$

 $\Box$ 

Assume  $q \in \mathcal{P} \setminus B_j$ . Then, using Lemma [10.3,](#page-37-0)

$$
d(q, p_j) \ge 10^j \ge 2 \ d(p_0, p_j).
$$

Hence,

$$
\frac{3}{2} d(q, p_j) = d(q, p_j) + \frac{1}{2} d(q, p_j) \ge d(q, p_j) + d(p_0, p_j) \ge d(q, p_0),
$$

which means

<span id="page-38-0"></span>
$$
d(q, p_j) \ge \frac{2}{3} d(q, p_0). \tag{44}
$$

 $\Box$ 

Finally, Since  $B_1 \subseteq \cdots \subseteq B_i \subseteq S$  (by Lemma [10.3\)](#page-37-0) we can apply Equation [\(43\)](#page-37-1) and Equation [\(44\)](#page-38-0) repeatedly to get

Cost 
$$
(p_i, S)
$$
 = Cost  $(p_i, B_i)$  + Cost  $(p_i, S \setminus B_i)$   
\n $\ge$  Cost  $(p_{i-1}, B_i) + \frac{2}{3}$  Cost  $(p_0, S \setminus B_i)$   
\n= Cost  $(p_{i-1}, B_{i-1})$  + Cost  $(p_{i-1}, B_i \setminus B_{i-1}) + \frac{2}{3}$  Cost  $(p_0, S \setminus B_i)$   
\n $\ge$  Cost  $(p_{i-2}, B_{i-1}) + \frac{2}{3}$  Cost  $(p_0, B_i \setminus B_{i-1}) + \frac{2}{3}$  Cost  $(p_0, S \setminus B_i)$   
\n= Cost  $(p_{i-2}, B_{i-1}) + \frac{2}{3}$  Cost  $(p_0, S \setminus B_{i-1})$   
\n $\ge$  Cost  $(p_0, B_1) + \frac{2}{3}$  Cost  $(p_0, S \setminus B_1)$   
\n $\ge$   $\frac{2}{3}$  Cost  $(p_0, S)$ .

**Definition 10.5** (*t*-robust point). We say p is *t*-robust w.r.t. P whenever there exist a *t*-robust sequence  $(p_0, p_1, \ldots, p_t)$  w.r.t. P such that  $p_0 = p$ .

<span id="page-38-1"></span>**Definition 10.6** (robust solution). Assume U is a set of centers. We call it robust w.r.t. P, if for every  $u \in \mathcal{U}$ , the following condition holds.

• u is t-robust w.r.t. P, where t is the smallest integer satisfying  $10^t \ge d(u, U - u)/200$ .

### 10.4 Well-Separated Pairs

**Definition 10.7** (well-separated pair). Suppose U and V are two sets of centers. For  $u \in U$  and  $v \in V$ , we call  $(u, v)$  a well-separated pair with respect to  $(\mathcal{U}, V)$ , whenever the following inequalities hold.

$$
d(u, \mathcal{U} - u) \geq \gamma d(u, v)
$$
  

$$
d(v, \mathcal{V} - v) \geq \gamma d(u, v)
$$

It is easy to see that each point  $u \in \mathcal{U}$  either forms a well-separated pair with a unique  $v \in \mathcal{V}$ , or it does not form a well-separated pair with any center in  $\mathcal V$ . This can be shown by a simple argument using triangle inequality (assuming the value of  $\gamma$  is large enough).

### 10.5 Relation Between Improper and Proper Optimum Values

<span id="page-38-2"></span>For some technical reasons, in some part of our algorithm, we look for proper solutions and for some parts we look for improper solutions. Here, we provide a relation between the cost of an improper and a proper solution, which we will use in our analyses.

**Lemma 10.8.** Assume **P** is the underlying ground metric space and  $P \subseteq P$ . Then, we have

$$
\mathrm{OPT}_k(\mathcal{P}) \le \mathrm{OPT}_k^{\mathcal{P}}(\mathcal{P}) \le 2 \mathrm{OPT}_k(\mathcal{P}).
$$

Proof. The left inequality is obvious since every proper solution can be considered as an improper solution as well. For the right inequality, assume  $\mathcal{V}^*$  is the optimum improper solution for k-median on P. Consider the projection function  $\pi_{\mathcal{P}} : \mathcal{V}^* \to \mathcal{P}$ . Let  $\mathcal{U} = \pi_{\mathcal{P}}(\mathcal{V}^*)$ . We show that  $\mathcal{U}$  is a 2 approximate solution for the proper k-median problem on  $P$ . Note that  $\mathcal U$  is a proper feasible solution. Assume  $v^* \in \mathcal{V}^*$  is projected to  $\pi_{\mathcal{P}}(v^*) = v \in \mathcal{U}$ . For each  $p \in C_{v^*}(\mathcal{V}^*, \mathcal{P})$ , we have

$$
d(p, v) \le d(p, v^*) + d(v^*, v) \le 2 d(p, v^*).
$$

The last inequality is because  $p \in \mathcal{P}$  and  $\pi_{\mathcal{P}}(v^*) = v$ . By summing up this inequality for each  $p \in C_{v^*}(\mathcal{V}^*, \mathcal{P})$  (considering weights  $w(p)$ ), we conclude

$$
\mathsf{Cost}\left(v, C_{v^*}(\mathcal{V}^*, \mathcal{P})\right) \leq 2 \mathsf{Cost}\left(v^*, C_{v^*}(\mathcal{V}^*, \mathcal{P})\right).
$$

Since  $v \in \mathcal{U}$ , this means

$$
\mathsf{Cost}\left(\mathcal{U}, C_{v^*}(\mathcal{V}^*, \mathcal{P})\right) \leq 2 \, \mathsf{Cost}\left(v^*, C_{v^*}(\mathcal{V}^*, \mathcal{P})\right).
$$

Finally, by summing up these inequalities for each  $v^* \in \mathcal{V}^*$ , we have

Cost 
$$
(U, \mathcal{P}) \leq 2
$$
 Cost  $(V^*, \mathcal{P}) = 2$  OPT<sub>k</sub> $(\mathcal{P}),$ 

which concludes the right inequality since

$$
\mathrm{OPT}_k^{\mathcal{P}}(\mathcal{P}) \leq \mathsf{Cost}\,(\mathcal{U}, \mathcal{P}) \leq 2 \; \mathrm{OPT}_k(\mathcal{P}).
$$

 $\Box$ 

### 10.6 Key Lemmas Used Throughout The Paper

<span id="page-39-1"></span>In this section, we provide the key lemmas that we use in the analysis of our algorithm.

**Lemma 10.9** (Lazy Updates Lemma, Lemma 3.3 in  $[BCG^+24]$ ). Assume  $P$  and  $P'$  are two sets of points such that  $|\mathcal{P} \oplus \mathcal{P}'| \leq l$ . Then for every  $k \geq 0$  we have

$$
\mathrm{OPT}_{k+l}(\mathcal{P}') \leq \mathrm{OPT}_k(\mathcal{P}).
$$

*Proof.* Assume  $U \subseteq P$  of size at most k is such that  $Cost(\mathcal{U}, \mathcal{P}) = OPT_k(\mathcal{P})$ . Define  $\mathcal{U}' =$  $\mathcal{U} + (\mathcal{P} \oplus \mathcal{P}')$ . Obviously,  $\mathcal{U}'$  is a feasible solution for the  $(k+l)$ -median problem on  $\mathcal{P}'$  and since  $\mathcal{U}'$  contains  $\mathcal{P} \oplus \mathcal{P}'$ , we conclude

$$
\text{OPT}_{k+l}(\mathcal{P}') \leq \text{Cost}(\mathcal{U}', \mathcal{P}') = \text{Cost}(\mathcal{U} + (\mathcal{P} \oplus \mathcal{P}'), \mathcal{P}') \leq \text{Cost}(\mathcal{U}, \mathcal{P}) = \text{OPT}_k(\mathcal{P}).
$$

<span id="page-39-0"></span>**Lemma 10.10** (Double-Sided Stability Lemma). Assume for a point set P and values k,  $\eta$  and  $0 \leq r \leq k$  we have

$$
\mathrm{OPT}_{k-r}(\mathcal{P}) \leq \eta \mathrm{OPT}_k(\mathcal{P}).
$$

Then, the following inequality holds.

$$
\text{OPT}_k(\mathcal{P}) \le 4 \text{ OPT}_{k + \lfloor r/(12\eta) \rfloor}(\mathcal{P})
$$

*Proof.* Consider the LP relaxation for the k-median problem on  $P$  for each k as follows.

$$
\min \sum_{p \in \mathcal{P}} \sum_{c \in \mathcal{C}} (w(p) \cdot d(c, p)) x_{cp}
$$
\n
$$
\text{s.t. } x_{cp} \le y_c
$$
\n
$$
\sum_{c \in \mathcal{C}} x_{cp} \ge 1 \qquad \forall p \in \mathcal{P}
$$
\n
$$
\sum_{c \in \mathcal{C}} y_c \le k
$$
\n
$$
x_{cp}, y_c \ge 0 \qquad \forall c \in \mathcal{C}, p \in \mathcal{P}
$$

Note that  $\mathcal C$  is the set of potential centers to open. We assume  $\mathcal C$  is the underlying ground set of points **P**. This is because we considered the definition of  $\text{OPT}_k(\mathcal{P})$  for the improper case.

Denote the cost of the optimal fractional solution for this LP by  $FOPT_k$ . Since the space  $\mathcal P$  is fixed here, we denote  $\text{OPT}_k(\mathcal{P})$  by  $\text{OPT}_k$ . It is known that the integrality gap of this relaxation is at most 3 [\[CS11\]](#page-74-1). So, for every  $k$  we have

<span id="page-40-0"></span>
$$
\text{FOPT}_k \le \text{OPT}_k \le 3 \text{ FOPT}_k. \tag{45}
$$

**Claim 10.11.** For every  $k_1$ ,  $k_2$  and  $0 \le \alpha, \beta \le 1$  such that  $\alpha + \beta = 1$ , we have

$$
\text{FOPT}_{\alpha k_1 + \beta k_2} \le \alpha \text{ FOPT}_{k_1} + \beta \text{ FOPT}_{k_2}.
$$

*Proof.* Assume optimal fractional solutions  $(x_1^*, y_1^*)$  and  $(x_2^*, y_2^*)$  for above LP relaxation of  $k_1$  and  $k_2$ -median problems respectively. It is easy to verify that  $(\alpha x_1^* + \beta x_2^*, \alpha y_1^* + \beta y_2^*)$  is a feasible solution for fractional  $(\alpha k_1 + \beta k_2)$ -median problem whose cost is  $\alpha$  FOPT<sub> $k_1$ </sub> +  $\beta$  FOPT<sub> $k_2$ </sub>, which concludes the claim.  $\Box$ 

Now, plug  $k_1 = k - r$ ,  $k_2 = k + r/(12\eta)$ ,  $\alpha = 1/(12\eta)$  and  $\beta = 1 - \alpha$  in the claim. We have

$$
\alpha k_1 + \beta k_2 = \frac{1}{12\eta} (k - r) + \left( 1 - \frac{1}{12\eta} \right) \left( k + \frac{r}{12\eta} \right) = k - \frac{r}{(12\eta)^2} \le k.
$$

As a result,

 $\text{FOPT}_k \leq \text{FOPT}_{\alpha k_1 + \beta k_2} \leq \alpha \text{ FOPT}_{k_1} + \beta \text{ FOPT}_{k_2}.$ 

Together with Equation [\(45\)](#page-40-0), we have

$$
\text{OPT}_k \le 3\alpha \text{ OPT}_{k_1} + 3\beta \text{ OPT}_{k_2}.
$$

We also have the assumption that  $\text{OPT}_{k_1} = \text{OPT}_{k-r} \leq \eta \text{ OPT}_k$ , which implies

$$
\text{OPT}_k \leq 3\alpha\eta \text{ OPT}_k + 3\beta \text{ OPT}_{k_2}.
$$

Finally

$$
\text{OPT}_k \le \left(\frac{3\beta}{1-3\alpha\eta}\right) \text{OPT}_{k_2} \le 4 \text{ OPT}_{k_2} \le 4 \text{ OPT}_{k+\lfloor r/(12\eta)\rfloor}.
$$

<span id="page-40-1"></span>The second inequality follows from

$$
\frac{3\beta}{1-3\alpha\eta} \le \frac{3}{1-3\alpha\eta} = \frac{3}{1-1/4} = 4.
$$

**Lemma 10.12** (variation of Lemma 7.4 in [\[FLNS21\]](#page-75-1)). If U and V are two set of centers and  $\mathcal{P}$  is a set of points such that U is robust w.r.t. P. Then, for every well-separated pair  $(u, v)$  w.r.t.  $(\mathcal{U}, \mathcal{V})$ , we have

$$
\mathsf{Cost}\left(u, C_v(\mathcal{V}, \mathcal{P})\right) \leq 5 \, \mathsf{Cost}\left(v, C_v(\mathcal{V}, \mathcal{P})\right).
$$

*Proof.* Since, the point set P is fixed, denote  $C_v(V,\mathcal{P})$  by  $C_v$  for simplicity. If  $d(u, v) = 0$ , the statement is trivial. Now assume  $d(u, v) \geq 1$ . Since U is robust, then u is t-robust where t is the smallest integer such that

$$
10t \ge d(u, \mathcal{U} - u)/200 \ge (\gamma/200) \ d(u, v) = 20 \ d(u, v) \tag{46}
$$

The second inequality is because  $(u, v)$  is well-separated pair and the equality is because  $\gamma = 4000$ . Assume  $t^*$  is the integer satisfying

<span id="page-41-0"></span>
$$
20\ d(u,v) \le 10^{t^*} < 10 \cdot 20\ d(u,v). \tag{47}
$$

Note that  $t^* \geq 1$ . Since  $t^* \leq t$  and u is t-robust, then it is also  $t^*$ -robust which means there is a  $t^*$ -robust sequence  $(p_0, p_1, \ldots, p_{t^*})$  such that  $p_0 = u$ . For Simplicity, assume  $B_i = \text{Ball}_{10^i}^{\mathcal{P}}(p_i)$  for  $0 \leq i \leq t^*$ .

<span id="page-41-2"></span>**Claim 10.13.** For each  $0 \le i \le t^*$ , we have  $B_i \subseteq C_v$ .

*Proof.* Assume  $q \in B_i$ . Then,

$$
d(q, v) \leq d(q, p_i) + d(p_i, u) + d(u, v)
$$
  
= 
$$
d(q, p_i) + d(p_i, p_0) + d(u, v)
$$
  

$$
\leq 10^i + 10^i / 2 + 10^{t^*} / 20
$$
  

$$
\leq 2 \cdot 10^{t^*}.
$$

For the second inequality, we used  $q \in B_i$ , Lemma [10.3](#page-37-0) and Equation [\(47\)](#page-41-0). Now, for every  $v' \in \mathcal{V} - v$ we have

$$
d(v, v') \ge d(v, \mathcal{V} - v) \ge 4 \cdot 10^3 \ d(u, v) > 10^{t^* + 1} \ge 2 \ d(q, v).
$$

The second inequality is by  $(u, v)$  being well-separated (and  $\gamma = 4000$ ), the third one is by Equa-tion [\(47\)](#page-41-0). This concludes  $d(q, v') \geq d(v, v') - d(q, v) > d(q, v)$  which means v is the closest center to q in  $V$ . So,  $q \in B_i$  and finally  $B_i \subseteq C_v$ .  $\Box$ 

Now, we according to the definition of t-robust sequence we have two cases. **Case 1:** AverageCost  $(p_{t^*}, B_{t^*}) \ge 10^{t^*}/5$ . In this case we have  $p_{t^*-1} = p_{t^*}$  and

$$
d(v, p_{t^*}) = d(v, p_{t^*-1})
$$
  
\n
$$
\leq d(v, p_0) + d(p_0, p_{t^*-1})
$$
  
\n
$$
= d(v, u) + d(p_0, p_{t^*-1})
$$
  
\n
$$
\leq 10^{t^*}/20 + 10^{t^*-1}/2
$$
  
\n
$$
= 10^{t^*}/10.
$$

The second inequality holds by Lemma [10.3](#page-37-0) and Equation [\(47\)](#page-41-0). So,

<span id="page-41-1"></span>
$$
d(v, p_{t^*}) \le 10^{t^*} / 10. \tag{48}
$$

For every  $q \in C_v - B_{t^*}$  we have

$$
d(q, v) \ge d(p_{t^*}, q) - d(v, p_{t^*}) \ge 10^{t^*} - d(v, p_{t^*}) \ge d(v, p_{t^*}).
$$

The second inequality follows by  $q \in C_v - B_{t^*}$  and the last inequality follows by Equation [\(48\)](#page-41-1). So,

$$
d(q, v) \ge (d(q, v) + d(v, p_{t^*}))/2 \ge d(q, p_{t^*})/2,
$$

which implies

<span id="page-42-1"></span>Cost 
$$
(v, C_v - B_{t^*}) \ge \frac{\text{Cost}(p_{t^*}, C_v - B_{t^*})}{2}.
$$
 (49)

We also have

<span id="page-42-0"></span>AverageCost 
$$
(p_{t^*}, B_{t^*}) \ge 10^{t^*}/5 \ge 2 d(v, p_{t^*}),
$$
 (50)

by the assumption of this case and Equation [\(48\)](#page-41-1). Now, we conclude

Cost 
$$
(v, C_v)
$$
 = Cost  $(v, B_{t^*})$  + Cost  $(v, C_v - B_{t^*})$   
\n=  $w(B_{t^*})$  · AverageCost  $(v, B_{t^*})$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq w(B_{t^*})$  · (AverageCost  $(p_{t^*}, B_{t^*}) - d(v, p_{t^*}))$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq w(B_{t^*})$  ·  $\frac{\text{AverageCost}(p_{t^*}, B_{t^*})}{2}$  + Cost  $(v, C_v - B_{t^*})$   
\n $= \frac{\text{Cost}(p_{t^*}, B_{t^*})}{2}$  + Cost  $(v, C_v - B_{t^*})$   
\n $\geq \frac{\text{Cost}(p_{t^*}, B_{t^*})}{2}$  +  $\frac{\text{Cost}(p_{t^*}, C_v - B_{t^*})}{2}$   
\n $= \frac{\text{Cost}(p_{t^*}, C_v)}{2}$ .

The first inequality is triangle inequality, the second inequality holds by Equation [\(50\)](#page-42-0) and the last inequality holds by Equation [\(49\)](#page-42-1). Finally, since  $B_{t^*} \subseteq C_v$  (by Claim [10.13\)](#page-41-2), we can apply Lemma [10.4](#page-37-2) to get

$$
\mathsf{Cost}\left(u,C_v\right)=\mathsf{Cost}\left(p_0,C_v\right)\leq \frac{3}{2}\cdot \mathsf{Cost}\left(p_{t^*},C_v\right)\leq \frac{3}{2}\cdot 2\,\, \mathsf{Cost}\left(v,C_v\right)=3\,\, \mathsf{Cost}\left(v,C_v\right).
$$

**Case 2:** AverageCost  $(p_{t^*}, B_{t^*}) < 10^{t^*}/5$ . In this case, for every  $q \in C_v - B_{t^*}$ ,

$$
d(q, p_{t^*-1}) \ge d(q, p_{t^*}) - d(p_{t^*}, p_{t^*-1}) \ge 10^{t^*} - 10^{t^*}/2 = 10^{t^*}/2.
$$

The second inequality holds by  $q \in C_v - B_{t^*}$  and Lemma [10.3.](#page-37-0) So,

<span id="page-42-2"></span>
$$
d(q, p_{t^*-1}) \ge 10^{t^*}/2. \tag{51}
$$

We also have

$$
d(v, p_{t^* - 1}) \le d(v, u) + d(u, p_{t^* - 1})
$$
  
=  $d(v, u) + d(p_0, p_{t^* - 1})$   
 $\le 10^{t^*}/20 + 10^{t^* - 1}/2$   
=  $10^{t^*}/10$ .

The second inequality holds by Equation [\(47\)](#page-41-0) and Lemma [10.3.](#page-37-0) So,

<span id="page-42-3"></span>
$$
d(v, p_{t^*-1}) \le 10^{t^*} / 10. \tag{52}
$$

Combining Equation [\(51\)](#page-42-2) and Equation [\(52\)](#page-42-3), we have

$$
d(v, p_{t^*-1}) \le 10^{t^*} / 10 = \frac{1}{5} \cdot 10^{t^*} / 2 \le \frac{1}{5} \cdot d(q, p_{t^*-1}),
$$

which concludes

$$
\frac{d(q, p_{t^*-1})}{d(q, v)} \le \frac{d(q, p_{t^*-1})}{d(q, p_{t^*-1}) - d(p_{t^*-1}, v)} \le \frac{d(q, p_{t^*-1})}{d(q, p_{t^*-1}) - \frac{1}{5} \cdot d(q, p_{t^*-1})} = 5/4 \le 3.
$$

So, we have

$$
d(q, p_{t^*-1}) \le 3 \ d(q, v).
$$

Using this inequality for all  $q \in C_v - B_{t^*}$ , we conclude

<span id="page-43-0"></span>Cost 
$$
(p_{t^*-1}, C_v - B_{t^*}) \le 3
$$
 Cost  $(v, C_v - B_{t^*})$ . (53)

 $\Box$ 

Hence,

$$
\begin{array}{rcl}\n\text{Cost}(p_{t^*-1}, C_v) & = & \text{Cost}(p_{t^*-1}, B_{t^*}) + \text{Cost}(p_{t^*-1}, C_v - B_{t^*}) \\
& \leq & 3 \text{ OPT}_1(B_{t^*}) + \text{Cost}(p_{t^*-1}, C_v - B_{t^*}) \\
& \leq & 3 \text{ Cost}(v, B_{t^*}) + \text{Cost}(p_{t^*-1}, C_v - B_{t^*}). \\
& \leq & 3 \text{ Cost}(v, B_{t^*}) + 3 \text{ Cost}(v, C_v - B_{t^*}). \\
& = & 3 \text{ Cost}(v, C_v).\n\end{array}
$$

The equalities hold since  $B_{t^*} \subseteq C_v$  (by Claim [10.13\)](#page-41-2), the first inequality holds by the definition of  $t^*$ -robust sequence, the second inequality holds since  $v \in B_{t^*}$  (by Equation [\(47\)](#page-41-0)) and the last inequality holds by Equation [\(53\)](#page-43-0). Finally, applying Lemma [10.4](#page-37-2) implies

$$
\mathsf{Cost}\left(u,C_v\right)=\mathsf{Cost}\left(p_0,C_v\right)\leq \frac{3}{2}\cdot \mathsf{Cost}\left(p_{t^*-1},C_v\right)\leq \frac{3}{2}\cdot 3\,\mathsf{Cost}\left(v,C_v\right)\leq 5\,\mathsf{Cost}\left(u,C_v\right).
$$

In both cases, we showed that  $Cost(u, C_v) \leq 5$  Cost $(v, C_v)$  which completes the proof.

<span id="page-43-1"></span>**Lemma 10.14** (generalization of Lemma 7.3 in [\[FLNS21\]](#page-75-1)). Suppose P is a set of points, U is a set of k centers and V is a set of at most  $k + r$  centers. If the number of well-separated pairs with respect to  $(\mathcal{U}, \mathcal{V})$  is  $k - m$ , then there exist a  $\overline{\mathcal{U}} \subseteq \mathcal{U}$  of size at most  $k - |(m - r)/4|$  such that

Cost 
$$
(\bar{U}, \mathcal{P}) \le 6\gamma
$$
 (Cost  $(U, \mathcal{P})$  + Cost  $(V, \mathcal{P})$ ).

*Proof.* Consider the standard LP relaxation for the weighted  $k$ -median problem. We consider the set of potential centers to open  $\mathcal{U}$ , and we want to open at most  $k - (m - r)/4$  many centers. So, we have the following LP.

$$
\min \sum_{p \in \mathcal{P}} \sum_{u \in \mathcal{U}} (w(p) \cdot d(u, p)) x_{up}
$$
\n
$$
\text{s.t. } x_{up} \le y_u \quad \forall u \in \mathcal{U}, p \in \mathcal{P}
$$
\n
$$
\sum_{u \in \mathcal{U}} x_{up} \ge 1 \quad \forall p \in \mathcal{P}
$$
\n
$$
\sum_{u \in \mathcal{U}} y_u \le k - (m - r)/4
$$
\n
$$
x_{up}, y_u \ge 0 \quad \forall u \in \mathcal{U}, p \in \mathcal{P}
$$

Now, we explain how to construct a fractional solution for this LP.

**Fractional Opening of Centers.** Consider the projection  $\pi_{\mathcal{U}} : \mathcal{V} \to \mathcal{U}$  function. Assume  $U = U_I + U_F$  is a partition of U where  $U_I$  contains those centers  $u \in U$  satisfying at least one of the following conditions:

- u forms a well-separated pair with one center in  $V$ .
- $\bullet$   $|\pi^{-1}_{\mathcal{U}}|$  $\frac{1}{\mathcal{U}}(u) \geq 2.$

For every  $u \in \mathcal{U}_I$ , set  $y_u = 1$  and for every  $u \in \mathcal{U}_F$  set  $y_u = 1/2$ . First, we show that

$$
\sum_{u \in \mathcal{U}} y_u \leq k - (m - r)/4.
$$

Each center  $u \in \mathcal{U}$  that forms a well-separated pair with a center  $v \in \mathcal{V}$  has  $|\pi_{\mathcal{U}}^{-1}|$  $\overline{u}^{-1}(u)$  > 1 since u must be the closest center to v in  $\mathcal U$ . Since the number of well-separated pairs is  $k - m$ , we have

$$
k + r \geq |\mathcal{V}| = \sum_{u \in \mathcal{U}} |\pi^{-1}(u)| \geq \sum_{u \in \mathcal{U}_I} |\pi^{-1}(u)| \geq k - m + 2 \cdot (|\mathcal{U}_I| - (k - m)).
$$

Hence,

$$
|U_I| \le \frac{k + r + (k - m)}{2} = k - \frac{m - r}{2}.
$$

Finally, we conclude

$$
\sum_{u \in \mathcal{U}} y_u = \sum_{u \in \mathcal{U}_I} y_u + \sum_{u \in \mathcal{U}_F} y_u
$$
\n
$$
\leq k - \frac{m - r}{2} + \frac{1}{2} \cdot \frac{m - r}{2}
$$
\n
$$
= k - \frac{m - r}{4}.
$$

**Fractional Assignment of Points.** For every  $p \in \mathcal{P}$ , assume  $v_p = \pi_V(p)$  is the closest center to p in V and  $u_p = \pi_{\mathcal{U}}(v_p)$  is the closest center in U to  $v_p$ . We have three cases:

- If  $y_{u_p} = 1$ , then set  $x_{u_p} = 1$ . The cost of this assignment would be  $w(p) \cdot d(u_p, p)$ .
- If  $y_{u_p} = 1/2$  and there is a center  $u'_p \in \mathcal{U} u_p$  such that  $d(u_p, u'_p) \leq \gamma \cdot d(u_p, v_p)$ , then set  $x_{u_p p} = x_{u'_p p} = 1/2$ . Note that  $u'_p \neq u_p$  which means point p is assigned one unit to centers. The cost of this assignment would be

$$
\frac{1}{2}w(p)\left(d(p, u_p) + d(p, u'_p)\right) \leq \frac{1}{2}w(p)\left(d(p, u_p) + d(p, u_p) + d(u'_p, u_p)\right) \leq w(p)\left(d(p, u_p) + \frac{\gamma}{2} \cdot d(u_p, v_p)\right).
$$

• If  $y_{u_p} = 1/2$  and the previous case does not hold, then since  $(u_p, v_p)$  is not a well-separated pair, there is a center  $v'_p \in V - v_p$  such that  $d(v_p, v'_p) \leq \gamma \cdot d(u_p, v_p)$ . Let  $u'_p = \pi_{\mathcal{U}}(v'_p)$  and set  $x_{u_p p} = x_{u'_p p} = 1/2$ . First, we show that  $u'_p \neq u_p$ . Since  $y_{u_p} = 1/2$ , we have  $u_p \in U_F$ which concludes  $|\pi_{\mathcal{U}}^{-1}|$  $\vert u^{-1}(u_p) \vert \leq 1$ . We also know that  $\pi_{\mathcal{U}}(v_p) = u_p$ . So,  $v_p$  is the only center in

V mapped to  $u_p$  which implies  $\pi_{\mathcal{U}}(v'_p) \neq u_p$  or  $u'_p \neq u_p$  (note that  $v'_p \neq v_p$ ). So, point p is assigned one unit to centers. The cost of this assignment would be

$$
\frac{1}{2}w(p)\left(d(p, u_p) + d(p, u'_p)\right) \leq \frac{1}{2}w(p)\left(d(p, u_p) + d(p, u_p) + d(u_p, v'_p) + d(v'_p, u'_p)\right)
$$
\n
$$
\leq \frac{1}{2}w(p)\left(d(p, u_p) + d(p, u_p) + d(u_p, v'_p) + d(v'_p, u_p)\right)
$$
\n
$$
= w(p)\left(d(p, u_p) + d(u_p, v'_p)\right)
$$
\n
$$
\leq w(p)\left(d(p, u_p) + d(u_p, v_p) + d(v_p, v'_p)\right)
$$
\n
$$
\leq w(p)\left(d(p, u_p) + (\gamma + 1) d(u_p, v_p)\right).
$$

The second inequality is because of the choice of  $u'_p = \pi_{\mathcal{U}}(v'_p)$  and the last inequality is because  $d(v_p, v'_p) \leq \gamma \cdot d(u_p, v_p).$ 

**Bounding the Cost.** Assume  $u_p^* = \pi_{\mathcal{U}}(p)$  for each  $p \in \mathcal{P}$ . We have

$$
d(u_p, v_p) \le d(u_p^*, v_p) \le d(u_p^*, p) + d(p, v_p).
$$

The first inequality is by the choice of  $u_p = \pi_{\mathcal{U}}(v_p)$ . As a result,

<span id="page-45-0"></span>
$$
\sum_{p \in \mathcal{P}} w(p) d(u_p, v_p) \le \sum_{p \in \mathcal{P}} w(p) \left( d(u_p^*, p) + d(p, v_p) \right) = \text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P}). \tag{54}
$$

In each of the cases of fractional assignments of points to centers, the cost of assigning a point  $p \in C_v(\mathcal{V}, \mathcal{P})$  is at most  $w(p) (d(p, u_p) + (\gamma + 1) d(u_p, v_p))$ . As a result, the total cost of this assignment is upper bounded by

$$
\sum_{p \in P} w(p) (d(p, u_p) + (\gamma + 1) d(u_p, v_p)) \leq \sum_{p \in P} w(p) (d(p, v_p) + (\gamma + 2) d(u_p, v_p))
$$
  
\n
$$
\leq \text{Cost}(\mathcal{V}, \mathcal{P}) + (\gamma + 2) (\text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P}))
$$
  
\n
$$
\leq 2\gamma (\text{Cost}(\mathcal{U}, \mathcal{P}) + \text{Cost}(\mathcal{V}, \mathcal{P})).
$$

The second inequality follows by Equation [\(54\)](#page-45-0).

Finally, note that the integrality gap of the LP relaxation is known to be at most 3 [\[CS11\]](#page-74-1). As a result, there exist an integral solution whose cost is at most  $6\gamma$  (Cost  $(\mathcal{U}, \mathcal{P})$  + Cost  $(\mathcal{V}, \mathcal{P})$ ) and this solution opens at most  $k - \lfloor \frac{m-r}{4} \rfloor$  centers which completes the proof.

 $\Box$ 

# 11 Useful Subroutines of Our Algorithm

In this section, we provide useful static subroutines that we are going to use in our main algorithm.

### <span id="page-45-1"></span>11.1 Rand-Local-Search

This algorithm is first introduced in  $[BCG^+24]$ . Given a set of points P, a set of k centers U and a number  $s \leq k$ , the aim is to find a good subset of centers U of size  $k - s$ . The algorithm starts with an arbitrary  $\mathcal{U}^* \subseteq \mathcal{U}$  of size  $k - s$  and tries to improve this subset by random local swaps for  $\Theta(s)$  many iterations.

**Algorithm 6:** (Algorithm 3 in [\[BCG](#page-74-0)<sup>+</sup>24]), RAND-LOCAL-SEARCH( $P, U, s$ )

1  $\mathcal{U}^*$  ← arbitrary subset of  $\mathcal{U}$  of size  $k - s$ .

- 2 for  $\tilde{\Theta}(s)$  iterations do
- **3** Sample  $v \in \mathcal{U} \mathcal{U}^*$  independently and uniformly at random.
- $4 \mid z^* \leftarrow \arg\min_{z \in \mathcal{U}^*+v} \{ \textsf{Cost}\left( \mathcal{U}^*+v-z, \mathcal{P} \right) \textsf{Cost}\left( \mathcal{U}^*, \mathcal{P} \right) \}.$
- 5  $\mathcal{U}^* \leftarrow \mathcal{U}^* z^* + v.$
- 6 return  $\mathcal{U}^*$ .

<span id="page-46-3"></span>We have the following lemma which shows the subset derived from RAND-LOCAL-SEARCH is actually a good subset w.h.p.

**Lemma 11.1** (Lemma 3.18 in [\[BCG](#page-74-0)<sup>+</sup>24]). If  $\mathcal{U}^*$  is returned by RAND-LOCAL-SEARCH( $\mathcal{P}, \mathcal{U}, s$ ), then with high probability,

Cost 
$$
(\mathcal{U}^*, \mathcal{P}) \leq 2
$$
 Cost  $(\mathcal{U}, \mathcal{P}) + 12$  OPT<sub>k-s</sub> $(\mathcal{P})$ .

### <span id="page-46-2"></span>11.2 Develop-Centers

Given a set of points P, a set of centers U and an integer  $s \geq 1$ , the aim of this subroutine is to extend  $U$  to  $U$  by adding s centers which is a good approximation to the best solution that adds s centers to  $U$ , i.e. the algorithm finds  $U$  such that

Cost 
$$
(\tilde{U}, \mathcal{P}) \leq \beta \min_{\substack{\mathcal{F} \subseteq \mathcal{P}, \\ |\mathcal{F}| \leq s}} \text{Cost } (\mathcal{U} + \mathcal{F}, \mathcal{P})
$$
.<sup>15</sup>

The algorithm defines a new metric space and runs a standard  $(s + 1)$ -median static algorithm on this space. The high level idea behind this subroutine is that we have a set of fixed k centers  $\mathcal{U}$ that must be contained in  $\mathcal{U}$ . So, if we can treat these fixed centers as a single center instead of a set of k centers, we might be able to reduce the problem to  $(s + 1)$ -median. So, we contract all of the points U to a single point u<sup>\*</sup> and define a new space  $\mathcal{P}' = (\mathcal{P} - \mathcal{U}) + u^*$  with a new metric d' as follows.

<span id="page-46-1"></span>
$$
\begin{cases} d'(x, u^*) := d(x, \mathcal{U}) & \forall x \in \mathcal{P} \\ d'(x, y) := \min\{d'(x, u^*) + d'(y, u^*), d(x, y)\} & \forall x, y \in \mathcal{P} \end{cases}
$$
(55)

We define the weight of a point  $x \in \mathcal{P}' - u^*$  the same weight of x in  $\mathcal{P}$ . Finally, we set  $w(u^*)$  to be very large say  $w(u^*) = \beta n W \Delta$ , where W is the maximum weight of points in P. This makes any β approximate solution for  $(s + 1)$ -median problem on P' to contain u<sup>\*</sup> by force.

## Claim 11.2.  $(\mathcal{P}', d')$  is a metric space.

*Proof.* Intuitively, we can derive  $d'$  by the metric of shortest path in the following graph. For each  $p \in \mathcal{P}$  we have a node. The weight of the edge pq for  $p, q \in \mathcal{U}$  is 0 and the weight of any other two point is their  $d$  distance. Now,  $d'$  exactly equals to the metric derived by the shortest in this graph, which is well-known to be a metric. By the way, we provide another proof here that does not depend in this fact and is self-contained.

Now, we proceed with the formal proof. The only non trivial property about  $d'$  is the triangle inequality. We need to show that for every  $x, y, z \in \mathcal{P}'$ , we have

$$
d'(x, y) \le d'(x, z) + d'(y, z).
$$

<span id="page-46-0"></span><sup>&</sup>lt;sup>15</sup>Recall  $\beta$  from Section [10.2.1](#page-36-1)

If at least two of x, y and z are equal, the inequality is trivial. Otherwise, by symmetry between x and y, we have one of the following three cases.

Case 1:  $z = u^*$  and  $x, y \neq u^*$ .

This case is trivial by the definition of  $d'$  since

$$
d'(x,y) = \min\{d'(x,u^*) + d'(y,u^*), d(x,y)\} \le d'(x,u^*) + d'(y,u^*) = d'(x,z) + d'(y,z).
$$

Case 2:  $y = u^*$  and  $x, z \neq u^*$ .

Assume  $u_x, u_z \in \mathcal{U}$  are the projection of x and z on  $\mathcal{U}$  respectively with respect to metric d. So,  $d(x, \mathcal{U}) = d(x, u_x)$ ,  $d(z, \mathcal{U}) = d(z, u_z)$  and  $d(x, u_x) \leq d(x, u_z)$ . Note that  $d'(x, y) = d'(x, u^*) =$  $d(x, \mathcal{U}) = d(x, u_x)$  and  $d'(z, y) = d'(z, u^*) = d(z, \mathcal{U}) = d(z, u_z)$ . As a result,

$$
d'(x,y) = d(x, u_x)
$$
  
\n
$$
\leq d(x, u_z)
$$
  
\n
$$
\leq d(x, z) + d(z, u_z)
$$
  
\n
$$
= d(x, z) + d'(z, y).
$$

The first inequality is because of the choice of  $u_x$  in U and the second inequality is triangle inequality for metric d. So, we have the following

<span id="page-47-0"></span>
$$
d'(x, y) \le d(x, z) + d'(z, y). \tag{56}
$$

Since  $d'$  is non negative, we also have

<span id="page-47-1"></span>
$$
d'(x,y) = d'(x,u^*) \le (d'(x,u^*) + d'(z,u^*)) + d'(z,y)
$$
\n(57)

Combining Equation [\(56\)](#page-47-0) and Equation [\(57\)](#page-47-1) we have

$$
d'(x,y) \le \min\{d'(x,u^*) + d'(z,u^*), d(x,z)\} + d'(z,y) = d'(x,z) + d'(z,y).
$$

Case 3:  $x, y, z \neq u^*$ .

According to the definition of  $d'$  we have one of the following sub cases.

•  $d'(y, z) = d'(y, u^*) + d'(z, u^*).$ 

By the second case that we have already proved, we know that

$$
d'(x, u^*) \le d'(x, z) + d'(z, u^*).
$$

Hence,

$$
d'(x,y) = \min\{d'(x,u^*) + d'(y,u^*), d(x,y)\}\
$$
  
\n
$$
\leq d'(x,u^*) + d'(y,u^*)
$$
  
\n
$$
\leq d'(x,z) + d'(z,u^*) + d'(y,u^*)
$$
  
\n
$$
= d'(x,z) + d'(y,z).
$$

•  $d'(x, z) = d'(x, u^*) + d'(z, u^*).$ 

By symmetry between  $x$  and  $y$ , this sub case is similar to the previous sub case.

•  $d'(y, z) \neq d'(y, u^*) + d'(z, u^*)$  and  $d'(x, z) \neq d'(x, u^*) + d'(z, u^*)$ . According to the definition of  $d'(x, z)$  and  $d'(y, z)$  we have  $d'(x, z) = d(x, z)$  and  $d'(y, z) =$  $d(y, z)$ . Then, be triangle inequality for d we have

$$
d'(x,y) = \min\{d'(x,u^*) + d'(y,u^*), d(x,y)\}\
$$
  
\n
$$
\leq d(x,y)
$$
  
\n
$$
\leq d(x,z) + d(y,z)
$$
  
\n
$$
= d'(x,z) + d'(y,z).
$$

In all cases, we proved  $d'(x, y) \leq d'(x, z) + d'(y, z)$  which concludes  $(\mathcal{P}', d')$  is a metric space.

Next, we run any algorithm for  $(s + 1)$ -median problem on  $\mathcal{P}'$  w.r.t. metric d' to find a F of size at most  $(s+1)$  which is a  $\beta$  approximation for  $\text{OPT}_{s+1}(\mathcal{P}')$ . Finally, we let  $\tilde{\mathcal{U}} = \mathcal{U} + (\mathcal{F} - u^*)$ . Note that all of the points of  $\mathcal{F} - u^*$  are present in  $\mathcal{P}$  and also the size of  $\mathcal{U}$  is at most  $k + s$  since u <sup>∗</sup> ∈ F.



It is not obvious how the cost of a set w.r.t. metrics  $d$  and  $d'$  relate to each other. But, we will show that solution  $\mathcal F$  w.r.t. metric  $d'$  is going to be a good solution for our purpose w.r.t. metric  $d$ as well. So, we show the following guarantee for this subroutine.

<span id="page-48-3"></span>**Lemma 11.3.** If  $\hat{U}$  is returned by DEVELOP-CENTERS( $\mathcal{P}, \mathcal{U}, s$ ), then we have

$$
\mathsf{Cost}\left(\tilde{\mathcal{U}},\mathcal{P}\right)\leq\beta\min_{\substack{\mathcal{F}\subseteq\mathcal{P},\\|\mathcal{F}|\leq s}}\mathsf{Cost}\left(\mathcal{U}+\mathcal{F},\mathcal{P}\right).^{16}
$$

Proof. First, we show how the objective function of two solutions with respect to metrics d and d' relate to each other. Denote  $\mathsf{Cost}^d(X, \mathcal{P})$  to be the cost of X with respect to metric d on  $\mathcal{P}$ , i.e.  $\sum_{p\in\mathcal{P}} w(p)d(p,X)$ , and  $\mathsf{Cost}^{d'}(X,\mathcal{P}')$  to be the cost of X with respect to metric d' on  $\mathcal{P}',$ i.e.  $\sum_{p\in\mathcal{P}'}^{P^{\text{op}}}\psi(p)d'(p,X)$ . The following claim relates metrics d and d'.

<span id="page-48-2"></span>Claim 11.4. Assume  $\mathcal{F} \subseteq \mathcal{P}$ . Then, the following holds.

$$
\mathcal{C}ost^{d}\left(\mathcal{F}+\mathcal{U},\mathcal{P}\right)=\mathcal{C}ost^{d'}\left(\mathcal{F}+u^{*},\mathcal{P}'\right).
$$

*Proof.* Note that  $\mathcal{P}' = (\mathcal{P} - \mathcal{U}) + u^*$ . Since  $d'(u^*, \mathcal{F} + u^*) = 0$  and  $d(u, \mathcal{F} + \mathcal{U}) = 0$  for every  $u \in \mathcal{U}$ , it suffices to show that for each  $x \in \mathcal{P} - \mathcal{U}$ , we have  $d(x, \mathcal{F} + \mathcal{U}) = d'(x, \mathcal{F} + u^*)$ . Since  $d(x, \mathcal{F} + \mathcal{U}) = \min\{d(x, \mathcal{F}), d(x, \mathcal{U})\}\,$ , we have one of the following two cases.

**Case 1:**  $d(x, \mathcal{U}) \leq d(x, \mathcal{F})$ . This means  $d'(x, u^*) \leq d(x, \mathcal{F})$ . As a result, for every  $f \in \mathcal{F}$  we have

<span id="page-48-1"></span>
$$
d'(x, u^*) \le d(x, f) \tag{58}
$$

<span id="page-48-0"></span><sup>&</sup>lt;sup>16</sup>Recall  $\beta$  from Section [10.2.1](#page-36-1)

We also have the following since  $d'$  is non negative.

<span id="page-49-0"></span>
$$
d'(x, u^*) \le d'(x, u^*) + d'(f, u^*)
$$
\n(59)

Combining Equation [\(58\)](#page-48-1) and Equation [\(59\)](#page-49-0), for every  $f \in \mathcal{F}$ , we have

$$
d'(x, u^*) \le \min\{d'(x, u^*) + d'(f, u^*), d(x, f)\} = d'(x, f).
$$

Hence,  $d'(x, \mathcal{F} + u^*) = d'(x, u^*)$  implying that

$$
d'(x, \mathcal{F} + u^*) = d'(x, u^*) = d(x, \mathcal{U}) = d(x, \mathcal{F} + \mathcal{U}).
$$

The last equality is because of the assumption of this case.

**Case 2:**  $d(x, \mathcal{U}) > d(x, \mathcal{F})$ . Assume  $f_x \in \mathcal{F}$  is the projection of x onto  $\mathcal{F}$  with respect to metric d. We are going to show that  $f_x$  is also the projection of x onto  $\mathcal{F} + u^*$  with respect to metric d'.

We have  $d(x, f_x) = d(x, \mathcal{F}) \leq d(x, \mathcal{U}) = d'(x, u^*)$ . So,

<span id="page-49-1"></span>
$$
d(x, f_x) \le d'(x, u^*)\tag{60}
$$

By non negativity of  $d'$ , we have

$$
d(x, f_x) \stackrel{(60)}{\leq} d'(x, u^*) \leq d'(x, u^*) + d'(f_x, u^*),
$$
  
which concludes  $d(x, f_x) = \min\{d'(x, u^*) + d'(f_x, u^*), d(x, f_x)\} = d'(x, f_x)$ . So,

<span id="page-49-2"></span>
$$
d(x, f_x) = d'(x, f_x). \tag{61}
$$

Now, assume  $f \in \mathcal{F}$  is arbitrary. We have

<span id="page-49-4"></span>
$$
d'(x, f_x) \stackrel{(61)}{=} d(x, f_x) \stackrel{(60)}{\leq} d'(x, u^*) \leq d'(x, u^*) + d'(f, u^*), \tag{62}
$$

as well as

<span id="page-49-3"></span>
$$
d'(x, f_x) \stackrel{(61)}{=} d(x, f_x) \le d(x, f). \tag{63}
$$

The inequality in Equation [\(63\)](#page-49-3) is because of the choice of  $f_x$ . Combining Equation [\(62\)](#page-49-4) and Equation [\(63\)](#page-49-3), we have

$$
d'(x, f_x) \le \min\{d'(x, u^*) + d'(f, u^*), d(x, f)\} = d'(x, f).
$$

As a result, for every  $f \in \mathcal{F}$ , we have  $d'(x, f_x) \leq d'(x, f)$ . Combining with  $d'(x, f_x) \leq d'(x, u^*)$ (because of Equation [\(60\)](#page-49-1) and Equation [\(61\)](#page-49-2)), we conclude  $d'(x, \mathcal{F} + u^*) = d'(x, f_x)$ . Hence,

$$
d(x, \mathcal{F} + \mathcal{U}) = d(x, \mathcal{F}) = d(x, f_x) \stackrel{(61)}{=} d'(x, f_x) = d'(x, \mathcal{F} + u^*).
$$

The first equality is because of the assumption of this case that  $d(x, U) > d(x, \mathcal{F})$ . **Objective Function:** In each case, we showed  $d(x, \mathcal{F} + \mathcal{U}) = d'(x, \mathcal{F} + u^*)$  which concludes the lemma as follows.

$$
\begin{array}{rcl}\n\text{Cost}^d \left( \mathcal{F} + \mathcal{U}, \mathcal{P} \right) & = & \sum_{x \in \mathcal{P}} w(x) \cdot d(x, \mathcal{F} + \mathcal{U}) \\
& = & \sum_{x \in \mathcal{P} - \mathcal{U}} w(x) \cdot d(x, \mathcal{F} + \mathcal{U}) \\
& = & \sum_{x \in \mathcal{P} - \mathcal{U}} w(x) \cdot d'(x, \mathcal{F} + u^*) \\
& = & \sum_{x \in (\mathcal{P} - \mathcal{U}) + u^*} w(x) \cdot d'(x, \mathcal{F} + u^*) \\
& = & \text{Cost}^{d'} \left( \mathcal{F} + u^*, \mathcal{P}' \right).\n\end{array}
$$

Note that we used  $d'(u^*, \mathcal{F} + u^*) = 0$  and  $d(x, \mathcal{F} + \mathcal{U}) = 0$  for all  $x \in \mathcal{U}$ .

Now, assume F is the  $\beta$  approximate solution found by DEVELOP-CENTERS in line 4. Let

$$
\mathcal{F}^* = \arg\min_{\substack{\mathcal{F} \subseteq \mathcal{P}, \\|\mathcal{F}| \leq s}} \left\{ \text{Cost} \left( \mathcal{F} + \mathcal{U}, \mathcal{P} \right) \right\}.
$$

We have

$$
\begin{array}{rcl} \mathsf{Cost}^d\left(\mathcal{F}+\mathcal{U},\mathcal{P}\right) & = & \mathsf{Cost}^{d'}\left(\mathcal{F}+u^*,\mathcal{P}'\right) \\ \\ & = & \mathsf{Cost}^{d'}\left(\mathcal{F},\mathcal{P}'\right) \\ \\ & \leq & \beta ~\mathsf{OPT}^{d'}_{s+1}(\mathcal{P}') \\ \\ & \leq & \beta ~ \mathsf{Cost}^{d'}\left(\mathcal{F}^*+u^*,\mathcal{P}'\right) \\ \\ & = & \beta ~ \mathsf{Cost}^d\left(\mathcal{F}^*+\mathcal{U},\mathcal{P}\right), \end{array}
$$

where  $\text{OPT}_{s+1}^{d'}(\mathcal{P}')$  is the optimum  $(s+1)$ -median w.r.t. metric d' in space  $\mathcal{P}'$ . The first and the last equalities follow from Claim [11.4.](#page-48-2) The second equality follows from  $u^* \in \mathcal{F}$  (since  $w(u^*)$ ) is too large and since  $\mathcal F$  is  $\beta$ -approximate it should contain this point). The first inequality follows from the approximation ratio of solution F. The last inequality follows from the fact that  $\mathcal{F}^* + u^*$  is a set of size at most  $s + 1$ . Then we have the following as desired.

Cost 
$$
(\tilde{U}, \mathcal{P})
$$
 = Cost<sup>d</sup>  $(\mathcal{F} + \mathcal{U}, \mathcal{P}) \leq \beta$  Cost<sup>d</sup>  $(\mathcal{F}^* + \mathcal{U}, \mathcal{P}) = \beta \min_{\substack{\mathcal{F} \subseteq \mathcal{P}, \\ |\mathcal{F}| \leq s}} \text{Cost } (\mathcal{U} + \mathcal{F}, \mathcal{P})$ .

### <span id="page-50-0"></span>11.3 Fast-One-Median

The aim of this algorithm is to solve the 1-median problem on a set  $B$  as fast as possible. In order to find a single center which is a 3 approximate of  $\text{OPT}_1(B)$ , we sample a set S of  $\Theta(\log n)$  points from B independently. The sampling distribution is such that every  $p \in B$  is sampled proportional to its weight, i.e. with probability  $w(p)/w(B)$ . Then, we find the best center between these sampled points. So, we have the following algorithm.

Algorithm 8: FAST-ONE-MEDIAN( $B$ )

 $1 B \leftarrow \{b_1, b_2, \ldots, b_{|B|}\}\$ an arbitrary ordering.  $2 S \leftarrow \emptyset$ . 3 for  $\Theta(\log n)$  *iterations* do 4  $r \leftarrow [0, 1]$  uniformly at random. 5  $i^* \leftarrow$  smallest index such that  $\sum_{j=1}^{i^*} w(b_j) \geq r \cdot w(B)$ . 6  $S \leftarrow S + b_{i^*}.$  $\tau$   $q \leftarrow \arg \min \{ s \in S \mid \textsf{Cost}(s, B) \}.$ 8 return q.

<span id="page-50-1"></span>We show the following guarantee of this algorithm.

**Lemma 11.5.** If q is returned by FAST-ONE-MEDIAN(B), then with high probability,

 $Cost(q, B) \leq 3 \text{ OPT}_1(B).$ 

 $\Box$ 

Note that in this algorithm,  $q$  is a proper solution for 1-median problem on  $B$ , but in this lemma  $\text{OPT}_1(B)$  stands for the optimum improper solution. So, the solution of the algorithm is compared with the best improper solution, although it returns a proper solution.

*Proof.* Let  $m = |B|$  and  $z^*$  be the optimal solution to the improper 1-median problem in B. If y is sampled from the distribution where the probability of choosing p is  $w(p)/w(B)$ , then we have

$$
\mathbb{E}\left[\text{Cost}(y, B)\right] = \sum_{y \in B} \frac{w(y)}{w(B)} \text{Cost}(y, B) = \sum_{y \in B} \frac{w(y)}{w(B)} \sum_{x \in B} w(x) \cdot d(x, y)
$$
\n
$$
= \frac{1}{w(B)} \sum_{y \in B} \sum_{x \in B} w(y)w(x) \cdot d(x, y)
$$
\n
$$
\leq \frac{1}{w(B)} \sum_{y \in B} \sum_{x \in B} w(y)w(x) \cdot (d(x, z^*) + d(z^*, y))
$$
\n
$$
= \frac{1}{w(B)} \left[ \sum_{y \in B} w(y) \cdot \sum_{x \in B} w(x) \cdot d(x, z^*) + \sum_{x \in B} w(x) \cdot \sum_{y \in B} w(y) \cdot d(y, z^*) \right]
$$
\n
$$
= \sum_{x \in B} w(x) \cdot d(x, z^*) + \sum_{y \in B} w(y) \cdot d(y, z^*)
$$
\n
$$
= 2 \text{ OPT}_1(B).
$$

Thus, the expected approximation ratio of the 1-median solution  $y$  is at most 2. Hence, by Markov's inequality, the probability that the approximation ratio of sample  $\gamma$  is bigger than 3, is at most 2/3. Finally, since FAST-ONE-MEDIAN samples a set S of  $\Theta(\log n)$  points from B independently, the probability that all of these samples fail to have approximation ratio less than 3 is at most  $(2/3)^{|S|} = 1/n^{\Theta(1)}$ . As a result, with high probability there exists some  $y \in S$  such that Cost  $(y, B)$ 3 OPT<sub>1</sub> $(B)$ .

 $\Box$ 

# 12 Description of the Algorithm

In this section, we provide description of the algorithm as well as the main ideas and arguments on why the algorithm works correctly and how we achieve approximation, recourse and running time bounds.

The algorithm divides the input stream into some epochs on the fly. At the beginning of each epoch we have a solution  $\mathcal{U}^{(0)}$  of k centers for the current space  $\mathcal{P}^{(0)}$ . The solution is  $50\beta = O(1)^{17}$  $50\beta = O(1)^{17}$  $50\beta = O(1)^{17}$ approximate and is robust with respect to  $\mathcal{P}^{(0)}$ . Throughout the epoch we always maintain a  $O(\beta) = O(1)$  approximate solution. Then, at the end of the epoch we build a solution using only the initial solution  $\mathcal{U}^{(0)}$  of this epoch. So, this new solution is independent from the solutions maintained during the epoch. This new solution is going to be  $50\beta$  approximate and robust with respect to the new space and this is going to be the starting point of the next epoch. Now, we explain the algorithm on each epoch.

At the beginning of the epoch we find a value l such that

 $\Omega(1) \text{ OPT}_{k-l}(\mathcal{P}^{(0)}) \leq \text{OPT}_{k}(\mathcal{P}^{(0)}) \leq O(1) \text{ OPT}_{k+l}(\mathcal{P}^{(0)}).$ 

<span id="page-51-0"></span><sup>&</sup>lt;sup>17</sup>Recall  $\beta$  from Section [10.2.1](#page-36-1)

Note that the value of l could be zero. Next, we will find a subset of  $\mathcal{U}^{(0)}$  of size  $k-l$  like  $\mathcal{U}'$  whose cost is at most  $O(1)$  OPT<sub>k</sub>( $\mathcal{P}^{(0)}$ ). We call this part of the algorithm REMOVE-CENTERS. So, after this part, we have l and  $\mathcal{U}' \subseteq \mathcal{U}^{(0)}$  of size  $k - l$  with above guarantees.

Next, for l many iterations, we do lazy updates on  $\mathcal{U}'$  as follows. If a point gets inserted, we add it to  $\mathcal{U}'$ , and if a point gets deleted we do nothing (since we are dealing with the improper case, we can maintain a center in our main solution even if it gets deleted from the space). Obviously, during these updates the size of  $\mathcal{U}'$  is at most k which means our solution is valid. We will prove for l many iterations, this solution is a constant approximation for the value of  $\text{OPT}_k$  on the current space. We call this part of the algorithm LAZY-UPDATES.

Then, we do one more update to get the final space  $\mathcal{P}^{(l+1)}$  in this epoch. Now, we find a  $10\beta$ approximate solution  $\tilde{U}^{(0)}$  for  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$  by adding  $O(l+1)$  many centers to  $\mathcal{U}^{(0)}$ . Note that the solution might have more than  $k + l + 1$  centers, although our goal is to compete with  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$ . This is not obvious why such a solution exists. But, we show that it is possible and actually, the subroutine DEVELOP-CENTERS introduced in Section [11.2](#page-46-2) finds such a solution for this part.

Next, we add all of the inserted points during these  $l+1$  updates to  $\tilde{U}^{(0)}$  i.e.  $\mathcal{V} = \tilde{U}^{(0)} + (\mathcal{P}^{(l+1)} - \mathcal{P}^{(l+1)})$  $\mathcal{P}^{(0)}$ ). This is because we want a good solution for the new set of points  $\mathcal{P}^{(l+1)}$  and newly added points might be costly for  $\tilde{\mathcal{U}}^{(0)}$ . Note that if the weight of a point  $p \in \mathcal{P}^{(0)} \cap \mathcal{P}^{(l+1)}$  is changed (i.e. it gets deleted and then inserted with another weight), we consider it in  $\mathcal{P}^{(l+1)} - \mathcal{P}^{(0)}$ . Next, we reduce the size of V to get a subset of k centers W that is going to be a  $32\beta$  approximate solution for  $\text{OPT}_k(\mathcal{P}^{(l+1)})$ . We do this part by calling subroutine RAND-LOCAL-SEARCH introduced in Section [11.1.](#page-45-1)

So far, we have a solution W for the new set of point  $\mathcal{P}^{(l+1)}$  that satisfies  $|\mathcal{W}\oplus\mathcal{U}^{(0)}|=O(l+1)$ and is 32 $\beta$  approximate for  $\text{OPT}_k(\mathcal{P}^{(l+1)})$ . Next, we make solution W robust w.r.t. the new space  $\mathcal{P}^{(l+1)}$  and argue that it is actually a 50 $\beta$  approximate solution. We call this part of the algorithm ROBUSTIFY. Finally, we can start the next epoch with this new solution of  $k$  centers, since it is  $50\beta$  approximate and robust w.r.t. the new space.

So, we have the following pseudo-code for what we do in an epoch in a high level.  $\mathcal{P}^{(l)}$  in line 3 denotes the space after l updates in this epoch.

## Algorithm 9: MAIN-EPOCH $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)})$

 $1 \; (\mathcal{U}', l) \leftarrow \text{Remove-Centers}(\mathcal{U}^{(0)})$ . 2 LAZY-UPDATES $(\mathcal{U}', l)$ .  $\bm{3} \ \ \mathcal{P}^{(l+1)} \leftarrow \mathcal{P}^{(l)} \pm p_{l+1}.$  // read the  $(l+1)^{th}$  update.  $4 \tilde{U}^{(0)} \leftarrow$  DEVELOP-CENTERS $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, (8C+2)(l+1))$ . //  $C = 12 \cdot 3 \cdot 10^5 \gamma \beta^2$ .  $\mathfrak{v} \leftarrow \tilde{\mathcal{U}}^{(0)} + (\mathcal{P}^{(l+1)} - \mathcal{P}^{(0)}).$ 6  $W \leftarrow$  RAND-LOCAL-SEARCH $(V, |V| - k)$ . 7  $\mathcal{U}^{(l+1)} \leftarrow \text{RobustIFY}(\mathcal{P}^{(0)}, \mathcal{P}^{(l+1)}, \mathcal{U}^{(0)}, \mathcal{W}).$ 

### 12.1 Remove-Centers

Assume

<span id="page-52-1"></span>
$$
l^* = \arg \max \left\{ 0 \le l \le k \mid \text{OPT}_{k-l}(\mathcal{P}^{(0)}) \le 400\gamma\beta \text{ OPT}_{k}(\mathcal{P}^{(0)}) \right\}.
$$
 (64)

Note that  $\text{OPT}_k$  is considered in the improper case. We will find a value l' such that  $l' = \Omega(l^*)$ and

<span id="page-52-0"></span>
$$
\text{OPT}_{k-l'}(\mathcal{P}^{(0)}) \le 3 \cdot 10^5 \gamma \beta^2 \text{ OPT}_k(\mathcal{P}^{(0)}). \tag{65}
$$

Let  $\mathcal{R} = \{0, 2^0, 2^1, 2^2, \ldots, 2^{\lfloor \log k \rfloor} \}$ . We iterate over  $r \in \mathcal{R}$  in increasing order starting from 0, and call RAND-LOCAL-SEARCH $(\mathcal{U}^{(0)}, r)$  introduced in Section [11.1.](#page-45-1) If the cost of the subset returned by this subroutine is less than  $14 \cdot 400\gamma\beta$  Cost  $(\mathcal{U}^{(0)}, \mathcal{P}^{(0)})$ , we take the next  $r \in \mathcal{R}$  and repeat the process. We do this until reaching the maximum r' such that  $\mathcal{U}_{k-r'} = \text{RAND-LOCAL}$  $\text{SEARCH}(\mathcal{U}^{(0)}, r')$  satisfies

$$
\mathsf{Cost}\left(\mathcal{U}_{k-r'},\mathcal{P}^{(0)}\right)\le 14\cdot 400\gamma\beta\mathsf{Cost}\left(\mathcal{U}^{(0)},\mathcal{P}^{(0)}\right).
$$

Then, we let  $l' = r'$  (note that for simplicity, we have written this in the pseudo-code in a different way). Later, we will show that this l' satisfies Equation [\(65\)](#page-52-0) and  $l' \ge l^*/2$  with high probability. Next, we let  $l = \lfloor l'/C \rfloor$  where C is  $12 \cdot 400\gamma \beta \alpha^2$  and is determined using the Double-Sided Stability Lemma [10.10.](#page-39-0) Note that  $l + 1 = \Omega(l' + 1) = \Omega(l^* + 1)$  since C is a constant. We will prove that for this value of l we have the following guarantee.

$$
\frac{1}{3 \cdot 10^5 \gamma \beta^2} \, \text{OPT}_{k-l}(\mathcal{P}^{(0)}) \leq \text{OPT}_k(\mathcal{P}^{(0)}) \leq 4 \, \text{OPT}_{k+l}(\mathcal{P}^{(0)}).
$$

Next, we find a subset  $\mathcal{U}' \subseteq \mathcal{U}^{(0)}$  of size  $k - l$  such that

<span id="page-53-0"></span>
$$
\mathsf{Cost}\left(\mathcal{U}', \mathcal{P}^{(0)}\right) \le 2 \cdot 10^7 \gamma \beta^2 \, \mathsf{OPT}_{k+l}(\mathcal{P}^{(0)}).
$$
\n(66)

We do this by calling RAND-LOCAL-SEARCH $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, l)$ . So, we have the following algorithm for Remove-Centers.

Algorithm 10: REMOVE-CENTERS( $\mathcal{U}$ )

 $1 \mathcal{R} \leftarrow \{0, 2^0, 2^1, 2^2, \ldots, 2^{\lfloor \log k \rfloor} \}.$ 2 for  $r \in \mathcal{R}$  do 3  $\mathcal{U}_{k-r} \leftarrow \text{RAND-Local-SEARCH}(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, r).$  $\mathtt{4}\;\; \mid\; \; \text{if} \; \textsf{Cost}\left( \mathcal{U}_{k-r},\mathcal{P}^{(0)} \right) > 14\cdot 400 \gamma\beta \; \textsf{Cost}\left(\mathcal{U}^{(0)},\mathcal{P}^{(0)}\right) \; \textbf{then}$ 5 break for loop. 6  $l' \leftarrow \lfloor r/2 \rfloor$ . 7  $l \leftarrow \lfloor l'/C \rfloor$  where  $C = 12 \cdot 3 \cdot 10^5 \gamma \beta^2$ . 8  $\mathcal{U}' \leftarrow$  RAND-LOCAL-SEARCH $(\mathcal{U}, l)$ . 9 return  $(\mathcal{U}', l)$ .

## 12.2 Lazy-Updates

So far, we have  $\mathcal{U}'$  of size  $k - l$ . Now we perform l many updates in the input stream as follows. Whenever a point p gets inserted to space, we add it to  $\mathcal{U}'$  and if a point p gets deleted, we keep  $\mathcal{U}'$  unchanged. Note that since we deal with the improper dynamic k-median, we can maintain a center even if it gets deleted from the space. In order to prove this solution is actually a constant approximation of  $\text{OPT}_k(\mathcal{P})$ , where  $\mathcal P$  is the current space during these lazy updates, we combine the guarantee in Equation [\(66\)](#page-53-0) and Lazy Updates Lemma [10.9.](#page-39-1) This concludes our solution is always a constant approximation of  $\text{OPT}_k(\mathcal{P})$  for the current space  $\mathcal P$  during the next l updates.

Algorithm 11: LAZY-UPDATES( $\mathcal{U}', l$ )

1 for  $i = 1$  to l do 2 Read an update in the input stream. 3 if this update is insertion of p then 4  $\bigcup \mathcal{U}' \leftarrow \mathcal{U}' + p.$ 

### 12.3 Develop-Centers

This part starts after the  $(l + 1)$ 'th update in the input stream. So, we have the final set of points  $\mathcal{P}^{(l+1)}$ . We will add at most  $(8C+2)(l+1) = O(l+1)$  centers to  $\mathcal{U}^{(0)}$  to find a set  $\tilde{\mathcal{U}}^{(0)}$  such that

<span id="page-54-0"></span>
$$
\mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)}, \mathcal{P}^{(0)}\right) \le 10\beta \ \mathrm{OPT}_{k+l+1}(\mathcal{P}^{(0)}). \tag{67}
$$

We do this by calling DEVELOP-CENTERS $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, (8C+2)(l+1))$  introduced in Section [11.2.](#page-46-2) According to the guarantee of this subroutine, we get a  $\tilde{U}^{(0)}$  such that

$$
\mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)},\mathcal{P}^{(0)}\right) \leq \beta \min_{\substack{\mathcal{F} \subseteq \mathcal{P}^{(0)},\\|\mathcal{F}| \leq (8C+2)(l+1)}} \mathsf{Cost}\left(\mathcal{U}^{(0)} + \mathcal{F}, \mathcal{P}^{(0)}\right).
$$

In order to show that this  $\tilde{U}^{(0)}$  actually satisfies Equation [\(67\)](#page-54-0), it suffices to show that there exist  $\mathcal{F} \subseteq \mathcal{P}^{(0)}$  of size at most  $(8C+2)(l+1)$  such that  $\mathsf{Cost}\left(\mathcal{U}^{(0)}+\mathcal{F}, \mathcal{P}^{(0)}\right) \leq 10\;\text{OPT}_{k+l+1}(\mathcal{P}^{(0)}).$  We conclude this existential analysis by constructing  $\mathcal F$  using an optimum solution  $\mathcal V^*_{k+l+1}$  for  $(k+l+1)$ median problem on  $\mathcal{P}^{(0)}$ . We show that it suffices to add  $(8C+2)(l+1)$  many centers of  $\mathcal{V}_{k+l+1}^*$ to  $\mathcal{U}^{(0)}$  to get a constant approximation of  $\text{OPT}_{k+l+1}$ . These centers are elements of  $\mathcal{V}_{k+l+1}^*$  that does not form well-separated pair with any center in  $\mathcal{U}^{(0)}$ .

After termination of DEVELOP-CENTERS $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, (8C+2)(l+1))$ , we let  $\mathcal{V} = \tilde{\mathcal{U}}^{(0)} + (\mathcal{P}^{(l+1)} - \mathcal{V}^{(l+1)})$  $\mathcal{P}^{(0)}$ ). Note that we also consider points whose weight is changed. This concludes that V is a good set of centers in the new space  $\mathcal{P}^{(l+1)}$  as well as the initial space  $\mathcal{P}^{(0)}$ . The eventual conclusion is that

$$
\text{Cost}\left(\mathcal{V}, \mathcal{P}^{(l+1)}\right) \leq 10\beta \ \text{OPT}_k(\mathcal{P}^{(l+1)}).
$$

Next, we reduce the size of V to k in order to provide a feasible solution for  $\text{OPT}_k(\mathcal{P}^{(l+1)})$ . This part of the algorithm is done by calling RAND-LOCAL-SEARCH on  $\mathcal V$  to find a subset  $\mathcal W \subseteq \mathcal V$  of size k. Since we know that the cost of V on  $\mathcal{P}^{(l+1)}$  is at most  $10\beta \,\text{OPT}_k(\mathcal{P}^{(l+1)})$ , with the guarantee of RAND-LOCAL-SEARCH, we conclude that the cost of W on  $\mathcal{P}^{(l+1)}$  is at most 32 $\beta$  OPT<sub>k</sub>( $\mathcal{P}^{(l+1)}$ ) with high probability.

### 12.4 Robustify

So far we have a solution W which is  $32\beta$  approximate for  $\text{OPT}_k(\mathcal{P}^{(l+1)})$ . The aim of this part of the algorithm is to make  $W$ , robust w.r.t. the new space  $\mathcal{P}^{(l+1)}$ . Before we explain ROBUSTIFY, we define an integer  $t(u)$  for every center u. Throughout the algorithm, if U is our main solution, we always have an integer  $t(u)$  together with center u which indicates that u is  $t(u)$ -robust w.r.t. the current space. So, at the beginning of the epoch we know that every  $u \in \mathcal{U}^{(0)}$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(0)}$ .

Now, we explain how we make a robust solution w.r.t.  $\mathcal{P}^{(l+1)}$  by changing W. Recall from Definition [10.6](#page-38-1) that W is robust w.r.t.  $\mathcal{P}^{(l+1)}$ , whenever for all  $u \in \mathcal{W}$ , we have the following condition

<span id="page-54-1"></span>u is t-robust w.r.t.  $\mathcal{P}^{(l+1)}$ , where t is the smallest integer satisfying  $10^t \geq d(u, \mathcal{W}-u)/200$ . (68)

In this subroutine, we have a set  $S$  that helps us keep track of which elements violate Condition [68.](#page-54-1) First of all, we find some centers in  $W$  that might not satisfy this condition and put them into set S. We do this by calling FIND-SUSPECTS. Centers detected by FIND-SUSPECTS are going to be all centers  $u \in \mathcal{W}$  that u might not be  $t(u)$ -robust w.r.t. the new space  $\mathcal{P}^{(l+1)}$ , i.e. if a center  $u \in \mathcal{W}$ 

is not detected by FIND-SUSPECTS, then we are sure that u is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(l+1)}$ . Note that these centers found by FIND-SUSPECTS are not necessarily all of the centers violating Condition [68.](#page-54-1)

Then, we make all of the centers in  $S$  robust, by calling EMPTY-S. In this subroutine, for every  $w \in S$ , we determine the smallest integer t such that  $10^t \ge d(w, W - w)/100^{-18}$  $10^t \ge d(w, W - w)/100^{-18}$  $10^t \ge d(w, W - w)/100^{-18}$  and replace w by a center  $w_0$  via a call to MAKE-ROBUST $(w, t)$ . Now, this  $w_0$  satisfies Condition [68.](#page-54-1) We also remove w from S, define  $t(w_0) = t$  and save this integer with center  $w_0$ .

At this point, we are sure that every  $u \in \mathcal{W}$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(l+1)}$ . So, in order to figure out if a center  $u \in \mathcal{W}$  violates Condition [68,](#page-54-1) we make use of the integer  $t(u)$ . If t is the smallest integer satisfying  $10^t > d(u, W - u)/200$  and  $t < t(u)$ , then u definitely satisfies Condition [68.](#page-54-1)

Note that since W is changing, for every  $w \in W$ , the value of  $d(w, W - w)/200$  is changing as well. As a result, after each change in  $W$ , we should check whether or not any center in  $W$ violates Condition [68.](#page-54-1) If such a center exists, we add it to  $S$ . We keep adding new elements to S and removing elements from S (by EMPTY-S), until all of the centers in the current  $W$  satisfy Condition [68](#page-54-1) and  $\mathcal S$  in turn is empty. So, we have the following algorithm.



 $1 \mathcal{S} \leftarrow$  FIND-SUSPECTS $(\mathcal{P}^{(0)}, \mathcal{P}^{(l+1)}, \mathcal{W}, \mathcal{U}^{(0)})$ . 2 while true do  $3 \text{ if } \mathcal{S} = \emptyset \text{ then}$ 4 return 5 EMPTY-S $(S, \mathcal{W}, \mathcal{P}^{(l+1)}).$ 6 for  $u \in \mathcal{W}$  do 7  $t \leftarrow \lceil \log \left( d(u, \mathcal{W} - u)/200 \right) \rceil$ . 8 if  $t > t(u)$  then 9 |  $S \leftarrow S + u$ .

<span id="page-55-1"></span>It is not obvious why this algorithm terminates. But, we show that ROBUSTIFY calls MAKE-ROBUST on each center  $w \in \mathcal{W}$  at most once during a single call to ROBUSTIFY.

## Algorithm 13:  $\text{EMPTY-S}(\mathcal{S}, \mathcal{W}, \mathcal{P}^{(l+1)})$

1 pick w arbitrarily from  $S$ .  $2 \mathcal{S} \leftarrow \mathcal{S} - w.$  $\mathbf{3} \ \ t \leftarrow \left[ \log \left( d(w, \mathcal{W} - w)/100 \right) \right].$ 4 if  $t \geq 0$  then 5  $w_0 \leftarrow \text{MAKE-ROBUST}(\mathcal{P}^{(l+1)}, w, t).$ 6 else 7  $w_0 \leftarrow w$ .  $8 \t t \leftarrow 0.$  $9 \mathcal{W} \leftarrow \mathcal{W} - w + w_0.$ 10  $t(w_0) \leftarrow t$ .

In order to analyse the recourse, we show that the number of points added to  $S$  by calling FIND-SUSPECTS in the beginning of ROBUSTIFY is at most  $O(l + 1)$ . Then, we proceed by proving that the total recourse of the algorithm is  $O(1)$  in amortization. Note that during a single call to ROBUSTIFY the recourse might be as large as k, although we show the amortized recourse is  $O(1)$ throughout the total run of the algorithm (not just one epoch).

In order to analyse why the final solution is  $50\beta$  approximate, we show that the cost of the

<span id="page-55-0"></span><sup>&</sup>lt;sup>18</sup>Note that the denominator is 100 (not 200 as in Condition  $68$ ), this is because we want to prevent multiple calls to MAKE-ROBUST for a center. We use this in Lemma [13.1.](#page-57-0)

solution W is not going to increase by more than a factor of  $3/2$  by calling ROBUSTIFY.

As a result, we get the final solution of this epoch U which is robust and is also  $32\beta \times \frac{3}{2} \leq 50\beta$ approximate for  $\text{OPT}_k(\mathcal{P}^{(l+1)})$ .

#### 12.4.1 Find-Suspects

In this subroutine, we find all centers  $w \in \mathcal{W}$  that might not be  $t(w)$ -robust w.r.t. the new space  $\mathcal{P}^{(l+1)}$ . What we are looking for are the following centers.

- New centers u added to  $\mathcal{U}^{(0)}$  (i.e.  $u \in \mathcal{W} \mathcal{U}^{(0)}$ ).
- Centers  $u \in \mathcal{U}^{(0)} \cap \mathcal{W}$  whose neighborhood of radius  $2 \cdot 10^{t(u)}$  has changed during this epoch (i.e.  $\text{Ball}_{2 \cdot 10^{t(u)}}^{p^{(0)}}(u) \neq \text{Ball}_{2 \cdot 10^{t(u)}}^{p^{(l+1)}}(u)).$

Note that in both cases, we also consider the weight of the points. For instance, there might be a point p which is present in both  $\text{Ball}_{2 \cdot 10^{t(u)}}^{p^{(0)}}(u)$  and  $\text{Ball}_{2 \cdot 10^{t(u)}}^{p^{(l+1)}}(u)$ , but its weight has changed. In this case, we consider center u satisfying the second condition. So, we find all of the centers  $u \in \mathcal{W}$ satisfying at least one of the above conditions and add them to set S.



 $1 \mathcal{S} \leftarrow \mathcal{W} - \mathcal{U}^{(0)}.$ 2 for  $p \in \mathcal{P}^{(l+1)} \oplus \mathcal{P}^{(0)}$  do 3 for  $u \in \mathcal{U}^{(0)} \cap \mathcal{W}$  do 4 if  $d(u, p) \leq 2 \cdot 10^{t(u)}$  then  $\mathbf{5}$  | |  $\mathcal{S} \leftarrow \mathcal{S} + u.$ 6 return S.

Note that in line 2, we also consider points  $p \in \mathcal{P}^{(0)} \cap \mathcal{P}^{(l+1)}$  whose weight have changed. According to the definition of  $t(u)$ , we know that  $u \in \mathcal{U}^{(0)}$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(0)}$ . We will show that if a center  $u$  is not detected by FIND-SUSPECTS, i.e. does not satisfy any of the two above conditions, then it remains  $t(u)$ -robust with respect to the new space  $\mathcal{P}^{(l+1)}$ . This fact helps us argue that when the ROBUSTIFY subroutine is terminated, the solution  $\mathcal{U} = \text{ROBUSTIFY}(\mathcal{P}^{(0)}, \mathcal{P}^{(l+1)}, \mathcal{W}, \mathcal{U}^{(0)})$ is robust.

#### 12.4.2 Make-Robust

In this subroutine, we get a center w together with a non-negative integer t and return a center  $w_0$ , such that there exist a *t*-robust sequence like  $(w_0, w_1, \ldots, w_t)$  where  $w_t = w$ . To do this, we simply use the definition of t-robust sequence. Iterating over  $i$  from  $t$  to 1, assume that we have found the point  $w_i$  (initially  $w_t = w$ ). First, we check whether

$$
\text{AverageCost}\left(w_i, \text{Ball}_{10^i}^{\mathcal{P}}(w_i)\right) \ge 10^i/5.
$$

If this inequality holds, we simply let  $w_{i-1} = w_i$ . Otherwise, we find a 3 approximate solution  $q_i$  for 1-median problem on Ball $_{10i}^{\mathcal{P}}(w_i)$  using FAST-ONE-MEDIAN algorithm introduced in Section [11.3.](#page-50-0) Then, we let  $w_{i-1} = q_i$  if

$$
\mathsf{Cost}\left(q_i,\mathrm{Ball}_{10^i}^{\mathcal{P}}(w_i)\right) < \mathsf{Cost}\left(w_i,\mathrm{Ball}_{10^i}^{\mathcal{P}}(w_i)\right).
$$

Otherwise, we let  $w_{i-1} = w_i$ . With guarantees of FAST-ONE-MEDIAN algorithm, we prove that we achieve a t-robust sequence at the end of Make-Robust. So, we have the following algorithm.

Algorithm 15: MAKE-ROBUST $(\mathcal{P}, w, t)$ 

1  $w_t \leftarrow w$ . 2 for  $i = t$  down to 1 do  $\mathbf{3} \quad B_i \leftarrow \text{Ball}_{10^i}^{\mathcal{P}}(w_i).$  $4 \quad z \leftarrow$  AverageCost  $(w_i, B_i)$ . 5 if  $z \ge 10^i/5$  then 6  $w_{i-1} \leftarrow w_i$ . 7 else 8  $q_i \leftarrow \text{FAST-ONE-MEDIAN}(B_i, w_i).$  $\begin{array}{|c|c|} \hline \textbf{9} & \textbf{1} & \textbf{if } \textsf{Cost}\left(w_i,B_i\right) \leq \textsf{Cost}\left(q_i,B_i\right) \textbf{then} \hline \end{array}$ 10  $w_{i-1} \leftarrow w_i$ .  $11$  else 12  $w_{i-1} \leftarrow q_i$ . 13 return  $w_0$ .

Remark 12.1. Instead of FAST-ONE-MEDIAN, we can use the algorithm of [\[MP02\]](#page-75-0) to find a  $\beta$ -approximate solution  $q_i$  for 1-median problem on  $B_i$ .<sup>[19](#page-57-1)</sup>. But, if we do this, we lose another multiplicative factor of  $\beta$  on the approximation ratio in our final algorithm. We can prevent it by performing this simple FAST-ONE-MEDIAN subroutine instead of [\[MP02\]](#page-75-0).

# 13 Correctness of the Algorithm

Assume we have  $\mathcal{U}^{(0)}$  at the beginning of an epoch where  $\mathcal{U}^{(0)}$  is 50 $\beta$  approximate and it is also robust. The subroutine REMOVE-CENTERS, reduces the size of the solution to  $k - l$ , which means during the LAZY-UPDATES, we always maintain a solution of size at most  $k$  which is feasible. The approximation guarantee of RAND-LOCAL-SEARCH in Lemma [11.1](#page-46-3) holds with high probability. But, since we call REMOVE-CENTERS at most  $T$  times during any  $T$  updates of input stream, we conclude that (by a simple union bound) with high probability all of these guarantees hold.

Next, the  $(l+1)$ 'th update occurs. Then, algorithm adds some centers to  $\mathcal{U}^{(0)}$  and later reduces the size to k to get W which is feasible for the new space  $\mathcal{P}^{(l+1)}$ .

## 13.1 Robustify Calls Make-Robust Once for Each Center

<span id="page-57-0"></span>First, we show that ROBUSTIFY always terminates.

**Lemma 13.1** (Lemma 6.1 in [\[FLNS21\]](#page-75-1)). If ROBUSTIFY(W) calls a MAKE-ROBUST for a center  $w \in \mathcal{W}$  and replaces it with  $w_0$ , then it will not call MAKE-ROBUST on  $w_0$  until the end of the ROBUSTIFY subroutine.

*Proof.* Assume a MAKE-ROBUST call to a center  $w \in \mathcal{W}$  is made and it is replaced by  $w_0$ . Let  $W_1$  be the set of centers just before this call to MAKE-ROBUST is made on w. At this point of time,  $t(w_0)$  is the smallest integer satisfying  $10^{t(w_0)} \geq d(w, W_1 - w)/100$  (note that  $t(w_0) \geq 0$ , otherwise the algorithm should not have called Make-Robust duo to line 10 in the Robustify). For the sake of contradiction, assume that another call to MAKE-ROBUST is made on  $w_0$ . We assume that this pair w,  $w_0$  is the first pair for which this occurs. Let  $w' = \pi_{\mathcal{W}_1-w}(w)$  which means

<span id="page-57-1"></span><sup>&</sup>lt;sup>19</sup>Recall  $\beta$  from Section [10.2.1](#page-36-1)

 $d(w, W_1 - w) = d(w, w')$ . Then,  $10^{t(w_0)} \ge d(w, w') / 100$  and  $10^{t(w_0)} < d(w, w') / 10$  by definition of  $t(w_0)$ . So, by Lemma [10.3,](#page-37-0) we have

<span id="page-58-0"></span>
$$
d(w_0, w) \le 10^{t(w_0)}/2 \le d(w, w')/20.
$$
\n(69)

Assume  $\mathcal{W}_2$  is the set of centers just after the call to MAKE-ROBUST is made on  $w_0$ . Since we assumed  $w, w_0$  is the first pair that another call to MAKE-ROBUST on  $w_0$  is made, we have one of the two following cases.

•  $w' \in \mathcal{W}_2$ . In this case, we have

$$
d(w_0, \mathcal{W}_2 - w_0) \le d(w_0, w') \le d(w_0, w) + d(w, w') \le \frac{21}{20} d(w, w') \le 2 d(w, w').
$$

The last inequality holds by Equation [\(69\)](#page-58-0). This is in contradiction with the assumption that a call to MAKE-ROBUST on  $w_0$  is made, because  $w_0$  is  $t(w_0)$ -robust where  $10^{t(w_0)} \ge$  $d(w, w')/100 \geq d(w_0, \mathcal{W}_2 - w_0)/200$ . So, w<sub>0</sub> must not be selected to be added to S in ROBUSTIFY.

• There is  $w'_0 \in W_2$  that replaced w' by a single call to MAKE-ROBUST. When MAKE-ROBUST is called on w', the algorithm picks integer  $t(w'_0)$  that satisfies  $10^{t(w'_0)} \leq d(w', w_0)/10$  (otherwise, it should have picked  $t(w_0') - 1$  instead of  $t(w_0')$ ). Hence,

<span id="page-58-1"></span>
$$
d(w'_0, w') \le 10^{t(w'_0)}/2 \le d(w', w_0)/20 \le (d(w_0, w) + d(w, w'))/20 \le d(w, w')/10.
$$
 (70)

The first inequality holds by Lemma [10.3](#page-37-0) and the last inequality is Equation [\(69\)](#page-58-0). As a result,

$$
d(w_0, W_2 - w_0) \le d(w_0, w'_0)
$$
  
\n
$$
\le d(w_0, w) + d(w, w') + d(w', w'_0)
$$
  
\n
$$
\le d(w, w')/20 + d(w, w') + d(w, w')/10
$$
  
\n
$$
= \frac{23}{20} d(w, w')
$$
  
\n
$$
\le 2 d(w, w').
$$

The last inequality holds by Equation  $(69)$  and Equation  $(70)$ . This leads to the same contradiction.

 $\Box$ 

## 13.2 Correctness of Robustify

Consider a call to ROBUSTIFY occurs on W. First, in FIND-SUSPECTS, all of the centers  $u \in \mathcal{W}$ satisfying  $u \in \mathcal{W} - \mathcal{U}^{(0)}$  or  $d(p, u) \leq 2 \cdot 10^{t(u)}$  for at least one  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$  are added to S. We know that each center  $u \in \mathcal{W} \cap \mathcal{U}^{(0)}$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(0)}$  at the beginning of epoch. We now prove the following.

<span id="page-58-2"></span>**Lemma 13.2.** Assume  $u \in \mathcal{U}^{(0)}$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(0)}$  and S is returned by FIND-SUSPECTS. If  $u \notin \mathcal{S}$ , then u is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(l+1)}$  as well.

*Proof.* Let  $(p_0, \ldots, p_{t(u)})$  be a  $t(u)$ -robust sequence w.r.t.  $\mathcal{P}^{(0)}$ , where  $p_0 = u$ . According to Lemma [10.3,](#page-37-0)  $d(p_0, p_{t(u)}) \leq 10^{t(u)}/2$  which concludes

$$
\text{Ball}_{10^{t(u)}}^{\mathcal{P}^{(0)}}(p_{t(u)}) \subseteq \text{Ball}_{2 \cdot 10^{t(u)}}^{\mathcal{P}^{(0)}}(u).
$$

Because, the ball around u of radius  $2 \cdot 10^{t(u)}$  is not changed (i.e.  $\text{Ball}_{2 \cdot 10^{t(u)}}^{\mathcal{P}^{(0)}}(u) = \text{Ball}_{2 \cdot 10^{t(u)}}^{\mathcal{P}^{(l+1)}}(u)$ considering points by their weight), we conclude that ball around  $p_{t(u)}$  of radius  $10^{t(u)}$  is also not changed. Finally, with the definition of  $t(u)$ -robust sequence we conclude that  $(p_0, \ldots, p_{t(u)})$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(l+1)}$  as well. So,  $p_0 = u$  is  $t(u)$ -robust w.r.t.  $\mathcal{P}^{(l+1)}$ .  $\Box$ 

Assume  $\mathcal{U} = \text{RobustIFY}(P^{(0)}, P^{(l+1)}, W, \mathcal{U}^{(0)})$  is the final solution of the algorithm for  $\mathcal{P}^{(l+1)}$ . According to above lemma and description of the algorithm, we show that  $U$  is robust.

By Lemma [13.1](#page-57-0) we know that ROBUSTIFY calls MAKE-ROBUST on each  $u \in \mathcal{W}$  at most once. According to the proof of this lemma, if a center  $u \in \mathcal{U}$  is returned by a call to MAKE-ROBUST on center  $u' \in \mathcal{W}$ , then u does not violate Condition [68.](#page-54-1) Now, assume no call to MAKE-ROBUST was made on  $u \in \mathcal{W}$ . Hence, u was not found by FIND-SUSPECTS, and by Lemma [13.2,](#page-58-2) we conclude u is  $t(u)$ -robust w.r.t. the new set of points  $\mathcal{P}^{(l+1)}$ . Let t be the smallest integer such that  $10^t \geq d(u, \mathcal{U} - u)/200$ . Since u was not added to S, we conclude that  $t(u) \geq t$  (See Line [8](#page-55-1)) of ROBUSTIFY). So, u is t-robust w.r.t.  $\mathcal{P}^{(l+1)}$  which means u does not violate Condition [68](#page-54-1) for current  $U$ . As a result, the final  $U$  returned by ROBUSTIFY is robust.

Later, in Section [15.2,](#page-65-0) we show that it is also  $50\beta$  approximate. This means that the final solution of the algorithm at the end of the epoch satisfies the conditions needed as the initial solution of the next epoch.

#### 13.3 Correctness of Make-Robust

Assume a call to MAKE-ROBUST on  $(\mathcal{P}, w, t)$ . In order to show that the returned value  $w_0$  is actually a t-robust point w.r.t.  $P$ , we check the definition of t-robust sequence. According to the subroutine MAKE-ROBUST and the definition of t-robust sequence, we only need to show that for every  $1 \leq$  $i \leq t$ , the returned point  $q_i$  by FAST-ONE-MEDIAN( $B_i, w_i$ ) satisfies Cost  $(q_i, B_i) \leq 3$  OPT<sub>1</sub>( $B_i$ ). This is also the guarantee of FAST-ONE-MEDIAN in Lemma [11.5.](#page-50-1)

Later, in Section [14,](#page-59-0) we show that the total number of times that we call MAKE-ROBUST throughout the first T updates of the input stream is  $O(T)$ . Hence, with high probability all of these independent calls to MAKE-ROBUST return correctly.

## <span id="page-59-0"></span>14 Recourse Analysis

In this section, we provide the recourse analysis of the algorithm. We show the following lemma.

**Lemma 14.1.** The Total recourse of the algorithm throughout the first  $T$  updates is at most

$$
O(T(\log \Delta)^2).
$$

## 14.1 Difference Between  $\mathcal{U}^{(0)}$  and  $\mathcal{W}$

In DEVELOP-CENTERS, we are adding at most  $(8C+2)(l+1)$  centers to  $\mathcal{U}^{(0)}$  to make  $\tilde{\mathcal{U}}^{(0)}$ . Then, we add  $\mathcal{P}^{(l+1)} - \mathcal{P}^{(0)}$  to get V. As a result, the size of V is at most  $k + (8C + 3)(l + 1)$ . Next, we reduce the size of this set to k by calling RAND-LOCAL-SEARCH on  $\mathcal V$ . Since both of  $\mathcal U^{(0)}$  and  $\mathcal W$ are subsets of size  $k$  of set  $\mathcal V$ , we conclude that

$$
|\mathcal{W} \oplus \mathcal{U}^{(0)}| \leq 2 \cdot ((8C+3)(l+1)) \leq 20C(l+1).
$$

<span id="page-59-1"></span>So, we have the following lemma.

**Lemma 14.2.** For every epoch of length  $l + 1$ , we have  $|W \oplus U^{(0)}| < 20C(l + 1)$ .

### 14.2 Number of Centers Detected by Find-Suspects

At the beginning of FIND-SUSPECTS, the algorithm sets  $S = W - U^{(0)}$ . As a result, the size of this initial S is at most  $20C(l + 1)$  by Lemma [14.2.](#page-59-1) Next, for every point p that has gone through an update (either insertion or deletion) in this epoch (i.e.  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$ ) the algorithm finds all centers  $u \in \mathcal{W} \cap \mathcal{U}^{(0)}$  such that  $d(u, p) \leq 2 \cdot 10^{t(u)}$ . We claim that for a fix  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$ , there are at most  $O(\log \Delta)$  many centers u that satisfy this property.

<span id="page-60-0"></span>**Lemma 14.3.** For each  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$ , the number of  $u \in \mathcal{W} \cap \mathcal{U}^{(0)}$  satisfying  $d(p, u) \leq 2 \cdot 10^{t(u)}$ is at most  $O(\log \Delta)$ .

*Proof.* Assume  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$ . Let  $\mu$  be the number of centers  $u \in \mathcal{W} \cap \mathcal{U}^{(0)}$  that satisfy  $d(p, u) \leq 2 \cdot 10^{t(u)}$ . For each of these centers like u, there is a u' that was added to S and a call to MAKE-ROBUST was made on u' which returned u. Assume  $\{u_1, u_2, \ldots, u_\mu\}$  is the set of centers u satisfying  $d(p, u) \leq 2 \cdot 10^{t(u)}$  ordered in decreasing order by the time they replaced  $u'_i$  via a call to MAKE-ROBUST. So, when  $u_i$  is added to the main solution, center  $u_{i+1}$  was already present in the main solution which concludes

$$
10^{t(u_i)} \le d(u_i, u_{i+1})/10,
$$

by the definition of  $t(u_i)$  at that time for every  $1 \leq i \leq \mu - 1$ . Hence,

$$
10^{t(u_{i+1})} \ge d(p, u_{i+1})/2 \ge (d(u_i, u_{i+1}) - d(p, u_i))/2 \ge 5 \cdot 10^{t(u_i)} - 10^{t(u_i)} = 4 \cdot 10^{t(u_i)}.
$$

The first and last inequality holds by the assumption that  $d(p, u) \leq 2 \cdot 10^{t(u)}$  for every  $u \in$  $\{u_1, \ldots, u_\mu\}$ . Finally, this concludes  $t(u_\mu) > \cdots > t(u_2) > t(u_1)$ . Since we assumed the distances between any two point in the space is between 1 and  $\Delta$ , we know  $0 \leq t(u_i) \leq \lceil \log \Delta \rceil$  for each  $1 \leq i \leq \mu$  and so,  $\mu \leq (\log \Delta) + 2 = O(\log \Delta)$ .

<span id="page-60-1"></span>A quick corollary of this lemma is the following.

Corollary 14.4. The size of final S returned by FIND-SUSPECTS in an epoch of length  $l + 1$  is at most  $O((l + 1) \log \Delta)$ .

Proof. By Lemma [14.2](#page-59-1) and Lemma [14.3,](#page-60-0) we have

$$
|\mathcal{S}| \le 10C(l+1) + |\mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}| \cdot O(\log \Delta) = O((l+1)\log \Delta).
$$

### 14.3 Total Recourse

Assume the sequence of first T updates in the input stream. We show the total recourse of the algorithm during these T updates is at most  $O(T(\log \Delta)^2)$ . Consider that the algorithm performs E epochs in total. For every  $1 \le e \le E$ , let  $l_e + 1$ ,  $\mathcal{U}_e^{(0)}$  and  $\mathcal{W}_e$  be the length of, initial solution and the set of centers returned by RAND-LOCAL-SEARCH just before calling ROBUSTIFY in epoch e respectively. For every  $1 \le e \le E$  and every  $1 \le i \le l_e + 1$ , let  $\mathcal{U}_e^{(i)}$  be the main solution of the algorithm after the  $i$ 'th update in epoch  $e$ . As a result, the total recourse of the algorithm equals.

$$
\sum_{e=1}^{E} \sum_{i=0}^{l_e} |\mathcal{U}_e^{(i+1)} - \mathcal{U}_e^{(i)}|.
$$



The recourse after each lazy update is at most 1, which concludes for every  $1 \le e \le E$ , we have

$$
\sum_{i=0}^{l_e} |\mathcal{U}_e^{(i+1)} - \mathcal{U}_e^{(i)}| \leq l_e + |\mathcal{U}_e^{(l_e+1)} - \mathcal{U}_e^{(l_e)}|
$$
  

$$
\leq l_e + |\mathcal{U}_e^{(l_e)} - \mathcal{U}_e^{(0)}| + |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}|
$$
  

$$
\leq 2l_e + |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}|.
$$

Hence,

$$
\sum_{e=1}^{E} \sum_{i=0}^{l_e} |\mathcal{U}_e^{(i+1)} - \mathcal{U}_e^{(i)}| \le \sum_{e=1}^{E} \left( 2l_e + |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}| \right) \le 2T + \sum_{e=1}^{E} |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}|.
$$

So, it suffices to prove

$$
\sum_{e=1}^{E} |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}| = O(T(\log \Delta)^2).
$$

Recall Lemma [13.1.](#page-57-0) This lemma states that the ROBUSTIFY calls a MAKE-ROBUST on every center  $w \in \mathcal{W}$  at most once. So, if a center u is added to S in ROBUSTIFY, it is not going to be added to  $S$  in this call to ROBUSTIFY again. According to the ROBUSTIFY, it is obvious that  $\sum_{e=1}^{E} |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}|$  is at most the number of times that elements are added to S.

Now, we create a graph during the run of the algorithm as follows. The graph is a union of disjoint directed paths. Each node of the graph is alive or dead. At any time, every center in the main solution of the algorithm is corresponding to an alive node in this graph. A center might be corresponding to several nodes in the graph (since it can be added to  $\mathcal S$  several times during the total run of the algorithm), but it is corresponding to only one alive node.

Initially, the graph consists of  $k$  alive nodes corresponding to the initial solution of  $k$  centers at the very beginning of the algorithm. Now, we explain how we change the graph during the algorithm. At the end of the epoch, we mark all of the nodes corresponding to centers  $\mathcal{U}^{(0)} - \mathcal{W}$  as dead. Assume a center  $u \in \mathcal{W}$  at the end of an epoch. We have the following cases.

- $u \notin \mathcal{U}^{(0)}$ . In this case, we know that there is no alive node in the graph corresponding to u. We add a new alive node to the graph corresponding to  $u$ . This would be the starting node of a new path in the graph.
- $u \in \mathcal{U}^{(0)}$  and u is detected by FIND-SUSPECTS. In this case, we know that u is corresponding to an alive node  $V_u$  in the graph. We mark this node  $V_u$  dead and add a new alive node corresponding to  $u$  in the graph. This is also the starting node of a new path in the graph.
- $u \in \mathcal{U}^{(0)}$  and u is not detected by FIND-SUSPECTS, but u is added to S during the ROBUSTIFY. In this case, we know that  $u$  is corresponding to an alive node  $V_u$  in the graph and also  $u$ is going to be replaced by  $u_0$  by a call to MAKE-ROBUST. We mark  $V_u$  as dead, add a new node  $V_{u_0}$  corresponding to  $u_0$  in the graph and draw a directed edge from  $V_u$  to  $V_{u_0}$ .
- $u \in \mathcal{U}^{(0)}$  and u is not detected by FIND-SUSPECTS, and u is not added to S during the ROBUSTIFY. In this case, we do not change the graph.

According to this construction of the graph, the total number of paths in the graph is equal to the total number of centers detected by FIND-SUSPECTS and the total number of nodes in the graph is equal to the total number of elements added to  $S$  during the entire run of the algorithm.

Figure 1: The constructed graph looks like this. If a center is detected by FIND-SUSPECTS, it would be the end of the path. If a MAKE-ROBUST is called on a center, the path ending in the node corresponding to this center is extended.



By Corollary [14.4,](#page-60-1) the number of centers detected by  $\overline{F}$  IND-SUSPECTS at the end of epoch e is at most  $O((l_e + 1) \log \Delta)$ . As a result, the total number of centers detected by FIND-SUSPECTS, during the run of the algorithm for the first T updates of the input stream is at most  $O(T \log \Delta)$ . This concludes the number of paths of the graph is  $O(T \log \Delta)$ .

Now, we show that the length of each path in the graph is at most  $O(\log \Delta)$ . This completes the analysis. Consider centers  $u_1, u_2, \ldots, u_r$  corresponding to the directed path  $V_{u_1}, V_{u_2}, \ldots, V_{u_r}$  in this graph. First, note that for every  $1 \leq i \leq r-1$ , center  $u_i$  is not detected by FIND-SUSPECTS during the algorithm. Otherwise, we would have marked  $V_{u_i}$  as dead and  $V_{u_i}$  would have been the end of the path. The only reason that  $u_i$  is added to S is that  $10^{t(u_i)} < d(u_i, \mathcal{U} - u_i)/200$ . In this case, the algorithm picks the smallest integer t satisfying  $10^t \geq d(u_i, \mathcal{U} - u_i)/100$ , replaces  $u_i$  with  $u_{i+1}$  by a call to MAKE-ROBUST $(u_i, t)$  and sets  $t(u_{i+1}) = t$ . As a result, we have

$$
10^{t(u_i)} < d(u_i, \mathcal{U} - u_i)/200 < d(u_i, \mathcal{U} - u_i)/100 \le 10^{t(u_{i+1})}
$$

for every  $1 \leq i \leq r-1$ . Hence,  $t(u_1) \leq t(u_2) \leq \cdots \leq t(u_r)$ . Since, we assumed the maximum distance between any two points in the metric space is at most  $\Delta$ , we conclude that  $t(u_i) \leq \lceil \log \Delta \rceil$ for every  $1 \leq i \leq r$ . Together with  $t(u_1) < t(u_2) < \cdots < t(u_r)$ , we conclude that  $r \leq \lceil \log \Delta \rceil + 1 =$  $O(\log \Delta)$ .

Putting everything together, the number of paths in the graph is at most  $O(T \log \Delta)$  and the length of each path is at most  $O(\log \Delta)$ , which concludes the total number of nodes in the created graph is at most  $O(T(\log \Delta)^2)$ . Hence, the total number of elements added to S during the run of the algorithm is at most  $O(T(\log \Delta)^2)$ . Finally, this implies

$$
\sum_{e=1}^{E} |\mathcal{U}_e^{(0)} - \mathcal{U}_e^{(l_e+1)}| = O(T(\log \Delta)^2),
$$

which completes the analysis of recourse.

## 15 Approximation Ratio Analysis

In this section we prove that the approximation ratio of the algorithm is constant.

Important note: Since, subroutines RAND-LOCAL-SEARCH and FAST-ONE-MEDIAN are randomised and their approximation guarantee hold with high probability, some of the lemmas in this section occur with high probability. But, we omit repeating this phrase over and over and provide the statements without it. Assume  $T$  many updates in the input stream. According to the algorithm, we call RAND-LOCAL-SEARCH at most  $O(T)$  times. According to the recourse analysis in Section [14,](#page-59-0) we call FAST-ONE-MEDIAN at most  $O(T)$  times. As a result, we can conclude that all of these subroutines simultaneously return correctly with high probability. So, we omit using w.h.p. in the analysis in this section.

Assume that  $\mathcal{U}^{(0)}$  at the beginning of an epoch has approximation ratio 50 $\beta$ . We will prove during the epoch, approximation ratio of our solution at any time is at most  $2 \cdot 10^7 \gamma \beta^2$ . Then, we prove that the approximation ratio of final  $\mathcal U$  at the end of epoch is 50 $\beta$  which is the starting point of the next epoch. Since the approximation ratio of the algorithm would be very large even if we optimize the parameters, we do not bother to use tight inequalities in the proofs.

## 15.1 Analysis of Remove-Centers and Lazy-Updates

We start by analyzing REMOVE-CENTERS. Assume  $\mathcal{R} = \{0, 2^0, 2^1, 2^2, \ldots, 2^{\lfloor \log k \rfloor} \}$  and

$$
l^* = \arg \max \left\{ 0 \le l \le k \mid \text{OPT}_{k-l}(\mathcal{P}^{(0)}) \le 400\gamma\beta \text{ OPT}_{k}(\mathcal{P}^{(0)}) \right\}.
$$

According to REMOVE-CENTERS, the value of  $l'$  is the maximum number in  $R$  such that

$$
\mathsf{Cost}\left(\mathcal{U}_{k-l'}, \mathcal{P}^{(0)}\right) \leq 14 \cdot 400 \gamma \beta \, \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right).
$$

<span id="page-63-0"></span>Next, the algorithm sets  $l = \lfloor l'/C \rfloor$ . Now, we show good properties of this choice of l.

Lemma 15.1. We have

$$
\text{OPT}_{k-l'}(\mathcal{P}^{(0)}) \leq 3 \cdot 10^5 \gamma \beta^2 \text{ OPT}_k(\mathcal{P}^{(0)}).
$$

*Proof.* According to the definition of  $l'$ , we have

$$
\begin{array}{rcl}\n\text{OPT}_{k-l'}(\mathcal{P}^{(0)}) & \leq & \text{Cost}\left(\mathcal{U}_{k-l'}, \mathcal{P}^{(0)}\right) \\
& \leq & 14 \cdot 400\gamma\beta \text{ Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) \\
& \leq & 50\beta \cdot 14 \cdot 400\gamma\beta \text{ OPT}_k(\mathcal{P}^{(0)}) \\
& \leq & 3 \cdot 10^5\gamma\beta^2 \text{ OPT}_k(\mathcal{P}^{(0)}).\n\end{array}
$$

<span id="page-63-1"></span>**Lemma 15.2.** We have  $l + 1 \ge (l^* + 1)/(2C)$ .

*Proof.* First, we show that  $l' \geq l^*/2$ . We have three cases:

- $l^* = 0$ . The inequality is obvious.
- $l^* \geq 1$  and  $l' = 0$ . In this case, the value of  $l'' = 1 \in \mathcal{R}$  (which is bigger than  $l'$ ) also satisfies

$$
\begin{array}{lcl} \mathsf{Cost}\left(\mathcal{U}_{k-l''}, \mathcal{P}^{(0)}\right) & \leq & 2 \; \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) + 12 \; \mathsf{OPT}_{k-l''}(\mathcal{P}^{(0)}) \\ \\ & \leq & 2 \; \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) + 12 \; \mathsf{OPT}_{k-l^*}(\mathcal{P}^{(0)}) \\ \\ & \leq & 2 \; \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) + 12 \cdot 400\gamma\beta \; \mathsf{OPT}_k(\mathcal{P}^{(0)}) \\ \\ & \leq & \left(14 \cdot 400\gamma\beta\right) \; \mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right). \end{array}
$$

The first inequality holds by the guarantee of RAND-LOCAL-SEARCH in Lemma [11.1,](#page-46-3) the second one holds since  $l'' \geq l^*$ , and the third one holds by the definition of  $l^*$ . This is in contradiction with the choice of  $l' \in \mathcal{R}$  in the algorithm, since  $l'' > l'$  and the algorithm must have picked  $l''$  instead of  $l'$ .

•  $l^* \geq 1$  and  $l' \geq 1$ . In this case if we have  $l' < l^*/2$ , then the above argument works for  $l'' = 2l' \in \mathcal{R}$  which leads to the same contradiction (note that since  $l^{*}/2 \leq k/2$ , then  $l'' \leq k$ must be in  $\mathcal{R}$ ).

So, we have  $l' \geq l^*/2$ . Since both of l' and C are integers, we have  $l+1 \geq l'/C+1/C$ . Hence,  $l + 1 \ge (l' + 1)/C \ge (l^* + 1)/(2C).$ 

<span id="page-64-0"></span>Lemma 15.3. We have

$$
\frac{1}{3 \cdot 10^5 \gamma \beta^2} \ \text{OPT}_{k-l}(\mathcal{P}^{(0)}) \leq \text{OPT}_k(\mathcal{P}^{(0)}) \leq 4 \ \text{OPT}_{k+l}(\mathcal{P}^{(0)}).
$$

Proof. Using Double-Sided Stability Lemma [10.10,](#page-39-0) we easily conclude that the algorithm picks an l with the property that both of  $\text{OPT}_{k-l}(\mathcal{P}^{(0)})$  and  $\text{OPT}_{k+l}(\mathcal{P}^{(0)})$  are within a constant factor of  $\text{OPT}_k(\mathcal{P}^{(0)})$  as desired. More precisely, let  $\eta = 3 \cdot 10^5 \gamma \beta^2$  and  $r = l'$  in Double-Sided Stability Lemma [10.10.](#page-39-0) Note that

$$
\lfloor r/(12\eta)\rfloor = \lfloor l'/(12 \cdot 3 \cdot 10^5 \gamma \beta^2) \rfloor = \lfloor l'/C \rfloor = l.
$$

According to Lemma [15.1,](#page-63-0) we have  $\text{OPT}_{k-r}(\mathcal{P}^{(0)}) \leq \eta \text{ OPT}_{k}(\mathcal{P}^{(0)})$ . Hence,

$$
\text{OPT}_k(\mathcal{P}^{(0)}) \le 4 \text{ OPT}_{k+|r/(12\eta)|}(\mathcal{P}^{(0)}) = 4 \text{ OPT}_{k+1}(\mathcal{P}^{(0)}).
$$

Since  $l' \geq l$ , Lemma [15.1](#page-63-0) concludes

$$
\text{OPT}_{k-l}(\mathcal{P}^{(0)}) \leq \text{OPT}_{k-l'}(\mathcal{P}^{(0)}) \leq 3 \cdot 10^5 \gamma \beta^2 \text{ OPT}_k(\mathcal{P}^{(0)}).
$$

<span id="page-64-1"></span>Next, we bound the cost of  $\mathcal{U}'$  returned by Rand-Local-Search $(\mathcal{U}^{(0)}, l)$ .

Lemma 15.4. We have

$$
\mathsf{Cost}\left(\mathcal{U}', \mathcal{P}^{(0)}\right) \leq 2 \cdot 10^7 \gamma \beta^2 \; \text{OPT}_{k+l}(\mathcal{P}^{(0)}).
$$

Proof. According to Lemma [11.1](#page-46-3) and Lemma [15.3,](#page-64-0)

Cost 
$$
(\mathcal{U}', \mathcal{P}^{(0)}) \leq 2 \text{ Cost } (\mathcal{U}^{(0)}, \mathcal{P}^{(0)}) + 12 \text{ OPT}_{k-l}(\mathcal{P}^{(0)})
$$
  
\n $\leq 2 \cdot (50\beta) \text{ OPT}_{k}(\mathcal{P}^{(0)}) + 12 \cdot (3 \cdot 10^5 \gamma \beta^2) \text{ OPT}_{k}(\mathcal{P}^{(0)})$   
\n $\leq 4 \cdot 10^6 \gamma \beta^2 \text{ OPT}_{k}(\mathcal{P}^{(0)})$   
\n $\leq 4 \cdot (4 \cdot 10^6 \gamma \beta^2) \text{ OPT}_{k+l}(\mathcal{P}^{(0)})$   
\n $\leq 2 \cdot 10^7 \gamma \beta^2 \text{ OPT}_{k+l}(\mathcal{P}^{(0)}).$ 



 $\Box$ 

Finally, we show that the maintained solution during the lazy updates is a constant approximation of  $OPT_k$  on the current space. Assume that  $1 \leq i \leq l$  updates has happened to  $\mathcal{P}^{(0)}$  and we have the current set of points  $\mathcal{P}^{(i)}$ . According to the algorithm, the solution for this set of points is  $\mathcal{U}^{(i)}$  such that  $\mathcal{U}' + (\mathcal{P}^{(i)} - \mathcal{P}^{(0)}) \subseteq \mathcal{U}^{(i)}$ . Note that there might be some point p that has been added during these i updates and then deleted. So, p is not present in  $\mathcal{P}^{(i)} - \mathcal{P}^{(0)}$ , but it is present in our solution  $\mathcal{U}^{(i)}$ . As a result, LAZY-UPDATES Lemma [10.9](#page-39-1) and Lemma [15.4](#page-64-1) conclude

$$
\begin{array}{rcl} \mathsf{Cost}\left(\mathcal{U}^{(i)}, \mathcal{P}^{(i)}\right) & \leq & \mathsf{Cost}\left(\mathcal{U}'+(\mathcal{P}^{(i)}-\mathcal{P}^{(0)}), \mathcal{P}^{(i)}\right) \\ \\ & \leq & \mathsf{Cost}\left(\mathcal{U}', \mathcal{P}^{(0)}\right) \\ \\ & \leq & 2\cdot 10^7 \gamma \beta^2 \ \mathrm{OPT}_{k+l}(\mathcal{P}^{(0)}) \\ \\ & \leq & 2\cdot 10^7 \gamma \beta^2 \ \mathrm{OPT}_k(\mathcal{P}^{(i)}). \end{array}
$$

<span id="page-65-4"></span>So, we have the following.

**Corollary 15.5.** The approximation ratio of algorithm during LAZY-UPDATES is at most  $2 \cdot 10^7 \gamma \beta^2$ .

### <span id="page-65-0"></span>15.2 Analysis of Develop-Centers

In this section, we show  $\tilde{\mathcal{U}}^{(0)}$  returned by Develop-Centers is  $10\beta$  approximate for  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$ .

We start by proving that it is possible to add at most  $O(l+1)$  points to  $\mathcal{U}^{(0)}$  to obtain a set of centers  $\tilde{U}$  which is 10 approximate of  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$ . Then, we show DEVELOP-CENTERS finds  $\tilde{U}^{(0)}$  that is 10 $\beta$  approximate of  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$ . Assume  $\mathcal{V}_{k+l+1}^*$  is the optimum **proper** solution of size  $k+l+1$  for  $(k+l+1)$ -median problem on  $\mathcal{P}^{(0)}$  (we will use the assumption that this is a proper solution in Lemma [15.8\)](#page-67-0). Note that  $\text{OPT}_{k+l+1}(\mathcal{P}^{(0)})$  stands for the optimum improper solution. According to Lemma [10.8,](#page-38-2)  $\mathcal{V}_{k+l+1}^*$  is a 2 approximate solution for the improper  $(k+l+1)$ -median on  $\mathcal{P}^{(0)},$  i.e.

<span id="page-65-2"></span>
$$
\mathsf{Cost}\left(\mathcal{V}_{k+l+1}^*, \mathcal{P}^{(0)}\right) \le 2 \, \mathrm{OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$
\n
$$
(71)
$$

<span id="page-65-3"></span>**Lemma 15.6.** If the number of well-separated pairs with respect to  $(\mathcal{U}^{(0)}, \mathcal{V}_{k+l+1}^*)$  is  $k - m$ , then there exists  $\mathcal{V}' \subseteq \mathcal{V}_{k+l+1}^*$  of size at most  $m+l+1$  such that

$$
\text{Cost}\left(\mathcal{U}^{(0)}+\mathcal{V}',\mathcal{P}^{(0)}\right)\leq 10\ \text{OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$

*Proof.* Consider orderings  $\mathcal{U}^{(0)} = \{u_1, u_2, \dots, u_k\}$  and  $\mathcal{V}_{k+l+1}^* = \{v_1, v_2, \dots, v_{k+l+1}\}$  such that  $(u_i, v_i)$  are all  $k - m$  well-separated pairs w.r.t.  $(\mathcal{U}^{(0)}, \mathcal{V}_{k+l+1}^*)$  for  $1 \leq i \leq k - m$ . Define

$$
\mathcal{V}' = \{v_{k-m+1}, v_{k-m+2}, \dots, v_{k+l+1}\}
$$

of size  $m+l+1$ . For simplicity, denote  $C_{v_i}(V^*_{k+l+1}, \mathcal{P}^{(0)})$  by  $C_{v_i}$  for each  $1 \leq i \leq k+l+1$ . Note that these sets give a partition of  $\mathcal{P}^{(0)}$ . Now, consider  $\mathcal{U}^{(0)} + \mathcal{V}'$ . We show how to assign points of  $\mathcal{P}^{(0)}$  to centers in  $\mathcal{U}^{(0)} + \mathcal{V}'$ . For every  $1 \leq i \leq k-m$ , we assign all of the points of  $C_{v_i}$  to  $u_i$  which is present in  $\mathcal{U}^{(0)} + \mathcal{V}'$ . This gives us,

<span id="page-65-1"></span>
$$
\sum_{i=1}^{k-m} \text{Cost} \left( \mathcal{U}^{(0)} + \mathcal{V}', C_{v_i} \right) \le \sum_{i=1}^{k-m} \text{Cost} \left( u_i, C_{v_i} \right) \le \sum_{i=1}^{k-m} 5 \text{ Cost} \left( v_i, C_{v_i} \right). \tag{72}
$$

The last inequality is by Lemma [10.12](#page-40-1) for  $P = P^{(0)}$ ,  $\mathcal{U} = \mathcal{U}^{(0)}$ ,  $\mathcal{V} = \mathcal{V}_{k+l+1}^*$  and every  $1 \le i \le k-m$ . For each  $k - m + 1 \leq i \leq k + l + 1$ , we assign all of the points of  $C_{v_i}$  to  $v_i$  which is present in  $\mathcal{U}^{(0)} + \mathcal{V}'$ . This gives us,

<span id="page-66-0"></span>
$$
\sum_{i=k-m+1}^{k+l+1} \text{Cost}\left(\mathcal{U}^{(0)} + \mathcal{V}', C_{v_i}\right) \le \sum_{i=k-m+1}^{k+l+1} \text{Cost}\left(v_i, C_{v_i}\right). \tag{73}
$$

As a result,

$$
\begin{array}{rcl}\n\text{Cost} \left( \mathcal{U}^{(0)} + \mathcal{V}', \mathcal{P}^{(0)} \right) & = & \sum_{i=1}^{k+l+1} \text{Cost} \left( \mathcal{U}^{(0)} + \mathcal{V}', C_{v_i} \right) \\
& = & \sum_{i=1}^{k-m} \text{Cost} \left( \mathcal{U}^{(0)} + \mathcal{V}', C_{v_i} \right) + \sum_{i=k-m+1}^{k+l+1} \text{Cost} \left( \mathcal{U}^{(0)} + \mathcal{V}', C_{v_i} \right) \\
& \leq & \sum_{i=1}^{k-m} 5 \text{ Cost} \left( v_i, C_{v_i} \right) + \sum_{i=k-m+1}^{k+l+1} \text{Cost} \left( v_i, C_{v_i} \right) \\
& \leq & 5 \sum_{i=1}^{k+l+1} \text{Cost} \left( v_i, C_{v_i} \right) \\
& = & 5 \text{ Cost} \left( \mathcal{V}_{k+l+1}^*, \mathcal{P}^{(0)} \right) \\
& \leq & 10 \text{ OPT}_{k+l+1}(\mathcal{P}^{(0)}).\n\end{array}
$$

The first inequality holds by Equation [\(72\)](#page-65-1) and Equation [\(73\)](#page-66-0) and the last inequality holds by Equation [\(71\)](#page-65-2).  $\Box$ 

Next, we show that the number of well-separated pairs w.r.t.  $(\mathcal{U}^{(0)}, \mathcal{V}_{k+l+1}^*)$  is large.

# <span id="page-66-1"></span>Lemma 15.7.  $m \leq (8C+1)(l+1)$ .

*Proof.* Let  $b = \lfloor (m - (l + 1))/4 \rfloor$ . By plugging  $P = P^{(0)}$ ,  $U = U^{(0)}$ ,  $V = V^*_{k+l+1}$  and  $r = l + 1$  in Lemma [10.14,](#page-43-1) there exist a  $\bar{\mathcal{U}} \subseteq \mathcal{U}^{(0)}$  of size at most  $k - b$  such that

$$
\mathsf{Cost}\left(\bar{\mathcal{U}}, \mathcal{P}^{(0)}\right) \leq 6 \gamma \left(\mathsf{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) + \mathsf{Cost}\left(\mathcal{V}^*_{k+l+1}, \mathcal{P}^{(0)}\right)\right).
$$

We also have

$$
\mathsf{Cost}\left(\mathcal{U}^{(0)},\mathcal{P}^{(0)}\right)\leq 50\beta\ \mathrm{OPT}_k(\mathcal{P}^{(0)})
$$

and

$$
\text{Cost}\left(\mathcal{V}_{k+l+1}^*, \mathcal{P}^{(0)}\right) \leq 2\;\text{OPT}_{k+l+1}(\mathcal{P}^{(0)}) \leq 2\;\text{OPT}_k(\mathcal{P}^{(0)}).
$$

Combining these three inequalities together, we have

$$
\begin{array}{rcl}\n\text{OPT}_{k-b}(\mathcal{P}^{(0)}) & \leq & \text{Cost}\left(\bar{\mathcal{U}}, \mathcal{P}^{(0)}\right) \\
& \leq & 6\gamma \left(\text{Cost}\left(\mathcal{U}^{(0)}, \mathcal{P}^{(0)}\right) + \text{Cost}\left(\mathcal{V}_{k+l+1}^*, \mathcal{P}^{(0)}\right)\right) \\
& \leq & 6\gamma \left(50\beta \text{ OPT}_k(\mathcal{P}^{(0)}) + 2 \text{ OPT}_k(\mathcal{P}^{(0)})\right) \\
& \leq & (6\gamma) \cdot (52\beta) \text{ OPT}_k(\mathcal{P}^{(0)}) \\
& \leq & 400\gamma\beta \text{ OPT}_k(\mathcal{P}^{(0)}).\n\end{array}
$$

Now, with the maximality in the definition of  $l^*$  in Equation [\(64\)](#page-52-1), we have  $\frac{m-(l+1)}{4}$  $\left|\frac{(l+1)}{4}\right|=b\leq l^{*}$ which concludes

$$
m \le 4(l^* + 1) + (l + 1).
$$

<span id="page-67-0"></span>Together with Lemma [15.2,](#page-63-1) we have  $m \leq (8C + 1)(l + 1)$ .

**Lemma 15.8.** Let  $s = (8C + 2)(l + 1)$ . We have

$$
\min_{\substack{\mathcal{F}\subseteq \mathcal{P}^{(0)},\\|\mathcal{F}|\leq s}} \text{Cost}\left(\mathcal{U}^{(0)} + \mathcal{F}, \mathcal{P}^{(0)}\right) \leq 10 \text{ OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$

*Proof.* According to Lemma [15.6,](#page-65-3) there exist a  $\mathcal{V}' \subseteq \mathcal{V}_{k+l+1}^*$  of size at most  $m+l+1$  such that

$$
\text{Cost}\left(\mathcal{U}^{(0)}+\mathcal{V}',\mathcal{P}^{(0)}\right)\leq 10\;\text{OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$

Note that  $\mathcal{V}' \subseteq \mathcal{V}_{k+l+1}^* \subseteq \mathcal{P}^{(0)}$  since  $\mathcal{V}_{k+l+1}^*$  is a proper solution. We also have

$$
|\mathcal{V}'| \le m + l + 1 \le (8C + 2)(l + 1) = s,
$$

<span id="page-67-1"></span>where the last inequality holds by Lemma [15.7.](#page-66-1) This concludes the lemma.

**Lemma 15.9.** Assume  $\tilde{\mathcal{U}}^{(0)}$  is returned by DEVELOP-CENTERS( $\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, s$ ). Then,

$$
\mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)},\mathcal{P}^{(0)}\right) \leq 10\beta \; \text{OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$

Proof. According to Lemma [15.8](#page-67-0) and the guarantee of DEVELOP-CENTERS in Lemma [11.3,](#page-48-3) we have

$$
\mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)},\mathcal{P}^{(0)}\right) \leq \beta \min_{\substack{\mathcal{F} \subseteq \mathcal{P}^{(0)},\\|\mathcal{F}| \leq s}} \mathsf{Cost}\left(\mathcal{U}^{(0)} + \mathcal{F},\mathcal{P}^{(0)}\right) \leq 10\beta \; \text{OPT}_{k+l+1}(\mathcal{P}^{(0)}).
$$



<span id="page-67-2"></span>After termination of DEVELOP-CENTERS, the algorithm lets  $V = \tilde{U}^{(0)} + (\mathcal{P}^{(l+1)} - \mathcal{P}^{(0)})$  and calls RAND-LOCAL-SEARCH $(\mathcal{V}, |\mathcal{V}| - k)$  to get  $\mathcal{W}$ .

Lemma 15.10. We have,

$$
\mathsf{Cost}\left(\mathcal{V}, \mathcal{P}^{(l+1)}\right) \leq 10\beta \; \text{OPT}_k(\mathcal{P}^{(l+1)}).
$$

<span id="page-67-3"></span>Proof. According to Lemma [15.9,](#page-67-1)

$$
\begin{array}{lcl} \mathsf{Cost}\left(\mathcal{V}, \mathcal{P}^{(l+1)}\right) & = & \mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)} + (\mathcal{P}^{(l+1)} - \mathcal{P}^{(0)}), \mathcal{P}^{(l+1)}\right) \\ \\ & \leq & \mathsf{Cost}\left(\tilde{\mathcal{U}}^{(0)}, \mathcal{P}^{(0)}\right) \\ & \leq & 10\beta \; \mathrm{OPT}_{k+l+1}(\mathcal{P}^{(0)}) \\ & \leq & 10\beta \; \mathrm{OPT}_k(\mathcal{P}^{(l+1)}). \end{array}
$$

 $\Box$ 





Lemma 15.11. We have

$$
\text{Cost}\left(\mathcal{W}, \mathcal{P}^{(l+1)}\right) \leq 32\beta \ \text{OPT}_k(\mathcal{P}^{(l+1)}).
$$

*Proof.* With guarantee of RAND-LOCAL-SEARCH in Lemma [11.1,](#page-46-3) and with Lemma [15.10,](#page-67-2) we have

$$
\begin{array}{rcl}\n\text{Cost} \left( \mathcal{W}, \mathcal{P}^{(l+1)} \right) & \leq & 2 \text{ Cost} \left( \mathcal{V}, \mathcal{P}^{(l+1)} \right) + 12 \text{ OPT}_k(\mathcal{P}^{(l+1)}) \\
& \leq & 20\beta \text{ OPT}_k(\mathcal{P}^{(l+1)}) + 12 \text{ OPT}_k(\mathcal{P}^{(l+1)}) \\
& \leq & 32\beta \text{ OPT}_k(\mathcal{P}^{(l+1)})\n\end{array}
$$

### 15.4 Analysis of Cost of Robustify

<span id="page-68-3"></span>Finally, we analyze the cost of ROBUSTIFY on  $W$ .

**Lemma 15.12** (Lemma 7.5 in [\[FLNS21\]](#page-75-1)). Assume W is a set of k centers. If U is the output of ROBUSTIFY on  $W$ , then

$$
\mathsf{Cost}\left(\mathcal{U},\mathcal{P}^{(l+1)}\right) \leq \frac{3}{2}\,\,\mathsf{Cost}\left(\mathcal{W},\mathcal{P}^{(l+1)}\right).
$$

*Proof.* By Lemma [13.1,](#page-57-0) ROBUSTIFY calls MAKE-ROBUST on each center at most once. Let r be the number of centers in W for which a call to MAKE-ROBUST has happened. Assume  $W =$  $\{w_1, \ldots, w_k\}$  is an ordering by the time that MAKE-ROBUST is called on the centers  $w_1, w_2, \ldots, w_r$ and the last elements are ordered arbitrarily. Assume also that  $\mathcal{U} = \{w'_1, \ldots, w'_k\}$  where  $w'_i$  is obtained by the call MAKE-ROBUST on  $w_i$  for each  $1 \leq i \leq r$  and  $w'_i = w_i$  for each  $r + 1 \leq i \leq k$ .

For every  $1 \leq j \leq r$ , integer  $t(w'_j)$  is the smallest integer satisfying

$$
10^{t(w'_j)} \ge d(w_j, \{w'_1, \ldots, w'_{j-1}, w_{j+1}, \ldots, w_k\})/100.
$$

Hence,

<span id="page-68-0"></span>
$$
10^{t(w'_j)} \le d(w_j, w'_i)/10 \quad \forall i < j \tag{74}
$$

and

<span id="page-68-1"></span>
$$
10^{t(w'_j)} \le d(w_j, w_i)/10 \quad \forall i > j.
$$
\n(75)

Now, for every  $1 \leq i < j \leq r$ , we conclude

$$
10 \cdot 10^{t(w'_j)} \le d(w'_i, w_j) \le d(w_i, w_j) + d(w_i, w'_i) \le d(w_i, w_j) + 10^{t(w'_i)}/2 \le \frac{11}{10} d(w_i, w_j).
$$

The first inequality holds by Equation [\(74\)](#page-68-0), the third one holds by Lemma [10.3](#page-37-0) (note that  $w'_i =$ MAKE-ROBUST $(w_i)$  and the last one holds by Equation [\(75\)](#page-68-1) (by exchanging i and j since  $i < j$ ). This concludes for each  $i < j$ , we have  $d(w_i, w_j) > 2 \cdot 10^{t(w'_j)}$ . The same inequality holds for each  $i > j$  by Equation [\(75\)](#page-68-1). As a result,  $d(w_i, w_j) > 2 \cdot 10^{t(w'_j)}$  for all  $i \neq j$ . This concludes

$$
\text{Ball}^{\mathcal{P}}_{10^{t(w'_j)}}(w_j) \subseteq C_{w_j}(\mathcal{W}, \mathcal{P}),
$$

for every  $1 \leq j \leq r$ . By applying Lemma [10.4,](#page-37-2) we have

<span id="page-68-2"></span>
$$
\mathsf{Cost}\left(w'_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \le \frac{3}{2} \mathsf{Cost}\left(w_j, C_{w_j}(\mathcal{W}, \mathcal{P})\right) \quad \forall 1 \le j \le r. \tag{76}
$$

Finally, since  $C_{w_j}(\mathcal{W}, \mathcal{P})$  for  $1 \leq j \leq k$  form a partition of  $\mathcal{P}$ , we conclude

Cost 
$$
(\mathcal{U}, \mathcal{P})
$$
 =  $\sum_{j=1}^{k} \text{Cost} (\mathcal{U}, C_{w_j}(\mathcal{W}, \mathcal{P}))$   
\n $\leq \sum_{j=1}^{k} \text{Cost} (w'_j, C_{w_j}(\mathcal{W}, \mathcal{P}))$   
\n=  $\sum_{j=1}^{r} \text{Cost} (w'_j, C_{w_j}(\mathcal{W}, \mathcal{P})) + \sum_{j=r+1}^{k} \text{Cost} (w'_j, C_{w_j}(\mathcal{W}, \mathcal{P}))$   
\n $\leq \frac{3}{2} \sum_{j=1}^{r} \text{Cost} (w_j, C_{w_j}(\mathcal{W}, \mathcal{P})) + \sum_{j=r+1}^{k} \text{Cost} (w_j, C_{w_j}(\mathcal{W}, \mathcal{P}))$   
\n $\leq \frac{3}{2} \sum_{j=1}^{k} \text{Cost} (w_j, C_{w_j}(\mathcal{W}, \mathcal{P}))$   
\n=  $\frac{3}{2} \text{ Cost} (\mathcal{W}, \mathcal{P}).$ 

The second inequality holds by Equation [\(76\)](#page-68-2).

<span id="page-69-0"></span>**Corollary 15.13.** If  $U$  is the final solution of the algorithm for the epoch, then

$$
\mathsf{Cost}\left(\mathcal{U},\mathcal{P}^{(l+1)}\right)\leq 50\beta\ \mathrm{OPT}_k(\mathcal{P}^{(l+1)}).
$$

Proof. According to Lemma [15.11](#page-67-3) and Lemma [15.12,](#page-68-3) we have

$$
\text{Cost}\left(\mathcal{U},\mathcal{P}^{(l+1)}\right) \leq \frac{3}{2} \text{ Cost}\left(\mathcal{W},\mathcal{P}^{(l+1)}\right) \leq \frac{3}{2} \cdot 32\beta \text{ OPT}_k(\mathcal{P}^{(l+1)}) \leq 50\beta \text{ OPT}_k(\mathcal{P}^{(l+1)}).
$$

## 15.5 Final Approximation Ratio

According to Corollary [15.5,](#page-65-4) the approximation ratio of the main solution during the epoch is at most  $2 \cdot 10^7 \gamma \beta^2$ . The approximation ratio of the main solution at the beginning of (and consequently end of) each epoch is at most  $50\beta$  by Corollary [15.13.](#page-69-0) As a result, the approximation ratio of the main solution is always at most

$$
2 \cdot 10^7 \gamma \beta^2 = \max\{2 \cdot 10^7 \gamma \beta^2, 50\beta\}.
$$

# 16 Analysis of Update Time

In this section, we prove that we can implement the algorithm that runs in amortized  $\tilde{O}(n)$  time.

## 16.1 Sorted Distances to Main Centers

Assume that U is the current solution and P is the current space. For any point  $p \in \mathcal{P} + \mathcal{U}$ , we maintain a balanced binary search tree  $\mathcal{T}_p$  that contains the centers U sorted by their distances to p. Every time a new p is inserted to P, we build the tree  $\mathcal{T}_p$  which takes  $O(k)$  time (since we should sort the distance of p to centers in  $\mathcal{U}$ . The total time needed to construct these trees after T updates in the input stream is at most  $O(Tk)$ .

Whenever a point is deleted from  $P$ , if it is not present in our solution  $U$ , we remove the tree  $\mathcal{T}_p$ , otherwise we keep the tree. As a result, at any time the number of trees that we have is at most  $n + k$ , where n is the size of the current space.

Every time a center u is deleted from the main solution  $\mathcal U$  and  $u'$  is inserted to  $\mathcal U$ , for every tree  $\mathcal{T}_p$ , we remove the element u from  $\mathcal{T}_p$  and add u' to  $\mathcal{T}_p$ . For each p, this can be done in  $O(\log k)$ time. So, the overall time consumed for updating these  $n+k$  trees after each change in U would be at most  $\tilde{O}(n+k) = O(n)$ , where *n* is the size of the current space. Since, we have already proved in Section [14,](#page-59-0) that the total change of the main solution during T updates is at most  $O(T(\log \Delta)^2)$ , then the total time consumed for updating all of the trees throughout the first T updates in the input stream is at most  $O(Tn)$ , where n is the maximum size of the space during these T updates.

As you can see, the total time needed for constructing and maintaining these trees throughout the first T updates in the input stream is at most  $O(Tn)$ , where n is the maximum size of the space during these T updates. Obviously, this is  $O(n)$  in amortization.

So, we assume that we always have access to sorted distances of p to all centers  $\mathcal{U}$ , where p is either present in the current space or in the main solution  $\mathcal{U}$ .

### 16.2 Rand-Local-Search

In [\[BCG](#page-74-0)<sup>+</sup>24], the authors provide an implementation for this subroutine that runs in  $\tilde{O}(ns)$  time. This is with the assumption that we have access to sorted distances of each  $p \in \mathcal{P}$  to centers in U. We have these sorted distances by the argument in the previous section. So, we conclude that we can run RAND-LOCAL-SEARCH, in  $O(ns)$  time. We refer the reader to Lemma 7.2 in [\[BCG](#page-74-0)<sup>+</sup>24], to see the full implementation and arguments.

#### 16.3 Remove-Centers

In this subroutine, we run a RAND-LOCAL-SEARCH for each  $r \in \mathcal{R}$  starting from the smallest value, until we reach the largest r specified in the algorithm. For each  $r \in \mathcal{R}$  that we call RAND-LOCAL-SEARCH $(\mathcal{P}^{(0)}, \mathcal{U}^{(0)}, r)$ , the running time of RAND-LOCAL-SEARCH is  $\tilde{O}(nr)$ . Since  $|\mathcal{R}| = O(\log k)$ , by the description of the algorithm, it is obvious that the most costly RAND-LOCAL-SEARCH that we call is the last one which takes at most  $\tilde{O}(n(2l')) = \tilde{O}(nl')$  time. Finally, since  $l + 1 = \Omega(l' + 1)$ , we can charge the total running time of this part to the  $l+1$  updates in the epoch, which is  $O(n)$  in amortization. More precise, since we have not performed these  $l + 1$  updates yet at the beginning of the epoch, we can not charge the running time to these updates. But, we can first charge them to the previous  $l + 1$  elements and at the end of the epoch, we take them back and charge them to  $l + 1$  updates in the epoch. So, at any time during the algorithm, we charged  $O(n)$  units to any update at most twice which is still  $O(n)$ .

### 16.4 Develop-Centers

In this subroutine, we define a new space  $\mathcal{P}' = (\mathcal{P} - \mathcal{U}) + u^*$  with a new metric d' as Equation [\(55\)](#page-46-1). Since we have access to trees  $\mathcal{T}_x$ , we know the value of  $d(x, \mathcal{U})$  in constant time. Note that in this subroutine, we only search for  $\mathcal{U} \subseteq \mathcal{P} + \mathcal{U}$ . So, we only need access to sorted distances of points in  $\mathcal{P} + \mathcal{U}$  (instead of every point in P) to centers in  $\mathcal{U}$  to be able to do this fast.

So, according to the definition of metric d' in Equation [\(55\)](#page-46-1), for every  $x \in \mathcal{P}' - u^*$ , we can evaluate  $d'(x, u^*)$  in constant time using tree  $\mathcal{T}_x$  and for every  $x, y \in \mathcal{P}' - u^*$  we can evaluate  $d'(x, y)$  in constant time using trees  $\mathcal{T}_x$  and  $\mathcal{T}_y$ . This means that we can design an oracle D' that evaluates  $d'(x, y)$  for every given  $x, y \in \mathcal{P}'$  in constant time.

Next, we run any fast  $\beta$  approximate algorithm for **proper**  $(s+1)$ -median problem on  $\mathcal{P}'$  using oracle D'. So, we have the desired  $\mathcal F$  in  $\tilde{O}(|\mathcal P'|(s+1))$  time which is  $\tilde{O}(n(l+1))$  since  $s = O(l+1)$ and  $|\mathcal{P}'|$  is at most the size of  $\mathcal{P}$ . Finally, we can charge this running time to the  $l+1$  updates of the epoch which leads to an amortized running time of  $O(n)$ .

Note that in above arguments n is the size of the current space  $P$ , not the underlying ground metric space P.

### 16.5 Fast-One-Median

The sampling process can be done easily. First, consider an arbitrary ordering  $B = \{b_1, b_2, \ldots, b_{|B|}\}.$ Then sample a uniformly random  $r \in [0,1]$ . Finally, we pick the smallest  $i^*$  such that

$$
\sum_{j=1}^{i^*} w(b_j)/w(B) \ge r.
$$

This  $i^*$  indicates that our sample is  $b_{i^*}$ . It is very easy to see that each  $b_i$  is samples proportional to its weight  $w(b_i)$  and also sampling a point takes  $O(|B|)$  time. The number of samples is  $O(1)$ . So, the total time we need to sample these points is at most  $O(|B|)$ . For each sample s, we iterate over all elements of B to find Cost(s, B) which takes  $|B| = O(n)$  time. Hence, the total running time of FAST-ONE-MEDIAN is at most  $O(n)$ .

#### 16.6 Find-Suspects

Assume an epoch of length  $l + 1$ . We can find  $W - U^{(0)}$  in  $O(k)$  time by a simple iteration over centers  $w \in \mathcal{W}$  and check whether w is in our main solution  $\mathcal{U}^{(0)}$  at the beginning of the epoch. The number of points  $p \in \mathcal{P}^{(0)} \oplus \mathcal{P}^{(l+1)}$  is at most  $l + 1$ . The number of centers  $u \in \mathcal{U}^{(0)} \cap \mathcal{W}$  is at most k and these centers can be found in the same way as  $W - U^{(0)}$ . For each p and u we can check  $d(p, u) \leq 2 \cdot 10^{t(u)}$  in constant time. In total, we can run FIND-SUSPECTS in  $O(k(l+1))$  time. Now, we charge this running time to  $l + 1$  updates of this epoch which gives an amortized update time of  $O(k)$ .

### 16.7 Make-Robust

The main for loop is performed t times where  $t \leq \lceil \log \Delta \rceil = O(1)$  (since  $\Delta$  is the aspect ratio of the metric space). For each  $1 \leq i \leq t$ , first we iterate over all points of  $P$  to find  $B_i$ . This takes  $O(n)$  time. Finding AverageCost  $(w_i, B_i)$  also takes at most  $|B_i| = O(n)$  time. The most expensive part is calling FAST-ONE-MEDIAN, which takes  $O(n)$  time. Hence, the total running time of MAKE-ROBUST is at most  $O(n)$ , where n is the size of the current space.

### 16.8 Robustify

At the beginning, a call to FIND-SUSPECTS is made which runs in amortized  $O(k)$  time. The analysis of ROBUSTIFY highly depends on the fact that total change of the main solution is  $O(1)$
in amortization. A single call to ROBUSTIFY might be costly, although we show that the amortized update time remains  $O(n)$ .

We show that throughout the first  $T$  updates of the input stream, the running time of all calls to ROBUSTIFY is at most  $O(Tn)$ . ROBUSTIFY calls EMPTY-S in Line [5,](#page-55-0) and have a loop in Line [6.](#page-55-1) Assume the number of times that the algorithm calls EMPTY-S is  $N$ . Note that  $N$  is also the number of times ROBUSTIFY performs the for loop in Line [6.](#page-55-1)

N is at most the number of elements added to  $\mathcal S$ . This is because a call to EMPTY-S is made only if S is not empty, and when that happens, S becomes empty through a call to EMPTY-S. So, to call EMPTY-S again, at least one element should be added to  $S$ . Finally, by the analysis in Section [14,](#page-59-0) the number of elements added to S is at most  $O(T)$  in total, which concludes  $N = O(T)$ . The most costly part in EMPTY-S is MAKE-ROBUST. Note that we have the value of  $d(w, W - w)$ in constant time using tree  $\mathcal{T}_w$ . The first element of the tree is w since  $d(w, w) = 0$  and the second element is w' such that  $d(w, w') = d(w, W - w)$ . We will show that we can perform MAKE-ROBUST in  $O(n)$  time. So, the total time spent by the algorithm for performing all of the calls to EMPTY-S is at most  $N \cdot \tilde{O}(n) = \tilde{O}(T_n)$ .

Now, consider the for loop in Line [6.](#page-55-1) In this for loop, we are iterating over all elements of  $W$  and the total running time to perform it is  $O(k)$ . Note that we have the value of  $d(u, W - u)$  in constant time for each  $u \in \mathcal{W}$  using tree  $\mathcal{T}_u$ . The total running time of this for loop is  $N \cdot O(k) = O(Tk)$ .

In total, the running time of ROBUSTIFY throughout the first T updates is at most  $O(Tn)$ which is  $O(n)$  in amortization.

## 16.9 Total Running Time

According to the implementation provided in this section, the total running time of the algorithm after T updates in the input stream is at most  $O(Tn)$ , where n is the maximum size of the space throughout these T updates. Note that n is not the size of the underlying ground metric space  $P$ . This is important since we are reducing the amortized running time to  $O(k)$  in next section and we need the guarantee that  $n$  is the maximum size of the space throughout the run of the algorithm.

## 17 Obtaining  $\tilde{O}(k)$  Amortized Update Time

In this section, we show how to reduce the amortized running time of the algorithm to  $O(k)$  instead of  $O(n)$ . Note that n is the maximum size of the space at any time during the whole run of the algorithm (it is **not** the size of the underlying ground metric space  $P$ ). As a result, if we make sure that the size of the space is at most  $O(k)$  at any point in time, then the amortized running time of the algorithm would be  $\tilde{O}(k)$  as desired.

We use the result of [\[BCLP23\]](#page-74-0) to sparsify the input. A simple generalization of this result is presented in Section 10 of  $[BCG+24]$  which extends this sparsifier to weighted metric spaces. The authors provided an algorithm to sparsify the space to  $O(k)$  weighted points. More precisely, given a dynamic metric space  $(\mathcal{P}, w, d)$  and parameter  $k \in \mathbb{N}$ , there is an algorithm that maintains a dynamic metric space  $(\mathcal{P}', w', d)$  in  $\tilde{O}(k)$  amortized update time such that the following holds.

- $\mathcal{P}' \subseteq \mathcal{P}$  and the size of  $\mathcal{P}'$  at any time is  $\tilde{O}(k)$ .
- A sequence of T updates in  $(\mathcal{P}, w, d)$ , leads to a sequence of  $\lambda \cdot T$  updates in  $(\mathcal{P}', w', d)$ . In other words, the amortized recourse of  $\mathcal{P}'$  is at most  $\lambda$ .

• Every  $\alpha$  approximate solution to the k-median problem in the metric space  $(\mathcal{P}', w', d)$  is also a  $O(\alpha)$  approximate solution to the k-median problem in the metric space  $(\mathcal{P}, w, d)$  with probability at least  $1 - \tilde{O}(1/n^c)$ .

The sparsifier of [\[BCG](#page-74-1)<sup>+</sup>24] works by maintaining  $O(\log \Delta)$  copies of the sparsifier of [\[BCLP23\]](#page-74-0), feeding each one a subset of the metric space consisting of the points whose weights are in a given range, and taking the union of these spasifiers. Thus, it follows that the amortized recourse of this sparsifier is at most the amortized recourse of the sparsifier of [\[BCLP23\]](#page-74-0). The authors of  $[BCG^+24]$ argue that the recourse of [\[BCLP23\]](#page-74-0) is at most  $\tilde{O}(1)$ , and thus  $\lambda = \tilde{O}(1)$ . In [\[BCLP24\]](#page-74-2), the authors give a more refined analysis of the recourse of [\[BCLP23\]](#page-74-0), showing that it is constant. Thus, it follows that  $\lambda = O(1)$ .

Now, suppose that we are given a sequence of updates  $\sigma_1, \sigma_2, \ldots, \sigma_T$  in a dynamic metric space  $(\mathcal{P}, w, d)$ . Instead of feeding the metric space  $(\mathcal{P}, w, d)$  directly to our algorithm, we can perform this dynamic sparsification to obtain a sequence of updates  $\sigma'_1, \sigma'_2, \ldots, \sigma'_{T'}$  for a metric space  $(\mathcal{P}', w', d)$ , where  $T' = O(T)$ , and feed the metric space  $(\mathcal{P}', w', d)$  to our dynamic algorithm instead. Since our algorithm maintains a  $O(1)$  approximate solution U to the k-median problem in  $(\mathcal{P}', w', d)$ , then U is also a  $O(1)$  approximate solution for the k-median problem in  $(\mathcal{P}, w, d)$  with high probability.

Since the length of the stream is multiplied by  $O(1)$ , we would have a multiplicative overhead of  $O(1)$  in the amortized update time and recourse (amortized w.r.t. the original input stream). As a result, we have Theorem [1.1.](#page-4-0)

## References

- <span id="page-74-1"></span>[BCG<sup>+</sup>24] Sayan Bhattacharya, Martín Costa, Naveen Garg, Silvio Lattanzi, and Nikos Parotsidis. Fully dynamic k-clustering with fast update time and small recourse. In 65th IEEE Symposium on Foundations of Computer Science (FOCS), 2024.
- [BCIS05] Mihai Badoiu, Artur Czumaj, Piotr Indyk, and Christian Sohler. Facility location in sublinear time. In Automata, Languages and Programming, 32nd International Colloquium, (ICALP), volume 3580, pages 866–877. Springer, 2005.
- <span id="page-74-0"></span>[BCLP23] Sayan Bhattacharya, Martín Costa, Silvio Lattanzi, and Nikos Parotsidis. Fully dynamic k-clustering in  $\tilde{O}(k)$  update time. In Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023, 2023.
- <span id="page-74-2"></span>[BCLP24] Sayan Bhattacharya, Mart´ın Costa, Silvio Lattanzi, and Nikos Parotsidis. Fully dynamic k-center clustering made simple.  $CoRR$ , abs/2410.11470, 2024.
- [BEF+23] MohammadHossein Bateni, Hossein Esfandiari, Hendrik Fichtenberger, Monika Henzinger, Rajesh Jayaram, Vahab Mirrokni, and Andreas Wiese. Optimal fully dynamic k-center clustering for adaptive and oblivious adversaries. In Proceedings of the 2023 ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 2677–2727. SIAM, 2023.
- [BGJ+24] Sayan Bhattacharya, Gramoz Goranci, Shaofeng H.-C. Jiang, Yi Qian, and Yubo Zhang. Dynamic facility location in high dimensional euclidean spaces. In Forty-first International Conference on Machine Learning (ICML). OpenReview.net, 2024.
- [BLP22] Sayan Bhattacharya, Silvio Lattanzi, and Nikos Parotsidis. Efficient and stable fully dynamic facility location. In Advances in Neural Information Processing Systems (NeurIPS), 2022.
- [CFG+24] Emilio Cruciani, Sebastian Forster, Gramoz Goranci, Yasamin Nazari, and Antonis Skarlatos. Dynamic algorithms for k-center on graphs. In David P. Woodruff, editor, Proceedings of the ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 3441– 3462. SIAM, 2024.
- [CGS18] T.-H. Hubert Chan, Arnaud Guerquin, and Mauro Sozio. Fully dynamic k-center clustering. In Proceedings of the 2018 World Wide Web Conference on World Wide Web (WWW), pages 579–587. ACM, 2018.
- [CHP+19] Vincent Cohen-Addad, Niklas Hjuler, Nikos Parotsidis, David Saulpic, and Chris Schwiegelshohn. Fully dynamic consistent facility location. In Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada, pages 3250–3260, 2019.
- [CS11] Tim Carnes and David B. Shmoys. Primal-dual schema and lagrangian relaxation for the k-location-routing problem. In Leslie Ann Goldberg, Klaus Jansen, R. Ravi, and José D. P. Rolim, editors, Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques - 14th International Workshop, APPROX 2011, and 15th International Workshop, RANDOM 2011, Princeton, NJ, USA, August 17-19, 2011.

Proceedings, volume 6845 of Lecture Notes in Computer Science, pages 99–110. Springer, 2011.

- [DHS24] Max Dupré la Tour, Monika Henzinger, and David Saulpic. Fully Dynamic k-Means Coreset in Near-Optimal Update Time. In 32nd Annual European Symposium on Algorithms, ESA  $2024$ , volume 308 of LIPIcs, pages 100:1–100:16. Schloss Dagstuhl -Leibniz-Zentrum für Informatik, 2024.
- [FLNS21] Hendrik Fichtenberger, Silvio Lattanzi, Ashkan Norouzi-Fard, and Ola Svensson. Consistent k-clustering for general metrics. In Proceedings of the 2021 ACM-SIAM Symposium on Discrete Algorithms, SODA 2021, Virtual Conference, January 10 - 13, 2021, pages 2660–2678. SIAM, 2021.
- [FS25] Sebastian Forster and Antonis Skarlatos. Dynamic Consistent k-Center Clustering with Optimal Recourse. In Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), 2025. (to appear).
- [GHL+21] Gramoz Goranci, Monika Henzinger, Dariusz Leniowski, Christian Schulz, and Alexander Svozil. Fully dynamic k-center clustering in low dimensional metrics. In Proceedings of the Symposium on Algorithm Engineering and Experiments, ALENEX 2021, Virtual Conference, January 10-11, 2021, pages 143–153. SIAM, 2021.
- [HK20] Monika Henzinger and Sagar Kale. Fully-dynamic coresets. In 28th Annual European Symposium on Algorithms, ESA 2020, September 7-9, 2020, Pisa, Italy (Virtual Conference), volume 173 of LIPIcs, pages 57:1–57:21. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020.
- [LHG<sup>+</sup>24] Jakub Lacki, Bernhard Haeupler, Christoph Grunau, Václav Rozhon, and Rajesh Jayaram. Fully dynamic consistent k-center clustering. In ACM-SIAM Symposium on Discrete Algorithms (SODA), 2024.
- [LV17] Silvio Lattanzi and Sergei Vassilvitskii. Consistent k-clustering. In Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017, volume 70 of Proceedings of Machine Learning Research, pages 1975–1984. PMLR, 2017.
- [Mey01] Adam Meyerson. Online facility location. In 42nd Annual Symposium on Foundations of Computer Science (FOCS), pages 426–431, 2001.
- [MP00] Ramgopal R. Mettu and C. Greg Plaxton. The online median problem. In 41st Annual Symposium on Foundations of Computer Science (FOCS), pages 339–348, 2000.
- [MP02] Ramgopal R. Mettu and C. Greg Plaxton. Optimal time bounds for approximate clustering. In Proceedings of the 18th Conference in Uncertainty in Artificial Intelligence  $(UAI)$ , pages 344–351, 2002.
- [WS11] David P. Williamson and David B. Shmoys. The Design of Approximation Algorithms. Cambridge University Press, 2011.