

Linear finishing made easy

The Line-Mate III <sup>™</sup> is a versatile variable speed tool that allows you to quickly and easily apply a wide range of linear finishes to metal surfaces. Its powerful motor will help you complete even the toughest jobs with ease. RPM remains constant under load for a consistent and uniform finish every time. When you have a project that requires a linear scratch pattern applied to the surface, trust Line-Mate to get the job done quickly and efficiently.

We now stock the most popular
WALTER ABRASIVES & are a
full-line distributor of the brand!
Please call or scan the adjacent code!



Description	QUICK-STEP LINE-MATE III™
Model name	6268C
Order No.	30-A 268 (30-A 269 for the kit
Anti-vibration side handle	√
Lock-on switch	√
AC/DC compatibility	AC only
Soft-Start™	√
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	√
DIALSPEED™ variable RPM selector	√
Spindle	%" - 11
RPM no-load	1,000 to 3,800
Amps	12.4 A
Power	1500 W
Weight	6 lbs
Max. wheel dimensions	4 1/2" diameter x 4" length
Standard equipment	60
Side handle	48-Z 034
Manual clamping nut	30-B 037
Pin key wrench	48-Z 148
Inner flange	30-B 057



## Includes:

- 1 Line-Mate III<sup>™</sup> with standard equipment plus carrying case (30-A 268)
- 1 1 expanding drum (07-F 061)
  - 6 cloth drum belts (2 each grit: 60: 07-F 506, 80: 07-F 508 and 120: 07-F 511)
  - 2 BLENDEX drum belts (Coarse: 07-H 502, medium: 07-H 503)
  - 1 TWO-IN-ONE drum (4 1/4" x 4": 07-K 342)
  - 1 BLENDEX drum (4 1/4" x 4" medium: 07-M 343).





WARRANTY LONG-RUN

## RAIL-MATE™

A&M ITEM #5503496 \$924.35



Remove welds and finish pipes, tubes and railings faster

This power tool allows you to use our premium abrasive products to finish pipes, tubes and railings. This powerful finishing tool features Soft-Start technology to avoid kickback when starting the tool, Dialspeed™ variable speed control and Dynamax™ RPM Monitoring to maintain consistent speed under load.

Description	RAIL-MATE™ SANDER SYSTEM
Model name	6288A
Order No.	30-A 288 (30-A 289 for the kit)
Lock-on switch	✓
AC/DC compatibility	AC compatibility only
Soft-Start™	✓
DYNAMAX™ RPM monitoring	√
POWERGUARD™ overheat protection	<b>V</b>
LED indicator	√
DIALSPEED™ variable RPM selector	<b>V</b>
Spindle	5⁄s" - 11
RPM no-load	1,600 to 3,200
Surface speed	3-12 m/sec.
MAX belt size L x W	760 mm x 40 mm
MAX pipe diameter	7 in. (180 mm)
MAX polishing deg.	270"
Amps	10A
Power	1200 W
Tool weight	6.8 lbs
QUICK-R™ front nut	30-B 020



Includes:

- 1 Rail-Mate sander (30-A 288)
- . 6 Coolcut XX belts (2 of each: grit 60, 14-X 156; grit 80, 14-X 158; grit 120: 14-X 162)
- · 3 Blendex belts (1 of each grade: Coarse, 07-D 152; Medium 07-D 153; Fine 07-D 154)

**Valid thru 12/31/24** in US only. Specifications and pricing are subject to change without notice. Not responsible for typographical errors. Offers cannot be combined with any other promotional or discount offers. Please see our website for a full listing of our Terms & Conditions.

