UK Patent Application (19)GB (11)2514020

12.11.2014

(21) Application No: 1410789.0

(22) Date of Filing: 16.01.2013

Date Lodged: 17.06.2014

(30) Priority Data:

(31) 61592774 (32) 31.01.2012 (33) **US**

(86) International Application Data: PCT/NO2013/050011 En 16.01.2013

(87) International Publication Data: WO2013/115651 En 08.08.2013

(71) Applicant(s):

AGR Subsea AS Postboks 163, Straume 5342, Norway

(72) Inventor(s):

Sigurd Ree **Roger Sverre Stave**

(74) Agent and/or Address for Service:

HGF Limited Document Handling - HGF (Leeds), Belgrave Hall, Belgrave Street, Leeds, LS2 8DD, **United Kingdom**

(51) INT CL:

E21B 21/00 (2006.01) E21B 21/08 (2006.01)

(56) Documents Cited:

US 20110129358 A1 US 20110061872 A1 US 20030066650 A1 WO2011058031A2

(58) Field of Search:

INT CL E21B

Other: EPO-Internal, PAJ, WPI data

- (54) Title of the Invention: Boost system and method for dual gradient drilling Abstract Title: Boost system and method for dual gradient drilling
- (57) Boost system and method for dual gradient drilling where a marine riser (1) has a mud return line (14) connected at a first connection position (18) below the lowest foreseeable mud level (12) in the marine riser (1), and where a mud return pump (16) is connected to the mud return line (14), and where a recirculation line (20) that has a recirculation pump (22), is connected to the marine riser (1) at a second connection position (24) below the lowest foreseeable mud level (12) in the marine riser (1), and at a third connection position (26) on the marine riser (1) below said second connection position (24).




Fig. 1