



US007080928B2

(12) **United States Patent**  
**Barnhart et al.**

(10) **Patent No.:** **US 7,080,928 B2**  
(45) **Date of Patent:** **\*Jul. 25, 2006**

(54) **ELECTRONICALLY CONTROLLED  
AIRCRAFT RETRACTABLE LANDING  
LIGHT WITH MANUAL RETRACTION  
CAPABILITY**

(75) Inventors: **Brian J. Barnhart**, New Carlisle, OH  
(US); **Craig E. Giffen**, Hilliard, OH  
(US); **Scott E. Hamilton**, North  
Lewisburg, OH (US); **Saed M.  
Mubaslat**, Miamisburg, OH (US)

(73) Assignee: **Honeywell International Inc.**,  
Morristown, NJ (US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 145 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **10/153,945**

(22) Filed: **May 23, 2002**

(65) **Prior Publication Data**

US 2003/0107899 A1 Jun. 12, 2003

**Related U.S. Application Data**

(60) Provisional application No. 60/339,635, filed on Dec.  
12, 2001.

(51) **Int. Cl.**  
**B60Q 2/02** (2006.01)

(52) **U.S. Cl.** ..... **362/465**; 362/466; 362/472;  
362/287; 315/82

(58) **Field of Classification Search** ..... 362/464,  
362/465, 466, 470, 472, 526, 527, 286, 287,  
362/467; 315/208, 307, 311, 0.82

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,641,261 A	2/1972	Chaplin et al.	
4,115,841 A	9/1978	Alexander	
4,212,050 A	7/1980	Trenkler	
4,233,652 A	11/1980	Oswald	
4,353,110 A	10/1982	Ellis	
4,916,445 A	4/1990	Crossley	
5,293,304 A	3/1994	Godfrey	
5,355,131 A	10/1994	Metz et al.	
5,369,557 A	11/1994	Ronney	
D361,142 S	8/1995	Allred	
5,580,148 A	12/1996	Liao	
5,584,560 A	12/1996	Gosswiller et al.	
5,589,901 A	12/1996	Means	
5,806,956 A	9/1998	Hyun-Jo	
6,191,547 B1	2/2001	Fricke et al.	
6,315,435 B1	11/2001	Hamilton et al.	
6,608,445 B1 *	8/2003	Melvin et al. ....	315/82
6,669,351 B1 *	12/2003	Shea et al. ....	362/153.1

\* cited by examiner


*Primary Examiner*—Thomas M. Sember

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch &  
Birch, LLP

(57) **ABSTRACT**

An electronically controlled retractable landing light (100) for use with aircraft. A controller (106) compares the commanded position of a lighthead (108) by means of a contactless absolute position sensor (212). Operation of a brake (111), motor (110), and lamp (112) is controlled by a control unit (210). Electrical power to the brake (111), motor (110), and lamp (112) is slowly applied and removed to reduce electromagnetic emissions and extend the service life of a power stage (208), brake (111), motor (110), and lamp (112). The lighthead (108) may be manually stowed in the event of a fault.

**26 Claims, 3 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3

**ELECTRONICALLY CONTROLLED  
AIRCRAFT RETRACTABLE LANDING  
LIGHT WITH MANUAL RETRACTION  
CAPABILITY**

CROSS REFERENCE

This application is related to an application entitled "Efficient Solid State Switching and Control System for Retractable Landing Lights," by inventors D. Melvin and S. Mubaslat, filed concurrently with the present application, and issued as U.S. Pat. No. 6,608,445.

This application claims the benefit of U.S. Provisional Application No. 60/339,635 filed Dec. 12, 2001 entitled "Electronically Controlled Retractable Landing Light."

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to aircraft retractable landing lights. Specifically, the invention is directed to an aircraft retractable landing light having electronic position control and switching with manual lighthouse retraction capability.

2. Description of the Related Art

Landing lights are mounted to aircraft to illuminate the area forward of the aircraft during night operations on taxiways and runways. A "retractable landing light" is a remotely controlled, articulating light that can be stowed flush with the outside surface of the aircraft when not in use, reducing aerodynamic drag on the aircraft. The retractable landing light's lamp is housed in a lighthouse. The lighthouse is in turn hingedly affixed to a housing assembly, which is mounted to the airframe. The lighthouse is extended for use and retracted to a stowed position by means of an unsealed torque-amplifying transmission mechanism driven by an electric motor. The lighthouse is held in place by an electromechanical brake. When the flight crew actuates a remote control to an "Extend" position, the brake is released by applying electrical power to the brake's coil. Electrical power is simultaneously applied to the motor, causing the motor's output shaft to turn, driving the transmission. The lighthouse then extends to a predetermined position, aiming the lamp to illuminate the area forward of the aircraft. Power is then removed from the motor and the brake, causing the lighthouse to stop moving. The brake re-engages, preventing the motor's output shaft from turning. The holding force of the brake is amplified by the transmission mechanism, effectively holding the lighthouse in position against the force of the windstream encountered by an aircraft in flight. The motor and brake are also simultaneously activated when the remote control is placed in a "Stow" position. However, power is applied to the motor so as to cause the motor's output shaft to rotate counter to the direction used to extend the lighthouse. When the lighthouse is flush with the surface of the aircraft, power is again removed simultaneously from the motor and brake, holding the lighthouse in the stowed position. The lamp may be automatically switched on by means of a limit switch after the lighthouse is extended and then switched off when the lighthouse is retracted. Alternatively, the lamp may be manually controlled by a switch in the cockpit.

Prior retractable landing lights suffer from a number of shortcomings. In particular, prior retractable landing lights utilize electromechanical limit switches to detect the lighthouse's position, and electromechanical relays for control of the motor, brake, and lamp. Electromechanical switches and relays have limited operational life due to mechanical wear.

In addition, these switches and relays generate electromagnetic interference due to arcing at their electrical contacts. Electromechanical switches also hinder the ability to change the operational characteristics of the retractable landing light. It is desirable to change such operational characteristics as the extension angle of the lighthouse and the switching sequence of the lamp, brake, and motor in order to meet the particular needs of various models of aircraft.

Another drawback of electromechanical switches is that they do not lend themselves to precise position control due to the limited resolution of actuators. Precise position control is desirable to aim the lamp at the proper angle. If the lighthouse is extended to a smaller angle than desired, the lamp will be aimed too close to the aircraft. Conversely, if the lighthouse extension angle is too great, the lamp will be aimed too far ahead of the aircraft. Both conditions result in a reduction in visibility for the flight crew. Attempts to implement more precise mechanical position controls in prior retractable landing lights have resulted in more complex actuators, reducing the reliability of the retractable landing light. Mechanical wearing of the actuators, combined with changes in setting due to vibration, also contributes to shifting of the lamp extension angle over time, requiring regular maintenance to re-adjust the lighthouse to the proper angle.

A further disadvantage of electromechanical switches and relays is that current flow through the motor, brake and lamp is limited only by the capacity of the aircraft's electrical system and wiring. This places significant stress on the relay contacts, motor, brake, and lamp, causing these components to suffer reduced service life. "Soft" starting of the motor, brake, and lamp is desirable to limit electromagnetic emissions and maximize the life of these components.

A retractable landing light may be installed into more than one model of aircraft. However, design differences between models of aircraft usually necessitate a change in the extension angle setting of the lighthouse so that the lamp is properly aimed for a particular aircraft. This involves a time-consuming manual adjustment of position-control limit switches and repeated cycling of the retractable landing light. Means for pre-setting selectable extension angles for different models of aircraft is desired in order to reduce the amount of maintenance work required to install the retractable landing light into two or more models of aircraft.

Prior retractable landing lights utilize an open gearbox. Over time, exposure to the elements when the lighthouse is extended causes a loss of gearbox lubrication. Low viscosity grease is used to counter this loss, but at the expense of gearbox efficiency, particularly at low temperature extremes.

Retractable landing lights inherently have a failure mode whereby the lighthouse cannot be retracted. The aircraft cannot be dispatched in this condition, requiring maintenance personnel to remove and replace the retractable landing light. This can cause significant delays in the dispatch of the aircraft, particularly if the failure occurs at a remote location with limited maintenance capability. Although prior retractable landing lights have included manual retraction capability, the release mechanisms are slow and cumbersome.

Some improvements in remotely articulating aircraft lights have been made, such as Hamilton et al. U.S. Pat. No. 6,315,435 B1. However, Hamilton et al. teaches the use of potentiometers having wiping elements in contact with a resistive element. Potentiometers are subject to wear-out, limiting the service life of the aircraft light. Further, Hamilton does not teach how to preconfigure the operating envelope of an articulating light for different aircraft models,

since the preset positions disclosed in Hamilton define only the operating envelope limits for the lighthouse. Changes in the operating envelope to accommodate different aircraft models must be made by trial-and-error upon installation of the light into the aircraft. Also, Hamilton does not disclose how to reduce electromagnetic emissions and extend the service life of the motor brake and motor. In Metz et al., U.S. Pat. No. 5,355,131, an aircraft landing light utilizing contactless position sensing is taught. However, the position sensing disclosed in Metz does not accommodate reconfiguration of the operating envelope for different aircraft models, necessitating trial-and-error adjustment.

There is a need to limit inrush currents and eliminate the low-reliability relays and switches associated with retractable landing lights. There is also a need to provide a more reliable, precise, and easily reconfigurable means of controlling the position of the retractable landing light's lighthouse. There is a further need to protect the gearbox from the elements. Finally, there is a need to provide capability for aircraft with failed retractable landing lights to delay repair and to dispatch with the failed light in place.

#### SUMMARY OF THE INVENTION

This invention is directed to an electronically controlled retractable landing light. The retractable landing light utilizes contactless absolute position sensing to detect the position of the lighthouse. The retractable landing light also incorporates electronic control of the brake, motor, and lamp. An improved means of manually retracting the lighthouse allows the aircraft to be dispatched in spite of a failure of the retractable landing light.

Specifically, the present invention includes filters to isolate electrical noise between the retractable landing light and the aircraft. A power supply is used to convert the power supplied by the aircraft to a level compatible with the retractable landing light. A power stage utilizes solid state switches with "soft-switching" capability to limit electrical stress on the solid-state switches when turning the brake, motor, and lamp on and off. This soft-switching capability reduces electromagnetic emissions from the brake, motor, and lamp, and extends the service life of these components. A control unit monitors mode and position command signals and lighthouse position pre-sets. The control unit actuates the brake, motor, and lamp to move the lighthouse to the commanded position, hold the lighthouse in place, and turn the lamp on and off, depending on the mode selected. The control unit also provides proper, synchronized timing of the actuation of the brake, motor, and lamp to eliminate overlapping actuation of these devices for reduced electromagnetic emissions and to minimize the generation of switching transients on the aircraft electrical bus.

The present invention comprises an electronically controlled retractable light, comprising: means for mounting the retractable light; an electrical motor connected with said mounting means, said motor including a brake; means for reducing speed and amplifying torque coupled to said motor, said speed reducing and torque amplifying means being environmentally sealed; a lighthouse connected movably with said mounting means and connected with said speed reducing and torque amplifying means, said lighthouse including at least one lamp; contactless means for monitoring absolute position of said lighthouse; at least one solid state switch, wherein said solid state switch slowly activates and deactivates; and a control unit communicating with said position monitoring means to: monitor the position of said lighthouse; provide timed actuation of said brake, motor, and

lamp to prevent simultaneous actuation of said brake, motor and lamp; and to stow said lighthouse or position said lighthouse at a predetermined angle.

These and other features will become better understood with reference to the following description, appended claims, and accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the retractable landing light;  
 FIG. 2 is an electrical block diagram of the retractable landing light; and  
 FIG. 3 is a detail of the manual retraction means.

#### DETAILED DESCRIPTION OF THE INVENTION

A retractable landing light **100** is shown in FIG. 1. A baseplate or mounting means **102** is a chassis and also facilitates mounting of the retractable landing light **100** into an aircraft. Power from the aircraft is converted to a level compatible with a lamp **112** by a transformer **104**. A controller **106** monitors the position of a lighthouse **108**. The controller **106** also provides "soft start" solid-state power switching of a motor **110**, a brake **111**, and the lamp **112** to extend the life of the motor **110**, brake **111**, and lamp **112** and reduce electromagnetic emissions. In addition, the controller **106** may provide protection from fault conditions such as excessive current or over-temperature conditions, a stalled motor **110**, and blockages to the lighthouse **108**. Further, the controller **106** easily facilitates changes to the setpoint of the lighthouse **108** and the addition of new functions. The controller **106** may optionally include means for regularly flashing the lamp **112** on and off or from a higher voltage to a lower voltage to attract the attention of other aircraft operating in the vicinity, reducing the risk of runway incursions.

An environmentally sealed gearbox or other means for reducing speed and amplifying torque **114** converts the high-speed, low-torque output of the motor **110** to a low-speed, high-torque rotational mechanical drive. The output of gearbox **114** is coupled to means for driving and linking, such as a pair of drive arms **116** and connecting links **118**, which provide leverage to move the lighthouse **108** against the force of the airstream encountered by an aircraft in flight.

Vibration-damping gasketing **120** is placed between the lamp **112** and a lamp retainer **122**. The vibration-damping gasketing **120** equally distributes the retaining force applied to the lamp **112** by lamp retainer **122**, reducing the risk of failure of lamp **112** due to cracking of the glass envelope of lamp **112**. Further, the vibration-damping gasketing **120** reduces mechanical stress on the filament of lamp **112** due to vibration, aiding to extend the service life of the lamp **112**.

A block diagram of the electrical portion of the retractable landing light **100** is shown in FIG. 2. A set of filters **202** and **204** isolate electrical noise, such as electromagnetic interference, between the aircraft and a power supply **206**, a power stage **208**, and a control unit **210**. The power supply **206** converts electrical power from the aircraft to a level compatible with the control unit **210** and the power stage **208**. The position of the lighthouse **108** is sensed by an absolute position sensor **212**. Means for controlling such as the control unit **210** provides control functions, such as for example, turning the lamp **112** on and off, actuation of power to brake **111** and motor **110**, setting the direction of rotation of the motor **110**, and resolution of the position of the lighthouse **108**. The power stage **208** provides "soft start"

electrical drive for the brake **111**, motor **110**, and the lamp **112** to reduce electrical stress on brake **111**, motor **110**, and lamp **112** and to reduce electromagnetic emissions from the brake **111**, motor **110**, and lamp **112**. The control unit **106** may also monitor for fault conditions, such as excessive current or over-temperature conditions, a stalled motor **110**, and blockages to the lighthouse **108**. If a fault is detected, control unit **106** will disable power stage **208** until the fault is cleared.

The extend angle setting switch **214** is set to the desired position for a particular aircraft when the retractable landing light **100** is installed into the aircraft. The extend angle setting switch **214** provides selectable preset position commands to the control unit **210** for positioning the lighthouse **108** to one or more predetermined extension angles (i.e., extension setpoints), eliminating the time-consuming step of manually calibrating the extension angle of lighthouse **108** for a particular aircraft. Extend angle setting switch **214** may utilize one or more bits of digital logic, or may be an analog voltage level, such as derived from a voltage divider network. Means for monitoring the state of the extend angle setting switch **214**, such as control unit **210**, is configured such that the state of extend angle setting switch **214** represents a predetermined extension angle, or extension setpoint, for lighthouse **108**. Upon receiving an "Extend" command at terminal **218**, control unit **210** will position the lighthouse **108** at the extension angle represented by the state of extend angle switch **214**.

Contactless means for monitoring absolute position **212**, such as a Hall-effect rotary position sensor, is coupled to the lighthouse **108** and provides the control unit **210** with continuous information on the angular extension position of the lighthouse **108** so that the control unit **210** can control actuation of the brake **111**, actuation of the motor **110**, the direction of rotation of the motor **110**, and illumination of the lamp **112** by appropriate synchronization of the on-off control of the power stage **208**. Incremental-type position encoders may alternatively be used, but absolute-type position encoders are preferred because absolute-type position encoders do not require periodic calibration to an index position.

The retractable landing light **100** is commanded to extend or retract, and to switch the lamp **112** on and off, by means of control signals supplied to the control unit **210**. To command the lighthouse **108** to a stowed position when the retractable light **100** is not in use, an electrical control signal is applied to a "Retract" input terminal **216**, causing the lighthouse **108** to move to a predetermined stow position, preferably out of the airstream to minimize aerodynamic drag on the aircraft. To command the lighthouse **108** to extend, an electrical control signal is applied to an "Extend" input terminal **218**. To turn on the lamp **112**, an electrical control signal is applied to a "Lamp On" terminal **220**. The control unit **210** may optionally provide means for indicating to the flight crew that the lighthouse **108** is in an extended position, such as a status output signal via a "Extended Indicator" terminal **224**. The output signal present at terminal **224** is wired to an appropriate indication means in the cockpit, such as an indicator light or a caution and warning computer. The voltage level present at the "Extended Indicator" terminal **224** may be fixed at a level compatible with the associated cockpit indication means by connecting an appropriate voltage source to an "Indicator Supply" input terminal **222**.

If the lighthouse **108** cannot be stowed due to a failure condition, the aircraft may not be permitted to dispatch due to operating limitations for the aircraft. The retractable

landing light **100** may optionally include means for disengaging the lighthouse **108** to manually stow the lighthouse **108** as shown in FIG. 3 to overcome this limitation. The manual retraction means will allow the aircraft to dispatch under conditions where the lighthouse **108** must be stowed but operation of the retractable landing light **100** is not required, such as daylight operations. To manually stow the lighthouse **108**, one or more release bolts **302** are removed. This disengages the drive arms **116** from the gearbox **114**, allowing the lighthouse **108** to be pivoted to the stowed position by pushing the lighthouse **108** until the lighthouse **108** is flush with the baseplate **102**. The release bolts are then re-installed while holding the lighthouse **108** in place, securing the lighthouse **108** in the stowed position. The aircraft may then be dispatched.

In operation, the landing light **100** may be actuated by one of manual and automatic means. For manual operation, the flight crew commands the desired position for the retractable landing light **100** by means of a control switch remotely mounted in the cockpit. Alternatively, the command signal may be generated automatically, such as from an "air-ground" switch that senses whether or not the aircraft is in flight. When the controller **106** receives a command signal, the controller **106** compares the commanded position to the actual position of lighthouse **108**, using absolute position encoder **212**. The controller **106** first actuates the brake **111** and then the motor **110**, which in turn drives a speed reduction and torque amplification transmission means **114**, such as a gearbox. The gearbox **114**, which is sealed from exposure to the elements, converts the high-speed, low-torque output of the motor **110** into a low-speed, high-torque mechanical drive capable of extending the lighthouse **108** against the force of the windstream encountered by an aircraft in flight. The gearbox **114** moves a drive arm **116**, attached to the lighthouse **108** by a set of connecting links **118**, causing the lighthouse **108** to extend or retract as needed until the proper position for the lighthouse **108** is reached. The controller **106** controls power to the lamp **112**, switching the lamp **112** on when the lighthouse **108** is in an extended position and switching the lamp **112** off when the lighthouse **108** is in a stowed position. The controller **106** provides a "soft start" turn-on of the lamp **112** by limiting inrush current, thereby extending the life of the lamp **112**. The lighthouse **108** further aids to increase the life of lamp **112** through the use of vibration-damping gasketing **120** to reduce mechanical stress on the lamp **112**.

What is claimed is:

1. An electronically controlled retractable light, comprising:

- means for mounting the retractable light;
- an electrical motor connected with said mounting means, said motor including a brake;
- means for reducing speed and amplifying torque coupled to said motor, said speed reducing and torque amplifying means being environmentally sealed;
- a lighthouse connected movably with said mounting means and connected with said speed reducing and torque amplifying means, said lighthouse including at least one lamp;
- a contactless means for monitoring absolute position of said lighthouse;
- at least one solid state switch configured to perform separate power switching events for said brake, motor, and lamp, respectively, wherein said at least one solid state switch performs the power switching events according to a soft switching scheme; and

a control unit communicating with said position monitoring means and at least one solid state switch to: monitor the position of said lighthouse; prevent simultaneous power switching events for said brake, motor and lamp; and to position said lighthouse at a predetermined angle.

2. The electronically controlled retractable light of claim 1, further comprising an extend angle setting switch to set at least one extension setpoint for said lighthouse.

3. The electronically controlled retractable light of claim 2, further comprising means to monitor the state of said extend angle setting switch.

4. The electronically controlled retractable light of claim 2, wherein said control unit communicating further comprises means to monitor the state of said extend angle setting switch.

5. The electronically controlled retractable light of claim 1, wherein the means for reducing speed and amplifying torque include means for driving and linking, and said retractable light further comprising means for disengaging said means for driving and linking from said means for reducing speed and amplifying torque to manually stow said lighthouse.

6. The electronically controlled retractable light of claim 1, wherein said lighthouse includes a lamp retainer, and vibration-damping gasketing is positioned between said lamp and said lamp retainer.

7. The electronically controlled retractable light of claim 1, wherein said control unit provides means for indicating to the crew when said lighthouse is not in a stowed position.

8. The electronically controlled retractable light of claim 1, wherein said retractable lamp is actuated by one of manual and automatic means.

9. The electronically controlled retractable light of claim 1, further including means to regularly flash said lamp to attract attention.

10. The electronically controlled retractable light of claim 1, wherein said control unit is operable to monitor for over-current faults, over-temperature faults, stall of said motor, and blockages of said lighthouse, and wherein said control unit is operable to disable said solid state switches until said faults, motor stall, and blockages are no longer present.

11. The electronically controlled retractable light of claim 1, wherein said retractable light is an aircraft light.

12. A process for providing an electronically controlled, retractable light, comprising:

- providing means for mounting the retractable light;
- placing at said mounting means an electrical motor, said motor including a brake;
- providing environmentally sealed means for reducing the speed and amplifying the torque of said motor;
- movably connecting a lighthouse to said mounting means and connecting said lighthouse with said means for speed reducing and torque amplifying, said lighthouse including at least one lamp;
- performing separate power switching events for said brake, motor, and lamp, respectively, according to a soft switching scheme;
- applying torque to said lighthouse by way of said means for speed reducing and torque amplifying;
- providing contactless means for monitoring absolute position of said lighthouse;
- providing means for controlling said lighthouse in order to: monitor the position of said lighthouse; prevent simultaneous power switching events for said brake, motor and lamp; and

stowing said lighthouse or positioning said lighthouse at a predetermined angle of extension.

13. The process of claim 12, further comprising providing at least one extension setpoint for said lighthouse.

14. The process of claim 13, further comprising monitoring said extension setpoint.

15. The process of claim 12, further comprising providing said means for speed reducing and torque amplifying with means for driving and linking, and providing means for disengaging said means for driving and linking from said means for speed reducing and torque amplifying to manually stow said lighthouse.

16. The process of claim 12, further comprising adding a lamp retainer to said lighthouse and placing vibration-damping gasketing between said lamp and said lamp retainer.

17. The process of claim 12, further comprising providing means for indicating to the crew when said lighthouse is not in a stowed position.

18. The process of claim 12, further comprising regularly flashing said lamp to attract attention.

19. The process of claim 12, further comprising monitoring for at least one of over-current faults, over-temperature faults, stall of said motor, and blockages of said lighthouse, and disabling said motor, brake, and lamp until said at least one of over-current faults, over-temperature faults, motor stall, and blockages are no longer present.

20. A process for providing an electronically controlled, retractable light, comprising:

- providing means for mounting the retractable light;
- placing at said mounting means an electrical motor, said motor including a brake;
- providing environmentally sealed means for reducing the speed and amplifying the torque of said motor;
- movably connecting a lighthouse to said mounting means and connecting said lighthouse with said means for speed reducing and torque amplifying, said lighthouse including at least one lamp;
- supplying electrical power to said brake, motor, and lamp such that power to said brake, motor, and lamp can be slowly activated and deactivated;
- applying torque to said lighthouse by way of said means for speed reducing and torque amplifying;
- providing contactless means for monitoring absolute position of said lighthouse;
- providing means for controlling said lighthouse in order to: monitor the position of said lighthouse; provide timed actuation of said brake, motor, and lamp to prevent simultaneous actuation of said brake, motor and lamp;
- stowing said lighthouse or positioning said lighthouse at a predetermined angle of extension;
- providing at least one extension setpoint for said lighthouse wherein said extension setpoints include a setting for positioning said lighthouse at a stowed position;
- monitoring said extension setpoint; and
- providing said means for speed reducing and torque amplifying with means for driving and linking, and providing means for disengaging said means for driving and linking from said means for speed reducing and torque amplifying to manually stow said lighthouse.

21. The process of claim 20, further comprising: adding a lamp retainer to said lighthouse and placing vibration-damping gasketing between said lamp and said lamp retainer; and providing means for indicating to the crew when said lighthouse is not in a stowed position.



22. A method for electronically controlling a mounted retractable light, which is provided with a mounted electrical motor including a brake and a movably connected lighthouse including a lamp, comprising:

performing separate power switching events for said brake, motor, and lamp, respectively, where the power switching events are performed in such a manner as to gradually or switch off electrical power to the brake, motor, and lamp using soft switching;

monitoring absolute position of the lighthouse; and  
controlling actuation of the brake, motor, and lamp so as to prevent simultaneous power switching events for the brake, motor and lamp.

23. The method of claim 22, further comprising:

setting a plurality of angle extension setpoints for positioning the lighthouse, the angle extensions setpoints including a setpoint corresponding to a stowed position for the lighthouse; and

selecting one of a plurality of position commands corresponding to the extension setpoints in order to position the lighthouse at a desired extension setpoint.

24. The method of claim 22, wherein the monitoring step is performed without the use of contacts.

25. The method of claim 22, further comprising reducing speed and amplifying torque of the electrical motor output using an environmentally sealed device.

26. A device for electronically controlling a mounted retractable light, which is provided with a mounted electrical motor including a brake and a movably connected lighthouse including a lamp, comprising:

means for performing separate power switching events for said brake, motor, and lamp, respectively, wherein the power switching events are performed in such a manner as to gradually supply and switch off electrical power to the brake, motor, and lamp using soft switching;

means for monitoring absolute position of the lighthouse; and

means for controlling actuation of the brake, motor, and lamp so as to prevent simultaneous power switching events for the brake, motor and lamp.

\* \* \* \* \*