



(19) **United States**  
(12) **Patent Application Publication**  
Sato et al.

(10) **Pub. No.: US 2011/0003499 A1**  
(43) **Pub. Date: Jan. 6, 2011**

(54) **CARD CONNECTOR**

**Publication Classification**

(75) Inventors: **Shigeru Sato**, Chiba-shi (JP);  
**Masato Koyasu**, Sakura-shi (JP);  
**Yosuke Takai**, Sakura-shi (JP);  
**Masaaki Oshima**, Tokyo (JP)

(51) **Int. Cl.**  
**H01R 13/62** (2006.01)  
(52) **U.S. Cl.** ..... **439/325**

Correspondence Address:  
**OLIFF & BERRIDGE, PLC**  
**P.O. BOX 320850**  
**ALEXANDRIA, VA 22320-4850 (US)**

(57) **ABSTRACT**

A card insertion slot in the card connector through which two types of cards, large and small cards, can be selectively installed in a card accommodation space include first and second guideways in corresponding to the sizes of the cards. The card connector includes first and second contacts, a lock bracket configured to detect the width of the large card, an actuator configured to be rotatable, and a partition member including a partition plate configured to be movable. When the large card is inserted into the card connector, the lock bracket is moved from the first position to the second position. When the large card is further fed into the card connector, the actuator is rotated from the first position to the second position, and the partition plate is moved from the first position to the second position.


(73) Assignees: **YAMAICHI ELECTRONICS CO., LTD.**, TOKYO (JP); **SONY CORPORATION**, TOKYO (JP)

(21) Appl. No.: **12/801,080**

(22) Filed: **May 20, 2010**

(30) **Foreign Application Priority Data**

Jul. 2, 2009 (JP) ..... 2009-158094






FIG. 1




FIG.2




FIG. 3A




FIG. 3B




FIG.4





FIG. 5B






FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C






FIG. 8A




FIG. 8B




FIG.9




FIG.10




FIG. 11A




FIG. 11B




FIG.12




FIG.13




FIG. 14A




FIG. 14B

**CARD CONNECTOR**

**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims the benefit of Japanese Patent Application No. 2009-158094, filed Jul. 2, 2009, which is hereby incorporated by reference herein in its entirety.

**BACKGROUND OF THE INVENTION**

[0002] 1. Field of the Invention

[0003] The present invention relates to a card connector in which cards of different sizes can be installed through one card insertion slot, and more specifically, to a card connector in which an actuator configured to sort cards in accordance with the sizes of the cards enables movement of a movable plate configured to guide each card upward and downward.

[0004] 2. Description of the Related Art

[0005] In connection with electronic apparatuses and information terminal apparatuses, card connectors are known in which a card with a built-in integrated circuit (hereinafter simply referred to as an "IC card") used as a CPU or a memory is installed in order to enhance the functions of the electronic apparatus. On the other hand, various types of IC cards for installation in the card connector have emerged; the IC cards vary in size, shape, and the positions where external contact points are arranged. In association with the wide variety of emerging IC cards, there has been a demand for a card connector in which many types of IC cards can be installed.

[0006] For example, a card connector disclosed in Japanese Patent Laid-Open No. 2001-135385 is used for IC cards having different thicknesses but almost the same length and including pads corresponding to external contact points and the positions of which are the same for all the IC cards so as to allow contacts to be shared by the different types of IC cards. A card connector disclosed in Japanese Patent Laid-Open No. 2004-193111 is used for IC cards which vary in thickness, width, length, or pad position and in which contacts are arranged in a card insertion direction depending on the length of the IC card. A card connector disclosed in Japanese Patent Laid-Open No. 2004-206963 is used for IC cards which have different thicknesses and widths but almost the same length and which vary in pad position.

[0007] The card connector proposed in Japanese Patent Laid-Open No. 2004-206963 allows two types of IC cards with different shapes to be selectively installed therein, and includes an intervening partition plate configured to allow each IC card to reliably contact corresponding contacts. The card connector determines the size of the inserted IC card (specifically, the width of the IC card) to allow the partition plate to be actuated so that the IC card is guided to a predetermined position. The partition plate in the card connector extends from a recognition means (specifically, a card guide) for determining a difference in size among IC cards to an end wall of a connector main body positioned opposite a card insertion slot. Moreover, the card connector is configured such that the two types of IC cards are both inserted into the card connector in a normal insertion posture (in other words the pads face downward).

[0008] When the two types of IC cards are thus inserted into the card connector in the same posture, the contacts for the IC card installed over the partition plate are arranged at the midpoint of the height of the card connector. Thus, the con-

tacts need to be accurately installed in order to provide a desired electric contact pressure between the IC card and contacts. Furthermore, the relationship between the partition plate and the contacts arranged above and below the partition plate contributes to limiting reduction of the overall height of the card connector.

[0009] An object of the present invention is to provide a card connector of a type including a partition plate configured to enable two types of IC cards with different shapes to be installed therein, thus allowing an appropriate electric contact pressure to be exerted between each IC card and the corresponding contacts. Furthermore, the card connector according to the present invention allows a reduction in the height of the card connector.

**SUMMARY OF THE INVENTION**

[0010] To accomplish the above-described object, the present invention provides a card connector in which a base member and a cover member form a card accommodation space with a card insertion slot and in which two types of cards, a large card and a small card, are capable of being selectively installed in the card accommodation space, the card insertion slot including paired first guideways along which the large card is guided and paired second guideways along which the small card is guided, the card connector including a plurality of contacts including a plurality of first contacts for the large card which include contact points arranged so as to face downward in the card accommodation space and a plurality of second contacts for the small card which include contact points arranged so as to face upward in the card accommodation space, paired lock brackets configured to detect the width of the large card provided in the first guideways to move from a first position to a second position, an actuator configured to engage with the paired lock brackets and to be rotatable from the first position to the second position, the actuator including at least an engagement portion and a passage opening through which the small card is capable of passing, and a partition member including a partition plate configured to be movable from the first position to the second position and a driving piece configured to engage with the engagement portion, the partition member sorting the inserted large and small cards to an upper part and a lower part, respectively, of the card accommodation space, wherein when the large card is inserted into the card connector with an external contact oriented upward, the lock bracket is moved from the first position to the second position to enable the actuator to be rotated, and when the large card is further fed into the card connector, the actuator is rotated from the first position to the second position to move the partition plate from the first position to the second position, thus allowing the large card to be guided to the upper part of the card accommodation space.

[0011] According to the present invention, preferably, a pair of the engagement portions is formed on the actuator, and a pair of the driving pieces configured to engage with the respective paired engagement portions is formed on the partition plate.

[0012] Furthermore, according to the present invention, the engagement portion preferably includes a recess portion formed therein and with which the driving piece is engaged.

[0013] Moreover, in the card connector according to the present invention, preferably, the partition member is movable to a third position, and includes paired elongate spring receiving portions on respective opposite sides of the parti-



tion plate, and the partition plate is biased to the first position by paired pushup springs provided on the base member and corresponding to the paired elongate spring receiving portions.

[0014] Additionally, in the card connector according to the present invention, the partition member further includes a vertical guide piece and at least paired regulation pieces so as to allow the partition plate to be guided upward and downward and to allow elevation of partition plate to be regulated.

[0015] In the card connector according to the present invention, the second contact and the paired pushup springs may be formed as inserts embedded in the base member.

[0016] The present invention includes a lock bracket and an actuator to allow two types of cards, large and small cards, to be prevented from being incorrectly inserted. Furthermore, a partition member moves upward and downward to allow the two types of cards, the large and small cards, to be reliably sorted. Additionally, the height of the card connector can be reduced. Moreover, the present invention allows cards to be inserted into the card connector both in a normal state and in a reverse state. This allows the contacts to be significantly displaced so as to reliably achieve electric contact, and enables a reduction in the height of the card connector. Furthermore, the present invention utilizes the rotation of the actuator to move the partition member. This enables a reduction in the number of components required, and allows the configuration of the card sorting mechanism to be simplified. Moreover, the present invention uses, pushup springs to bias the partition member upward and provides the vertical guide piece and the regulation pieces. This enables the partition member to be reliably moved upward and downward and allows the electric contact between each of the large and small cards and the corresponding contacts to be ensured.

[0017] Further features of the present invention will become apparent from the following description of the exemplary embodiments (with reference to the attached drawings).

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a perspective view of a card connector according to the present invention;

[0019] FIG. 2 is a perspective view of the card connector shown in FIG. 1 and from which a cover member has been removed;

[0020] FIG. 3A is a top view of the card connector shown in FIG. 1;

[0021] FIG. 3B is a sectional view taken along line IIIB-III B in FIG. 3A;

[0022] FIG. 4 is a top view of the card connector in FIG. 2;

[0023] FIG. 5A is a perspective view of a partition plate used for the card connector in FIG. 1;

[0024] FIG. 5B is a top view of the partition plate shown in FIG. 5A;

[0025] FIG. 6A is a top view of the card connector in which an IC card has come into contact with lock brackets to cancel a locked state and from which the cover member has been removed as in the case of FIG. 4;

[0026] FIG. 6B is a sectional view taken along line VIB-VIB in FIG. 6A;

[0027] FIG. 7A is a top view similar to FIG. 6A, showing the card connector in which the actuator is rotating;

[0028] FIG. 7B is a sectional view taken along line VII B-VII B in FIG. 7A;

[0029] FIG. 7C is a sectional view taken along line VIIC-VIIC in FIG. 7A;

[0030] FIG. 8A is a top view similar to FIG. 6A, showing the card connector in which the actuator has finished rotating, with the tip portion of the IC card starting to climb onto the partition plate;

[0031] FIG. 8B is a sectional view taken along line VIII B-VIII B in FIG. 8A;

[0032] FIG. 9 is a sectional view similar to FIG. 8B, showing the card connector in which the tip of the IC card has come into abutting contact with a front wall;

[0033] FIG. 10 is a sectional view similar to FIG. 8B, showing the card connector in which the IC card has been completely installed in the card connector;

[0034] FIG. 11A is a top view similar to FIG. 3A, showing the card connector in which the IC card has been placed under the partition plate;

[0035] FIG. 11B is a sectional view taken along line XI B-XI B in FIG. 11A;

[0036] FIG. 12 is a sectional view similar to FIG. 11B, showing the card connector in which the tip of the IC card has come into abutting contact with the front wall;

[0037] FIG. 13 is a sectional view similar to FIG. 11B, showing the card connector in which the IC card has been completely installed in the card connector;

[0038] FIG. 14A is a top view of an insert embedded in base member; and

[0039] FIG. 14B is a side view of the insert shown in FIG. 14A.

#### DESCRIPTION OF THE EMBODIMENTS

[0040] A preferred embodiment of the present invention will be described below with reference to FIG. 1 to FIG. 14.

[0041] First, the configuration of a card connector will be described. FIG. 1 is a perspective view of the card connector according to the present invention. FIG. 2 is a perspective view of the card connector from which a cover member has been removed. FIG. 3A is a top view of the card connector shown in FIG. 1. FIG. 3B is a sectional view taken along line III B-III B in FIG. 3A. FIG. 4 is a top view of the card connector. FIG. 5A is a perspective view of a partition plate used for the card connector. FIG. 5B is a top view of the partition plate shown in FIG. 5A. FIG. 14A is a top view of an insert embedded in a base member. FIG. 14B is a side view of the insert shown in FIG. 14A.

[0042] In the description below, the terms “left” and “right” refer to the +x direction and -x direction, respectively, in the coordinate system shown in FIGS. 1 and 2. The terms “front” and “rear” refer to the +y direction and -y direction, respectively, shown in FIG. 1. The terms “upward” and “downward” refer to the +z direction and -z direction, respectively, shown in FIG. 1.

[0043] The card connector according to the present invention is such that two types of IC cards 200 and 300 (see FIGS. 6A and 6B and FIGS. 11A and 11B) with different sizes (for example, different thicknesses or widths) can be selectively installed in the card connector 1. One of the IC cards used in the present embodiment, the IC card (hereinafter simply referred to as the “large card”) 200, is, for example, an SD (Secure Digital) card, which is wide and thick. The other IC card, the IC card (hereinafter simply referred to as the “small card”) 300, is, for example, a Memory Stick Duo (registered trade mark) or Memory Stick PRO-HG Duo, which is narrower and thinner than the large card. However, the IC cards

used are not limited to those described above. The two types of IC cards **200** and **300** have only to vary at least in width and pad arrangement.

[0044] In the present embodiment, the large card **200** is an IC card with a wide upper portion **201** and a narrow lower portion **202** and thus both the left and right sides have a stepped shape. In the present embodiment, as shown in FIG. 6A to FIG. 10, the large card **200** is installed in the card connector **1** in a reverse state, in which a surface of the large card **200**, on which pads **203** serving as external contacts are formed, faces upward (in other words, the large card **200** is turned upside down). On the other hand, the small card **300** is an ID card with an upper portion and a lower portion narrower than the upper and lower portions **201** and **202**, respectively, of the large card **200**. In the present embodiment, the small card is installed in the card connector **1** in a normal state in which a surface of the small card, on which pads (not shown in the drawings) serving as external contacts are formed, is oriented downward.

[0045] The card connector **1** generally includes a base member **10**, a cover member **20**, a partition member **40**, a lock bracket **50**, an actuator **60**, a plurality of contacts **80** and **90**, and an ejector mechanism **100**. In the present embodiment, the card connector **1** may further include a write protect switch **70** and a card recognition switch **120**.

[0046] The cover member **20** generally includes a top plate **21**, a right side wall **22**, and a left side wall **23** and has a substantially inverted-U vertical cross section. The cover member **20** is formed by using press working to punch and bend a thin metal plate. A plurality of mounting holes **24** are formed in each of the right and left side walls **22** and **23** of the cover member **20**. The mounting holes **24** engage with corresponding projections **19** formed on each of a right side wall **13** and a left side wall **14** of a base member **10** described below, to form the card connector **1**. That is, as shown in FIG. 1, the cover member **20** is laid on top of the base member **10** to form an IC card accommodation space with a card insertion slot **5** that is open backward.

[0047] The base member **10** includes a bottom wall **11**, a front wall **12**, and the right and left side walls **13** and **14**, and is shaped generally like a box. The base member **10** is formed of plastic, which is electrically insulated. Furthermore, a metal insert **30** described below (see FIGS. 14A and 14B) is embedded in the bottom wall **11** of the base member **10** by insert molding. As described above, the base member **10** is laid on bottom of the cover member **20** to form the IC card accommodation space. The IC card accommodation space includes the IC card insertion slot **5** that is open backward.

[0048] A plurality of through-holes **12a** penetrating the front wall **12** in a front-rear direction is formed in the upper part of the front wall **12** of the base member **10**. A plurality of first contacts **80** corresponding to the respective pads on the large card **200** are pressed in the respective through-holes **12a**. Thus, the plurality of first contacts **80** are supported, like cantilevers, by the front wall **12** so that respective contact points **81** can be displaced upward and downward. The contact points **81** projecting from the contacts **80** and shaped like circular arcs are supported so that the circular arc projecting portions are directed downward.

[0049] Paired guideways are formed in the right and left side walls **13** and **14**, respectively, so that the two types of IC cards with different widths are guided along the guideways into the card accommodation space. In the present embodiment, an upper-stage guideway **15**, a middle-stage guideway

**16**, and a lower-stage guideway **17** are formed on a side of each of the right and left side walls **13** and **14** which faces the card accommodation space; the paired upper-stage guideways **15**, the paired middle-stage guideways **16**, and the paired lower-stage guideways **17** are formed in the right and left side walls **13** and **14**, respectively. The upper-stage guideway **15**, the middle-stage guideway **16**, and the lower-stage guideway **17** are each perpendicular to the bottom wall **11** and are formed parallel to one another. The two adjacent guideways form a step.

[0050] The paired upper-stage guideways **15** formed in the right and left side walls **13** and **14**, respectively, each have almost the same width as or a slightly larger width than that of the lower portion **202** of the large card **200**. Similarly, the paired middle-stage guideways **16** each have almost the same width as or a slightly larger width than that of the upper portion **201** of the large card **200**. The paired lower-stage guideways **17** each have almost the same width as or a slightly larger width than that of the small card. That is, the upper-stage guideway **15** and the middle-stage guideway **16** correspond to a first guideway along which the large card **200** in the reverse state is guided. The lower-stage guideway **17** corresponds to a second guideway along which the small card **300** is guided.

[0051] Paired lock brackets **50** are provided behind the right and left side walls **13** and **14**, respectively, of the base member **10**. In the present embodiment, the paired lock brackets **50** are arranged in respective rear accommodation grooves **13a** and **14a** formed in the rear parts of the right and left side walls **13** and **14**, respectively, so as to lie laterally symmetrically opposite each other (the rear accommodation grooves **13a** and **14a** are formed closer to the card insertion slot **5**).

[0052] The paired lock brackets **50** have the same shape. Here, the right lock bracket **50** located in the rear accommodation groove **13a** of the right side wall **13** will be described. Description of the left lock bracket **50** located in the rear accommodation groove **14a** of the left side wall **14** is omitted.

[0053] The lock bracket **50** includes an elastic deformation piece **51** located on a card accommodation space side (inner side) of the rear accommodation groove **13a** and a fixed piece **53** located on a side (outer side) far from the card accommodation space. The elastic deformation piece **51** and the fixed piece **53** are parallel to each other and are coupled to each other at the rear parts thereof so as to generally have a substantially U-shaped horizontal cross section. A contact portion **52** is provided near the rear part of the elastic deformation piece **51** which is coupled to the fixed piece **53**; the contact portion **52** projects into the card accommodation space through an opening **16a** formed in the middle-stage guideway **16** of the right side wall **13** near the card insertion slot **5**. An opening **54** to be engaged with a projecting pin **62** (**63**) of an actuator **60** described below is formed on a front free end side of the elastic deformation piece **51**. Specifically, the lock bracket **50** is formed by using press working to punch a thin metal plate to obtain an elongate plate and then to fold the elongate plate. The lock bracket **50** is supported in the rear accommodation groove **13a** of the left side wall **13** by using an appropriate technique to fix the fixed piece **53** in the rear accommodation groove **13a** of the left side wall **13** (in the present embodiment, pressing the fixed piece **53** in a predetermined recessed groove). The rear accommodation groove **13a** is formed such that the groove **13a** as a whole communicates with the card accommodation space, within an area of

the groove **13a** located in front of a part thereof corresponding to the opening **54** in the elastic deformation piece **51** and extending to a partition wall **13b**. Thus, the paired upper-stage guideways **15**, the paired middle-stage guideways **16**, and the paired lower-stage guideways **17** extend from the card insertion slot **5** to a position immediately in front of the part of the rear accommodation groove **13a** corresponding to the opening **54** in the elastic deformation piece **51**.

[0054] When the paired lock brackets **50** are assembled into the card connector **1**, in other words, when the large card **200** is not installed in the card connector **200**, the paired lock brackets **50** are placed in a first position where paired contact portions **52** of the paired elastic deformation pieces **51** are closed as shown in FIG. 4. With the paired lock brackets **50** thus arranged, when the upper portion **201** of the large card **200** is guided along the paired middle-stage guideways **16**, the paired contact portions **52** are pushed out from the card accommodation space by the large card **200**. That is, the paired lock brackets **50** move to a second position where the paired contact portions **52** are open. The exit (push-out) of the paired contact portions **52** from the card accommodation space causes the paired elastic deformation pieces **51** to be displaced so as to laterally open the front free ends of the paired elastic deformation pieces **51**. Then, the projecting pins **62** of the actuator **60** are removed from the openings **54** formed at the front free ends of the paired elastic deformation pieces **51**. This enables the actuator **60** to move pivotally.

[0055] A front accommodation groove **13c** is formed, via the partition wall **13b**, in front of the rear accommodation groove **13a** in the left side wall **13** of the base member **10**. The write protect switch **70** and card recognition switch **120** both formed to partly project into the card accommodation space are arranged in the front accommodation groove **13c** in the left side wall **13**.

[0056] A front accommodation groove **14c** is formed, via the partition wall **14b**, in front of the rear accommodation groove **14a** in the right side wall **14**. The eject mechanism **100** is located in the front accommodation groove **14c** in the right side wall **14** to assist discharging the IC card **200** or **300** installed in the card accommodation space.

[0057] The eject mechanism **100** according to the present embodiment is of a conventional, well-known push-push type and will be described in brief. In the present embodiment, the eject mechanism **100** generally includes a swinging arm **101**, an eject member **104**, a card abutting member **105**, and a compression coil spring **107**.

[0058] The swing arm **101** included in the eject mechanism **100** functions as a cam follower with one end swingably supported by the partition wall **14b** and the other end guided through a cam groove **103** formed in the eject member **104**. As shown in FIG. 4, a heart cam **102** and a cam groove **103** are formed on the top surface of the eject member **104**. The eject member **104** is accommodated in the front accommodation groove **14c** formed in front of the partition wall **14b** of the right side wall **14**, so as to move slidably forward and rearward through the front accommodation groove **14c**. Thus, the front accommodation groove **14c** in the right side wall **14** is longer than the eject member **104**. The card abutting member **105** is coupled to the eject member **104** and formed so as to project into the card accommodation space. At least a part of the card abutting member **105** is formed so as to be able to come into abutting contact with the front end of the installed IC card **200** or **300** and to move forward and rearward together with the eject member **104**. In the present embodiment, the card

abutting member **105** is located so as to be movable forward and rearward, when assembled into the card connector, on the left spring receiving portion **43** of the elongate paired spring receiving portions formed lower than a partition plate **41** of the partition member **40** described below. Furthermore, the card abutting member **105** includes a groove extending in the front-rear direction and formed in a part thereof corresponding to the contacts **80** so as to prevent forward and rearward movement of the card abutting member **105** from being hindered. Furthermore, in the front accommodation groove **14c** in the right side wall **14** in which the eject member **104** is accommodated, at least a part of the front accommodation groove **14c** in which the coupling member **105** moves forward and rearward is preferably formed so as to communicate with the card accommodation space. The compression coil spring **107** is located in the front of the front accommodation groove **14c** in the right side wall **14** to bias the eject member **104** rearward. The functions and advantages of the eject mechanism **100** are well known and will thus not be described below.

[0059] The plurality of second contacts **90** corresponding to the respective plural pads on the small card **300** are supported like cantilevers in front of the bottom wall **11** of the base member **10**. In the present embodiment, the plurality of second contacts **90** are formed as inserts **30**, as shown in FIGS. **14A** and **14B**. The second contacts **90** are insert-molded when the base member **10** is manufactured so that a predetermined part of each of the second contacts **90** is embedded in the bottom wall **11**. In the present embodiment, the second contacts **90** are arranged in a front row and a rear row corresponding to the arrangement of the pads on the small card **300** as shown in FIGS. **14A** and **14B**. In FIG. **14B**, reference numeral **90a** denotes contacts arranged in the front row. Reference numeral **90b** denotes contacts arranged in the rear row. The plurality of second contacts **90a** and **90b** arranged in the front and rear rows, respectively, are supported like cantilevers such that contact points **91a** and **91b** of the second contacts **90a** and **90b** can be displaced upward and downward (see FIG. **3B**). To increase the amount by which the contact points **91a** and **91b** of the contacts **90a** and **90b** are displaced, the bottom wall **11** includes openings penetrating the bottom wall **11** and formed in the respective areas thereof corresponding to respective parts of the contacts **90** and **90b** supported like cantilevers. Furthermore, the contact points **91a** and **91b** of the contacts **90a** and **90b** formed so as to project like circular arcs are supported so that the circular arc projecting portions are directed upward.

[0060] Each of the inserts **30** embedded in the bottom wall **11** of the base member **10** includes paired pushup springs **31** and **32** formed on the respective laterally opposite sides of the second contact **90** to support the partition member **40** described below so that the partition member **40** is directed upward. Since the pushup springs **31** and **32** support the partition member **40** in such a way that the partition member **40** is directed upward, the inserted small card **300** is prevented from interfering with the rear end of the partition member **40**. Contact point portions of the pushup springs **31** and **32** which come into abutting contact with the partition member **40** are preferably positioned in front of paired driving pieces **44** and **45** described below and behind the contact points of the contacts (the contact point portions are located closer to the insertion slot **5** than the contact points). Thus, for example, the actuator **60** can reliably lower the partition member **40** and assuredly prevent the small card **300** from interfering with the rear end of the partition member **40**. Moreover, the pushup

springs **31** and **32** can be prevented from interfering with the actuator **60**. Furthermore, paired pressure springs **33** and **34** are formed behind the second contacts **90** and on the respective laterally opposite sides thereof to prevent the small card **300** from popping out when the small card **300** is removed from the card connector **1**. The pushup springs **31** and **32** and the pressure springs **33** and **34** are fixed to predetermined positions on the bottom wall **11** by insert molding and supported on the bottom wall **11** like cantilevers similarly to the second contacts **90**.

[0061] Each of the inserts **30** is integrally formed by using press working to punch a thin metal plate so as to form the plurality of second contacts **90** (**90a** and **90b**), the pushup springs **31** and **32**, and the pressure springs **33** and **34** on the thin metal plate. However, after the insert molding, for example, as shown in FIGS. **14A** and **14B**, predetermined parts of the insert **30** are cut such that the contacts, the pushup springs, and the pressure springs can function independently.

[0062] Now, the partition member **40** will be described, which is configured to sort the installed IC card (in the present embodiment, the large card **200** or the small card **300**) to the different areas. The partition member **40** has the function of sorting the installed IC card to the different areas and reliably holding the installed IC card. That is, the IC card installed over the partition member **40** is firmly sandwiched between the cover member **20** and the partition member **40**. The IC card installed under the partition member **40** is firmly sandwiched between the partition member **40** and the base member **10**. This ensures a contact pressure required for the electric contact between each of the IC card and the contacts. The partition member **40** is shown in FIGS. **5A** and **5B** in detail.

[0063] The partition member **40** includes the partition plate **41**, the elongate paired spring receiving portions **42** and **43**, the paired driving pieces **44** and **45**, and paired regulation pieces **46** and **47**. The partition member **40** moves upward and downward in a part of the card accommodation space located in front of a line joining the partition walls **13b** and **14b** of the right and left side walls **13** and **14**. The partition member **40** thus allows the IC cards with different sizes to be sorted and guided to an upper area and a lower area, respectively, in the card accommodation space.

[0064] The partition plate **41** is flat and is placed, when assembled into the card connector **1**, in a first position that traverses the card accommodation space as shown in FIGS. **2**, **3B**, and **4**. In this case, the partition plate **41** is preferably located such that the height of the bottom surface of the partition plate **41** from the bottom wall **11** is almost the same as the thickness of the small card **300**. In the present embodiment, the partition plate **41** is provided higher than the paired spring receiving sections **42** and **43**. This configuration allows the small card **300** to be guided along a vertical step portion connecting the opposite sides of the partition plate **41** to the respective paired spring receiving portions **42** and **43**. Thus, the width of the partition plate **41** is the same as that of the small card **300**. Furthermore, since the partition plate **41** is located higher than the paired spring receiving portions **42** and **43**, the card abutting member **105** of the eject mechanism **100** can come into abutting contact with the small card **300**. This enables the eject mechanism **100** to be shared by the large and small cards. To avoid interfering with the first and second contacts **80** and **90** and the eject mechanism **100** even when moved upward or downward, the partition plate **41** is

appropriately shaped such that, for example, a substantially rectangular front cutout **41a** is formed in the partition plate **41**.

[0065] The elongate paired spring receiving portions **42** and **43** are provided on the respective laterally opposite sides of the partition plate **41** so as to lie opposite the respective paired pushup springs **31** and **32** provided on the bottom wall **11** of the base member **10** when assembled into the card connector. Thus, the paired spring receiving portions **42** and **43** are biased upward by the respective paired pushup springs **31** and **32**. As a result, the partition member **40** is normally placed in a first position where the partition member **40** is pushed upward. In the present embodiment, as described above, the paired spring receiving portions **42** and **43** are provided lower than the partition plate **41**. The sum of the length of the partition plate **41** and the length of the paired spring receiving portions **42** and **43** provided on the respective laterally opposite sides of the partition plate **41**, that is, the width of the partition member **40**, is set almost equal to the width of the large card **200**.

[0066] Vertical guide pieces **42a**, **42b**, and **43a** are provided outside and orthogonally to the respective elongate paired spring receiving portions **42** and **43**. The vertical guide pieces **42a**, **42b**, and **43a** are provided at appropriate positions along the elongate paired spring receiving portions **42** and **43** in the front-rear direction. The vertical guide pieces **42a**, **42b**, and **43a** move along the inner wall surfaces (which face the card accommodation space) of the right side wall **13** and left side wall **14** of the base member **10** to guide the partition member **40** upward and downward. The upward movement of the partition member **40** and thus the partition plate **41** can be regulated using the vertical guide pieces **42a**, **42b**, and **43a** with the respective heights appropriately set, in combination with the paired regulation pieces **46** and **47** described below. That is, the vertical guide pieces **42a**, **42b**, and **43a** and the paired regulation pieces **46** and **47** regulate such that the partition plate **41** does not move up above the first position where the height of the partition plate **41** is the same as the thickness of the small card.

[0067] The paired driving pieces **44** and **45** are provided at the rear ends of the respective elongate paired receiving portions **42** and **43** so as to extend rearward from the rear ends. The paired driving pieces **44** and **45** extend from the rear ends of the elongate paired spring receiving portions **42** and **43** by a predetermined length. Thus, when the actuator **60** moves pivotally, the paired driving pieces **44** and **45** can engage with engaging recess portions **64a** and **65a** formed on the respective opposite sides of the actuator **60** as paired engagement portions. As the actuator **60** rotates, the driving pieces **44** and **45** come into engagement with the respective paired engaging recess portions **64a** and **65a** of the actuator **60**. Then, further rotation of the actuator **60** causes the paired driving pieces **44** and **45** to be pushed down against the bias force of the pushup springs **31** and **32**. Thus, the partition plate **41** is tilted such that the rear part of the partition plate **41** is lower than the front part thereof (second position). Hence, upon reaching the rear end of the partition plate **41**, the large card **200** can be guided onto the top surface of the partition plate **41**. Thereafter, the large card **200** is also guided through the card accommodation space along the vertical guide pieces **42a**, **42b**, and **43a**. The large card **200** pushes down the whole partition member **40**, which thus moves to a third position where the partition member **40** is parallel to the bottom wall **11**. The present invention is not limited to the paired driving pieces. For

example, the driving piece may extend rearward from the rear end of a central part of the partition plate 41. In this case, an engagement portion may be provided on the actuator corresponding to the position of the driving piece; a single engagement portion may be provided in a central part of the actuator. However, the paired driving pieces are preferably provided on the respective opposite sides of the actuator because this configuration enables the partition member 40 to be uniformly pushed down without being laterally tilted.

[0068] The paired regulation pieces 46 and 47 extend upward from the front ends of the respective elongate paired spring receiving portions 42. The paired regulation pieces 46 and 47 are bent orthogonally to the elongate paired spring receiving portions 42. The paired regulation pieces 46 and 47 come into abutting contact with, for example, the inner wall surface (which faces the card accommodation space) of the front wall 12 to place the partition plate 41 and the paired driving pieces 44 and 45 at predetermined positions in the card accommodation space. Furthermore, the paired regulation pieces 46 and 47 move along the inner wall surface of the front wall 12 to guide the partition member 40 upward and downward, while regulating the upward movement of the partition member 40.

[0069] Subsequently, the actuator 60 will be described, which inhibits insertion of IC cards different from the large card and which, when the large card is inserted into the card connector, tilts the partition member 40 to guide the large card to a predetermined position in the card accommodation space.

[0070] The actuator 60 includes a shutter portion 61, paired projecting pins 62 and 63, paired leg portions 64, and paired rotating shafts 67 and 68. The actuator 60 is located across the card accommodation space so as to be rotatable in the card accommodation space. Furthermore, the actuator 60 includes a passage opening formed by the shutter portion 61 and the paired leg portions 64 and 65 and having a substantially rectangular vertical cross section. The small card 300 can pass through the passage opening 66.

[0071] When the IC card is not installed in the card connector as shown in FIG. 1 to FIG. 4, the shutter portion 61 is located so as to extend orthogonally to a card insertion direction to laterally traverse the card accommodation space, thus sealing the upper part of the card accommodation space. The paired projecting pins 62 and 63 are formed on the respective laterally opposite sides of the shutter portion 61 so as to project outward from the respective laterally opposite sides (the paired projecting pins 62 and 63 project into the corresponding right and left rear accommodation grooves 13a and 14a). When the IC card is not installed in the card connector as shown in FIG. 1 to FIG. 4, the paired projecting pins 62 and 63 engage with the openings 54 in the corresponding paired lock brackets 50 as described above. The paired projecting pins 62 and 63 engage with the openings 54 in the respective paired lock brackets 50 to inhibit pivotal movement of the actuator 60 and thus insertion of the IC card. That is, the actuator 60 cannot be pivotally moved unless the paired contact portions 52 of the paired lock brackets 50 are pushed out from the card accommodation space to displace the paired elastic deformation pieces 51 to simultaneously remove the paired projecting pins 62 and 63 from the respective paired openings 54. That is, it is impossible that the IC card itself pushes the shutter portion 61 to pivotally move and bring the actuator 60 down. This prevents the card accommodation space from being opened, thus inhibiting the IC card from being fed forward beyond the shutter portion 61.

[0072] The leg portions 64 and 65 are provided on the respective laterally opposite sides of the shutter portion 61 and inside the respective paired projecting pins 62 and 63 so as to face downward. The shutter portion 61 and the paired leg portions 64 and 65 form the passage opening 66 with a rectangular vertical cross section (see FIG. 3B). The vertical cross sectional shape of the passage opening 66 is set almost as large as or slightly larger than that of the small card 300. That is, the distance between the paired leg portions 64 and 65 is thus almost the same as that between the paired lower-stage guideways 17. The engaging recess portions 64a and 65a are formed in the front surfaces of the respective paired leg portions 64 and 65. When the actuator 60 rotates, the paired engaging recess portions 64a and 65a come into engagement with and push down the respective driving pieces 44 and 45 of the partition member 40. As a result, the rear end of the partition plate 41 is pushed down. The engaging recess portions 64a and 65a thus formed allows adjustment of the amount by which the partition plate 41 is pushed down (the difference between the position of the partition plate 41 before the pushdown and the position of the partition plate 41 after the pushdown). Thus, the partition plate 41 can be prevented from being excessively pushed down. This enables the vertical height of the connector to be reduced.

[0073] The rotating shafts 67 and 68 are formed at the lower ends of the respective paired leg portions 64 and 65 so as to project laterally outward from the lower ends. The paired rotating shafts 67 and 68 are arranged in the respective rear accommodation grooves 13a and 14a in the right and left side walls 13 and 14. The paired rotating shafts 67 and 68 traverse the bottom parts of the respective rear accommodation grooves 13a and 14a and are rotatably supported by the right and left side walls 13 and 14, respectively. A torsion coil spring 69 is wound around one or both of the paired rotating shafts 67 and 68 (in the present embodiment, only the right rotating shaft 67). The torsion coil spring 69 biases the shutter portion 61 of the actuator 60 to an upright position, that is, a first position where the shutter portion 61 closes the card accommodation space, as shown in FIG. 1 to FIG. 4.

[0074] The actuator 60 is normally located in the first position where the shutter portion 61 of the actuator 60 partly closes the card accommodation portion as shown in FIG. 1 to FIG. 4. When the large card 200 is inserted into the card connector, the actuator 60 is disengaged from the lock brackets 50 and can then rotate around the rotating shafts 67 and 68 as described below. When the large card 200 is further fed into the card connector, the shutter portion 61 of the actuator 60 comes into abutting contact with the large card 200, which thus rotates and pushes the actuator 60 down forward. The actuator 60 thus moves rotationally to a second position where the shutter portion 61 opens the card accommodation space. Furthermore, when inserted into the card connector, the small card 300 passes through the passage opening 66 formed in the actuator 60 without rotating the actuator 60.

[0075] The card connector 1 according to the present invention is configured as described below. A specific operation of selectively installing the IC card in the card connector 1 according to the present invention will be described below. First, an operation of installing the large card 200 in the card connector 1 according to the present invention will be described with reference to FIGS. 3B and 4 and FIG. 6A to FIG. 10. FIG. 6A to FIG. 10 are diagrams showing how the large-sized IC card is installed in the card connector. FIG. 6A is a top view of the card connector in which the IC card has

come into contact with the lock brackets to cancel the locked state and from which the cover member has been removed as in the case of FIG. 4. FIG. 6B is a sectional view taken along line VIB-VIB in FIG. 6A. FIG. 7A is a top view of the card connector in which the actuator is rotating and from which the cover member has been removed as in the case of FIG. 6A. FIG. 7B is a sectional view taken along line VIIIB-VIIIB in FIG. 7A. FIG. 7C is a sectional view taken along line VIIC-VIIC in FIG. 7A. FIG. 8A is a top view of the card connector in which the actuator has finished rotating, with the tip portion of the IC card starting to climb onto the partition plate, and from which the cover member has been removed as in the case of FIG. 6A. FIG. 8B is a sectional view taken along line VIIIIB-VIIIIB in FIG. 8A. FIG. 9 is a sectional view similar to FIG. 8B, showing the card connector in which the tip of the IC card has come into abutting contact with the front wall. FIG. 10 is a sectional view similar to FIG. 8B, showing the card connector in which the IC card has been completely installed in the card connector.

[0076] As shown in FIGS. 3B and 4, when the large card 200 is not installed in the card connector, the lock brackets 50, actuator 60, and partition member 40 of the card connector 1 are located in the respective first positions. Specifically, the lock brackets 50 are located in the first position wherein the paired contact portions of the lock brackets 50 are closed. The actuator 60 is located in the first position where the shutter portion 61 of the actuator 60 partly closes the card accommodation space. At this time, the paired openings 54 in the paired lock brackets 50 engage with the respective paired projecting pins 62 and 63 of the actuator 60. Furthermore, the partition member 40 is located in the first position where the partition plate 41 of the partition member 40 is parallel with the bottom wall 11 of the base member 10 and in which the height of the partition plate 41 from the bottom wall 11 is almost the same as the thickness of the small card 300.

[0077] As shown in FIGS. 6A and 6B, the large card 200 is inserted through the card insertion slot 5 in the reverse state in which the surface of the large card 200 with the pads 203 formed thereon is oriented upward. That is, the large card 200 is inserted through the card insertion slot 5 so that the wide upper portion 201 of the large card 200 moves along the middle-stage guideway 16, while the narrow lower portion 202 of the large card 200 moves along the upper-stage guideway 15.

[0078] When the large card 200 is inserted forward, the wide upper portion 201 comes into contact, through the openings 16a in the middle-stage guideways 16, with the paired contact portions 52 of the paired lock brackets 50 projecting into the card accommodation space. The contact causes the paired contact portions 52 to be simultaneously retracted from the card accommodation space. That is, the paired contact portions 52 are moved to the second position. Thus, the paired elastic deformation pieces 51 of the paired lock brackets 50 are opened (moved to the second position) to simultaneously disengage the paired projecting pins 62 and 63 of the actuator 60 from the respective paired openings 54 in the paired elastic deformation pieces 51. This allows the actuator 60 to be rotated.

[0079] In the state shown in FIGS. 6A and 6B, when the large card 200 is further fed forward, the tip of the large card 200 comes into abutting contact with the shutter portion 61 of the actuator 60 as shown in FIGS. 7A and 7B. At this time, as described above, the actuator 60 is allowed to rotate. Thus, as the large card 200 is fed forward, the actuator 60 is rotated

counterclockwise in FIG. 7B so as to be pushed down forward against the bias force of the torsion coil spring 69. During the rotation of the actuator 60, as shown in FIG. 7C, the engaging recess portions 64a and 65a formed in the respective paired leg portions 64 and 65 of the actuator 60 comes into engagement with the respective lateral paired driving pieces 44 and 45 of the partition member 40.

[0080] As shown in FIGS. 8A and 8B, when the large card 200 is further fed forward, the actuator 60 rotates to the second position where the actuator 60 is completely brought down. The upper part of the card accommodation space is opened such that the large card 200 can pass through the upper part. Thus, the large card 200 moves forward over the shutter portion 61.

[0081] At this time, the rotation of the actuator 60 up to the second position causes the paired driving pieces 44 and 45 to be sufficiently pushed down to tilt the partition member 40. Thus, the rear end of the partition plate 41 of the partition member 40 is pushed down. That is, the partition plate 41 is moved to the second position. Hence, the tip of the large card 200 is ready to run onto the rear end of the partition plate 41.

[0082] In the state shown in FIGS. 8A and 8B, when the large card 200 is further fed forward, the tip of the large card 200 comes into abutting contact with the card abutting member 106 of the eject mechanism 100. The large card 200 is pushed in forward against the bias force of the compression coil spring 107 of the eject mechanism 100. As shown in FIG. 9, the large card 200 is pushed in until the tip of the large card 200 reaches the front wall 12 of the base member 10.

[0083] In the state shown in FIG. 9, when the force acting to push in the large card 200 is removed, the large card 200 is held in the card accommodation space in the card connector 1 at a position to which the large card 200 has been slightly pushed back by the action of the push-push eject mechanism 100. At this time, the plurality of pads 203 on the large card 200 can come into contact with the corresponding plural first contacts 80. Furthermore, the large card 200 pushes the partition member 40 located in the card accommodation space, down to a third position via the partition plate 41 of the partition member 40 against the bias force of the paired pushup springs 31 and 32 embedded in the bottom wall 11. In other words, the partition plate 41 of the partition member 40 contacts the surface of the upper portion 201 of the large card 200 to push the large card 200 up to the third position where the large card 200 is parallel to the bottom wall 11. Thus, the plurality of pads 203 of the large card 200 can electrically contact the corresponding plural first contacts 80 at the respective appropriate pressures. When the large card 200 is installed in the card accommodation space in the card connector 1, the surface of the upper portion 201 of the large card 200 may contact the plurality of second contacts 90 for the small card 300. This configuration does not affect the large card 200 because no pad is formed on the surface of the upper portion 201 of the large card 200 and because the surface of the upper portion 201 is not electrically conductive. Rather, the contact between the large card 200 and the plurality of second contacts 90 increases the contact pressure between the large card 200 and the first contacts 80. Consequently, the repulsive force of the contacts can be utilized.

[0084] When removing the card connector 1, the large card 200, in the state shown in FIG. 10, is pushed in again into the state shown in FIG. 9. Subsequently, in the state shown in FIG. 9, the force acting to push in the large card 200 is released. The large card 200 is then discharged from the card

connector 1 under the action of the eject mechanism 100. The partition member 40, the lock brackets 50, and the actuator 60 return to the respective first positions.

[0085] Now, an operation of installing the small card 300 in the card connector 1 according to the present invention will be described with reference to FIGS. 3B and 4 and FIG. 11A to FIG. 13. FIG. 11A to FIG. 13 are diagrams showing how the small-sized IC card is installed in the card connector. In FIGS. 11A and 11B, when the small card 300 is not installed in the card connector 1, the card connector 1 is in exactly the same state as that of the large card 200 as shown in FIGS. 3B and 4.

[0086] The small card 300 is inserted through the card insertion slot 5 along the lower-stage guideways 17 in the normal state in which the surface of the small card 300 with the pads 203 formed thereon is oriented downward. The inserted small card 300 is guided along the lower-stage guideways 17 and thus prevented from coming into contact with the lock brackets 50. Thus, the actuator 60 is still located in the first position. However, the small card 300 can pass through the passage opening 66 and thus advance through the card accommodation space without being interfered with. Moreover, the partition plate 41 of the partition member 40 is located in the first position the height of which is larger than the thickness of the small card 300. Thus, as shown in FIGS. 11A and 11B, the small card 300 can be inserted into the part of the card accommodation space located under the partition plate 41 of the partition member 40.

[0087] FIGS. 12 and 13 show the state observed immediately before the small card 300 is installed in the card connector 1. This operation is similar to that performed on the large card 200 and will thus not be described below. Furthermore, as is the case with the large card 200, when the small card 300 is inserted in the card connector, the top surface (the surface with no pad formed thereon) of the small card 300 may contact the plurality of first contacts 80 for the large card 200.

[0088] Even if the large card 300 is mistakenly inserted along the middle-stage guideways 16, the small width of the small card 300 precludes the paired contact portions 52 of the paired lock brackets 50 from being simultaneously moved to the second position. Thus, the actuator 60 is not enabled to rotate. Hence, the small card 300 is inhibited from being fed forward beyond the shutter member 61. This prevents the IC card 300, the card connector 1, and even an electronic apparatus connected to the IC card 300 via the card connector 1 from being damaged.

[0089] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

What is claimed is:

1. A card connector in which a base member and a cover member form a card accommodation space with a card insertion slot and in which two types of cards, a large card and a small card having a width less than the large card, are capable of being selectively installed in the card accommodation space, the card insertion slot including paired first guideways along which the large card is guided and paired second guideways along which the small card is guided, the card connector comprising:

a plurality of contacts including a plurality of first contacts for the large card which comprise contact points arranged so as to face downward in the card accommo-

dation space and a plurality of second contacts for the small card which comprise contact points arranged so as to face upward in the card accommodation space;

paired lock brackets configured to detect the width of the large card provided in the first guideways to move from a first position of the lock brackets to a second position of the lock brackets;

an actuator configured to engage with the paired lock brackets and to be rotatable from the first position of the actuator to the second position of the actuator, the actuator comprising at least an engagement portion and a passage opening through which the small card is capable of passing; and

a partition member comprising a partition plate configured to be movable from the first position of the partition plate to the second position of the partition plate and a driving piece configured to engage with the engagement portion, the partition member sorting the inserted large and small cards to an upper part and a lower part, respectively, of the card accommodation space,

wherein when the large card is inserted into the card connector with an external contact oriented upward, the lock bracket is moved from the first position of the lock bracket to the second position of the lock bracket to enable the actuator to be rotated, and when the large card is further fed into the card connector, the actuator is rotated from the first position of the actuator to the second position of the actuator to move the partition plate from the first position of the partition plate to the second position of the partition plate, thus allowing the large card to be guided to the upper part of the card accommodation space.

2. The card connector according to claim 1, wherein a pair of the engagement portions is formed on the actuator, and a pair of the driving pieces configured to engage with the respective paired engagement portions is formed on the partition plate.

3. The card connector according to claim 2, wherein the engagement portion comprises a recess portion formed therein and with which the driving piece is engaged.

4. The card connector according to claim 1, wherein when the large card is further fed into the card connector, the partition plate of the partition member is 'capable of moving to a third position where the partition plate is parallel to a bottom wall of the base member.

5. The card connector according to claim 1, wherein the partition member further comprises a vertical guide piece and at least paired regulation pieces so as to allow the partition plate to be guided upward and downward and to allow elevation of partition plate to be regulated.

6. The card connector according to claim 1, wherein the partition member comprises paired elongate spring receiving portions on respective opposite sides of the partition plate, and the partition plate is biased to the first position of the partition plate by paired pushup springs provided on the base member and corresponding to the respective paired elongate spring receiving portions.

7. The card connector according to claim 6, wherein the second contact and the paired pushup springs are formed as inserts embedded in the base member.