
(No Model.)

R. N. SMITH. CANE UMBRELLA.

No. 531,878.

Patented Jan. 1, 1895.



THE NORRIS PETERS CO., PHOTO-LITHO., WASHINGTON, D. C.

UNITED STATES PATENT OFFICE.

RUTH NEWEY SMITH, OF PATCHOGUE, NEW YORK.

CANE-UMBRELLA.

SPECIFICATION forming part of Letters Patent No. 531,878, dated January 1, 1895.

Application filed September 20, 1894. Serial No. 523,611. (No model.)

To all whom it may concern:

Be it known that I, RUTH NEWEY SMITH, a citizen of the United States, residing at Patchogue, in the county of Suffolk and State of

5 New York, have invented new and useful Improvements in Cane-Umbrellas, of which the following is a specification. The object of this invention is to simplify

the construction and operation of cane umto brellas and the invention resides in the novel features of construction set forth in the following specification and claims and illustrated in the annexed drawings, in which-

Figure 1 is a sectional elevation of the um-15 brella open. Fig. 2 is a like elevation of the umbrella closed. Fig. 3 is a section along x x

Fig. 1. A is the stick of the umbrella. B is the runner from which extend the stretchers C and D o is the head which is fixed to the stick A and to which the ribs E are hinged in the usual manner. The cover H is applied as well known. To the bottom end of the stick A is firmly secured a plug F which fits into the hollow 5 cane or handle G and is provided with a lip 10 adapted to engage a catch 11 fastened to

the cane or staff G. The runner B is provided with a plug 12 which fits the hollow cane G and is provided o with a rim 13 forming a stop which abuts

against the edge of the hollow cane. When the umbrella is closed it can be inserted into the hollow cane until the rim 13 of the plug 12 strikes the edge of the cane and 5 when it has reached this position, the catch 11 engages the head D so as to retain the umbrella in position. The cane is provided with a knob or handle 14 which forms its top when the cane is used for walking and its bottom

o when the umbrella is open. The runner B travels between the oppositely located head D and plug F and when the um-brella is open the plug of the runner abutting against handle G holds the umbrella head D 5 projecting beyond the handle. By releasing catch 11 and drawing the umbrella stick out of the handle or cane, the umbrella can be closed by moving runner B toward plug F and when the closed umbrella now has its head D o inserted into the hollow cane or staff, said head forms a lip for engagement of the catch

11 and the runner plug abutting against the cane will hold the plug F projecting beyond the cane so that said plug F will form the lower end of the cane as seen in Fig. 2. 55

As the umbrella whether open or closed is inserted into the hollow cane from only one end, the other end of the cane can remain permanently closed and does not require any temporary closing device such as a removable 60 plug, or screw cap or the like.

To open the umbrella the catch 11 is moved to release head D and the umbrella having been withdrawn from the handle or case G is reversed so that the plug F enters the case G, 65 the rim 13 resting or abutting against said case, and the stick A is then pushed toward the catch 11 so that the latter will engage and hold plug F, this motion of the stick A bringing the head D toward runner B so that the 70 umbrella is opened.

What I claim as new, and desire to secure by Letters Patent, is-

1. In a cane umbrella, the combination with a hollow handle, of an umbrella adapted to 75 be inserted in the handle and provided with a runner having a plug, the opposite ends of which are adapted to be inserted in the handle, said plug being provided intermediate its ends with an annular rim which abuts against 80 the open end of the hollow handle in both the open and closed position of the umbrella, substantially as described.

2. In a cane umbrella, the combination with a hollow handle, of an umbrella adapted to be 85 inserted in the handle, said umbrella having a stick provided at one end with a fixed plug and with a runner carrying a second plug, the latter plug having its opposite ends reduced to fit within the handle and provided inter- 90 mediate its ends with an annular rim which abuts against the open end of the hollow handle in both the open and closed position of the umbrella, and a catch carried by the umbrella and operating to engage the fixed plug and 95 hold the umbrella stick in said handle, substantially as described.

3. In a cane umbrella, the combination with a hollow handle provided with a catch, of an umbrella having a stick provided at one end 100 with a head and at its other end with a fixed plug adapted to be alternately inserted in the

handle and engage the catch, and a runner adapted to travel between the head and the fixed plug, said runner being provided with a plug adapted to abut against the open end of 5 the handle for alternately holding the head and the fixed plug projecting beyond the handle, substantially as described.

In testimony whereof I have hereunto set my hand in the presence of two subscribing witnesses.

RUTH NEWEY SMITH.

Witnesses: GARDNER (

GARDNER C. G. SMITH, E. F. KASTENHUBER.