




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : E04F 15/10, 15/02</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/34075 (43) International Publication Date: 8 July 1999 (08.07.99)</p>
<p>(21) International Application Number: PCT/GB98/03896 (22) International Filing Date: 23 December 1998 (23.12.98) (30) Priority Data: 9727395.7 24 December 1997 (24.12.97) GB (71) Applicant (for all designated States except US): SUNDERLAND LIMITED [GB/GB]; 2 Water Street, Ramsey, Isle of Man IM8 1JP (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): MacDONALD, Ken [GB/GB]; 21 Poyntell Crescent, Chislehurst, Kent BR7 6PJ (GB). (74) Agent: JENSEN & SON; 70 Paul Street, London EC2A 4NA (GB).</p>		<p>(81) Designated States: AU, CA, DE, DE (Utility model), MX, NZ, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i></p>

(54) Title: INTERLOCKING TILES

(57) Abstract

Tiles, preferably floor tiles having an upper surface (1) which has engagement members (6) extending from two adjacent sides (2 and 3). The engaging elements (6) have a recess between them which is a mirror image of the engaging elements (6) of an adjacent tile. Rib (9) on the outer extensions (6a, 6b, 6c) of the engaging elements (6) engages with slot (10) along the lengths of sides (2, 3) to form a fluid tight seal between adjacent tiles which are interlocked by engaging elements (6).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Interlocking Tiles

This invention relates to tiles, particularly interlocking tiles which are adapted to be interlocked together to cover a surface. A preferred application of the tiles of the invention is as a floor covering.

It is known to provide rectangular or square floor tiles in which two adjacent sides have projections, the other two adjacent sides having recesses corresponding to the shape of the projections. In this way, a large number of the tiles can be interlocked to form a floor covering. Known arrangements of such interlocking floor tiles have the disadvantage that the joint where the tiles are interlocked is visible and not only detracts from the appearance of the tile inherently, but also imposes limitations on the practicality of the tile since liquid such as water can seep down the joint line between adjacent tiles. This is a particular problem in locations such as kitchens and hospitals and some factories, where a great deal of liquid is liable to be distributed over the floor.

The present invention seeks to provide a floor tile with an additional sealing arrangement which substantially prevents the ingress of water to the underside of the tiles. According to the present invention there is provided an interlocking, generally planar tile, having a four-sided, preferably square, shape with an outer face and an inner face, each side having a plurality of engagement elements interlockingly engageable with corresponding engagement elements on an adjacent tile, a first two adjacent sides having the outer surface extending over the engagement elements, an edge rib extending along the length of the side and extending downwardly away from the outer surface, on the other two adjacent sides, the engagement elements extending outwardly beyond the upper surface and having a recess extending along the length of the side, which recess is adapted to receive a said rib on a first side on an adjacent tile, the engagement of the rib in the recess forming a substantially fluid tight joint between the two tiles.

Preferably, the tile is a floor tile formed of a resilient material such as a plastics material or a natural or synthetic rubber. In an alternative embodiment, the main body of the tile is formed of a ceramic material and the engagement elements, rib

and recess are formed in a peripheral seal or gasket of resilient material extending round the periphery of the tile on its underside.

The recess is preferably located at the root of the engaging elements immediately adjacent to the edge of the upper surface so that when an adjacent tile is placed on this tile, the rib engages in the recess so that the upper surfaces of the two tiles are closely abutting to substantially conceal the joint between the two tiles.

A preferred embodiment of the present invention will now be described by way of example with reference to the accompanying drawings in which:-

Figure 1 shows a plan view of the upper side of a floor tile,

Figure 2 shows the underside of the embodiment of Figure 1,

Figure 3 shows a corner section of two tiles in greater detail,

Figure 4 shows the two tiles of Figure 3 joined together,

Figures 5 and 6 show the underside of a fragment of two tiles as shown in Figures 3 and 4,

Figures 7 and 8 show a top view and an underneath view of four tiles connected together, Figure 7 being the top side and Figure 8 from the bottom side,

Figure 9 shows a cross-section through a second embodiment, and

Figure 10 shows a plan view of the second embodiment.

Referring now to Figure 1, there is shown a floor tile formed of a synthetic plastics material with an upper surface 1 having a pattern of circles which, apart from being decorative, provide a substantially non-slip surface. Of course, many other types of decorative pattern may be provided. The upper surface is square in plan view and has two adjacent sides 2 and 3 carry engagement members 6 extending beyond the profile of the upper surface.

The two adjacent sides 2, 3 each have a plurality of engaging elements 6 extending therefrom. Each projecting engaging element consists, essentially, of an equilateral rhomboid having an outer edge which is substantially longer than its inner side at the root of the member where it joins the main body. Between adjacent engageable members, there is therefore a recess which consists of a mirror image of an engageable element so that the engageable elements 6 on an adjacent tile can be

located in these recesses. In this embodiment, there are nine projecting elements 6 on each side.

In this embodiment, the elements 6 are approximately 4mm in thickness and the overall thickness of the tile is approximately 6.7mm. The thickness of the tile will be varied in dependence on the actual application. At the root of the elements 6, adjacent the upper surface, there is a slot 10 extending along the length of the sides 2, 3. At the ends of each side 2, 3 there are shaped extensions 6a, 6b, 6c which cooperate with corresponding extensions on adjacent tiles to complete the slots 10 along the complete lengths of the sides, as will be described hereinafter.

Referring now to Figure 2, there is shown the underside of the tile of Figure 1. It can be seen that the two adjacent sides 4 and 5 have engagement elements 6. The upper surface 8 of the tile overlies the elements 6 and extends slightly further outwardly. On this outer extension, the tile has a rib 9 extending along the length of the side and extending downwardly perpendicularly away from the upper surface 1.

Referring now to Figures 3 to 6, there is shown a scrap view of the corners of two tiles to be joined together. Figure 3 shows the top of the tiles about to be placed together and Figure 4 shows them secured together. Figure 5 shows the underside of the tiles corresponding to Figure 3 and Figure 6 shows the underside view corresponding to Figure 4. It can be seen that the outwardly extending elements 6 on one tile engage with the elements 6 on the other tile which are covered by the upper surface. At the same time, the rib 9 engages with the slot 10 throughout the length of the side. In this way, a substantially fluid tight seal is formed between adjacent tiles.

Referring now to Figures 7 and 8, there is shown the junction between four juxta-posed tiles. It can be seen that the four corner extensions cooperate and abut closely to form a complete seal which results from the formation of a complete slot and rib in this region to thereby complete the seal round the edge of all adjacent tiles. It can thus be seen that the use of one design of tile which can interlock with an identical tile enables a floor of any size to be covered securely by tiles having a substantially liquid-tight seal at the joints between tiles.

The material of the tile will depend largely on the application, but may be vinyl, polyvinyl chloride, polypropylene or polyethylene. In a second embodiment,

to be described with reference to Figures 9 and 10, the main body of the tile is formed of a rigid substance such as a ceramic material.

Referring now to Figures 9 and 10, there is shown a second embodiment in which Figure 9 is a cross-section along the line II-II of Figure 10. Figure 10 is a plan view of the tile. The main body 1 of the tile is formed of a ceramic material with the engaging elements and recesses formed in a resilient seal or gasket which locates in a peripheral recess in the underside of the tile and extends round the periphery of the tile, to which it is preferably bonded. In other respects, the engaging elements and the recesses, ribs and slots are the same as the first embodiment.

It will be appreciated that many variations may be made to the tile without departing from the inventive concept. For example, the shape and number of the projecting elements 6 may differ; all that is required is that they mesh universally with other tiles of the same design. It is also possible to incorporate different facings on the upper surface, for example a ceramic layer. The tile may also be adapted for covering other surfaces such as roofing, walls, shower units etc., although it is particularly intended for heavy duty applications such as factories and operating theatres.

CLAIMS:

1. An interlocking, generally planar tile, having a four-sided, preferably square, shape with an outer face and inner face, each side having a plurality of engagement elements interlockingly engageable with corresponding engagement elements on an adjacent tile, a first two adjacent sides having the outer surface extending over the engagement elements, an edge rib extending along the length of the side and extending downwardly away from the outer surface, on the other two adjacent sides, the engagement elements extending outwardly beyond the upper surface and having a recess extending along the length of the side, which recess is adapted to receive a said rib on a first side on an adjacent tile, the engagement of the rib in the recess forming a substantially fluid tight joint between the two tiles.
2. An interlocking, generally planar tile according to claim 1 wherein the tile is formed of a resilient material such as a plastics material or a natural or synthetic rubber.
3. An interlocking, generally planar tile according to claim 1 wherein the main body of the tile is formed of a ceramic material and the engagement elements, rib and recess are formed in a peripheral seal or gasket of resilient material extending round the periphery of the tile on its underside.
4. An interlocking, generally planar tile according to claim 3, wherein the recess is located at the root of the engaging elements immediately adjacent to the edge of the upper surface so that when an adjacent tile is placed on this tile, the rib engages in the recess so that the upper surfaces of the two tiles are closely abutting to substantially conceal the joint between the two tiles.
5. An interlocking, generally planar tile according to any preceding claim wherein the tile is a floor tile.




FIG. 1




FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7







FIG. 8





INTERNATIONAL SEARCH REPORT

Intern al Application No
PCT/GB 98/03896

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 E04F15/10 E04F15/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
IPC 6 E04F E01C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 044 371 A (IMMOBILIERE THIONVILLESE SOCI) 27 January 1982 see page 5, line 24 - page 8, line 36; figures 1-14 ---	1,2,5
A	US 4 287 693 A (COLLETTE RODERICK E) 8 September 1981 see column 2, line 42 - column 5, line 7; figures 1-8 ---	1,2,5
A	US 3 657 852 A (WORTHINGTON WALTER J ET AL) 25 April 1972 see column 1, line 49 - column 3, line 2; figures 1-7 -----	1-5

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

31 March 1999

Date of mailing of the international search report

09/04/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Ayiter, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/03896

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0044371	A	27-01-1982	NONE	
US 4287693	A	08-09-1981	CA 1147127 A	31-05-1983
US 3657852	A	25-04-1972	NONE	