



(12) PATENT ABRIDGMENT (11) Document No. AU-B-36045/93
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 659930

- (54) Title
LIQUID DISPENSER ASSEMBLY WITH ADAPTOR
- International Patent Classification(s)
 (51)^s **B05B 011/00 B65D 025/38 B67D 005/40**
- (21) Application No. : **36045/93** (22) Application Date : **29.01.93**
- (87) PCT Publication Number : **WO93/14983**
- (30) Priority Data
- | (31) Number | (32) Date | (33) Country |
|---------------|-----------------|------------------------------------|
| 829759 | 31.01.92 | US UNITED STATES OF AMERICA |
| 984876 | 02.12.92 | US UNITED STATES OF AMERICA |
- (43) Publication Date : **01.09.93**
- (44) Publication Date of Accepted Application : **01.06.95**
- (71) Applicant(s)
CONTICO INTERNATIONAL, INC.
- (72) Inventor(s)
DONALD D. FOSTER
- (74) Attorney or Agent
SPRUSON & FERGUSON , GPO Box 3898, SYDNEY NSW 2001
- (56) Prior Art Documents
AU ~~266650~~ 15551/62 B05B 11/02 9/043
- (57) Claim

1. An assembly for dispensing liquid from a container having a liquid within an interior of the container; the container having an opening in the container, the opening providing access to the container interior, the assembly comprising:

a conduit having a length that enables extension of the conduit into the liquid held within the container interior;

a hand-held dispenser connected to the conduit, the hand-held dispenser having a pump operable for drawing liquid from the container interior by way of the conduit when the conduit is extended into the liquid held in the container interior;

an adaptor having a configuration dimensioned to enable insertion of the adaptor through the container opening and into the interior of the container and having a connector for affixing the adaptor on the container with the adaptor inserted through the container opening; and

the dispenser having a connector releasably affixing the dispenser on the adaptor and the conduit extending from the dispenser through the adaptor and into the container with the adaptor inserted through the container opening; the conduit having flexible portions that provide extension upon disconnecting the dispenser from the adaptor for remote operation of the dispenser from the adaptor.

20. A container adaptor for connecting a container to a hand-held pump dispenser having a conduit, where the container has an interior holding a liquid and an opening to the interior, and the dispenser has a handle that is accessible on the dispenser for gripping of the handle by a person's hand, the container adaptor comprising:

at least one wall having a cup-shaped configuration defining an interior chamber within the cup-shaped wall and a first opening in the wall providing access to the interior chamber and a second opening in the wall for insertion of the conduit therethrough, the interior chamber having a volume sufficiently large to receive therein the dispenser handle when inserted through the first wall opening, the cup-shaped wall having first means positioned around the first opening in the wall for releasably affixing the wall to the dispenser when the dispenser handle is inserted through the first wall opening and is received in the interior chamber, and the wall having an exterior configured for insertion of the cup-shaped wall through the container opening and into the container interior, the wall having second means positioned on the wall exterior for releasably affixing the wall to the container when the wall is inserted through the container opening and into the container interior.




<p>(51) International Patent Classification ⁵ : B65D 23/10, B67D 5/40</p>	<p>A1</p>	<p>(11) International Publication Number: WO 93/14983 (43) International Publication Date: 5 August 1993 (05.08.93)</p>
--	------------------	---

<p>(21) International Application Number: PCT/US93/00899 (22) International Filing Date: 29 January 1993 (29.01.93) (30) Priority data: 07/829,759 31 January 1992 (31.01.92) US 07/984,876 2 December 1992 (02.12.92) US (71) Applicant: CONTICO INTERNATIONAL, INC. [US/ US]; 1101 North Warson Road, St. Louis, MO 63132 (US). (72) Inventor: FOSTER, Donald, D. ; 2524 Trenton Station, St. Charles, MO 63303 (US). (74) Agents: ROLNICKI, Joseph, M. et al.; Rogers, Howell & Haferkamp, 7777 Bonhomme, Suite 1700, St. Louis, MO 63105 (US).</p>	<p>(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. <div style="font-size: 2em; font-weight: bold; text-align: center;">659930</div></p>
--	--

(54) Title: LIQUID DISPENSER ASSEMBLY WITH ADAPTOR

(57) Abstract

A dispenser assembly (10) for dispensing liquid from a container (20, 132) has a dispenser (12, 140) operable remotely from the container (20, 132) by way of tube (16, 112) communicating the dispenser (12, 140) and the liquid within the container (20, 132). The dispenser assembly (10) has a hand-held dispenser (12, 140) and a tube (16, 112) connected to the dispenser (12, 140) for extension into the liquid within the container (20, 132). The dispenser (12, 140) is operable to dispense liquid from the container (20, 132) by way of the tube (16, 112). An adaptor (50, 100, 121) is secured to the container (20, 132) with the tube (16, 112) operable for extending from the dispenser (12, 140) through the adaptor (50, 100, 121) and into the container (20, 132). With the dispenser (12, 140) disconnected from the adaptor (50, 100, 121) and with the adaptor (50, 100, 121) secured to the container (20, 132), the dispenser (12, 140) may be operated remotely from the container (20, 132) to dispense the liquid from the container (20, 132).




Liquid Dispenser Assembly With Adaptor

Background and Summary of Invention

This invention relates to a liquid dispenser assembly, and particularly such an assembly for use with a liquid container and where the dispenser is operated remotely
5 from the container. A tube connects the dispenser with the container for feeding the liquid to the dispenser. The present invention is an improvement over remotely operated dispensers of the type described above, and further includes a unique adaptor secured to the container and to which the dispenser may be connected for sale and storage and disconnected for remote operation.

10 Liquid dispenser assemblies of the type to which this invention is generally directed are well-known in the art. The dispenser assembly shown in Figure 1 of the drawing is typical of the prior art. The dispenser assembly 10 of the prior art includes a trigger
sprayer 12



having a neck portion 13, a handle portion 14 and a tube 16. The trigger dispenser 12 is of the type well-known in the art and which is operable by means of a trigger 18 to pump liquid from a suitable container, such as container 20, and out a nozzle and orifice cap 22 of the dispenser. The cap 22 may be fixed or may be adjustable to provide a variety of spray patterns, all of which is well-known. The dispenser assembly 10 also includes a threaded closure 24 to connect the handle portion to the neck portion of the dispenser.

The container 20 is of a type typically found in retail stores and may be of plastic and have a threaded neck 30 and handle portion 32 for carrying and holding the container. When the container and dispenser assembly are packaged for retail sale in the stores, the container has a threaded cap 34 with a hole 36 in the top. A gasket 38 is located between the cap and the threaded neck 30 of the bottle to seal the opening and prevent the liquid within the bottle from spilling. When packaged for sale in the store, typically the dispenser assembly, including the trigger sprayer 12, portion 14, and tube 16, are packaged in a sealed plastic bag. The bag has a hole so that the bag containing the dispenser assembly may be hung over the neck 30 of the container with the cap 34 extending through the hole. To use the prior art assembly of Figure 1, the user removes the plastic bag from the container, and removes the dispenser assembly from the plastic bag. The user then inserts the end of the tube 16 through the hole 36 and pierces the gasket 38, thus inserting the tube into the liquid within the container. The user holds the container with one hand while operating the trigger sprayer with the other to pump the liquid from the container and out the dispenser. The container and dispenser assembly of Figure 1 typically are used to dispense products such as insecticides, herbicides, and the like.

There are several disadvantages associated with the container and dispenser assembly of Figure 1. Once the gasket is pierced, if the container is tipped over during use, the liquid within the container will leak between the tube and gasket and between the tube and opening 36. Another disadvantage is that the dispenser assembly is awkward to store and there is no provision for sealing the container. Still another disadvantage is that the plastic bags containing the dispenser assemblies frequently become separated from the containers in the retail store creating customer confusion and annoyance. The present invention overcomes these problems.

In accordance with the present invention in one form there is provided an assembly for dispensing liquid from a container having a liquid within an interior of the container; the container having an opening in the container, the opening providing access to the container interior, the assembly comprising:

a conduit having a length that enables extension of the conduit into the liquid held within the container interior;

a hand-held dispenser connected to the conduit, the hand-held dispenser having a pump operable for drawing liquid from the container interior by way of the conduit when the conduit is extended into the liquid held in the container interior;

an adaptor having a configuration dimensioned to enable insertion of the adaptor through the container opening and into the interior of the container and having a connector for affixing the adaptor on the container with the adaptor inserted through the container opening; and

the dispenser having a connector releasably affixing the dispenser on the adaptor and the conduit extending from the dispenser through the adaptor and into the container with the adaptor inserted through the container opening; the conduit having flexible portions that provide extension upon disconnecting the dispenser from the adaptor for remote operation of the dispenser from the adaptor.

In a further form the invention there is provided a dispensing system comprising:

a container for holding a liquid within an interior of the container, the container having an opening to the container interior;

an adaptor inserted through the container opening and into the container interior and the adaptor and container having connectors releasably affixing the adaptor to the container with the adaptor inserted through the container opening and into the container interior;

a conduit extending through the adaptor and into the container interior with the adaptor connected to the container for conducting liquid out of the container and through the adaptor;

a hand-held dispenser connected to the conduit, the dispenser having a pump for drawing liquid from the container by way of the conduit; and



the dispenser and adaptor having connectors releasably affixing the dispenser and adaptor together with the conduit extending from the dispenser to the adaptor, and into the container; the conduit having flexible portions that provide extension upon disconnecting the dispenser from the adaptor for remote operation of the dispenser.

5 In another form of the invention there is provided an assembly for dispensing a liquid from a container, said assembly comprising:

a dispensing head;

a handle attached to the dispensing head, the head being configured for gripping by a user's hand and having an open-ended, cylindrical chamber therein;

10 a flexible conduit extending from the dispensing head through the chamber and having a length that enables insertion of the conduit into liquid of the container for delivering the liquid from the container to the dispensing head, at least a portion of the flexible conduit being housed in the handle chamber; and said portion of said flexible conduit being flexibly extendable from the handle chamber; and

15 a connector attached to the handle releasably affixing the dispenser head to an adaptor, the connector located on the handle so that the handle extends at least partially into the adaptor when the dispenser head is connected to the adaptor.

In yet a further form of the invention there is provided a container adaptor for connecting a container to a hand-held pump dispenser having a conduit, where the 20 container has an interior holding a liquid and an opening to the interior, and the dispenser has a handle that is accessible on the dispenser for gripping of the handle by a person's hand, the container adaptor comprising:

at least one wall having a cup-shaped configuration defining an interior chamber within the cup-shaped wall and a first opening in the wall providing access to the interior 25 chamber and a second opening in the wall for insertion of the conduit therethrough, the interior chamber having a volume sufficiently large to receive therein the dispenser handle when inserted through the first wall opening, the cup-shaped wall having first means positioned around the first opening in the wall for releasably affixing the wall to the dispenser when the dispenser handle is inserted through the first wall opening and is 30 received in the interior chamber, and the wall having an exterior configured for insertion of the cup-shaped wall through the container opening and into the container interior, the wall having second means positioned on the wall exterior for releasably affixing the wall to the container when the wall is inserted through the container opening and into the container interior.

35 While the adaptor may be disconnected from the container, it remains connected to it when sold in the stores, when in use, and when the dispenser is stored during non-use. The dispenser and adapter have means for connecting the dispenser and adaptor together with the conduit or tube extending from the dispenser, through the adaptor, and into the container. The dispenser may be disconnected from the adaptor while the adaptor



remains secured to the container, for operation of the dispenser remotely from the container. The tube extends through the adaptor in sealing engagement therewith to prevent liquid from entering the interior of the adaptor. Thus, the interior of the adaptor remains dry and sealed from the liquid. When the dispenser assembly is connected to the
5 adaptor, the handle portion of the dispenser extends into the interior of the adaptor and remains dry and out of contact with the liquid. In use where the dispenser is disconnected from the adaptor and operated remotely, the adaptor remains secured to the container to provide a seal against spilling.

In one preferred embodiment of the invention, the adaptor has a chamber therein.
10 The tube has a preformed

2
3
4
5
6
7
8
9



coil portion housed within the chamber with the dispenser and adaptor connected. The coil portion extends upon disconnecting the dispenser from the adaptor for remote operation of the dispenser. This embodiment has the
5 advantage that the exterior surface of the preformed coiled tube portion which may come in contact with the user during use, is protected from the liquid, it being housed within the adaptor chamber.

These and other advantages of the invention are
10 apparent from the drawing and detailed description to follow.

Description of the Drawings

Figure 1 shows a dispenser assembly and container of the prior art.

15 Figure 2 is a side elevational view of a liquid dispenser assembly with adaptor of the present invention shown with the dispenser assembly connected to the adaptor for sale in the stores or storage.

Figure 3 shows the dispenser assembly of Figure 2
20 but with the dispenser assembly disconnected from the adaptor for use by remote operation of the dispenser assembly.

Figure 4 is a view in partial section of the dispenser assembly and adaptor of Figure 2 shown with the
25 dispenser assembly connected to the adaptor.

Figure 5 is a view similar to Figure 2 but showing another preferred embodiment of the invention.

Figure 6 is a view showing the embodiment of Figure 5 but with the dispenser assembly disconnected
30 from the adaptor for use by remote operation of the dispenser.

Figure 7 is a view in partial section of the dispenser assembly and adaptor of Figure 5.

Figure 8 is a view similar to Figures 2 and 5 but
35 showing still another preferred embodiment of the present invention.

Figure 9 is a view in partial section of the dispenser assembly and adaptor of Figure 8.

Figure 10 is a section view taken along the line 10-10 of Figure 9.

5 Figure 11 is a front elevation view of the valve case of Figure 9.

Figure 12 is an exploded view, showing a side elevation of the valve case in partial section and showing the adaptor partly broken away.

10 Detailed Description of Preferred Embodiments

With reference to the drawing, one preferred embodiment of the liquid dispenser assembly with adaptor of the present invention is shown in Figures 2-4. Generally, the dispenser assembly is the same as shown in
15 Figure 1 except that the closure 24 has an outwardly extending shoulder 40 and an internally threaded ring portion 42 depending therefrom. The container 20 is also the same but does not include the cap 34 or gasket 38 as these are not used with the present invention. An adap-
20 tor 50 is generally cup-shaped and has a cylindrical tubular portion 52 and a bottom 54 with a central opening 56 therethrough. At the top of the cylindrical portion 52 is a shoulder 58 with a ring portion 60 depending therefrom. The ring portion 60 has internal threads 62
25 that mate with the threaded neck 30 of the container. Extending upwardly from the shoulder 58 is an externally threaded ring 64. The threads of the ring 64 mate with those of the threaded ring 42 of closure 24 of the dispenser assembly.

30 The tube 16 is connected within the neck and handle portions of the dispenser. The upper end of the tube is connected to a fitting 70 such that liquid pumped through the tube is fed through suitable passages within the trigger dispenser as is well-known in the art. The
35 tube is further supported at the lower end of the handle

portion by means of a bracket 72 and an extended cylindrical portion 74 to provide sealing engagement between the tube and the lower end of the handle portion. The tube fits within the opening 56 at the bottom of the adaptor. The opening is somewhat undersized to provide a tight-fit engagement while allowing the tube to be pushed and pulled through the opening. The tube is preferably of plastic and is flexible and somewhat forgiving to allow the tube to be pushed and pulled through the opening and yet provide a liquid-tight seal.

The dispenser assembly and container of Figures 2-4 are sold in the retail stores with the adaptor secured to the container and with the dispenser assembly connected to the adaptor as shown in Figures 2 and 4. There is little or no likelihood of the dispenser assembly becoming inadvertently separated from the container as frequently occurred with the prior art arrangement.

To use the dispenser assembly, the dispenser assembly is disconnected from the adaptor, leaving the adaptor secured to the container. The tube is pulled from the container through the opening 56 while leaving a sufficient length of tube extending into the liquid as shown in Figure 3. Typically, the user operates the dispenser assembly by holding the container in one hand while remotely operating the dispenser with the other to pump liquid from the container and through the nozzle and cap 22 of the dispenser. Preferably, a retainer clip 80 is secured to the tube to act as a stop so that the user does not inadvertently pull all of the tube from the container, but instead leaves a sufficient length of tube within the liquid as shown in Figure 3.

To store the dispenser assembly and container after use, the tube is pushed back through the opening 56 and into the container, and the dispenser assembly is again connected to the adaptor by screwing the closure 24

onto the threaded ring 64 of the adaptor. The assembly is sealed against leakage both while in use and storage.

Another preferred embodiment of the invention is shown in Figures 5-7. This embodiment is the same as the one shown in Figures 2-4 except as will be explained.

The sprayer assembly of this embodiment also has a handle portion 90 similar to the handle portion 14 of the embodiment of Figures 2-4, but is somewhat shorter. The dispenser assembly of this embodiment also has an adaptor 100 similar to the adaptor 50 of the previous embodiment but is substantially longer. The dispenser assembly of this embodiment also has a tube 110 similar to the tube 16 of the previous embodiment except that it has a pre-formed coil portion 112 housed within a chamber 114 within the adaptor, the chamber being defined within the adaptor beneath the handle portion 90 of the dispenser. The upper end of the tube extends into the handle and neck portions of the dispenser and is secured thereto as with the first described embodiment. Also as with the first described embodiment, the tube extends in a tight-fit engagement through an opening at the bottom of the adaptor.

The operation and use of the dispenser assembly and adaptor of this embodiment is similar to that of the first described embodiment, except that when the dispenser assembly is disconnected from the adaptor for remote operation of the dispenser, the preformed coil portion 112 of the tube extends as shown in Figure 6, rather than the tube being pulled through the opening at the bottom of the adaptor as with the first described embodiment. To place the dispenser assembly back in its stored position, the preformed coil portion is allowed to collapse as in Figures 5 and 7 to be housed in the chamber 114 with the dispenser assembly connected to the adaptor. The primary advantage of this embodiment is that the lower portion of the tube in contact with the liquid is

never pulled from the container where it might contact the user, and the portions of the tube that are contacted by the user always remain segregated from the liquid.

Still another preferred embodiment of the present invention is shown in Figures 8-12. Generally, this embodiment is the same as the one shown in Figures 5-7 except as will be explained.

The dispenser assembly of this embodiment has a valve case 120 which is integrally molded as one-piece, and which performs the functions of the handle portion 90, the threaded closure 24, and the fitting 70 of Figure 7. The valve case 120 includes an inverted-cup shaped portion 121 that defines a central cavity 122. The ring portion 42 of this valve case 120, as better shown in Figures 11 and 12, is formed with opposite inwardly projecting tabs 124.

The dispenser assembly of this embodiment also has an adaptor 126 similar to the adaptor 100 of Figure 7 except that the adaptor 126 is shorter, and the shoulder 58 does not include the depending ring portion 60. As better shown in Figure 12, the adaptor 126 has the top portion 64 formed with bayonet-type provisions 128 which mate with the tabs 124 of the valve case 120. The adaptor 126 includes a collar 130 that is rotatably mounted on the shoulder 58 and has internal threads that mate with the threaded neck 30 of the container. The adaptor 126 has a vent 131.

This embodiment of the present invention includes a container 132 similar to the container 20 of Figures 1-7 except that this container 132 has a crown portion 134 that extends at least to the top of the dispensing assembly, as shown in Figure 8, and preferably somewhat above the top. Also, the container 132 has the handle portion 32 sloped as shown in Figure 8. The container 132 is provided with the sloping handle portion 32 so that when the container is carried and liquid is in the container,

the liquid will settle in the opposite bottom corner where the inlet to the dip tube 110 is located. This insures that during use, while the container is held in one hand and the sprayer in the other, the inlet to the dip tube 110 will be below the liquid level, even when the liquid level is drawn low. The crown portion 134 extends as high as or higher than the top of the dispensing head 140 to act as protection during shipment, storage, and the like. The crown portion 134 is located toward the vertical center of the container so that the container and its liquid contents will balance it upside down.

The dispensing assembly of this embodiment has a dispensing head 140. Both the dispensing head 140 and the trigger dispenser 12 are well-known in the art. Although the dispensing head 140 is more particularly shown here, it is merely representative of pump sprayers in general, and it is to be understood that there are many variations of dispensers that may be used with this invention, dispensers 12 and 140 being only examples.

The dispensing head 140 is an operable assembly which includes a housing 142, a trigger 144, a plunger 146, a spring 148, a spinner assembly 150, and the nozzle and orifice cap 22. The housing 142 is a molded piece that defines several chambers, including a vertical chamber 152, a horizontal chamber 154, a piston chamber 156 and a vent chamber 158 reciprocally receiving a vent piston 160. The wall of the vent chamber has a vent opening 162 which (with the vent opening 131) vents the container when the vent piston is retracted (moves to the left as viewed in Figure 9) upon pulling the trigger 144. The fitting end 70 of the valve case 120 is press fitted into the vertical chamber 152. The trigger 144 has its upper end pivotally supported by the housing 142 by means of oppositely extending lugs (not shown, but which extend into and out of the view of Figure 9) which pivot within

recesses in spaced side panels of the housing 142. Manually operating the trigger 144 causes the pumping of liquid through the tube from the container for ejection out the nozzle and orifice cap 22, as is well-known in the art.

With the bayonet-type connection between the valve case 120 and the adaptor 126, the valve case 120 can either be snapped directly onto the adaptor 126, or connected by orienting the dispensing head 140 at 90° to the container crown 134 and then rotating the dispensing head 140 a quarter turn until the dispensing head 140 is aligned with the container crown 134 as shown in Figure 8. The dispensing head 140 is mounted to the container 132 in the proper orientation by virtue of the adjustability provided by the collar 130. Thereafter, the dispensing head 140 is connected and disconnected to the adaptor 126 by means of the bayonet connection so that the dispensing head 140 is easily oriented to the same position for storage. The bayonet provisions 128 of the adaptor 126 and the threads of the collar 130 tighten in opposite directions so that rotation of the tabs 124 to disconnect the dispensing head 140 tends to tighten the collar 130 onto the threaded neck 30. The collar 130 and neck 30 may also be adapted to be connected with bayonet type provisions, but preferably at least the valve case 120 and adaptor 126 connect by bayonet type connections for ease and orienting the dispensing head 140.

The operation and use of the dispenser assembly and adaptor 126 of Figures 8-12 are similar to that of the embodiment of Figures 5-7, except that the cavity 122 of the valve case 120 cooperates with the chamber 114 of the adaptor 126 for housing the preformed coils 112 of the tube, as shown in Figures 9 and 10.

While the present invention has been described by reference to specific embodiments, it should be understood that modifications and variations of the invention

may be constructed without departing from the scope of the invention defined in the following claims.

The claims defining the invention are as follows:-

1. An assembly for dispensing liquid from a container having a liquid within an interior of the container; the container having an opening in the container, the opening providing access to the container interior, the assembly comprising:

5 a conduit having a length that enables extension of the conduit into the liquid held within the container interior;

a hand-held dispenser connected to the conduit, the hand-held dispenser having a pump operable for drawing liquid from the container interior by way of the conduit when the conduit is extended into the liquid held in the container interior;

10 an adaptor having a configuration dimensioned to enable insertion of the adaptor through the container opening and into the interior of the container and having a connector for affixing the adaptor on the container with the adaptor inserted through the container opening; and

the dispenser having a connector releasably affixing the dispenser on the adaptor
15 and the conduit extending from the dispenser through the adaptor and into the container with the adaptor inserted through the container opening; the conduit having flexible portions that provide extension upon disconnecting the dispenser from the adaptor for remote operation of the dispenser from the adaptor.

2. The assembly of claim 1 wherein:

20 the dispenser is a trigger dispenser that includes a handle portion that is readily accessible for gripping of the handle portion by a person's hand.

3. The assembly of claim 2 wherein:

the adaptor has a tubular portion with a hollow interior, and the handle portion of the dispenser extends at least partially into the interior of the tubular portion of the
25 adaptor with the dispenser affixed on the adaptor.

4. The assembly of claim 3 wherein:

the tubular portion of the adaptor and handle portion of the dispenser extend at least partially into the container when the adaptor is inserted into the container opening and is affixed on the container and the dispenser is affixed on the adaptor.

30 5. The assembly of claim 2 wherein:

the adaptor has a chamber therein, and the conduit has a preformed coil portion housed within the chamber with the dispenser affixed to the adaptor; the coil portion extending upon disconnecting the dispenser from the adaptor for remote operation of the dispenser.

35 6. The assembly of claim 1 wherein:

the hand-held dispenser has a handle portion, and the handle portion has a chamber therein,

the conduit has a preformed coil portion, and the adaptor has a chamber therein that cooperates with the chamber of the handle portion for housing the preformed coil portion



with the dispenser affixed to the adaptor; the coil portion extending upon disconnecting the dispenser from the adaptor for remote operation of the dispenser.

7. The assembly of claim 1 wherein:

the dispenser and adaptor include interengaging bayonet connectors.

5 8. The assembly of claim 1 wherein:

the conduit has a retainer for preventing complete removal of the conduit from the adaptor.

9. The assembly of claim 1 wherein:

the adaptor has a threaded connector for affixing the adaptor on the container when
10 the adaptor is inserted into the container opening.

10. The assembly of claim 1 wherein:

the dispenser connector includes threaded connectors.

11. A dispensing system comprising:

a container for holding a liquid within an interior of the container, the container
15 having an opening to the container interior;

an adaptor inserted through the container opening and into the container interior and the adaptor and container having connectors releasably affixing the adaptor to the container with the adaptor inserted through the container opening and into the container interior;

20 a conduit extending through the adaptor and into the container interior with the adaptor connected to the container for conducting liquid out of the container and through the adaptor;

a hand-held dispenser connected to the conduit, the dispenser having a pump for drawing liquid from the container by way of the conduit; and

25 the dispenser and adaptor having connectors releasably affixing the dispenser and adaptor together with the conduit extending from the dispenser to the adaptor, and into the container; the conduit having flexible portions that provide extension upon disconnecting the dispenser from the adaptor for remote operation of the dispenser.

12. The dispensing system of claim 11 wherein:

30 the connectors connecting the dispenser and adaptor are interengaging threaded connectors.



13. The dispensing system of claim 11 wherein:

the connectors for connecting the dispenser and adaptor are interengaging bayonet connectors.

35 14. The dispensing system of claim 11 wherein:

the adaptor has a chamber therein, and the flexible portions of the conduit include a preformed coil portion which can be housed within the chamber while the dispenser is connected to the adaptor.

15. The dispensing system of claim 11 wherein:



the container has a configuration that positions the container opening in a horizontal plane when the container rests upon a flat, horizontal surface and the container has a handle having a center axis positioned at an angle relative to a plane of the container opening, whereby when the container is suspended by the handle with the handle axis
5 positioned in a horizontal plane, the plane of the container opening is positioned at an angle relative to the horizontal plane.

16. An assembly for dispensing a liquid from a container, said assembly comprising:

a dispensing head;

10 a handle attached to the dispensing head, the head being configured for gripping by a user's hand and having an open-ended, cylindrical chamber therein;

a flexible conduit extending from the dispensing head through the chamber and having a length that enables insertion of the conduit into liquid of the container for delivering the liquid from the container to the dispensing head, at least a portion of the
15 flexible conduit being housed in the handle chamber; and said portion of said flexible conduit being flexibly extendable from the handle chamber; and

a connector attached to the handle releasably affixing the dispenser head to an adaptor, the connector located on the handle so that the handle extends at least partially into the adaptor when the dispenser head is connected to the adaptor.

20 17. The assembly of claim 16 wherein:

the connector is a bayonet type connection.

18. The assembly of claim 16 further comprising:

an adaptor having a configuration dimensioned to enable insertion of the adaptor through an opening of the container and into an interior volume of the container, the
25 adaptor having a hollow interior with an opening thereto, the adaptor interior being dimensioned to house a portion of the flexible conduit therein.

19. The assembly of claim 18 wherein:

the handle of the dispensing head and the adaptor are configured to be connected together with the handle chamber and adaptor interior communicating and housing a
30 portion of the conduit therein.

20. A container adaptor for connecting a container to a hand-held pump dispenser having a conduit, where the container has an interior holding a liquid and an opening to the interior, and the dispenser has a handle that is accessible on the dispenser for gripping of the handle by a person's hand, the container adaptor comprising:

35 at least one wall having a cup-shaped configuration defining an interior chamber within the cup-shaped wall and a first opening in the wall providing access to the interior chamber and a second opening in the wall for insertion of the conduit therethrough, the interior chamber having a volume sufficiently large to receive therein the dispenser handle when inserted through the first wall opening, the cup-shaped wall having first means



positioned around the first opening in the wall for releasably affixing the wall to the dispenser when the dispenser handle is inserted through the first wall opening and is received in the interior chamber, and the wall having an exterior configured for insertion of the cup-shaped wall through the container opening and into the container interior, the
5 wall having second means positioned on the wall exterior for releasably affixing the wall to the container when the wall is inserted through the container opening and into the container interior.

21. The container adaptor of claim 20, wherein:

the second means for releasably affixing the wall to the container is a threaded
10 connector.

22. The container adaptor of claim 20, wherein:

a flange extends outwardly from the wall exterior and the second means for releasably affixing the wall to the container includes a threaded collar mounted for rotation on the wall and the flange.

15 23. An assembly for dispensing a liquid from a container, substantially as herein described with reference to Figures 1 to 4, 5 to 7 or 8 to 12.

Dated 10 March, 1995

Contico International, Inc.

Patent Attorneys for the Applicant/Nominated Person

SPRUSON & FERGUSON






FIG. 1.
(PRIOR ART)

36045/93

FIG. 5.




FIG. 6.





FIG. 7.



SUBSTITUTE SHEET








FIG. 9.

FIG. 10.





INTERNATIONAL SEARCH REPORT

International application No.
PCT/US93/00899

A. CLASSIFICATION OF SUBJECT MATTER

IPC(S) :B65D 23/10;B67D 5/40
US CL :222/383; 220/771

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 222/179.5,324,382,464,465.1,527,530,538

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US,A, 3,078,471 (Knibb) 26 February 1963 column 3, line 16- column 5, line 39, Fig. 1-4.	1-9 2-4,7-8, 10-11,25-27
X	US,A 4,925,040 (Wang) 15 May 1990 column 1, line 40- column 2 line 30, Fig 4-6.	12 & 13-16
X	US,A 4,365,751 (Satto et al) 28 December 1982 column 2, line 16- column 3, line 3, Fig. 1.	17-21
Y	US,A 3,061,202 (Tyler) 30 October 1962 column 2, line 7- column 3, line 60 Figure 3 & 7.	2-4,25-27

Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:	T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be part of particular relevance	X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	Z	document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means		
"P" document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

18 APRIL 1993

Date of mailing of the international search report

05 MAY 1993

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

KENNETH BOMBERS

Facsimile No. NOT APPLICABLE

Telephone No. (703) 308-1113

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US93/00899

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A, 2,805,001 (Biederman) 03 September 1957 column 1, line 42- column 2, line 29 Fig 1-3.	7-8
X Y	US,A, 3,927,797 (Flider) 23 December 1975 column 2, line 5.	22-23 24
A	US,A, 5,154,324 (Stratford) 13 October 1992 column 4, line 64- column 5, line 48 fig. 4 & 5.	1-21 & 25-28
Y	US,A, 4,541,529 (Hestehave et al.) 17 September 1985 column 4, lines 4-39 Fig. 2.	24