



US 20080054028A1

(19) **United States**

(12) **Patent Application Publication**  
**Brannon et al.**

(10) **Pub. No.: US 2008/0054028 A1**

(43) **Pub. Date: Mar. 6, 2008**

(54) **DISPENSING CLOSURE HAVING A FLOW CONDUIT WITH KEY-HOLE SHAPE**

**Related U.S. Application Data**

(75) Inventors: **Patrick J. Brannon**, Warwick, RI (US); **Clifford W. Skillin**, Blackstone, MA (US); **Sergey Romanov**, Cranston, RI (US)

(60) Provisional application No. 60/824,322, filed on Sep. 1, 2006, provisional application No. 60/893,883, filed on Mar. 8, 2007.

**Publication Classification**

Correspondence Address:  
**BARLOW, JOSEPHS & HOLMES, LTD.**  
**101 DYER STREET, 5TH FLOOR**  
**PROVIDENCE, RI 02903**


(51) **Int. Cl.**  
**B67D 3/00** (2006.01)  
(52) **U.S. Cl.** ..... **222/547; 222/564**  
(57) **ABSTRACT**


(73) Assignee: **Polytop Corporation**, Slatersville, RI (US)

A dispensing closure has a flow conduit that provides a sufficient flow restriction to prevent unwanted spurting of the product when the container is initially opened. The dispensing closure includes a closure body with an upper deck and a flow conduit extending through the upper deck. The flow conduit includes an entry orifice having an entrance axis and an exit orifice having an exit axis. The entrance axis is parallel to, but not co-linear with, the exit axis to provide a non-linear flow path from an interior of the closure to the exterior of the closure.

(21) Appl. No.: **11/849,979**

(22) Filed: **Sep. 4, 2007**








FIG. 2




FIG. 3




FIG. 4

## DISPENSING CLOSURE HAVING A FLOW CONDUIT WITH KEY-HOLE SHAPE

### CROSS REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is related to and claims priority from earlier filed U.S. Provisional Patent Application No. 60/893,883 filed Mar. 8, 2007 and U.S. Provisional Patent Application No. 60/824,322 filed Sep. 1, 2006, all of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

**[0002]** The present invention relates to container closures, and more particularly to squeeze-type container dispensing closures.

**[0003]** There are two major trends occurring in the design of dispensing containers and closures. The first trend is a focus on providing a “clean pour” during dispensing of the product. Many food products, such as mustard and ketchup, have a high viscosity and require the user to tip the container, shake down the product and then squeeze the container to dispense the product. Past dispensing closures tended to leak product onto the top deck of the closure after dispensing, creating a messy appearance and often requiring cleaning to reseal the closure. The current emphasis in “clean pour” design is on preventing spurling of the product when the container is inverted to the dispensing position and/or shaken down, and creating a “suck-back” effect as pressure is released from the container to draw the product back into the closure.

**[0004]** A second trend is a growing number of dispensing containers and closures being designed so that they can be stored in an inverted position, i.e. cap down. In this regard, the product is always located right at the dispensing closure for easy dispensing right from storage. This reduces the need to tip and shake the container to push the product down to the dispensing closure. There is a balance however, between having the product at the closure for dispensing and the need to prevent the product from immediately spurting out once the lid of the closure is opened.

**[0005]** Both of these trends have resulted in the design of dispensing closures having various types of valve structures that facilitate both a clean pour and inverted storage. For example, a silicone valve structure is illustrated and described in U.S. Pat. No. 5,271,531. While these silicone valves have been widely accepted by both the manufacturers and the consumers, they are somewhat more difficult to manufacture, as they require several inter-fitting parts, and thus they tend to be more expensive than traditional one-piece dispensing closures.

**[0006]** Another perceived drawback to the silicone valve closure is that they are constructed out of two different types of plastic and thus, from a recycling standpoint, they are more difficult to recycle because the silicone valve must be separated from the plastic closure body for recycling. While this is not a major issue in the United States, at least yet, it is currently a major issue in Europe where recycling is extremely important and even mandated in some countries.

**[0007]** Other designs of dispensing closures focus on the use of interior partitions to slow the flow of the product exiting the dispensing orifice. For example, U.S. Pat. No. 5,123,575 discloses a design of a dispensing closure having multiple chambers. This patent discloses a container for

motor oil with three interior chambers, namely a primary chamber between the first partition and the bottom wall, a secondary partition between the first and second partitions and a tertiary chamber between the top wall and the second partition. While the concept of the design may provide the desired flow characteristics, the design is virtually impossible to mold using conventional injection molding or blow molding techniques and thus is not commercially feasible.

**[0008]** U.S. Pat. No. 5,819,994 also discloses a dispensing closure using multiple chambers. This patent discloses a flow controlling cap for a fluid (water) container that controls fluid flow by means of gravity and pressure, and has a first chamber formed by a first hollow cylinder and a second chamber formed by a second hollow cylinder having a greater diameter than the first hollow cylinder. While the circuitous path of this design is effective for water, the flow characteristics of water are different than other viscous fluids and thus the design is not believed to be suited for other more viscous products. In short, it would be difficult to force viscous fluids through the multi-chamber design.

**[0009]** Accordingly, there exists a need in the industry for a one-piece dispensing closure that provides a “clean pour” and prevents premature flowing of viscous product prior to squeezing the dispensing container. In addition, there exists a need a design of a dispensing closure that is easy to mold and made of one type of recyclable plastic.

### SUMMARY OF THE INVENTION

**[0010]** The present invention preserves the advantages of existing dispensing closures while providing new advantages not found in currently available dispensing closures and overcoming many disadvantages of such currently available dispensing closures. The general concept of the present invention is to provide a non-linear flow path from an interior of the dispensing closure to an exterior of the dispensing closure so that the product does not immediately spurt out upon opening of the closure lid and/or inverting and shaking the container to move the product toward the dispensing orifice.

**[0011]** Generally, the dispensing closure comprises a closure body, a closure lid and a living hinge structure hingedly connecting the closure lid to the closure body. The closure body has an upper deck and a skirt depending from the upper deck where the skirt is configured and arranged to mount to a product container (not shown). Preferably, the product container is a conventional squeeze-type container. Preferably, the skirt is internally threaded for threaded mounting on a product container.

**[0012]** A flow conduit extends through the upper deck for the passage of a viscous product, such as mustard. The flow conduit includes an entry orifice (inside the container) having an entrance axis and an exit orifice (outside the container) having an exit axis. The entrance axis is parallel to, but not co-linear with the exit axis to provide a non-linear flow path from the interior of the closure to the exterior of the closure. The bottom wall of the flow conduit thus prevents the direct flow of product into the flow conduit along the exit axis.

**[0013]** It is therefore an object of the present invention to provide a one-piece low cost dispensing closure that does not include a valve structure.

**[0014]** It is a further object of the embodiment to provide a dispensing closure having a “clean-pour” dispensing characteristic.

[0015] Another object of the embodiment is to provide a dispensing closure having a sufficient flow restriction, to counter product head pressure created when an upright container is quickly inverted and shaken to dispense product.

[0016] Another object of the embodiment is to provide an obstructed flow path or a non-linear flow path from an interior of the dispensing closure to an exterior of the dispensing closure.

[0017] Another object of the embodiment is to provide a flow conduit that allows product to flow freely upon squeezing while also providing a passive flow restriction.

[0018] Other objects, features and advantages of the invention shall become apparent as the description thereof proceeds when considered in connection with the accompanying illustrative drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The novel features which are characteristic of the dispensing closure are set forth in the appended claims. However, the dispensing closure, together with further embodiments and attendant advantages, will be best understood by reference to the following detailed description taken in connection with the accompanying drawing Figures.

[0020] FIG. 1 is a perspective view of the dispensing closure constructed in accordance with the teachings of the present invention;

[0021] FIG. 2 is a bottom view thereof;

[0022] FIG. 3 is a cross-sectional view of thereof as taken along line 3-3 of FIG. 1; and

[0023] FIG. 4 is a diagrammatical view thereof.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] Referring now to the drawings, the dispensing closure 10 of the instant invention is illustrated in FIGS. 1-4. As will hereinafter be more fully described, the instant dispensing closure 10 includes a unique flow conduit arrangement, which includes an offset, obstructed, and non-linear flow path. The unique arrangement provides anti-sputtering in upright containers as well as "suck-back" for cleaner product dispensing, i.e. "clean pour".

[0025] Generally, the dispensing closure 10 comprises a closure body 20, a closure lid 130 and a living hinge structure 140 hingeably connecting the closure lid 130 to the closure body 20. The closure body 20 has an upper deck 30 and a skirt 40 depending from the upper deck 30 where the skirt 40 is configured and arranged to mount to a product container (not shown). Preferably, the product container is a conventional squeeze-type container. Preferably, the skirt 40 is internally threaded for threaded mounting on a product container (See FIG. 2). However, it is to be understood that other skirt mounting arrangements are also contemplated within the scope of the invention, and the invention should not be limited to the inwardly threaded skirt as the only means for mounting.

[0026] A flow conduit generally indicated at 50 extends through the upper deck 30 for the passage of a viscous product, such as mustard. The flow conduit 50 is generally defined by an interior wall 50C, an exterior wall 50F, and a bottom wall 50G (baffle). The flow conduit 50 includes an entrance orifice 50A (inside the container) having an

entrance axis X and an exit orifice 50B (outside the container) having an exit axis Y. Generally, the entrance axis X is offset from the exit axis Y to provide a non-linear flow path (see arrows F) from the interior of the closure 10 to the exterior of the closure. More specifically, the flow conduit 50 is expanded to the side of the exit orifice 50B, and the entrance orifice 50A is located in the bottom wall 50G, but offset from the exit orifice 50B. The entrance axis X is thus parallel to but not co-linear with the exit axis Y. Referring briefly to FIG. 2, it is noted that the overall shape of the flow conduit 50 when viewed from the bottom is a key-hole shape.

[0027] The bottom wall 50G of the conduit thus prevents the direct flow of product (see arrows P—FIG. 1A) into the flow conduit along the exit axis Y and acts as a baffle to counter product head pressure created by either storing the product in an inverted condition, or head pressure created when an upright container is quickly inverted to dispense product. Flow of the product is shown by arrow F.

[0028] The baffling effect is also enhanced by the passage of the product from the container, through the small entrance orifice 50A and into the interior of the flow conduit 50. The velocity of the product will increase as it travels through the entrance orifice 50A. However, the velocity of the product then decreases as it travels into the larger interior volume of the flow conduit 50 before it leaves through the exit orifice 50B. Sputtering thus occurs into the interior of the flow conduit 50 and not directly out of the exit orifice. Accordingly, when the container is inverted, and is rapidly shaken up and down by a user to dispense the product, the product first decelerates into the larger volume interior flow conduit 50, and does not spurt out the exit orifice 50B. When pressure is applied to the squeeze container, the product is then forced out of the exit orifice 50B.

[0029] It is to be noted that the dimensions of the flow conduit 50 are adjustable, depending upon the viscosity of the product stored within an interior of the dispensing closure 10. For example, if lower viscosity mustard is contained within the interior of the dispensing closure 10, it may be desirable for the flow conduit 50 to be smaller in size or dimension to achieve a lower flow rate. In the preferred embodiment as shown, the exit orifice 50B is circular, and is somewhat smaller than the entrance orifice 50A.

[0030] Based on the disclosure above, the present invention provides a one-piece dispensing closure. Also, the invention provides a one-piece dispensing closure having a "clean-pour" dispensing characteristic. Furthermore, the invention provide a one-piece dispensing closure having a sufficient flow restriction within the flow path to counter product head pressure created when an upright container is quickly inverted and/or shaken to dispense product.

[0031] It would be appreciated by those skilled in the art that various changes and modifications can be made to the illustrated embodiments without departing from the spirit of the embodiments. All such modifications and changes are intended to be covered by the appended claims.

What is claimed is:

- 1. A dispensing closure for a highly viscous food condiment comprising:
  - a closure body;
  - a closure lid; and

a living hinge structure hingeably connecting said closure lid to said closure body,  
said closure body including  
an upper deck,  
a skirt depending from the upper deck, said skirt being configured and arranged to mount to a product container, and  
a flow conduit extending through said upper deck,  
said flow conduit including an entrance orifice having an entrance axis and an exit orifice having an exit axis,

said entrance axis being stepped from said exit axis whereby said flow conduit provides a non-linear flow path from an interior of said closure to an exterior of said closure,  
said entrance axis being parallel to said exit axis, said entrance orifice being larger than said exit orifice.

2. The dispensing closure of claim 1 wherein said exit orifice is circular, and said entrance orifice is non-circular.

3. The dispensing closure of claim 1 wherein said flow conduit has a key-hole shaped cross-section.

\* \* \* \* \*