

(21) Application No: **0920486.8**
(22) Date of Filing: **03.04.2008**
(30) Priority Data:
(31) **20072118** (32) **24.04.2007** (33) **NO**
(86) International Application Data:
PCT/US2008/059226 En 03.04.2008
(87) International Publication Data:
WO2008/134191 En 06.11.2008

(51) INT CL:
E21B 33/076 (2006.01)
(56) Documents Cited by ISA:
GB 1286055 A **WO 2006/030186 A**
US 5893417 A **US 4673041 A**
US 3517738 A **US 3242991 A**
US 20080110613 A1 **US 20060124314 A1**
US 20030221844 A1
(58) Field of Search by ISA:
INT CL **E21B**
Other: **EPO-Internal**

(71) Applicant(s):
FMC Technologies, Inc.
(Incorporated in USA - Delaware)
1803 Gears Road, Houston, Texas 77067,
United States of America
(72) Inventor(s):
Brian Skeels
Hans Jorgen Lindland
Olav Inderberg
Bjorn Jahnsen
(74) Agent and/or Address for Service:
Elkington and Fife LLP
Prospect House, 8 Pembroke Road, SEVENOAKS,
Kent, TN13 1XR, United Kingdom

(54) Abstract Title: **Lightweight device for remote subsea wireline intervention**

(57) In one illustrative embodiment, the present invention is directed to a device adapted to be positioned adjacent an end (122) of a tool housing of a subsea lubricator (120), wherein the device (130) includes a structural member that is adapted to be positioned adjacent an end of the tool housing, a non-metallic body coupled to the structural member and a sealing device (391) that is adapted to sealingly engage a wireline (140) extending through the sealing device. The present invention is also directed to a method which includes lowering an assembly toward a tool housing of a subsea lubricator (120) positioned subsea using a wireline (140) for the tool to support a weight of the assembly, wherein the assembly includes a wireline tool (150) and a device including a structural member that is adapted to be positioned adjacent the end of a tool housing, a non-metallic body coupled to the structural member, and a sealing device that is adapted to sealingly engage a wireline (140) extending through the sealing device.

