




(86) Date de dépôt PCT/PCT Filing Date: 2008/09/17
 (87) Date publication PCT/PCT Publication Date: 2009/03/26
 (85) Entrée phase nationale/National Entry: 2010/03/19
 (86) N° demande PCT/PCT Application No.: JP 2008/066719
 (87) N° publication PCT/PCT Publication No.: 2009/038068
 (30) Priorités/Priorities: 2007/09/21 (JP2007-245494);
 2007/10/11 (JP2007-265734)

(51) Cl.Int./Int.Cl. *B61F 5/44* (2006.01),
B61F 3/12 (2006.01)
 (71) Demandeur/Applicant:
 SUMITOMO METAL INDUSTRIES, LTD., JP
 (72) Inventeurs/Inventors:
 KIKKO, SATOSHI, JP;
 NAKAI, TAKUJI, JP;
 TSUTSUI, YUJIN, JP
 (74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : BOGIE DIRECTEUR POUR MATERIEL ROULANT, MATERIEL ROULANT ET VEHICULE ARTICULE
 (54) Title: STEERABLE TRUCK FOR A RAILWAY CAR, A RAILWAY CAR, AND AN ARTICULATED CAR

Fig. 1



(57) Abrégé/Abstract:

A steering bogie for rolling stock having excellent curve passing performance which can be actually achieved easily at a low cost. When running on a curved track, the bogie frame is steered in the direction along the tangential direction of a curved track by

(57) **Abrégé(suite)/Abstract(continued):**

controlling only the steering angle of a rear wheel shaft so that a steering angle, i.e. the angle of the center line of the rear wheel shaft and a virtual line connecting the centers of the bogie frame and the curved track in a horizontal plane, becomes larger than a steering angle, i.e. the angle of the center line of a front wheel shaft and the virtual line. Consequently, a steering bogie for rolling stock having excellent curve passing performance which can be actually achieved easily at a low cost is provided.

Abstract

A steerable truck for a railway car which has excellent ability to travel along a curved track and which can actually be realized simply and with a low cost is provided.

5 A truck frame is steered so as to be aligned with the tangential direction of a curved track by controlling only the steering angle of a rear wheelset so that during travel along a curved track, the steering angle which is the angle in a horizontal plane of the centerline of the rear wheelset with respect to an imaginary straight line connecting the center of the truck frame and the center of the curved track is larger
10 than the steering angle which is the angle formed between the imaginary straight line and the centerline of the front wheelset. As a result, a steerable truck for a railway car which has excellent ability to travel along a curve and which can be actually realized simply and at a low cost is provided.

Steerable Truck for a Railway Car, a Railway Car,
and an Articulated Car

Technical Field

This invention relates to a steerable truck for a railway car and a railway car
5 and an articulated car equipped with this steerable truck.

Background Art

Improving the ability of a railway car to smoothly travel along a curved track
is and has been an important technical problem. There is a strong desire for an
increased ability of a railway car to travel along curves, particularly for railway cars
10 traveling along sharp curves in suburban railways such as underground railways.

Figure 14 is an explanatory view schematically showing the behavior of a
conventional truck 3 in which the wheels are not steered with respect to a truck
frame 2 when traveling along a curved track 4. The truck frame 2 which is
traveling along a curved track 4, the wheelset 1f positioned to the front in the
15 direction of travel (referred to in this description as the front wheelset) and the
wheelset 1r positioned to the rear in the direction of travel (referred to in this
description as the rear wheelset) assume the attitudes shown in Figure 14. Symbol
O in Figure 14 indicates the center of the arc defined by the curved track 4.

Non-Patent Document 1 discloses that (a) the flange of the wheel 5 on the
20 outer side of the front wheelset 1f contacts the rail 4a on the outer side and an
attack angle θ develops; (b) this attack angle θ causes a lateral pressure Q_{si} to be
applied by the inner track; and (c) the rear wheelset 1r is located approximately
midway between the left and right rails 4a and 4b, so in the rear wheelset 1r, an
attack angle θ does not develop to the same extent as in the front wheelset 1f.
25 However, since a sufficient difference between the rolling radius of the left and
right wheels 5 is not obtained, the radius difference in the rear wheelset is
insufficient and causes a longitudinal creep force F_{vc} to develop. The inner track
lateral pressure Q_{si} and the longitudinal creep force F_{vc} produce a yawing moment
 M_y in the counterclockwise direction about the center of gravity of the truck frame

2. In Figure 14, Q_{so} indicates the outer track lateral pressure which develops in the front wheelset 1f.

Non-Patent Document 2 discloses that the truck frame 2 also has a yawing angle ϕ which is defined as the angle in a horizontal plane of the truck frame to the left and right with respect to the radial direction of the curved track. The yawing angle ϕ of the truck frame 2 has the same rotational direction as the attack angle θ of the front wheelset 1f. The yawing angle ϕ of the truck frame 2 causes the attack angle θ of the front wheelset 1f which is supported by this truck frame 2 to further increase.

Patent Document 1 discloses an invention in which in order to increase the ability of a railway car to travel along a curved track, an actuator is used as a supplemental means so that the truck frames which are positioned to the front and rear in the direction of travel pivot in synchrony with respect to the car body in the self-steering direction. That invention can decrease the yawing angle of the truck frame during travel along a curved track.

However, in order to carry out the invention disclosed in Patent Document 1, it is necessary to provide not only an actuator but also a controller for the actuator. In addition, it is necessary to provide safety measures for the event in which control of the actuator cannot be carried out in a normal manner. Therefore, the apparatus becomes complicated and costly.

A link-type steerable truck which uses links without using an actuator is also being developed. Figure 15 is an explanatory view schematically showing the structure of a typical link-type steerable truck 11. Figure 15(a) is a plan view and Figure 15(b) is a side view thereof.

In this steerable truck 11, the front wheelset 1f and the rear wheelset 1r are connected to a bolster 12, which is mounted on an unillustrated car body, and to a truck frame 13 by pairs of first links 14a and 14b. Of the first links 14a and 14b, each of the first links 14b which is connected to the truck frame 13 (referred to below as steering levers 14b) is connected to an axle box 19 which rotatably supports the front wheelset 1f or the rear wheelset 1r by a second link 15.

In this steerable truck 11, displacement of the bolster 12 on the car body side

with respect to the truck 11 by the bogie angle is transmitted to the steering levers 14b through the first links 14a. In the example shown in Figure 15, the connection points between the first links 14a and the steering levers 14b are connection points 16 on the car body side.

5 The transmitted displacement adjusts the steering amount based on the lever ratio when the connection points between the steering levers 14b and the truck frame 13, i.e., the connection points 17 on the truck frame side act as centers of pivoting (fulcrums), and the front wheelset 1f and the rear wheelset 1r are steered through the connection points between the steering levers 14b and the second links
10 15, namely, through the connection points 18 on the wheelset side.

Figure 16 is an explanatory view showing the behavior of the steerable truck 11 when traveling along a curved track.

As shown in Figure 16, in this steerable truck 11, the steering angle α_1 , which is the angle between the centerline CL1 of the front wheelset 1f and an
15 imaginary straight line CL3 in a horizontal plane connecting the center of the truck frame 13 with the center of a circular arc defined by the curved track, is the same as the steering angle α_2 formed between the centerline CL2 of the rear wheelset 1r and the straight line CL3.

- Non-Patent Document 1: "Properties of Trucks and Tracks During Travel
20 Along a Sharp Curve and their Effect on Rail Corrugation", J-Rail '95
- Non-Patent Document 2: "Methods of Measuring the Attack Angle of Wheels and the Relative Displacement of Wheels and Rails by Measurement on the Ground", Proceedings of the 73rd Regular General Meeting of the Japan Society of Mechanical Engineers
- 25 - Patent Document 1: JP 2002-87262 A1

Disclosure of Invention

Problem which the Invention is to Solve

With the steerable truck 11 shown in Figures 15 and 16, in order to increase the ability to travel along a curve, it is necessary for the truck frame 13 to movably
30 support the axle boxes 19 for the front wheelset 1f and the rear wheelset 1r so that

the front wheelset 1f and the rear wheelset 1r both have prescribed steering angles α_1 and α_2 .

Therefore, in this steerable truck 11, there is a limit to the degree of increase in the stiffness with which the truck frame 13 supports the front wheelset 1f and the rear wheelset 1r, and it is not easy to simultaneously provide all of the properties demanded of a truck for a railway car including the ability to stably travel along a straight track and prescribed vibration properties.

The present invention was made in light of such problems of the prior art, and it provides a steerable truck for a railway car which can be simply carried out at a low cost and which has excellent ability to travel along a curved track without worsening properties such as the ability to travel along a straight track and vibration properties. It also provides a railway car and articulated cars equipped with this steerable truck.

Means for Solving the Problem

The steering angle of the front wheelset and the steering angle of the rear wheelset in the steerable truck disclosed in Patent Document 1 and the like and in the steerable truck explained while referring to Figures 15 and 16 are set to the same value based on the premise that a railway car which can reverse the direction of travel should be symmetric in the fore and aft direction.

The present invention is contrary to such technical common sense, and it is based on the original technical concept: "When traveling along a curved track, of the steering angles of the wheelsets which are defined as the angles between an imaginary straight line connecting the center of the truck frame and the center of a circular arc defined by the curved track in a horizontal plane (referred to below as the reference line) and the centerlines of the front and rear wheelsets, by controlling the steering angle of the rear wheelset and preferably by controlling the steering angle only of the rear wheelset such that the steering angle which is the angle between the reference line and the centerline of the rear wheelset becomes larger than the steering angle which is the angle between the reference line and the centerline of the front wheelset, steering is performed such that the truck frame is

aligned with the tangential direction of the curved track. Namely, the yawing angle of the truck frame which is the angle in a horizontal plane of the centerline in the fore and aft direction of the truck frame with respect to the radial direction of the curved track can be decreased. As a result, a steerable truck for a railway car which has excellent ability to travel along a curved track and which can be carried out simply and at a low cost and without a worsening of properties such as the ability to travel along a straight track and vibration properties can be provided".

The present invention is a steerable truck for a railway car having a truck frame which rotatably supports a front wheelset positioned on the front side in the direction of travel and a rear wheelset positioned on the rear side in the direction of travel through axle boxes, and a truck frame steering unit for controlling the steering angle of at least the rear wheelset when traveling along a curved track, characterized in that when the truck is traveling along a curved track, the truck frame is steered so as to be aligned with the tangential direction of the curved track by controlling the steering angle of the rear wheelset by the truck frame steering unit so that the steering angle of the rear wheelset is larger than the steering angle of the front wheelset.

Also the present invention is a steerable truck for a railway car having a truck frame which rotatably supports a front wheelset positioned on the front side in the direction of travel and a rear wheelset positioned on the rear side in the direction of travel through axle boxes, and a truck frame steering unit for controlling the steering angle of at least the rear wheelset when traveling along a curved track, characterized in that when the truck is traveling along a curved track, the yawing angle of the truck frame, which is the angle formed in a horizontal plane between the radial direction of the curved track and the centerline in the fore and aft direction of the truck frame, is decreased by controlling the steering angle of the rear wheelset by the truck frame steering unit so that the steering angle of the rear wheelset is larger than the steering angle of the front wheelset.

In the present invention, the truck frame steering unit preferably controls only the steering angle of the rear wheelset during travel along a curved track.

In the present invention, control of the steering angle of the rear wheelset by

the truck frame steering unit is preferably carried out by a link mechanism mounted on the truck frame. Furthermore, the link mechanism preferably controls the steering angle in accordance with the bogie angle which is the relative displacement of the truck frame with respect to the car body when traveling along a curved track.

5 In the present invention, the link mechanism preferably has a first link which connects the car body and the truck frame, and a second link which connects the first link and at least an axle box which rotatably supports the rear wheelset.

In the present invention, the stiffness of the links connected to the rear wheelset is preferably different from the stiffness of the links connected to the front
10 wheelset.

From another standpoint, the present invention is a railway car having a truck on the front side and a truck on the rear side in the direction of travel, characterized in that at least one of the trucks on the front side and the rear side in the direction of travel is the above-described steerable truck for a railway car
15 according to the present invention.

The present invention is also a railway car characterized by having the above-described steerable truck for a railway car according to the present invention on the front side and on the rear side in the direction of travel, with the steerable trucks for a railway car being provided so that the rear wheelset is positioned on the
20 inner side in the direction of travel.

In addition, the present invention is articulated cars characterized by having the above-described steerable truck for a railway car according to the present invention at least in the articulated portion between two car bodies.

Effects of the Invention

25 According to the present invention, a steerable truck for a railway car which has excellent ability to travel on a curved track and which can actually be realized because it can be carried out simply and at low cost, and a railway car and articulated cars having this steerable truck can be provided

Brief Explanation of the Drawings

Figure 1 is an explanatory view schematically showing the structure of a first example of a steerable truck according to the present invention (an example in which only the rear wheelset is controlled), Figure 1(a) being a plan view and Figure 1(b) being a side view.

5 Figure 2 is an explanatory view illustrating the behavior of the steerable truck according to the present invention shown in Figure 1 when traveling along a curved track.

Figure 3 is an explanatory view schematically showing the structure of a second example of a steerable truck according to the present invention (an example in which the lever ratios of steering levers vary), Figure 3(a) being a plan view, and Figures 3(b) - 3(d) being side views, Figure 3(b) showing the case in which the lever ratios of a steering levers are the same, Figure 3(c) showing the case in which the lever ratio of a steering lever is greater for the rear wheelset, and Figure 3(d) showing the case in which only the rear wheelset is steered.

15 Figure 4 is an explanatory view schematically showing the structure of a third example of a steerable truck according to the present invention (an example in which the stiffness of the steering links is varied), Figure 4(a) being a plan view and Figure 4(b) being a side view.

Figure 5 is an explanatory view schematically showing the structure of a fourth example of a steerable truck according to the present invention (an example in which the location of the points where the steering links apply a force is varied), Figure 5(a) being a plan view and Figure 5(b) being a side view.

Figures 6(a) and 6(b) are explanatory views showing an example of applying a steerable truck according to the present invention to a car with 2-axle bogie trucks.

Figure 7 is an explanatory view showing an example of applying a steerable truck according to the present invention to articulated cars with 2-axle bogie trucks, Figure 7(a) being an explanatory view schematically showing the entire cars, Figure 7(b) being a plan view of an articulated portion, and Figure 7(c) being a side view of the articulated portion.

Figure 8 gives graphs showing the results of an investigation of the lateral

force in the outer track which develops in the front wheelset when a car is traveling along a curved track, Figure 8(a) showing the case using a steerable truck according to the present invention, and Figure 8(b) showing the case using a conventional truck.

5 Figure 9 gives graphs showing the results of an investigation of the longitudinal creep force which develops in the rear wheelset when a car is traveling along a curved track, Figure 9(a) showing the case using a steerable truck according to the present invention and Figure 9(b) showing the case using a conventional truck.

10 Figure 10 is an explanatory view showing an example of applying a steerable truck according to the present invention to a bolsterless truck, Figure 10(a) being a plan view and Figure 10(b) being a side view.

 Figure 11 is an explanatory view showing an example of applying a steerable truck according to the present invention to a 3-axle bogie truck, Figure 11(a) being
15 a plan view and Figure 11(b) being a side view.

 Figure 12 is an explanatory view showing various types of axle box suspensions which can be used in a steerable truck according to the present invention, Figure 12(a) showing a guide arm-type axle box suspension, Figure
20 12(b) showing a wing-type axle box suspension, and Figure 12(c) showing a shock absorbing rubber-type axle box suspension.

 Figure 13 is an explanatory view showing various types of axle box suspensions which can be used in a steerable truck according to the present invention, Figure 13(a) showing a leaf spring-type axle box suspension, Figure
25 13(b) showing an Alstom-type axle box suspension, and Figure 13(c) showing a multi-layered conic rubber-type axle box suspension.

 Figure 14 is a view showing the behavior of a conventional truck when traveling along a curved track.

 Figure 15 is an explanatory view schematically showing the structure of a typical link-type steerable truck, Figure 15(a) being a plan view and Figure 15(b)
30 being a side view.

 Figure 16 is an explanatory view showing the behavior of the steerable truck

shown in Figure 15 when traveling along a curved track.

Explanation of Symbols

	1f	front wheelset;	1r	rear wheelset
	12	bolster;	13	truck frame
5	14a	first link;	14b	first link (steering lever)
	15	second link		
	16	connection point on car body side		
	17	connection point on truck frame side		
	18	connection point on wheelset side		
10	21	steerable truck;	31	railway car

Best Mode for Carrying out the Invention

Below, the best mode for carrying out the present invention will be explained while referring to the attached drawings.

In the following explanation, an example will be given of the case in which control of the steering angle of the rear wheelset by a truck frame steering unit according to the present invention is carried out by a link mechanism mounted on the truck frame. In addition, in the following explanation, the same components as the components in above-described Figures 14 - 16 are affixed with the same symbols, so a repeated explanation thereof will be omitted.

Figure 1 is an explanatory view schematically showing the structure of a first example of a steerable truck 21 according to the present invention, Figure 1(a) being a plan view and Figure 1(b) being a side view.

This steerable truck 21 has a truck frame steering unit 20 mounted only on the rear wheelset 1r.

The rear wheelset 1r in this steerable truck 21 is connected to a bolster 12 which is mounted on an unillustrated car body and to a truck frame 13 by pairs of first links 14a and 14b. Of the first links 14a and 14b, each first link 14b which is connected to the truck frame 13 (referred to below as the steering lever 14b) is connected by a second link 15 to an axle box 19 which rotatably supports the rear wheelset 1r.

In this steerable truck 21, displacement of the bolster 12 on the car body side with respect to the truck 21 by the bogie angle is transmitted from first links 14a to the steering levers 14b. In the example shown in Figure 1, first links 14a are connected to the steering levers 14b at connection points 16 on the car body side.

5 The transmitted displacement adjusts the steering amount in accordance with the lever ratio when the connection points between the steering levers 14b and the truck frame 13, namely, connection points 17 on the truck frame side act as centers of pivoting (fulcrums), and the rear wheelset 1r is steered through the connection points between steering levers 14b and the second links 15, namely, through
10 connection points 18 on the wheelset side.

Figure 2 is an explanatory view showing the behavior of this steerable truck 21 when traveling along a curved track.

With this steerable truck 21, only the rear wheelset 1r is steered by the truck frame steering unit 20, so the relationship between the steering angle α_1 of the front
15 wheelset 1f and the steering angle α_2 of the rear wheelset 1r becomes $\alpha_2 > \alpha_1$.

The rear wheelset 1r which is steered by the truck frame steering unit 20 is moved towards the outer rails as shown by the arrow in Figure 2 by the self-steering function (the function in which the wheelset shifts in the axial direction so that a suitable rolling radius difference is obtained). Due to this movement, a rolling
20 radius difference is obtained between both wheels of the rear wheelset 1r. As the rolling radius difference increases, the longitudinal creep forces F_{vc} end up being in the directions shown in Figure 2, which are opposite to the directions of the forces for the conventional truck 3 shown in Figure 14.

In a steerable truck 21 in which the bolster 12 on the car body side, the truck
25 frame 13, and the rear wheelset 1r are connected by pins or the like, the longitudinal creep forces F_{vc} which act on the rear wheelset 1r are transmitted by the steering levers 14b from the rear wheelset 1r to the axle boxes 19 with the connection points 16 on the car body side acting as fulcrums and with the connection points 18 on the wheelset side acting as points of effort, and it is transmitted to the truck frame 13
30 via the connection points 17 on the truck frame side as acting forces F .

Therefore, in the steerable truck 21, as described above, the longitudinal

creep forces F_{vc} is applied to the truck frame 13 as acting forces F in the opposite directions from a conventional truck 3.

With the conventional truck 3 shown in Figure 14, the longitudinal creep forces F_{vc} produce a yawing moment M_y (referred to below as an antisteering moment, abbreviated as ASM) which imparts a yawing angle ϕ to the truck frame 13. In contrast, with this steerable truck 21, the above-described forces F produce a moment M (steering moment, abbreviated as SM) which decreases the yawing angle.

In this steerable truck 21, due to the truck frame 13 rotating in the clockwise direction as shown in Figure 2, the outer track lateral force Q_{so} , the inner track lateral force Q_{si} , and the attack angle θ of the front wheelset 1f are all decreased.

Next, the difference between a typical link-type steerable truck and a truck according to the present invention will be explained. In the typical link-type steerable truck 11 shown in Figure 15, the steering angle of the front wheelset 1f and the steering angle of the rear wheelset 1r are the same. In contrast, in the steerable truck 21 according to the present invention shown in Figure 1, the steering angle of the rear wheelset 1r is larger than the steering angle of the front wheelset 1f. The difference between a typical steerable truck 11 and a steerable truck 21 according to the present invention is a difference in the function of the steering levers 14b. This relationship is summarized in Table 1. In Table 1, pattern 1 corresponds to the typical link-type steerable truck 11 shown in Figure 15, and pattern 2 corresponds to the steerable truck 21 according to the present invention shown in Figure 1. The typical steerable truck 11 shown in Figure 15 uses the connection points 16 with the bolster as points of effort, it uses the connection points 17 with the truck frame as fulcrums, and it uses the connection points 18 with the axle boxes as points of load, whereby both the front and rear wheelsets are steered. In contrast, in the steerable truck 21 of the present invention shown in Figure 1, the connection points 18 with the axle boxes are used as points of effort, the connection points 16 with the bolster are used as fulcrums, and the connection points 17 with the truck frames are used as points of load, and the truck frame is steered.

Table 1

	Connection point 16	Connection point 17	Connection point 18	Steering location
Pattern 1	Point of effort	Fulcrum	Point of load	Wheelset steering
Pattern 2	Fulcrum	Point of load	Point of effort	Truck frame steering

By comparing Figure 16 and Figure 2, it can be seen that by making the steering angle of the rear wheelset 1r larger than the steering angle of the front wheelset 1f, steering can be performed so that the truck frame 13 is aligned with the tangential direction of the curved track 4. As a result, the outer track lateral force Q_{so} acting on the front wheelset 1f and the attack angle θ can be decreased.

The present invention was accomplished based on the above-described new knowledge.

Namely, as shown in Figures 1 and 2, when a steerable truck 21 for a railway car according to the present invention is traveling along a curved track, by controlling the steering angle of the rear wheelset 1r and preferably the steering angle only of the rear wheelset 1r so that the steering angle α_2 which is the angle formed in a horizontal plane between the centerline CL2 of the rear wheelset 1r with respect to the reference line CL3 which is an imaginary straight line connecting the center of the truck frame 13 and the center of the circular arc defined by the curved track is made larger than the steering angle α_1 which is the angle of the centerline CL1 of the front wheelset 1f with respect to the reference line CL3, the truck frame 13 is steered so as to be aligned with the tangential direction of the curved track. Namely, the yawing angle ϕ of the truck frame which is the angle in a horizontal plane of the centerline of the truck frame in the fore and aft direction with respect to the radial direction of the curved track can be decreased.

As an example of the structure of a truck frame steering unit 20 which makes the truck frame 13 steerable, as shown in Figure 1, for example, the bolster 12 on the car body side and the truck frame 13 can be connected by the first links 14a and

14b, and first links 14b and the rear wheelset 1r can be connected by the second links 15.

This link-type truck frame steering unit 20 makes actuators such as are used in Patent Document 1 unnecessary, so not only does a controller for an actuator become unnecessary, but safety measures for the case in which control of the actuator cannot be carried out in the normal manner also become unnecessary.

In a steerable truck 21 for a railway car according to the present invention, a truck frame steering unit 20 which makes the steering angle α_2 of the rear wheelset 1r larger than the steering angle α_1 of the front wheelset 1f is not limited to the one shown in Figure 1 which steers only the rear wheelset 1r.

As shown in Figures 3 - 5, a truck 21 which steers both the front wheelset 1f and the rear wheelset 1r can be similarly employed as long as the steering angle α_2 of the rear wheelset 1r is made larger than the steering angle α_1 of the front wheelset 1f.

Figure 3 is an explanatory view schematically showing the structure of a second example of a steerable truck 21 according to the present invention (an example in which the lever ratios of the steering levers are varied), Figure 3(a) being a plan view, and Figures 3(b) - 3(d) being side views. Figure 3(b) shows the case in which the lever ratios of the steering levers are the same, Figure 3(c) shows the case in which the lever ratios for the steering levers are larger for the rear wheelset, and Figure 3(d) shows the case in which only the rear wheelset is steered.

In the truck frame steering unit 20-1 shown in Figure 3, the horizontal first links 14a and 14b of the link-type truck frame steering unit 20 shown in Figure 1 are replaced by vertically disposed steering levers 14b. The steering angle α_2 of the rear wheelset 1r is made larger than the steering angle α_1 of the front wheelset 1f by making the lever ratios of the steering levers 14b different for the front wheelset 1f and the rear wheelset 1r.

In this case, the lever ratios of the steering levers 14b for the front wheelset 1f and the rear wheelset 1r do not satisfy $L_r = L_f$ as shown in Figure 3(b), but rather the lever ratios of the steering levers 14b for the front wheelset 1f and the rear wheelset 1r are made to satisfy $L_r > L_f$ as shown in Figure 3(c), whereby the

steering angle α_2 of the rear wheelset 1r can be made larger. In this truck frame steering unit 20-1 as well, the structure may be made such that only the rear wheelset 1r is steered ($L_f = 0$) as shown in Figure 3(d).

In this manner, by making the steering angle α_2 of the rear wheelset 1r larger than the steering angle α_1 of the front wheelset 1f, the force acting upon the rear wheelset 1r is made different from the force acting on the front wheelset 1f, so a force acts on connection points 17 on the truck frame side. Accordingly, the present invention can also be accomplished by the structure shown in Figures 3(c) and 3(d).

Figure 4 is an explanatory view schematically showing the structure of a third example of a steerable truck according to the present invention (an example in which the stiffness of the steering links is varied), Figure 4(a) being a plan view and Figure 4(b) being a side view.

In order to make the steering angle α_1 of the front wheelset 1f different from the steering angle α_2 of the rear wheelset 1r, the truck frame steering unit 20-2 shown in Figure 4 varies the stiffness of the second links 15 for the front wheelset 1f and the rear wheelset 1r instead of by varying the lever ratios of the steering levers 14b for the front wheelset 1f and the rear wheelset 1r as shown in Figure 3.

By making the stiffness of the rear wheelset 1r higher than the stiffness of the front wheelset 1f, the balance of the forces acting on the connection points 17 on the truck frame side is upset, forces are generated at the connection points 17, and the truck frame 13 is steered by the forces acting at the connection points 17.

Figure 5 is an explanatory view schematically showing the structure of a fourth example of a steerable truck according to the present invention (an example in which the positions of the points where the steering links apply a force is varied), Figure 5(a) being a plan view and Figure 5(b) being a side view.

The truck frame steering unit 20-3 shown in Figure 5 varies the points where forces are applied for steering the rear wheelset 1r and the front wheelset 1f so as to vary the steering angle α_1 of the front wheelset 1f and the steering angle α_2 of rear wheelset 1r instead of by varying the lever ratios of the steering levers 14b as shown in Figure 3 or varying the stiffness of the second links 15 as shown in Figure

4.

If the positions of the steering links 14b for the front wheelset 1f are inwards in the widthwise direction of a car from the positions of the steering links 14b for the rear wheelset 1r, even if the lever ratios are the same, if the distances b_f , b_r of the positions where forces act on the front wheelset 1f and the rear wheelset 1r satisfy $b_r > b_f$, the balance of the forces acting on the connection points 17 on the truck frame side is upset. As a result, the truck frame 13 can be steered.

Next, a situation in which a steerable truck 21 according to the present invention is mounted on a railway car 31 will be explained.

Figure 6(a) and 6(b) are explanatory views showing an example in which a steerable truck according to the present invention is applied to a car with 2-axle bogie trucks.

The basic arrangement is such that the steering angle for the rear wheelset 1r of each steerable truck 21 is larger for the steerable trucks 21 mounted both on the front side and on the rear side in the direction of travel in Figure 6(a).

However, the direction of travel of the railway car 31 reverses. Therefore, as shown in Figure 6(b), the arrangement of the steerable truck 21 positioned on the rear side in the direction of travel in Figure 6(a) may be the opposite of the arrangement of the steerable truck 21 positioned on the front side in the direction of travel. This is because the wheelset having the highest lateral pressure in the railway car 31 is the front wheelset 1f of the steerable truck 21 on the front side in the direction of travel, and the lateral pressure of the front wheelset of the steerable truck 21 on the rear side in the direction of travel is smaller. For the same reason, the structure may be such that only the truck on the front side in the direction of travel is made a steerable truck 21 according to the present invention.

Figure 7 is an explanatory view showing an example in which a steerable truck according to the present invention is applied to articulated cars with 2-axle trucks. Figure 7(a) is an explanatory view schematically showing the entire car, Figure 7(b) is a plan view of an articulated portion, and Figure 7(c) is a side view of the articulated portion.

In the case shown in Figure 7(a) in which car A is mounted on car B to form

articulated cars, a steerable truck 21 according to the present invention can be used as the trucks for car B. In this case, the same effect as for the case shown in Figure 6(b) is obtained regardless of the direction of travel. In the case of the articulated car shown in Figure 7, the trucks installed in locations other than where two car
 5 bodies are connected also use a steerable truck 21 according to the present invention, but a conventional truck can be used in portions other than the articulated portions.

The steerable truck 21 according to the present invention shown in Figure 1 was mounted as shown in Figure 6(a) on a typical commuter train, a test run was
 10 carried out at a speed of 15 km/hour on a curved region with a radius of curvature R of 120 m (cant of 60 mm), and the outer track lateral pressure generated in the front wheelset 1f and the longitudinal creep force generated in the rear wheelset 1r were measured. The results of measurement are shown in the following Table 2 and in the graphs of Figures 8 and 9.

15 Table 2

	Conventional truck	Steerable truck of present invention	Comments
Outer rail lateral pressure produced in front wheelset [kN]	11	4	
20 Longitudinal creep forces produced in rear wheelset [kN]	-7.4	3.7	+ value: acting as SM

From the results shown in Figure 8 and Table 2, it can be seen that the outer track lateral pressure which develops in the front wheelset 1f of a steerable truck 21 according to the present invention is smaller than the outer track lateral pressure
 25 which develops in the front wheelset of a conventional truck. In addition, it can be seen as shown in Figure 9(a) that in a steerable truck 21 according to the present invention, the longitudinal creep forces which develop in the rear wheelset 1r switch from the directions producing an ASM to the directions producing a SM to achieve the desired steering.

A steerable truck according to the present invention exhibits the behavior shown in Figure 2 when traveling along a curved track. Due to the rear wheelset moving towards the outer track side, a rolling radius difference develops, and longitudinal creep forces act in the opposite directions from in a conventional truck. Due to the "steering levers", this yawing moment in the clockwise direction acts on the truck frame as a yawing moment in the clockwise direction.

At this time, as shown in Table 1, the fulcrums of the "steering levers" are on the car body side, the points of effort are on the wheelset side, and the points of load are on the truck frame side. Therefore, due to the yawing moment acting on the truck frame, the yawing angle of the truck frame decreases. Due to the yawing angle of the truck frame decreasing, the attack angle of the front wheelset also decreases, and the inner track lateral pressure and the outer track lateral pressure both decrease.

In the above description, examples of carrying out the present invention have been explained, but the present invention is not limited to these examples, and suitable variations are of course possible as long as they fall within the technical concept set forth by the claims.

Figure 10 is an explanatory view showing an example of applying a steerable truck according to the present invention to a bolsterless truck, Figure 10(a) being a plan view and Figure 10(b) being a side view.

Figures 1 - 5 explain examples in which the present invention is applied to a bolster-type truck, but since it is sufficient that the bogie angle as an input corresponds to a relative displacement of a car and a truck, the present invention may also be applied to a bolsterless truck as shown in Figure 10. Reference number 20 in Figure 10 indicates a car body.

Figure 11 is an explanatory view showing an example in which a steerable truck according to the present invention is applied to a 3-axle bogie truck. Figure 11(a) is a plan view and Figure 11(b) is a side view.

Figures 1 - 10 show examples in which a steerable truck 21 according to the present invention is applied to a 2-axle truck. In the case shown in Figure 11 in which a steerable truck 21 according to the present invention is applied to a 3-axle

bogie truck, the steering angle of the rear wheelset 1r is made larger in the same manner as for a 2-axle truck. Symbol 1m in Figure 11 indicates the middle wheelset.

Figures 12 and 13 are explanatory views showing various types of axle box
5 suspensions which can be used in a steerable truck according to the present invention. Figure 12(a) shows a guide arm-type axle box suspension, Figure 12(b) shows a wing-type axle box suspension, Figure 12(c) shows a shock absorbing rubber-type axle box suspension, Figure 13(a) shows leaf spring-type axle box suspension, Figure 13(b) shows an Alstom-type axle box suspension, and Figure
10 13(c) shows a multi-layered conic rubber-type axle box suspension.

An axle box suspension used in a steerable truck according to the present invention is not limited to the monolink type as in the examples of Figures 1, 2, 7, and 10 and it is also possible to use various axle box suspensions like those shown in Figures 12 and 13.

Claims

1. A steerable truck for a railway car having a truck frame which rotatably supports a front wheelset positioned on the front side in the direction of travel and a rear wheelset positioned on the rear side in the direction of travel through axle
5 boxes, and a truck frame steering unit for controlling the steering angle of at least the rear wheelset when traveling along a curved track, characterized in that when the truck is traveling along a curved track, the truck frame is steered so as to be aligned with the tangential direction of the curved track by controlling the steering
10 angle of the rear wheelset by the truck frame steering unit so that the steering angle of the rear wheelset is larger than the steering angle of the front wheelset.

2. A steerable truck for a railway car having a truck frame which rotatably supports a front wheelset positioned on the front side in the direction of travel and a rear wheelset positioned on the rear side in the direction of travel through axle
15 boxes, and a truck frame steering unit for controlling the steering angle of at least the rear wheelset when traveling along a curved track, characterized in that when the truck is traveling along a curved track, the yawing angle of the truck frame, which is the angle formed in a horizontal plane between the radial direction of the curved track and the centerline in the fore and aft direction of the truck frame, is decreased by controlling the steering angle of the rear wheelset by the truck frame
20 steering unit so that the steering angle of the rear wheelset is larger than the steering angle of the front wheelset.

3. A steerable truck for a railway car as set forth in claim 1 or claim 2 wherein only the steering angle of the rear wheelset is controlled by the truck frame steering unit during travel along a curved track.

25 4. A steerable truck for a railway car as set forth in any one of claims 1 - 3 wherein control of the steering angle of the rear wheelset by the truck frame steering unit is carried out by a link mechanism mounted on the truck frame.

5. A steerable truck for a railway car as set forth in claim 4 wherein the link mechanism controls the steering angle in accordance with the bogie angle which is the relative displacement of the truck frame with respect to the car body during travel along a curved track.

5 6. A steerable truck for a railway car as set forth in claim 3 or claim 4 wherein the link mechanism has a first link which connects the car body and the truck frame, and a second link which connects the first link and at least an axle box which rotatably supports the rear wheelset.

10 7. A steerable truck for a railway car as set forth in any one of claims 4 - 6 wherein the stiffness of a link connected to the rear wheelset is different from the stiffness of a link connected to the front wheelset.

15 8. A railway car having a truck on the front side and a truck on the rear side in the direction of travel, characterized in that at least one of the trucks on the front side and on the rear side in the direction of travel is a steerable truck for a railway car as set forth in any one of claims 1 - 7.

 9. A railway car characterized by having a steerable truck for a railway car as set forth in any one of claims 1 - 7 on the front side and on the rear side in the direction of travel, wherein the rear wheelset of the steerable truck for a railway car is positioned on the inner side in the direction of travel.

20 10. Articulated cars characterized by having a steerable truck for a railway car as set forth in any one of claims 1 - 7 at least in the articulated portion between two car bodies.

Fig. 1




Fig. 2





Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8





Fig. 9





Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16





Fig. 1

(a)



(b)

