

(21) Application No 8926318.0
(22) Date of filing 21.11.1989
(30) Priority data
(31) 8827606 (32) 25.11.1988 (33) GB

(51) INT CL⁴
F16C 33/06
(52) UK CL (Edition J)
F2A AD44 A151 A192
U1S S2037

(71) Applicant
Vandervell Limited

(Incorporated in the United Kingdom)

Norden Road, Maidenhead, Berkshire,
SL6 4BG, United Kingdom

(56) Documents cited
GB 2210113 A GB 1386253 A GB 1297559 A

(72) Inventors
Michael Gordon Willis
Ewan Norman Frank Robbie

(58) Field of search
UK CL (Edition J) F2A AD44
INT CL⁴ F16C
Online databases: EDOC ; WPI

(74) Agent and/or Address for Service
D J Goddard, R F Hadfield, D D E Newman, J A Crux,
G K Gibson
Bowdon House, Ashburton Road West, Trafford Park,
Manchester, M17 1RA, United Kingdom

(54) Flanged bearing

(57) In a flanged journal bearing wherein a thrust flange is joined to a half bearing liner by means of co-operating lugs on the flange and slots in the bearing end face, the lugs 42 are offset from the remainder 44 of the flange material in order to provide increased mechanical interlocking after machining of the bearing.




FIG.1 PRIOR ART




FIG.3




FIG.4




FIG. 1 PRIOR ART




FIG. 2 PRIOR ART




FIG. 5




FIG. 4




FIG. 3

Bearings

The present invention relates to bearings and particularly to bearings of the flanged type having flanges which are separately manufactured and attached during manufacture to form an integrally flanged bearing.

In our British Patent Nos. 1297559 and 1386253, flanged bearings are described. These bearings are constructed by forming radially inwardly directed lugs on the inner periphery of an annular thrust bearing and which lugs co-operate with slots or recesses formed in one or both end faces of a thin wall half bearing liner. The circumferentially outer edges of the slots or recesses are then deformed such as to prevent detachment of the thrust bearing in the axial direction and still allow relative mutual movement between the components.

It has been found that where such bearings are proposed for use in engines with crankshafts having relatively

large fillet radii at the journal axial ends that the amount of material required to be machined away at the junction between the half bearing end face and the thrust washer inner periphery leaves only a relatively small amount of interlocking material.

According to the present invention a flanged bearing comprises a thin wall bearing liner and at least one thrust flange attached to one bearing liner end face, the thrust flange having at least one radially, inwardly directed lug on the inner periphery and which lug co-operates with a slot formed in the bearing liner end face, the circumferentially outer edges of which slot are deformed such as to retain the thrust flange on the bearing liner in the axial direction and wherein the material comprising the lug is offset from the plane of the material comprising the remainder of the thrust flange.

Preferably there are two or more co-operating lugs and slots per thrust flange.

In one embodiment there may be a thrust flange at each bearing liner axial end face.

Preferably the lug may be offset from the remainder of the thrust flange by means of shearing with a press tool.

Alternatively, the plane of the lug and the plane of the remainder of the thrust flange may be mutually offset by machining or bending methods.

In order that the present invention may be more fully understood an example will now be described by way of illustration only with reference to the accompanying drawings, of which;

Figure 1 shows a prior art flanged bearing according to GB 1386253;

Figure 2 shows a cross section through the end face/joint region of the prior art bearing of Figure 1 after machining;

Figure 3 shows an elevation of a thrust flange for a flanged bearing according to the present invention;

Figure 4 shows a section through the thrust flange of Figure 3 on the line AA; and

Figure 5 which shows a cross section through the bearing including the thrust flange of Figure 3 after machining to accommodate the same housing and crankshaft as in Figure 2.

Referring now to Figures 1 and 2 and where the same features are denoted by common reference numerals. A flanged bearing is shown generally at 10 the bearing comprises a thin-wall half bearing liner 12 and two thrust flanges 14. Three slots 20 are formed in each bearing end face 22 (only one end face is shown). Both the liner and the flanges are made from strip material having a steel backing 16 and a bearing alloy lining 18. The slots 20 co-operate with three radially inwardly directed lugs 24 formed on the inner periphery 26 of the flange such that when the slots and lugs are engaged the inner periphery 26 lies adjacent the outer periphery 28 of the bearing liner backing. Axial disengagement of the flange from the liner is prevented by the outer corners 30 of the slots being deformed towards one another and thus over the lug outer edges. In this manner the liner and flange are allowed slight mutual relative movement.

After assembly the end face region of the liner and flange are machined to accept the end fillet radius of a co-operating crankshaft journal (not shown). The machined profile to accommodate the fillet radius is represented by the dashed line 34 in Figure 2 which is a schematic section taken through a co-operating lug and slot of Figure 1. It may be seen that after machining the only interlocking metal remaining is that shown by the hatched

area 36 and that the majority of the deformed corners 30 will also have been removed.

Figures 3 and 4 show a thrust flange 40, again having three lugs 42. The lugs 42 are offset out of the plane of the thrust bearing annulus 44 and the co-operating slots 46 in half bearing liner 48 are correspondingly deeper in the axial direction. The deeper slots are to ensure that the spatial position of the inner face 50 of the steel backing 52 remains constant for a given bearing housing (not shown).

It may be seen in Figure 5 that after machining to the desired profile indicated by the dashed line 54 the interlocking cross sectional area shown by the hatched area 56 is considerably greater than the area 36 of Figure 2. The amount of metal remaining from the deformed corners of the slots 46 is also greatly increased thus enhancing the mechanical integrity of the assembled bearing.

CLAIMS

1. A flanged bearing, the bearing comprising a thin wall bearing liner and at least one thrust flange attached to one bearing liner end face, the thrust flange having at least one radially, inwardly directed lug on the inner periphery and which lug co-operates with a slot formed in the bearing liner end face, the circumferentially outer edges of which slot are deformed such as to retain the thrust flange on the bearing liner in the axial direction and wherein the material comprising the lug at its region of attachment to the liner is offset from the plane of the material comprising the remainder of the thrust flange
2. A bearing according to claim 1 having two or more co-operating lugs and slots per thrust flange.
3. A bearing according to either claim 1 or claim 2 wherein there is a thrust flange at each end face.
4. A bearing according to any one preceding claim wherein the plane of the material forming the lug is offset from the plane of the material forming the remainder of the thrust flange.

5. A bearing substantially as hereinbefore described with reference to the accompanying specification and figures 3, 4 and 5 of the drawings.