


Sept. 29, 1970

A. G. DEHNE

3,530,681

HYDRAULICALLY DRIVEN CRYOGENIC REFRIGERATOR

Filed Aug. 5, 1968



Axel G. Dehne,
INVENTOR.

BY.

A. M. Lesniak

ATTORNEY.

1

2

3,530,681
**HYDRAULICALLY DRIVEN CRYOGENIC
REFRIGERATOR**

Axel G. Dehne, Los Angeles, Calif., assignor to Hughes Aircraft Company, Culver City, Calif., a corporation of Delaware

Filed Aug. 5, 1968, Ser. No. 750,163
Int. Cl. F25b 9/00

U.S. Cl. 62-6

13 Claims

ABSTRACT OF THE DISCLOSURE

This disclosure specifically relates to an arrangement wherein cryogenic refrigerator expander and compressor pistons are actuated back and forth under the influence of refrigerant pressure and hydraulic pressure. Continuation of the refrigerant is avoided by providing bellows to hermetically seal the pistons within respective interconnected refrigerator subchambers. Each piston is controlled by a valve assembly having a two-position valve to allow refrigerant gas pressure to move the respective piston in a first direction when the valve is in a first position and to allow hydraulic pressure to move the respective piston in a second direction when the valve is in a second position. These valves are shifted between positions at appropriate times in the refrigeration cycle by hydraulic signals traveling through hydraulic passages including portions positioned within the pistons so that the pistons may reciprocate 90° out of phase.

This invention relates to a fluid drive unit for operating cryogenic refrigerators or other devices. The invention further relates to a hydraulic drive unit for reciprocating a plurality of pistons in phased synchronous relationship. More particularly, the invention relates to an arrangement wherein a hydraulic drive unit is utilized for reciprocating the pistons of a cryogenic refrigerator.

As is well known, cryogenic refrigerators utilizing the Stirling and other cycles, employ, in the transfer of a gas between a compression cylinder and an expansion cylinder, a regenerating device through which a compressible refrigerant gas is passed and which characteristically absorbs heat from the refrigerant as it moves to the expansion chamber, delivering gas thereto at a relatively low temperature. On the return phase of the cycle, the relatively cold refrigerant again passes through the regenerator, absorbing heat stored therein so that the refrigerant is delivered to the compression chamber at a relatively high temperature.

Cryogenic refrigerators of the prior art operating in this manner have conventionally employed electric motors producing a rotary motion and crank and rod mechanisms for converting the rotary motion into synchronously phased reciprocation of the compressor and expander pistons. Such an arrangement gives rise to problems. For example, this type of arrangement requires bearings and lubricants, and the lubricants tend to contaminate the refrigerant. More importantly, such arrangements are relatively noisy due to piston slapping, and side loads on the seals of the cryogenic refrigerator limit the useful life of the refrigerator. Further, and most significantly, the utility of such arrangements is somewhat restricted due to vibration thereof during operation. Operational vibrations are generally undesirable in mechanical devices and, with reference to cryogenic refrigerators which may be used in conjunction with vibration sensitive equipment or optical devices, such vibrations should be minimized as much as possible. Generally, when rotating mechanisms are used to drive a crank and rod arrangement, counter weights are rigidly placed on the crank in

such a position as to reduce vibration. Also, it is common to dynamically balance the moving pistons of such prior art devices against vibration by operating two such devices, suitably arranged within a common housing, in opposed directions. In the first instance detrimental vibrations can not be completely avoided, while, in the second instance, detrimental vibrations can be completely avoided but at the expense of a duplicate mechanism.

It is, therefore, a primary object of the invention to provide a hydraulic drive unit for a plurality of pistons.

It is another object of the invention to provide a hydraulic drive unit for a cryogenic refrigerator wherein hydraulic fluid pressure is operable to reciprocate an expander and compressor piston in phased synchronous relationship whereby relatively noise-free long-life operation is obtainable.

It is another object of the invention to provide a cryogenic refrigerator which, in operation, is capable of approximating a Stirling cycle.

It is another object of the invention to provide an arrangement wherein the refrigerant of a cryogenic refrigerator is permanently sealed to avoid contamination by lubricants.

It is another object of the invention to provide an arrangement for reciprocating the pistons of a cryogenic refrigerator which can be readily dynamically balanced, due to the elimination of the conventional crank and rod, by the provision of opposite stroking weights to essentially eliminate vibrations during operation thereof.

These and other objects are accomplished in accordance with the invention by operating an expander piston and a compressor piston in out-of-phase synchronous relationship. The pistons respectively reciprocate in an expander cylinder and a compressor cylinder which are interconnected and which contain a compressible refrigerant gas such as helium or the like under pressure. These pistons are moved back and forth in the respective chambers by refrigerant pressure and hydraulic pressure by controlled application of fluid pressure to the pistons by means of suitable hydraulic valving. The valving includes a two-position valve for each piston to allow refrigerant pressure to move the respective piston in a first direction when the valve is in a first position and to allow hydraulic pressure to move the respective piston in a second direction when the valve is in a second position. These valves are shifted between positions at appropriate times in the refrigeration cycle by hydraulic signals traveling through hydraulic passages including portions positioned within the pistons so that the pistons are caused to reciprocate 90° out of phase.

These and other features and advantages of the invention can be more clearly understood by reference to the following specification and the related drawing wherein a preferred embodiment incorporating the invention is shown. In the drawing certain parts are shown in cross section to facilitate an understanding of the invention.

Describing the arrangement in detail and directing attention to the figure, it will be seen that the cryogenic refrigerator 10 for cooling load 11 comprises a hermetically sealed chamber in a housing. Cooling load 11 may be any device such as an infrared detector or parametric amplifier which must be maintained at cryogenic temperatures. The housing chamber is comprised of an expander subchamber 12 and a compressor subchamber 13 interconnected by a passage 14. The wall of refrigerator 10 in the vicinity of expander subchamber 12 is extremely thin to limit flow of heat by conduction to subchamber 12 thus increasing the efficiency of refrigerator 10. Expander piston 15 and compressor piston 16 have respective piston heads or displacers 17 and 18. Disposed within a peripheral groove within each piston head is an O-

ring and continuous annular Teflon rider, 17a and 18a respectively, which effectively serve as seals and which may not be necessary in a given embodiment. Obviously, a skilled workman can design the pistons, and so forth, so as to obtain various piston compression ratios as deemed expedient. Respective resilient members such as bellows 19 and 20 are welded or otherwise suitably attached to peripheral portions of piston heads 17 and 18, and to the walls of the housing so as to hermetically seal cryogenic refrigerator 10. The chamber of cryogenic refrigerator 10 is filled with a compressible refrigerant gas such as helium or the like under a relatively high pressure.

Expander piston 15 has conventional regenerator means 21, such as a one stage regenerator, through which refrigerant gas may pass back and forth. Exemplarily, regenerator means 21 may comprise stacked stainless steel screens, glass beads, lead balls, or the like, which characteristically have a suitable thermal capacity characteristic and a relatively high surface area to volume ratio.

The expander piston 15 is provided with peripheral grooves in which O-rings 22 and 23 are disposed. These O-rings are operative to expand respective seals (not shown), such as Teflon riders, of generally annular configuration having an L-shaped cross section, against the wall of the piston cylinder to prevent or minimize leakage of refrigerant gas back and forth between expander subchamber 12 and expander bellow chamber 24. Expander passages 25 and 26 provide communication between expander subchamber 12 and compressor subchamber 13 via regenerator 21 which is mounted within an enlarged chamber in the expander piston portion or displacer 27. Passage 26 is so arranged as to provide the aforementioned communication regardless of the position of expander piston 15.

In order to provide for synchronous reciprocation of pistons 15 and 16 a hydraulic drive unit 28 is provided. Unit 28 comprises hydraulic drive valve assemblies 29 and 30. In valve assembly 29, a movable valve spool 31 is disposed within portion 32a of hydraulic reservoir 32. Spool 31 and portion 32a are complementarily shaped so that spool 31 is snugly fitted within portion 32a, and portion 32a is of sufficient length to allow spool 31 to slide back and forth therein. Portion 32b of reservoir 32 is dimensioned for a snug slide fit with the corresponding portion of piston 15.

In the embodiment shown, spool 31 is cylindrical, but it may be of any suitable shape. Spool 31 has transverse spaced holes or openings 33 and 34 drilled therethrough and so located that when valve spool 31 is in a first position opening 33 is aligned with valve port 35 and when valve spool 31 is in a second position, opening 34 is aligned with valve port 36. In lieu of openings 33 and 34 peripheral grooves may be cut into spool 31 to serve the same purpose.

In hydraulic valve assembly 30, it can be seen that movable valve spool 37, hydraulic reservoir 38, reservoir portions 38a and 38b, spool openings 39 and 40, and valve ports 41 and 42 are arranged in a fashion similar to the arrangement of the comparable elements of hydraulic valve assembly 29. Hydraulic pump P₁ is connected to port 35 and hydraulic pump P₂ is connected to port 41. Port 36 is connected to vent line V₁ and port 42 is connected to vent line V₂.

Hydraulic conduit means operably connect hydraulic pump P_b to valve spools 31 and 37 whereby these spools may be moved back and forth to control the application of hydraulic fluid pressure to the faces 41 and 42 of the respective expander piston 15 and compressor piston 16. Hydraulic fluid passages 43, 44, 45, 46, 47 and 48 are arranged so that, when expander piston 15 is at the bottom of its stroke, fluid pressure from hydraulic pump P_b will actuate valve spool 31 to bring valve spool opening 33 into alignment with valve port 35. Hydraulic fluid passages 49, 50, 51 and 52 are arranged so that, shortly after expander piston 15 has completed one half of its up-

ward stroke, hydraulic pump P₁ will actuate valve spool 37 to align valve spool opening 39 with valve port 41. Hydraulic fluid passages 46 and 53 are arranged so that, when expander piston 15 has completed its upward stroke, a hydraulic path is completed between hydraulic pump P₁ and vent line V₃ whereby valve spool 31 is actuated so as to bring valve spool opening 34 into alignment with valve port 36. Hydraulic fluid passages 50 and 49 are arranged so that, when compressor piston 16 has reached the top of its upward stroke, a hydraulic fluid path is completed between hydraulic pump P₂ and vent line V₁ whereby valve spool 37 is actuated to bring valve spool opening 40 into alignment with valve port 42. Finally, O-rings 54 and 55, together with respective seals (not shown) of the same type as those used in conjunction with previously mentioned O-rings 22 and 23, are respectively disposed in peripheral grooves adjacent respective pistons 15 and 16 and seal the housing of hydraulic unit 28 to prevent or minimize leakage of hydraulic fluid therefrom.

In operation, assuming pistons 15 and 16 are in the position shown, piston 15 has completed slightly more than half of its upward stroke, piston 15 being driven upward by the force of hydraulic pressure upon piston face 41 exerted by hydraulic pump P₁. At this time, piston face 41 has cleared passage 49 while passage 51 of piston 16 interconnects passages 50 and 52 whereby a hydraulic fluid path is completed between pump P₁ and vent line V₄ and valve spool 37 is moved to align opening 39 with valve port 41. Hydraulic pressure for pump P₂ now exerts a hydraulic force upon piston face 42 to drive compressor piston 16 upwardly. Both pistons 15 and 16 now travel concurrently upward, with expander piston 15 leading compressor piston 16 by approximately 90°, thereby compressing the refrigerant gas in the cryogenic refrigerator 10 to decrease the volume and increase the pressure thereof. During this initial phase of the cycle the heat of compression which is generated is rejected to the ambient through the walls of the housing, as indicated by Q_{out}, so that this phase is relatively isothermal.

Expander piston 15 now reaches its top position whereupon hydraulic fluid passages 46, 45, 53 and 48 complete a hydraulic fluid path between pump P₁ and vent line V₃ thus shifting valve spool 31 to bring valve spool opening 34 into alignment with valve port 36. The refrigerant gas pressure of the refrigerant gas in the interconnected subchambers 12 and 13 and in the bellow chambers 24 is now operative to push expander piston 15 downward expelling hydraulic fluid from hydraulic reservoir 32 through port 36 to vent line V₁. The extent to which the refrigerant gas in the bellow chamber 24 pushes the expander piston 15 downward in relation to the extent to which the refrigerant gas in the interconnected subchambers 12 and 13 pushes the expander piston 15 downward depends upon the design of the pistons 15 and 16, and so forth, as indicated earlier herein.

During the initial portion of this downward stroke of expander piston 15, compressor piston 16 continues upward and the arrangement preferably is such that the total volume of the refrigerator chamber remains substantially constant. During this second phase of the refrigeration cycle, wherein expander piston 15 is moving downward and compressor piston 16 is moving upward, refrigerant gas is transferred from compressor subchamber 13 to expander subchamber 12 through regenerator 21. Regenerator 21 absorbs and temporarily stores heat from the refrigerant. In this way the temperature and pressure of the refrigerant is reduced.

When compressor piston 16 reaches the top of its stroke the third phase of the refrigeration cycle begins wherein hydraulic pump P₂ is operably connected to vent line V₁ via hydraulic passages 50 and 49 to move valve spool 37 to the position wherein valve spool opening 40 is aligned with valve port 42. The refrigerant gas pressure

of the refrigerant gas in the interconnected subchambers 12 and 13 then moves compressor piston 16 downward to expell hydraulic fluid from reservoir 38 into vent line V_2 . During this third phase of the refrigeration cycle both pistons are moving downward so that the total volume of the refrigerator chamber is increasing. During this phase of the cycle the increasing volume within the chamber tends to decrease the refrigerant temperature. However, the refrigerant, at this time, absorbs heat from the walls of the housing thereby maintaining the refrigerant at a constant temperature which is lower than the refrigerant temperature during the initial or first-mentioned phase of the cycle. Thus, the thid phase is relatively isothermal.

Expander piston 15 now completes its downward stroke and a fluid path is completed, via passages 43-48, between hydraulic pump P_b and vent line V_3 so that valve spool 31 is moved to bring valve spool opening 33 and valve port 35 into alignment. Hydraulic pressure from hydraulic pump P_1 now exerts a hydraulic force upon piston face 41 and expander piston 15 begins its upward stroke. Thus the final or fourth phase of the refrigeration cycle is initiated. During this final phase pistons 15 and 16 are again moving in opposite directions and preferably in such a fashion as to maintain the volume of the refrigerator chamber constant. The upward traveling expander piston 15 now transfers refrigerant gas from expander subchamber 12 to compressor subchamber 13 through regenerator 21. During this final phase the refrigerant gas obtains heat from regenerator 21 which was previously stored therein. Thus a complete refrigeration cycle has been generated. If the total volume of the refrigerator chamber has been maintained substantially constant during the second and final phases then a Stirling cycle will have been approximated.

Exemplarily, the refrigerant gas may be under a pressure in the range of, for example, from 100 p.s.i.g. to about 300 p.s.i.g. during the refrigeration cycle. The forces exerted upon displacers 27, 17, and 18 and the force exerted on faces 41 and 42 respectively depends on pressure of the refrigerant gas or hydraulic fluid multiplied by the area of the parts 27, 17, 18, 41 and 42. Pistons 15 and 16 may be reciprocated at any rate, as for example 2000 cycles per minute, depending on the cooling capacity desired. The motion of pistons 15 and 16 may be sinusoidal or linear with time or otherwise. If it is desired to approximate a Stirling cycle, the motion and size of the pistons, and other parameters should be selected to obtain substantially constant volume conditions during the second and fourth phases of the refrigeration cycle.

The timing of the initiation of the compression strokes of pistons 15 and 16 clearly depend on the manner in which the fluid passages are arranged. It should be equally clear that, by the provision of suitable means, such as apertured sleeves, circumscribing the portions of pistons containing passages 44, 47, 53 and 51, and rotatably positioned thereabout, either on the associated piston portion or on the associated bore, the choice of a multiplicity of timing relationships is possible.

The cooling load may be maintained at cryogenic temperatures in a range of 20° Kelvin and higher. The cooling capacity of cryogenic refrigerator 10 can be adjusted simply by throttling or changing the fluid pressure of hydraulic pump P_1 and P_2 . Rejection of heat through the walls of the housing may be expedited by the provision of external means such as the forced conduction of air or liquid coolants and by the provision of heat radiating fins. The various hydraulic fluid passages may be arranged to obtain any desired synchronous phasing of the pistons 15 and 16. Thus, it will be appreciated that, while the described operation of the cryogenic refrigerator generates the well-known Stirling cycle, it should be readily apparent that other cycles may be generated with equal facility.

Various other modifications and improvements to the above-described preferred embodiment of the invention may be made within the skill of the art. Thus, if desired, the volume displaced by the moving pistons 15 and 16 can be varied by changing the size of the displacers 27 and 18 and corresponding subchambers 12 and 13. Regenerator means 21 need not be carried by expander piston 15 and may be stationarily disposed adjacent piston portion 27. Also the embodiment may be modified by use of multiple stage regenerator means in lieu of the shown regenerator means. Where bellow fatigue is found to be a problem one may extend the walls of the housing and provide additional piston heads to reduce mechanical load thereon. An additional passage may be employed, as indicated by the dotted lines 58, interconnecting the bellow chamber 24 to bellow chamber 56 to shunt a part of the refrigerant therethrough to reduce the mechanical load on bellows 19. Additionally, a plenum volume, as indicated by dotted lines 58a, in communication with such passage 58, may be provided to dampen pressure fluctuations in chambers 24 and 56. Such damping naturally lessens the force contribution of refrigerant gas in bellows chamber 24 to the downward pushing of the piston 15 during the previously described second phase of the refrigeration cycle.

Additionally, drive unit 28 can be readily modified so that hydraulic fluid may be utilized to drive pistons 15 and 16 in both directions if better control of piston motion is deemed desirable. Thus, should spring loads, insufficient refrigerant gas pressure, or other factors, impose strict design limitations to achieve the desired performance, additional piston faces, fluid passages, valve ports, and valve spool openings may be provided to facilitate control of downward motion of pistons 15 and 16. Exemplarily, the fluid required to drive the aforementioned additional piston faces can be controlled by valve spools 31 and 37.

Accordingly, it should be understood that the invention as described is by way of illustration and not limitation and may be modified all within the scope of the appended claims.

What is claimed is:

1. In combination:

a plurality of fluid chargeable reservoirs each having fluid inlet and fluid outlet means;

a plurality of reciprocable elements each having a face positioned within a respective reservoir so that application of pressurized fluid thereto upon fluid charging of the respective reservoir is operative to move the associated element;

valve means for allowing alternate fluid charging and discharging of each of said reservoirs via said fluid inlet and fluid outlet means by a source of pressurized fluid;

biasing means for urging and moving each of said elements upon termination of the application of pressurized fluid to the associated face, said biasing means comprising an envelope defining an enclosed space containing a pressurized medium arranged so that a movable part of said envelope can exert a force upon each of said elements; and

element position sensing means associated with said elements for controlling the operation of said valve means to produce movement of each of said elements in timed relationship.

2. The combination set forth in claim 1 wherein said envelope is partially defined by resilient means connected to each of said elements.

3. The combination of claim 2 wherein each of said resilient means comprises bellows.

4. The combination of claim 1 further comprising structure defining an enclosed space containing compressible refrigerant and also containing heat regenerator means and where said elements are arranged so that movement of said elements is operable to produce refrigeration.

5. The combination of claim 4 further including a cooling load associated with said structure.

6. The combination of claim 1 wherein said valve means comprises movable valve spool means associated with each of said fluid inlet and fluid outlet means.

7. The combination of claim 6 wherein each of said valve spool means comprises a member having fluid conducting means positionable by movement of said valve spool means to allow the aforementioned alternate fluid charging and discharging of each of said reservoirs.

8. The combination of claim 6 wherein said sensing means includes fluid control lines including fluid passages formed in said elements and arranged to operatively provide various fluid flow paths between said valve spool means and an external source of pressurized fluid so that fluid flow through such paths is operative to move and position each respective valve spool means in a predetermined fashion.

9. The combination of claim 8 further including a refrigerating device and a cooling load associated therewith and wherein said fluid control line means are interconnected so as to produce synchronous reciprocation of said elements and wherein said elements comprise part of said device so that reciprocation of said elements is operative to transfer heat away from said cooling load.

10. In combination:

a plurality of fluid chargeable reservoirs each having fluid inlet and fluid outlet means;

a plurality of reciprocable elements each having a respective face positioned within a respective reservoir;

means coupled to said reservoirs for supplying pressurized fluid thereto in order to charge said reservoirs;

valve means for allowing alternate fluid charging and discharging of each reservoir;

said faces each being arranged so that application of pressurized fluid thereto upon fluid charging of the associated reservoir is operative to move the associated element in a first direction;

means for urging and moving each of said elements in a second direction opposite to said first direction upon the termination of the application of pressurized fluid to the face of each element comprising an enclosed space partially defined by respective parts of each element which space contains a pressurized medium which can exert a force upon each of said parts to move the associated element in the second direction; and

element position sensing means associated with said elements for controlling the operation of said valve means to produce reciprocal movement of each of said elements in timed relationship.

11. In a refrigerating system comprising a refrigerating device and a fluid actuator therefor, the combination of: first and second chambers, a passage connecting said chambers, a regenerator associated with said first chamber, and refrigerant gas in said chambers;

third and fourth reservoir chambers each having an inlet and an outlet;

a first piston element arranged for reciprocation in said first and third chambers;

a second piston element arranged for reciprocation in said second and fourth chambers;

said first piston including a first displacer arranged in said first chamber and said second piston including a second displacer arranged in said second chamber for displacing, compressing, and expanding said refrigerant gas, said pistons each being arranged for separate reciprocation in respective forward and reverse directions of reciprocation;

first and second valve means respectively associated with said third and fourth chambers respectively for valve controlling the opening and closing of said inlets and outlets whereby fluid under pressure may

be allowed alternately to enter and exit the respective reservoir chambers to alternately move each element in said forward direction of reciprocation and enable each element to be moved in said reverse direction of reciprocation;

fluid actuator means operatively connected to both said valve means and controlled by said piston elements for effecting sequential opening and closing of said inlets and outlets by said respective valve means in such a way as to time the reciprocation of the respective elements; and

said refrigerant gas in said chambers being means for moving each said element in said opposite direction of reciprocation.

12. In a refrigeration system comprising a refrigerating device and fluid actuator therefor, the combination of:

first and second refrigerator chambers, a passage connecting said chambers, refrigerant gas under compression in said chambers, and a regenerator arranged for storing heat absorbed from said refrigerant gas and for releasing the stored heat to the refrigerant gas;

a third reservoir chamber having an inlet and an outlet and a fourth reservoir chamber having an inlet and an outlet;

a first reciprocable piston element disposed for reciprocation in both said first and third chambers and a second reciprocable piston element disposed for reciprocation in both said second and fourth chambers;

said piston elements each being further arranged to be separately reciprocable in respective forward and reverse directions so that reciprocation of said elements in synchronous, out-of-phase relation is effective to sequentially expand and compress said refrigerant gas while said regenerator by absorbing and releasing heat as aforesaid effects cooling in the vicinity of said first chamber;

supply means connected to each inlet for supplying fluid under pressure to each of said third and fourth chambers;

said piston elements being arranged so that fluid under pressure when supplied to said third and fourth chambers respectively acts to drive each piston element respectively in its forward direction by the exertion of fluid force against each piston element;

vent means connected to each outlet for venting the fluid from each of said third and fourth chambers;

first and second valves each positionable in first and second positions, said first valve in its first position being operative to open said inlet and in its second position being operative to open said outlet of said third chamber, said second valve in its first position being operative to open said inlet and in its second position being operative to open said outlet of said fourth chamber, the positioning of said valves effecting the supply and venting of the fluid to and from each of said reservoir chambers by the opening and closing of said inlets and outlets in a predetermined sequence;

valve actuator means for fluidically positioning each of said valves by sequentially supplying fluid under pressure to each one or the other of respective valve actuator ports arranged on opposite sides of each of the respective valves;

fluid paths means communicating with said valve actuator ports for defining a multiplicity of sequentially selectable fluid paths by which fluid under pressure is conveyable via certain selected fluid paths to the one or the other of said valve actuator ports on the opposite sides of the respective valves to fluidically move either of said valves from either one to the other one of its aforementioned first and second positions;

fluid path defining passages provided in said piston elements each being alignable with said reservoir ports of the aforementioned fluid path means upon reciprocation of said piston elements and being thus alignable during the reciprocation of said piston elements to effect the aforementioned sequential selection of certain ones of the aforesaid multiplicity of fluid paths at certain times during such reciprocation in order to move each of said valves respectively at certain times during such reciprocation from either one to the other one of its aforementioned first and second positions;

each piston element being arranged to further compress said refrigerant gas during movement in its forward direction which refrigerant gas drives each piston element in its reverse direction by the exertion of refrigerant gas compression force against each piston element;

whereby reciprocation of said piston elements are driven as aforesaid by said fluid and pressure forces during the operation of the refrigerating system.

13. In a refrigerating system including a refrigerating device and fluid actuator therefor, the combination comprising:

first and second interconnected refrigerator chambers containing compressible refrigerant under pressure therein;

third and fourth reservoir chambers for fluid each having an inlet and an outlet;

a first piston element extending between said first and third chambers including a first displacer disposed in said first chamber and a first face disposed in said said third chamber;

a second piston element extending between said second and fourth chambers and including a second displacer disposed in said second chamber and a second face disposed in said fourth chamber;

fluid supply means arranged for supplying fluid

under pressure to each of said third and fourth chambers via the inlets thereof, the fluid under pressure being supplied to said third and fourth chambers in order to push the faces of said pistons in order to move the associated piston element in a first direction of reciprocation;

first and second valves respectively pistonable in either of two positions and each being independent of said piston elements, each valve being positionable to either permit entry of fluid into different ones of said reservoir chambers via the inlets thereof or to permit the exhaust of such fluid from such chamber via the outlets thereof;

fluid control means for sequentially positioning said valves and controlled by the said piston elements in order to time the reciprocation of said piston elements, and

said valves and piston elements being arranged so that said refrigerant is operative to produce movement of each piston in a second direction of reciprocation.

References Cited

UNITED STATES PATENTS

321,085	6/1885	Carricaburu	91—193
393,461	11/1888	Donald	91—193
2,274,224	2/1942	Vickers	91—191
2,698,517	1/1955	Wilt	91—193
2,746,241	5/1956	Dros	60—24
3,045,436	7/1962	Gifford	62—6
3,091,092	5/1963	Dros	62—6
3,119,237	1/1964	Gifford	62—6
3,188,821	6/1965	Chellis	62—6
3,367,121	2/1968	Webb	62—6

WILLIAM J. WYE, Primary Examiner

U.S. Cl. X.R.

91—191, 193; 60—24

UNITED STATES PATENT OFFICE
CERTIFICATE OF CORRECTION

Patent No. 3,530,681 Dated September 29, 1970

Inventor(s) AXEL G. DEHNE

It is certified that error appears in the above-identified patent and that said Letters Patent are hereby corrected as shown below:

Column 1, line 16, delete the word "Continuation" and insert instead --Contamination--.

Column 9, line 16, delete "exer-" and insert instead the word --exertion--.

SIGNED AND
SEALED
JUN 18 1971

(SEAL)

Attest:

Edward M. Fletcher, Jr.
Attesting Officer

WILLIAM E. SCHUYLER, JR.
Commissioner of Patents