



(12) **United States Patent**
Mosby

(10) **Patent No.:** **US 11,176,852 B2**
(45) **Date of Patent:** **Nov. 16, 2021**

(54) **MOUNTING BRACKET SYSTEMS FOR SIGNS OR BANNERS**

(71) Applicant: **MS. CARITA SAFETRUCK, INC.**,
Livermore, CA (US)

(72) Inventor: **Gordon E. Mosby**, Tracy, CA (US)

(73) Assignee: **MS. CARITA SAFETRUCK, INC.**,
Livermore, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/987,377**

(22) Filed: **Aug. 6, 2020**

(65) **Prior Publication Data**

US 2021/0158729 A1 May 27, 2021

Related U.S. Application Data

(60) Provisional application No. 62/938,771, filed on Nov. 21, 2019.

(51) **Int. Cl.**

G09F 17/00 (2006.01)
G09F 7/18 (2006.01)
B60R 13/00 (2006.01)
G09F 21/04 (2006.01)

(52) **U.S. Cl.**

CPC **G09F 17/00** (2013.01); **B60R 13/005** (2013.01); **G09F 7/18** (2013.01); **G09F 21/048** (2013.01); **G09F 2007/1865** (2013.01); **G09F 2017/0075** (2013.01)

(58) **Field of Classification Search**

CPC G09F 2017/0075; G09F 17/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,851,608 A * 3/1932 Vitali G09F 21/04
40/591
3,136,289 A * 6/1964 Johnson G09F 17/00
116/28 R
3,454,253 A 7/1969 Lippiatt
3,623,690 A 11/1971 Bargman, Jr.
4,231,606 A 11/1980 Tuerk

(Continued)

FOREIGN PATENT DOCUMENTS

KR 20160112440 A 9/2016

Primary Examiner — David R Dunn


Assistant Examiner — Christopher E Veraa

(74) *Attorney, Agent, or Firm* — Nath, Goldberg & Meyer; Richard C. Litman

(57) **ABSTRACT**

The mounting bracket systems are used in pairs to support a banner on a vehicle. In a first embodiment, the system includes opposing masts having upper and lower extending tabs adapted for attaching a banner between the masts, an annular flange disposed around the mast, and a lower mast end inserted into a bushing attached to a vehicle by U-shaped mounting straps. In a second embodiment, the system includes opposing masts having upper and lower extending tabs adapted for attaching a banner between the masts. The bottom end of each mast is attached to a platform having an elongate U-shaped pocket insert having planar walls extending from the platform opposite the mast. The pocket inserts are adapted for insertion into stake pockets common to trucks and trailers that haul oversize loads. A clevis pin may be inserted through opposing walls of the pocket insert below the stake pocket.

16 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,375,134 A * 3/1983 Sheetz G09F 7/00
116/173
5,076,196 A * 12/1991 Chan B60Q 1/52
116/28 R
5,141,277 A 8/1992 Alexander
5,172,505 A * 12/1992 Borsella G09F 7/20
40/604
5,255,464 A * 10/1993 Marecek G09F 21/048
40/588
5,388,794 A 2/1995 Wolff
5,502,909 A * 4/1996 Rabkin B60Q 1/50
40/591
6,808,098 B1 * 10/2004 Bickett, III B60D 1/36
116/173
7,594,478 B2 9/2009 Karnes et al.
7,841,116 B2 * 11/2010 Whelan G09F 15/0025
40/604
9,010,000 B1 4/2015 Rodriguez
9,914,403 B1 * 3/2018 Richardson B60Q 1/2657
2004/0173724 A1 9/2004 Tolna
2006/0156600 A1 * 7/2006 Barker G09F 21/04
40/591
2009/0133616 A1 * 5/2009 Karnes B62D 33/0207
116/173
2012/0318189 A1 12/2012 Oyoung
2014/0345048 A1 * 11/2014 Mueller A45F 3/24
5/119
2015/0294605 A1 * 10/2015 Conway G09F 17/00
116/173

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

MOUNTING BRACKET SYSTEMS FOR SIGNS OR BANNERS

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of U.S. Provisional Patent Application No. 62/938,771, filed on Nov. 21, 2019.

BACKGROUND

1. Field

The disclosure of the present patent application relates to signs or banners, and particularly to mounting bracket systems for signs or banners.

2. Description of the Related Art

Signs and banners are useful for displaying information, such as advertising, directional, or safety-related information. It is often desirable to display such information, particularly safety information, on vehicles, such as small and large trucks or trailers. This information may relate to the size or weight of the vehicle, such as wide or oversized load information. These signs and banners are often supported by brackets. Many of these brackets are limited to the type of surface to which they can be attached, requiring specific mounting structures. Some of the brackets are designed to be placed in stake pockets found on small and large trucks, as well as some trailers. Unfortunately, stake pockets are often damaged, due to their location adjacent to the outer portions of these vehicles. When the stake pocket is damaged it may be difficult, if not impossible, to insert or remove the bracket into or out of the stake pocket.

Thus, mounting bracket systems for signs or banners solving the aforementioned problems are desired.

SUMMARY

The mounting bracket systems for signs or banners include two embodiments of brackets intended to be used in pairs to support a banner on a vehicle. The first embodiment of the system includes an upper mast having upper and lower extending tabs with orifices for attaching one end of the banner to the mast; an annular flange disposed around the mast; and a lower mast end for attachment to a supporting member. The first embodiment of the system includes a universal mounting bracket. The lower end of the mast is circular and extends into a bushing. The annular flange engages the top face of the bushing. The bushings are secured to a vehicle's (or other) outer vertical surface by U-shaped mounting straps. The second embodiment of the system is intended to be supported within a standard rectangular stake pocket found on heavy trucks and trailers. The lower end of the mast has a three-sided, generally orthogonal stake pocket insert. The bracket is inserted with the open side of the pocket insert facing outward, so that even if the stake pocket is damaged or bent inwardly, the pocket insert can still be received within and removed from the stake pocket. The pocket insert is secured by a bent clevis pin inserted through aligned holes in the stake pocket insert, and a hitch pin clipped to the clevis pin.

These and other features of the present disclosure will become readily apparent upon further review of the following specification and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an environmental, perspective view of a first embodiment of a mounting bracket system for signs or banners.

FIG. 2 is an environmental, perspective view of a second embodiment of a mounting bracket system for signs or banners.

FIG. 3 is a perspective view of the mounting brackets at opposing ends of the sign in the system of FIG. 1.

FIG. 4 is an exploded perspective view of one of the mounting brackets in the system of FIG. 1.

FIG. 5 is a perspective view of the mounting brackets at opposing ends of the sign in the system of FIG. 2.

FIG. 6 is an exploded perspective view of one of the mounting brackets of the system of FIG. 2.

FIG. 7 is a front view of the mounting bracket of FIG. 6.

FIG. 8 is a side view of the mounting bracket of FIG. 6.

FIG. 9 is a bottom view of the mounting bracket of FIG. 6.

FIG. 10 is a perspective view of a locking pin for use with the mounting brackets of the system of FIG. 2.

FIG. 11 is a perspective view of a hitch pin for use with the locking pin of FIG. 10.

Similar reference characters denote corresponding features consistently throughout the attached drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The mounting bracket systems for signs or banners include two embodiments of a system of brackets intended to be used in pairs to support a banner on a vehicle. In a first embodiment, the system **100** utilizes a pair of universal mounting brackets for each banner **B** and is shown in FIG. **1** supporting banners **B** on a side wall **SW** and a bumper **BR** of a truck **T**. These support surfaces are shown as an example, and any support surface, such as a stationary wall, vehicle sidewall or other vertical surfaces, may be used as a support surface. Further, while it is preferable that the surface is as close as possible to vertical for visibility, other surfaces up to and including horizontal surfaces may be desirable in some applications.

The details of the first system **100** are shown in FIGS. **3** and **4**. In FIG. **3**, opposing banner supports are shown to illustrate the cooperating position in which two brackets support a banner or sign there-between. The system **100** includes an upper mast **300** having upper **304** and lower **308** laterally extending tabs. A cap **302** covers the top of mast **300** to protect and seal the mast **300**, particularly when the mast **300** is hollow. The upper extending tab **304** includes a through-hole **306**, while the lower extending tab **308** also includes a through-hole **310**. The through-holes **306**, **310** are used to attach one end of the banner **B** to the mast **300** using string, rope, nylon cord, or other attaching means.

The bottom portion **301** of the mast **300** of the first system **100** includes an annular flange **312** and a lower end **412** for attachment to a supporting member or surface. The lower end **412** of the mast **300** is cylindrical and extends into a central hole **402** in a bushing **400**. The flange **312** is circular and engages a top flange **408** of the bushing **400**. The bushing **400** is secured to a vehicle's (or other) outer vertical surface by a U-shaped strap **314** or bracket that includes two fastener openings **316** in opposite ends **317** of the strap **314**. Fasteners **422** extend through the openings **316** and into the supporting surface, such as the side wall **SW** or the bumper **BR** of a truck **T**, as shown in FIG. **1**. The fasteners **422** may

be sheet metal screws, as shown, or any other fastener suitable for the type of surface to which the U-shaped strap **314** is affixed. The bushing **400** is generally cylindrical, but may include a flat surface **404** that contacts or abuts the supporting surface and a rounded outer surface **406** that nests within the U-shaped strap **314**. The top flange **408** and a lower flange **410** of the bushing **400** maintain the bushing's vertical position within the U-shaped strap **314**.

Alternatively, the strap **314** may not be U-shaped, but may be straight or linear, having a short cylinder or ferrule welded thereto between the fastener openings **316**. The bushing **400** may be a cylinder of low friction material inserted into the ferrule, and having a top annular flange that rests on the top edge of the ferrule, the flange **312** of the mast **300** resting on the top flange of the bushing **400**.

The lower end **412** of the mast **300** further includes a first through-hole **414** and a second through-hole **416** orthogonal to the first through-hole **414**. A locking linchpin **318** includes a cylindrical shaft **420** that is inserted into either the first through-hole **414** or the second through-hole **416** after the lower end **412** of the mast **300** has been inserted into the central hole **402** of the bushing **400** to thereby secure the lower end **412** of the mast **300** inside the bushing **400** using the flange **312** and the locking linchpin **318**. It should be noted that the first through-hole **414** and the second through-hole **416** extend perpendicular to one another to increase the ability to insert the locking linchpin **318** into one hole **414**, **416** or the other, whichever is not blocked by proximate obstacles. The locking linchpin **318** further includes an increased diameter head **418** and a locking pin ring **320** having ends that are attached to the head **418**, thereby providing a spring action that keeps the locking pin ring **320** in a locked position against the cylindrical shaft **420** of the locking linchpin **318**, thereby locking the cylindrical shaft **420** within the respective hole **414**, **416**. The locking pin ring **320** is shown in its spring-biased locked position in the left-hand example of the first system **100** in FIG. **3** and is shown in its spring-tensioned unlocked position in the right-hand example of the first system **100** in FIG. **3**.

In the second embodiment, the system **200** is intended to support a banner **B** within a standard rectangular stake pocket **SP** found on heavy trucks and trailers **TR**, as shown in FIG. **2**. The details of the second embodiment **200** of the brackets are shown in FIGS. **5-9**. As with the first embodiment, the system **200** includes a mast **500** having upper **504** and lower **508** laterally extending tabs. A cap **502** covers the top of mast **500** to protect and seal the mast **500**, particularly when the mast **500** is hollow. The upper tab **504** includes a through-hole **506**, while the lower tab **508** also includes a through-hole **510**. The through-holes **506**, **510** are used to attach one end of the banner **B** to the mast **500** using string, rope, nylon cord, or other attaching means. In FIG. **5**, opposing masts **500** are arranged in an opposite orientation to one another to illustrate their relative positions when supporting opposite ends of a banner or sign therebetween.

The bottom portion **501** of each mast **500** is attached to a three-sided, generally orthogonal stake pocket insert. The insert includes a first generally planar wall **514** and a parallel second generally planar wall **516** that are connected by a third generally planar wall **512**, thereby forming a three-sided insert with an open side that is opposite wall **512**. The insert below the mast **500** is inserted into a stake pocket **SP** with the open side of the insert facing outward, so that if the stake pocket **SP** is damaged or bent inward, the pocket insert can still be received within and removed from the stake pocket **SP**. The tabs **504**, **508** extend from the mast **500** in the opposite direction of the open side of the insert, such that

when the pocket insert is inserted into a stake pocket **SP** with its open side facing outward, a banner **B** can be supported between two systems **200**, as shown in FIG. **2**. The lower end of the first wall **514** includes through-holes **522** and **600**, and the lower end of the second wall **516** includes through-holes **524** and **602**. A locking clevis pin **526** is extended through either through-holes **522** and **524** or through-holes **600** and **602**, depending on the length of the stake pocket insert extending out of the bottom of the stake pocket **SP**.

The details of the locking pin **526** and an associated hitch pin **528** are shown in FIGS. **10** and **11**. The locking clevis pin **526** includes a first end **1000** with a bent lateral section **1002** that is at an obtuse angle to the longitudinal length of the locking pin **526**. The locking pin **526** also has a second end **1004** with a through-hole **1006** defined therein. Once the locking pin **526** has been inserted through the selected through holes **522**, **524** or **600**, **602**, the hitch pin **528** is inserted through the through-hole **1006** and clipped to the second end **1004** of the locking pin **526**. The bent lateral section **1002** and the hitch pin **528** thereby maintain the locking pin **526** within the selected through holes **522**, **524** or **600**, **602**. The hitch pin **528** includes a first end **1100** with an arcuate section **1102** and a second open end **1104**. One side **1106** of the hitch pin **528** is straight, while the second side **1108** includes first **1110**, second **1112** and third bends **1114**. When the straight side **1106** of the hitch pin **528** is inserted through the hole **1006** in the locking pin **526**, the bends **1110**, **1112** and **1114** hold the hitch pin in place on the locking pin, as is known with conventional hitch pins.

The top of the insert includes a generally rectangular, planar platform **518** that is attached to the top of the first **514**, second **516** and third **512** walls and extends beyond the first **514**, second **516** and third **512** walls. When the insert is placed within a stake pocket **SP**, the platform **518** rests on top of the stake pocket **SP** and limits the amount the insert extends into the stake pocket **SP**. The mast **500** is attached to a central position of the platform **518**, e.g., by welding, and extends substantially perpendicularly and upwardly from the platform **518**.

It is to be understood that the mounting bracket systems for signs or banners are not limited to the specific embodiments described above, but encompasses any and all embodiments within the scope of the generic language of the following claims enabled by the embodiments described herein, or otherwise shown in the drawings or described above in terms sufficient to enable one of ordinary skill in the art to make and use the claimed subject matter.

I claim:

1. A mounting bracket system for signs or banners, the system comprising:

a pair of elongated masts, each of the masts having an annular flange, a banner-mounting portion above the flange, and a vehicle mounting portion below the flange;

upper and lower tabs extending laterally from the banner-mounting portion of each of the masts, each of the tabs having an attachment hole defined therein adapted for attaching a sign or banner to the mast;

a pair of mounting straps, each of the straps being adapted for attaching the vehicle mounting portion of the corresponding mast to a vehicle; and

a pair of locking pins, the vehicle mounting portion of each of the masts having at least one transverse bore defined therein below the corresponding mounting strap, the locking pins being removably insertable through the corresponding at least one transverse bore to selectively lock the masts to the vehicle.

5

2. The mounting bracket system as recited in claim 1, wherein:

the at least one transverse bore comprises a first transverse bore and a second transverse bore extending perpendicular to the first transverse bore; and

each of the locking pins are selectively insertable through one of the transverse bores in the corresponding mast, respectively, to selectively lock the masts to the vehicle.

3. The mounting bracket system as recited in claim 1, further comprising a pair of bushings, each of the bushings having a central hole, each of the mounting straps attaching a corresponding one of the bushings to the vehicle, the vehicle mounting portion of the corresponding mast extending through the central hole in the corresponding bushing to mount the corresponding mast to the vehicle.

4. The mounting bracket system as recited in claim 3, wherein each of the bushings includes a top flange, the annular flange of the corresponding mast engaging the top flange of the bushing to limit travel of the vehicle mounting portion of the mast through the central hole in the bushing.

5. The mounting bracket system as recited in claim 4, wherein:

the bushings include lower flanges; and
the top flanges and the lower flanges of the bushings maintain the bushings' vertical position within the mounting straps.

6. The mounting bracket system as recited in claim 5, wherein:

each of the bushings is generally cylindrical, having a flat vehicle-facing surface and a rounded outer surface;
the mounting straps are U-shaped;
the flat vehicle-facing surface is adapted for contacting a surface of the vehicle; and
the rounded outer surface nests within the corresponding U-shaped mounting strap.

7. The mounting bracket system as recited in claim 1, wherein:

the elongated masts are hollow and include tops; and
the mounting bracket system further comprises a pair of caps that cover the tops of masts to seal the masts.

8. The mounting bracket system for signs or banners as recited in claim 1, wherein each of the locking pins comprises:

a cylindrical shaft having a proximal end and a distal end;
a head disposed on the proximal end of the shaft, the head having a greater diameter than the shaft and a greater diameter than the at least one transverse bore defined in each of the masts; and

a locking pin ring extending through the head of the shaft, the locking pin ring being pivotal between a locked position against the shaft, limiting movement of the locking pin through the at least one transverse bore, and an unlocked position permitting free movement of the shaft through the at least one transverse bore.

9. The mounting bracket system as recited in claim 1, wherein each of the mounting straps has fastener openings defined in opposite ends of the mounting strap adapted for receiving a fastener for attaching the mounting strap to the vehicle.

10. A mounting bracket system for signs or banners, the system comprising:

a pair of elongated masts, each of the masts having a banner-mounting portion and a bottom end;
upper and lower tabs extending laterally from the banner-mounting portion of each of the masts, each of the tabs

6

having an attachment hole defined therein adapted for attaching a sign or banner to the mast;

a pair of pocket inserts, each of the masts having a corresponding one of the pocket inserts attached to the bottom end of the mast, each of the pocket inserts having:

a pair of parallel side walls, the side walls having at least one aligned pair of apertures defined therein;

a back wall extending between the parallel side walls, the side walls and the back wall defining a U-shaped insert having planar walls and an open side; and

a platform mounted on top of the U-shaped insert, the bottom end of the mast being attached to the platform, the U-shaped insert of each of the pocket inserts being adapted for insertion into a stake pocket; and

a clevis pin removably inserted through the at least one aligned pair of apertures in the side walls of each of the U-shaped inserts below the stake pocket.

11. The mounting bracket system for signs or banners as recited in claim 10, wherein the at least one aligned pair of apertures comprises two aligned pairs of apertures.

12. The mounting bracket system as recited in claim 10, wherein the clevis pin is elongated, having a first end defining an elbow and a second end having a transverse bore defined therein, the system further comprising a hitch pin having a straight leg and a clamping leg having a plurality of undulating bends, the clamping leg extending parallel to and being resiliently biased against the straight leg so that when the straight leg is inserted through the transverse bore, the clamping leg bears against the clevis pin to secure the clevis pin to the U-shaped insert below the stake pocket, the elbow in the clevis pin preventing the clevis pin from sliding through the aligned holes in the U-shaped insert.

13. The mounting bracket system as recited in claim 10, wherein the platform extends beyond the pair of parallel side walls and the back wall, forming a stop to thereby limit the amount the insert extends into the stake pocket.

14. The mounting bracket system as recited in claim 10, wherein the upper and lower tabs extend in a direction opposite to the open side of the U-shaped insert.

15. The mounting bracket system as recited in claim 10, wherein each of the elongated masts is hollow and has an open top end, the system further comprising a pair of caps covering the open top end of each of the masts, respectively, to seal the masts.

16. A mounting bracket system for signs or banners, the system comprising:

a pair of hollow elongated masts, each of the masts having a banner-mounting portion, a bottom end, and a top end;

upper and lower tabs extending laterally from the banner-mounting portion of each of the masts, each of the tabs having an attachment hole defined therein adapted for attaching a sign or banner to the mast;

a pair of pocket inserts, each of the masts having a corresponding one of the pocket inserts attached to the bottom end of the mast, each of the pocket inserts having:

a pair of parallel side walls, the side walls having two aligned pairs of apertures defined therein;

a back wall extending between the parallel side walls, the side walls and the back wall defining a U-shaped insert having planar walls and an open side, the upper and lower tabs extending in a direction opposite to the open side of the U-shaped insert; and

- a platform mounted on top of the U-shaped insert, the bottom end of the corresponding mast being attached to the platform, the U-shaped insert being adapted for insertion into a stake pocket, the platform extending beyond the pair of parallel side walls and the back wall, forming a stop to thereby limit the amount the insert extends into the stake pocket; 5
- a clevis pin removably inserted through at least one of the aligned pair of apertures in the side walls of each of the U-shaped inserts, respectively, the at least one aligned pair of apertures being below the stake pocket, the clevis pin being elongated, having a first end defining an elbow and a second end having a transverse bore defined therein; 10
- a hitch pin having a straight leg and a clamping leg having a plurality of undulating bends, the clamping leg extending parallel to and being resiliently biased against the straight leg so that when the straight leg is inserted through the transverse bore, the clamping leg bears against the clevis pin to secure the clevis pin to the U-shaped insert below the stake pocket, the elbow in the clevis pin preventing the clevis pin from sliding through the aligned holes in the U-shaped insert; and 15 20
- a pair of caps covering the top ends of the masts, respectively, to seal the masts. 25

* * * * *