



US 20210181446A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2021/0181446 A1**

**VAN BAELEN et al.**

(43) **Pub. Date: Jun. 17, 2021**

(54) **FRAME ASSEMBLIES FOR OPTICAL FIBER DISTRIBUTION ELEMENTS**

(52) **U.S. Cl.**  
CPC ..... **G02B 6/4452** (2013.01); **G02B 6/4471** (2013.01); **G02B 6/3897** (2013.01)

(71) Applicant: **COMMSCOPE CONNECTIVITY BELGIUM BVBA**, Kessel-Lo (BE)

(57) **ABSTRACT**

(72) Inventors: **David Jan Irma VAN BAELEN**, Winksele (BE); **Willem Lea Marcel DE VIS**, Merchtem (BE); **Wouter VRANKEN**, Nieuwrode (BE); **Heidi BLEUS**, Genk (BE); **Peter CLAES**, Berlaar (BE); **Geert Antoon PARTON**, Lubbeek (BE); **Karel VANWINKEL**, Tielt-Winge (BE); **Diederik HOUBEN**, Santa Ana, CA (US)

A telecommunications frame assembly includes a frame for housing a first set of fiber optic distribution devices in a vertically stacked arrangement on a right side of the frame and a second set of fiber optic distribution devices in a vertically stacked arrangement on a left side of the frame, wherein the frame defines top and bottom openings adjacent the outer edges of the frame at each of the right side and the left side for selectively leading cables to or from the fiber optic distribution devices to be mounted on the frame, the frame further defining a central vertical trough extending from a central top opening defined by the frame, wherein radius limiters are provided in vertically stacked arrangements at each of the right side and the left side of the frame for selectively guiding cabling between the first set and the second set of fiber optic distribution devices, wherein the radius limiters allow cabling to pass through the central trough between the right and left sides of the frame and/or into the central trough from either of the right and left sides of the frame for selective routing from or to the central top opening, the frame further defining a bottom trough that extends horizontally between the right and left sides of the frame, wherein each of the bottom openings adjacent the outer edges of the frame at the right and left sides communicate with the bottom trough and wherein the radius limiters at each of the right side and the left side of the frame also allow cabling to pass from the fiber optic distribution devices to the bottom trough.

(21) Appl. No.: **17/186,710**

(22) Filed: **Feb. 26, 2021**


**Related U.S. Application Data**

(63) Continuation of application No. PCT/EP2019/073253, filed on Aug. 30, 2019.

(60) Provisional application No. 62/725,877, filed on Aug. 31, 2018, provisional application No. 62/855,102, filed on May 31, 2019.

**Publication Classification**

(51) **Int. Cl.**  
**G02B 6/44** (2006.01)  
**G02B 6/38** (2006.01)






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12








FIG. 13






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26






FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34






FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44






FIG. 45



FIG. 46



FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51



FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58






FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67






FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75






FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81






FIG. 83






FIG. 84




FIG. 85




FIG. 86




FIG. 87







FIG. 89






FIG. 92








FIG. 93










FIG. 98




FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 103




FIG. 104






FIG. 105




FIG. 106




FIG. 107




FIG. 108

FIG. 109





FIG. 110






FIG. 111




FIG. 112




FIG. 113




FIG. 114




FIG. 115




FIG. 116




FIG. 117







FIG. 118

FIG. 119






FIG. 120




FIG. 121




FIG. 123




FIG. 122




FIG. 124




FIG. 125




FIG. 127




FIG. 128




FIG. 126






FIG. 129




FIG. 130

FIG. 131





FIG. 132






FIG. 133




FIG. 135

FIG. 134




FIG. 136




FIG. 137




FIG. 139




FIG. 138




FIG. 140




FIG. 141




FIG. 142






FIG. 143




FIG. 144




FIG. 145




FIG. 146




FIG. 148




FIG. 147




FIG. 149




FIG. 151

FIG. 150




FIG. 153




FIG. 154




FIG. 152




FIG. 155




FIG. 156




FIG. 157




FIG. 158




FIG. 159






FIG. 162




FIG. 161




FIG. 160




FIG. 163




FIG. 164




FIG. 165




FIG. 166




FIG. 167




FIG. 168




FIG. 169




FIG. 170




FIG. 171




FIG. 172




FIG. 173




FIG. 174






FIG. 175








FIG. 178




FIG. 179




FIG. 180




FIG. 181




FIG. 182




FIG. 183

## FRAME ASSEMBLIES FOR OPTICAL FIBER DISTRIBUTION ELEMENTS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a Continuation of PCT/EP2019/073253, filed on Aug. 30, 2019, which claims the benefit of U.S. Patent Application Ser. No. 62/725,877, filed on Aug. 31, 2018, and claims the benefit of U.S. Patent Application Ser. No. 62/855,102, filed on May 31, 2019, the disclosures of which are incorporated herein by reference in their entireties. To the extent appropriate, a claim of priority is made to each of the above disclosed applications.

### TECHNICAL FIELD

[0002] The present invention relates to optical fiber distribution systems, including frame assemblies and elements which populate such frame assemblies, and including components for managing and routing optical fiber cables to and from the mounted elements.

### BACKGROUND

[0003] Optical fiber distribution systems include fiber terminations and other equipment which is typically frame or rack mounted. Various concerns exist for the optical fiber distribution systems, including density, ease of use, and cable management. There is a continuing need for improvements in the optical fiber distribution area.

### SUMMARY

[0004] Certain implementations of a system in accordance with the examples of the disclosure include telecommunications frame assemblies where the frames of the assemblies support a plurality of optical fiber distribution elements, or other equipment and the cable routing associated with such equipment.

[0005] In one aspect, the disclosure is directed to a telecommunications frame assembly comprising a frame for housing a first set of fiber optic distribution devices in a vertically stacked arrangement on a right side of the frame and a second set of fiber optic distribution devices in a vertically stacked arrangement on a left side of the frame, wherein the frame defines top and bottom openings adjacent the outer edges of the frame at each of the right side and the left side for selectively leading cables to or from the fiber optic distribution devices to be mounted on the frame, the frame further defining a central vertical trough extending from a central top opening defined by the frame, wherein radius limiters are provided in vertically stacked arrangements at each of the right side and the left side of the frame for selectively guiding cabling between the first set and the second set of fiber optic distribution devices, wherein the radius limiters allow cabling to pass through the central trough between the right and left sides of the frame and/or into the central trough from either of the right and left sides of the frame for selective routing from or to the central top opening, the frame further defining a bottom trough that extends horizontally between the right and left sides of the frame, wherein each of the bottom openings adjacent the outer edges of the frame at the right and left sides communicate with the bottom trough and wherein the radius limiters at each of the right side and the left side of the frame

also allow cabling to pass from the fiber optic distribution devices to the bottom trough.

[0006] In another aspect, the disclosure is directed to a telecommunications frame assembly comprising a frame for housing a set of fiber optic distribution devices in a vertically stacked arrangement along a central portion of the frame, wherein the frame defines a vertical trough adjacent an outer edge at a right side of the devices and a vertical trough adjacent an outer edge at a left side of the devices, wherein the frame defines top openings adjacent the outer edges of the frame at each of the right side and the left side of the frame communicating with the vertical troughs for selectively leading cables to or from the fiber optic distribution devices to be mounted at central portion of the frame, wherein at least one of the right side or the left side includes radius limiters provided in a vertically stacked arrangement within the vertical trough for leading cabling between the devices and the top openings, wherein at least one of the right side or the left side is also configured for mounting fiber fan-out fixation assemblies including fiber fan-out holders and brackets for removably mounting the fiber fan-out holders within the vertical trough.

[0007] In another aspect, the disclosure is directed to a mounting system for latching a cable management structure to a telecommunications fixture so as to prevent relative sliding between the cable management structure and the telecommunications fixture and relative separation between the cable management structure and the telecommunications fixture that is in a direction generally perpendicular to the direction of the relative sliding. The mounting system comprises a first locking feature in the form of first and second hook-like members separated apart, each defining a vertical slide portion and a vertical retention portion having a larger profile than the slide portion, the first locking feature also including an elastically flexible latch positioned between the first and second hook-like members and a second locking feature in the form of first and second slots configured to align with the first and second hook-like members of the first locking feature, wherein each of the first and second slots defines a receiver portion and a retention portion, wherein the receiver portion is sized to accommodate the larger retention portion of the hook-like member and the retention portion is sized to accommodate the slide portion but not the larger retention portion of the hook-like member, the second locking features also defining a latch opening configured to receive the flexible latch of the first locking feature for preventing relative sliding between the cable management structure and the telecommunications fixture once the vertical slide portion of each hook-like member has been slid through the retention portion of each slot and the retention portion of each hook-like member is out of alignment with the receiver portion of each slot.

[0008] In another aspect, the disclosure is directed to a cable management structure comprising a fixation portion including a locking feature in the form of first and second hook-like members separated apart, each defining a vertical slide portion and a vertical retention portion having a larger profile than the slide portion, the locking feature also including an elastically flexible latch positioned between the first and second hook-like members and a bend radius protection portion extending from the fixation portion, the bend radius protection portion defining a curved profile.

[0009] In another aspect, the disclosure is directed to telecommunications device fixation assembly comprising a

bracket configured to be mounted to a telecommunications fixture, the bracket defining at least one planar wall, and a device holder configured to be removably mounted to the bracket, the device holder defining a device holding portion and a fixation portion, wherein the fixation portion defines at least one pocket configured to receive an edge of the planar wall of the bracket, the fixation portion further including an elastically flexible latch configured to snap fit to a portion of the planar wall of the bracket to fix the device holder to the bracket.

**[0010]** In another aspect, the disclosure is directed to a telecommunications device holder for fixedly mounting a telecommunications device to a fixture, the device holder comprising a device holding portion and a fixation portion, wherein the fixation portion defines at least one pocket configured to receive an edge of a wall, the fixation portion further including an elastically flexible latch configured to abut against another edge of the wall that is spaced apart from the edge of the wall received by the at least one pocket.

**[0011]** In another aspect, the disclosure is directed to a cable fixation structure for fixing at least a portion of a fiber optic cable to a telecommunications fixture against strain relief, the structure comprising a cable bracket portion and a base portion, wherein the cable bracket portion is configured for fixing the at least a portion of the fiber optic cable and the base is configured for routing fibers extending from the fiber optic cable, wherein the cable bracket portion is provided at an acute angle with respect to a vertical plane passing through a longitudinal axis defined by the base portion.

**[0012]** In another aspect, the disclosure is directed to cable fixation structure for fixing at least a portion of a fiber optic cable to a telecommunications fixture against strain relief, the structure comprising a base portion defining a series of pivot pins provided in a stepped configuration and a series of latch pins provided in a stepped configuration spaced apart from and corresponding to the pivot pins and a cable clamp portion pivotally mounted on a selected one of the pivot pins and configured to be latched on a corresponding one of the latch pins to clamp a cable against the base, wherein the cable clamp portion is removable and remountable on a selected pivot pin and can be latched on a corresponding latch pin depending upon the size and or the number of cables being fixed by the cable fixation structure.

**[0013]** In another aspect, the disclosure is directed to a cable management structure comprising a base portion for removable mounting on a telecommunications fixture, the base portion defining an upper guide portion and a lower guide portion separated by a cable channel, wherein a transverse slit defined between the upper and lower guide portions communicates with the cable channel for insertion of cables into the channel and a flexible portion that is elastically flexible and is biased to cover at least a portion of the slit for retaining cables within the channel.

**[0014]** In another aspect, the disclosure is directed to a double-hinging door for a telecommunications frame, the door comprising a main portion for providing closure for the telecommunications frame, the main portion defining a bottom edge of the door, the door defining a right side and a left side, a hinge rod at both the right side and the left side of door configured for insertion into hinge openings defined by door mounts of the telecommunications frame for allowing the door to be selectively pivotable in either a clockwise or a counterclockwise direction for opening, a handle on

each of the right side and the left side associated with a respective hinge rod on the right side and the left side for moving the hinge rod vertically upwardly out of a respective hinge opening when the handle is brought from a closed position to an open position, and a height-adjustable spacer provided on the hinge rod at each of the right and left sides of the door, each spacer configured to protrude from the bottom edge of the main portion of the door and be positioned between the bottom edge and a respective door mount when the handle associated with that spacer is in the closed position.

#### DESCRIPTION OF THE DRAWINGS

**[0015]** Non-limiting and non-exhaustive embodiments are described with reference to the following figures, which are not necessarily drawn to scale, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

**[0016]** FIG. 1 is a front view of one embodiment of a telecommunications frame assembly having features that are examples of inventive aspects in accordance with the principles of the present disclosure, the frame assembly provided in the form of a cross-connect patching system;

**[0017]** FIG. 2 is a front view of another embodiment of a telecommunications frame assembly having features that are examples of inventive aspects in accordance with the principles of the present disclosure, the frame assembly provided in the form of an inter-connect system;

**[0018]** FIG. 3 is a front view of an overlength bay that can be used between two of the frame assemblies shown in FIG. 1 for guiding patch cabling between two of such frame assemblies;

**[0019]** FIG. 4 is a front perspective view of the frame assembly of FIG. 1, shown populated with optical distribution elements;

**[0020]** FIG. 5 illustrates the right and left frames forming the cross-connect frame assembly of FIG. 1 separated from each other, where the frames of the cross-connect assembly of FIG. 5 are also shown as using a different type of overlength drums in the form of slide drums;

**[0021]** FIG. 6 illustrates an example cable patch routing between the right and left frames of the cross-connect frame assembly of FIG. 1;

**[0022]** FIG. 7 schematically illustrates the cable patch routing physically shown in FIG. 6;

**[0023]** FIG. 8 illustrates a plurality of the cross-connect frame assemblies of FIG. 1 provided in a side-to-side stacked arrangement;

**[0024]** FIG. 9 is an example of a fixed-length fiber optic patch cable that can be patched between various elements on respective right and left frames of the cross-connect assembly of FIG. 1

**[0025]** FIGS. 10-13 illustrate the types of cables on the fixed side of the elements that can be paired with the jumpers that are provided on the flexible side of the elements in a given frame of the cross-connect assembly;

**[0026]** FIG. 14 is one example of the cable routing that can be used on the fixed side of a left frame of the cross-connect assembly, where the cables are directed from a top of the frame toward the elements;

**[0027]** FIG. 15 is another example of the cable routing that can be used on the fixed side of a left frame of the cross-connect assembly, where the cables are directed from a bottom of the frame toward the elements;

[0028] FIG. 16 is another example of the cable routing that can be used on the fixed side of a left frame of the cross-connect assembly, where the cables are directed from both the top and the bottom of the frame toward the elements, the schematic illustrating the split point for the up or down routing of the cables;

[0029] FIG. 17 is used to illustrate one example cable routing that can be used on the fixed side of a right frame of the cross-connect assembly, where the cables are directed toward a bottom of the frame from the elements;

[0030] FIG. 18 is another example of the cable routing that can be used on the fixed side of a left frame of the cross-connect assembly, where the cables are directed from a top of the frame toward the elements and where the cables are trunk cables that are split out using fan-outs mounted to the frame;

[0031] FIG. 19 illustrates a similar routing to that shown in FIG. 18 for trunk cables, however on the fixed side of a right frame of the cross-connect assembly;

[0032] FIG. 20 illustrates an example cable routing that can be used on the fixed side of a left frame of the cross-connect assembly, where the cables are a combination of trunk cables that are split out using fan-outs mounted to the frame, directed from a top of the frame toward the elements and jumper cables directed to the elements from a bottom of the frame;

[0033] FIG. 21 illustrates an example cable routing for combination cabling similar to that shown in FIG. 20, where both the trunk cables and jumper cables are directed from a top of the frame toward the elements;

[0034] FIG. 22 illustrates an example cable routing for combination cabling similar to that shown in FIG. 21, where the jumper cables are directed to an upper set of distribution elements and trunk cables are directed to a lower set of distribution elements;

[0035] FIG. 23 illustrates an example cable routing for the fixed side of a left frame of the cross-connect assembly where a plurality of elements on different levels receive fibers to be spliced from a single OSP cable fixed at the side of one of the elements in a grouping;

[0036] FIG. 24 illustrates an example cable routing similar to that shown in FIG. 23 for the fixed side of the right frame of the cross-connect assembly;

[0037] FIG. 25 illustrates the mounting of a group of elements where fibers to be spliced from a single OSP cable fixed at the side of the one of the elements is routed to all of the elements in the group, where the length of cabling is provided with enough slack to accommodate the mounting;

[0038] FIG. 26 illustrates the positioning of the fan-outs that can be mounted on the left frame of the cross-connect assembly for the trunk cables coming from a top of the frame;

[0039] FIG. 27 illustrates a perspective view of the left frame of the cross-connect assembly with an example fan-out fixation assembly being used to break out trunk cables;

[0040] FIG. 28 illustrates a schematic showing the use of a combination of OSP splice cables directed to from the bottom of the cross-connect assembly toward the lower elements and trunk cables with fan-outs directed from the top of the cross-connect assembly toward the upper elements;

[0041] FIG. 29 illustrates a group of elements designated for splicing fibers from an OSP cable to other groups of elements within a frame at the fixed side of the cross-connect assembly;

[0042] FIG. 30 illustrates a top perspective view of an example dedicated spliced element from the group shown in FIG. 29;

[0043] FIG. 31 illustrates the central region of the cross-connect frame assembly where bundle collectors are used to guide cabling between the right and left frames of the cross-connect assembly and toward the bottom through of the cross-connect assembly;

[0044] FIG. 32 illustrates the overlength drums used adjacent the central region of the cross-connect frame assembly for guiding cabling from the flexible sides of the frames toward the bundle collectors shown in FIG. 31;

[0045] FIG. 33 illustrates the use of the overlength bay shown in FIG. 3 between two of the cross-connect frame assemblies for guiding patch cabling between two of such frame assemblies;

[0046] FIG. 34 is a perspective view of the overlength bay of FIG. 33 shown in isolation;

[0047] FIG. 35 illustrates the overlength bay of FIG. 34 in an unassembled configuration;

[0048] FIG. 36 illustrates the cross-connect assembly of FIG. 1 with pivot doors mounted thereon;

[0049] FIG. 37 illustrates one of the doors of FIG. 36 in isolation;

[0050] FIG. 38 illustrates two cross-connect assemblies stacked in a side-by-side configuration with pivot doors mounted thereon;

[0051] FIG. 39 is a rear perspective of the door of FIG. 37 illustrating the flat-rod door latch system;

[0052] FIG. 40 illustrates a close-up view of the spring-loaded rods of the door latch system of FIG. 39, each of which is activated by the corresponding door handle;

[0053] FIG. 41 illustrates one of the door mounts that are configured to be mounted on various locations on the frame assemblies of the present disclosure for receiving the pivot doors for the assemblies;

[0054] FIG. 42 illustrates another version of a rod receiver for mounting on the door mounts of the frame assemblies;

[0055] FIG. 43 is a left perspective view of the inter-connect frame assembly of FIG. 2;

[0056] FIG. 44 is a right perspective view of the inter-connect frame assembly of FIG. 43;

[0057] FIG. 45 illustrates an example routing for cabling on the equipment side of the inter-connect frame where a combination of hook drums and overlength drums are used to guide cabling from the elements toward the top of the frame;

[0058] FIGS. 46-52 illustrate the types of cables on the OSP side of the elements that can be paired with the types of cables on the equipment side of the elements that are provided on the inter-connect frame;

[0059] FIG. 53 schematically illustrates one example of the cable routing that can be used on the inter-connect frame for trunk cables on the OSP side and trunk cables on the equipment side;

[0060] FIG. 54 physically illustrates an example cable routing on the equipment side of the inter-connect assembly;

[0061] FIG. 55 illustrates the inter-connect assembly of FIG. 2 with pivot doors mounted thereon;



[0062] FIG. 56 illustrates an example cable routing on the cross-connect assembly of FIG. 1 using a combination of different types of overlength drums at the center of the assembly including fixed drums and slide drums;

[0063] FIG. 57 illustrates the left frame of the cross-connect frame assembly in an empty configuration without any of the mounted distribution elements, ready to be disassembled for packaging;

[0064] FIG. 58 illustrates the right frame of the cross-connect frame assembly in an empty configuration without any of the mounted distribution elements, ready to be disassembled for packaging;

[0065] FIG. 59 illustrates the frame of the inter-connect assembly in an empty configuration without any of the mounted distribution elements, ready to be disassembled for packaging;

[0066] FIG. 60 illustrates another perspective view of the overlength bay, ready to be disassembled for packaging;

[0067] FIG. 61 illustrates another perspective view of the left frame of the cross-connect frame assembly, ready to be disassembled for packaging;

[0068] FIG. 62 illustrates the left frame of FIG. 61 in a disassembled configuration, ready for packaging;

[0069] FIG. 63 illustrates parts of the disassembled frame of FIG. 62 organized for placement into a packaging box;

[0070] FIG. 64 illustrates the packaging box for use in transporting the frame of FIGS. 61-63;

[0071] FIG. 65 is an alternative of a cross-connect frame assembly having features that are similar to that shown in FIG. 1, where the right and left frames utilize separating fins for forced routing between the flexible sides of the frames;

[0072] FIG. 66 illustrates an example cable routing utilizing the separating fins of the cross-connect frame assembly of FIG. 65;

[0073] FIG. 67 illustrates the separating fins of FIGS. 65-66 in closer detail;

[0074] FIG. 68 illustrates push-through type cable management structures that can be used with the separating fins of the cross-connect frame assembly of FIGS. 65-67 for keeping cable bundles organized;

[0075] FIG. 69 illustrates a color-coding concept that can be used to keep track of the cable routings between the flexible sides of the frames on another example cross-connect system;

[0076] FIG. 70 illustrates a front perspective view of an example cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0077] FIG. 71 illustrates a rear perspective view of the cable management structure of FIG. 70;

[0078] FIG. 72 illustrates the cable management structure of FIG. 70 mounted on a wall defined by the various telecommunications frames of FIGS. 1-69;

[0079] FIG. 73 illustrates a rear side of the wall of FIG. 72 illustrating the mounting interface between the wall and the cable management structure;

[0080] FIG. 74 illustrates a front perspective view of the fixation portion of the cable management structure of FIG. 70;

[0081] FIG. 75 illustrates a side view of the fixation portion of the cable management structure of FIG. 70;

[0082] FIG. 76 is a bottom view of the fixation portion of the cable management structure of FIG. 70;

[0083] FIG. 77 illustrates an example of the cable management structure of FIG. 70 with a different fixation portion;

[0084] FIG. 78 illustrates the cable management structure of FIGS. 70-76 from a bottom perspective view;

[0085] FIG. 79 illustrates a plurality of cable management structures similar to those shown in FIGS. 70-77, wherein the flanges thereof include bent portions forming staggered openings for facilitating insertion of cables when the drums are provided in a vertically stacked arrangement;

[0086] FIG. 80 illustrates a plurality of another set of cable management structures similar to those shown in FIGS. 70-77, wherein the flanges thereof include angled profiles to form angled openings for facilitating insertion of cables when the drums are provided in a vertically stacked arrangement;

[0087] FIG. 81 illustrates another example of a cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0088] FIG. 82 illustrates a front perspective view of another example of a cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0089] FIG. 83 illustrates the cable management structure of FIG. 82 from a rear perspective;

[0090] FIG. 84 illustrates two of the cable management structures of FIG. 82 snapped-together in a side-by-side configuration;

[0091] FIG. 85 illustrates the two cable management structures of FIG. 82 in a separated configuration along with a radius extender;

[0092] FIG. 86 illustrates the cable management structure of FIG. 82 with an alternative version of a radius extender;

[0093] FIG. 87 illustrates a number of the cable management structures and radius extenders mounted on a part of the telecommunications frame of FIGS. 1-69;

[0094] FIG. 88 illustrates another example of a cable management structure in the form of a slide drum that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0095] FIG. 89 illustrates the movable part of the slide drum of FIG. 88 in an extended position;

[0096] FIG. 90 is a rear perspective view of the slide drum of FIG. 88;

[0097] FIG. 91 illustrates the movable part of the slide drum removed from the fixed portion of the slide drum;

[0098] FIG. 92 is another perspective view of the movable part of the slide drum removed from the fixed portion of the slide drum;

[0099] FIG. 93 illustrates a number of the slide drums of FIG. 88 mounted together in a vertically stacked configuration;

[0100] FIG. 94 is a top perspective view of the slide drum of FIG. 88;

[0101] FIG. 95 is a bottom perspective view of the slide drum of FIG. 88;

[0102] FIG. 96 illustrates another example of a cable management structure in the form of a slide drum that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69, wherein the fixed part is provided with an angle to a vertical wall such that the movable part moves both outwardly and upwardly with

respect to the fixed part of the slide drum, the movable part shown in an extended position;

[0103] FIG. 97 illustrates a side view of the cable management structure of FIG. 96 with the movable part in a retracted position with respect to the fixed part;

[0104] FIG. 98 illustrates the fixed part of the slide drum of FIG. 96 in isolation;

[0105] FIG. 99 illustrates the movable part of the slide drum of FIG. 96 in isolation;

[0106] FIG. 100 is a front perspective view of the cable management structure of FIG. 96 with the movable part in a retracted position with respect to the fixed part;

[0107] FIG. 101 illustrates one of the optical distribution elements that can be mounted on the various telecommunications frames shown in FIGS. 1-69 with an example cable management structure having features that are examples of inventive aspects in accordance with the present disclosure mounted to a side thereof, wherein the cable management structure is configured for use on either side of one of the optical distribution elements for directing cabling away from or toward the optical distribution element;

[0108] FIG. 102 illustrates the cable management structure of FIG. 101 exploded off the optical distribution element;

[0109] FIG. 103 illustrates a plurality of the cable management structures shown in FIG. 101 shown mounted to sides of optical distribution elements in a vertically stacked arrangement;

[0110] FIG. 104 illustrates a side perspective view of the cable management structure of FIG. 101 in isolation;

[0111] FIG. 105 illustrates a rear perspective view of the cable management structure of FIG. 101;

[0112] FIG. 106 illustrates the cable management structure of FIG. 101 in an exploded configuration to show the removable parts thereof;

[0113] FIG. 107 is a side view of the cable management structure of FIG. 101;

[0114] FIG. 108 is a rear view of the cable management structure of FIG. 101;

[0115] FIG. 109 is an example of another embodiment of a cable management structure having features that are similar to that shown in FIGS. 101-108;

[0116] FIG. 110 is a rear view of the cable management structure of FIG. 109;

[0117] FIG. 111 is an example of another embodiment of a cable management structure having features that are similar to that shown in FIGS. 101-110;

[0118] FIG. 112 is a bottom perspective view of the cable management structure of FIG. 111;

[0119] FIG. 113 is an example of another embodiment of a cable management structure that can be mounted to the sides of the optical distribution elements shown in FIGS. 101-102;

[0120] FIG. 114 is a front perspective view of another embodiment of a cable management structure that can be mounted to the sides of the optical distribution elements shown in FIGS. 101-102;

[0121] FIG. 115 is a side perspective view of another embodiment of a cable management structure that can be mounted to the sides of the optical distribution elements shown in FIGS. 101-102;

[0122] FIG. 116 is a rear perspective view of the cable management structure of FIG. 115;

[0123] FIG. 117 is an example of another embodiment of a cable management structure that can be mounted to the sides of the optical distribution elements shown in FIGS. 101-102;

[0124] FIG. 118 is an example of a cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0125] FIG. 119 is an example of another cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0126] FIG. 120 is an example of yet another version of a cable management structure that can be mounted to on certain locations of the various telecommunications frames shown in FIGS. 1-69;

[0127] FIG. 121 is an example of a strength member fixation structure having features that are examples of inventive aspects in accordance with the present disclosure;

[0128] FIG. 122 illustrates the cable bracket portion of the fixation structure of FIG. 121 in an exploded configuration;

[0129] FIG. 123 illustrates the base portion of the fixation structure of FIG. 121 in an exploded configuration;

[0130] FIG. 124 schematically illustrates the mounting of the cable bracket to the base of the fixation structure of FIG. 121;

[0131] FIG. 125 illustrates the cable bracket and the base of FIG. 124 in a fully assembled configuration;

[0132] FIG. 126 illustrates a side perspective view of the fixation structure of FIG. 121 with the cable bracket in an upwardly angled orientation;

[0133] FIG. 127 illustrates one example of a tube holder that can be slidably received by the base of the fixation structure of FIG. 121;

[0134] FIG. 128 illustrates another example of a tube holder that can be slidably received by the base of the fixation structure of FIG. 121;

[0135] FIG. 129 is an example of another embodiment of a strength member fixation structure having features that are similar to that shown in FIGS. 121-128;

[0136] FIG. 130 illustrates a plurality of the strength member fixation structure shown in FIG. 129 shown mounted to sides of optical distribution elements in a vertically stacked arrangement;

[0137] FIG. 131 illustrates one of the optical distribution elements in isolation with the fixation structure of FIG. 130 mounted thereon with the cable bracket in an upwardly angled orientation;

[0138] FIG. 132 illustrates an optical distribution element in isolation with the fixation structure of FIG. 130 mounted thereon with the cable bracket in a downwardly angled orientation;

[0139] FIG. 133 illustrates another stack of optical distribution elements similar to that shown in FIGS. 130-132 with a plurality of the strength member fixation structures of FIG. 129 mounted to the sides thereof;

[0140] FIG. 134 schematically illustrates a stack of optical distribution elements similar to that shown in FIG. 133 where the strength member fixation structures are used to route fibers to respective elements from cabling mounted at each of the elements;

[0141] FIG. 135 schematically illustrates a stack of optical distribution elements similar to that shown in FIG. 134 but

using a single strength member fixation structure to route fibers from a single cable to different elements within the stack;

[0142] FIG. 136 schematically illustrates the use of the strength member fixation structures of FIG. 129 for routing of a plurality of fiber carrying tubes of a single cable to different optical distribution elements in a stack;

[0143] FIG. 137 schematically illustrates the use of the strength member fixation structures of FIG. 129 for routing the optical fibers of a single cable to different optical distribution elements in a stack;

[0144] FIG. 138 is an example of another embodiment of a strength member fixation structure having features that are similar to that shown in FIGS. 121-137 but utilizing a free-hinging design between the base and the cable bracket;

[0145] FIG. 139 is another embodiment of a strength member fixation structure utilizing a free-hinging design between the base and the cable bracket;

[0146] FIG. 140 illustrates the strength member fixation structure of FIG. 139 with the cable bracket at a downwardly angled orientation with respect to the base;

[0147] FIG. 141 illustrates the strength member fixation structure of FIG. 139 with the cable bracket orientated along the same horizontal plane with respect to the base;

[0148] FIG. 142 illustrates the strength member fixation structure of FIG. 139 with the cable bracket at an upwardly angled orientation with respect to the base;

[0149] FIG. 143 is another embodiment of a strength member fixation structure having features similar to those shown in FIGS. 121-142 but utilizing a design where the cable bracket is integrally formed with and fixed to the base portion of the fixation structure at an angled orientation;

[0150] FIG. 144 illustrates a side view of a plurality of the fixation structures of FIG. 143 in a vertically stacked arrangement;

[0151] FIG. 145 illustrates a front perspective view of a plurality of the fixation structures of FIG. 143 in a vertically stacked arrangement;

[0152] FIG. 146 illustrates another perspective view of a plurality of the fixation structures of FIG. 143 in a vertically stacked arrangement;

[0153] FIG. 147 is another embodiment of a strength member fixation structure having features similar to those shown in FIGS. 121-146 but utilizing a design where the cable bracket is integrally formed with and fixed to the base portion of the fixation structure, wherein the cable bracket and the base are aligned along a horizontal plane and wherein the cable bracket forms an angle with the base along a vertical plane that goes through a longitudinal axis defined by the base;

[0154] FIG. 148 illustrates a side view of a plurality of the fixation structures of FIG. 147 in a vertically stacked arrangement;

[0155] FIG. 149 illustrates a front perspective view of a plurality of the fixation structures of FIG. 147 in a vertically stacked arrangement;

[0156] FIG. 150 is an example of another embodiment of a strength member fixation structure that provides a universal-type clamping mechanism for accommodating different sizes and numbers of cabling, the fixation structure shown in an exploded configuration;

[0157] FIG. 151 illustrates the strength member fixation structure of FIG. 150 in an assembled configuration with the

clamp portion in a pivoted down orientation with respect to the base for clamping a cable;

[0158] FIG. 152 illustrates the fixation structure of FIGS. 150-151 with the clamp portion in a non-clamped orientation;

[0159] FIG. 153 illustrates a bottom perspective view of an example embodiment of the clamp portion of the fixation structure of FIGS. 150-152;

[0160] FIG. 154 illustrates a bottom perspective view of another example embodiment of the clamp portion of the fixation structure of FIGS. 150-152;

[0161] FIGS. 155-158 illustrate fixation structure of FIGS. 150-152 in various configurations for clamping various numbers and sizes of cables;

[0162] FIG. 159 is an example of a fan-out fixation assembly having features that are examples of inventive aspects in accordance with the present disclosure, the fixation assembly shown with a bracket and one fan-out holder mounted on the bracket;

[0163] FIG. 160 illustrates a rear perspective view of the fan-out holder of the fixation assembly of FIG. 159;

[0164] FIG. 161 illustrates a front perspective view of the fan-out holder of the fixation assembly of FIG. 159;

[0165] FIG. 162 illustrates a side view of the fan-out holder of the fixation assembly of FIG. 159;

[0166] FIG. 163 illustrates the fan-out fixation assembly of FIG. 159 with the bracket thereof fully populated with the fan-out holders thereof;

[0167] FIG. 164 is an example of another embodiment of a fan-out holder having features that are similar to that shown in FIGS. 160-162;

[0168] FIG. 165 is an example of yet another embodiment of a fan-out holder having features that are similar to that shown in FIG. 164;

[0169] FIG. 166 illustrates another embodiment of a fan-out fixation assembly utilizing another bracket and fan-out holders;

[0170] FIG. 167 is a rear perspective view of one of the fan-out holders that is used on the fan-out fixation assembly shown in FIG. 166;

[0171] FIG. 168 is a side perspective view of the fan-out holder of FIG. 167;

[0172] FIG. 169 illustrates the bracket of the fan-out fixation assembly of FIG. 166 in isolation;

[0173] FIG. 170 illustrates the fan-out fixation assembly of FIG. 166 being used to fix a fan-out device to a telecommunications fixture;

[0174] FIG. 171 illustrates another embodiment of a fan-out fixation assembly that utilizes a double-sided design;

[0175] FIG. 172 is a side perspective view of one of the fan-out holders that is used on the fan-out fixation assembly shown in FIG. 171;

[0176] FIG. 173 is an example of another embodiment of a fan-out holder having features that are examples of inventive aspects in accordance with the present disclosure;

[0177] FIG. 174 illustrates the fan-out holder of FIG. 173 from a rear perspective view;

[0178] FIG. 175 illustrates a side view of the fan-out holder of FIG. 173;

[0179] FIG. 176 illustrates a portion of another embodiment of a door, similar to that shown in FIGS. 37-40, that is configured for mounting to the various telecommunications frames of FIGS. 1-69, the door shown with a right side handle in the open position;

[0180] FIG. 177 illustrates the door of FIG. 176 with the left side handle in the open position;

[0181] FIG. 178 is a diagrammatic view illustrating the position of the spacer assembly of the door of FIGS. 176-177 when the handle is in the closed position;

[0182] FIG. 179 is a diagrammatic view illustrating the position of the spacer assembly of the door of FIGS. 176-177 when the handle has been moved to the open position;

[0183] FIG. 180 is a perspective view of the latching system of the door of FIGS. 176-177 shown in isolation;

[0184] FIG. 181 is a close-up view of a portion of the latching system of FIG. 180 illustrating the details of the spacer assembly;

[0185] FIG. 182 is a front view of the latching system of the door of FIGS. 176-177 shown in isolation; and

[0186] FIG. 183 is a close-up view of a portion of the latching system of FIG. 182 illustrating the details of the spacer assembly and the position of the spacer assembly when the handle is in the closed position.

#### DETAILED DESCRIPTION

[0187] Various embodiments will be described in detail with reference to the drawings, wherein like reference numerals represent like parts and assemblies throughout the several views. Reference to various embodiments does not limit the scope of the claims attached hereto. Additionally, any examples set forth in this specification are not intended to be limiting and merely set forth some of the many possible embodiments for the appended claims.

[0188] With reference to FIG. 1, an example of an optical distribution frame or rack assembly 110 is shown. According to the depicted embodiment, the frame assembly 110 is provided as a cross-connect frame assembly formed from the combination of a right frame 112 and a left frame 114. The cross-connect frame assembly 110 is configured to allow interchangeable patching between devices supported by the right frame 112 and devices supported by the left frame 114.

[0189] FIG. 2 illustrates another example embodiment of an optical distribution frame or rack assembly 120 in accordance with the present disclosure. According to the depicted embodiment, the frame assembly 120 is provided as an inter-connect frame assembly that is designed for applications with little or no re-patching requirements, where the distribution devices mounted on the frame 122 of the frame assembly 120 define an outside plant (OSP) cable side 124 and an equipment cable side 126.

[0190] FIG. 3 illustrates an overlength bay 130 that can be used between two of the cross-connect frame assemblies 110 shown in FIG. 1.

[0191] As noted above, each of the right and left frames 112, 114 of either the cross-connect assembly 110 or the frame 122 of the inter-connect assembly 120 is configured to support a plurality of optical fiber devices in the form of distribution elements 100, such as a sliding chassis type element. Such elements may be configured for use as patch panels to connect patch cables entering one side of the element 100 to an incoming cable, such as a distribution cable or a feeder cable entering an opposite side of the element 100. Examples of such elements 100 are described in PCT Patent Application Serial Nos. PCT/EP2014/051714, filed Jan. 29, 2014; PCT/EP2014/063717, filed Jun. 27,

2014; and PCT/EP2015/066899, filed Jul. 23, 2015, the entireties of which are hereby incorporated by reference.

[0192] Each optical fiber distribution element 100 mounted to the optical distribution frame assemblies 110/120 is provided with a first side 102 and an opposite second side 104 at which cables may enter or exit the element 100.

[0193] The cross-connect assembly 110 is designed to allow patching between elements 100 supported by the right frame 112 and elements 100 supported by the left frame 114, where the first side 102 (e.g., left side) of each of the elements 100 in the left frame 114 and the second side 104 (e.g., right side) of each of the elements 100 in the right frame 112 are considered the fixed sides of the cross-connect assembly 110 and where the center portion 115 of the cross-connect assembly 110 is designed as the flexible side allowing re-patching of cabling between the elements 100 on the right and left frames 112, 114.

[0194] A number of cross-connect assemblies 110 can be stacked in a side-by-side configuration in a data center as shown in FIG. 8. An overlength bay such as the bay 130 illustrated in FIG. 3 can be used between two cross-connect assemblies 110 as shown in FIG. 33.

[0195] As noted above, the frame assembly 120 shown in FIG. 2 is provided as an inter-connect frame assembly that is designed for applications with little or no re-patching requirements for the elements 100 housed within its frame 122.

[0196] Now referring to FIGS. 1 and 4-33, examples of the cross-connect frame assembly 110 are illustrated. As shown, the cross-connect frame assembly 110 may be formed by a combination of the right frame 112 and the left frame 114 that are placed adjacent each other to facilitate cross-patching between the devices 100 mounted on the frames. It should be noted that features discussed for the left frame 114 mirror those for the right frame 112 and only one of the frames will be discussed in detail where applicable.

[0197] For a given frame, e.g., the left frame 114, the left side 113 of the frame 114 is designated as the fixed side and the right side 117 is designated as the flexible side, where interchangeable patching can occur.

[0198] The frame 114 defines a rear wall 12 with fastener openings 132 for the mounting of the distribution elements 100 in a vertically stacked arrangement.

[0199] The rear wall 12, at the left side 113 of the left frame 114 may also include fastener openings 34 for the mounting of fan-out holder brackets 4002 as will be discussed in further detail below for mounting of fan-outs.

[0200] The right side 117 of the left frame 114 closer to the center 115 of the cross-connect frame assembly 110 are provided a series of overlength drums 1000, arranged in a vertical column for managing cables extending from the devices 100. The overlength drums 1000, as shown in FIGS. 6-7 and as discussed in further detail below, are configured to guide cables 5 from the devices 100 toward bundle collectors 1200 that are provided toward a bottom 134 of the left frame 114. The bundle collectors 1200 are also discussed in further detail below.

[0201] From the bundle collectors 1200 of the left frame 114, the patch cabling 5 can be passed to the bundle collectors 1200 of the right frame 112. From the bundle collectors 1200, the patch cabling 5 can be routed over the overlength drums 1000 provided on the right frame 112 and patched to the elements 100 supported by the right frame 112.

[0202] Positioned underneath the overlength drums 1000 is provided a divider wall 136 for keeping the cables 5 that are being routed up toward the drums 1000 from the cables 5 being routed down from the drums 1000 toward the bundle collectors 1200. FIG. 31 illustrates the central region 115 of the cross-connect frame assembly 110 where bundle collectors 1200 are used to guide cabling between the right and left frames 112, 114 of the cross-connect assembly 110 and toward a bottom through 40 of the cross-connect assembly 10. FIG. 32 illustrates the overlength drums 1000 used adjacent the central region 115 of the cross-connect frame assembly 110 for guiding cabling 5 from the flexible sides of the frames 112, 114 toward the bundle collectors 1200 shown in FIG. 31.

[0203] A bottom trough 140 defined by the cross-connect frame assembly 110 can be used to route cables 5 between the right and left frames 112, 114 along the bottom of the frame assembly 110. Horizontally positioned bundle collectors 1200 on the left and right frames 114, 112 are designed to guide cables 5 toward the bottom through 140.

[0204] As shown, the cross-connect frame assembly 110 defines a central opening 142 at the top of the assembly 110 that leads in to a central trough 144 for cables 5 to be routed out of the assembly 110. Both the central opening 142 and the central trough 144 are formed by combining the right and left frames 112, 114 in a side-by-side arrangement. Cabling 5 can selectively be routed through the bundle collectors 1200, within the central trough 144, and out the top of the frame assembly 110 through the central opening 142.

[0205] Each of the right and left frames 112, 114 of the cross-connect assembly also defines openings 146 at the outer sides both at the top and the bottom for incoming cables 5 to be routed to the fixed sides of the elements 100.

[0206] As shown in FIGS. 1 and 4-33, the fixed sides of the frames 112, 114 may utilize fan-out fixation assemblies 4000 for guiding cables 5 to the elements 100. Such fan-out fixation assemblies 4000 are discussed in further detail below. And, at the outer sides of the elements 100, strength member fixation structures 3000 can be mounted to the elements 100 for fixing cabling 5 to the fixed sides of the elements 100. Examples of such strength member fixation structures 3000 are discussed in further detail below.

[0207] Each of the fiber distribution elements 100 may include cable management structures 2000 that can be used on the flexible patching sides thereof. It should be noted that the cable management structure 2000 can be designed to be mounted on either side 102/104 of an element 100, depending on whether the element 100 is mounted on the right frame or the left frame of the cross-connect assembly 110 since the flexible side of the cross-connect assembly is positioned toward the center. The cable management structures 2000 can also be used on either side of the interconnect assembly 120 as discussed above.

[0208] The cable management structures 2000 are designed as push-through cable management structures that keep cables 5 contained adjacent the elements 100 while providing bend radius protection to cables 5 extending away from the elements 100 as the cables 5 are guided toward the overlength drums 1000.

[0209] Examples of the cable management structures 2000 are discussed in further detail below.

[0210] FIG. 5 illustrates an example of a cross-connect frame assembly 110 that utilizes overlength drums in the

form of slide drums 1300. Further details of such slide drums 1300 that provide an alternative cable routing solution are discussed below.

[0211] As shown, each of the right and left frames 112, 114 of the cross-connect assembly 110 may also include door mounts 150. The door mounts 150 are configured to receive the spring-loaded rods 152 of pivot doors 154 that can be used to cover and protect the internal parts of the cross-connect assembly 110 as shown in FIGS. 36-42 and discussed in further detail below.

[0212] Regarding the cable routing provided by the cross-connect frame assembly 10, FIG. 6 illustrates an example cable patch routing between the right and left frames 112, 114 of the cross-connect frame assembly 110. FIG. 7 schematically illustrates the cable patch routing physically shown in FIG. 6. The cross-connect frame assembly 110 is designed such that the cable routing features for guiding the cabling 5 between the devices 100 on the left frame 114 and the devices on the right frame 112 allow the use of fixed length fiber optic patch cables 5 between various elements 100 on respective right and left frames 112, 114 of the cross-connect assembly 110. An example of a patch cable 5 is shown in FIG. 9. According to one example, the patch cable 5 used in the cross-connect assembly 110 may be about 4.5 meters or about 5 meters in length.

[0213] FIGS. 10-13 illustrate the types of cables 5 on the fixed side of the elements 100 that can be paired with the jumpers 5 that are provided on the flexible side of the elements 100 in a given frame 112/114 of the cross-connect assembly 110. FIG. 10 illustrates, for the fixed side, a cable 5 where fibers extending from can be spliced to the connectors within the elements 100. FIGS. 11 and 12 illustrate, for the fixed side, trunk cables 5 that are broken out using fan-outs. FIG. 13 illustrates, for the fixed side, individual jumper cables 5 that can be extended to the elements 100.

[0214] FIG. 14 is one example of the cable routing that can be used on the fixed side of a left frame 114 of the cross-connect assembly 110, where the cables 5 are directed from the top opening 146 of the frame 114 toward the elements 100. FIG. 15 is another example of the cable routing that can be used on the fixed side of a left frame 114 of the cross-connect assembly 110, where the cables 5 are directed from the bottom opening 146 of the frame 114 toward the elements 100. FIG. 16 is another example of the cable routing that can be used on the fixed side of a left frame 114 of the cross-connect assembly 110, where the cables 5 are directed from both the top and the bottom openings 146 of the frame 114 toward the elements 100, the schematic illustrating the split point for the up or down routing of the cables 5. FIG. 17 is used to illustrate one example cable routing that can be used on the fixed side of a right frame 112 of the cross-connect assembly 110, where the cables 5 are directed toward a bottom of the frame from the elements 100. The routing illustrated in FIG. 17 essentially mirrors the routing illustrated in FIG. 14 for the left frame 114 of the cross-connect assembly 110. It should be noted that the routings illustrated in FIGS. 15 and 16 for the left frame 114 can also be mirrored for the right frame 112.

[0215] FIG. 18 is another example of the cable routing that can be used on the fixed side of a left frame 114 of the cross-connect assembly 110, where the cables 5 are directed from a top of the frame 114 toward the elements 100 and where the cables 5 are trunk cables that are split out using fan-outs mounted with fan-out fixation assemblies 4000 to

the frame 114. FIG. 19 illustrates a similar routing to that shown in FIG. 18 for trunk cables 5, however on the fixed side of a right frame 112 of the cross-connect assembly 110. [0216] FIG. 20 illustrates an example cable routing that can be used on the fixed side of a left frame 114 of the cross-connect assembly 110, where the cables 5 are a combination of trunk cables that are split out using fan-outs mounted to the frame 114, directed from a top of the frame 114 toward the elements 100 and jumper cables directed to the elements 100 from a bottom of the frame 114. FIG. 21 illustrates an example cable routing for combination cabling 5 similar to that shown in FIG. 20, where both the trunk cables and jumper cables are directed from a top of the frame 114 toward the elements 100.

[0217] FIG. 22 illustrates an example cable routing for combination cabling 5 similar to that shown in FIG. 21, where the jumper cables are directed to an upper set of distribution elements 100 and trunk cables are directed to a lower set of distribution elements 100.

[0218] FIG. 23 illustrates an example cable routing for the fixed side of a left frame 114 of the cross-connect assembly 110 where a plurality of elements 100 on different levels receive fibers to be spliced from a single OSP cable 5 fixed at the side of one of the elements 100 in a grouping. FIG. 24 illustrates an example cable routing similar to that shown in FIG. 23 for the fixed side of the right frame 112 of the cross-connect assembly 110.

[0219] FIG. 25 illustrates the mounting of a group of elements 100 where fibers to be spliced from a single OSP cable 5 fixed at the side of one of the elements 100 is routed to all of the elements 100 in the group, where the length of cabling 5 is provided with enough slack to accommodate the mounting.

[0220] FIG. 26 illustrates the positioning of the fan-outs using fixation assemblies 4000 that can be mounted on the left frame 114 of the cross-connect assembly 110 for the trunk cables coming from a top of the frame 114 and FIG. 27 illustrates a perspective view of the left frame 114 of the cross-connect assembly 110 with an example fan-out fixation assembly 4000 being used to break out trunk cables. As noted previously, examples of fan-out fixation assemblies 4000 that can be used on the frames 112, 114 is illustrated in FIGS. 159-175.

[0221] FIG. 28 illustrates a schematic showing the use of a combination of OSP splice cables directed to from the bottom of the cross-connect assembly 110 toward the lower elements 100 and trunk cables with fan-outs directed from the top of the cross-connect assembly 110 toward the upper elements 100. FIG. 29 illustrates a group of elements 100 designated for splicing fibers from an OSP cable to other groups of elements 100 within a frame 112/114 at the fixed side of the cross-connect assembly 110. An example of a dedicated splice element 100 is shown in FIG. 30.

[0222] As noted above, an overlength bay 130 can be used between two of the cross-connect frame assemblies 110. Such an overlength bay 130 is illustrated in FIG. 33 being used between two cross-connect assemblies 110. FIG. 34 is a perspective view of the overlength bay 130 of FIG. 33 shown in isolation and FIG. 35 illustrates the overlength bay 130 of FIG. 34 in an unassembled configuration. As shown, the overlength bay 130 includes a column of the overlength drums 1000 that are provided in a vertically stacked arrangement with a bundle collector 1200 positioned toward the bottom of the overlength bay 130. A bottom trough portion

131 of the overlength bay 130 is designed to continue the troughing system 140 provided by the cross-connect frame assemblies 110 when the overlength bay 130 is positioned between them. Door mounts 150, similar to those used on the right and left frames 112, 114 of the cross-connect assembly 110 are also provided on the overlength bay 130 for providing coverage for the internal features if needed.

[0223] The doors 154 for use on the frame assemblies 110, 120, 130 are discussed herein with reference to FIGS. 36-42. The doors 154 include upper and lower spring loaded rods 152 that are insertable into rod receivers 156 that are provided on the door mounts 150. As shown, each rod receiver 156 defines a channel 158 with a tapered surface 159 that allows guiding of a door rod 152 into the channel 158 where the spring-loaded rod 152 can snap into a hinge opening 157 after riding along the tapered surface 159.

[0224] The spring-loaded rods 152 of the doors 154 allow the doors 154 to be pivotally opened in either direction. Each door 154 includes left and right squeeze handles 155. The handles 155 form part of a door latch system that allows a given door 154 to be pivotally opened in a selected direction. The pair of handles 155 on the right side of the door 154 are coupled to upper and lower spring-loaded rods 152 on the right side. And, the pair of handles 155 on the left side of the door 154 are coupled to upper and lower spring-loaded rods 152 on the left side. Pressing a set of either the right or the left handles 155 toward each other moves the upper rod 152 downwardly and moves the lower rod 152 upwardly. When the rods 152 clear the hinge openings 157, the rods 152 can move out of the channels 158 and the door 154 is free to swing out, pivoting about the rods 152 that are positioned on the opposite side.

[0225] In the same manner, the door 154 can be pivoted pivotally opened in the other direction. It should be noted that a door 154 can be entirely removed from a frame assembly 110/120/130 if both sets of handles 155 on the right and left sides are squeezed together, removing all four spring-loaded rods 152 from the hinge openings 157. FIG. 42 illustrates another version of a rod receiver 153 for mounting on the door mounts 150 of the frame assemblies 110/120/130.

[0226] It should be noted that the doors 154 for the inter-connect frame 120 assembly can be configured similar to the doors 154 for the cross-connect assembly 110. However, as shown in FIG. 55, the door mounts 150 on the inter-connect frame 122 are mounted adjacent the floor in a data-center, and, thus, the doors 154 can extend all the way down to the floor since a bottom trough is not utilized in an inter-connect application.

[0227] FIGS. 176-183 illustrate another embodiment of a door 254 for use on the frame assemblies 110, 120, and 130. The door 254 is similar in function to the door 154 discussed above and provides for a double-hinging operation. However, in order to limit or prevent a main portion 253 of the door 254 from bumping into or contacting the door mounts 150 during pivotal operation, the door 254 has been provided with a spacer assembly 251 on each of its rods 252 on both the right and left sides 256, 257 of the door 254, as will be discussed in further detail below. The spacer assembly 251 effectively provides spacing between a bottom edge 258 of the main portion 253 of the door 254 and the door mount 150 at each of the right side 256 and the left side 257 of the door 254 such that, regardless of which way the door 254 is pivoted, the main portion 253 of the door 254 will not bump

into or contact the door mount 150 at the opposite side during the pivotal motion. The spacer assembly 251 is height-adjustable at each side 256, 257 of the door 254 to ensure proper operation and to accommodate any height differences or tolerances between the two opposing hinge points.

[0228] Similar to the door 154 discussed above and shown in FIGS. 36-42, the door 254 includes upper and lower rods 252 that are insertable into the rod receivers 156 that are provided on the door mounts 150. Similar to the door 154 discussed above, the rod 252 on each of the right and left sides of the door 254 enters into the hinge opening 157 of a door mount 150 after being guided by the tapered surface 159 defined within the channel 158 of each opening 157.

[0229] The rods 252 of the doors 254 allow the doors 254 to be pivotally opened in either direction, similar to that discussed for door 154. Each door 254 includes left and right handles 255. In the depicted example, the handles are rotational or swivel type handles. The handles 255 form part of a door latch system, similar to that shown for 154, that allows a given door 254 to be pivotally opened in a selected direction. The handle 255 on the right side 256 of the door 254 is coupled to upper and lower rods 252 on the right side. And, the handle 255 on the left side 257 of the door 254 is coupled to upper and lower rods 252 on the left side. Rotating either the right or the left handle 255 to an open position, moves the upper rod 252 downwardly and moves the lower rod 252 upwardly. As noted above, when the rods 252 clear the hinge openings 157 of the door mounts 150, the rods 252 can move out of the channels 158 and the door 254 is free to swing out, pivoting about the rods 252 that are positioned on the opposite side.

[0230] In the same manner, the door 254 can be pivoted open in the other direction. It should be noted that a door 254, similar to door 154, can be entirely removed from a frame assembly 110/120/130 if both of the handles 255 on the right and left sides are rotated together, removing all four rods 252 from the hinge openings 157. FIGS. 180 and 182 illustrate the latching system of the door 254 in isolation.

[0231] Referring to FIGS. 178-183, in the depicted embodiment of the door 254, there are guiding pins 259 extending upwardly provided at the bottom edge 258 on each side 256, 257 of the door 254 that are received by openings 260 provided by the rods 252. The guiding pins 259 and the openings 260 provide a guiding system for proper vertical operation and alignment of the rods 252 with respect to the main portion 253 of the door 254. Even though the embodiment of the door 154 is not shown in FIGS. 36-42 to include such a guiding system, the door 154 can certainly be provided with such a guiding system, similar to that shown for door 254.

[0232] Referring back to FIGS. 176-179, as mentioned above, since the door 154/254 provides for a double-hinged operation and the hinges for the door 154/254 are provided at generally the same level on both sides of the door, sometimes due to manufacturing tolerances and play and due to the double-hinging nature of the door 154/254, the main portion of a door might bump into the door mount 150 at the other side of the door when the door is being pivoted to a closed position. And, if there is a height difference between the two hinge points at the two opposing sides of the door, one side of the door might clear its respective hinge point, but the other side will then always tend to bump into its respective hinge point. Thus, in order to limit or prevent

this issue, the embodiment of the door 254 has been provided with a spacer assembly 251 on its rods 252 on both the right and left sides 256, 257 of the door 254, as mentioned above.

[0233] The spacer assembly 251, as noted above, is configured to provide spacing between the bottom edge 258 of the door 254 and the door mount 150 at each of the right side 256 and the left side 257 of the door 254 such that, regardless of which way the door 254 is pivoted, the main portion 253 of the door 254 will not bump into or contact the door mount 150 at the opposite side during the pivotal motion. The spacer assembly 251 is height-adjustable at each side 256, 257 of the door 254 to ensure proper operation and to accommodate any height differences or tolerances between the two opposing hinge points. FIG. 176 illustrates a portion of the door 254 with the right side handle 255 in the open position and the left side handle 255 in the closed position. FIG. 177 illustrates the door 254 with the left side handle 255 in the open position and the right side handle in the closed position. FIG. 178 is a diagrammatic view illustrating the position of the spacer assembly 251 when a handle 255 is in the closed position, and FIG. 179 is a diagrammatic view illustrating the position of the spacer assembly 251 when a handle 255 has been moved to the open position.

[0234] Referring to FIGS. 176-183, the spacer assembly 251, as shown, may include a polymeric bumper or spacer structure 263 that is threaded onto a threaded portion 265 of the rods 252. The height of the bumper structure 263 along the threaded portion 265 of the rods 252 is adjusted to rest against the door mount 150 and to provide the proper spacing such that when the handle 255 at that given side is at a closed position, the door 254 will be raised to a sufficient point off the door mount 150 that the opposing side of the door 254 can pivot without bumping into or contacting the opposing door mount 150. This height-adjustable bumper structure 263 is provided on the rods 252 on both sides 256, 257 of the door 254 to ensure that both sides of the door 254 can pivot without having any contact issues. And, the height-adjustability aspect of the bumper structure 263 on each side of the door 254 can accommodate any manufacturing related issues such as door hinge height differences, tolerances, etc.

[0235] It should be noted that when the rod 252 at a given side is in the hinge opening 157 of a door mount 150 and the handle 255 at that side is in the closed position, the bumper or spacer structure 263 on the rod 252 pushes against the door mount 150 to effectively raise the entire door 254 upwardly. The vertical position of the spacer structure 263 is set at a point along the rod 252 where the door 254 is raised to clear the opposing door mount 150 at the opposing side. And, the bumper or spacer 263 at the opposing side of the door 254 is similarly adjusted in height.

[0236] In certain examples, the bumper 263 may be provided in the form of a plastic nut 267. In the depicted example, the bumper 263 is a knurled plastic nut 267. The spacer assembly 251, as shown, may include a counter stop structure 269 on the rod 252 that provides an upper vertical stop for the bumper 263. In the depicted example, the counter stop structure 269 is in the form of a counter nut 271 and a split lock washer 273 provided between the bumper 263 and the counter nut 271.

[0237] It should be noted, as shown in FIGS. 178-179, that the door 254 is provided with an opening 272 along the

bottom edge 258 at both of the right and left sides 256, 257 of the door 254 that is large enough to accommodate the raised and lowered positions of the bumper structure 263. When the handle 255 is in the closed position as shown in FIG. 178, the polymeric bumper structure 263 is exposed from the bottom edge 258 of the door 254 and contacts against the door mount 150 to raise the door 254, as described above.

[0238] Thus, the embodiment of the door 254, which is a double-hinging door, has been provided with a spacer assembly 251 that is configured to limit or prevent damage to the main portion 253 of the door 254 during pivotal movement of the door. And, as described above, the spacer assembly 251 is provided as a height-adjustable assembly that can accommodate manufacturing related issues such as height differences/tolerances between the two opposing hinges. Even though such manufacturing issue can be accounted for in other ways, such as adjusting the height of the hinging points, the spacer assembly 251 provides one solution to account for such tolerance issues and to limit or prevent damage to such double-hinging doors 254.

[0239] The inter-connect frame assembly 120 is shown in closer detail in FIGS. 2 and 43-54. As noted above, the inter-connect frame assembly 120 is designed for applications with little or no re-patching requirements, where the mounted distribution devices 100 define an OSP cable side 124 and an equipment cable side 126.

[0240] In the depicted example, the left side of the inter-connect frame 122 may be designated and configured as the OSP side 124 and the right side may be designated and configured as the equipment side 126. At both the OSP side 124 and the equipment side 126, the frame defines top openings 172 for incoming and outgoing cables 5.

[0241] It should be noted that the left OSP side 124 of the inter-connect frame 122 may be configured in a similar manner as the fixed side of the frames 112, 114 of the cross-connect assembly 110. The equipment side 126 utilizes, in addition to overlength drums 1000 that are provided in a vertical stack, upper and lower hook drums 1100. The hook drums 1100 are configured to guide cabling 5 from the elements 100 downwardly and around the bottom sides of the overlength drums 1000 as shown in FIG. 45. Dividers 174 can be provided to separate cables 5 coming from the elements 100 and cables 5 that have been routed around the hook drums 1100. Examples of the hook drums 1100 are discussed in further detail below.

[0242] Fan-out fixation assemblies similar to fixation assemblies 4000 noted above may be used at the right and left side 126, 124 of the inter-connect frame 122.

[0243] FIGS. 46-52 illustrate the types of cables 5 on the OSP side 124 of the elements 100 that can be paired with the types of cables 5 on the equipment side 126 of the elements 100 that are provided on the inter-connect frame 122.

[0244] As shown in FIG. 46, splice cables at the OSP side 124 can be paired with individual jumpers at the equipment side 126. As shown in FIG. 47, splice cables at the OSP side 124 can be paired with trunk cables utilizing fan-outs at the equipment side 126. As shown in FIG. 48, trunk cables utilizing fan-outs at the OSP side 124 can be paired individual jumpers at the equipment side 126. As shown in FIGS. 49-51, trunk cables utilizing fan-outs at the OSP side 124 can be paired with trunk cables utilizing fan-outs at the equipment side 126. And, as shown in FIG. 52, trunk cables

utilizing fan-outs at the OSP side 124 can be paired with individual jumpers at the equipment side 126.

[0245] FIG. 53 schematically illustrates one example of the cable routing that can be used on the inter-connect frame 122 for trunk cables on the OSP side 124 and trunk cables on the equipment side 126. FIG. 54 physically illustrates an example cable routing on the equipment side 126 of the inter-connect assembly 120, where the hook drums 1100 and the overlength drums 1000 are illustrated as being utilized.

[0246] Referring now to FIGS. 56-69, alternative examples of either the cross-connect assembly or the inter-connect assembly and the modular packaging for such assemblies is illustrated.

[0247] For example, FIG. 56 illustrates an example cable routing on the cross-connect assembly 110 using a combination of different types of overlength drums at the center of the assembly including fixed drums 1000 and slide drums 1300.

[0248] FIGS. 57-64 relate to the packaging of the frame assemblies 110, 120, 130 of the present disclosure. FIG. 57 illustrates the left frame 114 of the cross-connect frame assembly 110 in an empty configuration without any of the mounted distribution elements 100, ready to be disassembled for packaging and FIG. 58 illustrates the right frame 112 of the cross-connect frame assembly 110 in an empty configuration without any of the mounted distribution elements 100, ready to be disassembled for packaging.

[0249] FIG. 59 illustrates the frame 122 of the inter-connect assembly 120 in an empty configuration without any of the mounted distribution elements 100, ready to be disassembled for packaging. FIG. 60 illustrates another perspective view of the overlength bay 130, ready to be disassembled for packaging. FIG. 61 illustrates another perspective view of the left frame 114 of the cross-connect frame assembly 110, ready to be disassembled for packaging. FIG. 62 illustrates the left frame 114 of FIG. 61 in a disassembled configuration, ready for packaging. FIG. 63 illustrates parts of the disassembled frame 114 of FIG. 62 organized for placement into a packaging box 190. And, FIG. 64 illustrates the packaging box 190 for use in transporting the frame 114 of FIGS. 61-63.

[0250] FIG. 65 illustrates an alternative embodiment of a cross-connect frame assembly 210 having features that are similar to the assembly 110 shown in FIG. 1, where the right and left frames 212, 214 utilize separating fins 220 for forced routing between the flexible sides of the frames 212, 214. As shown, the fins 220 are designed to provide an error-proof method as the patch cables 5 are guided toward and around the overlength drums 1000 at the left and right frames 214, 212. Toward the center 215 at each of the left and right frames 214, 212 are also provide vertical dividers 222 for keeping cabling 5 organized as the cabling 5 extends around further overlength drums 1000 provided at the center bottom of the frame assembly 210. FIG. 66 illustrates an example cable routing utilizing the separating fins 220 of the cross-connect frame assembly 210 of FIG. 65 and FIG. 67 illustrates the separating fins 220 of FIGS. 65-66 in closer detail.

[0251] FIG. 68 illustrates push-through type cable management structures 2700 that can be used with the separating fins 220 of the cross-connect frame assembly 210 of FIGS. 65-67 for keeping cable bundles 5 organized. Such cable



management structures 2700 and similar structures utilizing push-through designs are discussed below and illustrated in FIGS. 118-120.

[0252] FIG. 69 illustrates a color-coding concept that can be used to keep track of the cable routings between the flexible sides of the frames 312, 314 on another example of a cross-connect frame assembly 310. According to this concept, different colored cabling may be used for designating different routing directions. For example, according to one example, a color such as white may be used for cabling 5 going to or coming from the bottom trough. Red could be used for cabling 5 going to or coming from the top trough. Green could be used for internal return routing. Yellow could be used to indicate cabling 5 going to or coming from an adjacent frame. Pink could be used for cabling 5 going to or coming from a back side frame.

[0253] Referring now to FIGS. 70-100, the various cable management structures that are used in certain locations throughout the frame assemblies 110/120 or on the overlength bay 130 are shown in closer detail.

[0254] FIGS. 70-76 illustrate one example of the overlength drum 1000 that is used on the frame assemblies 110/120 or on the overlength bay 130. The overlength drum 1000 is configured to be removably mounted to certain locations on the frame assemblies 110/120 or on the overlength bay 130 and is used to manage or support extra cable length or slack.

[0255] The designated frame walls 12 may be designed with a universal type mounting interface such that a given wall 12 can removably receive different types of cable management structures depending on the cable management need.

[0256] One example of a mounting interface between a given frame wall 12 and an example overlength drum 1000 will be described with reference to FIGS. 70-76. As shown in FIGS. 70-76, the mounting features that are provided on a frame wall 12 include a plurality of slots 14, each defining an upper wider portion 16 (i.e., receiver portion) and a lower narrower portion 18 (i.e., retention portion). In the depicted example, two such slots 14 are vertically aligned in a first column on the frame wall 12 and two such slots 14 are vertically aligned on a second column spaced apart from the first column. Between the two columns is positioned a latch opening 20, the significance of which will be described in further detail below.

[0257] The example of the overlength drum 1000 that will be used to describe the mounting mechanism between a frame wall 12 and the drum 1000 is shown in FIGS. 70-76.

[0258] As shown, the depicted overlength drum 1000 defines a fixation portion 1002, a bend radius protection portion 1004 extending from the fixation portion 1002, and a cable retention portion 1006 positioned at the end of the bend radius protection portion 1004. With the cable retention portion 1006 having both upward and downward extensions 1008, the depicted overlength drum 1000 provides a generally T-shaped configuration.

[0259] The bend radius protection portion 1004 defines a generally cylindrical profile providing the curvature needed for radius protection for cables routed on the overlength drum 1000.

[0260] The fixation portion 1002 defines the mating mounting features that are designed to mate with the mounting features that are provided on a frame wall 12. The fixation portion 1002 includes a plurality of hook-like mem-

bers 1010. Two hook-like members 1010 are vertically aligned in a first column and two hook-like members 1010 are vertically aligned in a second column spaced apart from the first column. Between the two columns is positioned a flexible latch 1012 with a retaining tab 1014 extending rearward from the latch 1012.

[0261] Each hook-like member 1010 defines a vertical retention portion 1016 that defines a larger profile. Each hook-like member 1010 also defines a vertical slide portion 1018 that has a thinner profile than the vertical retention portion 1016, wherein the slide portion 1018 is oriented perpendicular to the retention portion 1016 and connects the retention portion 1016 to a rear wall 1020 defined by the fixation portion 1002 of the overlength drum 1000. Each hook-like member 1010 also defines a horizontal stop portion 1022 that is oriented perpendicular to both the slide portion 1018 and the retention portion 1016, where the horizontal stop portion 1022 also connects the larger retention portion 1016 to the rear wall 1020.

[0262] As shown, the vertical slide portion 1018 and the horizontal stop portion 1022 are connected to the vertical retention portion 1016 of the hook-like members 1010 such that they meet at the inner, upper corner of the retention portion 1016.

[0263] When the overlength drum 1000 is being mounted to a frame wall 12, the larger vertical retention portions 1016 are aligned with and passed through the upper wider receiver portions 16 of the slots 14. The hook-like members 1010 are then slid downwardly with the vertical slide portions 1018 sliding within the lower narrower retention portions 18 of the slots 14. The hook-like members 1010 are slid downwardly until the horizontal stop portions 1022 abut the apertures forming the ends of the wider receiver portions 16 of the slots 14 to stop the slidable movement of the hook-like members 1010. When the hook-like members 1010 are being slidably mounted, the flexible latch 1012 of the fixation portion 1002 of the drum 1000 is elastically flexed, riding along the wall 12. At the point the horizontal stop portions 1022 abut the slot apertures, stopping the movement of the hook-like members 1010, the flexible latch 1012 can flex back under a bias with the retaining tab 1014 snapping into the latch opening 20 that is positioned in the middle of the two columns of slots 14 on the frame wall 12.

[0264] The mounting features essentially provide a dovetail type mounting interface between the frame wall 12 and the overlength drum 1000. However, the thinner vertical slide portions 1018 and the horizontal stop portions 1022 are formed at the edges of the larger retention portion 1016 and meet at a corner of the retention portion 1016 to provide extra stiffness to the hook-like members 1010. The upper wider portions 16 and the lower narrower portions 18 of the slots 14 are provided to match the mounting features defined by the hook-like members 1010.

[0265] When the hook-like members 1010 have been slid all the way down, the larger retention portions 1016 overlap with the lower narrower portions 18 of the slots 14 and abut an opposing side of the frame wall 12 to retain the hook-like members 1010 against the frame wall 12. The retaining tab 1014 of the flexible latch 1012 abuts the upper edge 22 of the aperture defining the latching slot 14 to prevent unwanted upward movement of the drum 1000. If the drum 1000 needs to be removed, the retaining tab 1014 can be pushed away from the wall 12 toward the drum 1000, elastically flexing

the latch **1012**, until the tab **1014** clears the wall **12**, and the drum **1000** can be slid upwardly.

[0266] It should be noted that in the depicted embodiment, the fixation portion **1002** of the drum **1000** defines a base **1024** that is large enough in perimeter to fully surround the mounting features of the fixation portion **1002**. The base **1024** of the fixation portion **1002** abuts the frame wall **12** and provides extra stiffness for protection against bending forces on the drum **1000**.

[0267] As shown, the flexible latch **1012** of the drum **1000** is fully surrounded by an aperture **1026** defined by the base **1024** of the fixation portion **1002**. Only the retaining tab **1014** protrudes out of the aperture **1026**. The base **1024** fully surrounding the flexible latch **1012** limits pinching of any fiber optic cables between the latch **1012** and the frame wall **12**.

[0268] In certain examples, an additional fastener hole **1028** may be provided both on the base **1024** defined by the fixation portion **1002** of the drum **1000** and on the frame wall **12** for extra fastening and safety. Such an example is shown in FIG. 77.

[0269] As also shown in an example in FIG. 78, the overlength drum **1000** may also define a longitudinal slot **1030** extending from the rear of the drum **1000** toward the front. The longitudinal slot **1030** may be used to receive a central wall if the drum **1000** is going to be placed at the upper edge of a separator wall or a different transversely extending wall structure on one of the frame assemblies **110/120** or on the overlength bay **130**.

[0270] In certain other embodiments, flanges **1032** defined by the cable retention portions **1006** of the drums **1000** that are positioned at the ends of the bend radius protection portions **1004** may define different various shapes. As shown in FIG. 79, the flanges **1032** may include bent portions **1034** forming staggered openings **1036** for facilitating insertion of cables when the drums **1000** are provided in a vertically stacked arrangement.

[0271] As also shown in FIG. 80, the flanges **1032** may provide an angled profile **1038** to form angled openings **1040** for facilitating insertion of cables when the drums **1000** are provided in a vertically stacked arrangement.

[0272] FIG. 81 illustrates an example of a hook-drum **1100** that can be used on certain locations throughout the telecommunications frame assembly **20** of the present disclosure. It should be noted that the hook drum **1100** includes the same mounting features that were discussed above with respect to the overlength drum **1000** such that it can interface with the universal type mounting features provided on a given frame wall **10**.

[0273] As shown, the hook drum **1100** defines bend radius protection along two perpendicular planes. The bend radius protection portion **1104** extending from the fixation portion **1102** provides bend radius protection along a vertical plane. The flange **1132** defined by the cable retention portion **1106** is also curved to provide bend radius protection along a horizontal plane that is perpendicular to the vertical plane. The drum **1100** is referred to as a hook drum since essentially the entire cable retention portion **1106** extends upwardly from the bend radius protection portion **1104**, forming a generally L-shaped configuration.

[0274] An example embodiment of the bundle collectors **1200** that are used throughout the cross-connect frame assemblies **110** or on the overlength bay **130** is illustrated in FIGS. 82-87. As shown, the depicted bundle collector **1200**

defines a fixation portion **1202** that uses similar features to those described above with respect to the overlength drums **1000** and the hook drums **1100** for removably snap-fitting the bundle collectors **1200** to a frame wall **12**. In the depicted example, each bundle collector **1200** includes two rows of hook-like members **1210** that are spaced apart further than those shown from the overlength and hook drums and also two flexible latches **1212** positioned in the middle of the hook-like members **1210**. As such, the bundle collectors **1200** are designed to be mounted to frame walls **12** that have mating mounting features.

[0275] Each bundle collector **1200** defines a rear bend radius protection portion **1204** and right and left bend radius protection portions **1206**, **1208** that extend from the rear bend radius protection portion **1204**. The right and left bend radius protection portions **1206**, **1208** define inwardly extending portions **1210** that cooperatively form a cable insertion slot **1211**. As shown, with the rear portion **1204**, the right and left portions **1206**, **1208** and the inwardly extending portions **1210** thereof, the bundle collector **1200** defines a central cable channel **1213** with bend radius protection when leading cabling out in four different directions.

[0276] As shown in FIGS. 82-87, each bundle collector **1200** defines features for mating in a side-to-side relationship with another bundle collector **1200** to form a double bundle collector. Adjacent the front of each bundle collector **1200**, on opposite sides, are provided a dovetail tab **1215** and a dovetail slot **1217**, respectively, for slidable mounting of a bundle collector **1200** to a similarly configured bundle collector **1200**.

[0277] Also, as shown, each of the right and left bend radius protection portions **1206**, **1208** of the bundle collector **1200** define snap openings **1219** for selectively receiving radius extenders **1221** with a snap-fit interlock.

[0278] When two bundle collectors **1200** are mounted next to each other or a radius extender **1221** is mounted to one of the bundle collectors **1200**, a full circular drum is formed for providing bend radius protection to cables.

[0279] An alternative L-shaped edge protector or extender **1223** is shown in FIGS. 86-87, where the edge protector **1223** can be snap-fit to one of the bundle collectors **1200** using the snap openings **1219**. The edge protectors **1223** can be used in the manner shown in FIG. 87 to provide extra protection for cable slack.

[0280] Now referring to FIGS. 88-95, one of the sliding drums **1300** that can alternatively be used throughout parts of the telecommunications frame assemblies **110/120** or on the overlength bay **130** is described in further detail. As shown, the sliding drum **1300** defines a fixed part **1302** that is configured to be mounted to a frame wall **12** and a movable part **1304** that can slidably move away from the fixed **1302** part to facilitate cable access.

[0281] It should be noted that the fixed part **1302** defines a fixation portion **1306** that may use similar mounting features to those described above with respect to the overlength drums **1000** and the hook drums **1100** for removably snap-fitting the sliding drums **1300** to a frame wall **12**.

[0282] The fixed part **1302** of the slide drum **1300** defines upper and lower support portions **1308**, **1310** that extend from the fixation portion **1306**. The upper and lower support portions **1308**, **1310** receive and guide the movable part **1304** of the drum **1300**.

[0283] As shown in FIGS. 88-95, the movable part **1304** is removably mounted to the fixed part **1302** of the drum

**1300** between the upper and lower support portions **1308**, **1310**. The movable part **1304** defines a slide tab **1314** that has a generally dovetail type structure (defining a connector portion **1316** and a larger retention portion **1318**) that can be inserted through an opening **1320** at the upper support portion **1308**. Once inserted through the opening **1320**, the connector portion **1316** of the slide tab **1314** slides along a narrow slit **1322** defined by the upper support portion **1308**. The retention portion **1318** of the slide tab **1314** prevents separation of the slide tab **1314** from the narrow slit **1322** until it is aligned with the opening **1320**. The narrow slit **1322** essentially defines a longitudinal track for the movement movable part **1304** of the drum **1300**.

[0284] The upper support portion **1308**, at both ends of the narrow slit **1322**, defines positive stops **1324** for abutting the retention portion **1318** of the slide tab **1314**. The positive stops **1324** are also configured to form snap-fit interlock structures **1326** for retaining the slide tab **1314** at the ends of the track unless a force overcoming the frictional force provided by the snap-fit interlock structures **1326** starts moving the movable part **1304** of the drum **1300**.

[0285] As shown, each of the upper and lower support portion **1308**, **1310** defines intermating grip features **1330** for flexibly snap-fitting two of the drums **1300** in a vertically stacked configuration. As shown, the intermating grip features **1330** on a lower support portion **1310** of a given drum **1300** is oriented in an opposite orientation with respect to the grip features **1330** on an upper support portion **1308** of a given drum **1300** for providing the intermating capability.

[0286] As also shown, the lower support portion **1310** of the slide drum **1300** may define slots **1332** adjacent the front and the back that are used to receive a central wall if the slide drum **1300** is going to be placed at the upper edge of a separator wall or a different transversely extending wall structure on one of the frame assemblies **110/120** or on the overlength bay **130**.

[0287] Another version of a slide drum **1400** is illustrated in FIGS. **96-100**. In the version illustrated in FIGS. **96-100**, the fixed part **1402** is provided with an angle to a vertical frame wall **12** such that the movable part **1404** moves both outwardly and upwardly with respect to the fixation portion **1406** of the drum **1400**. In this manner, the movable part **1404**, since it is at an angle, can automatically slide back to its unextended position under the weight of any cabling.

[0288] As shown, a finger grip **1407** could be added for facilitating movement of the movable part **1404**. Also, a snap mechanism **1409** can be provided for retaining the movable part **1404** on the fixed part **1402** once the two parts have been assembled together. As shown, the snap mechanism **1409** may be formed by flexible cantilever arms **1411** that abut enlarged portions **1417** of a pair of rails **1413** of the movable part **1404**, where the rails **1413** are designed to slide along slits **1415** provided on both sides of the fixed part **1402**.

[0289] In other embodiments, instead of providing an angle for automatic movement of the movable part **1404**, the movable part **1404** may include a spring-loaded design, where the spring provides a bias on the movable part **1404** for automatically pulling the movable part **1404** back to its original position when a technician is done loading the drum **1400** with cabling or unloading the drum **1400**.

[0290] Even though the above described cable management structures have been illustrated and discussed herein as being used within the telecommunications frame assemblies

**110/120** or on the overlength bay **130** of the present disclosure, it should be noted that the inventive aspects can be utilized in any telecommunications fixture, such as a frame, a panel, or a rack, where cable slack needs to be managed, as long as the walls of such fixtures are designed with the mounting features described above.

[0291] As discussed above, the cross-connect assembly **10** is designed to allow patching between elements **100** supported by a right frame and elements **100** supported by a left frame, where the first side **102** (e.g., left side) of each of the elements in the left frame and the second side **104** (e.g., right side) of each of the elements in the right frame are considered the fixed sides of the cross-connect assembly **10** and where the center portion of the cross-connect assembly **10** is designed as the flexible side allowing re-patching of cabling between the elements on the right and left frames.

[0292] FIGS. **101-108** illustrate one example embodiment of a cable management structure **2000** that can be used on the flexible patching side of one of the fiber distribution elements housed by the cross-connect assembly **10**. It should be noted that the cable management structure **2000** can be designed to be mounted on either side **102/104** of an element **100**, depending on whether the element **100** is mounted on the right frame or the left frame of the cross-connect assembly **10** since the flexible side of the cross-connect assembly is positioned toward the center. The cable management structures **2000** can also be used on either side of the inter-connect assembly **20** as discussed above.

[0293] The cable management structures **2000** are configured to be in a vertically stacked arrangement when mounted to vertically stacked optical fiber distribution elements **100**.

[0294] As shown in FIGS. **101-108**, each optical fiber distribution element **100** is provided with mounting features **106** (e.g., slots) for slidably receiving the cable management structures **2000**. As shown in FIGS. **101-108**, each cable management structure **2000** includes mounting features **2002** that are configured to mate with the mounting features in the form of slots **106** provided on the optical fiber distribution elements **100** for sliding in and snap-fitting the cable management structures **2000** to the optical fiber distribution elements **100**. The mounting features **2002** of the cable management structure **2000** include a dovetail configuration **2004** and are slidably inserted into the slots **106** of the optical fiber distribution elements **100**. A flexible tab **2006** provided at the rear side of the cable management structure **2000** is used to latch and fix the cable management structure **2000** relative to the optical fiber distribution element **100**. The flexible tab **2006** is also used to unlatch the cable management structure **2000** from the optical fiber distribution element **100** before the dovetail structures **2004** are slid in a direction opposite to the insertion direction for removing the cable management structure **2000** from the slots **106** of the optical fiber distribution element **100**. It should be noted that the intermating mounting features of the optical fiber distribution elements **100** and the cable management structures **2000** are similar in form and function to that described in PCT Patent Application Serial Number PCT/EP2014/063717, filed Jun. 27, 2014, the entirety of which is hereby incorporated by reference, and therefore, further details relating thereto will not be discussed herein.

[0295] Referring to FIGS. **101-108**, each cable management structure **2000** defines a cable guiding base portion **2010** and a movable clip portion **2012** for retaining cables.

As noted above, the base portion **2010** defines the mounting features **2002** for snap-fitting the cable management structure **2000** to an optical fiber distribution element **100**. As shown, the base portion **2010** defines an upper guide portion **2014** and a lower guide portion **2016**. Between the upper and lower guide portions **2014, 2016** is defined a cable channel **2018** that extends from a front opening **2020** to a rear opening **2022** of the cable management structure **2000**. A slit **2024** is defined between the upper guide portion **2014** and the lower guide portion **2016** that allows cables to be inserted into the channel **2018**. The slit **2024** communicates with the cable channel **2018** and allows entry of cables into the channel **2018**. Each of the upper and lower guide portions **2014, 2016** defines radius limiting curves for leading fiber optic cabling either upwardly or downwardly while providing bend limit protection to the fibers of the cabling.

[0296] The movable clip portion **2012** is configured to close the slit **2024** for retaining the cables in the channel **2018**. The movable clip portion **2012** is also designed to facilitate insertion of cables into the channel **2018** as will be discussed below.

[0297] The clip **2012** defines a fixation portion **2026** for snap fitting to the base **2010** of the cable management structure **2000**. An elongate portion **2028** of the clip **2012** is elastically flexible with respect to the fixation portion **2026**. The elongate portion **2028** allows the clip to be flexed under a bias. The clip **2012** is biased upwardly to close the slit **2024**. As shown, the elongate portion **2028** of the clip **2012** is accommodated by a partition **2030** positioned at the lower guide portion **2016**. The partition **2030** allows the elongate portion **2028** of the clip **2012** to be flexed between downward and upward directions.

[0298] A finger tab **2032** is defined at the end of the elongate portion **2028** of the clip **2012**. The finger tab **2032** can be accessed by the finger of a technician for flexing the clip **2012** downwardly. The finger tab **2032** protrudes out slightly from side faces **2034** defined by the upper and lower guide portions **2014, 2016** for both facilitating the insertion of cabling into the cable management structure **2000** and for access by the finger of a technician in removal of cabling from the cable management structure **2000**.

[0299] The finger tab **2032** defines a tapered side face **2036** and a tapered front face **2038**. The tapered faces **2036, 2038** allow cables to be inserted into the slit **2024** and to automatically force the clip **2012** downwardly by contact therewith as the cables are being fed into the channel **2018**. The tapered front face **2038** of the clip **2012** allows cabling that is being inserted into the channel **2018** from the front opening **2020** toward the rear opening **2022** to contact the clip **2012** and to start forcing the clip **2012** to flex downwardly. Thus, the tapered surfaces **2036, 2038** of the clip **2012** are designed such that, when contacted by cabling along a first direction, the tapered surfaces **2036, 2038** force movement of the flexible portion **2028** under a bias in a second direction that is different than the first direction. In the shown example, the first direction is a lateral direction of the cables being inserted and the second direction is along an upward to downward direction for the movement of the clip **2012**.

[0300] After insertion of the cable into the channel **2018**, the movable clip **2012** flexes upwardly under its inherent bias to retain the cables within the channel **2018**. As shown, the elongate portion **2028** of the clip **2012** also defines a certain amount of curvature that mates with the curved

portions of the upper and lower guide portions **2014, 2016** to assist with bend radius protection. As also shown, the clip **2012** defines a vertical wall **2040** at the opposing inner side **2042** of the finger tab **2032** that is configured to keep cables retained within the channel **2018**. The vertical wall **2040** defines a lip **2044** that extends partially over the inner side **2046** of the upper guide portion **2014** to provide extra protection against unwanted removal of cables from the cable management structure **2000**.

[0301] With the design thereof, including the flexible clip **2012**, the cable management structure **2000** acts as a push-in structure for facilitating insertion of the cables into the channel **2018**. Due to the tapered surfaces **2036, 2038** defined by the finger tab **2032**, the cables simply have to be pushed toward the slit **2024** of the cable management structure **2000** to automatically contact and flex the elongate portion **2028** of the clip **2012** downwardly. And, as noted above, after the clip **2012** has biased back to its original position, if the cables need to be removed, the clip **2012** has to be acted on by a technician to flex it down to expose the slit **2024** for removal of the cables.

[0302] Referring now to FIGS. **109-110**, an alternative embodiment of a cable management structure **2100** is shown. The cable management structure **2100** is similar in form and function to the cable management structure **2000** illustrated in FIGS. **101-108** and described above and also includes a flexible clip **2112**. In the version shown in FIGS. **109-110**, a portion of the flexible clip **2112** forms a part of the lower guide **2116** and includes curvature for guiding cables transversely out of the channel **2118**.

[0303] Another version of a cable management structure **2200** is illustrated in FIGS. **111-112**, the version of the cable management structure **2200** shown in FIGS. **111-112** defines a cover portion **2212** with a finger tab **2232** that has to be manually flexed downwardly in exposing the slit **2224** for insertion of cables. The cable management structure **2200** does not define a separately formed clip portion. The cover portion **2212** is designed as being integrally formed with the lower guide portion **2216** as shown, where the cover portion **2212** is flexible enough to elastically move with respect to the upper guide portion **2214** to expose the slit **2224**.

[0304] FIG. **113** illustrates another alternative embodiment of a cable management structure **2300**. The version **2300** shown in FIG. **113** is designed as a push-in structure for insertion of the cables into the channel **2318**. Similar to the management structure **2200** shown in FIGS. **111-112**, the cable management structure **2300** does not have a separate flexible clip for covering the slit **2324**. The lower guide portion **2316** is elastically flexible with respect to the upper guide portion **2314**. The lower guide portion **2316** is designed with an integrally formed blocker **2317** toward the rear end thereof. The blocker **2317** defines a tapered face **2338** that tapers toward the front of the cable management structure **2300**. The tapered face **2338** is designed to be automatically contacted by the cables for flexing of the lower guide portion **2316** during insertion of cables. Due to the tapered surface **2338**, the cables simply have to be inserted into the slit **2324** and once the cables approach the rear end **2325** of the slit **2324**, the lower guide portion **2316** is automatically contacted and flexed downwardly for complete insertion of the cables into the channel **2318**. After insertion, the lower guide portion **2316** flexes upwardly with the blocker **2317** preventing unwanted removal of cables from the channel **2318**. The lower guide portion **2316**

defines a finger tab **2332** adjacent the blocker **2317** for manual flexing of the lower guide portion **2316** for removal of cables.

[0305] FIG. **114** illustrates another alternative embodiment of a cable management structure **2400** that is provided as a push-in structure. In the version shown in FIG. **114**, both the upper and lower guide portions **2414**, **2416** are flexible for receiving the cables into the channel **2418**. The upper and lower guide portions **2414**, **2416** cooperatively define a notch **2415** that guides the insertion of the cables into the channel **2418**. When the upper and lower guide portions **2414**, **2416** are allowed to bias back to their original position, the upper and lower guides **2414**, **2416** abut each other to seal the side opening **2424** into the channel **2418**. In the version shown in FIG. **114**, the upper and lower guide portions **2414**, **2416** may be integrally formed as a single piece and can be mounted to a base portion **2410** via a dovetail type interlock structure **2412**.

[0306] FIGS. **115-116** illustrate another embodiment of a cable management structure **2500** that is similar in form and function to the version **2400** shown in FIG. **114**. Similar to the version **2400** shown in FIG. **114**, the cable management structure **2500** provides a push-in design where at least one of the upper guide portion **2514** and the lower guide portion **2516** are elastically flexible.

[0307] FIG. **117** illustrates yet another embodiment of a cable management structure **2600** where at least a portion of the lower guide **2616** is elastically flexible in exposing the channel **2618** for insertion of cables. As shown, the lower guide portion **2616** is provided with an integrally formed finger tab **2632** that facilitates guiding of the cables into the slit **2624** and into the channel **2618**. The finger tab **2632** defines a face **2636** that tapers down sideways for contact with the cables. As the cables are pushed-in toward the slit **2624**, the cables contact the finger tab **2632** and automatically move the tab **2632** downwardly for exposing the channel **2618** for insertion of the cables.

[0308] FIGS. **118-120** illustrate various alternative embodiments of cable management structures that utilize the push-through concept in automatic insertion of cables into a cable management channel and retaining therein. As discussed below, some of the cable management structures may be designed to be mounted to the optical fiber distribution elements **100** themselves and some may be designed to be mounted to various locations around the frame assemblies **110/120**.

[0309] FIG. **118** illustrates a version of a cable management structure **2700** that has a rigid fixation portion **2710** that can be mounted to a fixture and a pair of rubber flaps **2712** forming a push through portion for insertion of cabling into a channel **2718** defined by the rigid fixation portion **2710**.

[0310] FIG. **119** illustrates a version of a cable management structure **2800** where a rigid fixation portion **2810** defines two separate vertical cable channels **2818a**, **2818b**, each accessible via a push-through portion **2812** formed by two flexible rubber flaps. As shown, at the exit of the second channel **2818b** are provided curved portions **2820** that provide bend radius protection both in the up and down direction and in the lateral direction.

[0311] FIG. **120** illustrates a version of a cable management structure **2900** that includes a rigid fixation portion **2910**, where the rigid fixation portion **2910** is divided into two vertical channels **2918** separated by a curved radius

limiter **2920**. Each of the adjacent channels **2918** are accessed via push-through portions **2912** formed by two flexible rubber flaps similar to the embodiments discussed above.

[0312] As noted above, even though some of the cable management structures have been designed for routing cabling around the frame assemblies **110/120** housing the optical fiber distribution elements **100**, the push-through concepts can be used on the elements **100** themselves.

[0313] Even though the above described cable management structures have been illustrated and discussed herein as being mounted to and used with the optical fiber distribution elements **100** of the present disclosure, it should be noted that the inventive cable management structures can be utilized in other telecommunications panels and fixtures. The specifically depicted devices are only exemplary and are used to convey the inventive concepts provided by the cable management structures.

[0314] FIGS. **121-158** illustrate some example embodiments of strength member fixation structures that can be used on the fixed side of one of the fiber distribution elements housed by either the cross-connect assembly **10** or the inter-connect assembly **20** for fixing cabling to a side of the element **100** and directing cabling into the elements. It should be noted that the fixation structures can be designed to be mounted on either side **102/104** of an element **100**, depending on whether the element **100** is mounted on the right frame or the left frame of the cross-connect assembly **10** since the fixed sides of the cross-connect assembly is positioned toward the exterior. A similar scenario is applicable to the inter-connect assembly **20** depending upon which side of the element requires fixation.

[0315] In the depicted example, each optical fiber distribution element **100** is configured to receive an associated strength member fixation structure such that the fixation structures can be provided in a vertically stacked arrangement when mounted to vertically stacked optical fiber distribution elements **100**. In this manner, a cable carrying a large number of fibers can be fixed to a single fixation structure and the individual fibers can be led to different elements **100** on the vertical stack utilizing the cable guiding features of the stacked fixation structures. An example of an assembly that shows a given cable fixed with respect to each element **100** is illustrated in FIG. **134**. An example of an assembly where the fibers coming out of a single larger cable are distributed to a plurality of elements **100** in a vertical stack is illustrated in FIG. **135**.

[0316] Referring now to FIGS. **121-126**, one specific example embodiment of a strength member fixation structure **3000** is illustrated. The depicted fixation structure **3000** includes a base **3002** and a cable bracket **3004**. In the depicted example, the cable bracket **3004** is configured to be mounted to the base **3002** in one of two different angled orientations. In a first orientation, the cable bracket **3004** is snap-fit such that the bracket **3004** is angled downwardly with respect to a longitudinal axis **L** defined by the base **3002** of the fixation structure **3000**. In a second orientation, the same cable bracket **3004** can be snap-fit to the base **3002** such that the bracket **3004** is angled upwardly with respect to the longitudinal axis **L** defined by the base **3002**. The angled mounting of the bracket **3004** can be determined and selected by the needed cable routing extending toward the entry point of the optical distribution elements **100**. The angling of the cable bracket **3004** provides a smoother

transition from a vertically extending cable to a horizontal entry position for the elements **100**.

[0317] According to one example embodiment, the cable brackets **3004** may be angled approximately 45 degrees with respect to the longitudinal axis **L** defined by the base **3002**.

[0318] Still referring to FIGS. **121-126**, the cable bracket **3004** defines mounting structures **3006** that intermate with mounting structures **3008** provided on the base **3002** for the selective angled mounting of the bracket **3004**.

[0319] The intermating mounting structures provided by the cable bracket and the base for selective angled mounting of the cable bracket are illustrated in further detail in FIGS. **124-125**. As shown, the rear end **3010** of the base **3002** is provided with two angled walls **3012**, each defining a pair of mounting slots **3014**. Each mounting slot **3014** defines a wider receiver portion **3016** and a narrower retention portion **3018**. The cable bracket **3004** defines a pair of dovetail structures **3020** that are configured to align with the slots **3014** of a selected wall **3012** on the base **3002**. Each dovetail structure **3020** defines a stem portion **3022** and a larger retention portion **3024**. In addition to the dovetail structures **3022**, the cable bracket **3004** also defines a flexible latch **3026** that is configured to snap fit into a latch opening **3028** provided on each of the two angled walls **3012** on the base **3002**.

[0320] If the cable bracket **3004** needs to be angled down, the upper, downwardly-angled wall **3012a** is selected on the base **3002**. If the cable bracket **3004** needs to be angled up, the lower, upwardly-angled wall **3012b** is selected on the base. Once the desired mounting wall **3012** is selected on the base **3002**, the retention portions **3024** of the dovetail structures **3020** are aligned with and passed through the wider receiver portions **3016** of the slots **3014**. The cable bracket **3004** is then slid in a front to rear direction bringing the retention portions **3024** of the dovetail structures **3020** out of alignment from the wider receiver portions **3016** of the slots **3014**. In this manner, the cable bracket **3004** is prevented from being removed from the base **3002**. The sliding occurs until the flexible latch **3026** flexes under a bias, snapping into the latch opening **3028** that is positioned on the base **3002**, locking the cable bracket **3004** in the desired angled orientation relative to the base **3002**.

[0321] It should be noted that the dovetail structures **3020** of the cable bracket **3004** define a generally triangular profile with opposing angled faces **3030**. The angled faces **3030** are designed to abut upper or lower walls **3013** of the base **3002** in providing rigidity to the angled mounting of the cable bracket **3004** relative to the base **3002**. A fully mounted configuration is shown in FIG. **125**.

[0322] If the cable bracket **3004** needs to be removed from the base **3002** to reverse the angled orientation, the flexible latch **3026** is pressed until the latch **3026** clears the latch opening **3028** and the dovetail structures **3020** are slid in the rear to front direction.

[0323] Now referring back to FIGS. **121-123**, as shown, the cable bracket **3004** is the portion that initially receives the cable jacket before the fibers or tubes carrying the fibers are routed out for entry into the elements **100**. The cable bracket **3004** defines a cable channel **3032** that defines a turn portion **3034** for allowing cables to turn from a transverse direction toward the elements **100** to a parallel direction with respect to the elements **100**. By the time the cable enters the base **3002** of the fixation structure **3000**, the cable has

transitioned to a position that is generally parallel to the side of the optical distribution element(s) **100**.

[0324] The cable bracket **3004** may include an insert **3036** for providing grip to the cable jacket adjacent the outer end **3038** of the bracket **3004**. In certain embodiments, the grip insert **3036** may be shaped to provide fixation to certain types of cable jackets (e.g., flexible tube holders having a diameter of about 16 mm). Slots **3040** are provided for accommodating cable-ties that may be used to fix various types of cable jackets of the cable to the bracket **3004**.

[0325] A fixation clamp portion **3042** of the cable bracket **3004** for fixing a strength member of a cable is illustrated in FIG. **122**. It should be noted that the configuration and functionality of the fixation clamp **3042** is similar to that described in PCT Patent Application Serial Nos. PCT/EP2014/058196, filed Apr. 23, 2014 and PCT/EP2014/063717, filed Jun. 27, 2014, the entireties of which are hereby incorporated by reference, and therefore, further details relating thereto will not be discussed herein.

[0326] As shown, the fixation clamp **3042** is adjacent the inner end **3044** of the cable bracket **3004** and is positioned on the cable bracket **3004** prior to the turn portion **3034**.

[0327] As shown, a cover **3046** may be used to help guide the cabling from a transverse direction toward a parallel direction while providing bend radius protection. According to certain examples, the cover **3046** may be transparent.

[0328] The cable bracket **3004** is designed such that one or more methods of cable fixation can be utilized using the cable bracket **3004**. The grip insert **3036** may provide fixation to the jacket of the cable in addition to the cable-ties. The aramid yarns of the strength members may be additionally clamped by the fixation clamp **3042**. In certain embodiments, simply the jacket of the cable can be fixed to the cable bracket **3004** using the grip insert **3036** and cable-ties.

[0329] For example according to certain embodiments, 1 or 2 cables having a diameter between about 5-8.5 mm may be fixed by the grip insert **3036** and the cable-ties, wherein the strength members may be clamped by the fixation clamp **3042**. According to another example, if 3 or 4 of such cables are being led to the distribution elements, just the jackets may be fixed with the grip inserts **3036** and the cable-ties without the strength member fixation.

[0330] If a cable having a diameter between about 8-15 mm is used, the cable bracket **3004** may be able to only accommodate a single cable, where the jacket of the cable and the strength member is fixed to the cable bracket **3004**.

[0331] A flexible tube having a diameter of about 16 mm may be snap fit to the cable channel **3032** defined by the cable bracket **3004** and further fixed therein by the cover **3046**.

[0332] The base **3002** of the fixation structure **3000** is the part of the fixation structure that is mountable to a side of a given optical distribution element **100**. As discussed above with respect to the cable management structures such as structures **2000** that are mounted at the exit side of the elements **100**, each optical fiber distribution element **100** is provided with mounting features **106** (e.g., slots) for slidably receiving such structures. Similar to the cable management structures **2000** discussed above, the base **3002** of the fixation structure **3000** can include mounting features **3048** that are configured to mate with the mounting features in the form of slots **106** provided on the optical fiber distribution elements **100** for sliding in and snap-fitting the fixation structures **3000** to the optical fiber distribution elements **100**.

The mounting features **3048** provided on the base **3002** can include a dovetail configuration **3050** and can be slidably inserted into the slots **106** of the optical fiber distribution elements **100** as discussed above in detail for the cable management structures **2000**. As shown, similarly, a flexible tab **3052** provided on the base **3002** may be used to latch and fix the fixation structure **3000** relative to the optical fiber distribution element **100**. The flexible tab **3052** is also used to unlatch the fixation structure **3000** from the optical fiber distribution element **100** before the dovetail structures **3050** are slid in a direction opposite to the insertion direction for removing the fixation structure **3000** from the slots **106** of the optical fiber distribution element **100**.

[0333] Still referring to the base portion **3002** of the fixation structure **3000**, the base portion **3002** defines a set of rear groove plates **3054** and a set of front groove plates **3056**. The base **3002** also defines a gap **3058** between the front and rear groove plates **3056**, **3054**. The gap **3058** can be used to route fibers or tubes holding fibers upwardly or downwardly to different elements **100** on different levels. An example is shown in FIG. **135** as noted previously. Radius limiters **3060** may be provided on the base **3002** at the gap **3058** for providing bend radius protection while leading fibers or tubes upwardly or downwardly.

[0334] Provided toward the front **3062** of the base **3002** is also a tube-holder receiver **3064**. The receiver **3064** is configured to slidably receive a variety of different tube holders **3066**, where the configuration of the tube holders **3066** can be selected based on the different sizes of tubes carrying the fibers.

[0335] As shown in FIGS. **127-128**, a plurality of tube holders **3066** can be slidably inserted into the tube-holder receiver **3064**. The tube-holders **3066** may be coupled with a dovetail type interlock **3068**.

[0336] Similar to the cover **3046** shown for the cable bracket **3004**, a transparent cover **3070** can also be used on the base **3002** to protect the fibers or the fiber holding tubes. The cover **3070**, in the depicted example, is snap fit to the base **3002** and is designed to generally cover the gap **3058** provided on the base **3002**.

[0337] Another strength member fixation structure **3100** similar in shape and function to the fixation structure **3000** is illustrated in FIGS. **121-126**. The version **3100** illustrated in FIGS. **129-137** does not include a cover for the base portion **3102** of the fixation structure **3100**.

[0338] Now referring to FIG. **138**, it should be noted that although the above-described fixation structures **3000/3100** include cable brackets **3004/3104** that are fixedly mounted to the base portions **3002/3102** at an angle, in certain other embodiments, the cable brackets and the bases may define a free-hinging configuration. In such an embodiment of a fixation structure **3200**, the base **3202** and the cable bracket **3204** cooperatively define a hinge structure **3205** rather than fixed angled mounting for allowing rotation to the cable bracket **3204** along an axis that is parallel to the longitudinal axis **L** defined by the base **3202**. In certain embodiments, the movement can cover about a 120-degree path, extending from -60 degrees below a horizontal plane to +60 degrees above a horizontal plane going through the longitudinal axis of the base **3202**.

[0339] As shown, the cable bracket **3204** may include a covered tube or jacket holding portion **3233** adjacent the turn portion **3234**. The jacket holding portion **3233** may define a slit **3235** for insertion of fibers extending out of the

cable jacket once the jacket has been stripped and is designed to protect the fibers therein during pivotal movement of the cable bracket **3204**.

[0340] Another similar free-hinging design is illustrated for the fixation structure **3300** in FIGS. **139-142**. In the cable bracket **3304** of the fixation structure **3300** illustrated in FIGS. **139-142**, a curved wall **3333** may be used to protect the fibers extending from the cable bracket **3304** to the base **3302** during pivotal movement of the bracket **3304** with respect to the base **3302**.

[0341] In the free-hinging versions of the fixations structures **3200/3300** illustrated in FIGS. **138-142**, the base **3202/3302** may define integrally formed tube holders adjacent the front end rather than a receiver for housing separately inserted individual tube holders.

[0342] Even though the earlier versions of the strength member fixation structure **3000/3100** shown in FIGS. **121-137** and described above provide a fixed angle for the cable bracket **3004/3104** relative to the base **3002/3102**, the bracket **3004/3104** is still able to be removed from the base **3002/3102** and selectively mounted in one of two desired orientations. It should be noted that in certain embodiments, the cable bracket may simply be integrally formed with the base to provide a permanently angled mount. Such an example of a fixation structure **3400** is shown in FIGS. **143-146**. It should be noted that the fixation structure **3400** may be provided in two versions, a downwardly angled version and an upwardly angled version, depending on the needed routing.

[0343] Another version of a fixed integrally formed strength member fixation structure **3500** is shown in FIGS. **147-149**. In the version shown in FIGS. **147-149**, the cable bracket portion **3504** may be angled with respect to the base **3502** but only along the same horizontal plane. This configuration still provides a smooth transition for cables coming from a transverse direction toward a parallel direction relative to the sides of the distribution elements **100**. The fixation structure **3500** shown in FIGS. **147-149** essentially provides the same routing as when the free-hinging cable brackets **3204/3304** are horizontally aligned with the bases **3202/3302** in the versions shown in FIGS. **138-142**. However, in this version, the routing is provided in a permanently fixed manner. Again, in the version of the fixation structure **3500** shown in FIGS. **147-149**, the cable bracket **3504** may define a curved protection wall **3533** at the turn portion **3534** for protection and bend control of fibers or fiber holding tubes.

[0344] FIGS. **150-158** illustrate another version of a strength member fixation structure **3600** that may be used with the optical fiber distribution elements **100** of the present disclosure.

[0345] The version of the strength member fixation structure **3600** shown in FIGS. **150-158** is a universal type fixation structure that can be used to accommodate a variety of cable types, sizes, and diameters. The fixation structure **3600** can also be used to fix different numbers of cables as shown.

[0346] The strength member fixation structure **3600** is designed to provide strength member and jacket fixation without the use of friction based grip inserts or cable-ties.

[0347] In the depicted embodiment, the fixation structure **3600** defines a base **3602**. The base **3602** is generally a U-shaped structure forming a longitudinal cable channel **3632** for receiving one or more cables. The walls **3612** of the

U-shaped structure and the bottom **3614** of the cable channel **3632** can form clamping surfaces as will be discussed.

[0348] Adjacent the front end **3616** of the base **3602** is provided a strength member clamp structure **3642** that is formed from a downwardly biased metal member **3644**. The metal member **3644** defines hook portions **3646** for clamping the strength members against a top surface **3648** of the base **3602** under the bias of the spring-based metal member **3644**.

[0349] Along the sidewalls **3612** of the base are provided a series of pivot pins **3650** in a stepped configuration as shown. Spaced from the pivot pins **3650**, toward the front end **3616** of the base **3602** are a series of latch pins **3652** provided in a matching stepped configuration similar to the pivot pins **3650**.

[0350] A metallic clamp **3604** is configured to pivot about one of the pivot pins **3650** and latch into a corresponding latch pin **3652** at the front **3616** of the base **3602** to capture and fix the outer jacket of a given cable.

[0351] As shown in FIGS. **153-154**, the metallic clamp **3604** may include a biased spring member **3605** for pushing on a cable. FIG. **153** illustrates a version of the metallic clamp **3604** with a biased spring member **3605** that has a snap-on insert **3607** for providing additional grip features **3609**. Such grip features **3609**, instead of being provided with a separate insert, can be integrated into the spring member **3605** itself.

[0352] The pivotable metallic clamp **3604** is positioned on the base **3602** depending upon the number of cables or the cable sizes that are being fixed. Once an appropriate pivot pin **3650** is selected based on the number of cables or cable size, the clamp **3604** is pivoted down with a latch **3660** of the metallic clamp **3604** latching to a corresponding latch pin **3652** at the front **3616** of the base **3602**.

[0353] The fixation structure **3600** is shown in various configurations in clamping various numbers and sizes of cables in FIGS. **155-158**. As shown, even though the bottom **3614** of the cable channel **3632** may form a clamping surface in clamping smaller diameter cables, the vertical sidewalls **3612** defining the cable channel **3632** may also have chamfered edges **3666** that are used to clamp either larger cables or cables provided in a side-by-side arrangement, as shown in FIGS. **155-158**.

[0354] A fixation structure such as the structure **3600** shown in FIGS. **150-158** can be provided with mounting features for mounting to a side of an optical distribution element **100** similar to the versions discussed above.

[0355] Even though the above described strength member fixation structures have been illustrated and discussed herein as being mounted to and used with the optical fiber distribution elements **100** of the present disclosure, it should be noted that the inventive fixation structures can be utilized in other telecommunications panels and fixtures. The specifically depicted devices are only exemplary and are used to convey the inventive concepts provided by the strength member fixation structures.

[0356] Referring now to FIGS. **159-163**, the fan-out fixation assemblies **4000** that can be used in certain locations throughout the frame assemblies **110/120** is shown in closer detail.

[0357] The fan-out fixation assembly **4000** includes a fixation bracket **4002** that is configured to be mounted to portions of the frame assemblies **110/120** at desired loca-

tions and fan-out holders **4004** that are configured to be removably attached to the fixation bracket **4002**.

[0358] As shown, the fixation bracket **4002**, according to one embodiment, defines a generally U-shaped configuration with a rear wall **4006** and a pair of sidewalls **4008** extending from the rear wall **4006**. The rear wall **4006** defines fastener openings **4010** for mounting to a wall defined by one of the telecommunications frame assemblies **110/120**. The sidewalls **4008** define upper and lower latching slots **4012**, **4014** for receiving the fan-out holders **4004** with a snap-fit interlock as will be described in further detail.

[0359] In the example embodiment shown, the sidewalls **4008** extending from the rear wall **4006** of the bracket **4002** are spaced apart and provide room for accommodation of the fan-out holders **4004** that are coupled to the bracket **4002**. In this manner, the fan-out holders **4004** can be horizontally stacked on each sidewall **4008**, where the fan-outs are positioned toward the center of the bracket **4002**.

[0360] The upper and lower slots **4012**, **4014** provided on each sidewall **4008** may be large enough to accommodate the latching structures of a plurality of fan-out holders **4004** that are stacked along the sidewall **4008**. And, as shown, a support divider **4016** may split a first upper slot **4012a** from a second upper slot **4012b** on each sidewall **4008**. Similarly, a support divider **4016** may split a first lower slot **4014a** from a second lower slot **4014b** on each sidewall **4008**. Each sidewall **4008** may also define a lateral lip **4018** at top and bottom portions thereof that can abut a wall defined by the frame assemblies **110/120** and provide extra support against bending.

[0361] Referring now specifically to the fan-out holders **4004**, each fan-out holder **4004** defines a latch side **4020** and a fan-out holding side **4022**. The fan-out holding side **4022** defines a generally curved pocket **4024** for nesting of the fan-out thereagainst. The pocket **4024** defines surface texturing **4026**, in the form of a pin pattern according to the depicted example, that helps with gripping the jacket of a fan-out. The surface texturing **4026** can help provide protection against jacket slip during axial pull or cable torsion. It should be noted that the type of surface texturing depicted in the given embodiments are only exemplary and other types of surface texturing can be provided.

[0362] The fan-out holding side **4022** also defines openings **4028** for receiving cable-ties **4030** for securing the fan-outs against the fan-out holders **4004**. Once the fan-outs are positioned within the pockets **4024**, the cable-ties **4030** can be looped through the openings **4028** and around the fan-out jackets and tightened to secure the fan-outs to the holders **4004**. An example embodiment illustrating the use of the cable-ties **4030** is shown in FIG. **170**.

[0363] The latch side **4020** of the fan-out holder **4004** defines a pair of hook-like members **4032**, each having a horizontal portion **4034** and a vertical portion **4036**. The vertical portion **4036** is spaced apart from an abutment surface **4038** of the latch side **4020** such that the vertical portion **4036** forms a pocket **4040** for capturing the sidewall **4008** between the vertical portion **4036** and the abutment surface **4038**. As shown, the upper hook-like member **4032** is for placement over an upper top edge **4042** defined by each sidewall **4008** and the lower hook-like member **4032** is spaced apart and positioned for placement over a lower top edge **4044** defined on each sidewall **4008**, where the upper top edge **4042** defines the bottom end of each upper slot



**4012** on the sidewalls **4008** and the lower top edge **4044** defines the bottom end of each lower slot **4014** on the sidewalls **4008**.

[0364] Positioned between the spaced-apart hook-like members **4032** is a flexible latch **4046**. The flexible latch **4046** extends past the abutment surface **4038** of the latch side **4020** of the fan-out holder **4004** and is configured to be flexed back against a bias when being mounted to the sidewall **4008**.

[0365] As shown, when each fan-out holder **4004** is being placed on a sidewall **4008**, the upper and the lower hook-like members **4032** are brought adjacent a sidewall **4008**. The upper hook-like member **4032** is aligned with and passed through the upper slot **4012** and the lower hook-like member **4032** is aligned with and passed through the lower slot **4014**. And, then, the fan-out holder **4004** is slid vertically downward with the flexible latch **4046**, having been flexed back and riding along the inner side of the sidewall **4008**. When the flexible latch **4046** arrives at the lower slot **4014**, the latch **4046** snaps laterally to be captured against a lower bottom edge **4048** defined by the sidewall **4008**, where the lower bottom edge **4048** defines the top end of each lower slot **4014** on the sidewalls **4008**.

[0366] The cooperation of the flexible latch **4046** and the hook-like members **4032** keep the fan-out holders **4004** coupled to the sidewalls **4008**. As noted above, a plurality of fan-out holders **4004** can be placed on each sidewall **4008** in a horizontally stacked configuration as shown in FIG. **163**. In the depicted embodiment, the fan-out holding sides **4022** of the fan-out holders **4004** are positioned toward the center of the bracket **4002**.

[0367] If a fan-out or fan-out holder needs to be removed from the bracket **4002**, the latch **4046** can be flexed back laterally until the latch **4046** clears the lower bottom edge **4048** of the sidewall **4008**. Once the latch **4046** clears the lower bottom edge **4048**, the fan-out holder **4004** can be slidably lifted vertically to free the upper and lower hook-like members **4032** from the sidewall **4008**.

[0368] FIG. **164** illustrates an alternative embodiment of a fan-out holder **4104** that can be used with a bracket **4002** such as that shown in FIGS. **159** and **163**. The fan-out holder **4104** is similar in form and function to the version illustrated in FIGS. **159-163** and described above. In the version shown in FIG. **164**, a single upper hook-like portion **4132** is provided while the bottom portion of the fan-out holder **4104** defines an elastically flexible latch **4146**. The flexible latch **4146** is general biased upwardly and defines a tab **4148** for latching the fan-out holder **4104** against a bracket. When the fan-out holder **4104** is being mounted on a bracket such as the bracket **4002** shown in FIGS. **159** and **163**, the hook-like portion **4132** is initially slid over a top edge of a sidewall **4008** and moved vertically downwardly until the tab **4148** clears a bottom edge **4048** of a sidewall **4008** and snaps back upwardly to capture the bottom edge **4048** of the sidewall **4008** between the tab **4148** and the abutment surface **4138** defined by the fan-out holder **4104**.

[0369] In the version of the fan-out holder **4104** shown in FIG. **164**, if there is any pull on the fan-out, the pulling force is directly transferred on the flexible latch **4146**. The version of the fan-out holder **4004** shown in FIGS. **159-163** provides the advantage of transferring any pulling forces on the fan-out to the fixed portions of the fan-out holder **4004** such as the upper and lower hook-like members **4032**, while the

flexible latch **4046** is only used for latching the fan-out holder **4004** and does not experience any of the applied forces.

[0370] Another version of a fan-out holder **4204** is illustrated in FIG. **165**. The version of the fan-out holder **4204** is similar in form and function to the version **4104** illustrated in FIG. **164** except that fixed stop surfaces **4206** are provided on both sides of the flexible latch **4246**. This version provides the advantage of the fixed stop surfaces **4206** being able to absorb any axial pulling forces on the fan-out holder **4204** rather than transferring the entire force to a flexible portion of the fan-out holder **4204** such as the elastic latch **4246**.

[0371] Both of the versions **4104**, **4204** shown in FIGS. **164-165** are removed from a bracket **4002** by flexing down the elastic latch until the tab clears a bottom edge **4048** of a sidewall **4008**.

[0372] Now referring to FIGS. **166-170**, an alternative embodiment of a fan-out fixation assembly **4300** is illustrated. The fan-out fixation assembly **4300** is similar in form and function to the assembly **4000** shown in FIGS. **159-163** except for a few differences.

[0373] In the version of the fan-out fixation assembly **4300** shown in FIGS. **166-170**, the bracket **4302** is defined by a generally L-shaped structure, each defining a rear wall **4306** and a sidewall **4308** extending therefrom.

[0374] The rear wall **4306** defines fastener openings **4310** for mounting to a wall **12** defined by the telecommunications frame assemblies **110/120**. The sidewall **4308** defines a plurality of latching slots **4312** that are discretely spaced apart extending from the front toward the rear of the sidewall **4308**.

[0375] The generally L-shaped bracket **4302** is designed such that two of the brackets **4302** can be used in adjacent relationship together in an opposing configuration as shown in FIG. **166**. The rear walls **4306** are positioned in opposing directions while the sidewalls **4308** are positioned adjacent together, leaving enough room therebetween for the accommodation of the fan-out holders **4304**, as will be discussed below.

[0376] In the use of the fan-out fixation assembly **4300** shown in FIGS. **166-170**, the brackets **4302** and the fan-out holders **4304** are designed such that the fan-outs are generally positioned away from the sidewalls **4308**, rather than toward the center of the bracket **4302** as in the embodiment of FIGS. **159-163**.

[0377] Referring specifically to the fan-out holder **4304** in FIGS. **167-168** that is used with the bracket **4302**, each fan-out holder **4304** again defines a latch side **4320** and a fan-out holding side **4322**. The fan-out holding side **4322** defines a generally curved pocket **4324** for nesting of the fan-out thereagainst. The pocket **4324** defines surface texturing **4326**, in the form of ribs according to the depicted example, that helps with gripping the jacket of a fan-out. As noted above, the surface texturing **4326** can help provide protection against jacket slip during axial pull or cable torsion. And, as also noted above, the type of surface texturing depicted in the given embodiments are only exemplary and other types of surface texturing can be provided.

[0378] Similar to the fan-out holders **4004**, **4104**, **4204** depicted in FIGS. **159-165**, the fan-out holding side **4322** also defines openings **4328** for receiving cable-ties **4030** for securing the fan-outs against the fan-out holders **4304**. Once the fan-outs are positioned within the pockets **4324**, the

cable-ties **4030** can be looped through the openings **4328** and around the fan-out jackets and tightened to secure the fan-outs to the holders **4304**.

[0379] The latch side **4320** of the fan-out holder **4304** in FIGS. **167-168** defines a central slot **4340**. A flexible latch **4346** extends partially into the slot **4340**. The fan-out holder **4304** is designed such that the slot **4340** receives the entire sidewall **4308** of the bracket **4302** as the fan-out holder **4304** is slid horizontally across the bracket **4302**. The flexible latch **4346** defines a tab **4348** with a tapered face **4350** and a flat retention face **4352**. The tapered face **4350** is configured for contacting portions of the sidewall **4308** of the bracket **4302** for flexing of the latch **4346** while allowing sliding of the fan-out holder **4304** to a desired position on the sidewall **4308**. Once the desired position is reached, the latch **4346** snaps back under a bias into one of the latching slots **4312** with the flat retention face **4352** holding the fan-out holder **4304** against the aperture defining the latching slot **4312**.

[0380] A fully mounted fan-out holder **4304** is shown in FIG. **170** with the cable-ties **4030** used to fix the fan-out to the holder **4304**.

[0381] Another alternative embodiment of a fan-out fixation assembly **4400** is illustrated in FIGS. **171-172**. In the version illustrated in FIGS. **171-172**, the fan-out holder **4404** is provided as a double fan-out holder with fan-out holding features on opposite sides of the holder **4404** and a central slot **4440** for slidably receiving a sidewall **4408** of a bracket **4402** as shown in FIG. **172**. It should be noted that although the double fan-out holder **4404** of FIGS. **171-172** has been depicted without a latch structure, in certain embodiments, a latch structure may be incorporated into the holder **4404** similar to that shown in the version **4304** shown in FIGS. **167-168**, if a respective slotted bracket is utilized.

[0382] Another alternative embodiment of a fan-out holder **4504** is illustrated in FIGS. **173-175**. In the version shown in FIGS. **173-175**, the fan-out holder **4504** and a cable-tie **4530** are integrated together. As shown, the fan-out holder **4504** may define upper and lower notches **4532** for mounting against opposing edges of a bracket or within vertically spaced-apart latching slots. The body **4505** of the fan-out holder **4504** may be flexible enough to bend portions of the holder **4504** when placing on a bracket. As shown, an integrated cable-tie **4530** may be positioned to wrap-around a fan-out that has been placed within the pocket **4524** defined at the fan-out holding side **4522** and inserted through a retaining structure **4546** at the opposing side. Once the cable-tie **4530** has been wrapped around the fan-out and inserted through the retaining structure **4546**, the cable-tie **4530** may be cut to remove any excess length.

[0383] Even though the above described fan-out fixation assemblies and the associated brackets and holders have been illustrated and discussed herein as being used within the telecommunications frame assemblies **110/120** of the present disclosure, it should be noted that the inventive aspects can be utilized in any telecommunications fixture, such as a frame, a panel, or a rack, where cable fan-outs are utilized, as long as such fixtures are configured to receive the described brackets.

[0384] The various embodiments described above are provided by way of illustration only and should not be construed to limit the claims attached hereto. Those skilled in the art will readily recognize various modifications and changes that may be made without following the example

embodiments and applications illustrated and described herein, and without departing from the true spirit and scope of the disclosure.

What is claimed is:

1. A telecommunications frame assembly comprising:
  - a frame for housing a first set of fiber optic distribution devices in a vertically stacked arrangement on a right side of the frame and a second set of fiber optic distribution devices in a vertically stacked arrangement on a left side of the frame, wherein the frame defines top and bottom openings adjacent the outer edges of the frame at each of the right side and the left side for selectively leading cables to or from the fiber optic distribution devices to be mounted on the frame, the frame further defining a central vertical trough extending from a central top opening defined by the frame, wherein radius limiters are provided in vertically stacked arrangements at each of the right side and the left side of the frame for selectively guiding cabling between the first set and the second set of fiber optic distribution devices, wherein the radius limiters allow cabling to pass through the central trough between the right and left sides of the frame and/or into the central trough from either of the right and left sides of the frame for selective routing from or to the central top opening, the frame further defining a bottom trough that extends horizontally between the right and left sides of the frame, wherein each of the bottom openings adjacent the outer edges of the frame at the right and left sides communicate with the bottom trough and wherein the radius limiters at each of the right side and the left side of the frame also allow cabling to pass from the fiber optic distribution devices to the bottom trough.
2. A telecommunications frame assembly according to claim 1, wherein the frame is defined by a right frame and a left frame that are separated brought together in a side-by-side arrangement to form the frame.
3. A telecommunications frame assembly according to claim 2, wherein the right frame is configured to house the first set of fiber optic distribution devices and a plurality of the radius limiters for cabling extending from the first set of fiber optic distribution devices and wherein the left frame is configured to house the second set of fiber optic distribution devices and a plurality of the radius limiters for cabling extending from the second set of fiber optic distribution devices.
4. A telecommunications frame assembly according to claim 2, wherein the central top opening and the central trough extending from the central top opening are formed by combining the right and left frames in a side-by-side arrangement.
5. A telecommunications frame assembly according to claim 1, wherein a plurality of the telecommunications frame assemblies are provided in a side-by-side configuration.
6. A telecommunications frame assembly according to claim 5, wherein an overlength bay is provided between two of the telecommunications frame assemblies, wherein the overlength bay also defines a plurality of radius limiters provided in vertically stacked arrangement and a bottom trough portion for communicating with the bottom troughs of the telecommunications frame assemblies when the overlength bay is positioned between two of the telecommunications frame assemblies.

7. A telecommunications frame assembly according to claim 1, further comprising the first set of fiber optic distribution devices mounted in a vertically stacked arrangement on the right side of the frame and the second set of fiber optic distribution devices mounted in a vertically stacked arrangement on the left side of the frame.

8. A telecommunications frame assembly according to claim 7, wherein the first and second set of fiber optic distribution devices are elements defining a fixed chassis portion and a slidable drawer portion for allowing access to the interior of the drawer.

9. A telecommunications frame assembly according to claim 1, wherein either of the right side or the left side of the frame are configured for mounting fiber fan-out fixation assemblies including fiber fan-out holders and brackets for removably mounting the fiber fan-out holders.

10. A telecommunications frame assembly according to claim 1, wherein the radius limiters provided in vertically stacked arrangements at each of the right side and the left side of the frame include a first set of radius limiters defined by overlength drums and a second set of radius limiters defined by bundle collectors, wherein the overlength drums are configured to guide cabling toward the bundle collectors for either passing cabling through the central trough to an opposing side of the frame or into the central trough for communicating with the central top opening or into the bottom trough.

11. A telecommunications frame assembly according to claim 1, further comprising door mounts at the top and bottom of each of the right and left sides of the frame for mounting pivotally openable doors.

12. A telecommunications frame assembly according to claim 11, wherein each mounted door includes a latch system that allows any mounted door to be pivotally openable in either direction.

13. A telecommunications frame assembly according to claim 12, wherein the latch system at each side of the door includes a height-adjustable spacer for providing a predetermined amount of spacing between a bottom edge defined by a main portion of the door and the respective door mount at each side of the door.

14. A telecommunications frame assembly according to claim 13, wherein the height-adjustable spacer is provided in the form of a polymeric threaded nut that is threaded on a vertical rod of the latch system at each side of the door, wherein the vertical rod at each side of the door is configured to be inserted into a respective door mount for providing pivotability to the door.

15. A telecommunications frame assembly according to claim 14, wherein the spacer contacts a counter stop structure to limit further upward movement of the spacer after the spacer has been vertically adjusted.

16. A telecommunications frame assembly comprising:  
a frame for housing a set of fiber optic distribution devices in a vertically stacked arrangement along a central portion of the frame, wherein the frame defines a vertical trough adjacent an outer edge at a right side of the devices and a vertical trough adjacent an outer edge at a left side of the devices, wherein the frame defines top openings adjacent the outer edges of the frame at each of the right side and the left side of the frame

communicating with the vertical troughs for selectively leading cables to or from the fiber optic distribution devices to be mounted at central portion of the frame, wherein at least one of the right side or the left side includes radius limiters provided in a vertically stacked arrangement within the vertical trough for leading cabling between the devices and the top openings, wherein at least one of the right side or the left side is also configured for mounting fiber fan-out fixation assemblies including fiber fan-out holders and brackets for removably mounting the fiber fan-out holders within the vertical trough.

17. A telecommunications frame assembly according to claim 16, further comprising the fiber optic distribution devices mounted in a vertically stacked arrangement on the frame.

18. A telecommunications frame assembly according to claim 17, wherein the fiber optic distribution devices are elements defining a fixed chassis portion and a slidable drawer portion for allowing access to the interior of the drawer.

19. A telecommunications frame assembly according to claim 16, wherein the radius limiters provided in vertically stacked arrangement include a first set of radius limiters defined by hook drums and a second set of radius limiters defined by overlength drums, wherein the hook drums are configured to guide cabling toward the overlength drums for passing cabling through at least one of the top openings.

20. A double-hinging door for a telecommunications frame, the door comprising:

a main portion for providing closure for the telecommunications frame, the main portion defining a bottom edge of the door, the door defining a right side and a left side;

a hinge rod at both the right side and the left side of door configured for insertion into hinge openings defined by door mounts of the telecommunications frame for allowing the door to be selectively pivotable in either a clockwise or a counterclockwise direction for opening;

a handle on each of the right side and the left side associated with a respective hinge rod on the right side and the left side for moving the hinge rod vertically upwardly out of a respective hinge opening when the handle is brought from a closed position to an open position; and

a height-adjustable spacer provided on the hinge rod at each of the right and left sides of the door; each spacer configured to protrude from the bottom edge of the main portion of the door and be positioned between the bottom edge and a respective door mount when the handle associated with that spacer is in the closed position.

21. A door according to claim 20, wherein the height-adjustable spacer is provided in the form of a polymeric threaded nut that is threaded on the hinge rod at each of the right and left sides of the door.

22. A door according to claim 20, wherein the spacer contacts a counter stop structure to limit further upward movement of the spacer after the spacer has been vertically adjusted.

\* \* \* \* \*