



US008654018B2

(12) **United States Patent**
Warther

(10) **Patent No.:** **US 8,654,018 B2**

(45) **Date of Patent:** ***Feb. 18, 2014**

(54) **PRINTED PLANAR RFID ELEMENT
WRISTBANDS AND LIKE PERSONAL
IDENTIFICATION DEVICES**

(58) **Field of Classification Search**
USPC 235/487, 492; 343/718, 702, 700 MS,
343/848

See application file for complete search history.

(75) Inventor: **Richard O. Warther**, West Chester, PA
(US)

(56) **References Cited**

(73) Assignee: **Vanguard Identificaiton Systems, Inc.**,
West Chester, PA (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 300 days.

4,157,540 A 6/1979 Oros
4,212,393 A 7/1980 Lenkoff
4,333,072 A 6/1982 Beigel
4,549,264 A 10/1985 Carroll et al.

(Continued)

This patent is subject to a terminal dis-
claimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/951,749**

WO 8404493 A1 11/1984
WO 8907052 A1 8/1989
WO 2006052422 A2 5/2006
WO 2007011514 A2 1/2007

(22) Filed: **Nov. 22, 2010**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2011/0226861 A1 Sep. 22, 2011

Office Action issued Aug. 8, 2012 in U.S. Appl. No. 11/967,502.

(Continued)

Related U.S. Application Data

Primary Examiner — Huedung Mancuso

(63) Continuation-in-part of application No. 11/967,502,
filed on Dec. 31, 2007, and a continuation-in-part of
application No. 11/735,891, filed on Apr. 16, 2007,
which is a continuation-in-part of application No.
11/099,998, filed on Apr. 6, 2005, now Pat. No.
7,204,652, and a continuation-in-part of application
No. 12/497,031, filed on Jul. 2, 2009.

(74) *Attorney, Agent, or Firm* — Panitch Schwarze Belisario
& Nadel LLP

(60) Provisional application No. 61/263,186, filed on Nov.
20, 2009, provisional application No. 60/882,623,
filed on Dec. 29, 2006.


(57) **ABSTRACT**

Each personal identification device includes a planar identi-
fication element with at least a core of flexible, porous and
preferably microvoided polymer sheet material and a planar
RFID assembly encoded with a unique electro/magnetic code
permanently and integrally joined together with the core. The
sheet material is sufficiently porous to collapse around the
core so the sheet product remains planar yet flexible. A sepa-
rate carrier can be provided or devices can be made in batches
with scoring define one or more individual RFID devices
removable from a remainder of a sheet product.

(51) **Int. Cl.**
H01Q 1/12 (2006.01)

(52) **U.S. Cl.**
USPC **343/718**

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,560,445 A	12/1985	Hoover et al.	6,484,947 B1 *	11/2002	Miyata	235/492
4,578,572 A	3/1986	Hice	6,581,824 B1	6/2003	McClure et al.	
4,598,275 A	7/1986	Ross et al.	6,588,658 B1	7/2003	Blank	
4,658,357 A	4/1987	Carroll et al.	6,674,923 B1	1/2004	Shih et al.	
4,682,415 A	7/1987	Adell	6,693,544 B1	2/2004	Hebbecke	
4,694,283 A	9/1987	Reeb	6,700,493 B1	3/2004	Robinson	
4,717,177 A	1/1988	Boram	6,724,690 B1	4/2004	Endo et al.	
4,807,908 A	2/1989	Gerbel	6,769,718 B1	8/2004	Warther et al.	
4,851,815 A	7/1989	Enkelmann	6,779,727 B2	8/2004	Warther	
4,861,644 A	8/1989	Young et al.	6,782,648 B1	8/2004	Mosher, Jr.	
4,973,944 A	11/1990	Maletta	6,784,017 B2	8/2004	Yang et al.	
4,978,146 A	12/1990	Warther et al.	6,836,215 B1	12/2004	Laurash et al.	
5,032,823 A	7/1991	Bower et al.	6,888,502 B2	5/2005	Beigel et al.	
5,106,124 A	4/1992	Volkman et al.	6,924,688 B1	8/2005	Beigel	
5,115,223 A	5/1992	Moody	6,971,200 B2	12/2005	Valenti, Jr.	
5,218,343 A	6/1993	Stobbe et al.	6,992,952 B2	1/2006	Endo et al.	
5,233,167 A	8/1993	Markman et al.	6,994,262 B1 *	2/2006	Warther	235/492
5,340,968 A	8/1994	Watanabe et al.	7,022,385 B1	4/2006	Nasser	
5,366,249 A	11/1994	Diemert	7,042,360 B2	5/2006	Light et al.	
5,381,137 A	1/1995	Ghaem et al.	7,071,826 B2	7/2006	Peterson	
5,430,441 A	7/1995	Bickley et al.	7,109,871 B2	9/2006	Lentine et al.	
5,444,223 A	8/1995	Blama	7,119,690 B2	10/2006	Lerch et al.	
5,446,447 A	8/1995	Carney et al.	7,187,055 B2	3/2007	Beigel	
5,448,110 A	9/1995	Tuttle et al.	7,188,764 B2	3/2007	Penuela	
5,478,991 A	12/1995	Watanabe et al.	7,204,425 B2	4/2007	Mosher, Jr. et al.	
5,492,558 A	2/1996	Miller et al.	7,204,652 B2	4/2007	Warther	
5,493,805 A	2/1996	Penuela et al.	7,207,488 B2	4/2007	Hammerslag et al.	
5,495,981 A	3/1996	Warther	7,225,993 B2	6/2007	Warther	
5,497,140 A	3/1996	Tuttle	7,230,519 B2	6/2007	Coughlin et al.	
5,503,665 A	4/1996	Miller et al.	7,240,446 B2	7/2007	Bekker	
5,512,879 A	4/1996	Stokes	7,316,358 B2	1/2008	Kotik et al.	
5,528,222 A	6/1996	Moskowitz et al.	7,327,251 B2	2/2008	Corbett, Jr.	
5,529,345 A	6/1996	Kohls	7,375,638 B2	5/2008	Light et al.	
5,531,482 A	7/1996	Blank	7,377,447 B2	5/2008	Oberle	
5,560,970 A	10/1996	Ludeb uhl	7,450,012 B2	11/2008	Harmon	
5,574,470 A	11/1996	de Vall	7,454,855 B2	11/2008	Kotik et al.	
5,581,257 A	12/1996	Greene et al.	7,520,078 B2	4/2009	Ali et al.	
5,609,716 A	3/1997	Mosher, Jr.	7,584,896 B2	9/2009	Warther	
5,615,504 A	4/1997	Peterson et al.	7,845,569 B1	12/2010	Warther et al.	
5,646,592 A	7/1997	Tuttle	7,909,955 B2	3/2011	Warther	
5,682,143 A	10/1997	Brady et al.	2001/0023014 A1	9/2001	Patel et al.	
5,708,419 A	1/1998	Isaacson et al.	2002/0084325 A1	7/2002	Reardon	
5,719,586 A	2/1998	Tuttle	2002/0087394 A1	7/2002	Zhang	
5,743,567 A	4/1998	Warther	2003/0016122 A1	1/2003	Petrick	
5,769,457 A	6/1998	Warther	2003/0042317 A1	3/2003	Behm et al.	
5,776,278 A	7/1998	Tuttle et al.	2003/0042731 A1	3/2003	Li	
5,781,110 A	7/1998	Habeger, Jr. et al.	2003/0173408 A1	9/2003	Mosher et al.	
5,798,984 A	8/1998	Koch	2003/0174049 A1	9/2003	Beigel et al.	
5,799,426 A	9/1998	Peterson	2004/0090868 A1 *	5/2004	Endo et al.	368/10
5,838,253 A	11/1998	Wurz et al.	2004/0091659 A1	5/2004	Banks et al.	
5,863,016 A	1/1999	Makwinski et al.	2004/0104274 A1	6/2004	Kotik et al.	
5,863,076 A	1/1999	Warther	2004/0111335 A1	6/2004	Black et al.	
5,883,576 A	3/1999	De La Huerga	2004/0188010 A1	9/2004	Chaoui	
5,912,981 A	6/1999	Hansmire et al.	2005/0097896 A1	5/2005	Critchley et al.	
5,935,308 A	8/1999	Siddiqui et al.	2005/0108912 A1	5/2005	Bekker	
5,939,181 A	8/1999	Kumano et al.	2005/0146435 A1	7/2005	Girvin et al.	
5,963,134 A	10/1999	Bowers et al.	2005/0184874 A1	8/2005	Mosher	
5,973,598 A	10/1999	Beigel	2005/0205202 A1	9/2005	Chaoui et al.	
5,973,600 A	10/1999	Mosher, Jr.	2006/0019745 A1	1/2006	Benbrahim	
5,979,941 A	11/1999	Mosher, Jr. et al.	2006/0032907 A1	2/2006	Zercher	
5,997,042 A	12/1999	Blank	2006/0037502 A1	2/2006	Warther	
6,010,159 A	1/2000	Warther	2006/0076402 A1	4/2006	Lerch et al.	
6,039,356 A	3/2000	Warther et al.	2006/0077060 A1	4/2006	Lerch et al.	
6,050,622 A	4/2000	Gustafson	2006/0087437 A1	4/2006	Lerch et al.	
6,078,791 A	6/2000	Tuttle et al.	2006/0091671 A1	5/2006	Raming	
6,089,611 A	7/2000	Blank	2006/0124757 A1 *	6/2006	Warther	235/492
6,124,377 A	9/2000	Kaiser et al.	2006/0129308 A1	6/2006	Kates	
6,144,303 A	11/2000	Federman	2006/0192674 A1	8/2006	Roberta	
6,181,287 B1	1/2001	Beigel	2006/0200674 A1	9/2006	Welker et al.	
6,192,253 B1	2/2001	Charlier et al.	2006/0230661 A1	10/2006	Bekker	
6,290,138 B1	9/2001	Ohno et al.	2007/0008138 A1	1/2007	Mosher et al.	
6,305,716 B1	10/2001	Warther et al.	2007/0012771 A1	1/2007	Singleton	
6,325,294 B2	12/2001	Tuttle et al.	2007/0018832 A1	1/2007	Beigel et al.	
6,441,736 B1	8/2002	Leighton	2007/0026144 A1	2/2007	Park et al.	
6,457,643 B1	10/2002	Way	2007/0028495 A1	2/2007	Kotik et al.	
			2007/0120687 A1	5/2007	Lerch et al.	
			2007/0159332 A1	7/2007	Koblasz	
			2007/0194129 A1	8/2007	Jones	
			2007/0199988 A1	8/2007	Labgold et al.	

(56)

References Cited


OTHER PUBLICATIONS

U.S. PATENT DOCUMENTS

2007/0215711	A1 *	9/2007	Warther	235/492
2008/0236011	A1	10/2008	Bekker	
2008/0290176	A1	11/2008	Fleet	
2009/0009412	A1 *	1/2009	Warther	343/718
2010/0065648	A1	3/2010	Warther	

EP Patent Application 07255085.8; European Search Report dated Feb. 27, 2009, 10 pages.
Office Action issued Jan. 3, 2013 in U.S. Appl. No. 11/967,502.

* cited by examiner






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12








FIG. 13






FIG. 18




FIG. 21




FIG. 19




FIG. 22




FIG. 20

1

PRINTED PLANAR RFID ELEMENT WRISTBANDS AND LIKE PERSONAL IDENTIFICATION DEVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a non-provisional of U.S. Patent Application No. 61/263,186 filed Nov. 20, 2009 and is a continuation in part of application Ser. No. 11/967,502 filed Dec. 31, 2007 which is related to U.S. Patent Application No. 60/882,623 filed Dec. 29, 2006, and incorporated by reference herein in its entirety. It is further a continuation-in-part of application Ser. No. 11/735,891 filed Apr. 16, 2007 and incorporated by reference herein. Through application Ser. No. 11/735,891, it is a continuation-in-part of application Ser. No. 11/099,998 filed Apr. 6, 2005, now U.S. Pat. No. 7,204,652. It is further a continuation in part of application Ser. No. 12/497,031 filed Jul. 2, 2009.

BACKGROUND OF THE INVENTION

The present invention relates to sheet products and, in particular, to printed form sheet products with RFID capabilities used for or in personal identification devices.

BRIEF SUMMARY OF THE INVENTION

In one aspect, the invention is a personal identification device comprising: a planar radio frequency identification element, the element including a flexible core having opposing first and second major opposing outer sides and formed from at least one strip of a flexible, microvoided, polymer sheet material, and a planar radio frequency transponder assembly including a planar electro/magnetic data storage element and a planar antenna permanently and integrally fixed with at least an inner major side of the flexible, porous polymer sheet material, the at least one microvoided, polymer sheet material core strip varying in thickness in the element, the at least one flexible, porous polymer sheet material core strip being thinned over the planar radio frequency transponder assembly in comparison to thicknesses of the at least one flexible, porous polymer sheet material core strip adjoining the planar radio frequency transponder assembly; and carrier means configured for holding the planar radio frequency identification element and for releasably securing the planar radio frequency identification element to a user to be identified by the planar radio frequency identification element.

In another aspect, the invention is a method of making a personal identification device comprising the steps of: providing an at least generally planar RFID element including first and second opposing major planar outer sides with indicia printed on at least one of the outer sides; providing a plastic band having an RFID element holder and at least a first strap extending away from the RFID element holder; and securing the generally planar RFID element to band at the RFID element holder.

In yet another aspect, the invention preferably is an RFID element made by a method comprising the steps of: printing indicia on a first side of a first flexible planar substrate sheet having major opposing first and second sides and uniform thickness between the major sides; applying a first one of either a radio frequency identification array antenna and a radio frequency identification array printed circuit chip to the second major side of the first planar substrate sheet; separately applying a second, remaining one of the radio frequency identification array antenna and the radio frequency

2

identification array printed circuit chip to the second major side of the first planar substrate sheet in operative overlying relationship and in connection with the first applied one to form an operative radio frequency identification array on the first planar substrate sheet; fixedly and permanently joining a first major outer side of a second planar substrate sheet to the first major side of the first planar substrate sheet overlying the applied antenna and printed circuit chip to form at least part of a multilayer planar core having first and second major outer sides, at least one of the first and second planar substrate sheets being microvoided; fixedly and permanently applying at least a first planar cover sheet to at least the first major outer side of the planar core; and scoring the planar core and at least first planar cover sheet to define at least one multilayer, integral, individual planar radio frequency identification element removable from the core and at least first planar cover sheet, the planar radio frequency identification element containing the operative radio frequency identification array and the planar radio frequency identification element having opposing major planar sides fitting into an area no greater than about three and five-eighths by about two and three-eighths inches.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of preferred embodiments of the invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there is shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

In the drawings, which are at least partially diagrammatic:

FIG. 1 is a perspective view of an exemplary preferred wristband of the present invention;

FIG. 2 is an exploded view of the wristband of FIG. 1;

FIG. 3 is a perspective view of a first alternate embodiment exemplary wristband of the present invention;

FIG. 4 is a side elevation view of the wristband of FIG. 3;

FIG. 5 is a side elevation view of a second alternate embodiment, exemplary wristband of the present invention;

FIG. 6 is a side elevation view of a third alternate embodiment, exemplary wristband of the present invention;

FIG. 7 is a side elevation view of a fourth alternate embodiment, exemplary wristband of the present invention; and

FIG. 8 is a side elevation exploded view of a fifth alternate embodiment, exemplary wristband of the present invention;

FIG. 9 depicts a printed sheet product construction for sixth alternate embodiment wristbands of the present invention;

FIG. 10 is a perspective view of one of the wristbands of the sheet product of FIG. 9;

FIG. 11 is a perspective view of a seventh alternate embodiment wristband of the present invention;

FIG. 12 is a perspective view of an eighth alternate embodiment wristband of the present invention;

FIG. 13 is a perspective view of a ninth alternate embodiment wristband of the present invention;

FIG. 14 is a plan view of a tenth alternate embodiment wristband of the present invention;

FIG. 15 is a perspective view of an eleventh alternate embodiment wristband of the present invention;

FIG. 16 is a cross-sectional view of an exemplary individual radio frequency identification element;

FIG. 17 is a plan view of a radio frequency transponder assembly as might be used in the individual identification elements and devices of the present invention;

FIGS. 18-20 depict the fabrication of another embodiment of the invention;

FIG. 21 is a side elevation of the planar radio frequency identification (“RFID”) element with planar radio frequency transponder assemblies resulting from FIGS. 18-20; and

FIG. 22 shows a slightly different alternative construction.

DETAILED DESCRIPTION OF THE INVENTION

Certain terminology is used in the following description for convenience only and is not limiting. The words “right,” “left,” “lower” and “upper” designate directions in the drawings to which reference is made. The words “inwardly” and “outwardly” refer to directions toward and away from, respectively, the geometric center of the stated component and designated parts thereof. The terminology includes the words above specifically mentioned, derivatives thereof and words of similar import. Furthermore, the term “electro/magnetic” is used to refer generally to devices that are electrical or magnetic or both and other than photonic in character, function and/or data storage or transmission.

In the drawings, like numerals indicate like elements. FIGS. 1 and 2 depict a presently preferred embodiment wrist-band type identification device of the present invention indicated generally at 100. Device 1000 includes a planar radio frequency identification (“RFID”) element 10 with planar radio frequency transponder assembly indicated diagrammatically in phantom at 27 and a carrier 110, which is a remainder of the device 1000 and is configured to receive and hold the printed planar radio frequency identification element 1010 and releasably secure the planar radio frequency identification element 1010 to a user (not depicted) who can be uniquely identified by the planar radio frequency identification element 1010 when properly interrogated or polled. The carrier 110 includes a relatively enlarged holder portion or simply “holder” indicated generally at 120 and an attachment portion indicated generally at 115 connected with the holder 120 and configured to releasably secure the holder 120 to the user. Attachment portion 115 includes at least one strap portion or simply “strap” 130 and, in this embodiment, a second strap 140. The holder 120 is configured to receive and hold the printed planar radio frequency identification element 1010. The straps 130, 140 are collectively configured at least by sizing and shaping to releasably secure the printed planar radio frequency identification element 1010 in holder 120 to a user (not depicted). Strap 130 has a first end 130a secured and with the holder 120. Second strap 140 has a first end 140a that in this embodiment is also secured with the holder 120 on a side of the holder 120 opposite from the at least one end 130a.

FIG. 2 depicts a presently preferred construction of device 100. The straps 130, 140 are preferably formed in a one piece band 116 with a third portion, a central portion 118, monolithically and fixedly connected with the first ends 130a, 140a of the first and second strap portions 130, 140. Holder 120 preferably is provided by two half shell portions, a front half 122 and a rear half 124 secured around the central portion 118 of the band 116. The halves 122, 124 may be joined by any of a variety of known connections. Preferably, back half 124 is provided with a back wall 124a supporting a plurality of posts 124b, which are sized to be received in a plurality of opposing bores 122b (in FIG. 1 with ends of posts 124b) supported at the outer corners of the front wall 122a of front half 122. The posts 124b are held in the bores 122b in any of several different ways. The posts 124b are preferably adhesively joined or solvent or ultrasonically welded with the bores 122b. The posts 124b and bores 122b can alternatively (or additionally)

be configured for snap or friction (press) securement or screws can be passed through back wall 124a and substituted for posts 124b to be received in bores 122b. Preferably, central portion 118 of band 116 is generally the same shape as the shell halves 122, 124 and is sized sufficiently large to require the provision of cutouts 118a at its corners to pass posts 124b and provide an interference engagement between the band 116 and holder 120, thereby preventing the band 116 from being slid from the holder 120. The planar radio frequency identification element 1010 is preferably captured within holder 120 between the front half 122 and the band 118.

Though not required for RFID operation, the front half shell 122 can be provided with an opening 122c to expose at least a portion a central of one major planar outer side 1014 of the planar radio frequency identification element 1010, preferably a side bearing printed indicia or other printing indicated generally at 1022. The printing 1022 may include one or more static fields 1034 (in phantom), which would not contain data that could be used to identify either the planar radio frequency identification element 1010 or the user to whom it was assigned. It typically would but does not have to be repeated identically on multiple other copies of the element. Element 1010 preferably does include one or more variable data fields, two being indicated at 1024 and 1025. Variable date field with 1025 is preferably printed with machine readable bar code indicia that contains a unique code that is the same as or that can at least can be cross referenced against the code of the RFID signal generated by the element 1010 to uniquely identify the element 1010 and/or its assigned user. Variable data field 1024 preferably is printed with legible (human readable) alphanumeric characters that may represent the same code as that of the bar code variable data field 1025 or the same code as the code of the RFID signal or yet some other code that at least can be cross-referenced against the RFID and/or bar code(s). Preferably the variable data fields 1024, 1025 are encoded with the same unique code that uniquely identify the device 100 and its element 1010 from other like devices and elements and thereby uniquely identify one user to whom the code(s) and device are provided or otherwise assigned.

Band 116 is preferably at least about 15 cm (6 inches) long and preferably adjustable in total length but could be longer and/or of different form for releasable securement around the leg, arm, neck (including a necklace), head or even waist of the user. Preferably, strap portion 130 is provided with a slide catch 132 at its distal, free end 130b of the type now commonly found in use on various plastic slide ties (e.g. cable ties, fence ties, etc.). Strap portion 140 is further preferably provided at its opposing, second distal free end 140b with a series of serrations 142 each having sloping front surfaces 142a for slide entry into and through the catch and transverse end surfaces 142b for interference with the catch 132 preventing strap end 140b from being backed out of the catch 132. Strap portion 140 can also be provided with transverse grooves 144 or other lines of weakness to permit the removal of any desired amount of excess strap 140 from the free end 140b.

FIGS. 3 and 4 depict a first alternate embodiment personal RFID device of the present invention in the form of a wrist-band indicated generally at 2100, with carrier 2110 carrying a planar RFID element 1010 of FIGS. 1-2. Carrier 2110 includes a central, planar RFID element holder portion or simply “holder” indicated generally at 2120 and an attachment portion indicated generally at 2115 in the form of one strap portion or strap 2130 having at least one end, a first end 2130a, secured and preferably fixed with the holder 2120, a remainder of the strap extending away from the first end 2130a. The strap 2130 has a second end 2130b that is also be

5

secured and fixed with the holder **2120** on a side of the holder opposite from the at least one end **2130a**. The strap **2130** is preferably at least partially expandable. It may be provided with an expandable portion (not depicted) or, more preferably, the holder **2120** and strap **2130** are formed together in one continuous, unbroken piece from an expandable material such as being molded in one band (also indicated by **2115**) from a thermoplastic elastomeric (TPE) like a silicone or ethylene propylene diene monomer (EPDM) rubber. The exposed side **1014** of the RFID element **1010** bears visible printing (indicated diagrammatically by phantom box **1022**), the contents of which have already been discussed.

Referring to FIG. 5, a second alternate embodiment RFID wristband type personal identification device of the present invention is indicated at **2200** with a planar RFID element **1010** and a carrier **2210** having a central holder portion (i.e. “holder”) **2220** and an attachment portion **2215** including first and second strap portions or straps, **2230**, **2240**, each having a first end **2230a**, **2240a** secured and preferably fixed with the central holder **2220**, and a second, free end **2230b**, **2240b** extending away from the holder **2210** and the fixed end of the strap. Where two straps **2230**, **2240** are provided and each strap has one end attached to the holder **2220** (e.g. **2230a**, **2240a**) and one opposite, free end (e.g. **2230b**, **2240b**), a fastening may be provided to form a closed loop with free ends **2230b**, **2240b** to at least temporarily or releasably secure the loop around part of a user. One such temporary fastening is indicated generally at **2260** in FIG. 35 and includes two, releasably mating portions **2260a**, **2260b**, which are loop and hook portions, respectively, of a releasable flexible fabric strip known as Velcro®.

FIG. 6 depicts a third alternate embodiment RFID wristband type of personal identification device of the present invention indicated generally at **2300** with a planar RFID element **1010** and a carrier portion **2310** having a holder portion (“holder”) **2320** and an attachment portion **2315** in the form of a one piece band **2316** with enlarged portion **2318** and a single strap **2330** having a first end **2330a** secured and preferably fixed with the enlarged central portion **2318** of holder **2320** and a second free end **2330b**. Again, a releasable fabric strip fastening **2360** is provided, this time with a first one of the two portions **2360a**, **2360b** attached to an underside of the holder **2320** opposite the upper side of the holder **2320** on which the RFID element **1010** is displayed, and a second, remaining one of the portions **2360a**, **2360b** attached to a surface of the strap **2330** at or at least proximal to its second end **2330b** where it underlies and faces the underside of the enlarged central portion **238** of holder **2320** and the first fastening portion **2360a**. The second end **2330b** is held on a user’s wrist and the remainder of the device **2300** is wrapped around the user’s wrist and onto the second end **2330b** sufficiently for the fastening portions **2360a**, **2360b** to overlap in facing, juxtaposed orientation and releasably mate.

FIG. 7 depicts a fourth alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **2400** with a planar RFID element **1010** and a carrier portion **2410** including a holder **2420** and an attachment portion **2415** including a one piece band **2416** with enlarged portion **2418** and one strap **2430**, which is a slight variation of the third alternate embodiment. The holder **2420** is provided with a loop **2420c** on an outer edge of the holder **2420** opposite the edge to which the first end **2430a** of the strap **2430** is fixed and preferably part of a one-piece band **2316**. Mating first and second portions **2460a**, **2460b** of the flexible fabric releasable fastening **2460** are again provided, a first releasable fastening portion **2460b** on one major side **2430c** of the strap **2430** at or at least proximal to the second,

6

free end **2430b** of the strap. A second, remaining fastening portion **2460a** is also provided on the one major side **2430c** of the strap **2430** proximal to the second, free end **2430b** of the strap but spaced inwardly or more proximal to end **2430a** along the strap **2430** from the first releasable fastening portion **2460b**. The distal end **2430b** of the strap can be threaded through loop **2420c** of the holder **2420** and doubled back upon itself so that the fastening portions **2460a**, **2460b** are in facing juxtaposed position to releasably engage.

FIG. 8 depicts in an exploded view, a fifth alternate embodiment RFID wristband type personal identification device of the present invention designated generally at **2500** with a planar RFID element **1010** and a carrier including a one piece body **2516** with an enlarged central portion **2518** forming a bottom of holder portion **2520** and a pair of straps **2530** and **2540** each having a first end **2530a**, **2540a** secured, preferably fixed and integral with the enlarged central portion **2518** of holder **2520** and a second, “free” end **2530b**, **2540b** distal to the holder. The band **2516** is formed, preferably molded, with central portion **2518**, loop **2420c** and with straps **2530**, **2540** in one continuous unbroken piece from a thermoplastic material that is resiliently flexible at ambient temperatures. The straps **2530**, **2540** retain a curved shape from molding and are resiliently flexible to permit them to be spread apart from an original, molded configuration for application to a user’s wrist and to retract to or towards their original configuration to releasably secure the device **2500** them to the user’s wrist.

FIG. 8 also depicts certain structures and methods of fabrication that might be used in making wristbands of the present invention. The enlarged portion and straps of the first three alternate embodiments **2100**, **2200**, **2300**, as well as some embodiments to be described, suggestively would be molded monolithically in one continuous body or band of a thermoplastic material that is at least flexible if not elastic at ambient temperatures. For example, the RFID element **1010** can be fixed directly to the surface of the enlarged portion **2518** forming the base of a holder portion **2520** by an adhesive layer **1015** or, depending upon the material forming the exterior of the element **1010**, a solvent or thermal weld (neither depicted). In another possible method of fabrication, the RFID element **1010** is operably connected and preferably fixedly secured to the body **2516** by means of a bezel-like retaining ring **2560** which is itself separately fabricated and secured to the enlarged portion **2518** of body **2516** over the RF **10** element **1010** by suitable means. On the one hand, the securement joining the ring **2560** to the enlarged portion **2518** of the holder may be adhesive layer indicated generally at **2570** or a solvent or heat weld (not depicted) or a mechanical securement such as mating threads, snap fit contours, post and hole structures on the holder and ring and/or separate mechanical fasteners such as screws, rivets or the like (none of the latter being depicted). If desired, the attachment portion and holder portions of the previous alternate embodiments **2100**, **2200**, **2300**, **2400** could be molded as one continuous integral piece from elastomeric material.

FIGS. 9-10 depicts a sixth alternate embodiment RFID wristband configuration and still another method of fabrication. An individual wristband **2600** (FIG. 10) is formed in one piece with a plurality or set of similar bands from a lamination of flexible sheet elements and RFID components indicated collectively at **2600'** in FIG. 9. A first sheet portion **2602** is formed of a porous, preferably microvoided, thermoplastic material that will collapse around the RFID circuit under heat and pressure typically employed in the lamination of the various sheets together. A plurality of individual RFID transponder circuits **27a**, **27b**, . . . **27i**, etc. are sealed between the

first sheet portion **2602** and a second sheet portion **2603**. The first and second sheet portions may be halves of a single sheet folded between its side edges so as to overlap with the RFID components **27** located between the facing halves. Alternatively, the second sheet portion **2603** may be separate from the first sheet portion **2602** as shown in FIG. **9** and may be the same microvoided thermoplastic material or made of an entirely different plastic material that can be bonded to the first sheet portion **2602**. If desired, a reinforcement layer **2604** of a strong yet readily flexible material such as stretched tetrafluoroethylene (e.g. Tyvek®) or other axially oriented polymer sheet material or a layer of para-aramid or glass fiber is bonded with one of the two sheet portions (e.g. **2602**) if it is not used directly as the second sheet portion **2603**. Flexible sheets **2602** and **2603** (with sheet **2604** if provided) constitute a core. Preferably, a transparent, readily flexible layer **2605** may be provided over one outer side of the sheet portion **2603** that is intended to be exposed on the wristband (i.e. **2603**) as a first cover sheet to protect that exposed surface and any printing that might be provided on that surface. If desired, another flexible, transparent sheet **2606** may be provided over the remaining outer side of sheet **2602** and over the reinforcement layer **2604**, if provided as a second coversheet. This might be done if it were desired to make the major outer sides of the wristbands **2600** look the same or for user comfort or durability. Alternatively, a metalized plastic sheet may be substituted as the bottom most sheet **2602/2604/2606** to provide the exposed bottom side **2615a** (FIG. **10**) of the resultant device **2600** where the metal can preferably face the skin of the user. Such metalized inner surface can be provided on any other embodiment of the invention or either the back of the planar RFID element **1010** or, more preferably, on the inner side of the carrier portion. A more resilient layer **2607** (in phantom) can also be further provided over one side of the central holder portion **2620** to reinforce that portion of the device **2600** against flexing and protect the RFID **27** components in the holder portion **2620** (FIG. **10**). While it is shown over sheet **2603**, it can just as easily be positioned under sheet **2602** or **2604**. Finally, while any fastening may be used to secure the free ends **2630b**, **2640b** of the first and second straps **2630** and **2640**, it is suggested that a layer of contact adhesive **2670** on a removable release strip **2675** be provided on the outermost one of the sheets **2602-2606** so that it ends up on the outer surface of one of the straps (e.g. **2630**, **2640**).

After assembly and lamination, the resulting printed sheet product **2600'** is scored to form a plurality of individual wristbands **2600a**, **2600b**, . . . , **2600i**, etc., each with its own unique RFID assembly **27a**, **27b**, . . . , **27i**, etc., having its own unique transponder code. It may also bear its own printed image **1022** (**1022a**, . . . , **1022i** in FIG. **9**) which, again, might be a bar or alphanumeric code unique to each individual wristband **2600a**, **2600b**, . . . , **2600i**, or both, or a logo or other static field(s) indicia or a combination of unique printed code field(s) with common static indicia field(s). While a sheet product **2600'** is shown in FIG. **9**, it will be appreciated that continuous webs forming layers **2602-2606**, including a continuous web supporting transponders **27a** for positioning between the sheets or webs **2602**, **2603**, can be provided along with continuous strip(s) **2607** and/or **2670/2675** for making long webs of multiple wristbands **2600** at one time.

FIG. **11** depicts a seventh alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **2700** including a planar RFID element **1010** and carrier indicated generally at **2710**. Carrier **2710** includes a holder portion **2720** and an attachment portion **2715** with straps **2730**, **2740**. This embodiment includes RFID element mounting and a strap securement

which might be used with other securements and mountings, respectively, being disclosed in other embodiments All of the holder portions disclosed in prior FIGS. **3-8** had retaining rings that were integrally formed with the holder portion or attached to it in assembly (like FIG. **8**) but which, in any case, surrounded or essentially surrounded the RFID element **2110**. The retainer structure need not surround or essentially surround or even substantially surround the outer perimeter of the RFID element **1010**. FIG. **11** shows a curved retainer structure **2770** that is approximately C shaped having a recessed channel **2774** and an open side **2772** into which the RFID element **1010** can be slid. The RFID element **1010** can be held in place by an adhesive or simply friction with the channel **2774** and/or by extending the structure **2770** for an angle of slightly more than 180 degrees around the element **1010** so as to create a pinch point at the open side **2772** or by the provision of a stop member **2778** (diagrammatically, in phantom) in the holder portion, for example, a wedge forming a ramp surface leading into the retainer structure **2770**. The free strap ends **2730b**, **2740b** of straps **2730**, **2740** are adjustably secured together by a fastening including a molded post **2760a** mating with any of the plurality of holes **2760b**.

FIG. **12** is a perspective view of an eighth alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **2800**. Device **2800** includes planar RFID element **1010** in a carrier **2810** including one-piece body **2816** with enlarged central portion **2818** and integral straps **2830**, **2840**. Wristband **2800** incorporates two more possible variations in wristband construction. First, the planar RFID element **1010** is held on the holder portion **2820** by the provision of a plurality of individual retainers **2825a**, **2825b** optionally with one or more stops **2825c** and **2825d** all preferably formed integrally with enlarged portion **2818** to define the holder portion **2820** and spaced around the RFID element **1010**. The retainers (collectively **2825**) may be resiliently flexible and provided with channels along their bases so that edges of the RFID element **1010** may be slid into them after riding over one of the stop elements **2825c**, **2825d**. Second, the free ends **2830b**, **2840b** of straps **2830**, **2840** may be held together by a fastening in the form of a separate mechanical fastener indicated generally at **2870**. The fastener **2870** can be a wrap, for example, of tape as depicted, or any of a variety of spring clips or clamps or any other clips or wraps that will compress or can be compressed or crushed around the joined free ends **2830b**, **2840b**.

FIG. **13** is a perspective view of a ninth alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **2900** with carrier portion **2910** and planar RFID element **1010**. Wristband **2900** also incorporates two more possible variations in wristband construction. Again, carrier **2910** has an attachment portion **2915** provided by a single body **2916** with enlarged central portion **2918** and integral straps **2930**, **2940**. First, the planar RFID element **1010** is held on the holder portion indicated generally **2920** by the provision of an adhesive layer **2970** (indicated by shading). If desired, a recess **2980** (in phantom) can be provided in the holder portion **2920** to receive the RFID element and the adhesive layer **2970**. Alternatively, the RFID element **1010** can be adhered to the holder portion **2920** (with or without recess **2980**) by a length of adhesive tape **2990**, preferably sufficiently transparent to read any printing on the exposed major planar surface of RFID element **1010**, or bearing printing itself and secured to the enlarged portion **2918** of body **2916** in the holder portion **2920** over the element **1010**. Alternatively, RFID element **1010** might be secured to the body **2816** by a cover layer of a transparent epoxy material. Second, the free ends **2830b**, **2840b** of indi-

vidual straps **2830**, **2840** are held together by another type of fastening, a separate, conventional mechanical fastener **2970** such as a staple (depicted) or a rivet or swaged stake(s) or nut and screw, (none depicted), etc., passed through one or both of the overlapped ends **2930b**, **2940b**.

FIG. **14** depicts diagrammatically a tenth alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **3100**. The tenth alternate embodiment **3100** is substantially identical to the preferred embodiment of FIGS. **1-2** having many of the same features with similar reference numbers. Fastening element **3132** at the free end **3030b** of its strap **3030** is different. A channel **3132a** is provided between a pair of raised stops **3132b**, **3132c**. The channel **3132a** is sufficiently wide to receive the narrowest width **W1** of the strap **3040** but narrower than the widest width **W2** so that the stops **3132b**, **3132c** contact and hold and preferably wedge an opposing pair of the transverse end surfaces **3042b**.

FIG. **15** depicts diagrammatically an eleventh alternate embodiment RFID wristband type personal identification device of the present invention indicated generally at **3200**. Wristband **3200** has a carrier **3210** that comprises a separate holder portion **3220** and a separate attachment portion **3215** in the form of a separate single strap **3230**, one end **3230a** of which can be threaded through the loops **3220a**, **3220b** provided on opposite edges of the holder portion **3220**. The strap **3230** can be of any construction with any fastening **3260** at its free ends **3230a**, **3230b**. One possible type of fastening **3260** is conventional buckle **3260a** and holes **3260b** formed into the strap **3230** itself.

FIG. **16** is a cross sectional view of a presently preferred individual planar radio frequency identification (RFID) element **1010** of the previous FIGS. **1-8** and **11-15**. Element **1010** includes a preferably planar and printable, flexible core indicated generally at **1012** having opposing first and second major planar outer sides **1014** and **1016**, a first major planar outer side **1014** being partially seen in various previous figures. Core **1012** is preferably provided by separate first and second printable core strips **1018**, **1020** which are planar, flexible and accept printing, and suggestedly at least one of which is a porous polymer sheet material, more particularly a microvoided polymer and preferably a microvoided polysilicate sheet material. The core strips **1018**, **1020** are overlapping and coextensive in the element **1010**. Core strips **1018**, **1020** can be joined together with and by any means suitable for the materials selected and as intended, preferably by an adhesive layer **1019** or by direct welding. Sandwiched between the core strips **1018**, **1020** is a radio frequency transponder assembly **27**, which is permanently and integrally fixed together with at least one and preferably each of the core strips **1018**, **1020** between the core strips **1018**, **1020**. As will be explained, assembly **27** includes circuit portion **29** (FIG. **17**) containing the unique electro/magnetic transponder code. Preferably, first and second cover strips **1040**, **1050** are again provided integrally and permanently secured to the first and second outer facing major sides **1014**, **1016**, of the core **1012** and respectively of the first and second core strips **1018**, **1020**, by suitable means such as adhesive layers **1041**, **1042**. Each cover strip **1040**, **1050** preferably is transparent and extends at least transversely entirely across the individual sheet element **1010** on the first and second major planar sides **1014**, **1016**, respectively, of strips **1018**, **1020** of the core **1012** cover strips **1040**, **1050** might be polyester (PE), poly vinyl chloride (PVC), polyethylene terephthalate (PET) or a polycarbonate material. A metalized layer **1060** might be provided directly on cover strips **1050** or attached afterwards.

Suggestedly, at least one of the core strips **1018**, **1020** comprises and, preferably consists essentially of a porous polymer sheet material that accepts printing, more specifically at least laser printing. More, preferably, one or both core strips **1018**, **1020** is essentially of a sheet of porous, specifically microvoided, polymer sheet material such as Teslin® of PPG Industries, Pittsburgh, Pa., or Artisyn® of Daramic, Inc., Charleston, S.C., both microvoided, polysilicate sheet materials, for laser printing. Teslin® is described in detail in U.S. Pat. No. 4,861,644, incorporated by reference herein. See also published U.S. Application No. 2001 0023014 also incorporated by reference herein. Teslin® is relatively very porous with a porosity of more than fifty percent. Preferably the microvoided polysilicate materials are permanently bonded together with a layer **1019** of suitable adhesive material such as WC9-PL, a heat activated, water based polyurethane adhesive of the Thornley Company of Wilmington, Del.

The microvoided sheet material is superior to non-voided materials used in all other known examples of encasing RFID transponder assemblies in plastic tags because the material readily collapses over the assemblies when the individual sheet products are heated and pressed to laminate them without damage to the assemblies. Double sheet constructions like elements **1010**, were made using seven mil thick Teslin®. The presence of the aforesaid RFID transponder assemblies **27** in these individual sheet products with two core strips could not be felt, the microvoided material essentially collapsing and possibly flowing around the assemblies where the assemblies were present between the sheets. In contrast, when bonded between sheets of conventional polymer card stock such as PVC or PE, which lack natural voids, a cavity has to be made to receive the RFID assembly or a lump is created when the sheet(s) are(is) bonded to the RFID assembly. The microvoided sheet products of the present invention further bond together better than the conventional polymer sheet stock, it is believed because the adhesive penetrates the porous sheet better than the conventional polymer card sheet stock, which is essentially without voids. The same is true for bonding of any outer protective cover sheet(s) directly to the microvoided core material. Note, where outer cover sheets are bonded over the printed outside of a core made from these preferred microporous material sheets, attempted removal of the cover sheet will tend to tear apart the core, destroying or at least distorting the printing, an added security feature. The microvoided products are "softer" and less brittle. As a result identification elements tend not to peel, crack or break in extended use like conventional PVC cards. This softer material transfers less pressure and stress to the transponder assemblies **27** when the removable identification elements are flexed during normal use. It has been further found that at least the preferred microvoided polymer materials affords faster static decay and is static dissipative compared with other, conventional, nonporous materials sometimes used in RFID tags and labels, including PVC, PET, and PC. This has been found to increase the range of Ultra High Frequency (UHF) transponder assemblies **27** up to about twenty percent.

As previously noted with respect to FIGS. **1** and **2**, at least one and, more typically, a plurality of spaced-apart, variable data fields, e.g., **1024** and **1025**, are printed on the core **1012** with a unique, multi-digit printed codes which are preferably identical to one another. In addition to the variable data fields **1024**, **1025**, etc., the printed sheet element **1010** may include one or more static graphic fields with an individual static graphic field **1034** being identified on side **1014**. It should be appreciated that this does not preclude a static graphic field from differing in appearance from element to element as where a large overall static design is applied to blocks of the

individual elements **1010** so that no static graphic field on elements adjoining each other when being made is the same. However, such different static graphics fields carry no information unique to the element which could be used to uniquely identify the element or the user to whom the element is uniquely assigned.

Individual radio frequency identification elements **1010** include a generally planar, ultra high frequency, passive, radio frequency identification (“RFID”) transponder assembly **27** configured to transmit an electro/magnetic signal containing a unique electro/magnetic code and possibly other information in response to a radiated, e.g., radio frequency (“RF”) polling or interrogation signal. Referring to FIG. **17**, such RFID assemblies **27** include an antenna **28** and a small chip **29** connected to the antenna. The chip **29b** includes a memory containing the unique electro/magnetic code, as well as transponder circuitry and a power circuit configured to temporarily store energy from the received RF polling/interrogation signal and use that energy to transmit the RF response. UHF assemblies **27** may also include programmable (random access) memory and control circuitry. The assembly **27** is preferably permanently and integrally fixed together within the core **1012** or with at least one of the core **1012** and the first cover strip **1040**, if provided. The electro/magnetic transponder assembly **27** may be first “tacked” to the core **1012** before the core **1012** is joined with the first cover strip **40** or, preferably, to a side of one of the core strips **1018**, **1020** facing the other case strip, before those strips are joined so as to be encapsulated between the strips **1018**, **1020** as shown. Such RFID assemblies **27** (also sometimes referred to as “inlays”) are available from a variety of suppliers, including but not limited to, Motorola of San Diego, Calif.; Texas Instruments of Attleboro, Mass.; Checkpoint Systems of Thorofare, N.J.; Gemplus Corp. of Redwood City, Calif.; Hughes Identification Devices of Tustin, Calif.; Cotag International of Wilmington, Del.; Abbhafco Incorporated of San Diego, Calif.; and Balough T.A.G. of Ann Arbor, Mich. For example, Gemplus offered smart labels in three shapes: a small square approximately one-half inch square, a large square approximately one inch square and a small disk permitting their incorporation into an element **1010** only slightly larger. All three sizes come in two versions, read-only and read/write. Each read-only version contains a unique, tamperproof code of sixty-four bits, which is directly programmed during manufacture. The read/write version has a 2 kb EEPROM memory that offers different access possibilities.

It also has been found possible to print by silk screen, electrically conductive inks/toners on at least one microvoided polymer plastic, the aforesaid Teslin® microvoided polysilicate thermoplastic material. More particularly, at least the antenna portions **28** of RFID transponder assemblies **27** can be printed leaving only the transponder chip **29** to be obtained from an outside source and applied. The chip **29** may be mounted on a holder (not depicted) to span the antenna **28**. Chips can be obtained from the previously identified manufacturers and applied automatically with “pick and place” equipment now commercially available from different manufacturers and/or distributors including but not limited to Mulbauer, a German company with a place of business in Newport News, Va. Mulbauer models TAL 4000, TMA 6000 and FCM 6000 can be considered to perform this task. The ability to silkscreen inks/toners directly on a microvoided polymer sheet material layer **1018** or **1020** like Teslin® makes manufacture of the planar ID elements easier. The preexisting antenna designs and geometries supplied by RFID assembly suppliers do not always fit the desired geometry of the ID element or where they do fit, they may be in relatively tight

registration. Even slight misalignment can result in the die cutting of an RFID assembly or its antenna when the individual ID elements are cut from larger sheets they are made in. Being able to print antennas provides manufacturing flexibility for antenna layout and design including size, shape and frequency characteristics and scheduling because end users will no longer have to await the supply of assemblies by manufacturers, where significant delays have occurred. Furthermore, the technique of applying an entire RFID assembly previously described utilizes a bed of wet glue on the substrate to receive and hold the assembly.

FIGS. **18-20** depict diagrammatically, the steps in producing yet another planar radio frequency identification (“RFID”) element **5000** with two different planar radio frequency transponder assemblies. There are applications in which both High Frequency and Ultra High Frequency RFID assemblies or “inlays” would be provided as an identification element such as one embedded into a wristband to facilitate various applications such as Ticket less access control, locker access control, vending machines and self service Kiosks. High frequency assemblies are relatively short ranged (i.e. inches) and so is useful for financial transactions. Ultra High “Inlays” have a longer range (e.g. tens of feet) for longer range applications such as interactive people locating. All of this could be achieved by using one dual frequency wristband.

Referring to FIG. **18**, a Teslin or like microporous polymer web **5002** is provided on which a UHF RFID assembly **5027** is positioned on a left side and an HF RFID assembly **5027'** is positioned on a right side opposing the first assembly **5027**. The assemblies can be temporarily tacked in place with a contact adhesive.

After the assemblies **5027**, **5027'** are positioned on the opposite sides (“halves”) **5002a**, **5002b** of the web **5002**, the web is folded over at the “hinge” **5003** provided for example, by perforation down the web **5002** between (i.e. generally equidistant) from the two assemblies **5027**, **5027'**. In FIG. **19**, an adhesive sheet **5050** is then inserted between the opposite sides/halves and heat and pressure (arrows **5052** in FIG. **20**) is applied to bond the halves **5002a**, **5002b** together. This product is identified as **5001** in FIGS. **20** and **21**. The important thing here is that the adhesive sheet **5050** will separate the two different frequency “Inlays” **5027**, **5027'** that once die cut as at **5062** or otherwise removed from the web/sheet product **5001**, will provide an RFID element **5060** having two different RFID assemblies **5027**, **5027'**. When combined with a wristband, the result has effectively two embedded different RFID tags incased within it.

A thin film of lamination (e.g. PE not depicted) may or may not be applied to either outer side (or to both sides) to protect the surface(s). To enhance the propagation of the RFID signals, for example in a wristband, a layer of foam material between the wearer’s skin and the facing side (inside) of the element **5060** or the wristband with the element. As before, the sheet **5001** can be scored itself to form the body of the wristband with the embedded assemblies, thereby putting distance between the UHF RFID assembly and the skin of the user. UHF RFID Tags read at a longer range when the tags are elevated away from liquids. Various foam material with pressure sensitive adhesives/liner are available through many vendors commercially.

If desired, another Teslin web **5002'** (FIG. **22**) is positioned or otherwise located over the positioned assemblies **5027**, **5027'** and first web **5002** and the assemblies hermetically sealed between the webs **5002**, **5002'**. The webs **5002**, **5002'** could be individual sheets, separate webs or even a single web or sheet folded approximately in two so as to overlap one another. The adhesive sheet **5050** would then be inserted

between the opposing sides of the resulting sandwich to provide an assembly with five polymer sheet layers and two RFID assemblies. Alternatively, adhesive sheet **5050** could be replaced with simply an adhesive layer resulting in a four polymer layer element to which cover sheets might be added to either of both major sides for protection.

Other specific manufacturing details and materials, including suggested materials and manufacturing techniques, as well as other configurations of printed sheet products including planar, printed identification elements have been disclosed in prior U.S. Pat. Nos. 4,978,146, 5,495,981 5,743, 567, 5,769,457, 5,863,076, 6,010,159, 6,769,718, 7,204,652 and/or 6,039,356, and Application Nos. 60/882,623 filed Dec. 29, 2006, Ser. No. 09/595,825 filed Jun. 16, 2000, each of which is incorporated by reference herein in its entirety.

It will be appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. In particular any of the holder portion constructions can be combined with any of the strap and strap securement constructions disclosed. Also, while bands are the preferred form, the personal RFID element carrier may be of any other form by which the element may be attached to the user. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention.

The invention claimed is:

1. A personal identification device comprising:
 - a planar radio frequency identification element, the element including a flexible core having opposing first and second major opposing outer sides and formed from at least two layers of flexible polymer sheet material, at least one layer being a flexible, porous polymer sheet material, and a first planar radio frequency transponder assembly operating at a first frequency and a second separate planar radio frequency transponder assembly operating at a second frequency different from the first frequency permanently and integrally fixed between the two layers of the flexible polymer sheet material, each of the first and second transponder assemblies including an antenna and an integrated circuit chip; and
 - carrier means configured for holding the planar radio frequency identification element and for releasably securing the planar radio frequency identification element to a user to be identified by the planar radio frequency identification element.
2. The personal identification device of claim 1 wherein the at least one layer of flexible, porous, polymer sheet material is a microvoided polysilicate sheet material.
3. The personal identification device of claim 2 wherein the core further includes a third sheet material layer having a major side facing and overlying an inner major side of the at least one flexible, microvoided, polymer sheet material layer and at least the first planar radio frequency transponder assembly, the third layer being permanently and fixedly joined with the inner major side of the at least one layer of flexible, microvoided, polymer sheet material, sealing the first planar radio frequency transponder assembly between the at least one layer of the flexible, microvoided, polymer sheet material and the third layer.
4. The personal identification device of claim 3 wherein the second layer of planar, flexible sheet material is a second sheet of the microvoided, polysilicate sheet material.
5. The personal identification device of claim 1 further comprising a first flexible transparent cover strip integrally

and permanently secured to the first outer side of the core, the first cover strip being coextensive with the first outer side of the core.

6. The personal identification device of claim 5 further comprising a unique code printed on a visible outer major planar face of at least one of the core and the first flexible transparent cover strip to uniquely identify the planar identification element from all other planar identification elements.

7. The personal identification device of claim 1, where the planar radio frequency identification element is integral with the carrier means, the at least one layer of flexible, porous polymer forming part of the carrier means and being of a length sufficient to wrap around a portion of a user to secure the device to the user.

8. The personal identification product of claim 1, further comprising a foam material layer as a major side of one of the element and the carrier means facing the user with the device secured to the user.

9. A method of making a personal identification device comprising the steps of:

- providing an at least generally planar radio frequency identification element including first and second opposing major planar outer sides with indicia printed on at least one of the outer sides and a first radio frequency identification transponder assembly operating at a first radio frequency and a second radio frequency identification transponder assembly operating at a second radio frequency different from the first radio frequency sealed within the element between first and second opposing major planar outer sides, each of the first and second transponder assemblies including an antenna and an integrated circuit chip; and
- providing an attachment portion with at least one strap with one securement capable of holding the holder portion on a user's wrist.

10. The method of claim 9 wherein the step of providing an at least generally planar radio frequency identification element comprises the steps of:

- providing a first planar substrate sheet portion and a second planar substrate sheet portion, each portion having major opposing first and second sides;
- locating the antenna and chip of the first radio frequency identification transponder assembly on the first major side of the first planar substrate sheet portion and the antenna and chip of the second radio frequency identification transponder assembly on the first major side of the second planar substrate sheet portion;
- fixedly and permanently joining the first major side of the second planar substrate sheet portion with the first major side of the first planar substrate sheet portion overlying the first and second radio frequency identification transponder assemblies to form at least part of a multilayer planar core having first and second major outer sides, at least one of the first and second planar substrate sheet portions being microvoided;
- fixedly and permanently applying at least a first planar flexible polymer cover sheet to at least the first major outer side of the planar core; and
- scoring the planar core and at least first planar cover sheet to define the at least generally planar radio frequency identification element removable from the core and from at least first planar cover sheet, the generally planar radio frequency identification element containing the operative first and second radio frequency identification transponder assemblies.

11. The method of claim 10 further comprising the step of printing on the second major side of one of the first and

15

second planar substrate sheet portions forming the first major outer side of the planar core before the fixedly and permanently applying step.

12. The method of claim 11 wherein the step of printing on the second major side of the one of the first and second planar substrate sheet portions occurs before the step of locating the first and second radio frequency identification arrays on the first and second sheet portions.

13. The method of claim 11 wherein the step of printing on the second major side of one of the first and second planar substrates includes printing a unique machine readable code.

14. The method of claim 10 wherein at least both of the first and second planar flexible sheet portions are microvoided material.

15. The method of claim 9 further comprising the step of providing a foam material layer on one of the radio frequency identification element and the attachment portion on a side to be facing the user with the device secured to the user.

16. The method of claim 9 wherein the step of providing an at least generally planar radio frequency identification element comprises the steps of:

providing first and second flexible planar substrate sheet portions;

applying the antenna and chip of the first radio frequency identification transponder assembly to a first major side of the first flexible planar substrate sheet portion and the antenna and chip of the second radio frequency identification transponder assembly to a first major side of the second flexible planar substrate sheet portion;

fixedly and permanently joining the first major sides of the first and second planar substrate sheet portions together to form a planar core with the first and second radio frequency identification transponder assemblies sealed between the first and second planar substrate sheet portions; and

scoring the planar core to define the at least generally planar radio frequency identification element.

16

17. The method of claim 16 further comprising the preliminary step of forming a hinge in a single planar microporous polymer substrate to define and connect together the first and second planar substrate sheet portions.

18. The method of claim 16 further comprising the step of providing a third sheet between the first and second flexible planar substrate sheet portions before the fixedly and permanently joining step and wherein the fixedly and permanently joining step further comprises fixedly and permanently joining the first major sides of the first and second planar substrate sheet portions to opposite major sides of the third sheet portion.

19. A method of making a radio frequency personal identification device comprising the steps of:

providing an at least generally planar multilayer flexible polymer material sheet intermediate product containing first and second radio frequency identification transponder assemblies operating at different first and second radio frequencies; and

scoring the intermediate product to define at least one multilayer, integral, individual planar radio frequency identification wristband removable from the intermediate product, the planar radio frequency identification wristband including a central holder portion containing the first and second radio frequency identification transponder assemblies and strap means extending away from the central holder portion, the strap means being of a length sufficient to be able to be completely wrapped around the wrist of a user to secure the wristband to the user.

20. The method of claim 19 further comprising the step of applying a layer of a contact adhesive on a release sheet to the intermediate product before the scoring step; and wherein the scoring step comprises scoring the individual wristband and so as to include a portion of the contact adhesive and release sheet located to secure parts of the wristband together around a wrist of the user.

* * * * *