



(22) **Date de dépôt/Filing Date:** 2008/06/02

(41) **Mise à la disp. pub./Open to Public Insp.:** 2009/12/02

(45) **Date de délivrance/Issue Date:** 2015/07/28

(51) **Cl.Int./Int.Cl.** *B65D 81/38* (2006.01),  
*A45C 11/20* (2006.01), *A47J 41/00* (2006.01)


(72) **Inventeur/Inventor:**  
PRUCHNICKI, RENIA, CA

(73) **Propriétaire/Owner:**  
CALIFORNIA INNOVATIONS INC., CA

(74) **Agent:** BERESKIN & PARR LLP/S.E.N.C.R.L.,S.R.L.

(54) **Titre :** CONTENEUR ISOTHERME AVEC DISPOSITIF DE LEVAGE ASYMETRIQUE

(54) **Title:** INSULATED CONTAINER WITH ASYMMETRIC LIFTING ARRANGEMENT



(57) **Abrégé/Abstract:**

A soft-sided insulated container assembly includes a collapsible cooler body made of insulated panels. The body is to be carried by an arrangement of lifting apparatus that includes asymmetrically arranged fittings. One lifting fitting may be an inboard shoulder

**(57) Abrégé(suite)/Abstract(continued):**

strap. Another fitting may be a handle located on an outboard portion of face of the container body, and may be at a height for engagement by the hand of the user. The soft-sided insulated container assembly may have a liner to contain liquids. The soft-sided insulated container assembly may have an easy access lid. The insulated container may be collapsed to a flat position, and secured in place. In one embodiment the asymmetric lifting arrangement includes a shoulder strap attached to the sides of the container in a manner that distributes the load into the sides of the container, and a grip, such as a handle, located on the lower portion of the front side of the container. The grip may be attached to the container so as to pull up on the bottom of the container when used by a person.

**INSULATED CONTAINER**  
**WITH ASYMMETRIC LIFTING ARRANGEMENT**

**Abstract**

A soft-sided insulated container assembly includes a collapsible cooler body made of insulated panels. The body is to be carried by an arrangement of lifting apparatus that includes asymmetrically arranged fittings. One lifting fitting may be an inboard shoulder strap. Another fitting may be a handle located on an outboard portion of face of the container body, and may be at a height for engagement by the hand of the user. The soft-sided insulated container assembly may have a liner to contain liquids. The soft-sided insulated container assembly may have an easy access lid. The insulated container may be collapsed to a flat position, and secured in place. In one embodiment the asymmetric lifting arrangement includes a shoulder strap attached to the sides of the container in a manner that distributes the load into the sides of the container, and a grip, such as a handle, located on the lower portion of the front side of the container. The grip may be attached to the container so as to pull up on the bottom of the container when used by a person.

**INSULATED CONTAINER**  
**WITH ASYMMETRIC LIFTING ARRANGEMENT**

**Field of the Invention**

5

This invention relates to the field of portable soft-sided insulated containers.

**Background of the Invention**

10

Soft sided insulated containers have become popular for carrying either articles that may best be served cool, such as beverages or salads, or warm, such as appetizers, hot dogs, and so on. Such containers are frequently used to carry liquids, whether hot liquids, such as soup containers, coffee or tea, or cold liquids such as beer, soft drinks, or other carbonated beverages, juices and milk. Or ice cream snacks or frozen flavoured refreshments. Sometimes these containers may be used to carry lunches, which may include a sandwich, fruit, carrot and celery sticks, a drink, cookies, and so on.

15

Typically, the container may be slung over one shoulder, and carried to the side of the body. For example, it may be used by a vendor at a sporting event. Articles carried in a container of this nature can be quite heavy, and perhaps somewhat awkward. The use of such a container can put a strain on the carrier's back, arms and shoulders. For example, many of the containers of this nature are designed to carry between six and thirty (or more) 355 ml soft drink cans of about 2 ½" dia. x 4 - 7/8" high. The container may also have a tendency to swing, or rotate, about the carrier's hips. This may not necessarily be comfortable or convenient.

20

25

**Summary of the Invention**

In an aspect of the invention there is a soft-sided insulated container assembly. It has a container body having length, height and depth, a primary lifting member, and a secondary grip. The container body has a centroid relative to the length, height, and lateral depth. The length is at least as great as the lateral depth. The container body has a soft-sided wall structure that includes an outer skin, an inner skin and a layer of insulation therebetween. The container body has an insulated chamber defined therewithin, and has an externally accessible closure member governing access thereto. The primary lifting member has first and second attachments longitudinally bracketing the centroid. The primary lifting member has a lifting member lying

30

35



inboard of the container body relative to the depth thereof. The lifting member is, in use, at an height higher than the body. The grip is located longitudinally intermediate the first and second attachments of the primary lifting member. The grip is located outboard of the container body relative to the lateral depth thereof. The grip is located at a height lower than the centroid.

5

In an additional feature of that aspect of the invention, the container has a pair of longitudinally spaced apart end walls and the primary lifting member includes portions distributing vertical load into the end walls. In another feature, the grip includes a handle standing outwardly from a face of the container body. In another feature the container has a base panel and sidewall panels extending peripherally upwardly therefrom the grip is rooted to pull upwardly on the base panel. In another feature the body has an uppermost panel, the panel includes the closure member, and the closure member has a hinged laterally inboard edge. In another feature the uppermost panel further includes an auxiliary zipperless access that is smaller than the closure member. In still another feature the primary lifting member includes a load spreading pad for engaging a shoulder of a person carrying the container, the pad having a lifting location that is higher than the centroid by a distance greater than the height of the container body. In yet another feature the container has another lifting member mounted to an outboard portion thereof, and is co-operable to meet the primary lifting member above the body whereby to permit the body to be carried as a hand satchel.

20

In still another feature the height is at least as great as the lateral depth. The container body has a four sided base panel, an upstanding peripheral wall that includes a front panel, a back panel, a first end wall and a second end wall, and a top panel all co-operating to define the insulated chamber therewithin. The first and second end walls are longitudinally spaced apart; the front and back panels is spaced apart laterally depthwise. The chamber having a liquid retaining liner mounted therein. The lid includes the closure member, and the closure member is hinged along a laterally inboard margin thereof. The primary lifting member includes a load distribution element at each end thereof. The load distribution elements pass loads into the first and second end walls both laterally inboard and laterally outboard of the centroid.

30

In another aspect of the invention there is a soft-sided insulated container assembly. It has a soft-sided insulated container, a primary lifting member and a secondary lifting member. The soft-sided insulated container has a front panel, a back panel and a pair of side panels. The front panel has a predominantly rectangular form. The rectangular form includes a pair of first and second generally opposed long sides, and a pair of first and second generally opposed short

35

sides. The primary lifting member is mounted to the pair of side panels. The primary lifting member having a center of lift closer to the back panel than to the front panel. The secondary lifting member is mounted to the front panel by mounting members such that the secondary lifting member is closer to the first long side than the second long side. The first lifting member including a load spreading pad for engagement of a user's shoulder. The second lifting member including a bail for grasping engagement by a user's hand.

In still another aspect of the invention there is a soft-sided insulated container assembly that includes a soft-sided insulated container having two primary lifting members and a secondary lifting member. The soft-sided insulated container has a front panel, a bottom panel and a back panel. The front panel has a predominantly rectangular form, the rectangular plan form having a pair of first and second generally opposed long sides, and a pair of first and second generally opposed short sides. The first long side is proximate to the bottom panel and the second long side is distant therefrom. The primary lifting members are mounted to the front and back panels respectively. The secondary lifting member is mounted to the front panel closer to the first long the than to the second long side.

In an additional feature of that aspect, the secondary lifting member has a mounting that attaches to the bottom panel and distributes loads thereto.

### **Brief Description of the Drawings**

These and other aspects of the invention may be more readily understood with the aid of the illustrative Figures includes herein below, and showing an example, or example, embodying the various aspects of the invention, provided by way of illustration, but not of limitation of the present invention, and in which:

Figure **1a** shows an isometric view from in front and above and to one corner of an embodiment of an insulated container according to an aspect of the present invention;

Figure **1b** is an opposite isometric view of the container of Figure **1a**;

Figure **1c** is a front view of the container of Figure **1a**;

Figure **1d** is a rear view of the container of Figure **1a**;

Figure **1e** is a left hand side view of the container of Figure **1a**, shown as carried by a person;



Figure **1f** is a top view of the container of Figure **1a**;  
Figure **1g** is a bottom view of the container of Figure **1a**;  
Figure **1h** is a view of the container of Figure **1a** in a closed condition;  
Figure **2a** is an isometric view of the container of Figure **1a** in a collapsed condition;  
5 Figure **2b** is a front view of the container of Figure **2a**;  
Figure **2c** is a rear view of the container of Figure **2a**;  
Figure **2d** is a right hand side view of the container of Figure **2a**;  
Figure **2e** is a top view of the container of Figure **2a**;  
Figure **2f** is a bottom view of the container of Figure **2a**;  
10 Figure **3a** shows an isometric view from in front, above and to one corner of an alternate  
embodiment of an insulated container to that of Figure **1a**;  
Figure **3b** is an alternate isometric view of the container of Figure **3a** from in front,  
above, and to the other front corner; and  
Figure **3c** is a further alternate isometric view of the container of Figure **3a** from in front,  
15 below, and to one corner.

### **Detailed Description**

20 The description that follows, and the embodiments described therein, are provided by  
way of illustration of an example or examples, of particular embodiments of the principles of the  
present invention. These examples are provided for the purpose of explanation, and not  
limitation, of those principles and of the invention. In the description, like parts are marked  
throughout the specification and the drawings with the same respective reference numerals. The  
drawings are generally roughly to scale unless noted otherwise. In some instances proportions  
25 may have been exaggerated in order more clearly to depict certain features of the invention.

30 A Cartesian frame of reference may be employed in which the long, or largest dimension  
of an object may be deemed to run in the direction of the x-axis, the base of the article, where  
substantially planar, may be considered to extend in an x-y plane, and the height of the article  
may be measured in the vertical, or z-direction. The largest panels of the containers described  
herein may be designated arbitrarily as the front and rear sides, faces, or portions of the  
container. Similarly, the closure member, or opening of the bag is arbitrarily designated as being  
at the top, and the base panel is designed as being at the bottom, as these terms may be  
appropriate for the customary orientation in which the objects may usually be found, sold, or  
35 employed, notwithstanding that the objects may be picked up and placed on one side or another

from time to time at the user's choice. It should also be understood that, within the normal range of temperatures to which human food and human touch is accustomed, although the term cooler, or cooler container, or cooler bag, may be used, such insulated structures may generally be used to keep food, beverages, or other objects wither warm or hot as well as cool, cold or frozen.

5

Reference is made to insulated containers. The adjective "insulated" is intended to be given its usual and normal meaning as understood by persons skilled in the art. It is not intended to encompass single layers, or skins, of conventional webbing materials, such as Nylon™, woven polyester, canvas, cotton, burlap, leather, paper and so on, that are not otherwise indicated as having, or being relied upon to have, particular properties as effective thermal insulators other than in the context of being provided with heat transfer resistant materials or features beyond that of the ordinary sheet materials in and of themselves. Following from *Philips v. AWH Corp.*, this definition provided in the specification is intended to supplant any dictionary definition, and to prevent interpretation in the U.S. Patent Office (or any other Patent Office) that strays from the customary and ordinary meaning of the term "insulated" as provided.

15

Similarly, this description may tend to discuss various embodiments of soft-sided containers, as opposed to hard-shell containers. In the jargon of the trade, a soft-sided cooler, or bag, or container, is one that does not have a substantially rigid, high density exoskeleton (typically a molded shell, e.g., of ABS or polyethylene, or other common types of molded plastic). Rather, a soft-sided container may tend to have, for example, an outer skin, a layer of insulation, and an internal skin, both the internal and external skins being of some kind of webbing, be it a woven fabric, a nylon sheet, or some other membrane. The layer of insulation, which may be a sandwich of various components, is typically a flexible or resilient layer, perhaps of a relatively soft and flexible foam. A soft-sided container may still be a soft-sided container where, as described herein, it may include a substantially rigid liner, or may include one or more battens (which may be of a relatively hard plastic) concealed within the soft sided wall structure more generally, or where hard molded fittings may be used either at a container rim or lip, or to provide a base or a mounting point for wheels, but where the outside of the assembly is pre-dominantly of soft-sided panels. Again, this definition is intended to forestall the U.S. Patent Office (or any other Patent Offices), from adopting an interpretation of the term "soft-sided" that diverges from the ordinary and the customary meaning of the term as understood by persons of ordinary skill in the art, and as explained herein.

20

25

30



Figures **1a** to **1h** and **2a** to **2f** show an example of an insulated container assembly **20** in embodying an aspect of the invention. The insulated container assembly **20** may include a soft-sided insulated container **22**, a removable, impermeable liner **24**, a first or primary lifting member **26** and second or secondary lifting member **28**.

5

The soft-sided insulated container **22** may have the general form of a generally six-sided box, or enclosure, having a first or bottom panel **30**, a second or top panel **32**, a third or front panel **34**, a fourth or back panel **36**, and a pair of left and right side panels **38** and **40**. In some embodiments the first panel **30** has a generally rectangular form, defined by a pair of first and second generally opposed long sides, or margins, **42**, **44** and a pair of first and second generally opposed short sides, or margins, **46**, **48**. The first panel **30** may have radiused corners. While, in the most general sense, the first and second panels **30**, **32** may have generally planar forms, and may be polygons, and may be quadrilaterals, whether of equal or unequal size, or of the same or different profiles or footprints, it may often be convenient for the first and second panels **30** and **32** to have substantially the same plan form profile or footprint, and for them to be spaced apart and parallel, such that the normal projection of one may lie upon, or substantially or predominantly upon, the other.

10

15

20

25

Each of the third, fourth, left side and right side panels **34**, **36**, **38**, **40** may have a first or bottom side or margin **50**, **52**, **54**, **56** and an opposing second or top side or margin **58**, **60**, **62**, **64**. The first and second margins **50**, **52**, **58**, **60** of the third and fourth panels **34**, **36** are long margins that correspond to the long sides, or margins, **42**, **44** of first panel **30**, and the first and second margins **54**, **56**, **62**, **64** of the left and right side panels **38**, **40** correspond to the short sides, or margins, **46**, **48** of first panel **30**. The first margins **50**, **52**, **54**, **56** of the third, fourth, left side, and right side panels **34**, **36**, **38**, **40** are joined to the corresponding margins **42**, **44**, **46**, **48** of first panel **30** and may extend away from first panel **30** such that the second margins **58**, **60**, **62**, **64** may form a rim or periphery **66** with which second panel **32** may cooperate.

30

35

The structure thus described defines a thermally insulated internal space, or cavity, chamber or accommodation, indicated generally as **68**. Access to accommodation **68** may be obtained by mounting second panel **32** in a movable condition, such that second panel **32** may move between an open condition (Figures **1a**, **1b**) and a closed condition (Figure **1h**) with respect to rim **66**, and with respect to accommodation **68** more generally. To this end, second panel **32** may be pivotally or hingedly mounted to rear panel **36**, and in particular, may have a long side or margin **70** that is mounted to the top side or margin **60** of rear panel **36** such that



second panel **32** may swing in the manner of a door, or first closure, operable to govern access to accommodation **68**.

5 In this structure, the long or lengthwise structure overall dimension  $L_{20}$  in the x-direction may tend to be greater than the lateral depth or breadth-wise dimension in the y-direction  $W_{20}$ , each of which may tend to be greater than the height or vertical depth or thickness  $H_{20}$  in the z-direction measured normal to first and second panels **30** and **32**. Indeed,  $L_{20}$  may tend to be in the range of  $1 W_{20}$  to  $1.5 W_{20}$ , and may tend to be in the range of 2 to 5 times  $H_{20}$ . In one embodiment, the ratio of proportions  $L_{20} : W_{20} : H_{20}$  may be roughly 5:4:2, (all +/-30%). In a  
10 typical embodiment, container assembly **20** may tend to be employed as a beverage cooler for cans such as the 355 ml cans noted above, whether 6, 12, 20, 24, 40 or 50, as may be.

Insulated container assembly **20** may include a securement in the nature of a releasable fitting **72**, such as may be operable to retain the second panel **32** in the closed position. Fitting  
15 **72** may be a friction fit, or interference fitting or bead, or lip, which may either be discrete or which may run in a substantially continuous manner about a portion or all of the rim **66**. Fitting **72** may include mating hook and eye attachment fittings (of which one type is sold under the name Velcro™), or it may be in the nature of a tracked fastener, of which one type is a zipper. In one embodiment, zipper **74** may extend about those portions of rim **66** not connected by hinge  
20 **76**, namely the second margins **58**, **62**, **64** of the third or front, left side and right side panels **34**, **38**, **40**. Hinge **76** may be in the nature of a living or fabric hinge or flap, as may be.

Liner **24** may be a flexible liner that may be attached about rim **66**, and may be on the inside thereof completely within the enclosure. Liner **24** has a base **78**, and four sides, front, rear,  
25 left hand, and right hand respectively, **80**, **82**, **84**, **86** extending upwardly from base **78**. Each of sides **80**, **82**, **84**, **86** is joined to base **78** at a base edge or margin **88**, **90**, **92**, **94**, as indicated, and each has an opposite distal edge or margin **96**, **98**, **100**, **102** distant from its base edge or margin. A chamber **104** is defined between base **78** and sides **80**, **82**, **84**, **86**. Chamber **104** has an opening **106** defined by the rim **108** formed collectively by distal edges **96**, **98**, **100**, **102** of sides  
30 **80**, **82**, **84**, **86**. Liner **24** may be a seamless folded liner made of vinyl or sheet stock, and may be translucent, or see-through. Liner **24** may be invertible and washable.

Liner **24** may be permanently installed, as by sewing around the periphery at rim **66**, or it may be removably installed with liner support fasteners **110**. In some embodiments the liner  
35 support fasteners **110** are of the nature of a continuous zipper around three sides of the rim **108**,



and a fastener **112** in the nature of a fabric hook-and-eye strip are sewn in place with stitching that is at an height relative to base **78** that is expected to be well above the liquid level in liner **24**. In other embodiments, fasteners **110** are all fabric hook and eye fasteners each mounted on one side of the rim **108**, and which mate with corresponding hook-and-eye fasteners strips mounted to the soft-sided insulated container **22**. These fastener strips are commonly sold under the name Velcro™.

Alternately or optionally, insulated container assembly **20** may include a secondary wall structure such as may be designated as a secondary or auxiliary pocket or pouch **114** mounted externally to the soft-sided insulated container **22**. Auxiliary pouch **114** may have an insulated wall structure, or may have a non-insulating retaining lodgement. It may be that auxiliary pouch **114** is mounted to the front panel **34**.

The first or primary lifting member **26** of the insulated container assembly **20** may be attached at one or more locations. In one embodiment, first lifting member **26** may have the form of a shoulder strap **116** mounted to a top portion of left and right side panels **38** and **40**. Strap **116** may be mounted eccentrically relative to the vertical centerline of left and right side panels **38** and **40**, and may be mounted to ascend at an angle shown as angle **[alpha]** which may be in the range of perhaps 65 – 80 degrees from horizontal (10 – 25 degrees from vertical). An extension of the centreline of strap **116** to bottom panel **30** may tend not to intersect the centroid **C** of the left or right side panel **38** or **40**, but rather pass between centroid **C** and back along left or right side panel **38** or **40**.

In some cases the strap **116** is a single continuous strap and in other cases the strap **116** includes, or is, an assembly of straps. Strap **116** may include a main or central portion **111**, to which a central load spreader, identified as pad **118**, may be mounted to spread the weight of the insulated container assembly **20** across the carrier's shoulder. In one form pad **118** may be generally triangular (or trapezoidal), with the base side of the triangle (or long side of the trapezoid) being for placement over the wearer's shoulder away from the neck, and the point or apex of the triangle (or short side of the trapezoid) toward the neck.

Strap **116** may also include an adjustment, or adjustments, such as slide buckles **113** to permit variation of the length of the components of central portion **111** of strap **116**. This length adjustment alters the height at which the assembly is carried on the carrier's body (Figure **1e**, **H<sub>118</sub>**.) and the relative difference in height between the lifting pad **118** on the strap, and the



height of outboard handle, namely secondary lifting member **28** (Figure **1e**,  $H_{28}$ ). The height of application of force on item **118** may be roughly the height of the container body,  $H_{20}$ , above the top panel, or may lie in the range of about 3:4 to 3:2 of  $H_{20}$  above the height of the top panel. It may be noted that the line of action of the lifting force on pad **118** is inboard of the inside face of back panel **36**, and may be offset from the centroid by a distance  $L_{118}$ . Similarly, the lateral distance to the secondary lifting member **28** from the centroid is shown as  $L_{28}$ . These two lateral distances are roughly comparable, being in the range of 2:3 to 3:2 of each other. In use,  $H_{28}$  may be in the range of  $\frac{1}{4}$  to  $\frac{1}{2}$  of the height of the cooler body generally, indicated as  $H_{20}$ . As indicated, member **28** lies below the centroid, whereas pad **118** is located on the shoulder well above the level of the centroid. In the illustration a lateral reaction is shown as  $F_R$ , applied by the body of the person carrying assembly **20** at roughly hip level, that being, more or less the same as the level of the bottom of assembly **20**, which may also be relatively close to, or at, the level of member **28** (within +/- 20 % of  $H_{20}$ , for example). In the closed position, shown in Figure **2e**, the height  $H_{123}$ , of the lower margin **123** of top panel **32**, as folded, is less than  $H_{20}$ , such that the lid, as folded for storage, does not cover over handle **120**.

Strap **116** (or strap assembly, **116**, as may be) may also include a pair of end spreaders **115**, such as may have the form of a two legged strap with a loose hard eye **117**. The two legs **119**, **121** each have a root secured to the end panel, be it **38** or **40**. The legs meet at a fold over one side of hard eye **117**. The location of the fold may be fixed by fixing the lengths of legs **119**, **121** relative to each other, as by stitching them together, and entrapping hard eye **117**. Central portion **111** wraps about the other side of hard eye **117**. As may be noted, the root of one leg **119** lies inboard of the centroid, and the root of the other leg **121** lies outboard. Inboard leg **121** ascends at an angle from the horizontal that is steeper than the outboard leg, the respective angles  $\beta_{119}$  and  $\beta_{121}$  being in the range of 70 – 85 degrees (in one embodiment about 78 degrees) and 55 – 75 degrees (in one embodiment about 65 degrees) from the horizontal.

The secondary gripping, or stabilizing or lifting member **28** of the insulated container assembly **20** may also be attached at one or more locations. In one embodiment, second lifting member **28** may have the form of a grip or handle **120** mounted to the front side of soft-sided insulated container **22**. In cases where insulated container assembly **20** includes an auxiliary pouch **114** (Figures **1a** to **1h** and **2a** to **2f**) the handle **20** may be mounted to auxiliary pouch **114**. In other cases handle **20** may be mounted directly to front panel **34**. As noted above, handle **120** may be mounted below the vertical midway point ( $H_{20}/2$ ) of soft-sided insulated container **22**. In some embodiments handle **120** is mounted to auxiliary pouch **114** using straps **122** that run



substantially horizontal to bottom margin **50** of front panel **34**. Straps **122** may be attached to handle **120** such that there is a space **124** between handle **120** and auxiliary pouch **114**. Space **124** allows the user or carrier of the insulated container assembly **20** to at least part of the hand between auxiliary pouch **114** and handle **120** permitting the user to grip or hold onto handle **120**.

5 This asymmetric arrangement allows lifting on both the inside and outside of the bag; it may allow the hand to hold on the outside of the bag and to stabilise the bag in terms of motion around the carrier's hip, and, finally, it may permit the user to hold the bag in a manner that may tend to reduce fatigue in the carrier's arm.

10 In summary, there is a soft-sided insulated container assembly that has an asymmetric lifting arrangement. The container has a long dimension to which, in use, the carrier's hips are oriented cross-wise. That is, if the person carrying the container is walking forward, the long dimension of the bag is generally oriented in a direction more or less parallel with the direction in which the person is walking. In this embodiment the container may tend to be longer than

15 high, and higher than deep. In one embodiment the ratio of length **L**, to height **H**, to depth **W**, may be of the order of 14:12:10 (all +/- 20 %). The container has a primary lifting member, namely strap **116**, that has longitudinally spaced lifting connections, those connections straddling the centroid of the container longitudinally. That is, spreader members **115** are mounted to the long ends of the container such that the center of mass in the container, in any loading condition,

20 must lie somewhere intermediate the two longitudinal stations, namely the end walls **38**, **40**, at which lifting forces are applied. The spreader members themselves are mounted to transmit vertical shear into the endwalls **38**, **40** in a distributed manner, whether through two (or more) legs such as legs **119**, **121**, or in a triangular flap or gusset. The connection of these spreader roots lies above the centroid of the endwall, such that the center of lift may tend to lie above the

25 center of mass when the container is loaded. The soft-sided insulated container assembly also includes a secondary lifting or holding member, namely outside or outboard handle **120**. This handle is mounted longitudinally intermediate the lifting points or regions of the primary lifting member. That is, handle **120** is mid-way along the body of container assembly **20** whereas strap **116** lifts at the location of the application of forces of spreaders **115** at either end of assembly **20**.

30 Further, the centroid of the container lies between the location of application of the lateral reaction force of the carrier's body and handle **120**. In addition, the centroid of the container assembly lies between the location of application of inboard and outboard lifting forces at items **118** and **120** respectively. In some embodiments, handle **120** may tend to be longitudinally in line with the carrier's hips, or, expressed differently, the handle may be on a radius the runs

35 through the center of the container (as viewed from above) and through the wearer's hips, so



that, when held, it may tend to discourage rotation about a vertical axis of rotation relative to the carrier's hips, and thereby to stabilise the position of assembly **20** on the hip while it is being carried. Alternatively, handle **120** may facilitate such motion if and when desired, such as to dispense objects from the container. The motion is then stabilised such that undesired swaying or migration about the hips may be reduced. Thus the centroid, which may be taken as a proxy for presumed center of mass when loaded, is bracketed between the applied vertical forces longitudinally (i.e., in the x-direction) and in the inboard-outboard direction (i.e., the y-direction), and in terms of loads tending to rotate container assembly **20** about the vertical axis (or z-direction). The location may also be such as to place the crook of the carrier's elbow generally adjacent to the upper outboard vertex of the container which may, again, tend to aid in facilitating stabilization of container assembly **20** against the carrier's torso during transport.

Alternately, or optionally, insulated carrier assembly **20** may include an auxiliary access **130** to accommodation **68** in the nature of a lid or door **132** mounted as an inset in second panel **28**. Auxiliary access **130** may have an insulated wall structure, and may include a wing **134**, hingedly mounted to the main body of second panel **32**. Door **132** may employ a different type of securement from the main closure securement of second panel **32**. That is, whereas the main closure may employ a zipper, e.g. **74**, and may work to permit general access to accommodation **68** for loading, or for addition or removal of, for example, ice. Door **132**, by contrast, may be rather smaller, and may have a quick release fastener (such as Velcro™ strips), and may be of a size to permit a user to reach in and extract, an individual beverage can, without having to open the whole upper portion of the container assembly **20**. Door **132** may also have a handle **136** that allows the user to easily open door **132** to gain access to accommodation **68**. Door **132** may be of substantially the same, or predominantly the same construction as the other insulated portions of container assembly **20** more generally. Optionally, insulated container assembly **20** might also include external beverage holders, or auxiliary pockets, or lodgements, whether insulated or uninsulated.

The wall structure of the soft-sided insulated container **22** may typically include an outer layer or skin, an internal layer (or layers) of insulating material, and an inner layer or skin. Insulating material may itself be a sandwich of insulating layers, or sub layers, such as a closed cell foam layer, an open cell foam layer, and a closed cell foam layer. It may be that the outer layer, may tend to be made of a relatively wear resistant material, be it a woven polyester material or some other. The internal layer may be a sheet of Nylon, and may have a reflective inner surface. Optionally, one or more panels may have stiffening battens mounted therein, e.g.,



it may be desired that the first panel **30** be stiffened for suitability as a base upon which to rest insulated container assembly **20**, either when resting in the opened position or when standing in the closed position. In that case, either may include a reinforcement or stiffener.

5            Container **22** with liner **24** installed can be folded into a collapsed condition as shown in Figures **2a** to **2g**. In this collapsed, or storage, condition, left and right side panels **38**, **40** fold inward, and first panel **30** folds upwards. This permits front panel **34** to move towards rear panel **36**. Second panel **32** is then drawn forward and downward in front of front panel **34** and auxiliary pouch **114**. Second panel **32** has mounted to its inner face a plurality of retainers **140**  
10            with a hook and eye fastener strip **142**. The retainers **140** are drawn around so fastener strips **142** engage with fastener strips **144** mounted to the outer, rearward face of rear panel **36**. When container **22** is in the open condition, straps **140** can engage storage strip **146** located on the inner face of second panel **32** to be stored or kept out of the way.

15            In another embodiment, in Figures **3a** to **3c**, a soft insulated container assembly **220** may include a soft-sided insulated container **222**, a first or primary lifting member **224** and a second or secondary lifting member **226**.

20            The soft-sided insulated container **222** may have the general form of a generally six-sided box, or enclosure, having a first or bottom panel **228**, a second or top panel **230**, a third or front panel **232**, a fourth or back panel **234**, and a pair of left and right side panels **236** and **238**. In some embodiments the first panel **228** has a generally rectangular form, defined by a pair of first and second generally opposed long sides, or margins, **240**, **242** and a pair of first and second generally opposed short sides, or margins, **244**, **246**. The first panel **228** may have radiused  
25            corners. The second panel **230** may also have a generally rectangular form, defined by a pair of first and second generally opposed long sides, or margins, **248**, **250** and a pair of first and second generally opposed short sides, or margins, **252**, **254**.

30            Each of the third, fourth, left and right side panels **232**, **234**, **236**, **238** may have a first or bottom side or margin **256**, **258**, **260**, **262** and an opposing second or top side or margin **264**, **266**, **268**, **270**. The first margins **256**, **258** of third and fourth panels **232**, **234** are long margins that correspond to the long sides, or margins, **240**, **242** of first panel **228**, and the first margins **260**, **262** of the left and right side panels **236**, **238** correspond to the short sides, or margins, **244**, **246** of first panel **228**. The first margins **256**, **258**, **260**, **262**, of third, fourth, left side, and right  
35            side panels **232**, **234**, **236**, **238** are joined to corresponding margins **240**, **242**, **244**, **246** of first



panel **228** and may extend away from first panel **228**. The second margins **264, 266** of the third and fourth panels **232, 234** are long margins that correspond to the long sides, or margins, **248, 250** of second panel **230**, and the second margins **268, 270** of the left and right side panels **236, 238** correspond to the short sides, or margins, **252, 254** of second panel **230**. The second margins **264, 266, 268, 270** of the third, fourth, left side, and right side panels **232, 234, 236, 238** are joined to the corresponding margins **248, 250, 252, 254** of second panel **230**.

The structure thus described may tend to define a thermally insulated internal space, or cavity, or accommodation, indicated generally as **272**. Access to accommodation **272** may be obtained by installing a tracked fastener **274**, such as a zipper **276** in the top panel **230**. In some embodiments the zipper **276** may extend substantially parallel to the long sides **248, 250** of the second panel **230**. Zipper **276** may also extend into the left and right side panels **236, 238** as shown in Figure **3a** to create a larger opening to access accommodation **272**.

The rear panel of container **222** may have a securement **278** in the nature of a longitudinally running strap with a releasable clasp **280**. The strap may be of adjustable length, and may run in the longitudinal direction. The ends of the securement member may be rooted or attached to the vertical webbing of the roots of the straps of primary lifting member **224**, in such manner as may tend to distribute loads into the panel. Securement **278** is located above the height of the centroid. As noted, container assembly **220** may be quite heavy when fully loaded. In those circumstances it may be carried on a pallet, or cart, or dolly having a platform or forks that support the bottom panel. The dolly may include stanchions, or posts, or a frame that stands upwardly away from the platform or forks. Securement member **278** may be secured about that frame, and cinched tight to secure container **220** for transport.

In one embodiment, the primary lifting member **224** includes front and rear carrying handles **282** and **284** with reinforced bails attached to both front panel **232** and **234**. Front and rear carrying handles may be used by a single carrier or user to lift or transport the soft insulated container assembly **220** in the manner of a satchel, or travelling grip or duffel bag. Alternatively they may be used by two users or carriers to support assembly **220** between them. The front and rear carrying handles **282** and **284** may include attachment straps which can be used to attach front and rear carrying handles **282** and **284** together.

In one embodiment, second lifting member **226** may have the form of an handle **286** mounted to the front panel **232** of the soft-sided insulated container **222**. Handle **286** may be



mounted below the vertical midway point ( $H/2$ ) of front panel **232**. Handle **286** may be mounted to front panel **232** using straps **288** that run substantially perpendicular to bottom margin **256** of front panel **232**. In some embodiments the ends or roots of straps **288** extend at least partially across, and attach to, the underside of bottom panel **228** so that when a user or carrier pulls on handle **286** straps **288** aid in lifting container **220** and in spreading the tension into panel **228**. The straps **288** may be attached to the handle **286** in such a manner that there is a space **290** between the handle **286** and the front panel **232**. The space **290** allows the user or carrier of the insulated container assembly **220** to place their hand or at least part of their hand between the front panel **232** and the handle **286** so they can grip or hold onto the handle **286**.

As with container assembly **20**, container assembly **220** is thus provided with an asymmetric lifting arrangement that includes an inboard, upper lifting member that is eccentrically mounted relative to the centroid of the container body, and a lower, outboard grip that is located below the centroid height. The container can therefore be carried over the shoulder, and stabilised by the generally downwardly hanging hand of the user.

The wall structure of the soft-sided insulated container **222** may typically include an outer layer or skin, an internal layer (or layers) of insulating material, and an inner layer or skin. Insulating material may itself be a sandwich of insulating layers, or sub layers, such as a closed cell foam layer, an open cell foam layer, and a closed cell foam layer. It may be that the outer layer, may tend to be made of a relatively wear resistant material, be it a woven polyester material or some other. The internal layer may be a sheet of Nylon, and may have a reflective inner surface. Optionally, one or more panels may have stiffening battens mounted therein, e.g., it may be desired that the first panel **228** be stiffened for suitability as a base upon which to rest insulated container assembly **220**, either when resting in the opened position or when standing in the closed position. In that case, the first panel **228** may include a reinforcement or stiffener.

Soft insulated container assembly **20** and soft insulated container assembly **220** may include any combination of primary and second lifting members **26**, **28**, **224**, **226** described above. For example the soft insulated container assembly **20** may include primary lifting member **224** and secondary lifting member **226**, or alternatively primary lifting member **26** and secondary lifting member **226**. Similarly, soft insulated container assembly **220** may include, for example, primary lifting member **26** and secondary lifting member **28**, or primary lifting member **224** and secondary lifting member **28**.

The principles of the present invention are not limited to these specific examples which are given by way of illustration. It is possible to make other embodiments that employ the principles of the invention and that fall within its spirit and scope of the invention. Since changes in or additions to the above-described embodiments may be made without departing  
5 from the nature, spirit or scope of the invention, the invention is not to be limited to those details but only by a purposive construction of the claims as required by law.



We claim:

1. A soft-sided insulated container assembly comprising:

a soft-sided insulated container, a primary lifting member and a secondary lifting member;

said soft-sided insulated container having a front panel, a back panel and a pair of first and second side panels;

said front panel having a predominantly rectangular form, said rectangular form having a pair of first and second generally opposed first and second long sides, and a pair of first and second generally opposed short sides, said first long side being located lower than said second long side;

said primary lifting member being mounted to the pair of first and second side panels;

said primary lifting member, in use, having a center of lift closer to said back panel than to said front panel; said secondary lifting member being mounted to the front panel by mounting members such that the secondary lifting member is closer to the first long side than it is to the second long side;

said primary lifting member including a load spreading pad for engagement of a user's shoulder; and

said secondary lifting member including a bail for grasping engagement by a user's hand;

said primary lifting member has a first end and a second end;

said first end of said primary lifting member is mounted to said first side panel;

said second end of said primary lifting member is mounted to said second side panel;

said primary lifting member is a shoulder strap;

said first end of said primary lifting member has a mount that has a first leg and a second leg, each of said first leg and said second leg is mounted to said first side panel, and each of said first leg and said second leg carries a portion of load of said first end of said primary lifting member, said first and second legs being mounted asymmetrically on said first side panel, and, as mounted, said first end of said primary lifting member being tilted toward said back panel; and

said second end of said primary lifting member has a mount that has a first leg and a second leg, each of said first leg and said second leg is mounted to said second side panel, and each of said first leg and said second leg carries a portion of load of said second end of said primary lifting member, said first and second legs being mounted asymmetrically on said second side panel, and, as mounted, said second end of said primary lifting member being tilted toward said back panel.

2. The soft-sided insulated container of claim 1 wherein: said container has a length, a height and a lateral depth, said length being at least as great as said lateral depth;  
said container has a centroid relative to said length, height, and lateral depth;  
said height is at least as great as said lateral depth;  
said first and second side panels are longitudinally spaced apart;  
said front and back panels are spaced apart laterally depthwise;  
said first end of said primary lifting member passes loads into said first side panel both laterally inboard and laterally outboard of said centroid, and said second end of said primary lifting member passes loads into said second side panel both laterally inboard and laterally outboard of said centroid.
3. The soft-sided insulated container of claim 1 wherein:  
said back panel defines an inboard wall of said container assembly, and said front panel defines an outboard wall of said container assembly, in use said inboard wall being carried next to a user's body, said outboard wall being carried away from the user's body;  
said secondary lifting member is a grip having the form of a handle having a bail, said handle being mounted to said outboard wall.
4. The soft-sided insulated container of claim 1 wherein said container has a centroid and said load spreading pad has a lifting location that, in use, is higher than said centroid by a distance greater than said height of said container body.
5. The soft-sided insulated container of claim 1 wherein said second lifting member includes a handle standing outwardly from a face of said container body.
6. The soft-sided insulated container of claim 5 wherein said container has a base panel and front, back, and sidewall panels extend peripherally upwardly therefrom, and said bail is rooted to pull upwardly on said base panel.
7. The soft-sided insulated container of claim 1 wherein said back panel defines an inboard wall of said container assembly, and said front panel defines an outboard wall of said container assembly, in use said inboard wall being carried next to a user's body, said outboard wall being carried away from the user's body; said container has an uppermost panel, said uppermost panel includes a closure member; and said closure member has a hinged laterally inboard edge.



8. The soft-sided insulated container of claim 7 wherein said uppermost panel further includes an auxiliary zipperless access that is smaller than said closure member.
9. The soft-sided insulated container assembly of claim 1 wherein:  
said container has a length, a height and a lateral depth; said container has a centroid relative to said length, height, and lateral depth; said length being at least as great as said lateral depth;  
said container has a soft-sided wall structure including an outer skin, an inner skin and a layer of insulation therebetween;  
said container has an insulated chamber defined therewithin, and an externally accessible closure member governing access thereto;  
said primary lifting member first and second ends longitudinally bracketing said centroid; in use, said load spreading pad lying inboard of said container relative to said lateral depth thereof, and at an height higher than said container;  
said bail being located longitudinally intermediate said first and second ends of said primary lifting member;  
said grip being located outboard of said container body relative to said lateral depth thereof; and said grip being located at a height lower than said centroid.
10. The soft-sided insulated container of claim 9 wherein said bail stands outwardly from said front panel of said container.
11. The soft-sided insulated container of claim 10 wherein said container has a base panel and sidewall panels extending peripherally upwardly therefrom, and said secondary lifting member is rooted to pull upwardly on said base panel.
12. The soft-sided insulated container of claim 9 wherein said container has an uppermost panel, said panel includes said closure member, and said closure member has a hinged laterally inboard edge.
13. The soft-sided insulated container of claim 12 wherein said uppermost panel further includes an auxiliary zipperless access that is smaller than said closure member.
14. A soft-sided insulated container assembly comprising:  
a soft-sided insulated container body having a length, a width and a depth;

said soft-sided insulated container body having an outside surface, an inside surface, and a layer of insulation therebetween;

said insulated container body including a front wall, a back wall, a bottom wall, a top wall, a first end wall and a second end wall; and

a lifting member; said front wall being spaced apart widthwise from said back wall, said first end wall being spaced apart lengthwise from said second end wall, and said bottom wall being spaced apart depthwise from said top wall;

said length being greater than said depth, and said length being greater than said width;

said front wall, back wall, bottom wall, top wall, first end wall and second end wall cooperating to define therewithin an insulated chamber in which to accommodate objects; and

said soft-sided insulated container body including a closure member operable to govern access to said insulated chamber;

said lifting member including a shoulder strap;

said lifting member having a first end mounted to said first end wall at a first mounting;

said lifting member having a second end mounted to said second end wall at a second mounting;

said first mounting being mounted asymmetrically to said first end wall;

said second mounting being mounted asymmetrically to said second end wall;

said first and second mountings being pre-angled away from vertical on a tilted angle having a component of direction toward said back wall.

15. The soft-sided insulated container assembly of claim 14 wherein, when viewed facing said first end wall, said container assembly has a centroid, and said mountings of said first and second ends of said lifting member are mounted above said centroid.

16. The soft-sided insulated container assembly of claim 15 wherein said shoulder strap includes a load spreading pad intermediate said first and second ends thereof.

17. The soft-sided insulated container assembly of claim 16 wherein said load-spreading pad has a predominantly triangular shape, with the base side of the triangle being for placement on the wearer's shoulder oriented away from the wearer's neck.

18. The soft-sided insulated container assembly of claim 15 wherein said back wall is an inboard wall, and said front wall is an outboard wall, said first end mounting includes an end spreader, said end spreader including a first portion secured to said first end wall inboard of said centroid, and a second portion secured to said first end wall outboard of said centroid.



19. The soft-sided insulated container assembly of claim 18 wherein said first portion ascends at a first angle to the vertical, said second portion ascends at a second angle to the vertical, and said first angle is steeper than said second angle.
20. The soft-sided insulated container assembly of claim 18 wherein said end spreader includes one of (a) at least two legs mounted to said first end wall; and (b) a triangular gusset mounted to said first end wall.
21. The soft-sided insulated container assembly of claim 14 wherein said first mounting includes an end spreader, said end spreader including a first portion secured to said first end panel inboard of said centroid, and a second portion secured to said first end panel outboard of said centroid.
22. The soft-sided insulated container assembly of claim 21 wherein said first portion ascends at a first angle to the vertical, said second portion ascends at a second angle to the vertical, and said first angle is steeper than said second angle.
23. The soft-sided insulated container assembly of claim 21 wherein said spreader member includes one of (a) at least two legs mounted to said first end wall; and (b) a triangular gusset mounted to said first end wall.
24. The soft-sided insulated container of claim 14 wherein said soft-sided insulated container is foldable to a collapsed position, and has fittings operable releasably to secure said soft-sided insulated container in said collapsed position.
25. A soft-sided insulated container assembly comprising:  
a soft-sided insulated container body having a length, a width and a depth;  
said soft-sided insulated container body having an outside surface, an inside surface, and a layer of insulation therebetween;  
said insulated container body including a front wall, a back wall, a bottom wall, a top wall, a first end wall and a second end wall; and  
a lifting member;  
said front wall being spaced apart widthwise from said back wall, said first end wall being spaced apart lengthwise from said second end wall, and said bottom wall being spaced apart depthwise from said top wall;

said length being greater than said depth, and said length being greater than said width;  
said front wall, back wall, bottom wall, top wall, first end wall and second end wall cooperating to define therewithin an insulated chamber in which to accommodate objects; and  
said soft-sided insulated container body including a closure member operable to govern access to said insulated chamber;  
said lifting member including a shoulder strap;  
said lifting member having a first end mounted to said first end wall at a first mounting;  
said lifting member having a second end mounted to said second end wall at a second mounting; said first mounting being asymmetric to said first end wall relative to vertical; and  
said second mounting being asymmetric to said second end wall relative to vertical.

26. The soft-sided insulated container assembly of claim 25 wherein said first and second mountings being pre-angled away from vertical on a tilted angle having a component of direction toward said back wall.

27. The soft-sided insulated container assembly of claim 25 wherein, when viewed facing said first end wall, said container assembly has a centroid, and said mountings of said first and second ends of said lifting member are mounted above said centroid.

28. The soft-sided insulated container assembly of claim 26 wherein, when viewed facing said first end wall, said container assembly has a centroid, and said mountings of said first and second ends of said lifting member are mounted above said centroid.

29. The soft-sided insulated container assembly of claim 26 wherein said back wall is an inboard wall and said front wall is an outboard wall, said first end mounting includes an end spreader, said end spreader including a first portion secured to said first end wall inboard of said centroid, and a second portion secured to said first end wall outboard of said centroid.

30. The soft-sided insulated container assembly of claim 29 wherein said first portion ascends at a first angle to the vertical, said second portion ascends at a second angle to the vertical, and said first angle is steeper than said second angle.

31. The soft-sided insulated container assembly of claim 29 wherein said end spreader includes one of (a) at least two legs mounted to said first end wall; and (b) a triangular gusset mounted to said first end wall.



32. The soft-sided insulated container assembly of claim 25 wherein said shoulder strap includes a load spreading pad intermediate said first and second ends thereof.
33. The soft-sided insulated container assembly of claim 32 wherein said load-spreading pad has a predominantly triangular shape, with the base side of the triangle being for placement on the wearer's shoulder oriented away from the wearer's neck.
34. The soft-sided insulated container of claim 25 wherein said soft-sided insulated container is foldable to a collapsed position, and has fittings operable releasably to secure said soft-sided insulated container in said collapsed position.
35. The soft-sided insulated container assembly of claim 26 wherein a handle is mounted to said front wall at a height lower than said centroid.
36. A soft-sided insulated container assembly comprising:  
a generally box-like insulated wall structure defining a chamber in which to place objects;  
said box-like insulated wall structure having first and second end walls spaced apart from each other in a lengthwise direction;  
a lifting member; said lifting member including a shoulder strap;  
said lifting member having a first end mounted to said first end wall at a first mounting;  
said lifting member having a second end mounted to said second end wall at a second mounting; and  
when viewed looking in the length-wise direction, said first mounting and said second mounting are angled away from vertical.
37. The soft-sided insulated container of claim 36 wherein said first end wall has a vertical axis, and, when viewed looking in the lengthwise direction, said first mounting is asymmetric relative to vertical.
38. The soft-sided insulated container of claim 36 wherein said first end wall has a centroid and, when viewed in the lengthwise direction, the first mounting is located upwardly of the centroid.
39. The soft-sided insulated container of claim 36 wherein, when viewed in the lengthwise direction, said first mounting is eccentric relative to said first end wall.

40. The soft-sided insulated container of claim 36 wherein said first end mounting includes an end spreader secured to said first end wall, said end spreader including a first portion and a second portion secured to said first end wall, said first portion being closer to said back wall than is said second portion.

41. The soft-sided insulated container of claim 40 wherein said first portion of said end spreader ascends at a first angle to the vertical, said second portion of said end spreader ascends at a second angle to the vertical, and said first angle is steeper than said second angle.

42. The soft-sided insulated container assembly of claim 40 wherein said end spreader includes one of (a) at least two legs mounted to said first end wall; and (b) a triangular gusset mounted to said first end wall.

43. The soft-sided insulated container of claim 36 wherein: said first end wall has a vertical axis, and, when viewed looking in the lengthwise direction, said first mounting is asymmetric relative to vertical and eccentric relative to said first end wall;

said first and second mountings being angled away from vertical on a tilted angle having a component of direction toward said back wall;

said first end wall has a centroid and, when viewed in the lengthwise direction, the first mounting is located upwardly of the centroid;

said first end mounting includes an end spreader, said end spreader including a first portion and a second portion, said first portion and said second portion being secured to said first end wall, said first portion being closer to said back wall than is said second portion;

said second mounting being mounted asymmetrically to said second end wall;

said end spreader includes one of (a) at least two legs mounted to said first end wall; and (b) a triangular gusset mounted to said first end wall.

44. The soft-sided insulated container of claim 36 wherein said soft-sided insulated container is foldable to a collapsed position, and has fittings operable releasably to secure said soft-sided insulated container in said collapsed position.






Figure 1a




Figure 1b







Figure 1c



**Figure 1d**






Figure 1e




Figure 1f







Figure 1g



**Figure 1h**








Figure 2a



**Figure 2b**





**Figure 2c**






Figure 2d






**Figure 2e**



**Figure 2f**



**Figure 3a**






Figure 3b




Figure 3c

