

(19)



(11)

EP 1 810 583 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
13.01.2010 Bulletin 2010/02

(51) Int Cl.:
A42B 3/32 (2006.01)

(21) Application number: **07100921.1**

(22) Date of filing: **22.01.2007**

(54) Adjustment mechanism for a helmet

Verstellmechanismus für einen Helm

Mécanisme d'ajustement pour casque

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**

- **ROGERS, Charles H.**
HALIFAX, MA 02338 (US)
- **STOKES, Peter**
BOSTON, MA 02113 (US)

(30) Priority: **20.01.2006 CA 2533493**

(74) Representative: **Texier, Christian et al**
Cabinet Régimbeau
20, rue de Chazelles
75847 Paris Cedex 17 (FR)

(43) Date of publication of application:
25.07.2007 Bulletin 2007/30

(56) References cited:
WO-A-2006/005184 US-A- 4 539 715
US-A- 5 956 776 US-A1- 2004 172 739
US-A1- 2005 015 857 US-B1- 6 324 700

(73) Proprietor: **Sport Maska Inc.**
Montréal, Québec H4R 3L3 (CA)

(72) Inventors:
• **ROGERS, David**
BOSTON, MA 02210 (US)

EP 1 810 583 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates in general to helmets and, more particularly, to a mechanism for adjusting the size of a helmet.

2. Background Art

[0002] Adjustable helmets have been known in the art for years, and used in different applications such as sports, firefighting, construction work, and the military. In particular, many of these adjustable helmets allow the wearer to adjust the helmet size to fit a particular head. For example, helmet adjustment mechanisms have consisted of a stud and notch or a headband with a rack and pinion adjusting mechanism.

[0003] Although these and other conventional adjustment mechanisms have worked well, they have failed in a number of areas. For instance, many prior art designs do not allow the helmet wearer to adjust the size of the helmet while wearing the helmet. Accordingly, the helmet wearer must remove the helmet, adjust the helmet, and retry the helmet size multiple times before a proper fit can be established.

[0004] Additionally, in many prior art devices, adjustment occurs merely with respect to a headband lodged and secured inside of a helmet, not with respect to the size of the helmet shell itself. Consequently, a specific helmet size, though fitting a wearer because of a headband adjustment, is not appropriate for the wearer.

[0005] Moreover many prior art adjustment mechanisms present a risk of being accidentally actuated which can leave the wearer susceptible to injury.

[0006] WO 2006/005184 discloses an adjustment mechanism for a helmet, featuring a first sliding surface with an opening with a plurality of fingers, a second sliding surface, the two surfaces being in sliding engagement with one another and a locking mechanism with teeth which interlock with the fingers.

SUMMARY OF INVENTION

[0007] It is therefore an aim of the present invention to provide an improved helmet adjustment mechanism.

[0008] Therefore, in accordance with the present invention, there is provided an adjustment mechanism for a helmet, the mechanism comprising a first sliding surface defined in a first portion of the helmet, the first sliding surface including an opening (i.e. an elongated opening) defined through the first portion, a second sliding surface defined in a second portion of the helmet, the second sliding surface having two spaced apart arms extending therefrom, the first and second sliding surfaces being in sliding engagement with one another with the arms pro-

truding through the opening and slideable therewithin, and a lever pivotally connected to the first portion in proximity to the opening and pivotable between a locked position and an unlocked position, the lever having a series of regularly spaced apart parallel teeth which in the locked position protrude through the opening with at least a selected one of the teeth being engageable between the two spaced apart arms to prevent the first and second sliding surfaces from sliding relative to one another, the lever in the unlocked position being pivoted away from the opening such that the teeth are disengaged from the arms.

[0009] Also in accordance with the present invention, there is provided a helmet comprising a first shell section including at least one first sliding surface with an opening (i.e. an elongated opening) defined therethrough, a second shell section connected to the first shell section to form a helmet shell, the first and second shell sections being connected to allow a relative sliding motion therebetween, the second shell section having one corresponding second sliding surface for each first sliding surface, the second sliding surface being in sliding engagement with the first sliding surface and having at least two spaced apart arms extending therefrom and protruding through the opening such that the relative sliding motion causes the arms to slide within the opening, and a lever for each first sliding surface, the lever having at least two teeth protruding therefrom, the lever being pivotally connected to the first shell section in proximity to the opening to be pivotable between a locked position and an unlocked position, the lever in the locked position having the teeth protruding through the opening with a selected one of the teeth being engageable between the two spaced apart arms to block the relative sliding motion, the lever in the unlocked position having the teeth disengaged from the arms to allow the relative sliding motion.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0010]** Reference will now be made to the accompanying drawings, showing by way of illustration a particular embodiment of the present invention and in which:
- [0011]** Figure 1 is a perspective view of a helmet having an adjustment mechanism according to a particular embodiment of the present invention;
- [0012]** Figure 2 is a perspective exploded view of a front section and of levers of the helmet of Figure 1;
- [0013]** Figure 3 is a side, partial view of the helmet of Figure 1, showing one of the levers in an unlocked position;
- [0014]** Figure 4 is a side view of a rear section of the helmet of Figure 1;
- [0015]** Figure 5 is a front view of the lever of Figure 3;
- [0016]** Figure 6 is a rear view of the lever of Figure 3; and
- [0017]** Figure 7 is a side view of the lever of Figure 3.

DESCRIPTION OF THE PARTICULAR EMBODIMENTS

[0018] Referring to Figure 1, a helmet such as a hockey helmet generally shown at 10 comprises a front section 12 and a rear section 14 cooperating to form a helmet shell. The front and rear sections 12,14 are preferably formed of a high strength plastic material, composite material or a combination of two or more materials having an impact absorbing liner 16 disposed therein. The front and rear sections 12, 14 are interconnected through a pair of locking assemblies generally indicated at 18, only one of which being shown in Figure 1. The locking assemblies 18 are part of the adjustment mechanisms according to a particular embodiment of the present invention.

[0019] Referring to Figure 2, the front section 12 has an inner surface 20 facing the head of a user and an opposed outer surface 22. The front section 12 also has two opposed side portions 24a,b, each including an elongated recess 26 defined in the outer surface 22. Although the recess 26 is shown here as having a parallelogram shape, it is understood that various other shapes are also possible, for example oblong, rectangular, triangular, etc. The recess 26 is defined by a recessed wall 28 substantially parallel to and inwardly offset from the outer surface 22, and connected thereto along its perimeter by a recessed border 30.

[0020] The recessed wall 28 includes an elongated opening 32 defined therethrough configured and designed to be in communication with the inner surface 20. Referring to Fig. 3, the opening 32 is formed by an elongated hole 34 from which extends a series of regularly spaced apart slots 36. The elongated hole 34 has a parallelogram shape defined by two parallel elongated sides 38 and two parallel short sides 40, the short sides 40 defining a width W_h of the elongated hole 34. The spaced apart slots 36 extend substantially parallel to the short sides 40, with each slot 36 extending from one of the elongated sides 38 in alignment with a corresponding slot 36 extending from the other elongated side 38.

[0021] Referring to Figures 2 and 3, the front section 12 also has first, second and third holes 42,44,46 defined in each of the side portions 24a,b. Each first hole 42 is defined through its respective recessed wall 28, while the second and third holes 44,46 are defined through the wall of the side portion 24a,b under the respective recess 26.

[0022] Referring to Figure 4, the rear section 14 has an inner surface (not shown), an outer surface 48, and two side portions 50 (only one of which is shown). Each side portion 50 has first, second and third slots 52,54,56 defined therethrough. The slots 52,54,56 are substantially parallel to each other and spaced apart in a pattern corresponding to a pattern formed by the first, second and third holes 42,44,46 of the front section 12, such that each slot 52,54,56 is aligned with a corresponding one of the holes 42,44,46 when the front and rear sections

12,14 are engaged to form the helmet 10.

[0023] In the embodiment shown, the slots 52,54,56 have an oblong shape, although alternate shapes such as rectangular, polygonal, etc. are also possible. Of course, the holes 42,44,46 and slots 52,54,56 can be in a number of alternative locations and configurations, including having the slots 52,54,56 defined in the front section 12 and the holes 42,44,46 defined in the rear section 14 and/or having more or less holes 42,44,46 and slots 52,54,56.

[0024] A plurality of screws 58 (see Figures 1 and 2) interconnect the front and rear sections 12,14, one screw 58 being inserted through each pair of corresponding hole and slot 42,52; 44,54; 46,56. The interconnected front and rear sections 12,14 are thus slidably with respect to one another through sliding of the screws 58 within the respective slot 52,54,56. The contact between the front and rear sections 12,14 is done through sliding surfaces 57,59 which are in sliding engagement with one another in a substantially interference-free manner. The sliding surfaces 57 of the front section 12 are defined by the inner surface 20 thereof within the side portions 24a, b (see Figure 2). The sliding surfaces 59 of the rear section 14 are defined by the outer surface 48 thereof within the side portions 50 (see Figure 4). Also, as the top portion of the rear section 14 overlaps the top portion of the front section 12 when the two are engaged to one another, the outer surface 22 of the front section 12 at that location slides against the inner surface (not shown) of the rear section 14, again without substantial interference.

[0025] The helmet front and rear sections 12,14 may be releasably secured together in a desired adjusted position by the locking assemblies 18. As part of the locking assemblies 18, each side portion 50 of the rear section 14 includes two spaced apart arms 60 (see Figures 3-4) extending from the outer surface 48. As can be seen in Figure 3, the arms 60 have a width W_a which is smaller than the width W_h of the elongated hole 34 of the front section 12, and are located such as to extend therethrough when the front and rear sections 12,14 are slidably engaged. Thus, the arms 60 are slidable within the elongated hole 34 following the relative sliding motion of the front and rear sections 12,14. The arms 60 define a free space 61 therebetween which has substantially the same size than and can be substantially aligned with corresponding slots 36 of the opening 32.

[0026] Each locking assembly 18 also includes a lever 62a,b. Referring to Figures 5 to 7, only the left-side lever 62b will be described in further detail, the right-side lever 62a being a mirror image of the left-side lever 62b. The lever 62b includes a body 64 shown here as having a parallelogram shape, although other shapes are also possible. In the embodiment shown, the body 64 is shaped such as to be receivable within the corresponding recess 26, as will be further detailed below.

[0027] Two attachment arms 66 extend from the body 64, each arm 66 having a hole 68 defined therethrough

(see Figure 7) with the two holes 68 being aligned with one another. The arms are receivable within corresponding indentations 70 defined in the front section 12 in proximity of the recess 26 (see Figure 2). A pin (not shown) is insertable through the aligned holes 68 and retained on the front section 12, thus attaching the lever 62b to the front section 12 in a pivotable manner. Other means of pivotably attaching levers 62a,b to the front section are possible, including through the use of a press-fit attachment, etc. The lever 62b is thus pivotable between a locked position, where the body 64 can be located within the recess 26 of the front section 12 (see Figure 1) and an unlocked position, where the body 64 can extend, for example, substantially perpendicular to the adjacent portion of the outer surface 22 of the front section 12 (see Figure 3). In an alternate embodiment, the recess 26 can be omitted and the lever 62b in the locked position lies against the outer surface 22 of the side portion 24.

[0028] Referring to Figure 5, the body 64 defines an outer surface 72 upon which can be included a desired indicia, for example the helmet brand or a team logo.

[0029] Referring to Figures 6-7, the body 64 also defines an inner surface 74 from which extend a plurality of spaced apart teeth 76, 78. In the embodiment shown, the teeth 76,78 are distributed in a top row of teeth 76 and a bottom row of teeth 78, with each top tooth 76 being aligned with a corresponding bottom tooth 78. Alternatively, the two rows of aligned teeth 76,78 can be replaced by a single row of larger teeth.

[0030] The teeth 76,78 are sized and positioned to be insertable in the slots 36 of the opening 32 of the front section 12 when the lever 62a,b is in the locked position, and as such are shown here as being distributed following a parallelogrammic pattern. The top and bottom teeth 76,78 thus together have a total width W_t (see Figure 6) which is greater than the width W_h (see Figure 3) of the elongated hole 34, the portion of the teeth 76,78 extending beyond the hole 34 being receivable within the slots 36. Of course, other configurations are possible, as long as the opening 32 is configured adequately to be able to receive the teeth 76,78 therein.

[0031] The body 64 is also shown as having a plurality of holes 80 defined therethrough between each pair of aligned bottom and top teeth 76,78, although such holes 80 can be alternately omitted.

[0032] Thus, in use and as described above, the helmet is formed by assembling the front and rear sections 12,14 (see Figure 1) by inserting and securing the screws 58 (see Figures 1-2) into each of the first, second and third slots 52,54,56 and corresponding one of the first, second and third holes 42,44,46.

[0033] Then, the size of the helmet 10 is adjusted with the levers 62a,b in the unlocked position shown in Figure 3. The front and rear sections 12,14 are thus free to slide with respect to one another, within a limit determined by the sliding motion of each screw 58 in its respective slot 52,54,56, and by the sliding motion of the arms 60 within the elongated hole 34. The front and rear sections 12,14

are moved to one of the positions where the free space 61 between the arms 60 is substantially continuous with one pair of aligned slots 36 of the opening 32. In the embodiment shown, seven (7) different positions are thus possible, i.e. one for each pair of aligned slots 36, although it is understood that more or less positions can be provided by varying the number of slots 36 or the number of arms 60.

[0034] Once the front and rear sections 12,14 are in the desired position, the levers 62a,b are pivoted to the locked position shown in Figure 1, where the teeth 76,78 are engaged in the elongated hole 34 and slots 36 of the opening 32 of the front section 12, and one pair of top and bottom teeth 76,78 is additionally engaged in the space 61 between the arms 60 extending from the rear section 14. Alternately, in cases where a single row of larger teeth are provided as discussed above, a single tooth is engaged within the space 61. Thus, the engaged arms 60 and teeth 76,78 effectively block the relative sliding motion of the front and rear sections 12,14, thus locking the helmet 10 in the desired position and size. The adjustment can be accomplished while a user is wearing the helmet 10 or, if desired, while the helmet 10 is removed from the wearer's head.

[0035] In the locked position, the levers 62a,b can advantageously be completely contained in the respective recess 26, and in a particular embodiment, disposed below the level of the outer surface 22 of the front section 12, and as such shielded from accidental or unwanted contact.

[0036] The embodiments of the invention described above are intended to be exemplary. Those skilled in the art will therefore appreciate that the foregoing description is illustrative only, and that various alternatives and modifications can be devised without departing from the spirit of the present invention.

[0037] For example, the present device could be used in numerous other types of helmets or protection gear, and should not be viewed as limited to hockey or even sports. For example, the present invention may be used in relation to lacrosse, football, and other contact sports. Also, the slots 36 could be omitted from the opening 32, and in this case the teeth 76,78 would be sized to fit within the elongated hole 34. More or less teeth 76,78 can be provided, as well as more than two arms 60.

[0038] Accordingly, the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

50

Claims

1. An adjustment mechanism for a helmet (10), the mechanism comprising:

55

a first sliding surface (57) defined in a first portion of the helmet (12), the first sliding surface (57) including an opening (32) defined through the

- first portion;
 a second sliding surface (59) defined in a second portion (14) of the helmet, the second sliding surface (59) having two spaced apart arms (60) extending therefrom, the first (57) and second (59) sliding surfaces being in sliding engagement with one another with the arms (60) protruding through the opening (32) and slidable therewithin; and
 a lever (62) pivotally connected to the first portion in proximity to the opening (32) and pivotable between a locked position and an unlocked position, the lever (62) having a series of regularly spaced apart parallel teeth (76,78) which in the locked position protrude through the opening (32) with at least a selected one of the teeth (76,78) being engageable between the two spaced apart arms (60) to prevent the first (57) and second (59) sliding surfaces from sliding relative to one another, the lever (62) in the unlocked position being pivoted away from the opening (32) such that the teeth (76, 78) are disengaged from the arm (60).
 5
2. The adjustment mechanism according to claim 1, wherein the first section has a recess defined therein around the opening, the lever being received in the recess in the locked position.
 25
3. The adjustment mechanism according to claim 1, wherein the opening is formed by an elongated hole and a series of parallel, regularly spaced apart slots extending from the elongated hole, the elongated hole slidably receiving the arms therein, and wherein when the lever is in the locked position a first portion of the teeth is received in the elongated hole and a remaining portion of the teeth is received within the slots.
 30
4. The adjustment mechanism according to claim 1, wherein the first and second sliding surfaces are in sliding engagement without substantial interference therebetween.
 40
5. A helmet (10) comprising:
 45
 a first shell section (12) including at least one first sliding surface (57) with an opening (32) defined therethrough;
 a second shell section (14) connected to the first shell section (12) to form a helmet shell, the first (12) and second (14) shell sections being connected to allow a relative sliding motion therebetween, the second shell section (14) having one corresponding second sliding surface (59) for each first sliding surface (57), the second sliding surface (59) being in sliding engagement with the first sliding surface (57) and having at least two spaced apart arms (60) extending therefrom and protruding through the opening (32) such that the relative sliding motion causes the arms (60) to slide within the opening (32) ; and
 a lever (62) for each first sliding surface (57), the lever (62) having at least two teeth (76,78) protruding therefrom, the lever (62) being pivotally connected to the first shell section (12) in proximity of the opening (32) to be pivotable between a locked position and an unlocked position, the lever (62) in the locked position having the teeth (76,78) protruding through the opening (32) with a selected one of the teeth (76,78) being engageable between the two spaced apart arms (60) to block the relative sliding motion the lever (62) in the unlocked position having the teeth (76,78) disengaged from the arms (60) to allow the relative sliding motion.
 55
6. The helmet according to claim 5, wherein the first section includes two opposed first side portions with an inner surface of each first side portion defining one of the at least one first sliding surface, and the second section includes two opposed second side portions with an outer surface of each second side portion defining one of the corresponding second sliding surfaces.
 60
7. The helmet according to claim 5, wherein an outer surface of a top portion of the first section is in contact with an inner surface of a top portion of the second section.
 65
8. The helmet according to claim 5, wherein one of the first and second sections has a plurality of slots defined therein and the other of the first and second sections has a corresponding hole defined therein for each of the plurality of slots, the second section being connected to the first section by the insertion of a connecting member through each of the slots and corresponding hole, the connecting members being slidable within a respective one of the slots to allow the relative sliding motion.
 70
9. The helmet according to claim 5, wherein the first section is a front section of the helmet shell and the second section is a rear section of the helmet shell.
 75
10. The adjustment mechanism according to claim 5, wherein the first section has a recess defined therein around the opening, the lever being received in the recess in the locked position.
 80
11. The adjustment mechanism according to claim 5, wherein the opening is formed by an elongated hole and a series of parallel, regularly spaced apart slots extending therefrom, the elongated hole slidably re-

ceiving the arms therein and having a width smaller than a total width of the teeth, and the slots being located and sized to receive a portion of the teeth extending beyond the elongated hole when the lever is in the locked position.

5

12. The adjustment mechanism according to claim 5, wherein the first and second sliding surfaces are in sliding engagement without substantial interference therebetween.

10

Patentansprüche

1. Verstellmechanismus für einen Helm (10), wobei der Mechanismus folgendes umfasst:

eine erste Gleitfläche (57), die in einem ersten Teil (12) des Helms definiert ist, wobei die erste Gleitfläche (57) eine Öffnung (32) umfasst, die durch den ersten Teil hindurch definiert ist; eine zweite Gleitfläche (59), die in einem zweiten Teil (14) des Helms definiert ist, wobei die zweite Gleitfläche (59) zwei beabstandete Arme (60) umfasst, die sich von dieser aus erstrecken, wobei die ersten (57) und zweiten (59) Gleitflächen miteinander in gleitendem Eingriff stehen, wobei die Arme (60) durch die Öffnung (32) hervorragen und darin verschiebbar sind; und einen Hebel (62), der verschwenkbar mit dem ersten Teil in der Nähe der Öffnung (32) verbunden ist und zwischen einer verriegelten Position und einer entriegelten Position verschwenkbar ist, wobei der Hebel (62) eine Reihe von gleichmäßig beabstandeten parallelen Zähnen (76, 78) aufweist, die in der verriegelten Position durch die Öffnung (32) hindurch hervorragen, wobei mindestens ein ausgewählter Zahn der Zähne (76, 78) zwischen die beiden beabstandeten Arme (60) in Eingriff gebracht werden kann, um die ersten (57) und zweiten (59) Gleitflächen daran zu hindern, sich im Verhältnis zueinander zu verschieben, wobei der Hebel (62) in der entriegelten Position von der Öffnung (32) weg verschwenkt wird, so dass die Zähne (76, 78) aus den Armen (60) gelöst werden.

20

25

30

35

40

45

2. Verstellmechanismus nach Anspruch 1, wobei der erste Abschnitt eine darin definierte Vertiefung um die Öffnung herum aufweist, wobei der Hebel in der verriegelten Position in der Vertiefung aufgenommen wird.

50

3. Verstellmechanismus nach Anspruch 1, wobei die Öffnung durch ein längliches Loch und eine Reihe von parallelen, gleichmäßig beabstandeten Schlitten gebildet wird, die sich von dem länglichen Loch aus erstrecken, wobei das längliche Loch die Arme

55

darin verschiebbar aufnimmt, und wobei, wenn der Hebel sich in der verriegelten Position befindet, ein erster Teil der Zähne in dem länglichen Loch aufgenommen wird, und ein restlicher Teil der Zähne in den Schlitten aufgenommen wird.

4. Verstellmechanismus nach Anspruch 1, wobei die ersten und zweiten Gleitflächen sich in verschiebbarem Eingriff ohne wesentliche Störung dazwischen befinden.

5. Helm (10), umfassend:

einen ersten Schalenabschnitt (12), der mindestens eine erste Gleitfläche (57) mit einer durch diese hindurch definierten Öffnung (52) umfasst;

einen zweiten Schalenabschnitt (14), der mit dem ersten Schalenabschnitt (12) verbunden ist, um eine Helmschale zu bilden, wobei der erste (12) und der zweite (14) Schalenabschnitt verbunden sind, um dazwischen eine relative Gleitbewegung zu ermöglichen, wobei der zweite Schalenabschnitt (14) eine entsprechende zweite Gleitfläche (59) für jede erste Gleitfläche (57) aufweist, wobei die zweite Gleitfläche (59) sich mit der ersten Gleitfläche (57) in verschiebbarem Eingriff befindet und mindestens zwei beabstandete Arme (60) aufweist, die sich davon aus erstrecken und durch die Öffnung (32) hindurch hervorragen, so dass die relative Gleitbewegung die Arme (60) veranlasst, in der Öffnung (52) zu gleiten; und

einen Hebel (62) für jede erste Gleitfläche (57), wobei der Hebel (62) mindestens zwei Zähne (76, 78) aufweist, die davon hervorragen, wobei der Hebel (62) verschwenkbar mit dem ersten Schalenabschnitt (12) in der Nähe der Öffnung (32) verbunden ist, um zwischen einer verriegelten Position und einer entriegelten Position verschwenkbar zu sein, wobei der Hebel (62) in der verriegelten Position die Zähne (76, 78) aufweist, die durch die Öffnung (32) hervorragen, wobei einer der Zähne (76, 78) zwischen den beiden beabstandeten Armen (60) in Eingriff gebracht werden kann, um die relative Gleitbewegung zu blockieren, wobei an dem Hebel (62) in der entriegelten Position die Zähne (76, 78) von den Armen (60) gelöst sind, um die relative Gleitbewegung zu ermöglichen.

6. Helm nach Anspruch 5, wobei der erste Abschnitt zwei gegenüberliegende erste Seitenteile umfasst, wobei eine Innenfläche jedes ersten Seitenteils eine der mindestens einen ersten Gleitfläche definiert, und der zweite Abschnitt zwei gegenüberliegende Seitenteile umfasst, wobei eine Außenfläche jedes zweiten Seitenteils eine der entsprechenden zwei-

- ten Gleitflächen definiert.
7. Helm nach Anspruch 5, wobei sich eine Außenfläche eines oberen Teils des ersten Abschnitts sich mit einer Innenfläche eines oberen Teils des zweiten Abschnitts in Kontakt befindet. 5
8. Helm nach Anspruch 5, wobei einer der ersten und zweiten Abschnitte eine Vielzahl von darin definierten Schlitten aufweist und in dem anderen der ersten und zweiten Abschnitte ein entsprechendes Loch definiert ist für jeden der Vielzahl von Schlitten, wobei der zweite Abschnitt mit dem ersten Abschnitt durch das Einfügen eines Verbindungselements durch jeden der Schlüsse und ein entsprechendes Loch hindurch verbunden ist, wobei die Verbindungselemente in einem jeweiligen Schlitz der Schlüsse verschiebbar sind, um die relative Gleitbewegung zu ermöglichen. 10 15
9. Helm nach Anspruch 5, wobei der erste Abschnitt ein vorderer Abschnitt der Helmschale und der zweite Abschnitt ein hinterer Abschnitt der Helmschale ist. 20 25
10. Verstellmechanismus nach Anspruch 5, wobei der erste Abschnitt eine darin definierte Vertiefung um die Öffnung herum aufweist, wobei der Hebel in der verriegelten Position in der Vertiefung aufgenommen wird. 30
11. Verstellmechanismus nach Anspruch 5, wobei die Öffnung durch ein längliches Loch und eine Reihe von parallelen, gleichmäßig beabstandeten Schlitten gebildet ist, die sich davon aus erstrecken, wobei das längliche Loch die Arme darin verschiebbar aufnimmt und eine Breite aufweist, die kleiner ist als eine Gesamtbreite der Zähne, und die Schlüsse angeordnet und dimensioniert sind, um einen Teil der Zähne aufzunehmen, der sich über das längliche Loch hinaus erstreckt, wenn der Hebel sich in der verriegelten Position befindet. 35 40
12. Verstellmechanismus nach Anspruch 5, wobei die ersten und zweiten Gleitflächen sich in verschiebbarem Eingriff ohne wesentliche Störung dazwischen befinden. 45
- partie ; une seconde surface coulissante (59) définie dans une seconde partie (14) du casque, la seconde surface coulissante (59) comportant deux bras espacés l'un de l'autre (60) s'étendant à partir de celle-ci, les première (57) et seconde (59) surfaces coulissantes étant en prise coulissante l'une avec l'autre, les bras (60) faisant saillie à travers l'ouverture (32) et pouvant coulisser à l'intérieur de celle-ci ; et un levier (62) relié de façon pivotante à la première partie à proximité de l'ouverture (32) et pouvant pivoter entre une position verrouillée et une position déverrouillée, le levier (62) comportant une série de dents parallèles espacées régulièrement les unes des autres (76, 78) qui, dans la position verrouillée, font saillie à travers l'ouverture (32), au moins une dent sélectionnée parmi les dents (76, 78) pouvant s'engager entre les deux bras espacés l'un de l'autre (60) pour empêcher les première (57) et seconde (59) surfaces coulissantes de coulisser l'une par rapport à l'autre, le levier (62) dans la position déverrouillée étant éloigné, en pivotant, de l'ouverture (32) de sorte que les dents (76, 78) se séparent des bras (60).
2. Mécanisme d'ajustement selon la revendication 1, dans lequel la première section comporte un évidement défini dans celle-ci autour de l'ouverture, le levier étant reçu dans l'évidement dans la position verrouillée. 30
3. Mécanisme d'ajustement selon la revendication 1, dans lequel l'ouverture est formée par un orifice allongé et une série de fentes parallèles espacées régulièrement les unes des autres s'étendant à partir de l'orifice allongé, l'orifice allongé recevant les bras dans celui-ci de façon coulissante, et dans lequel, lorsque le levier est dans la position verrouillée, une première partie des dents est reçue dans l'orifice allongé et une partie restante des dents est reçue à l'intérieur des fentes. 35 40
4. Mécanisme d'ajustement selon la revendication 1, dans lequel les première et seconde surfaces coulissantes sont en prise coulissante sans serrage important entre celles-ci. 45
5. Casque (10) comprenant : 50

Revendications


1. Mécanisme d'ajustement pour un casque (10), le mécanisme comprenant :


une première surface coulissante (57) définie dans une première partie du casque (12), la première surface coulissante (57) comprenant une ouverture (32) définie à travers la première


une première section de coquille (12) comprenant au moins une première surface coulissante (57) avec une ouverture (32) définie à travers celle-ci ; une seconde section de coquille (14) reliée à la première section de coquille (12) pour former une coquille de casque, les première (12) et se-

- conde (14) sections de coquille étant reliées pour permettre un mouvement coulissant relatif entre celles-ci, la seconde section de coquille (14) comportant une seconde surface coulissante correspondante (59) pour chaque première surface coulissante (57), la seconde surface coulissante (59) étant en prise coulissante avec la première surface coulissante (57) et comportant au moins deux bras espacés l'un de l'autre (60) s'étendant à partir de celle-ci et faisant saillie à travers l'ouverture (32) de sorte que le mouvement coulissant relatif entraîne le coulis- 5
sement des bras (60) à l'intérieur de l'ouverture (32) ; et
- un levier (62) pour chaque première surface coulissante (57), le levier (62) comportant au moins deux dents (76, 78) faisant saillie à partir de celui-ci, le levier (62) étant relié de façon pi- 15
votante à la première section de coquille (12) à proximité de l'ouverture (32) pour pouvoir pivo-
ter entre une position verrouillée et une position déverrouillée, le levier (62), dans la position ver-
rouillée, ayant les dents (76, 78) en saillie à tra-
vers l'ouverture (32), une dent sélectionnée par- 20
mi les dents (76, 78) pouvant s'engager entre les deux bras espacés l'un de l'autre (60) pour bloquer le mouvement coulissant relatif, le levier (62), dans la position déverrouillée, ayant les 25
dents (76, 78) séparées des bras (60) pour per-
mettre le mouvement coulissant relatif. 30
6. Casque selon la revendication 5, dans lequel la première section comprend deux premières parties latérales opposées, une surface intérieure de chaque première partie latérale définissant une parmi l'au- 35
moins une première surface coulissante, et la seconde section comprend deux secondes parties latérales opposées, une surface extérieure de chaque seconde partie latérale définissant une des secon-
des surfaces coulissantes correspondantes. 40
7. Casque selon la revendication 5, dans lequel une surface extérieure d'une partie supérieure de la première section est en contact avec une surface intérieure d'une partie supérieure de la seconde section. 45
8. Casque selon la revendication 5, dans lequel une des première et seconde sections comporte une plu- 50
ralité de fentes définies dans celle-ci et l'autre des première et seconde sections comporte un orifice correspondant défini dans celle-ci pour chacune par-
mi la pluralité de fentes, la seconde section étant reliée à la première section par l'insertion d'un élé-
ment de liaison à travers chacune des fentes et l'ori-
fice correspondant, les éléments de liaison pouvant coulisser à l'intérieur d'une fente respective parmi les fentes pour permettre le mouvement coulissant relatif. 55
9. Casque selon la revendication 5, dans lequel la première section est une section avant de la coquille de casque et la seconde section est une section arrière de la coquille de casque.
10. Mécanisme d'ajustement selon la revendication 5, dans lequel la première section comporte un évide- 10
ment défini dans celle-ci autour de l'ouverture, le le-
vier étant reçu dans l'évidement dans la position ver-
rouillée.
11. Mécanisme d'ajustement selon la revendication 5, dans lequel l'ouverture est formée par un orifice al- 15
longé et une série de fentes parallèles espacées ré-
gulièrement les unes des autres s'étendant à partir de celle-ci, l'orifice allongé recevant les bras dans celui-ci de façon coulissante et comportant une lar-
geur inférieure à une largeur totale des dents, et les fentes étant positionnées et dimensionnées pour re-
cevoir une partie des dents s'étendant au-delà de l'orifice allongé lorsque le levier est dans la position verrouillée.
12. Mécanisme d'ajustement selon la revendication 5, dans lequel les première et seconde surfaces cou- 20
lissantes sont en prise coulissante sans serrage im-
portant entre celles-ci.

FIG. 1













FIG. 4



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2006005184 A [0006]