



US011406763B2

(12) **United States Patent**
Hourmand et al.

(10) **Patent No.:** **US 11,406,763 B2**

(45) **Date of Patent:** **Aug. 9, 2022**

(54) **SYRINGE CARRIER**

(71) Applicant: **Sanofi-Aventis Deutschland GMBH**,
Frankfurt am Main (DE)

(72) Inventors: **Yannick Hourmand**, Cambridge (GB);
Douglas Ivan Jennings, Hertfordshire
(GB); **Matthew Ekman**, Cheshire (GB)

(73) Assignee: **Sanofi-Aventis Deutschland GMBH**,
Frankfurt am Main (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 263 days.

(21) Appl. No.: **16/353,282**

(22) Filed: **Mar. 14, 2019**

(65) **Prior Publication Data**

US 2019/0201629 A1 Jul. 4, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/976,824, filed on
May 10, 2018, now Pat. No. 10,646,656, which is a
continuation of application No. 14/362,537, filed as
application No. PCT/EP2012/074466 on Dec. 5,
2012, now Pat. No. 10,434,258.

(30) **Foreign Application Priority Data**

Dec. 8, 2011 (EP) 11192585

(51) **Int. Cl.**

A61M 5/31 (2006.01)
A61M 5/24 (2006.01)
A61M 5/32 (2006.01)

(52) **U.S. Cl.**

CPC **A61M 5/31** (2013.01); **A61M 5/24**
(2013.01); **A61M 5/32I** (2013.01); **A61M**
5/3202 (2013.01); **A61M 2005/2407** (2013.01);
A61M 2005/2414 (2013.01); **A61M 2005/2437**
(2013.01)

(58) **Field of Classification Search**

CPC **A61M 5/31**; **A61M 5/24**; **A61M 5/32I**;
A61M 5/3202; **A61M 2005/2407**; **A61M**
2005/2437; **A61M 2005/2414**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,026,873 A 3/1962 Miskel et al.
3,076,455 A 2/1963 McConnaughey et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2212489 2/1998
CN 101022841 5/2005
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion in International
Application No. PCT/EP2016/062503, dated Aug. 17, 2016, 9
pages.

(Continued)


Primary Examiner — Amber R Stiles

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

Described is a syringe carrier comprising a body adapted to
receive a barrel of a syringe. The body includes two sections
having distal ends with shoulder sections. The shoulder
sections are adapted to engage a circumferential gap
between the barrel of the syringe and a needle shield
covering a needle of the syringe.

20 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,144,178 A 8/1964 Sarnoff
 3,880,163 A 4/1975 Ritterskamp
 4,563,175 A 1/1986 Lafond
 4,643,724 A 2/1987 Jobe
 4,655,751 A 4/1987 Harbaugh
 4,735,311 A 4/1988 Lowe et al.
 4,838,857 A 6/1989 Strowe et al.
 4,871,355 A 10/1989 Kikkawa
 4,909,791 A 3/1990 Norelli
 4,931,040 A 6/1990 Haber et al.
 4,946,447 A 8/1990 Hardcastle et al.
 4,964,866 A 10/1990 Szwarc
 4,973,318 A 11/1990 Holm
 4,990,142 A 2/1991 Hoffman et al.
 4,997,422 A 3/1991 Chow et al.
 5,000,744 A 3/1991 Hoffman et al.
 5,078,698 A 1/1992 Stiehl et al.
 5,085,641 A 2/1992 Sarnoff et al.
 5,163,918 A 11/1992 Righi et al.
 5,169,392 A 12/1992 Ranford et al.
 5,282,793 A 2/1994 Larson
 5,320,609 A 6/1994 Haber et al.
 5,322,511 A 6/1994 Armbruster
 5,344,407 A 9/1994 Ryan
 5,350,367 A 9/1994 Stiehl et al.
 5,356,395 A 10/1994 Chen
 5,368,578 A 11/1994 Covington
 5,383,858 A 1/1995 Reilly et al.
 5,383,863 A 1/1995 Mardones
 5,439,450 A 8/1995 Haedt
 5,451,214 A 9/1995 Hajishoreh
 5,480,387 A 1/1996 Gabriel et al.
 5,520,653 A 5/1996 Reilly et al.
 5,599,309 A 2/1997 Marshall et al.
 5,637,101 A 6/1997 Shillington
 5,709,662 A 1/1998 Olive et al.
 5,779,675 A 7/1998 Uber et al.
 5,865,805 A 2/1999 Ziembra
 5,913,844 A 6/1999 Fago et al.
 5,925,032 A 7/1999 Clements
 5,928,205 A 7/1999 Marshall
 5,928,698 A 7/1999 Marshall
 6,059,756 A 5/2000 Yeh
 6,090,082 A 7/2000 King et al.
 6,203,530 B1 3/2001 Stewart
 6,210,369 B1 4/2001 Wilmot et al.
 6,371,939 B2 4/2002 Bergens et al.
 6,454,743 B1 9/2002 Weber
 6,544,234 B1 4/2003 Gabriel
 6,613,022 B1 9/2003 Doyle
 6,656,163 B1 12/2003 Marshall et al.
 6,726,657 B1 4/2004 Dedig
 6,743,205 B2 6/2004 Nolan, Jr. et al.
 7,118,552 B2 10/2006 Shaw et al.
 7,288,078 B2 10/2007 Fitzgerald
 7,717,877 B2 5/2010 Lavi et al.
 8,647,299 B2 2/2014 Stamp
 8,845,594 B2 9/2014 Jennings
 8,876,785 B2 11/2014 Holmqvist
 8,900,197 B2 12/2014 Crow
 8,992,746 B2 3/2015 Miyaji et al.
 9,072,833 B2 7/2015 Jennings et al.
 9,216,256 B2 12/2015 Olson et al.
 9,233,213 B2 1/2016 Olson et al.
 9,242,053 B2 1/2016 Wozencroft
 9,289,554 B2 3/2016 Hourmand et al.
 9,408,970 B2 8/2016 Hourmand et al.
 9,713,678 B2 7/2017 Hourmand et al.
 9,757,520 B2 9/2017 Corrigan
 9,867,940 B2 1/2018 Holmqvist et al.
 10,918,803 B2 2/2021 Kemp et al.
 11,103,649 B2 8/2021 Kemp et al.
 2001/0011163 A1 8/2001 Nonlan
 2002/0083564 A1 7/2002 James
 2003/0105430 A1 6/2003 Lavi et al.

2004/0039336 A1 2/2004 Amark et al.
 2004/0108339 A1 6/2004 Hansen
 2005/0020979 A1 1/2005 Westbye et al.
 2005/0027255 A1 2/2005 Lavi et al.
 2005/0075608 A1 4/2005 Holdgate
 2005/0101919 A1 5/2005 Brunnberg
 2005/0115507 A1 6/2005 Halachmi et al.
 2005/0165353 A1 7/2005 Pessin
 2005/0277896 A1 12/2005 Messerli et al.
 2006/0036216 A1 2/2006 Rimlinger et al.
 2006/0161114 A1 7/2006 Perot et al.
 2006/0167412 A1 7/2006 Marshall
 2006/0184133 A1 8/2006 Pessin
 2007/0173770 A1 7/2007 Stamp
 2007/0260348 A1 11/2007 Gordils
 2008/0147003 A1 6/2008 Menzi et al.
 2008/0228143 A1 9/2008 Stamp
 2008/0262427 A1 10/2008 Hommann
 2009/0012471 A1 1/2009 Harrison
 2009/0105663 A1 4/2009 Brand et al.
 2009/0254027 A1 10/2009 Moeller
 2010/0152655 A1 6/2010 Stamp
 2010/0179507 A1 7/2010 Hess
 2010/0185178 A1 7/2010 Sharp et al.
 2012/0053528 A1* 3/2012 Bollenbach A61M 5/24
 604/192
 2012/0130321 A1 5/2012 Woehr
 2012/0186075 A1 7/2012 Edginton
 2013/0220869 A1 8/2013 Klintenstedt et al.
 2014/0243753 A1 8/2014 Bostrom
 2014/0249479 A1 9/2014 Pfrang
 2014/0323985 A1 10/2014 Hourmand et al.
 2014/0330213 A1 11/2014 Hourmand et al.
 2014/0336590 A1 11/2014 Hourmand et al.
 2018/0140781 A1 5/2018 Kemp et al.
 2018/0140782 A1 5/2018 Kemp et al.
 2021/0077743 A1 3/2021 Kemp et al.
 2022/0016358 A1 1/2022 Kemp et al.

FOREIGN PATENT DOCUMENTS

CN 1911467 8/2006
 CN 2925504 7/2007
 CN 101400393 4/2009
 CN 101420995 4/2009
 CN 201213944 4/2009
 CN 103945879 7/2014
 DE 202009009119 12/2009
 EA 012008 6/2009
 EA 013934 8/2010
 EP 0518416 12/1992
 EP 0692272 1/1996
 EP 1702643 9/2006
 EP 2279771 2/2011
 EP 2438952 4/2012
 EP 2727617 6/2012
 EP 2777684 9/2014
 EP 2788052 9/2015
 EP 3153197 4/2017
 FR 2764195 12/1998
 GB 407109 3/1934
 GB 829724 3/1960
 GB 1122592 8/1968
 GB 2388033 11/2003
 GB 2396298 6/2004
 GB 2397767 8/2004
 GB 2447339 9/2008
 GB 2434317 1/2011
 GB 2471473 1/2011
 JP H08-10324 1/1996
 JP 2002-503127 1/2002
 JP 2005-021247 1/2005
 JP 2005/536300 12/2005
 JP 2006/507903 3/2006
 JP 2006-516901 7/2006
 JP 2008-500854 1/2008
 JP 2009/77943 4/2009
 JP 2009-523587 6/2009
 JP 2009-529395 8/2009

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2014-500086	1/2014
JP	2014-500089	1/2014
RU	2068708	11/1996
RU	2172638	8/2001
RU	2311203	11/2007
RU	2363500	8/2009
RU	2012137269	3/2014
WO	WO 1998/035714	8/1998
WO	WO 98/56442	12/1998
WO	WO 99/10030	3/1999
WO	WO 99/22792	5/1999
WO	WO 1999/022792	5/1999
WO	WO 00/24441	5/2000
WO	WO 2001/08727	2/2001
WO	WO 01/60435	8/2001
WO	WO 2001/93926	12/2001
WO	WO 02/47746	6/2002
WO	WO 2003/013632	2/2003
WO	WO 2003/068297	8/2003
WO	WO 2003/099358	12/2003
WO	WO 2004/007006	1/2004
WO	WO 2004/020026	3/2004
WO	WO 2004/050150	6/2004
WO	WO 2005/001161	1/2005
WO	WO 2013/083614	6/2005
WO	WO 2005/070481	8/2005
WO	WO 2005/083614	9/2005
WO	WO 2005/115506	12/2005
WO	WO 2005/115507	12/2005
WO	WO 2006/047810	5/2006
WO	WO 2006/085176	8/2006
WO	WO 2006/106291	10/2006
WO	WO 2006/106295	10/2006
WO	WO 2007/056792	5/2007
WO	WO 2007/083115	7/2007
WO	WO 2007/104636	9/2007
WO	WO 2007/129106	11/2007
WO	WO 2009/019437	2/2009
WO	WO 2009/022132	2/2009
WO	WO 2010/072644	7/2010
WO	WO 2010/097116	9/2010
WO	WO 2010/115822	10/2010
WO	WO 2010/136078	12/2010
WO	WO 2010/147553	12/2010
WO	WO 2011/000570	1/2011
WO	WO 2011/001161	1/2011
WO	WO 2011/101378	8/2011
WO	WO 2012/073032	6/2012
WO	WO 2012/089445	7/2012
WO	WO 2012/164403	12/2012
WO	WO 2013/072182	5/2013

OTHER PUBLICATIONS

International Preliminary Report on Patentability in International Application No. PCT/EP2016/062503, dated Dec. 5, 2017, 6 pages.

International Search Report and Written Opinion in International Application No. PCT/EP2016/062462, dated Sep. 27, 2016, 10 pages.

Chinese Search Report in Application No. 201280069195.4, dated Dec. 5, 2012, 2 pages.

Chinese Search Report in Chinese Application No. 201280069203.5, dated Oct. 9, 2015, 2 pages.

European Search Report in European Application No. 11192585.5, dated Apr. 20, 2012, 5 pages.

Extended European Search Report in Application No. 16195290.8, dated Mar. 15, 2017, 6 pages.

Extended European Search Report in Application No. 16195292.4, dated Mar. 15, 2017, 6 pages.

International Preliminary Report on Patentability in International Application No. PCT/EP2012/074468, dated Jun. 10, 2014, 5 pages.

International Search Report and Written Opinion in International Application No. PCT/EP2012/074466, dated Feb. 7, 2013, 9 pages.

International Search Report for Int. App. No. PCT/EP2012/074468, completed Mar. 13, 2013.

International Search Report in Application No. PCT/EP2011/052300, dated Jun. 16, 2011, 4 pages.

International Search Report in Application No. PCT/GB2005/002108, dated Sep. 6, 2005, 2 pages.

International Search Report in Application No. PCT/US00/20623, dated Nov. 21, 2000, 3 pages.

Merriam Webster Dictionary definition for “hinge”. Available online Dec. 18, 2016 at <https://www.merriamwebster.com/dictionary/hinge>.

Rote Liste, “50. Hypophysen-, Hypothalamushormone, andere regulatorische Peptide u. ihre Hemmstoffe,” Chapter 50, ed. 2008, 20 pages.

International Search Report for Int. App. No. PCT/EP2012/074469, completed Feb. 26, 2013.

International Preliminary Report on Patentability in International Application No. PCT/EP2012/074469, dated Jun. 10, 2014, 5 pages.

PCT International Preliminary Report on Patentability in International Appln No. PCT/EP2016/062462, dated Dec. 5, 2017, 7 pages.

PCT International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/074466, dated Jun. 10, 2014, 5 pages.

PCT International Preliminary Report on Patentability in International Appln. No. PCT/EP2012/074471, dated Jun. 10, 2014, 6 pages.

PCT International Search Report and Written Opinion in International Appln. No. PCT/EP2012/074471, dated Mar. 22, 2013, 8 pages.

EP Observations by a Third Party in Patent Appln. No. 16195290.8, dated Aug. 24, 2021, 5 pages.

Anders Holmqvist, and Hsueh-Yi Chen, Junior Party (U.S. Appl. No. 17/020,027) v. Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman, Senior Party (U.S. Appl. No. 17/020,027), Declaration of Interference, Patent Interference No. 106,135, filed Aug. 26, 2021, 8 pages.

dictionary.com [online], “Circlip,” 2016, retrieved on Feb. 24, 2022, retrieved from URL <<https://www.dictionary.com/browse/circlip>>, 4 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. Sanofi-Aventis Deutschland GMBH (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Medical Annotated Copy of Claims, filed Sep. 23, 2021, 9 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. Sanofi-Aventis Deutschland GMBH (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Medical Motion 2 (To Deny Benefit Accorded to Sanofi for Count 1), filed Dec. 15, 2021, 30 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. Sanofi-Aventis Deutschland GMBH (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Medical Motion 1 (For Judgment of No Written Description for Sanofi’s Involved Claims), filed Dec. 15, 2021, 30 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. Sanofi-Aventis Deutschland GMBH (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Opposition 1, filed Apr. 7, 2022, 34 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. Sanofi-Aventis Deutschland GMBH (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Sanofi Opposition 1 (Opposing SHL Motion 1 for Judgment for No Written Description), filed Apr. 7, 2022, 36 pages.

(56)

References Cited

OTHER PUBLICATIONS

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland and GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Sanofi-Aventis Motion 1 For Judgment under for Lack of Written Description under Section 112, filed Dec. 15, 2021, 28 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Sanofi-Aventis Annotated Copy of Claims, filed Sep. 23, 2021, 7 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Sanofi Opposition 2 (Opposing SHL Motion 2 to Deny Benefit Accorded to Sanofi for Count 1), filed Apr. 7, 2022, 38 pages.

Brief Communication in European Opposition in Application No. 1279544.9, dated Feb. 18, 2022, 34 pages.

Brief Communication in European Opposition in Application No. 12795446.9, dated Jan. 18, 2022, 57 pages.

Notice of Opposition in European Application No. 12795446.9, dated Aug. 19, 2021, 36 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 2010—Merriam-Webster Definition of C-shaped, dated Jan. 10, 2021, 2 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland and GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 2023—Transcript of Videotaped Deposition of Nigel David Harrison, dated Feb. 18, 2022, 234 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 2022—Declaration of Neil Sheehan, filed Apr. 6, 2022, 27 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 1001—Declaration of Nigel David Harrison, dated Dec. 11, 2021, 19 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 1013—Declaration of Gordon D. Row, MS, filed Apr. 7, 2022, 30 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan

Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 1014—Transcript of Remote Deposition of Neil Sheehan taken Mar. 3, 2022, 105 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398) v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourman, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 1015—Claim Chart demonstrating support for Sanofi's independent claim 2, filed Apr. 7, 2022, 11 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Rough Transcript of Deposition of Gordon Row, dated May 6, 2022, 55 pages.

Brief Communication in European Opposition in Application No. 12795446.9, dated May 16, 2022, 15 pages.

Office Action in U.S. Appl. No. 16/871,897, dated May 18, 2022, 26 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland and GMBH* (Inventors: Yannick Hourman, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Transcript of Deposition of Gordon Row, dated May 6, 2022, 61 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourman, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Reply 1, dated May 24, 2022, 34 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Reply 2, dated May 24, 2022, 35 pages.



SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourman, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, SHL Notice of Service of Supplemental Evidence, dated Jun. 7, 2022, 3 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135 SHL Updated Exhibit List, dated Jun. 7, 2022, 4 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 2025: Declaration of Neil Sheehan, dated Jun. 6, 2022, 9 pages.

SHL Medical AG (Inventors: Anders Holmqvist, and Hsueh-Yi Chen) Junior Party (U.S. Appl. No. 15/809,398), v. *Sanofi-Aventis Deutschland GMBH* (Inventors: Yannick Hourmand, Douglas Ivan Jennings, and Matthew Ekman), Senior Party (U.S. Appl. No. 17/020,027), Patent Interference No. 106,135, Exhibit 2001: Declaration of Neil Sheehan, dated Dec. 15, 2021, 44 pages.

* cited by examiner






FIG 5

FIG 6

FIG 7

















FIG 8




















D
FIG 44




D
FIG 45



D
FIG 46



D
FIG 47



P
FIG 48

SYRINGE CARRIER**CROSS REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. patent application Ser. No. 15/976,824, filed May 10, 2018, which is a continuation of U.S. patent application Ser. No. 14/362,537, filed Jun. 3, 2014, which is a U.S. National Phase Application pursuant to 35 U.S.C. § 371 of International Application No. PCT/EP2012/074466 filed Dec. 5, 2012, which claims priority to European Patent Application No. 11192585.5 filed Dec. 8, 2011. The entire disclosure contents of these applications are herewith incorporated by reference into the present application.

TECHNICAL FIELD

The invention relates to syringe carrier.

BACKGROUND

In a conventional medicament delivery device (e.g., an autoinjector), a pre-filled syringe is housed in a carrier which is axially movable to achieve needle penetration in an injection site and, optionally, needle withdrawal. A conventional carrier provides shoulders that are adapted to engage a neck on the syringe and prevent the syringe from disengaging the carrier. Because syringes are generally supplied with rigid needle shields covering the needle and those needle shields have a diameter greater than a diameter between the shoulders, a separate assembly step is required—inserting the syringe in the carrier and then attaching the rigid needle shield to the needle. Accordingly, there is a need for a syringe carrier which does not require this separate assembly step.

SUMMARY

It is an object of the present invention to provide an improved syringe carrier.

In an exemplary embodiment, a syringe carrier according to the present invention comprises a body adapted to receive a barrel of a syringe. The body includes two sections having distal ends with shoulder sections adapted to engage a circumferential gap between the barrel of the syringe and a needle shield covering a needle of the syringe.

In an exemplary embodiment, the sections are resiliently coupled to a collar on a proximal end of the body. The shoulder sections deflect when engaged by the needle shield and return to a non-deflected position when disengaged by the needle shield to engage the circumferential gap between the barrel of the syringe and the needle shield.

In an exemplary embodiment, the sections are resiliently coupled to a collar on a distal end of the body. The sections deflect when engaged by the needle shield and return to a non-deflected position when disengaged by the needle shield to engage a finger flange of the syringe. The body includes resilient arms having additional shoulder sections adapted to engage the circumferential gap between the barrel of the syringe and a needle shield covering a needle of the syringe. The arms deflect when engaged by the needle shield and return to a non-deflected position when disengaged by the needle shield to engage the circumferential gap between the barrel of the syringe and a needle shield.

In an exemplary embodiment, the sections are coupled via at least one hinge and are movable between an open position

and a closed position. A first section includes a pin adapted to engage a hole on a second section to secure the sections in the closed position.

In an exemplary embodiment, the sections are coupled via at least one clip and are movable between an open position and a closed position. The at least one clip includes a hook on a first section adapted to engage an eye on a second section to secure the sections in the closed position.

In an exemplary embodiment, the sections include doors hingedly coupled to the body and additional shoulder sections are formed on distal ends of the doors.

In an exemplary embodiment, the shoulder sections include proximally-facing contoured surfaces to accommodate a proximal portion of a neck of the syringe and distally-facing planar surfaces to abut the needle shield.

In an exemplary embodiment, the body includes one or more viewing windows.

In an exemplary embodiment, the body includes a retainer element adapted to provide an abutment surface to prevent the syringe from disengaging the syringe carrier in a proximal direction.

Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus, are not limitative of the present invention, and wherein:

FIG. 1 is a top view of an exemplary embodiment of a syringe carrier according to the present invention,

FIG. 2 is a lateral view of the syringe carrier of FIG. 1,

FIG. 3 is a longitudinal section of the syringe carrier of FIG. 1 in the section plane A-A,

FIG. 4 is a perspective view of the syringe carrier of FIG. 1,

FIG. 5 is a top view of another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 6 is a lateral view of the syringe carrier of FIG. 5,

FIG. 7 is a longitudinal section of the syringe carrier of FIG. 5 in the section plane A-A,

FIG. 8 is a perspective view of the syringe carrier of FIG. 5,

FIG. 9 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 10 is a lateral view of the syringe carrier of FIG. 9,

FIG. 11 is a longitudinal section of the syringe carrier of FIG. 9 in the section plane A-A,

FIG. 12 is a perspective view of the syringe carrier of FIG. 9,

FIG. 13 is another perspective view of the syringe carrier of FIG. 9 with a syringe inserted,

FIG. 14 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 15 is a lateral view of the syringe carrier of FIG. 14,

FIG. 16 is a longitudinal section of the syringe carrier of FIG. 14 in the section plane A-A,

3

FIG. 17 is a perspective view of the syringe carrier of FIG. 14,

FIG. 18 is another perspective view of the syringe carrier of FIG. 14 with a syringe inserted,

FIG. 19 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 20 is a lateral view of the syringe carrier of FIG. 19,

FIG. 21 is a longitudinal section of the syringe carrier of FIG. 19 in the section plane A-A,

FIG. 22 is a perspective view of the syringe carrier of FIG. 19,

FIG. 23 is another perspective view of the syringe carrier of FIG. 19 with a syringe inserted,

FIG. 24 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 25 is a lateral view of the syringe carrier of FIG. 24,

FIG. 26 is a longitudinal section of the syringe carrier of FIG. 24 in the section plane A-A,

FIG. 27 is a perspective view of the syringe carrier of FIG. 24,

FIG. 28 is another perspective view of the syringe carrier of FIG. 24 with a syringe inserted,

FIG. 29 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 30 is a lateral view of the syringe carrier of FIG. 29,

FIG. 31 is a longitudinal section of the syringe carrier of FIG. 29 in the section plane A-A,

FIG. 32 is a perspective view of the syringe carrier of FIG. 29,

FIG. 33 is another perspective view of the syringe carrier of FIG. 29 with a syringe inserted,

FIG. 34 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 35 is a lateral view of the syringe carrier of FIG. 34,

FIG. 36 is a longitudinal section of the syringe carrier of FIG. 34 in the section plane A-A,

FIG. 37 is a perspective view of the syringe carrier of FIG. 34,

FIG. 38 is another perspective view of the syringe carrier of FIG. 34 with a syringe inserted,

FIG. 39 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 40 is a lateral view of the syringe carrier of FIG. 39,

FIG. 41 is a longitudinal section of the syringe carrier of FIG. 39 in the section plane B-B,

FIG. 42 is a perspective view of the syringe carrier of FIG. 39,

FIG. 43 is another perspective view of the syringe carrier of FIG. 39 with a syringe inserted,

FIG. 44 is a top view of yet another exemplary embodiment of a syringe carrier according to the present invention,

FIG. 45 is a lateral view of the syringe carrier of FIG. 44,

FIG. 46 is a longitudinal section of the syringe carrier of FIG. 44 in the section plane B-B,

FIG. 47 is a perspective view of the syringe carrier of FIG. 44, and

FIG. 48 is another perspective view of the syringe carrier of FIG. 44 with a syringe inserted.

Corresponding parts are marked with the same reference symbols in all figures.

DETAILED DESCRIPTION

Generally, and applicable to all exemplary embodiments of the present invention, the syringe 2 comprises a barrel 2.1 and a neck 2.2 which has a smaller diameter than the barrel 2.1. A needle 3 is mounted to the neck 2.2 and a rigid needle

4

shield (RNS) 4 is removably arranged on the needle 3. When coupled to the needle 3, a portion of the RNS may cover a portion of the neck 2.2, leaving a circumferential gap between the barrel 2.1 and the RNS 4. The RNS 4 has a diameter substantially equal to the diameter of the barrel 2.1.

FIGS. 1-4 show a first exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 1 is a top view of the syringe carrier 1 for supporting a syringe 2. FIG. 2 is a lateral view of the syringe carrier of FIG. 1. FIG. 3 is a longitudinal section of the syringe carrier of FIG. 1 in the section plane A-A. FIG. 4 is a perspective view of the syringe carrier of FIG. 1 without the syringe 2.

As shown in FIGS. 1-4, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. The body 1.1 comprises a collar 1.2 at a proximal end dimensioned to allow axial insertion of the syringe 2 into the syringe carrier 1 in a distal direction D. Resilient sections 1.1.1 extend distally from the collar 1.2. Distal ends of the sections 1.1.1 include shoulder sections 1.4 shaped as portions of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections include facing surfaces 6. When the sections 1.1.1 are in a non-deflected position, the facing surfaces 6 may abut each other, and the shoulder sections 1.4 form a circular shoulder (because the facing surfaces 6 abut each other) adapted to engage the circumferential gap between the barrel 2.1 and the RNS 4.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by sliding the syringe 2 in the distal direction D into the syringe carrier 1. When the RNS 4 abuts the shoulder sections 1.4, additional axial force may be applied to cause the arms 1.3 to deflect radially. When the RNS 4 has bypassed the shoulder sections 1.4, the sections 1.1.1 may return to the non-deflected position, and the shoulder sections 1.4 may engage the circumferential gap between the barrel 2.1 and the RNS 4 and prevent the syringe 2 from moving in the distal direction D relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end 1.5 of the body 1.1 may be arranged to receive a finger flange 2.3 of the syringe 2.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, viewing windows 5 may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 1. In an exemplary embodiment, the windows 5 are formed when cut-outs in the arms 1.3 are substantially contiguous when the arms 1.3 are in the non-deflected position (as shown in FIG. 1). A projection 1.6 may be formed around each cut-out, and when the sections 1.1.1 are in the non-deflected position, the projections 1.6 may form an outline for the window 5. In another exemplary embodiment, the windows 5 may be formed in the sections 1.1.1.

FIGS. 5-8 show a second exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 6 is a lateral view of the syringe carrier 1 of FIG. 5. FIG. 7 is a longitudinal section of the syringe carrier 1 of FIG. 5 in the section plane A-A. FIG. 8 is a perspective view of the syringe carrier of FIG. 5 without the syringe 2.

As shown in FIGS. 5-8, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this

5

exemplary embodiment, the body 1.1 is comprised of two resilient sections 1.1.1 which, when together, have a cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. Distal ends of the sections 1.1.1 of the body 1.1 comprise part of a collar 1.2 dimensioned to allow axial insertion of the syringe 2 into the syringe carrier 1. Resilient arms 1.3 are formed in the body 1.1. Distal ends of the arms 1.3 include shoulder sections 1.4 shaped as portions of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections include facing surfaces 6. When the arms 1.3 are in a non-deflected position, the facing surfaces 6 may abut the distal ends of the sections 1.1.1 of the body 1.1 to form a circular shoulder adapted to engage the circumferential gap between the barrel 2.1 and the RNS 4.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by sliding the syringe 2 in the distal direction D into the syringe carrier 2. When the RNS 4 abuts proximal ends of the sections 1.1.1, the sections 1.1.1 may deflect radially. When the RNS 4 has bypassed the proximal ends of the section 1.1.1, the sections 1.1.1 may return to the non-deflected position. When the RNS 4 abuts the shoulder sections 1.4, the arms 1.3 may deflect until the RNS 4 bypasses the shoulder sections 1.4. Then, the arms 1.3 may return to the non-deflected position, and the shoulder sections 1.4 and the collar 1.2 may engage the circumferential gap between the barrel 2.1 and the RNS 4 and prevent the syringe 2 from moving in the distal direction D relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end 1.5 of the body 1.1 may be arranged to receive a finger flange 2.3 of the syringe 2. The proximal end 1.5 may also include a retainer element 1.7 which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, viewing windows 5 may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2. In an exemplary embodiment, the windows 5 are formed when cut-outs in the sections 1.1.1 are substantially contiguous when the sections 1.1.1 are in the non-deflected position (as shown in FIG. 5). A projection 1.6 may be formed around each cut-out, and when the sections 1.1.1 are in the non-deflected position, the projections 1.6 may form an outline for the window 5.

FIGS. 9-13 show a third exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 9 is a top view of a third embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 10 is a lateral view of the syringe carrier 1 of FIG. 9. FIG. 11 is a longitudinal section of the syringe carrier 1 of FIG. 9 in the section plane A-A. FIG. 12 is a perspective view of the syringe carrier of FIG. 9 without the syringe 2. FIG. 13 is another perspective view of the syringe carrier of FIG. 9.

As shown in FIGS. 9-13, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 is comprised of two sections 1.1.1 which, when together, have a cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. The sections 1.1.1 may be coupled by a side hinge which allows the section 1.1.1 to rotate relative to each other sufficient to receive the syringe 2. Proximal and

6

distal ends of the sections 1.1.1 include shoulder sections 1.4 shaped as portions of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections include facing surfaces 6. When the sections 1.1.1 are in a closed position, the facing surfaces 6 may abut each other so that the shoulder sections 1.4 form circular shoulders adapted to proximally abut a finger flange 2.3 on the syringe 2 and to distally engage the circumferential gap between the barrel 2.1 and the RNS 4. The facing surfaces 6 of one section 1.1.1 may include holes 1.10 and the facing surfaces 6 of the other section 1.1.1 may include pins 1.11 adapted to engage (e.g., frictionally, snap-fit, etc.) the holes 1.10 to secure the sections 1.1.1 in the closed position.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by opening the sections 1.1.1 about the hinge and placing the syringe 2 in the syringe carrier 2. When the sections 1.1.1 are closed, the pins 1.11 engage the holes 1.10, and the proximal shoulder sections 1.4 form circular shoulders adapted to proximally abut a finger flange 2.3 on the syringe 2 and the distal shoulder section 1.4 to distally engage the circumferential gap between the barrel 2.1 and the RNS 4. Thus, the syringe 2 is prevented from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end 1.5 may include a retainer element 1.7 which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, viewing windows 5 may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2. In an exemplary embodiment, the windows 5 are formed when cut-outs in the sections 1.1.1 are substantially contiguous when the sections 1.1.1 are in the closed position. A projection 1.6 may be formed around each cut-out, and when the sections 1.1.1 are in the non-deflected position, the projections 1.6 may form an outline for the window 5.

FIGS. 14-18 show a fourth exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 14 is a top view of a fourth embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 15 is a lateral view of the syringe carrier 1 of FIG. 14. FIG. 16 is a longitudinal section of the syringe carrier 1 of FIG. 14 in the section plane A-A. FIG. 17 is a perspective view of the syringe carrier of FIG. 14 without the syringe 2. FIG. 18 is another perspective view of the syringe carrier of FIG. 14.

As shown in FIGS. 14-18, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. A distal end of the body 1.1 includes a shoulder sections 1.4 shaped as a portion of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1, and at least one door 1.12 hingedly coupled to the body 1.1 and including a shoulder section 1.4. A hinge 1.9 coupling the door 1.12 to the body 1.1 may be provided on an axis parallel to the longitudinal axis of the syringe carrier 1 or on an axis transverse to the longitudinal axis of the syringe carrier 1. The shoulder section 1.4 includes facing surfaces 6 which abut facing surfaces 6 of

the door 1.12 when the door 1.12 is in a closed position (as shown in FIG. 14). When the door 1.12 is in the closed position, the facing surfaces 6 may abut each other so that the shoulder sections 1.4 on the body 1.1 and the door 1.12 to form a circular shoulder adapted to engage the circumferential gap between the barrel 2.1 and the RNS 4. The facing surfaces 6 of the door 1.12 may include holes 1.10 and the facing surfaces 6 of the body 1.1 may include pins 1.11 (or vice-versa) adapted to engage (e.g., frictionally, snap-fit, etc.) the holes 1.10 to secure the door 1.12 in the closed position.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by opening the door 1.12 and sliding the syringe 2 into the syringe carrier 1. When the circumferential gap between the barrel 2.1 and the RNS 4 engages the shoulder section 1.4 on the body 1.1, the door 1.12 may be closed to engage the gap and prevent the syringe 2 from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, viewing windows (not shown) may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2. In an exemplary embodiment, the windows are formed as cut-outs.

FIGS. 19-23 show a fifth exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 19 is a top view of a fifth embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 20 is a lateral view of the syringe carrier 1 of FIG. 19. FIG. 21 is a longitudinal section of the syringe carrier 1 of FIG. 19 in the section plane A-A. FIG. 22 is a perspective view of the syringe carrier of FIG. 19 without the syringe 2. FIG. 23 is another perspective view of the syringe carrier of FIG. 19.

As shown in FIGS. 19-23, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 is comprised of two sections 1.1.1 which, when together, have a cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. The sections 1.1.1 may be coupled together by clips. In an exemplary embodiment, a clip may comprise an eye 1.14 on a first section adapted to engage a hook 1.13 on a second section. The eye 1.14 may have a cross-section substantially equal to the cross-section of the hook 1.13 such that the eye 1.14 and hook 1.13 engage in a snap-fit. Distal ends of the sections 1.1.1 include shoulder sections 1.4 shaped as portions of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections include facing surfaces 6. When the sections 1.1.1 are in a closed position, the facing surfaces 6 may abut each other so that the shoulder sections 1.4 form circular shoulders adapted engage the circumferential gap between the barrel 2.1 and the RNS 4. Those of skill in the art will understand that the sections 1.1.1 may be hingedly connected.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by opening the sections 1.1.1 and placing the syringe 2 in the syringe carrier 2. When the sections 1.1.1 are closed, the eyes 1.14 engage the hooks 1.13 and the shoulder sections 1.4 engage the circumferential gap between the barrel 2.1 and the RNS 4. Thus, the syringe 2 is prevented from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, viewing windows may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

FIGS. 24-28 show a sixth exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 24 is a top view of a sixth embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 25 is a lateral view of the syringe carrier 1 of FIG. 24. FIG. 26 is a longitudinal section of the syringe carrier 1 of FIG. 24 in the section plane A-A. FIG. 27 is a perspective view of the syringe carrier of FIG. 24 without the syringe 2. FIG. 28 is another perspective view of the syringe carrier of FIG. 24.

As shown in FIGS. 24-28, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a partially cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. The body 1.1 may include a longitudinal slot (e.g., a cut-out) which is adapted to snap over the barrel 2.1 of the syringe 2. Proximal and distal ends of the body 1.1 include clamps 1.15, 1.16 which are adapted to retain the syringe 2 when in the syringe carrier 1. The distal end of the body 1 further includes shoulder sections 1.4 shaped as a portion of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections 1.4 form circular shoulders adapted to engage the circumferential gap between the barrel 2.1 and the RNS 4.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by pressing the barrel 2.1 against the clamps 1.15, 1.16, causing the clamps 1.15, 1.16 to deflect and widen the longitudinal slot in the body 1.1. When the barrel 2.1 bypasses the clamps 1.15, 1.16, the clamps 1.15, 1.16 return to their non-deflected position and retain the syringe 2 in the syringe carrier 1. The shoulder sections 1.4 engage the circumferential gap between the barrel 2.1 and the RNS 4. Thus, the syringe 2 is prevented from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, a viewing window may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

FIGS. 29-33 show a seventh exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 29 is a top view of a seventh embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 30 is a lateral view of the syringe carrier 1 of FIG. 29. FIG. 31 is a longitudinal section of the syringe carrier 1 of FIG. 29 in the section plane A-A. FIG. 32 is a perspective view of the syringe carrier of FIG.

29 without the syringe 2. FIG. 33 is another perspective view of the syringe carrier of FIG. 29.

As shown in FIGS. 29-33, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a partially cylindrical shape with an internal diameter corresponding to the diameter of the barrel 2.1. The body 1.1 includes a collar 1.2 at its proximal end and may include a longitudinal slot (e.g., a cut-out) formed in the body 1.1 distally of the collar 1.2 which is adapted to snap over the barrel 2.1 of the syringe 2. A pair of groove hinges 1.17 may be formed in the body 1.1 adjacent a proximal end of the slot. The distal end of the body 1 includes shoulder sections 1.4 shaped as a portion of a circle arranged in a transverse plane with respect to a longitudinal axis of the carrier 1. The shoulder sections 14 form circular shoulders adapted to engage the circumferential gap between the barrel 2.1 and the RNS 4.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by sliding the syringe 2 through the collar 1.2 in the distal direction D. When the RNS 4 abuts the shoulder sections 1.4, the body 1.1 may radially deflect (e.g., rotate) about the groove hinges 1.17. When the RNS 4 bypasses the shoulder sections 1.4, the body 1.1 may return to its non-deflected position and retain the syringe 2 in the syringe carrier 1. The shoulder sections 1.4 engage the circumferential gap between the barrel 2.1 and the RNS 4. Thus, the syringe 2 is prevented from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, a viewing window may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

FIGS. 34-38 show an eighth exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 34 is a top view of an eighth embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 35 is a lateral view of the syringe carrier 1 of FIG. 34. FIG. 36 is a longitudinal section of the syringe carrier 1 of FIG. 34 in the section plane A-A. FIG. 37 is a perspective view of the syringe carrier of FIG. 34 without the syringe 2. FIG. 38 is another perspective view of the syringe carrier of FIG. 34.

As shown in FIGS. 34-38, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a cylindrical shape with an annular groove 1.19 adjacent its distal end which is adapted to engage a circlip 8. The circlip 8 may engage the circumferential gap between the barrel 1.2 and the RNS 4.

The syringe 2, with RNS 4 attached to the needle 3 and the circlip 8 attached to the syringe 2, may be loaded into the syringe carrier 1 by sliding the syringe 2 into the syringe carrier 1 in the distal direction D. In a non-deflected position, an outer diameter of the circlip 8 may be substantially equal to a diameter of the body 1.1. Thus, when the syringe 2 with the circlip 8 is inserted into the syringe carrier 1, the circlip 8 may deflect radially until the circlip 8 reaches the annular groove 1.19. The circlip 8 may then expand to the non-deflected position and retain the syringe 2 in an axial

position relative to the syringe carrier 1. That is, the circlip 8 may engage the annular groove 1.19 and the circumferential gap between the barrel 2.1 and the RNS 4. Thus, the syringe 2 is prevented from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, a viewing window may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

FIGS. 39-43 show a ninth exemplary embodiment of a syringe carrier 1 according to the present invention. FIG. 39 is a top view of a ninth embodiment of a syringe carrier 1 for supporting a syringe 2. FIG. 40 is a lateral view of the syringe carrier 1 of FIG. 39. FIG. 41 is a longitudinal section of the syringe carrier 1 of FIG. 39 in the section plane A-A. FIG. 42 is a perspective view of the syringe carrier of FIG. 39 without the syringe 2. FIG. 43 is another perspective view of the syringe carrier of FIG. 39.

As shown in FIGS. 39-43, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has a cylindrical shape with an annular groove 1.19 having at least one aperture 1.20 adjacent its distal end which is adapted to engage a circlip 8.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by sliding the syringe 2 into the syringe carrier 1 in the distal direction D. When the circumferential gap between the barrel 2.1 and the RNS 4 is aligned with the annular groove 1.19, the circlip 8 may be coupled to the body 1.1 and engage the apertures 1.20. By extending inwardly through the apertures, the circlip 8 may be coupled to the outside of the body 1.1 but engage the circumferential gap between the barrel 2.1 and the RNS 4. The engagement between the circlip 8 and the apertures 1.20 prevents the circlip 8 from translating relative to the body 1.1, and the engagement between the circlip 8 and the circumferential gap prevents the syringe 2 from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the shoulder sections 1.4 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, a viewing window may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

FIGS. 44-48 show a tenth exemplary embodiment of a syringe carrier 1 and a tool 9 for inserting a syringe 2 into the syringe carrier 1 according to the present invention.

As shown in FIGS. 39-43, the syringe carrier 1 comprises an elongate body 1.1 arranged to receive the barrel 2.1. In this exemplary embodiment, the body 1.1 has an enlarged portion 1.21 on its distal end. The body 1.1 has cylindrical

11

shape with a first diameter and the enlarged portion 1.21 has a second diameter, larger than the first diameter. The enlarged portion 1.21 has one or more resilient barbs 1.22 extending toward a longitudinal axis of the body 1.1 and angled toward a proximal end of the body 1.1.

The syringe 2, with RNS 4 attached to the needle 3, may be loaded into the syringe carrier 1 by inserting the tool 9 into the enlarged portion 1.21 of the syringe carrier 1. The tool 9 may be a cylinder having an open end adapted to receive the RNS 4. The tool 9 may have a third diameter substantially equal to the second diameter. As the tool 9 is inserted into the enlarged portion 1.21, the tool 9 engages and deflects the resilient barbs 1.22. When the barbs 1.22 are deflected, the RNS 4 can pass the barbs 1.22 in the distal direction D and extend from a distal opening of the body 1.1. When a finger flange 2.3 of the syringe 2 abuts a proximal end of the body 1.1, the tool 9 may be removed and the barbs 1.22 may engage the circumferential gap between the barrel 2.1 and the RNS 4 to prevent the syringe 2 from moving axially relative to the syringe carrier 1.

In an exemplary embodiment, the proximal end may include a retainer element which is adapted to provide an abutment surface to prevent the syringe 2 from disengaging the syringe carrier 1 in the proximal direction P.

In an exemplary embodiment, the barbs 1.22 may include proximally-facing contoured surfaces to accommodate a proximal portion of the neck 2.2 of the syringe 2 and distally-facing planar surfaces to abut the RNS 4.

In an exemplary embodiment, a viewing window may be arranged in the body 1.1 for allowing visual access to the barrel 2.1 of the syringe 2 when the syringe 2 is in the syringe carrier 2.

It is apparent to those skilled in the art that the number of deflectable arms 1.3, shoulder sections 1.4, clips 8 may be varied without departing from the spirit and scope of the invention. Likewise, all the illustrated embodiments may be implemented with or without viewing windows 5, projections 1.6, restraining features retainer elements 1.7 and clips. Different kinds of clips may likewise be applied.

Those of skill in the art will understand that modifications (additions and/or removals) of various components of the apparatuses, methods and/or systems and embodiments described herein may be made without departing from the full scope and spirit of the present invention, which encompass such modifications and any and all equivalents thereof.

The invention claimed is:

1. A syringe carrier comprising:

an elongate body comprising one or more projections extending radially inward from a distal end of the elongate body, the distal end of the elongate body being configured to flex radially outward as a rigid needle shield of a syringe is slid distally along the one or more projections as the syringe is loaded into the syringe carrier, the distal end of the elongate body being configured to rebound radially inward when a proximal end of the rigid needle shield has moved distal to the one or more projections, and the one or more projections being configured to be disposed in a gap between a barrel of the syringe and the rigid needle shield when the proximal end of the rigid needle shield has moved distal to the one or more projections; and

first and second resilient members at a proximal end of the elongate body, the first and second resilient members being configured to apply a radially inward force to the syringe to restrict axial movement of the syringe after the syringe has been loaded into the syringe carrier.

12

2. The syringe carrier of claim 1, wherein the elongate body defines a longitudinal slot.

3. The syringe carrier of claim 1, wherein the first and second resilient members are positioned opposite one another.

4. The syringe carrier of claim 3, wherein an inner surface of the first resilient member faces an inner surface of the second resilient member.

5. The syringe carrier of claim 4, wherein the first and second resilient members are configured such that a portion of a barrel of the syringe is disposed between the inner surfaces of the first and second resilient members after the syringe has been loaded into the syringe carrier.

6. The syringe carrier of claim 3, wherein the first and second resilient members define a longitudinal slot.

7. The syringe carrier of claim 1, wherein the first and second resilient members form a clamp.

8. The syringe carrier of claim 1, wherein the one or more projections and the elongate body are integrally formed with one another.

9. The syringe carrier of claim 1, wherein each of the one or more projections has a proximally-facing contoured surface.

10. The syringe carrier of claim 9, wherein the proximally-facing contoured surface of the one or more projections is configured to accommodate a proximal portion of the neck of the syringe after the syringe has been loaded into the syringe carrier.

11. The syringe carrier of claim 9, wherein the one or more projections has a distally-facing planar surface.

12. The syringe carrier of claim 11, wherein the distally-facing planar surface of the one or more projections is configured to abut a proximal end of the rigid needle shield of the syringe after the syringe has been loaded into the syringe carrier.

13. The syringe carrier of claim 1, wherein the rigid needle shield has an outer diameter substantially equal to an outer diameter of the barrel of the syringe.

14. The syringe carrier of claim 1, wherein the rigid needle shield has an outer diameter greater than a distance between the one or more projections when the distal end of the elongate body is in an undeflected position.

15. The syringe carrier of claim 1, wherein the rigid needle shield has an outer diameter greater than a distance between the one or more projections when the distal end of the elongate body is rebounded radially inward.

16. The syringe carrier of claim 1, wherein the elongate body of the syringe carrier defines a window for allowing visual access to the barrel of the syringe after the syringe has been loaded into the syringe carrier.

17. A syringe carrier comprising:

an elongate body comprising one or more projections extending radially inward from a distal end of the elongate body, the distal end of the elongate body being configured to flex radially outward as a rigid needle shield of a syringe is slid distally along the one or more projections as the syringe is loaded into the syringe carrier, the distal end of the elongate body being configured to rebound radially inward when a proximal end of the rigid needle shield has moved distal to the one or more projections, and the one or more projections being configured to be disposed in a gap between a barrel of the syringe and the rigid needle shield when the proximal end of the rigid needle shield has moved distal to the one or more projections; and

means for restricting axial movement of the syringe after the syringe has been loaded into the syringe carrier, the means being located at a proximal end of the elongate body.

- 18. An assembly comprising: 5
a syringe;
a syringe carrier configured to receive the syringe, the syringe carrier comprising an elongate body comprising one or more projections extending radially inward from a distal end of the elongate body, the distal end of the elongate body being configured to flex radially outward as a rigid needle shield of the syringe is slid distally along the one or more projections as the syringe is loaded into the syringe carrier, the distal end of the elongate body being configured to rebound radially inward when a proximal end of the rigid needle shield has moved distal to the one or more projections, and the one or more projections being configured to be disposed in a gap between a barrel of the syringe and the rigid needle shield when the proximal end of the rigid needle shield has moved distal to the one or more projections; and 10
a clamp configured to apply a radially inward force to the syringe to restrict axial movement of the syringe after the syringe has been loaded into the syringe carrier. 15 20 25

19. The assembly of claim 18, wherein the clamp is part of the syringe carrier.

20. The assembly of claim 19, wherein the clamp comprises first and second resilient members positioned opposite one another. 30

* * * * *