

(19)
(12)

(KR)
(B1)

(51) 。 Int. Cl. ⁷
H04B 7/26

(45)
(11)
(24)

2002 11 07
10 - 0359809
2002 10 23

(21) 10 - 1999 - 0067876
(22) 1999 12 31

(65) 2001 - 0066277
(43) 2001 07 11

(73) 20 LG

(72) 436 - 5 101

(74)
:

(54)

가 가 .

3

, RTD

1 (CDMA)

2 1

3

4

1 (CDMA)

1 (100) , (101) , (101)
(102) , / , /
(103)

2 1

2 (Access channel) (S2
00, S201). (S202, S203),
(S204).
(S205), (S206).
(S207).

(Walsh code), (frame offset) (Vocoder)
(Traffic channel element)
(Nominal TX gain) , (Long code), ESN(Electric Serial Number)
(S208). (Parameter)

ulator) (TX Mod
(Null traffic) (S209). 0

(, 100) (Nominal TX gain)
0 127 가

가 , 가 , 가

(S210, S211). (Paging channel)

(Preamble) (S212).

(S213).

(S214).

ack

(S215, S216).

bs_ack/ms_

, ESN

가

가

RTD(Round Trip Delay)

RTD

3

3

1).

(Access channel)

RTD(Round Trip Delay) (S300, S30

(Paging channel)

(S302, S303),

(S304).

(S306).

(S305),

(S307).

(Traffic channel element)

(S301)

RTD

RTD

ESN(Electric Serial Number)

(Nominal TX gain)

(S308).

(Long code),

(TX Modulator)

(Null traffic) (S309).

(Paging channel)

(S310, S311).

(Preamble)

(S312).

(S313).

(S314).

ack

bs_ack/ms_

(S315, S316).

4 , RTD

RTD
N (N : 3 5) RTD

RTD 가 RTD

RTD

(S400). RTD

(S401).

(S400)

가

RTD (S402).

RTD

(S403).

가 (S404), (S401 S403)

가 RTD

가 RTD

RTD

1

[1]

RTD		RTD	
0 100	40	601 700	80
101 200	50	701 800	85
201 300	60	801 900	90
401 500	70
501 600	75	65535	100

가

가

가

가

가

(57)

1.

2.


1 , , , ,

가

3.

2 , , , ,

가



4

