# WORLD INTELLECTIVAL PROPERTY ORGANIZATION IT



# INTERNATIONAL APPLICATION PUBLISHE

(51) International Patent Classification 6:

(11) International Publication Number:

WO 96/03362

C07C 17/395, 17/38, 21/067

A1

(43) International Publication Date:

8 February 1996 (08.02.96)

(21) International Application Number:

PCT/EP95/02900

(22) International Filing Date:

20 July 1995 (20.07.95)

(81) Designated States: CA, CN, JP, KR, PL, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(30) Priority Data:

94202144.5

22 July 1994 (22.07.94)

EP

(34) Countries for which the regional or

international application was filed:

AT et al.

SHELL INTERNATIONALE RESEARCH (71) Applicant: MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(72) Inventors: DE JONG, Abe, Wiebe; Badhuisweg 3, NL-1031 CM Amsterdam (NL). NISBET, Timothy, Michael; Badhuisweg 3, NL-1031 CM Amsterdam (NL).

**Published** 

With international search report.

(54) Title: PURIFICATION OF ALLYL CHLORIDE

(57) Abstract

A process for the removal of (cyclo)aliphatic hexene and hexadiene isomers from allyl chloride, characterized by a chlorination step which is performed in the liquid phase.

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Viet Nam
GA	Gabon		•		

- 1 -

#### PURIFICATION OF ALLYL CHLORIDE

The present invention relates to the purification of allyl chloride by removal of certain undesired by-products.

5

10

15

20

25

Allyl chloride is commercially prepared by the high-temperature chlorination of propene. Its main use is in the production of dichlorohydrin, which term refers to the isomers 1,2-dichloro-3-hydroxypropane and 1,3-dichloro-2-hydroxypropane, generally by reacting an allyl chloride feed with water and chlorine in a dilute aqueous phase. The main use of dichlorohydrin is for preparing epichlorohydrin (1,2-epoxy-3-chloropropane), generally by dehydrochlorination in the presence of a base. These reactions may be carried out batchwise, semi-continuously or continuously. Other uses of allyl chloride are for the production of esters, allyl ethers and allyl amines (Ullman's Encyclopaedia of Industrial Chemistry, 5th Edition, vol. A 1985 page 431).

It is known, that the voluminous aqueous effluent emerging from the epichlorohydrin production plant can contain appreciable amounts of other chlorinated organic compounds (Extractable Organic Chlorine, EOCl, up to about 100 mg Cl/l). These chlorinated organic by-products are mainly chloroaliphatic ethers and chloroaliphatic alkanes. They are already present in the conventionally-prepared dichlorohydrin, and they are carried on to the effluent of the epichlorohydrin plant. Since these chlorinated organic by-products are toxic, their concentration in the waste water should be reduced as much as possible before the waste water is passed to receiving bodies such as rivers and lakes. Since the removal of the chlorinated organic by-products from the epichlorohydrin plant effluent by conventional methods, such as fractional distillation, is very expensive, there exists a need for an alternative method for reducing their level.

- 2 -

The present applicant's EP-A-O 359 331 is directed to a method of reducing the level of chlorinated organic by-products in the above-described reaction effluent by extracting the aqueous product of the reaction of allyl chloride with water and chlorine, with a water-immiscible solvent having an atmospheric boiling point of from 40 °C to 105 °C. The present applicant's EP-A-O 537 846 discloses a similar method wherein the extracting water-immiscible solvent is 1,2,3-trichloropropane.

5

10

15

20

25

30

35

In the present applicant's WO-94/1316 a different approach to reducing the level of chlorinated organic by-products in the above-described reaction effluent is presented. Therein it is disclosed, that the above undesirable chlorinated organic by-products are mainly chloroaliphatic ethers having 9 and 12 carbon atoms ( $C_9$  and  $C_{12}$ ), the level of the  $C_{15}$  chloroaliphatic ethers being much lower, and that their source in the allyl chloride feed is mainly hexadienes (i.e.  $C_6H_{10}$  isomers, in particular 1,5-hexadiene, 1,4-hexadiene and 2-methyl-1,4-pentadiene), which are by-products of the high temperature chlorination of propene to allyl chloride. When present in the allyl chloride feed to the above-described reaction with water and chlorine to form dichlorohydrin, these hexadienes also react with chlorine, water and dichlorohydrin to form the chloroaliphatic ethers found in the reaction effluent.

The commercial allyl chloride used for the production of dichlorohydrin is at least 97.5 wt% pure and contains hexadiene as an impurity (Ullman's Encyclopaedia of Industrial Chemistry, ibid.). In order to reach this degree of purity, the crude allyl chloride as produced by the chlorination of propene and which contains about 75-80% of allyl chloride plus lighter and heavier impurities, is conventionally purified. The purification is generally performed by distillation, in at least two steps, wherein light and heavy ends respectively are removed. Normally, 0.3-1.0 wt% of hexadiene is still present in the purified allyl chloride used for the production of dichlorohydrin. In WO-94/1316 it is disclosed that when an allyl chloride feed containing less than 0.30 wt% of hexadiene is used with water and chlorine for the production of dichlorohydrin, the

- 3 -

product contains much less of the undesirable chlorinated organic by-products, which substantially reduces the costs of purifying the aqueous effluent leaving the plant.

5

10

15

20

25

30

WO-94/1316 proceeds to disclose several methods for removing the hexadienes from the allyl chloride feed for the dichlorohydrin production, with a view to reducing the production of said undesired chlorinated organic by-products. One of these methods involves the hydrochlorination of the hexadienes present in the crude allyl chloride feed, with HCl in the presence of a Lewis acid such as MoCl<sub>5</sub>, to monochlorohexenes and dichlorohexanes. The boiling points, at atmospheric pressure, of the monochlorohexenes and dichlorohexanes being in the ranges of 110-140 °C and 170-220 °C respectively, they are much easier to separate from the allyl chloride (boiling point 45 °C) than are the hexadienes (boiling point 55-65 °C).

Although WO-94/1316 shows the hydrochlorination treatment to be very effective in selectively converting to monochlorohexenes and dichlorohexanes as much as 98% of the hexadienes present in the allyl chloride feed, in practice this method has the drawbacks that the catalyst used is expensive and that it has to be separated from the reaction product. Also, conversion of the hexadienes in the allyl chloride to products which are even heavier than are the monochlorohexenes and dichlorohexanes would be welcome. Of course, this conversion has to remain selective to the hexadiene, without unduly affecting the allyl chloride itself.

The crude allyl chloride also contains as by-products, in addition to the hexadienes, smaller amounts of other aliphatic and cycloaliphatic hexene and hexadiene isomers, such as normal hexenes, methylpentenes, methylcyclopentenes and methylcyclopentadienes and these are also carried on to the conventionally purified allyl chloride. The methylcyclopentene impurities, when present, were found to be converted in the epichlorohydrin production process to epoxymethylcyclopentanes which, if present in appreciable amounts, could affect the further processing of the epichlorohydrin.

- 4 -

It has now been found that the hexadienes, as well as the methylcyclopentenes and the other aliphatic and cycloaliphatic hexene and hexadiene isomers present in the crude allyl chloride and in the conventionally purified allyl chloride, can be effectively and efficiently removed by chlorination with molecular chlorine, in the liquid phase. In this chlorination step, the hexadienes are converted to dichlorohexenes and tetrachlorohexanes, which are heavier and thus even easier to separate from the allyl chloride mainstream than are the hydrochlorination products mentioned in WO-94/1316. The methylcyclopentenes in turn are converted in this chlorination step to dichloro methylcyclopentanes, which can also be easily separated from the allyl chloride mainstream. Surprisingly, it was found that the chlorination, when performed correctly, is very selective - in that the allyl chloride itself is not chlorinated to a substantial amount, although it is present in great excess to the unsaturated  $C_6$  impurities.

5

10

15

20

25

30

The present invention therefore is directed to a process for the removal of (cyclo)aliphatic hexene and hexadiene isomers from allyl chloride, characterized by a chlorination step which is performed in the liquid phase.

In the chlorination step molecular chlorine, which optionally can be mixed with an inert gas or with an inert liquid solvent such as 1,2,3 trichloropropane or carbon tetrachloride, is contacted in a reactor with the crude allyl chloride which is kept liquid in the combination of temperature and pressure employed. It is important that the allyl chloride be kept liquid, since only then the chlorination reaction is sufficiently selective. Gaseous allyl chloride reacts too readily with the chlorine to trichloropropane, which is not useful.

The temperature wherein the chlorination step according to the invention is performed can be varied within the ranges of from -20 to 120 °C, preferably from 20 to 80 °C, and the pressure is chosen such as to ensure that the allyl chloride is liquid at the temperature employed.

- 5 -

The total amount of chlorine used for the chlorination according to the invention is preferably between 1 and 5, more preferably between 1.5 and 3.5, mol per mol of combined (cyclo)aliphatic hexenes and hexadienes originally present in the crude allyl chloride. A substantially higher concentration of chlorine than is needed for the optimal chlorination of the hexenes and hexadienes will tend, after chlorinating all of the impurities, to proceed and chlorinate the allyl chloride itself.

Crude allyl chloride often also contains residual propene from which the allyl chloride was made. Since the propene will also react with chlorine (to dichloropropane) under the reaction conditions, and since the direct removal of propene by conventional separation means such as distillation does not present the same difficulties as the removal of hexadienes and methyl cyclopentenes, it is convenient to separate the propene from the crude allyl chloride before effecting the chlorination step according to the invention. Therefore, in a preferred embodiment of the present invention, the chlorination step is performed after the light ends removal from the crude allyl chloride.

The purification step according to the invention can be performed batchwise as well as continuously.

After the chlorination step according to the invention is performed, the allyl chloride purification can be completed by conventional means, such as distillation. Therefore, in a preferred embodiment, the present invention comprises the steps of:

- a. distillation of the crude allyl chloride to remove light ends;
- b. chlorination in the liquid phase of the (cyclo)aliphatic hexene and hexadiene isomers present in the crude allyl chloride; and
- c. distillation of the crude allyl chloride to remove heavy ends. The following Examples will illustrate the invention.

## EXAMPLE 1

5

10

15

20

25

30

35

16.7 g of feed A, laboratory grade allyl chloride containing 0.36 mol% of 1,5-hexadiene and a total of 0.46 mol% of (cyclo)aliphatic hexenes and hexadienes in >98 wt% of allyl chloride (Merck, Art. 800257) was placed in a 30 ml glass bottle at 21 °C and

- 6 -

atmospheric pressure. The liquid was agitated using a magnetic stirrer. Chlorine gas was dosed via a pipe under the liquid surface, at a rate of 5 mg/sec. The product was analysed by gas chromatography/mass spectrometry. The overall chlorination of hexadiene (to dichlorohexene and tetrachlorohexane) and allyl chloride (to 1,2,3-trichloropropane), after dosing 1 and 2 mole equivalents of chlorine on the total of (cyclo)aliphatic hexenes and hexadienes, are presented in Table 1.

## EXAMPLES 2 AND 3

5

10

15

20

25

30

35

Feed A was fed continuously at 400 g/h and 20  $^{\circ}$ C to the bottom of a vertically positioned glass pipe reactor (4 mm diameter, 1 m length).

Chlorine gas was bubbled through the allyl chloride by feeding it continuously, at a rate of 0.92 - 4.70 g/h, amounting to molar ratios of between 0.6 - 2.7 on the total of (cyclo)aliphatic hexenes and hexadienes, to the bottom of the reactor, through a fine nozzle positioned just below a glass sinter positioned 3 cm from the bottom and reaching across the entire cross-section of the reactor.

Reactor pressure below the sinter and at the reactor top was 160 - 180 kPa and atmospheric, respectively. Liquid samples were removed from the reactor top and analysed by gas chromatography for their content of chlorinated products of hexadienes (dichlorohexenes and tetrachlorohexanes, combined) and allyl chloride (trichloropropane). The overall chlorination results are also presented in Table 1.

# EXAMPLE 4

Similar to Examples 2 and 3, except that crude allyl chloride was used, containing 78 wt% of allyl chloride, 0.33 mol% of 1,5-hexadiene on allyl chloride and a total of 0.45 mol% of (cyclo)aliphatic hexenes and hexadienes, which feed was first distilled to remove propene (Feed B). The overall chlorination results are also presented in Table 1.

### EXAMPLE 5

Similar to Example 4, except that the allyl chloride content of the crude product used, also after removing propene, was 80 wt%, the hexadiene content 0.31 mol% and the total (cyclo)aliphatic hexenes

- 7 -

and hexadienes content 0.44 mol% (Feed C). The overall chlorination results are also presented in Table 1. Furthermore, the products balance of the hexadiene converted (to dichlorohexene and tetrachlorohexane) is detailed in Table 2.

## EXAMPLE 6

5

10

15

20

Feed C (as in Example 5) was fed continuously at 400 g/h to the bottom of a vertically positioned steel pipe reactor (4.4 mm diameter, 1 m length). Chlorine gas was fed continuously to the bottom of the reactor through a fine nozzle, at a molar ratio of 2.5 on the total of (cyclo)aliphatic hexenes and hexadienes. Reactor temperature was controlled with an oil jacket. Reactor pressure was controlled with a back-pressure regulator in the reactor exit. Liquid samples were removed and analysed by gas chromatography. The overall chlorination results at different temperatures are presented in Table 3.

From Examples 1-5 it appears, that the chlorination reaction is selective up to the point that almost all of the hexadiene is chlorinated.

Example 6 shows the effectivity of the chlorination at higher temperatures.

- 8 -  $\underline{\text{TABLE 1}}$  Overall chlorination in Examples 1-5

Example	Feed	Chlorine dosed,	mol% chlorinated		
No.		mol/mol hexenes a		of allyl	
		hexadienes		chloride	
1	А	1.0	66.0	0.09	
		2.0	97.0	0.27	
2	A	0.6	6.2	0.16	
		0.9	35.0	0.21	
		1.6	78.0	0.25	
		2.7	96.4	0.49	
3	А	1.0	47.3	0.16	
		1.4	75.1	0.20	
		1.6	84.0	0.24	
		1.7	94.7	0.26	
		1.9	94.9	0.31	
		2.7	98.9	0.61	
4	В	1.2	36.9	0.10	
		1.5	58.5	0.11	
		1.7	71.3	0.12	
		2.1	79.4	0.13	
		2.2	86.9	0.14	
		2.7	96.0	0.17	
		3.4	99.0	0.26	
5	С	1.4	50.1	0.09	
		1.5	50.2	0.13	
		1.7	70.3	0.11	
		2.2	87.5	0.13	
		2.7	96.3	0.17	
		3.3	99.9	0.28	

Chlorine dosed mol/mol hexenes	% of orig	inal hexadie	ene in product,	as
and hexadienes	hexadiene (unchanged)	dichloro- hexane	tetrachloro- hexane	total
1.4	49.9	46.4	2.9	99.2
1.5	49.8	44.1	3.3	97.2
1.7	29.7	62.0	6.6	98.3
2.2	12.5	70.4	13.6	96.5
2.7	3.7	69.4	24.1	97.2
3.3	0.1	47.7	46.0	93.8

TABLE 3
Overall chlorination in Example 6

Temperature	Outlet	mol% chlorinated		
(°C)	Pressure	of hexadiene	of allyl chloride	
	(kPa)			
40	100	96	0.20	
50	150	94	0.19	
60	200	92	0.20	
70	250	92	0.22	
80	300	89	0.24	

- 10 -

## CLAIMS

1. A process for the removal of (cyclo)aliphatic hexene and hexadiene isomers from allyl chloride, characterized by a chlorination step which is performed in the liquid phase.

5

10

15

20

25

- 2. A process according to claim 1, characterized in that the chlorination is performed by feeding gaseous chlorine, optionally mixed with an inert gas, or chlorine dissolved in an inert liquid.
- 3. A process according to claim 1 or 2, characterized in that the chlorination is performed at a temperature of between -20 and 120 °C and at a pressure which is sufficient to ensure that the allyl chloride is liquid at the temperature employed.
- 4. A process according to claim 3, characterized in that the chlorination is performed at a temperature of between 20 and 80 °C.
- 5. A process according to any one of claims 1 to 4, characterized in that the amount of chlorine used in the chlorination is between 1 and 5 mol per mol of combined (cyclo)aliphatic hexenes and hexadienes originally present in the crude allyl chloride.
- 6. A process according to claim 5, characterized in that the amount of chlorine used is between 1.5 and 3.5 mol per mol of combined (cyclo)aliphatic hexenes and hexadienes originally present in the crude allyl chloride.
- 7. A process according to any one of claims 1-6, comprising the steps of:
- a. distillation of the crude allyl chloride to remove light ends;
- b. chlorination in the liquid phase of the (cyclo)aliphatic hexene and hexadiene isomers present in the crude allyl chloride;
- c. distillation of the crude allyl chloride to remove heavy ends.

# INTERNATIONAL SEARCH REPORT

Inte mal Application No
PCT/EP 95/02900

A. CLASSI IPC 6	IFICATION OF SUBJECT MATTER C07C17/395 C07C17/38 C07C2	1/067	
According t	to International Patent Classification (IPC) or to both national cl	lassification and IPC	
	SEARCHED		
	locumentation searched (classification system followed by classification)	fication symbols)	
IPC 6	C07C	, ,	
Documental	tion scarched other than minimum documentation to the extent t	that such documents are included in the fields s	earched
		and the search terms used)	
Electronic d	lata hase consulted during the international scarch (name of data	a tase and, where practical, search arms area,	
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	he relevant passages	Relevant to claim No.
Y	WO,A,94 13611 (SHELL INTERNATION RESEARCH MAATSCAPPIJ B.V.) 23 cited in the application see the whole document	DNALE June 1994	1-6
Y	US,A,3 914 167 (J.B. IVY ET AL. October 1975 see the whole document	.) 21	1-6
Furt	ther documents are listed in the continuation of box C.	Patent family members are listed	in annex.
'A' docum	ategories of cited documents:	"T" later document published after the into or priority date and not in conflict we cited to understand the principle or the	ith the application out
"E" carlier		"X" document of particular relevance; the cannot be considered novel or canno involve an inventive step when the do	claimed invention
which citatio	ent which may throw doubts on priority claim(s) or its cited to establish the publication date of another on or other special reason (as specified)	"Y" document of particular relevance; the cannot be considered to involve an independent is combined with one of its	claimed invention eventive step when the hore other such docu-
other	nent referring to an oral disclosure, use, exhibition or means thent published prior to the international filing date but than the priority date claimed	ments, such combination being obviction the art.  '&' document member of the same patent	ous to a person skilled
	actual completion of the international search	Date of mailing of the international se	arch report
8	November 1995	1 6. 11. 95	
Name and	mailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer	
	NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016	Bonnevalle, E	

1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Inte onal Application No
PCT/EP 95/02900

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
WO-A-9413611	23-06-94	CN-A- 10	151269 094023 675866	23-06-94 26-10-94 11-10-95
US-A-3914167	21-10-75	NONE		