



- (51) International Patent Classification:
A61F 13/00 (2006.01)
- (21) International Application Number:
PCT/IB2013/001555
- (22) International Filing Date:
23 May 2013 (23.05.2013)
- (25) Filing Language:
English
- (26) Publication Language:
English
- (30) Priority Data:
61/651,483 24 May 2012 (24.05.2012) US
61/782,270 14 March 2013 (14.03.2013) US
- (71) Applicant: SMITH & NEPHEW PLC [GB/GB]; 15 Adam Street, London WC2N 6LA (GB).
- (72) Inventors: DAGGER, Anthony, C.; C/o Smith & Nephew Research Centre, York Science Park, Heslington, York YO10 5DF (GB). FRY, Nicholas, Charlton; C/o Smith & Nephew Research Centre, York Science Park, Heslington, York YO10 5DF (GB). HICKS, John, Kenneth; C/o Smith & Nephew Research Centre, York Science Park, Heslington, York YO10 5DF (GB). HUDDLESTON, Elizabeth, Mary; C/o Smith & Nephew Research Centre, York Science Park, Heslington, York YO10 5DF (GB). PHILLIPS, Marcus, Damian; C/o Smith & Nephew Research Centre, York Science Park, Heslington, York YO10 5DF (GB). SAXBY, Carl; C/o Smith & Nephew

Research Centre, York Science Park, Heslington, York YO10 5DF (GB). DUNN, Raymond M.; 10 Spring Street, Shrewsbury, MA 01545 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report (Art. 21(3))

(54) Title: DEVICES AND METHODS FOR TREATING AND CLOSING WOUNDS WITH NEGATIVE PRESSURE




FIG. 2B

(57) Abstract: The present invention relates to a negative pressure wound closure system and methods for using such a system. Preferred embodiments of the invention facilitate closure of the wound by preferentially contracting to provide for movement of the tissue.

WO 2013/175309 A1

DEVICES AND METHODS FOR TREATING AND CLOSING WOUNDS WITH NEGATIVE PRESSURE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application Nos. 61/651,483, filed May 24, 2012, entitled DEVICES AND METHODS FOR TREATING AND CLOSING WOUNDS WITH NEGATIVE PRESSURE, and 61/782,270, filed March 14, 2013, entitled DEVICES AND METHODS FOR TREATING AND CLOSING WOUNDS WITH NEGATIVE PRESSURE, the contents of which are hereby incorporated by reference in their entireties as if fully set forth herein. The benefit of priority to the foregoing applications is claimed under the appropriate legal basis including, without limitation, under 35 U.S.C. § 119(e).

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] Embodiments described herein relate to devices and methods that can be used to treat a wound with negative pressure. Particular embodiments can also be useful to aid in wound closure, for example in abdominal wounds.

Description of the Related Art

[0003] In the prior art, application of negative pressure may sometimes exert an outward force upon the wound margins due to the atmospheric pressure compressing the wound filler downward and outward against the margins of the wound. This downward compression of the wound filler slows the healing process and slows or prevents wound closure. Accordingly, there is a need to provide for an improved apparatus, method, and system for the treatment and closure of wounds.

SUMMARY OF THE INVENTION

[0004] Generally, the embodiments described herein can be used to assist in the treatment of wounds with negative pressure. The embodiments can be particularly useful in treating large wounds, such as abdominal wounds, where closure and approximation of the wound edges is challenging. By limiting the amount of vertical pressure applied to the

wound filler, by enhancing the horizontal collapse of the wound filler, and by enhancing attachment of the wound filler to the wound margins, together with additional details described herein, improved wound closure can be obtained.

[0005] In some embodiments, a wound filler for use in treating a wound with negative pressure comprises:

a porous filling material;

a plurality of vertically extending members configured to extend vertically when the wound filler is positioned within a wound bed, the vertically extending members being made of a more rigid material than the porous wound filling material; and

wherein upon application of negative pressure to the wound filler, the wound filler is configured to contract horizontally with the vertically extending members reducing vertical movement of the wound filler.

[0006] In certain embodiments, the vertically extending members can be struts, slabs, columns or tiles. In some embodiments, the vertically extending members of any of the aforementioned wound filler embodiments are elongate members configured to extend lengthwise across a wound bed and are aligned parallel to one another. In particular embodiments, the porous wound filling material of any of the aforementioned wound filler embodiments can surround the vertically extending members. In some embodiments, the porous wound filling material of any of the aforementioned wound filler embodiments can extend between the vertically extending members. In particular embodiments, the porous wound filling material of any of the aforementioned wound filler embodiments can comprise a plurality of slits or areas in which denser or more rigid struts or slabs are inserted.

[0007] In particular embodiments, the wound fillers of any of the aforementioned embodiments can include flexible material positioned between the vertically extending members to allow compression of the vertically extending members towards each other in a horizontal plane when the wound filler is positioned within a wound bed and is placed under negative pressure. In some embodiments, the vertically extending members of any of the aforementioned wound filler embodiments can be adhered to the porous wound filling material.

[0008] In some embodiments, one or more draw strings or cords can extend through the wound filler such that pulling of the draw strings causes contraction of the wound filler in a horizontal plane.

[0009] In certain embodiments, a negative pressure wound therapy system comprises a wound filler such as those described herein and a wound cover configured to be placed over the wound filler. In certain embodiments, the negative pressure wound therapy system described above further includes a connection for connecting the wound cover to a source of negative pressure. In some embodiments, the aforementioned negative pressure wound therapy system further comprises a negative pressure source configured to be connected to the wound cover to provide negative pressure to the wound filler when placed within the wound bed.

[0010] In some embodiments, a method of treating a wound comprises:
positioning a wound filler of any one of the previously described embodiments into a wound bed;
covering the wound filler with a wound cover; and
applying negative pressure to the wound cover, wherein the application of negative pressure causes the wound filler to contract horizontally with the vertically extending members reducing vertical movement of the wound filler.

[0011] Other embodiments of wound closure devices, stabilizing structures and associated apparatuses are described below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Other features and advantages of the present invention will be apparent from the following detailed description of the invention, taken in conjunction with the accompanying drawings of which:

[0013] Fig. 1 illustrates one embodiment of a negative pressure wound therapy system.

[0014] Fig. 2A is a cross-sectional view of one embodiment of a wound filler taken through a horizontal plane.

[0015] Fig. 2B is a cross-sectional view of a wound with a wound filler positioned therein.

[0016] Fig. 2C is a cross-sectional view of another type of wound with a wound filler positioned therein.

[0017] Fig. 2D is a cross-sectional view of another type of wound with a wound filler positioned therein.

[0018] Fig. 2E is a cross-sectional view of a wound with another embodiment of a wound filler positioned therein.

[0019] Figs. 3A-C illustrate embodiments of wound fillers comprising one or more draw strings.

[0020] Figs. 4A-B illustrate embodiments of a wound filler containing rigid columns or tiles.

[0021] Figs. A1-A11 and A13-A19 illustrate further embodiments of the present application.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0022] Embodiments of wound fillers and other wound treatment apparatuses and methods that may be utilized with and/or that may provide further details regarding the embodiments described below are found in U.S. Provisional Application No. 61/651,483, filed May 24, 2012, the entirety of which is hereby incorporated by reference and portions of which are included below in the section titled "Other Negative Pressure Therapy Apparatuses, Dressings, Wound Fillers, and Methods."

[0023] Various embodiments that can be used for the treatment of wounds will now be described with references to the following figures and description which follow. It will be of course understood that various omissions, substitutions, and changes in the form and details of the embodiments illustrated can be made without departing from the spirit of the disclosure. Additionally, the various features and processes described herein can be used independently of one another, or can be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure. Many of the embodiments described herein include similar components, and as such, these similar components can be interchanged in different embodiments.

[0024] Embodiments disclosed herein relate to apparatuses and methods of treating a wound with reduced pressure, including pump and wound dressing components and apparatuses. Generally, the embodiments including the wound fillers described herein

may be used in combination with a negative pressure system comprising a drape or wound cover placed over the filler. A vacuum source, such as a pump, may be connected to the cover, for example, through one or more tubes connected to an aperture or port made in or under the cover. The apparatuses and components comprising the wound overlay and packing materials, if any, are sometimes collectively referred to herein as dressings. Reference is made to the following applications, which are hereby incorporated by reference in their entireties: U.S. Application Serial No. 12/886,088, titled "SYSTEMS AND METHODS FOR USING NEGATIVE PRESSURE WOUND THERAPY TO MANAGE OPEN ABDOMINAL WOUNDS", published as US 2011/0213287 on September 1, 2011; and U.S. Application Serial No. 13/092,042, titled "WOUND DRESSING AND METHOD OF USE", published as US 2011/0282309 on November 17, 2011.

[0025] It will be appreciated that throughout this specification reference is made to a wound or wounds. It is to be understood that the term wound is to be broadly construed and encompasses open and closed wounds in which skin is torn, cut or punctured, or where trauma causes a contusion, or any other superficial or other conditions or imperfections on the skin of a patient or otherwise that benefit from reduced pressure treatment. A wound is thus broadly defined as any damaged region of tissue where fluid may or may not be produced. Examples of such wounds include, but are not limited to, acute wounds, chronic wounds, surgical incisions and other incisions, subacute and dehisced wounds, traumatic wounds, flaps and skin grafts, lacerations, abrasions, contusions, burns, diabetic ulcers, pressure ulcers, stoma, surgical wounds, trauma and venous ulcers or the like. In some embodiments, the components of the negative pressure treatment system described herein can be particularly suited for incisional wounds that exude a small amount of wound exudate.

[0026] As is used herein, reduced or negative pressure levels, such as $-X$ mmHg, represent pressure levels that are below standard atmospheric pressure, which corresponds to 760 mmHg (or 1 atm, 29.93 inHg, 101.325 kPa, 14.696 psi, etc.). Accordingly, a negative pressure value of $-X$ mmHg reflects absolute pressure that is X mmHg below 760 mmHg or, in other words, an absolute pressure of $(760-X)$ mmHg. In addition, negative pressure that is "less" or "smaller" than X mmHg corresponds to pressure that is closer to atmospheric pressure (e.g., -40 mmHg is less than -60 mmHg).

Negative pressure that is “more” or “greater” than $-X$ mmHg corresponds to pressure that is further from atmospheric pressure (e.g., -80 mmHg is more than -60 mmHg).

[0027] The negative pressure range for some embodiments of the present disclosure can be approximately -80 mmHg, or between about -20 mmHg and -200 mmHg. Note that these pressures are relative to normal ambient atmospheric pressure. Thus, -200 mmHg would be about 560 mmHg in practical terms. In some embodiments, the pressure range can be between about -40 mmHg and -150 mmHg. Alternatively a pressure range of up to -75 mmHg, up to -80 mmHg or over -80 mmHg can be used. Also in other embodiments a pressure range of below -75 mmHg can be used. Alternatively, a pressure range of over approximately -100 mmHg, or even 150 mmHg, can be supplied by the negative pressure apparatus.

[0028] As used herein, the term “horizontal,” when referring to a wound, indicates a direction or plane generally parallel to the skin surrounding the wound. The term “vertical,” when referring to a wound, generally refers to a direction extending perpendicular to the horizontal plane. The term “longitudinal,” when referring to a wound, generally refers to a direction in the horizontal plane taken in a direction along which the wound is longest. The term “lateral,” when referring to a wound, generally refers to a direction in the horizontal plane perpendicular to the longitudinal direction. The terms “horizontal,” “vertical,” “longitudinal,” and “lateral” can also be used to describe the wound fillers or other devices described throughout this specification. When describing these wound fillers or devices, these terms should not be construed to require that the structures or devices necessarily be placed into a wound in a certain orientation, though in certain embodiments, it may be preferable to do so.

[0029] As used herein, the term “fill material” comprises, in a non-limiting manner: porous wound filler materials and flexible materials. As used herein, compressible materials are included within the scope of flexible materials.

[0030] Turning to Figure 1, treatment of a wound with negative pressure in certain embodiments uses a negative pressure treatment system 101 as illustrated schematically here. In this embodiment, a wound site 110, illustrated here as an abdominal wound site, may benefit from treatment with negative pressure. Such abdominal wound sites may be a result of, for example, an accident or due to surgical intervention. In some cases, medical conditions such as abdominal compartment syndrome, abdominal

hypertension, sepsis, or fluid edema may require decompression of the abdomen with a surgical incision through the abdominal wall to expose the peritoneal space, after which the opening may need to be maintained in an open, accessible state until the condition resolves. Other conditions may also necessitate that an opening—particularly in the abdominal cavity—remain open, for example if multiple surgical procedures are required (possibly incidental to trauma), or there is evidence of clinical conditions such as peritonitis or necrotizing fasciitis.

[0031] In cases where there is a wound, particularly in the abdomen, management of possible complications relating to the exposure of organs and the peritoneal space is desired, whether or not the wound is to remain open or if it will be closed. Therapy, preferably using the application of negative pressure, can be targeted to minimize the risk of infection, while promoting tissue viability and the removal of deleterious substances from the wound site. The application of reduced or negative pressure to a wound site has been found to generally promote faster healing, increased blood flow, decreased bacterial burden, increased rate of granulation tissue formation, to stimulate the proliferation of fibroblasts, stimulate the proliferation of endothelial cells, close chronic open wounds, inhibit burn penetration, and/or enhance flap and graft attachment, among other things. It has also been reported that wounds that have exhibited positive response to treatment by the application of negative pressure include infected open wounds, decubitus ulcers, dehisced incisions, partial thickness burns, and various lesions to which flaps or grafts have been attached. Consequently, the application of negative pressure to a wound site 110 can be beneficial to a patient.

[0032] Accordingly, certain embodiments provide for a wound contact layer 105 to be placed over the wound site 110. Preferably, the wound contact layer 105 can be a thin, flexible material which will not adhere to the wound site or the exposed viscera in close proximity. For example, polymers such as polyurethane, polyethylene, polytetrafluoroethylene, or blends thereof may be used. In one embodiment, the wound contact layer is permeable. For example, the wound contact layer 105 can be provided with openings, such as holes, slits, or channels, to allow the removal of fluids from the wound site 110 or the transmittal of negative pressure to the wound site 110.

[0033] Certain embodiments of the negative pressure treatment system 101 may also use a porous wound filler 103, which can be disposed over the wound contact

layer 105. This pad 103 can be constructed from a porous material, for example foam, that is soft, resiliently flexible, and generally conformable to the wound site 110. Such a foam can include an open-celled and reticulated foam made, for example, of a polymer. Suitable foams include foams composed of, for example, polyurethane, silicone, and polyvinyl alcohol. Preferably, this pad 103 can channel wound exudate and other fluids through itself when negative pressure is applied to the wound. Some pads 103 may include preformed channels or openings for such purposes. In certain embodiments, the pad 103 may have a thickness between about one inch and about two inches. The pad may also have a length of between about 16 and 17 inches, and a width of between about 11 and 12 inches. In other embodiments, the thickness, width, and/or length can have other suitable values. Other embodiments of wound fillers that may be used in place of or in addition to the pad 103 are discussed in further detail below.

[0034] Preferably, a drape 107 is used to seal the wound site 110. The drape 107 can be at least partially liquid impermeable, such that at least a partial negative pressure may be maintained at the wound site. Suitable materials for the drape 107 include, without limitation, synthetic polymeric materials that do not significantly absorb aqueous fluids, including polyolefins such as polyethylene and polypropylene, polyurethanes, polysiloxanes, polyamides, polyesters, and other copolymers and mixtures thereof. The materials used in the drape may be hydrophobic or hydrophilic. Examples of suitable materials include Transeal® available from DeRoyal and OpSite® available from Smith & Nephew. In order to aid patient comfort and avoid skin maceration, the drapes in certain embodiments are at least partly breathable, such that water vapor is able to pass through without remaining trapped under the dressing. An adhesive layer may be provided on at least a portion the underside of the drape 107 to secure the drape to the skin of the patient, although certain embodiments may instead use a separate adhesive or adhesive strip. Optionally, a release layer may be disposed over the adhesive layer to protect it prior to use and to facilitate handling the drape 107; in some embodiments, the release layer may be composed of multiple sections.

[0035] The negative pressure system 101 can be connected to a source of negative pressure, for example a pump 114. One example of a suitable pump is the Renasys EZ pump available from Smith & Nephew. The drape 107 may be connected to the source of negative pressure 114 via a conduit 112. The conduit 112 may be connected

to a port 113 situated over an aperture 109 in the drape 107, or else the conduit 112 may be connected directly through the aperture 109 without the use of a port. In a further alternative, the conduit may pass underneath the drape and extend from a side of the drape. U.S. Patent No. 7,524,315 discloses other similar aspects of negative pressure systems and is hereby incorporated by reference in its entirety and should be considered a part of this specification.

[0036] In many applications, a container or other storage unit 115 may be interposed between the source of negative pressure 114 and the conduit 112 so as to permit wound exudate and other fluids removed from the wound site to be stored without entering the source of negative pressure. Certain types of negative pressure sources—for example, peristaltic pumps— may also permit a container 115 to be placed after the pump 114. Some embodiments may also use a filter to prevent fluids, aerosols, and other microbial contaminants from leaving the container 115 and/or entering the source of negative pressure 114. Further embodiments may also include a shut-off valve or occluding hydrophobic and/or oleophobic filter in the container to prevent overflow; other embodiments may include sensing means, such as capacitive sensors or other fluid level detectors that act to stop or shut off the source of negative pressure should the level of fluid in the container be nearing capacity. At the pump exhaust, it may also be preferable to provide an odor filter, such as an activated charcoal canister.

[0037] Figures 2A-2E illustrate embodiments of a wound filler 200 that may be used in the system described above comprising fill material 202 and extending members 204. In some preferred embodiments, the fill material is a porous wound filler material such as described above. In certain preferred embodiments, the fill material 202 is flexible. As shown in a horizontal cross-section in Figure 2A, the wound filler 200 may include a plurality of extending members 204 contained within an oval-shaped fill material 202. It will be appreciated that the fill material 202 can have other shapes, such as rectangular or square, and that the shape shown in Figure 2A may simply result from the filler being cut by a health practitioner to an appropriate size. The wound filler as shown in Figure 2A is shown with an outer dimension sized to fit within an oval-shaped wound when the wound is viewed from above.

[0038] In some embodiments, the extending members 204 are denser than the fill material 202. In some embodiments, the extending members 204 are between 1 to 2

times, between 2 to 4 times, between 4 to 6 times, between 6 to 8 times, or 8 times or more dense than the fill material. In certain embodiments, the extending members 204 are more rigid than the fill material 202. In some embodiments, the extending members are between 1 to 2 times, between 2 to 4 times, between 4 to 6 times, between 6 to 8 times, or 8 times or more rigid than the porous wound filling material.

[0039] In certain preferable embodiments, and as also shown in Figures 2B-2E, the extending members 204 are elongate members that extend vertically when the wound filler 200 is positioned within a wound bed. In particular embodiments, as shown in Figure 2A, the extending members 204 are elongate members that may also extend horizontally across a portion or the entire longitudinal length of the wound filler when the wound filler 200 is positioned within a wound bed. In some embodiments, the extending members 204 are sheets that may have parallel faces, while in other embodiments, the extending members 204 may comprise struts, slabs, columns, or tiles. In other embodiments, the extending members 204 extend at an angle from the horizontal or vertical plane of the wound.

[0040] The extending members 204 may be parallel or substantially parallel to one another, and may be spaced apart 204 either equally or unequally. In horizontal cross-section as shown in Figure 2A, each of the extending members may have the same thicknesses, or alternatively, they may have different thicknesses. In vertical cross-section as shown in Figures 2B-2E, the extending members may have the same vertical height or length, or may have different vertical heights or lengths. The dimensions of the wound filler, and particularly the horizontal length and the vertical height of the extending members as well as the number of extending members, may depend on the size to which the filler material is cut by the health practitioner. In the embodiments shown, the extending members may have a rectangular cross-section in both horizontal and vertical cross-section, where the horizontal length is greater than the thickness, and the vertical height is greater than the thickness. In some embodiments, the extending members may comprise sheets. In one embodiment, the wound filler is configured to be placed in a wound such that the horizontal length of the extending members is parallel or generally parallel to the longitudinal length of the wound, and the thickness dimension of the extending members extend in the lateral direction.

[0041] In some embodiments, as shown in Figure 2A, the fill material 202 contains slits or areas for the insertion of extending members 204. In some embodiments, the extending members 204 can be inserted after the wound filler 200 has been placed in the wound. In other embodiments, the extending members 204 are placed within the wound filler prior to insertion into the wound. In some embodiments, the slits or areas for insertion can be made after the wound filler 200 has been placed in the wound. In certain embodiments, the slits or areas for insertion are made before the wound filler is placed in the wound. In embodiments where the fill material 202 contains slits or areas for insertion of extending members, the slits may be open to a top surface and/or a bottom surface of the fill material to allow the extending members to be vertically inserted. As shown in Figure 2A, the horizontal length of the extending members may be shorter than a horizontal dimension of the fill material 202, such that the extending members 204 are fully surrounded by the fill material 202 in a horizontal plane. In some embodiments, the extending members may be attached to the fill material, such as with adhesive, barbs, Velcro™ or other attachment mechanisms. In other embodiments, the extending members may simply be inserted into the slits or areas for insertion of the fill material and be connected by friction, an interference fit, a slight expansion of the extending members, or other mechanical forces.

[0042] As shown in Figures 2B-2D, the extending members can be vertical when positioned within a wound. Figure 2B illustrates a side or vertical cross-sectional view of an embodiment of a wound filler 200 positioned within a wound 206, with vertical extending members 204 and fill material 202. The extending members may be similar to those shown in Figure 2A, or they may consist of alternate slabs of material that may be parallel or substantially parallel to one another. Thus, in some embodiments, instead of having extending members inserted or surrounded by fill material, the extending members and fill material can comprise multiple layers, sheets or slabs alternatingly stacked and adhered together to form a hybrid laminate. For example, a layer of more flexible or compressible wound filler (e.g., foam) may alternatingly be stacked with layers of more rigid wound filler. It will be appreciated that even in such a configuration, further layers of porous material such as foam may be placed above and below the wound filler 200, or the entire wound filler may be surrounded by a porous material such as foam.

[0043] In some embodiments, upon application of negative pressure to the wound filler 200, for example, using the system previously described with respect to Figure 1, the wound filler 200 is configured to contract horizontally 208 with the vertical extending members 204 reducing vertical movement of the wound filler 200. The fill material 202 extends between the plurality of vertically extending members 204 and the fill material and the vertically extending members may be adhered together. As shown in Figure 2B, as negative pressure is applied to close the wound 206, the fill material 202 between the vertically extending members 204 may desirably compress so that the vertically extending members come closer together as the wound closes.

[0044] Figure 2C illustrates a cross-sectional view of an embodiment of a wound filler 200 in a shallow wound 206, comprising a fill material 202 with spaced apart areas in which a plurality of extending members 204 are located. In a similar manner to the embodiments described in Figures 2A-2B, the wound filler is configured to compress horizontally 208, but vertical compression is limited.

[0045] Figure 2D illustrates another cross-sectional view of an embodiment of a wound filler 200 for use in a wound 206, similar to the embodiments described in Figures 2A-2C, comprising denser material 204 alternating with less dense material 202 similar to the embodiments described above. In the embodiment of Figure 2D, the wound filler 200 may have or be cut to a shape where the upper and lower surfaces of the wound filler are parallel or substantially parallel. As illustrated, the extending members of denser material 204 may have the same vertical height.

[0046] Figure 2E illustrates an embodiment of a wound filler similar to those described in Figure 2A-2D, where the wound filler can be placed in an abdominal wound 210 surrounded by abdominal tissue 212. In some embodiments, the wound filler 200 comprises fill material 202 and extending members 204 similar to the embodiments described above. In certain embodiments, when negative pressure is applied, the wound filler 200 is configured to contract in the horizontal plane while remaining rigid in the vertical plane.

[0047] In any of the embodiments herein described, the wound filler can be cut to an appropriate shape and size to fit within the wound. The wound filler can be trimmed to shape in any manner, for example by trimming around the circumference of an oval wound filler or by trimming the horizontal edges of a square or rectangular wound filler.

[0048] In some embodiments, after the wound filler is appropriately sized, the extending members can be aligned such that, when placed in a wound cavity, they are perpendicular and extend in a vertical direction from the wound bed. In certain embodiments, application of a vacuum can then cause the fill material to contract substantially only in the horizontal plane, as the extending members reduce movement in the vertical direction (and may also resist horizontal movement). In some embodiments, the compression of the filler can aid in closing the wound cavity in the horizontal plane.

[0049] In some embodiments, preferably applicable to the embodiments described in Figures 2A-2E, the thickness of the extending members can range from 1 to 10 mm (or about 1 to about 10 mm), for example about 1mm to about 2mm, about 2mm to about 3mm, about 3mm to about 4mm, about 4mm to about 5mm, about 5mm to about 6mm, about 6mm to about 7mm, about 7mm to about 8mm, about 8mm to about 9mm, about 9mm to about 10mm, and greater than 10mm (or greater than about 10mm). In certain embodiments, the width of the fill material can range from 1 to 20 mm (or about 1 to about 20 mm), for example about 1mm to about 5mm, about 5mm to about 10mm, about 10mm to about 15mm, about 15mm to about 20mm, and greater than 20mm (or greater than about 20mm). In any of the embodiments described herein, the fill material may be adhered to the extending members. In certain embodiments, the fill material is adhered to the extending members by an adhesive. In certain preferable embodiments, the fill material is adhered to the extending members via Velcro™ tape.

[0050] In any of the embodiments described herein, the extending members can be made from rigid plastics such as polystyrene, polycarbonate, poly(meth)acrylates, semi-rigid materials such as silicone, or from rigid foams or felted flexible foams. In some embodiments, felted flexible foams can be made by subjecting flexible foams, e.g. those used as the porous compressible filler, to heat and pressure to produce a dense, semi-rigid foam that is still porous. Such a configuration can also enhance horizontal movement so as to permit greater wound closure.

[0051] In some embodiments (not shown but described as Figure 2 in Provisional Application No. 61/651,483), a wound filler is provided comprising a minimally-compressible central core surrounded by a compressible outer layer. Such a configuration can reduce vertical movement and permit the wound edge to move inward in a direction toward the central core, thereby aiding in closing the wound. Further, the

amount of closure can be controlled by varying the size of the central core. In some embodiments, the central core comprises one or more of a rigid foam, closed cell foam, and silicone elastomers or rigid flexible foam. Further embodiments may also comprise alternating concentric rings of more rigid (or more dense) material and less rigid (or less dense) material.

[0052] In certain embodiments (not shown but described as Figure 3 in Provisional Application No. 61/651,483), an embodiment may be configured in the opposite manner as the embodiment described in the paragraph above, with a minimally-compressible outer layer surrounding a compressible core. The minimally-compressible outer layer can be configured to resist vertical compression, while the compression of the central core can aid in wound closure. As with the embodiment of the previous paragraph, this embodiment can be arranged in a concentric circle or oval configuration, or a linear configuration.

[0053] Figure 3A illustrates an embodiment of a wound filler 300 comprising fill material 302 and one or more draw strings or cords 304. The one or more draw strings or cords can extend through the fill material, preferably with free ends extending from the top side of the wound filler (i.e., the side of the filler that will face outward when the wound filler is inserted into a wound). When negative pressure is applied using a system such as described above, the draw strings (which may extend out or under a wound cover) can be tightened, for example by pulling in a vertical direction 306, thereby causing the wound filler to contract substantially only in a horizontal plane.

[0054] Figure 3B illustrates an embodiment of a wound filler 310 comprising fill material 302 and extending members 308 such as described in any of the embodiments above, and one or more draw strings or cords 304. The one or more draw strings or cords extend through the wound filler 310, preferably with free ends extending from the top side of the wound filler. In a preferred embodiment, the fill material 302 and the extending members 308 can be alternating. In a similar manner to the embodiments described in Figures 2A-2E, the extending members 308 can be dense, more rigid, or more dense and rigid than the fill material. The one or more draw strings can extend through the wound filler, preferably with free ends extending from the top side of the wound filler (i.e., the side of the filler that will face outward when the wound filler is inserted into a wound).

[0055] In the embodiment of Figure 3B, because the draw strings or cords 304 form loops between adjacent or spaced apart extending members 308, pulling of the draw strings can cause the extending members to compress the fill material therebetween and draw the extending members closer together. In some embodiments, the draw strings can be attached or secured at desired locations to the extending members 308 to facilitate the ability to draw the extending members closer together. In some embodiments, when negative pressure is applied using a system such as described above, the draw strings or cords can be tightened, for example by pulling in a vertical direction 306, thereby causing the wound filler to contract substantially only in a horizontal plane.

[0056] Figure 3C illustrates an embodiment of a wound filler 320 similar to the embodiment described in Figure 3B, comprising fill material 302, extending members 308, and multiple draw strings 324 configured to cause the wound filler 320 to contract in a horizontal direction. As illustrated, draw strings 324 may be secured to outer extending members 308, and may extend vertically through adjacent extending members out of the wound filler. In certain embodiments, when negative pressure is applied using a system such as described above, the draw strings or cords 324 can be tightened, for example by pulling in a vertical direction 306, thereby causing the wound filler to contract substantially only in a horizontal plane. In certain embodiments, the wound filler contains more than 2, more than 4, more than 6, or more than 8 draw strings or cords. Figures 4A-B illustrate different views of embodiments of a wound filler 400 similar to the embodiments described in Figures 1A-G. Figure 4A depicts a horizontal cross-sectional view of a wound filler 400 comprising fill material 402 and extending members 404 extending in a vertical plane or direction. Preferably, the extending members can be rigid columns or tiles. In preferred embodiments, the wound filler will preferentially collapse horizontally when negative pressure is applied, while the rigid columns or tiles 404 substantially prevent the wound filler from collapsing vertically, thus assisting in wound closure. In some preferred embodiments, the wound filler 400 can be cut to the size of the wound, as the columns or tiles 404 are preferably dispersed throughout the wound filler. In a preferred embodiment, the fill material 402 comprises foam. Figure 4B illustrates a vertical cross section of an embodiment of the wound filler described in Figure 4A.

[0057] In some embodiments, the rigid columns can comprise rigid plastic such as polystyrene, polycarbonate or a semi-rigid material such as a silicone. In certain

embodiments, the rigid columns can comprise a rigid or felted foam. In some embodiments, the columns may have a circular cross-section, and may have diameters for example from 5 mm to 10 mm (or about 5 mm to about 10 mm) with a spacing of 5 mm to 10 mm (or about 5 mm to about 10 mm) around them. For example, the diameter of the column can be about 1mm, about 2mm, about 3mm, about 4mm, about 5mm, about 6mm, about 7mm, about 8mm, about 9mm, about 10mm, or greater than 10mm (or greater than about 10mm). In certain embodiments, the spacing between the columns can range from about 1mm to 5mm, about 5mm to 10mm, about 10mm to 15mm, about 15mm to 20mm, or greater than 20mm (or greater than about 20mm).

[0058] In some embodiments (not shown but described as Figure 14 in Provisional Application No. 61/651,483), a wound filler may comprise one or more conduits that extend to the wound-facing perimeter and are configured to communicate negative pressure. Here, once the wound is sealed under a drape, the one or more conduits can apply negative pressure to the wound, thereby contacting one or more areas on the inside perimeter of the wound. The wound filler can comprise fill material and extending members as described hereinbefore. The wound filler is preferably configured to contain one or more laces or filaments with free ends extending in a vertical direction away from the wound. Upon application of negative pressure, and once the edges of the wound have made contact with the wound filler, the one or more laces or filaments can be pulled so as to collapse the wound filler inward, thereby aiding in the closure of the wound. In some embodiments, the laces or filaments are attached to the extending members and may comprise any of the draw string embodiments previously described herein.

[0059] In some embodiments, any of the aforementioned wound fillers can comprise a dissolvable foam. In certain embodiments, the wound filler can comprise an area of dissolvable foam surrounding or surrounded by one or more regions of foam that do not dissolve under ordinary physiological conditions. In particular embodiments, the dissolvable foam region can be central and surrounded by one or more strips of non-dissolvable foam. In some embodiments, the dissolvable foam can also be in a ring configuration and surrounded at least on a horizontal plane by non-dissolvable foam (or vice-versa). In certain embodiments, when implanted into a wound, the dissolvable portions of foam can at least partly dissolve, for example upon contact with wound

exudate, thereby providing additional space for the non-dissolvable foam to collapse toward. In preferable embodiments, this collapse can be used to promote horizontal closure of the wound. In some embodiments, the dissolvable foam can comprise polyvinyl alcohol foam (PVA).

[0060] In certain embodiments, the dissolvable foam can be replaced by a resorbable filler, for example a resorbable tissue filler scaffold. In some embodiments, this tissue filler can be constructed from biodegradable polymers such as polylactic acid, polyglycolic acid, or any combination of the two polymers. In particular embodiments, the resorbable scaffold can be configured to deliver beneficial molecules. In some embodiments, the scaffold is configured to deliver growth factors. In certain embodiments, the scaffold is configured to deliver antimicrobial molecules. In particular embodiments, such a scaffold can be seeded with beneficial cells, such as fibroblasts or stem cells. In some embodiments, such a scaffold can be seeded with keratinocytes.

[0061] In some embodiments, any of the aforementioned wound fillers can be constructed from a three-dimensional material comprising stiffer vertical components and compressible components extending in a lateral direction, such as 3D fabrics and fibers. In some embodiments, the material can present itself as a three-dimensional non-woven material. In particular embodiments, such a wound filler material can preferentially collapse or more readily collapse in a horizontal direction while resisting collapse in a vertical direction.

[0062] In some embodiments, any of the aforementioned wound filler materials can comprise a foam material with different-sized bubbles. In some embodiments, as smaller bubbles are more resistant to collapse than larger bubbles, the bubble sizes can be tailored to control the contraction of the wound filler. In certain embodiments, bubbles can be arranged in a gradient, such as a lengthwise or circular gradient, to control collapsibility of the wound filler. In certain embodiments, this arrangement of bubbled can be manufactured using a dual dispense injection process, wherein a first material having a first density (e.g., a first pore/bubble/void size) and a second material having a second density (e.g., a second pore/bubble/void size) are injected into a mold or a plurality of molds. In some embodiments, the second material can be the same material as the first material, but have a different pore size or different size voids or bubbles therein. In certain

embodiments, foams of different pore, bubble, or void sizes or density can be coupled together.

[0063] Some embodiments can comprise foam with varying compressibility obtained by changing the chemistry or makeup of the material used to make the foam as foam is being produced. For example, without limitation, longer soft (more compressible) polymer blocks or plasticizers can be used to make all or a portion of the foam more compressible. In some embodiments, soft (more compressible) blocks or soft (more compressible) portions of the filler can be made from polypropylene glycol or polytetramethylene glycol, or other similar materials. In some embodiments, the filler can have soft (more compressible) blocks or soft (more compressible) portions made from any suitable sufficiently high molecular weight material.

[0064] In some embodiments, during manufacture of the foam material, the makeup of the material passing through the injectors or dispensers used to inject or dispense the foam material can be altered such that the density or stiffness of the foam changes along the length of the foam. For example, without limitation, the foam can be manufactured such that softer, more compressible portions are sandwiched or positioned between stiffer, less compressible portions of the same length of foam. Thereby, the foam having varying compressibility can be produced integrally. In certain embodiments, including any of the embodiments herein where the foam or filler can be produced in multiple stages, softer more compressible foam portions can be injected into, or otherwise inserted into voids or bubbles within a less compressible foam material, or vice versa, or can be formed (i.e., injected) or positioned between portions of less compressible foam material. In some embodiments, the additional material, if formed in separate foam blocks or layers, can be laminated or otherwise coupled with the other material or materials with which it is to be used.

[0065] In some embodiments, a method of treating a wound can include positioning any one of the aforementioned wound fillers into a wound bed and covering the wound filler with a wound cover. Applying negative pressure to such an embodiment can cause the wound filler to contract horizontally with the vertically extending members reducing vertical movement of the wound filler.

Other Negative Pressure Therapy Apparatuses, Dressings, Wound Fillers, and Methods

[0066] Further embodiments of negative pressure therapy apparatuses, dressings, wound fillers and methods of using the same that may be utilized alone or in combination with the embodiments described herein, and further description of the embodiments found above, are found in U.S. Provisional Application No. 61/651,483, filed May 24, 2012, the entirety of which is hereby incorporated by reference. Portions of U.S. Provisional Application No. 61/651,483, which was included as an Appendix in U.S. Provisional Application No. 61/782,270, are reproduced below.

[0067] Figures. A1A-C illustrate embodiments of a porous wound filling material with slits or areas in which a denser porous wound filling material has been inserted, similar to the embodiments disclosed in Figures 2A-E. The embodiment is configured to be inserted into a wound. In some embodiments, the porous wound filling material is foam, for example an open-cell foam. The aforementioned embodiments can also enhance horizontal movement so as to permit greater wound closure.

[0068] In a manner similar to the embodiment disclosed in Figure 2B, Figure A1B illustrates an embodiment of a wound filler material that can be cut to shape and can consist of alternate slabs of flexible or compressible wound filler (e.g., foam) together with more rigid wound filler. Figure A2 illustrates a wound filler comprising a minimally-compressible central core surrounded by a compressible outer layer. Such a configuration can reduce vertical movement and permit the wound edge to move inward in a direction toward the central core, thereby aiding in closing the wound. Further, the amount of closure can be controlled by varying the size of the central core. In some embodiments, the central core comprises one or more of a rigid foam, closed cell foam, and silicone elastomers.

[0069] Figure A3 illustrates an embodiment that is configured in the opposite manner as Figure A2 above, with a minimally-compressible outer layer surrounding a compressible core. The minimally-compressible outer layer can be configured to resist vertical compression, while the compression of the central core can aid in wound closure. As with Figure A2, Figure A3 can be arranged in a concentric circle or oval configuration, or a linear configuration.

[0070] In this embodiment, the treatment device comprises a wound filler (e.g., foam) with telescopic tubes. The wound filler can be placed into a wound cavity with telescopic tubes positioned across the major axis of the wound and on top of the filler and

periwound area. In other embodiments, the tubes can be integrated through the wound filler. A drape can then be placed over the treatment device, and the entire assembly fluidically attached to a source of negative pressure.

[0071] Application of negative pressure will cause the filler to collapse in a horizontal plane, but the tubes will reduce vertical movement of the filler (which would otherwise apply a horizontal force that makes wound closure more difficult). As the wound margins contract, the telescopic tubes will collapse along their length, thus closing together with the wound.

[0072] With reference to Figure A5, in this embodiment, wound filling material such as foam is placed into a wound cavity. One or more stiffeners can then be placed over the wound, wound filler, and periwound area. The one or more stiffeners can be constructed from a rigid or semi-rigid material (such as a closed-cell foam) that resists compression. Application of vacuum causes the foam to collapse in the horizontal plane, while the one or more stiffeners reduce vertical compression of the foam.

[0073] Figure A6 illustrates an embodiment of a wound filler with a minimally-adherent wound contact layer on its base and configured to be placed in contact with the wound bed. In some embodiments, the wound contact layer can comprise silicone, or a foam with a thicker skin on one side. When vacuum is applied, the minimally-adherent wound contact layer would promote horizontal contraction of the foam so as to permit greater wound closure. Any of the embodiments disclosed herein, including without limitation those having foam or other fillers or wound packing, those having columns or struts or other support elements, can have a silicone or other slick material or film on one or more wound contacting surfaces thereof to reduce the adhesion or stickiness with respect to the wound.

[0074] Figure A7 illustrates an embodiment where a wound filler, which can be constructed from foam, comprises one or more threads or wires inserted therein. The wires preferably extend in a horizontal plane, and can be constructed from a shape-memory polymer or metal. The wires are preferably inserted or cast into the wound filler in an extended shape, and upon application of a stimulus, the wound filler preferentially contracts in the horizontal plane. In some embodiments, the stimulus causing contraction of the thread or wire can be moisture, heat, or application of reduced pressure.

[0075] In some embodiments, the wound filler can comprise entirely or in part an elastomeric shape-memory foam. The shape-memory foam can be pre-stressed into an extended configuration, and, upon exposure to moisture, will contract. An example of a suitable shape-memory foam is Elast-Eon™.

[0076] In this embodiment, a wound filler has one or more draw strings or cords extending through it, preferably with free ends extending from the top side of the wound filler (i.e., the side of the filler that will face outward when the wound filler is inserted into a wound). When negative pressure is applied, the draw strings can be tightened, for example by pulling in a vertical direction, thereby causing the foam to contract substantially only in a horizontal plane.

[0077] Figure A8 illustrates an embodiment similar to the embodiment described in Figure 3A-C. Draw strings or cords may extend through the structure. The drawstrings tighten under negative pressure and cause the structure to contract in only one plane.

[0078] Figure A9 illustrates an embodiment with a wound filler material with rigid columns or tiles extending in a vertical plane or direction, an embodiment similar to the embodiments described in Figures 4A-B. The wound filler, which can comprise foam, will preferentially collapse horizontally when negative pressure is applied. The rigid columns or tiles will substantially prevent the wound filler from collapsing vertically, thus assisting in wound closure. Advantageously, the wound filler can be cut to the size of the wound, as the columns or tiles are preferably dispersed throughout the wound filler.

[0079] Figure A10 illustrates an embodiment of a wound closure device comprising a rigid oasis, or core, surrounded by a soft, conformable wound filler such as a reticulated foam. The core comprises one or more passages communicating between the filler material and a source of negative pressure. Upon application of negative pressure, the wound filler will collapse toward the core, thereby preferentially collapsing in a horizontal plane and facilitating wound closure. In one embodiment, the core comprises a central conduit configured to be connected to the source of negative pressure (e.g., via a conduit or a miniature pump), where the central conduit links to one or more peripheral conduits in fluidic communication with the filler.

[0080] Figure A11 illustrates an embodiment of a wound closure system comprising a wound filler placed inside a wound and overlaid with a drape and frame. The

frame can be placed or assembled over the foam and onto the periwound area outside of the drape, and attaches to the drape so as to restrict vertical movement of the drape and wound filler. Accordingly, horizontal collapse of the filler will be maximized.

[0081] With reference to Figure A13A, this embodiment can have an inflatable bladder surrounded at least in part by a porous wound filler material such as foam. The inflatable bladder can be filled with liquid, and preferably comprises one or more ports (e.g., a syringe port) that can be used to adjust the amount of fluid therein. In use, the device is placed into a wound and covered with a drape, and, upon application of negative pressure, fluid can be withdrawn from the inflatable bladder to control the amount of contraction of the wound margins. Preferably, the fluid is withdrawn via a tube connected through or under the drape that connects the port to a different source of negative pressure such as a syringe.

[0082] In a manner similar to the embodiment illustrated in Figure A13A, Figure A13B illustrates an embodiment with an inflatable bag surrounded at least in part by a wound filler such as foam. Here, the inflatable bag is filled with air or gas, and suction (separate from a source of negative pressure used to treat the wound) can be applied to control the amount of contraction of the foam.

[0083] Figure A14 illustrates a semi-rigid wound filler comprising one or more conduits extending to a wound-facing perimeter of the filler that are configured to communicate negative pressure. Here, once the wound is sealed under a drape, the one or more conduits apply negative pressure to the wound, thereby contacting one or more areas on the inside perimeter of the wound. The semi-rigid wound filler is preferably configured to contain one or more laces or filaments with free ends extending in a vertical direction away from the wound. Upon application of negative pressure, and once the edges of the wound have made contact with the wound filler, the laces can be pulled so as to collapse the wound filler, thereby aiding in the closure of the wound.

[0084] In Figure A15, an embodiment of a wound filler such as foam can have its outside (wound-facing) edges cut to provide additional surface area and protrusions to aid in fixation to the wound surface. These edges can consequently enhance wound closure by aiding in pulling the wound edges together upon the application of negative pressure. For example, pinking shears or other serrated cutting implements can be used to add a sawtoothed, wavy, corrugated, irregular, or roughened outer perimeter to the

wound filler. Other embodiments can provide for grit-blasting, sanding, or adding particulates to the surface of the wound filler.

[0085] Figure A16 illustrates an embodiment of a pressure responsive foam for use in a wound. Upon application of negative pressure, conventional foams tend to collapse to approximately the same dimensions over the therapeutic ranges of negative pressure applied thereto. However, by tailoring a pressure responsive foam where the volume changes across the therapeutic range of negative pressure, greater control over wound closure can be achieved. For example, such a foam can have a given volume V_1 at a given pressure P_1 . If the negative pressure is increased to a new pressure P_2 , the foam's volume can decrease to a new volume V_2 that is smaller than V_1 . Accordingly, wound closure can be controlled by application of negative pressure to the wound.

[0086] Figure A17 illustrates an embodiment of a wound filler comprising a dissolvable foam. Here, the wound filler can comprise an area of dissolvable foam surrounding or surrounded by one or more regions of foam that do not dissolve under ordinary physiological conditions. In some configurations, the dissolvable foam region can be central and surrounded by one or more strips of non-dissolvable foam. The dissolvable foam can also be in a ring configuration and surrounded at least on a horizontal plane by non-dissolvable foam (or vice-versa). When implanted into a wound, the dissolvable portions of foam would at least partly dissolve, for example upon contact with wound exudate, thereby providing additional space for the non-dissolvable foam to collapse toward. This can be used to promote horizontal closure of the wound. In some embodiments, the dissolvable foam can comprise polyvinyl alcohol foam (PVA). In some embodiments, the dissolvable foam can be replaced by a resorbable filler, for example a resorbable tissue filler scaffold. In some embodiments, such a scaffold can be seeded with beneficial cells, such as fibroblasts or stem cells.

[0087] Figure A18 illustrates an embodiment of a wound closure device comprising a camera-shutter or iris-like configuration of multiple pieces of wound filler material. Preferably, the wound filler material is substantially rigid at least in a vertical plane. The multiple pieces of wound filler material are preferably configured to move inward from an open configuration illustrated above to a closed configuration upon the application of negative pressure, thereby contracting the wound margins in a horizontal

plane. The inward movement of the multiple pieces of wound filler material may resemble the inward movement of a camera shutter.

[0088] Figure A19 illustrates an embodiment of a wound filler device comprising one or more hooks disposed on an outer perimeter thereof, and preferably along a horizontal outer perimeter. The one or more hooks are configured to engage the edges of a wound so as to aid attachment of the filler, thereby aiding in wound closure upon the application of negative pressure. The one or more hooks can be made by using a sudden localized “blast” of heat that can partly melt the foam edge so as to produce a spike, hook, or other protrusion. Application of electrostatic energy to the wound filler can also be used to make the one or more hooks.

[0089] Features, materials, characteristics, or groups described in conjunction with a particular aspect, embodiment, or example are to be understood to be applicable to any other aspect, embodiment or example described herein unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The protection is not restricted to the details of any foregoing embodiments. The protection extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

[0090] While certain embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of protection. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms. Furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein may be made. Those skilled in the art will appreciate that in some embodiments, the actual steps taken in the processes illustrated and/or disclosed may differ from those shown in the figures. Depending on the embodiment, certain of the steps described above may be removed, others may be added. Furthermore, the features and attributes of the specific embodiments disclosed above may be combined in different ways to form additional embodiments, all of which fall within the scope of the present disclosure.

[0091] Although the present disclosure includes certain embodiments, examples and applications, it will be understood by those skilled in the art that the present disclosure extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses and obvious modifications and equivalents thereof, including embodiments which do not provide all of the features and advantages set forth herein. Accordingly, the scope of the present disclosure is not intended to be limited by the specific disclosures of preferred embodiments herein, and may be defined by claims as presented herein or as presented in the future.

WHAT IS CLAIMED IS:

1. A wound filler for use in treating a wound with negative pressure, comprising:

a porous wound filling material; and

a plurality of vertically extending members configured to extend vertically when the wound filler is positioned within a wound bed, the vertically extending members being made of a more rigid material than the porous wound filling material;

wherein upon application of negative pressure to the wound filler, the wound filler is configured to contract horizontally with the vertically extending members reducing vertical movement of the wound filler.

2. The wound filler of Claim 1, wherein the vertical extending members comprise one of struts, slabs, columns or tiles.

3. The wound filler of any one of the preceding claims, wherein the vertical extending members are elongate members configured to extend lengthwise across a wound bed and are aligned parallel to one another.

4. The wound filler of any one of the preceding claims, wherein the porous wound filling material surrounds the plurality of vertically extending members.

5. The wound filler of any one of the preceding claims, wherein the porous wound filling material extends between the plurality of vertically extending members.

6. The wound filler of any one of the preceding claims, wherein the porous wound filling material comprises a plurality of slits or areas in which a denser or more rigid struts or slabs are inserted.

7. The wound filler of any one of the preceding claims, wherein flexible material is positioned between the vertically extending members to allow compression of the vertically extending members towards each other in a horizontal plane when the wound filler is positioned within a wound bed and is placed under negative pressure.

8. The wound filler of any one of the preceding claims, wherein the plurality of vertically extending members are adhered to the porous wound filling material.

9. The wound filler of any one of the preceding claims, further comprising one or more draw strings or cords extending through the wound filler configured such that pulling of the draw strings will cause contracting of the wound filler in a horizontal plane.

10. A negative pressure wound therapy system, comprising:

the wound filler of any one of the preceding claims; and
a wound cover configured to be placed over the wound filler.

11. The system of Claim 10, further comprising a connection for connecting the wound cover to a source of negative pressure.

12. The system of Claim 10 or 11, further comprising a negative pressure source configured to be connected to the wound cover to provide negative pressure to the wound filler when placed within the wound bed.

13. A method of treating a wound, comprising:
positioning a wound filler of any one of Claims 1-9 into a wound bed;
covering the wound filler with a wound cover; and
applying negative pressure to the wound cover, wherein the application of negative pressure causes the wound filler to contract horizontally with the vertically extending members reducing vertical movement of the wound filler.




FIG. 1




FIG. 2A





FIG. 2B






FIG. 2D




FIG. 2E




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B

Fig. A1A




Fig. A1B




Fig. A1C




Fig. A2




Fig. A3





Fig. A4



Tubes within tubes positioned at the top of a wound filler. Prevents the filler from moving vertically but tubes will slide into each other allowing horizontal movement. Straws could be single with a concertina effect in the middle.

Fig. A5




Fig. A6




Fig. A7




Fig. A8




Fig. A9




Fig. A10




Fig. A11




Fig. A13A




Fig. A13B




Fig. A14




Fig. A15




Fig. A16




Fig. A17




Fig. A18





Fig. A19



INTERNATIONAL SEARCH REPORT

International application No PCT/IB2013/001555
--

A. CLASSIFICATION OF SUBJECT MATTER INV. A61F13/00 ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) A61F		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 10 2005 007016 A1 (FLEISCHMANN WILHELM [DE]) 24 August 2006 (2006-08-24) claims; figures 1-5 -----	1-13
X	US 2010/160876 A1 (ROBINSON TIMOTHY MARK [GB] ET AL) 24 June 2010 (2010-06-24) paragraphs [0006], [0032], [0055]; claims; figures 1,2,4a,5a, -----	1-7, 10-13
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents :		
"A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family	
Date of the actual completion of the international search	Date of mailing of the international search report	
27 August 2013	03/09/2013	
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Mirza, Anita	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/IB2013/001555

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 102005007016 A1	24-08-2006	AU 2005327845 A1	24-08-2006
		CN 101123930 A	13-02-2008
		DE 102005007016 A1	24-08-2006
		EP 1850818 A1	07-11-2007
		JP 5068181 B2	07-11-2012
		JP 2008529618 A	07-08-2008
		KR 20070114158 A	29-11-2007
		US 2008167593 A1	10-07-2008
		US 2013116635 A1	09-05-2013
		US 2013138054 A1	30-05-2013
		WO 2006087021 A1	24-08-2006

US 2010160876 A1	24-06-2010	AU 2009330210 A1	01-07-2010
		CA 2747743 A1	01-07-2010
		CN 102256637 A	23-11-2011
		EP 2367578 A2	28-09-2011
		JP 5229926 B2	03-07-2013
		JP 2012513826 A	21-06-2012
		KR 20110117108 A	26-10-2011
		RU 2011122965 A	27-01-2013
		SG 171796 A1	28-07-2011
		TW 201029696 A	16-08-2010
		US 2010160876 A1	24-06-2010
		WO 2010075180 A2	01-07-2010
