

(19) **DANMARK**



Patent- og
Varemærkestyrelsen

(10) **DK/EP 2894861 T3**

(12) **Oversættelse af
europæisk patentskrift**

- (51) Int.Cl.: **H 04 N 21/236 (2011.01)** **H 04 N 7/01 (2006.01)** **H 04 N 19/00 (2014.01)**
H 04 N 19/523 (2014.01) **H 04 N 19/587 (2014.01)** **H 04 N 19/59 (2014.01)**
H 04 N 19/70 (2014.01) **H 04 N 21/258 (2011.01)** **H 04 N 21/4402 (2011.01)**
- (45) Oversættelsen bekendtgjort den: **2020-02-10**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2020-01-01**
- (86) Europæisk ansøgning nr.: **13834928.7**
- (86) Europæisk indleveringsdag: **2013-09-02**
- (87) Den europæiske ansøgnings publiceringsdag: **2015-07-15**
- (86) International ansøgning nr.: **JP2013073576**
- (87) Internationalt publikationsnr.: **WO2014038522**
- (30) Prioritet: **2012-09-07 JP 2012197922**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Saturn Licensing LLC, 25 Madison Avenue, New York, NY 10022-3211, USA**
- (72) Opfinder: **TSUKAGOSHI, Ikuo, c/o SONY CORPORATION, 1-7-1 Konan, Minato-ku, Tokyo 108-0075, Japan**
- (74) Fuldmægtig i Danmark: **Plougmann Vingtoft A/S, Strandvejen 70, 2900 Hellerup, Danmark**
- (54) Benævnelse: **OVERFØRSELSINDRETNING, OVERFØRSELSFREMGANGSMÅDE, MODTAGEINDRETNING OG MODTAGEFREMGANGSMÅDE**
- (56) Fremdragne publikationer:
WO-A1-2012/017643
JP-A- 2005 130 313
JP-A- 2012 060 575
Wikipedia: "H.264/MPEG-4 AVC", , 29 August 2012 (2012-08-29), pages 1-10, XP055249926, Retrieved from the Internet: URL:https://en.wikipedia.org/w/index.php?title=H.264/MPEG-4_AVC&oldid=509814521 [retrieved on 2016-02-15]
SUGIO T ET AL: "Picture Adaptive 1/8-pel Motion Compensation Method", 6. JCT-VC MEETING; 97. MPEG MEETING; 14-7-2011 - 22-7-2011; TORINO; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16); URL: [HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/](http://wftp3.itu.int/av-arch/jctvc-site/),, no. JCTVC-F471, 1 July 2011 (2011-07-01), XP030009494,
ANONYMOUS: "The H.264 Advanced Video Compression Standard, 2nd Edition, chapter 10, Extensions and directions, Iain E. Richardson", NOT KNOWN,, 20 April 2010 (2010-04-20), XP030001641,
ANONYMOUS: "Text of ISO/IEC IS 14496-10:201X (7th edition)", 98. MPEG MEETING; 28-11-2011 - 2-12-2011; GENEVA; (MOTION PICTURE EXPERT GROUP OR ISO/IEC JTC1/SC29/WG11),, no. N12363, 2 February 2012 (2012-02-02), XP030018858,
'Operational Guidelines for Digital Terrestrial Television Broadcasting' ARIB TECHNICAL REPORT, ARIB TR-

Fortsættes ...

**B14, EDITION 4.9 vol. 1, no. 2/2, 03 July 2012, pages 3-44 - 3-46, XP008176645 Retrieved from the Internet:
<URL:http://www.arib.or.jp/english/html/overview/doc/4-TR-B14v4_9-1_p3-2.pdf> [retrieved on 2013-11-15]**

DESCRIPTION

TECHNICAL FIELD

[0001] The present technique relates to a transmission device, a transmitting method, a reception device, and a receiving method, particularly to the transmission device and the like which transmit image data of a spatial or temporal super-high-resolution image.

BACKGROUND ART

[0002] For example, in addition to a service for an HD image having valid pixels of 1920 × 1080, a service for a spatial super-high-resolution image such as 4K and 8K images respectively having two times and four times the valid pixels in horizontal and vertical directions (see Patent Document 1, for example) is proposed. Further, for example, in addition to a service for an image having a frame frequency of 30 Hz, a service for a temporal super-high-resolution image having a frame frequency such as 60 Hz and 120 Hz is proposed. Note that these services for the super-high-resolution images will be suitably referred to as super-high definition service.

[0003] Non-Patent Document 1 shows, according to its abstract, a picture adaptive 1/8-pel motion compensation method. In the proposed method, for P slice, 1/8-pel motion compensation is enabled and all reference pictures are referred using 1/8-pel motion vectors. On the other hand, for B slice, 1/8-pel motion compensation is enabled but all reference pictures are referred using 1/4-pel motion vector in order not to increase overhead to signal motion vector difference.

CITATION LIST

PATENT DOCUMENT

[0004] Patent Document 1: Japanese Patent Application Laid-Open No. 2011-057069

NON-PATENT DOCUMENT

[0005] Non-Patent Document 1: SUGIO T ET AL, "Picture Adaptive 1/8-pel Motion Compensation Method", 6. JCT-VC MEETING; 97. MPEG MEETING; 14-7-2011 - 22-7-2011; TORINO; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC

JTC1/SC29/WG11 AND ITU-T SG.16); URL: HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/, no. JCTVC-F471, XP030009494

SUMMARY OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0006] In the case where scalable coding is applied to image data of the above-described super-high definition service, image data having a resolution suitable to own display capability can be easily obtained even in a receiver not supporting the super-high definition service. However, in the case where scalable coding is not applied to the image data of the super-high definition service, the image data having the resolution suitable to own display capability can be hardly obtained in the receiver not supporting the super-high definition service.

[0007] An object of the present technique is to facilitate obtainment of image data having a resolution suitable to own display capability in a receiver not supporting a super-high definition service in the case where image data of the super-high definition service is transmitted without scalable coding.

SOLUTIONS TO PROBLEMS

[0008] The invention is defined in the appended claims.

[0009] According to an example of the present technique, a transmission device includes: a transmission unit configured to transmit a container in a predetermined format having a video stream including encoded image data; and an auxiliary information inserting unit configured to insert, into the video stream, auxiliary information for downscaling a spatial and/or temporal resolution of the image data.

[0010] According to the present technique, the container in the predetermined format having the video stream including the encoded image data is transmitted by the transmission unit. The encoded image data is, for example, the image data applied with encoding such as MPEG4-AVC(MVC), MPEG2 video, or HEVC. The container may be, for example, a transport stream (MPEG-2 TS) adopted in the digital broadcast standard. Further, the container may be, for example, the container in the MP4 format used in the Internet delivery or other formats.

[0011] The auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video stream by the auxiliary information inserting unit. For example, the auxiliary information may indicate a limit of accuracy for a motion vector included in the encoded image data. Also, for example, the auxiliary information may identify a picture to

be selected at the time of downscaling a temporal resolution at a predetermined ratio.

[0012] Thus, according to the present technique, the auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into video stream. Therefore, in the case where the image data of the super-high definition service is transmitted without scalable coding, image data having a resolution suitable to own display capability can be easily obtained in a receiver not supporting the super-high definition service

[0013] Meanwhile, according to the present technique, for example, an identifying information inserting unit configured to insert, into a layer of the container, identifying information indicating that the auxiliary information is inserted into the video stream may be further provided. In this case, the receiver can grasp that the auxiliary information is inserted into the video stream even without decoding the video stream, and the auxiliary information can be extracted appropriately.

[0014] For example, the identifying information may be added with downscaling information indicating an available ratio in downscaling the spatial and/or temporal resolution. Further, the identifying information may be added with spatial and/or temporal resolution information of the image data included in the video stream. Moreover, the container is a transport stream, for example, and the identifying information inserting unit may be configured to insert the identifying information into descriptor under a video elementary loop of a program map table included in the transport stream.

[0015] Furthermore, according to the present technique, for example, a resolution information inserting unit configured to insert, into a layer of the container, spatial and/or temporal resolution information of the image data included in the video stream may be further provided. In this case, contents of the downscaling processing can be determined based on the resolution information in the receiver not supporting the super-high definition service in the case where the image data of the super-high definition service is transmitted without scalable coding.

[0016] For example, the resolution information may be added with identifying information identifying whether the video stream is provided with support for a low performance decoder not supporting the spatial and/or temporal resolution of the image data. Further, the container is a transport stream, for example, and the resolution information inserting unit may be configured to insert the resolution information into descriptor under an event information table included in the transport stream.

[0017] Additionally, according to still another example of the present technique, a transmission device includes: a transmission unit configured to transmit a container in a predetermined format having a video stream including encoded image data; and an identifying information inserting unit configured to insert, into a layer of the container, identifying information such that a super-high definition service by the video stream can be identified at least per program basis.

[0018] According to the present technique, the container in the predetermined format having the video stream including the image data is transmitted by the transmission unit. The container may be, for example, a transport stream (MPEG-2 TS) adopted in the digital broadcast standard. Further, the container may be, for example, the container in the MP4 format used in the Internet delivery or other formats.

[0019] The identifying information is inserted into the layer of the container by the identifying information inserting unit such that the super-high definition service by the video stream can be identified at least per program basis. For example, the identifying information may be added with the spatial and/or temporal resolution information of the image data. The container is, for example, a transport stream, and the identifying information inserting unit may be configured to insert the identifying information into the descriptor under the event information table included in the transport stream.

[0020] Thus, according to the present technique, the identifying information is inserted into the layer of the container such that the super-high definition service by the video stream can be identified at least per program basis. Therefore, the receiver can easily identify the super-high definition service, and properly and instantly determine whether downscaling processing of the spatial and/or temporal resolution is needed and also a ratio thereof by making comparison with the own display capability.

[0021] Meanwhile, according to the present technique, the identifying information may be added with, for example, support information indicating whether the video stream is provided with support for a low performance decoder not supporting the spatial and/or temporal resolution of the image data. In this case, the receiver can easily determine whether the video stream is provided with the support for the low performance decoder, more specifically, determine whether the auxiliary information for downscaling the spatial and/or temporal resolution is inserted or the like.

[0022] Further, according to still another example of the present technique, a reception device includes: a receiving unit configured to receive a video stream including encoded image data; and a processing unit configured to apply downscaling processing of a spatial and/or temporal resolution to the encoded image data based on auxiliary information for downscaling the spatial and/or temporal resolution of the image data, and obtain display image data having a desired resolution, wherein the auxiliary information is inserted into the video stream.

[0023] According to the present technique, the video stream including the encoded image data is received by the receiving unit. The auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video stream. Further, the downscaling processing of the spatial and/or temporal resolution is applied to the encoded image data by the processing unit based on the auxiliary information, and the display image data having the desired resolution can be obtained.

[0024] Thus, according to the present technique, the downscaling processing of the spatial

and/or temporal resolution is applied to the encoded image data based on the auxiliary information inserted into the video stream, and the display image data having the desired resolution can be obtained. Therefore, a load of the downscaling processing can be reduced.

[0025] Meanwhile, according to the present technique, for example, the receiving unit may receive a container in the predetermined format including the video stream, the downscaling information indicating the available ratio in downscaling the spatial and/or temporal resolution may be inserted into the layer of the container, and the processing unit may control the downscaling processing in order to obtain the display image data based on the downscaling information.

[0026] Further, according to the present technique, for example, the receiving unit may receive the container in the predetermined format including the video stream, the spatial and/or temporal resolution information of the image data included in the video stream may be inserted into the layer of the container, and the processing unit may control the downscaling processing to obtain the display image data based on the resolution information.

EFFECTS OF THE INVENTION

[0027] According to the present technique, in the case where image data of super-high definition service is transmitted without scalable coding, image data having a resolution suitable to own display capability can be easily obtained in a receiver not supporting super-high definition service.

BRIEF DESCRIPTION OF DRAWINGS

[0028]

Fig. 1 is a block diagram illustrating an exemplary configuration of an image transmitting and receiving system as an embodiment.

Figs. 2(a) to 2(c) are explanatory diagrams for downscaling processing of a spatial resolution.

Fig. 3 is a block diagram illustrating an exemplary configuration of a decoder of a receiver.

Figs. 4(a) to 4(d) are explanatory diagrams for the downscaling processing of the spatial resolution.

Fig. 5 is an explanatory diagram for a case where there is no limit provided for accuracy of a motion vector MV, for example, in the case where accuracy of a motion vector MV1 is 1/4-pixel (quarter pixel) accuracy.

Fig. 6 is an explanatory diagram for a case where there is a limit provided to the accuracy of

the motion vector MV, for example, the case where a motion vector MV2 is provided with 1/2-pixel (half pixel) accuracy.

Figs. 7(a) to 7(c) are explanatory diagrams for the downscaling processing of a temporal resolution.

Fig. 8 is a block diagram illustrating an exemplary configuration of a transmitting data generation unit configured to generate a transport stream TS.

Figs. 9(a) to 9(b) are diagrams illustrating a head access unit of a GOP into which an SEI message is inserted as auxiliary information, and an access unit other than the head access unit.

Figs. 10(a) and 10(b) are diagrams illustrating exemplary structures (Syntax) of the SEI message (downscaling_spatial SEI message) each including information indicating a limit of accuracy for the motion vector MV as the auxiliary information.

Fig. 11 is a diagram illustrating contents of main information in the exemplary structure of the SEI message (downscaling_spatial SEI message).

Figs. 12(a) and 12(b) are diagrams illustrating exemplary structures (Syntax) of an SEI message (picture_temporal_pickup SEI message) each including information indicating a picture to be selected at the time of downscaling the temporal resolution at a predetermined ratio as the auxiliary information.

Fig. 13 is a diagram illustrating contents of main information in the exemplary structure of the SEI message (picture_temporal_pickup SEI message).

Fig. 14 is a diagram illustrating an exemplary structure (Syntax) of a downscaling descriptor (downscaling_descriptor).

Fig. 15 is a diagram illustrating a modified example of the structure (Syntax) of the downscaling descriptor (downscaling_descriptor).

Fig. 16 is a diagram illustrating contents of main information in the exemplary structure of the downscaling descriptor (downscaling_descriptor).

Fig. 17 is a diagram illustrating an exemplary structure (Syntax) of super high resolution descriptor.

Fig. 18 is a diagram illustrating contents of main information in the exemplary structure of the super high resolution descriptor.

Fig. 19 is a diagram illustrating an exemplary configuration of a transport stream TS.

Fig. 20 is a block diagram illustrating an exemplary configuration of the receiver.

MODE FOR CARRYING OUT THE INVENTION

[0029] In the following, a mode for carrying out the invention (hereinafter referred to as "embodiment") will be described. Note that a description will be provided in the following order.

1. Embodiment
2. Modified example

<1. Embodiment>

[Image Transmitting and Receiving System]

[0030] Fig. 1 is a diagram illustrating an exemplary configuration of an image transmitting and receiving system 10 as an embodiment. The image transmitting and receiving system 10 includes a broadcasting station 100 and a receiver 200. The broadcasting station 100 transmits a transport stream TS as a container through a broadcast wave.

[0031] The transport stream TS has a video stream including encoded image data. Transmission image data includes data corresponding to various kinds of imaging services. Examples of the imaging services may include, in addition to a service for a high definition (HD) image having valid pixels of 1920 × 1080, a service for a spatial super-high-resolution image such as 4K and 8K images respectively having two times and four times the valid pixels in horizontal and vertical directions (super-high definition service). Further, the examples of imaging services may include, in addition to an imaging service for an image having the frame frequency of 30 Hz, a service for a temporal super-high-resolution image having a frame frequency of such as 60 Hz and 120 Hz (super-high definition service).

[0032] With respect to image data of the super-high definition service, there are cases where: the image data is transmitted after scalable coding is applied; and the image data is transmitted without scalable coding. Backward compatibility is guaranteed by applying scalable coding to the image data, and the image data having a resolution suitable to own display capability can be easily obtained even in a receiver not supporting the super-high definition service.

[0033] In the case of transmitting the image data of the super-high definition service, auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into a video stream. The auxiliary information is inserted into a user data area of a picture header or a sequence header of the video stream, for example.

[0034] For example, the auxiliary information for downscaling the spatial resolution indicates a limit of accuracy for a motion vector included in the encoded image data. For example, when the limit of accuracy for a normal motion vector is $1/4$ pixel accuracy, the limit of accuracy for the motion vector is changed to, for example, $1/2$ pixel accuracy or 1 pixel accuracy in order to reduce a processing load for downscaling the spatial resolution on a receiver side.

[0035] Also, the auxiliary information for downscaling the temporal resolution identifies a picture to be selected at the time of downscaling the temporal resolution at the predetermined ratio. For example, a picture to be selected at the time of downscaling the resolution at the ratio of $1/2$ corresponds to every other picture (frame) is indicated by this information. Further, for example, the picture to be selected at the time of downscaling the resolution at the ratio of $1/4$ corresponds every four pictures (frames) is indicated by this information.

[0036] By inserting the auxiliary information as described above, the image data having the resolution suitable to the own display capability can be easily obtained in the receiver not supporting the super-high definition service in the case where the image data of the super-high definition service is transmitted without scalable coding. The details of the auxiliary information will be described later.

[0037] Further, the identifying information indicating that the auxiliary information is inserted into the video stream is inserted into a layer of the transport stream TS. For example, the identifying information is inserted under a video elementary loop (Video ES loop) of a program map table (PMT: Program Map Table) included in the transport stream TS. This identifying information enables the receiving side to find that the auxiliary information is inserted into the video stream although without decoding the video stream, and the auxiliary information can be appropriately extracted.

[0038] There may be a case where the above downscaling information is added with spatial and/or temporal resolution information of the image data included in the video stream. In this case, the receiving side can grasp the spatial and/or temporal resolution of the image data without decoding the video stream. The details of the downscaling information will be described later.

[0039] Further, the identifying information is inserted into the layer of the transport stream TS such that the super-high definition service by the video stream can be identified at least per program basis. For example, according to the present embodiment, the spatial and/or temporal resolution information of the image data included in the video stream is inserted into the layer of the transport stream TS. For example, the resolution information is inserted under an event information table (EIT: Event Information Table) included in the transport stream TS. By the resolution information (identifying information), the spatial and/or temporal resolution of the image data can be grasped without decoding the video stream.

[0040] The resolution information is added with identifying information identifying whether the video stream is provided with support for a low performance decoder not supporting the spatial

and/or temporal resolution of the image data. In this case, the receiving side can easily determine whether the video stream is provided with support for the low performance decoder, more specifically, whether the auxiliary information for downscaling the spatial and/or temporal resolution is inserted or the like. The details of the resolution information will be described later.

[0041] The receiver 200 receives the transport stream TS transmitted from the broadcasting station 100 through the broadcast wave. The transport stream TS has the video stream including the encoded image data. The receiver 200 executes decoding processing for the video stream and obtains display image data.

[0042] In the case where the image data of the super-high definition service is transmitted without scalable coding and the own display capability does not support the super-high definition service, the receiver 200 applies the downscaling processing of the spatial and/or temporal resolution to the encoded image data based on the auxiliary information, and obtains the display image data having a desired resolution. In this case, the downscaling processing is controlled by a resolution of received image data and an available ratio of downscaling.

[0043] For example, there may be a case where the display image data having the desired resolution cannot be obtained depending on the resolution of the received image data and the available ratio of downscaling, but in such a case, the downscaling processing is not executed. Further, in the case where there are plural available ratios of downscaling, the display image data having the desired resolution is obtained by selecting a downscaling ratio in accordance with the resolution of the received image data.

[Downscaling Processing of Resolution]

[0044] The downscaling processing executed at the receiver 200 will be described. First, the downscaling processing of a spatial resolution will be described. For example, consideration is given to a case where the received image data is image data of an 8K image as illustrated in Fig. 2(a). More specifically, the downscaling processing to reduce the spatial resolution to 1/2 in horizontal and vertical directions is applied at the receiver 200 which has display capability for a 4K image, and the image data of the 4K image can be obtained as illustrated in Fig. 2(b). Also, for example, the downscaling processing to reduce the spatial resolution to 1/4 in horizontal and vertical directions is applied at the receiver 200 which has the display capability for HD image, and the image data of HD image can be obtained as illustrated in Fig. 2(c).

[0045] Fig. 3 is a diagram illustrating an exemplary configuration of a decoder of the receiver 200. Entropy decoding processing is applied to received encoded image data V_e at an entropy decoding unit 353a, and inverse quantization processing is applied at an inverse quantization unit 353b. Further, space-frequency inverse conversion processing is applied at a space-frequency inverse conversion unit 353c to the data applied with the inverse quantization processing, and data $D(n)$ is obtained.

[0046] In this case, the space-frequency inverse conversion processing is applied only to a frequency component in an area corresponding to the downscaling ratio per $N \times N$ encoded block (see a hatching area in Fig. 4(a), and downsampled image data is obtained as the data $D(n)$. Note that the example in Fig. 4 is the case where the downscaling ratio is $1/2$.

[0047] Pixel data in an area corresponding to a motion vector MV is read out from image data in a previous frame recorded in a frame buffer 353d per encoded block (see Fig. 4(b), and supplied to an interpolation filter 353e and interpolation arithmetic operation is executed to generate a predicted block after interpolation (see Fig. 4(c)). Further, in an adder 353f, the predicted block after interpolation generated at the interpolation filter 353e is added to the data $D(n)$ (see Fig. 4(d)), and downsampled image data $Vd(n)$ in a current frame can be obtained.

[0048] Here, pixel accuracy for the motion vector MV added to the encoded image data Ve is defined as P . For example, in the case of executing reduction decoding to $1/2$ at the space-frequency inverse conversion unit 353c, the pixel accuracy becomes rougher, namely, $1/2$, compared to the original accuracy P . In order to execute motion compensation with the pixel accuracy P for the original motion vector MV , the image data at the frame buffer 353d is needed to be interpolated so as to conform to the pixel accuracy P .

[0049] For example, in the case where the original motion vector MV is encoded with $1/4$ pixel accuracy, the accuracy at the time of applying the motion compensation to the image data that has been applied with reduction decoding and stored in the frame buffer 353d is reduced to $1/2$ pixel accuracy of the image data. Therefore, the image data in the frame buffer 353d is needed to be interpolated to $1/(1/4 \times 1/2)$ in order to execute the motion compensation with the accuracy of the original motion vector MV .

[0050] Therefore, in the case where there is no limit provided for the accuracy of the motion vector MV , a range of a predicted pixel to be a target of the arithmetic operation of the interpolation filter becomes large and the number of taps of the interpolation filter is increased. As a result, a load of the arithmetic operation is increased. In contrast, in the case where there is a limit provided for the accuracy of the motion vector MV , the range of the predicted pixel to be the target of the arithmetic operation of the interpolation filter becomes small and the number of taps of the interpolation filter is reduced. As a result, the load of the arithmetic operation is reduced.

[0051] Fig. 5 is a diagram illustrating a case where there is no limit provided for the accuracy of the motion vector MV , more specifically, the case where the accuracy of the motion vector $MV1$ is $1/4$ -pixel (quarter pixel) accuracy. In this case, the filter arithmetic operation corresponding to the number of phases enough to cover the accuracy of the $MV1$ is needed to be executed in order to obtain an interpolation pixel from among adjacent predicted pixels. In the case of executing the interpolation arithmetic operation by using a low-pass filter, the number of filter taps of the interpolation filter is increased and accordingly the number of predicted pixels to be the targets is increased in order to secure a passband higher than a

certain level and make a vicinity of cutoff frequency steep.

[0052] Fig. 6 is a diagram illustrating a case where there is the limit provided for the accuracy of the motion vector MV, more specifically, the case where accuracy of a motion vector MV2 is 1/2-pixel (half pixel) accuracy. In this case, the filter arithmetic operation corresponding to the number of phases enough to cover the accuracy of the MV2 is needed to be executed in order to obtain the interpolation pixel from among the adjacent predicted pixels. Since the accuracy of the MV2 is rougher than the accuracy of the MV1, the number of phases becomes reduced. In this case, compared to the above case where no limit is provided, the less number of taps of the interpolation filter and the less number of predicted pixels to be the targets are needed in order to secure equivalent passing.

[0053] Judging from this, according to the present embodiment, encoding is executed by suitably providing the limit of accuracy for the motion vector MV in a transmitting side, like the above-described motion vector MV2. In this case, according to the present embodiment, information related to the limit of accuracy for the motion vector MV is inserted into the video stream as the auxiliary information. The receiver 200 recognizes the limit of accuracy of the motion vector MV from the auxiliary information at the time of executing the downscaling processing of the spatial resolution, and can perform the interpolation processing conforming to the limit of accuracy. As a result, the processing load can be reduced.

[0054] Next, the downscaling processing of the temporal resolution will be described. For example, consideration is given to a case where the received image data is image data of 120 fps as illustrated in Fig. 7(a). A half picture rate flag and a quarter picture rate flag are inserted into a video stream as the auxiliary information.

[0055] The half picture rate flag is "1" at every other picture (frame). In other words, the picture to be selected can be identified by the half picture rate flag at the time of downscaling the temporal resolution to 1/2. Further, the quarter picture rate flag is "1" at every three pictures (frames). In other words, the picture to be selected can be identified by the quarter picture rate flag at the time of downscaling the temporal resolution to 1/4.

[0056] For example, in the receiver 200 having the display capability for an image of 60 fps, only every other picture is picked out and decoded to obtain the image data of the image of 60 fps based on the half picture rate flag as illustrated in Fig. 7(b). Further, for example, in the receiver 200 having the display capability for an image of 30 fps, every four pictures is picked out and decoded to obtain the image data of the image of 30 fps based on the quarter picture rate flag as illustrated in Fig. 7(c).

[Exemplary Configuration of Transmitting Data Generation Unit]

[0057] Fig. 8 is an exemplary configuration of a transmitting data generation unit 110 configured to generate the above-described transport stream TS in the broadcasting station

100. The transmitting data generation unit 110 includes an image data output unit 111, a video encoder 112, an audio data output unit 115, an audio encoder 116, and a multiplexer 117.

[0058] The image data output unit 111 outputs image data corresponding to various kinds of imaging services. The examples of the imaging services may include, in addition to the service for a high definition (HD) image having valid pixels of 1920×1080 , the service for the spatial super-high-resolution image such as 4K and 8K images respectively having two times and four times the valid pixels in horizontal and vertical directions (super-high definition service). Further, the examples of imaging services may include, in addition to the imaging service for the image having the frame frequency of 30 Hz, the service for the temporal super-high-resolution image having the frame frequency of such as 60 Hz and 120 Hz (super-high definition service). The image data output unit 111 is formed of, for example, a camera configured to capture an image of an object and output image data thereof, or an image data reading unit configured to read image data from a storage medium and output image data thereof.

[0059] The video encoder 112 applies encoding, such as MPEG4-AVC (MVC), MPEG2 video, or HEVC, to the image data output from the image data output unit 111, and obtains encoded image data. Further, the video encoder 112 generates a video stream (video elementary stream) including the encoded image data by a stream formatter (not illustrated) disposed at a later stage.

[0060] In this case, for example, there may be a case where image data of the super-high definition service is applied with scalable coding in order to guarantee backward compatibility while there also may be a case where the image data is not applied with scalable coding. In the case where the image data is not applied with scalable coding, the video encoder 112 inserts, into the video stream, the auxiliary information for downscaling the spatial and/or temporal resolution for convenience of the receiver not supporting the super-high definition service.

[0061] The audio data output unit 115 outputs audio data corresponding to the image data. The audio data output unit 115 is formed of, for example, a microphone or an audio data reading unit configured to read out audio data from a storage medium and output the audio data. The audio encoder 116 applies encoding, such as MPEG-2 Audio and AAC, to the audio data output from the audio data output unit 115, and generates an audio stream (audio elementary stream).

[0062] The multiplexer 117 packetizes and multiplexes each of the elementary streams generated at the video encoder 112, a graphics encoder 114 and the audio encoder 116, and generates a transport stream TS. In this case, a PTS (Presentation Time Stamp) is inserted into a header of each PES (Packetized Elementary Stream) for synchronous reproduction on the receiving side.

[0063] The multiplexer 117 inserts, into a layer of the transport stream TS, the downscaling information indicating the spatial and/or temporal downscaling at an available ratio in the case

where the image data of the super-high definition service is transmitted without scalable coding. More specifically, the downscaling information is inserted under the video elementary loop (Video ES loop) of the program map table (PMT: Program Map Table) included in the transport stream TS.

[0064] Additionally, the multiplexer 117 inserts the identifying information into the layer of the transport stream TS such that the super-high definition service by the video stream can be identified at least per program basis. For example, according to the present embodiment, the multiplexer 117 inserts, into the layer of the transport stream TS, the spatial and/or temporal resolution information of the image data included in the video stream. More specifically, the resolution information is inserted under the event information table (EIT: Event Information Table) included in the transport stream TS.

[0065] Operation of the transmitting data generation unit 110 illustrated in Fig. 8 will be briefly described. The image data corresponding to the various kinds of image services output from the image data output unit 111 is supplied to the video encoder 112. In the video encoder 112, encoding such as MPEG4-AVC (MVC), MPEG2 video, or HEVC is applied to the image data, and the video stream (video elementary stream) including the encoded image data is generated. The video stream is supplied to the multiplexer 117.

[0066] In this case, for example, there may be a case where image data of the super-high definition service is applied with scalable coding in order to guarantee backward compatibility while there also may be a case where the image data is not applied with scalable coding. In the video encoder 112, in the case where scalable coding is not applied, the auxiliary information for downscaling the spatial and/or temporal resolution is inserted into the video stream for convenience of the receiver not supporting the super-high definition service.

[0067] The audio data corresponding to the image data and output from the audio data output unit 115 is supplied to the audio encoder 116. In the audio encoder 116, encoding such as MPEG-2 Audio and AAC is applied to the audio data, and the audio stream (audio elementary stream) is generated. The audio stream is supplied to the multiplexer 117.

[0068] In the multiplexer 117, the elementary stream supplied from each encoder is packetized and multiplexed, and the transport stream TS is generated. In this case, the PTS is inserted into the header of each PES for synchronous reproduction on the receiving side. Further, in the multiplexer 117, the downscaling information indicating the spatial and/or temporal downscaling at the available ratio is inserted under the video elementary loop (Video ES loop) of the PMT. Furthermore, in the multiplexer 117, the spatial and/or temporal resolution information of the image data included in the video stream is inserted under the resolution EIT.

[Configurations of Auxiliary Information, Identifying Information, and Resolution Information, and TS Structure]

[0069] As described above, the auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video stream. For example, in the case where an encoding method is MPEG4-AVC or in the case of an encoding type in which a coding structure of an NAL packet or the like is similar such as HEVC, the auxiliary information is inserted into an "SEIs" section of an access unit (AU) as an SEI message.

[0070] In this case, the information as the auxiliary information indicating the limit of accuracy for the motion vector MV is inserted as an SEI message (downscaling_spatial SEI message). Further, the information as the auxiliary information indicating the picture to be selected at the time of downscaling the temporal resolution at the predetermined ratio is inserted as an SEI message (picture_temporal_pickup SEI message). Fig. 9 (a) is a diagram illustrating a head access unit of a GOP (Group Of Picture), and Fig. 9(b) is a diagram illustrating an access unit other than the head access unit of the GOP. The SEI message is encoded at an earlier position on a bit stream than slices where the pixel data is encoded, and therefore, the receiver identifies the SEI contents, thereby achieving to determine subsequent decoding processing.

[0071] Fig. 10(a) is a diagram illustrating an exemplary structure (Syntax) of the "downscaling_spatial SEI message". "uuid_iso_iec_11578" has an UUID value specified in "ISO/IEC 11578:1996 Annex A.". In a field of "user_data_payload_byte", "userdata_for_downscaling_spatial()" is inserted. Fig. 10(b) is a diagram illustrating an exemplary structure (Syntax) of the "userdata_for_downscaling_spatial()". A flag of "constrained_to_half_pixel_MV_flag" and a flag of "constrained_to_integer_pixel_MV_flag" are included in this structure. "userdata_id" is an identifier represented by unsigned 16 bits.

[0072] When the flag "constrained_to_half_pixel_MV_flag" is "1" as illustrated in Fig. 11, it is indicated that the accuracy of the motion vector MV is limited to 1/2 pixel accuracy. Further, when the "constrained_to_integer_pixel_MV_flag" is "1" as illustrated in Fig. 11, it is indicated that the accuracy of the motion vector MV is limited to integer pixel accuracy.

[0073] Fig. 12(a) is an exemplary structure (Syntax) of the "picture_temporal_pickup SEI message". The "uuid_iso_iec_11578" includes the UUID value specified in "ISO/IEC 11578:1996 Annex A.". In the field of "user_data_payload_byte", the "userdata_for_picture_temporal()" is inserted. Fig. 12(b) is an exemplary structure (Syntax) of the "userdata_for_picture_temporal()". A flag of the "half picture rate flag" and a flag of the "quarter picture rate flag" are included in this structure. The "userdata_id" is an identifier represented by unsigned 16 bits.

[0074] When the flag of "half picture rate flag" is "1" as illustrated in Fig. 13, it is indicated that a picture is to be picked out and decoded by a decoder having the display capability for a 1/2 temporal resolution. Further, when the flag of "quarter picture rate flag" is "1" as illustrated in Fig. 13, it is indicated that a picture is to be picked out and decoded by a decoder having the display capability for a 1/4 temporal resolution.

[0075] Additionally, as described above, for example, the identifying information indicating that

the auxiliary information for downscaling the above-described spatial and/or temporal resolution of the image data is inserted into the video stream under the video elementary loop (Video ES loop) of the program map table (PMT) in the transport stream TS.

[0076] Fig. 14 is a diagram illustrating an exemplary structure (Syntax) of downscaling descriptor (downscaling_descriptor) as the identifying information. Further, Fig. 15 is a diagram illustrating a modified example of the structure (Syntax) of the downscaling descriptor (downscaling_descriptor). Fig. 16 is a diagram illustrating contents of main information (Semantics) in these exemplary structures.

[0077] An 8-bit field of "downscaling_descriptor_tag" indicates a descriptor type, and here indicates the downscaling descriptor. An 8-bit field of "downscaling_descriptor_length" indicates a length (size) of the descriptor and indicates the number of subsequent bytes as the length of the descriptor.

[0078] A 2-bit field of "downscaling_type" indicates a downscaling type. For example, "01" indicates the temporal resolution downscaling, "10" indicates the spatial resolution downscaling, and "11" indicates the temporal and spatial resolution downscaling.

[0079] When the "downscaling_type" is "01" and "11", the 2-bit field of "temporal_downscaling_factor" becomes effective. The 2-bit field indicates an available ratio (downscale) in downscaling the temporal resolution. For example, "00" indicates that downscaling cannot be executed. Further, "01" indicates that downscaling at the ratio of 1/2 can be executed. "10" indicates that downscaling at the ratio of 1/4 can be executed, and also indicates that downscaling at the ratio of 1/2 can be also executed. Additionally, when "temporal_downscaling_factor" is "01" and "10", it is also indicated that the auxiliary information for downscaling the temporal resolution is inserted into the video stream.

[0080] Further, when the "downscaling_type" is "10" and "11", a 2-bit field of "spatial_downscaling_factor" becomes effective. The 2-bit field indicates the available ratio (downscale) in downscaling the spatial resolution. For example, "00" indicates that downscaling cannot be executed. Further, "01" indicates that downscaling can be executed horizontally and vertically at the ratio of 1/2. "10" indicates that downscaling can be executed horizontally and vertically at the ratio of 1/4 and also indicates that downscaling can be executed at the ratio of 1/2. Additionally, when the "spatial_downscaling_factor" is "01" and "10", it is indicated that the auxiliary information for downscaling the spatial resolution is inserted into the video stream.

[0081] A 3-bit field of "spatial resolution class type" indicates a class type of the spatial resolution of the transmission image data. For example, "001" indicates 1920 × 1080, namely, the HD resolution. Further, for example, "010" indicates 3840 × 2160, namely, the 4K resolution. Additionally, for example, "011" indicates 7680 × 4320, namely, 8K resolution.

[0082] A 3-bit field of "temporal resolution class type" indicates a class type of the temporal resolution of the transmission image data. For example, "001" indicates 24 Hz, 25 Hz, 29.97

Hz, 30 Hz, etc., "010" indicates 50 Hz, 59.94 Hz, 60 Hz, etc., "011" indicates 100 Hz, 120 Hz, etc., and "100" indicates 200 Hz, 240 Hz, etc.

[0083] Further, as described above, for example, the spatial and/or temporal resolution information of the image data included in the video stream is inserted under the event information table (EIT) of the transport stream TS. Fig. 17 is an exemplary structure (Syntax) of a Super High resolution descriptor as the resolution information. Further, Fig. 18 is a diagram illustrating contents of main information (Semantics) in the exemplary structure.

[0084] A 3-bit field of the "Spatial resolution class type" indicates a class type of the spatial resolution of the transmission image data. For example, "001" indicates 1920 × 1080, namely, the HD resolution. Further, for example, "010" indicates 3840 × 2160, namely, the 4K resolution. Additionally, for example, "011" indicates 7680 × 4320, namely, the 8K resolution.

[0085] A 3-bit field of "Temporal resolution class type" indicates a class type of the temporal resolution of the transmission image data. For example, "001" indicates 24 Hz, 25 Hz, 29.97 Hz, 30 Hz, etc., "010" indicates 50 Hz, 59.94 Hz, 60 Hz, etc., "011" indicates 100 Hz, 120 Hz, etc., and "100" indicates 200 Hz, 240 Hz, etc.

[0086] A 2-bit field of "Backward_compatible_type" indicates whether backward compatibility is guaranteed with respect to the transmission image data. For example, "00" indicates that backward compatibility is not guaranteed. "01" indicates that backward compatibility is guaranteed with respect to the spatial resolution. In this case, the transmission image data is applied with scalable coding with respect to the spatial resolution, for example. "10" indicates that backward compatibility is guaranteed with respect to the temporal resolution. In this case, the transmission image data is applied with scalable coding with respect to the temporal resolution, for example.

[0087] The flag information of "lower_capable_decoder_support_flag" indicates whether support is provided for the low performance decoder not supporting the spatial and/or temporal resolution of the transmission image data. For example, "0" indicates that support is not provided. "1" indicates that support is provided. For example, as described above, in the case where the auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video stream, the flag information becomes "1".

[0088] Fig. 19 is a diagram illustrating an exemplary configuration of the transport stream TS. The transport stream TS includes a PES packet "PID1:video PES1" of the video elementary stream and a PES packet "PID2: Audio PES1" of the audio elementary stream. The auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video elementary stream as the SEI message.

[0089] In this case, the information as the auxiliary information indicating the limit of accuracy for the motion vector MV is inserted as the SEI message (downscaling_spatial SEI message) (see Fig. 10). Further, the information as the auxiliary information indicating the picture to be

selected at the time of downscaling the temporal resolution at the predetermined ratio is inserted as the SEI message (picture_temporal_pickup SEI message) (see Fig. 12).

[0090] Further, the transport stream TS includes the PMT (Program Map Table) as the PSI (Program Specific Information). The PSI indicates which program each elementary stream included in the transport stream belongs to. Further, the transport stream TS includes the EIT (Event Information Table) as SI (Serviced Information) to execute control per event (program) basis.

[0091] The elementary loop having information related to each elementary stream exists in the PMT. In the exemplary structure, the video elementary loop (Video ES loop) exists. In the video elementary loop, information such as a stream type and a packet identifier (PID) is disposed corresponding to one video elementary stream described above, and also the descriptor describing information related to the video elementary stream thereof is disposed as well.

[0092] The downscaling descriptor (downscaling_descriptor) is inserted under the video elementary loop (Video ES loop) of the PMT (see Fig. 14). The descriptor indicates, as described above, that the auxiliary information for downscaling the spatial and/or temporal resolution of the image data is inserted into the video stream.

[0093] Further, the Super High resolution descriptor under the EIT (see Fig. 17). The descriptor forms the identifying information identifying the super-high definition service by the video stream at least per program basis as described above. More specifically, the descriptor includes the spatial and/or temporal resolution information of the transmission image data.

[Exemplary Configuration of Receiver]

[0094] Fig. 20 is a diagram illustrating an exemplary configuration of the receiver 200. The receiver 200 includes a CPU 201, a flash ROM 202, a DRAM 203, an internal bus 204, a remote control receiving unit (RC receiving unit) 205, and a remote control transmitter (RC transmitter) 206.

[0095] Further, the receiver 200 includes an antenna terminal 211, a digital tuner 212, a transport stream buffer (TS buffer) 213, and a demultiplexer 214. Further, the receiver 200 includes a coded buffer 215, a video decoder 216, a decoded buffer 217, a video RAM 218, a coded buffer 241, an audio decoder 242, and a channel mixing unit 243.

[0096] The CPU 201 controls operation of the respective units in the receiver 200. The flash ROM 202 stores control software and maintains data. The DRAM 203 constitutes a work area of the CPU 201. The CPU 201 develops, on the DRAM 203, software and data read from the flash ROM 202 and starts up the software to control the respective units in the receiver 200. The RC transmitter 205 receives a remote control signal (remote control code) transmitted from the RC transmitter 206, and supplies the same to the CPU 201. The CPU 201 controls the

respective units in the receiver 200 based on the remote control code. The CPU 201, flash ROM 202, and DRAM 203 are mutually connected via the internal bus 204.

[0097] The antenna terminal 211 is a terminal to input a television broadcast signal received by a receiving antenna (not illustrated). The digital tuner 212 processes the television broadcast signal received at the antenna terminal 211, and outputs a predetermined transport stream TS corresponding to a user's selected channel. The transport stream buffer (TS buffer) 213 temporarily stores the transport stream TS output from the digital tuner 212. The transport stream TS includes the video elementary stream and the audio elementary stream.

[0098] The demultiplexer 214 extracts each one of the video and audio streams (elementary stream) from the transport stream TS temporarily stored in the TS buffer 213. Further, the demultiplexer 214 extracts the above-described downscaling descriptor (downscaling_descriptor) and Super High resolution descriptor from the transport stream TS and transmits these descriptor to the CPU 201.

[0099] The CPU 201 can grasp, from the Super High resolution descriptor, the spatial and temporal resolution information of the received image data, also the information regarding whether the received image data has backward compatibility, and the information regarding whether the received image data is provided with the support for the low performance decoder. Additionally, the CPU 201 can grasp, from the downscaling descriptor, the information regarding whether the auxiliary information for downscaling processing of the spatial and/or temporal resolution is inserted into the video stream and also the information regarding the available ratio in downscaling the spatial and/or temporal resolution.

[0100] The CPU 201 controls processing such as decoding in the receiver 200 based on these grasped information. For example, in the case where the image data for the super-high definition service unsupported by the own display capability is received and scalable coding is not applied to the image data, the CPU 201 executes the downscaling processing of the spatial and/or temporal resolution based on the auxiliary information inserted into the video stream and executes control such that display image data having a desired resolution can be obtained.

[0101] The coded buffer 215 temporarily stores the video elementary stream extracted at the demultiplexer 214. The video decoder 216 applies the decoding processing to the video stream stored in the coded buffer 215 under control of the CPU 201, and obtains the display image data. Note that there may be a case where downscaling processing of the spatial and/or temporal resolution cannot be executed and the display image data having the resolution suitable to the own display capability cannot be obtained depending on the contents of the received image data.

[0102] Further, the video decoder 216 extracts the SEI message inserted into the video stream, and transmits the same to the CPU 201. The SEI message also includes the "downscaling_spatial SEI message" and "picture_temporal_pickup SEI message". In the case

where downscaling processing of the spatial and/or temporal resolution is executed at the video decoder 216, the CPU 201 causes the downscaling processing to be executed based on the auxiliary information included in the SEI message.

[0103] More specifically, in the case of executing the downscaling processing of the spatial resolution, the downscaling processing is executed based on the information related to the limit of accuracy for the motion vector MV included in the SEI message "downscaling_spatial SEI message", thereby reducing the processing load. On the other hand, in the case of executing the downscaling processing of the temporal resolution, the downscaling processing is executed based on the information related to the selected picture according to the ratio included in the SEI message "picture_temporal_pickup SEI message", thereby reducing the processing load.

[0104] The decoded buffer 217 temporarily stores the display image data obtained at the video decoder 216. The video RAM 218 imports the display image data stored in the decoded buffer 217, and outputs the image data to a display at an appropriate timing.

[0105] The coded buffer 241 temporarily stores the audio stream extracted at the demultiplexer 214. The audio decoder 242 applies the decoding processing to the audio stream stored in the coded buffer 241 and obtains decoded audio data. With respect to the audio data obtained at the audio decoder 242, the channel mixing unit 243 obtains audio data for each channel in order to implement, for example, 5.1ch sound, and then supplies the audio data to a speaker.

[0106] Operation of the receiver 200 will be described. The television broadcast signal received at the antenna terminal 211 is supplied to the digital tuner 212. In the digital tuner 212, the television broadcast signal is processed, and a predetermined transport stream TS corresponding to a channel selected by a user is output. The transport stream TS is temporarily stored at the TS buffer 213. The transport stream TS includes the video elementary stream and the audio elementary stream.

[0107] In the demultiplexer 214, each of the video and audio streams (elementary stream) is extracted from the transport stream TS temporarily stored at the TS buffer 213. Further, in the demultiplexer 214, the downscaling descriptor (downscaling_descriptor) and Super High resolution descriptor are extracted from the transport stream TS, and transmitted to the CPU 201. In the CPU 201, the processing such as decoding executed at the receiver 200 is controlled based on the information included in these descriptors.

[0108] The video stream extracted at the demultiplexer 214 is supplied to the coded buffer 215 and temporarily stored. In the video decoder 216, the decoding processing is applied to the video stream stored in the coded buffer 215 under control of the CPU 201, and the display image data suitable to the own display capability can be obtained.

[0109] In this case, in the video decoder 216, the SEI message including "downscaling_spatial SEI message", "picture_temporal_pickup SEI message", etc. inserted into a basic video stream

is extracted and transmitted to the CPU 201. In the CPU 201, in the case where the downscaling processing of the spatial and/or temporal resolution is executed at the video decoder 216, the downscaling processing is executed based on the auxiliary information included in the SEI message.

[0110] The display image data obtained at the video decoder 216 is temporarily stored in the decoded buffer 217. After that, in the video RAM 218, the display image data stored in the decoded buffer 217 is imported and then output to the display at the appropriate timing. In this manner, the image is displayed on the display.

[0111] Further, the audio stream extracted at the demultiplexer 214 is supplied to the coded buffer 241 and temporarily stored. In the audio decoder 242, the decoding processing is applied to the audio stream stored in the coded buffer 241, and the decoded audio data is obtained. The audio data is supplied to the channel mixing unit 243. In the channel mixing unit 243, for example, the audio data for each channel to achieve 5.1ch sound is generated with respect to the audio data. The audio data is supplied to, for example, the speaker, and audio is output in accordance with the image display.

[0112] As described above, according to the image transmitting and receiving system 10 illustrated in Fig. 1, transmission is executed upon inserting the auxiliary information for downscaling the spatial and/or temporal resolution of the image data into the video stream. Therefore, in the case where the image data of the super-high definition service is transmitted without scalable coding, the image data having the resolution suitable to the own display capability can be easily obtained even in the receiver 200 not supporting the super-high definition service.

<2. Modified Example>

[0113] Note that, in the above-described embodiment, the example in which a container is a transport stream (MPEG-2 TS) has been described. However, the present technique is applicable to a system having a configuration in which delivery is carried out to a receiving terminal by utilizing a network such as the Internet. In the case of the Internet delivery, delivery is carried out mostly by the container in the MP4 format or other formats. In other words, the containers in various kinds of formats, such as the transport stream (MPEG-2 TS) adopted in the digital broadcasting standard and the MP4 format used in the Internet delivery are applicable as the container.

REFERENCE SIGNS LIST

[0114]

	Image transmitting and receiving system
100	Broadcasting station
110	Transmitting data generation unit
111	Image data output unit
112	Video encoder
115	Audio data output unit
116	Audio encoder
117	Multiplexer
200	Receiver
201	CPU
212	Digital tuner
213	Transport stream buffer (TS buffer)
214	Demultiplexer
215	Coded buffer
216	Video decoder
217	Decoded buffer
218	Video RAM
241	Coded buffer
242	Audio decoder
243	Channel mixing unit

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JF2011057069A [0004]

Non-patent literature cited in the description

- **SUGIO T et al.**Picture Adaptive 1/8-pel Motion Compensation Method6. JCT-VC MEETING; 97. MPEG MEETING; 14-7-2011 - 22-7-2011; TORINO; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16), [0005]

Patentkrav

1. Overførselsindretning omfattende:

- en overførselsenhed konfigureret til at overføre en transportstrøm i et forudbestemt format, idet transportstrømmen omfatter en
- 5 videoelementærstrøm inklusive kodet billeddata, en hændelsesinformationstabel, og en programafbildningstabel; og en hjælpeinformationsindsættelsesenhed konfigureret til at indsætte rumlig hjælpeinformation i videoelementærstrømmen som en supplerende udvidelsesinformation, SEI, meddelelse,
- 10 **kendetegnet ved at** rumlig nedskaleringsinformation, der indikerer et tilgængeligt forhold i nedskalering af den rumlige opløsning, indsættes under en videoelementærsløjfe af programafbildningstabellen, hvor overførselsindretningen yderligere omfatter en opløsningsinformationsindsættelsesenhed konfigureret til at indsætte
- 15 rumlig opløsningsinformation af det kodede billeddata under hændelsesinformationstabellen, hvor den rumlige hjælpeinformation indikerer en nøjagtighedsbegrænsning for en bevægelsesvektor inkluderet i det kodede billeddata ved at indikere, at nøjagtighedsbegrænsningen er variabel fra 1/4 pixelnøjagtighed til 1/2
- 20 pixelnøjagtighed eller 1 pixelnøjagtighed hvor det kodede billeddata overføres uden skalerbar kodning.

2. Overførselsindretning ifølge krav 1, hvor

- 25 hjælpeinformationsindsættelsesenheden er konfigureret til at indsætte, i videoelementærstrømmen, tidsmæssig hjælpeinformation, der identificerer et billede, der skal vælges ved tidspunktet for nedskaleringen af en tidsmæssig opløsning ved et forudbestemt forhold.

30 3. Overførselsindretning ifølge krav 2, hvor

- opløsningsinformationsindsættelsesenheden er konfigureret til at indsætte, under hændelsesinformationstabellen, tidsmæssig opløsningsinformation af det kodede billeddata, og hvor tidsmæssig nedskaleringsinformation, der indikerer et tilgængeligt forhold i

nedskalering af den tidsmæssige opløsning, indsættes under videoelementærsløjfen af programafbildningstabellen.

4. Overførselsindretning ifølge et hvilket som helst af kravene 1 til 3, yderligere omfattende en identifikationsinformationsindsættelsesenhed konfigureret til at indsætte, under videoelementærsløjfen af programafbildningstabellen, identifikationsinformation, der indikerer, at den rumlige og/eller den tidsmæssige hjælpeinformation indsættes i videostrømmen.

10 5. Overførselsindretning ifølge krav 4, hvor den rumlige og/eller den tidsmæssige nedskaleringsinformation tilføjes til identifikationsinformationen.

6. Overførselsindretning ifølge krav 4 eller 5, hvor identifikationsinformationsindsættelsesenheden indsætter 15 identifikationsinformationen i en deskriptor under videoelementærsløjfen af programafbildningstabellen.

7. Overførselsfremgangsmåde omfattende trinnene:
at overføre en transportstrøm i et forudbestemt format idet
20 transportstrømmen omfatter en videoelementærstrøm inklusive kodet billeddata, en hændelsesinformationstabel og en programafbildningstabel;
og
at indsætte rumlig hjælpeinformation i videoelementærstrømmen som en supplerende udvidelsesinformation, SEI, meddelelse,
25 **kendetegnet ved at** overførselsfremgangsmåden yderligere omfatter:
at indsætte rumlig nedskaleringsinformation, der indikerer et tilgængeligt forhold i nedskalering af den rumlige opløsning under en videoelementærsløjfe af programafbildningstabellen; og
at indsætte rumlig opløsningsinformation af det kodede billeddata under
30 hændelsesinformationstabellen,
hvor den rumlige hjælpeinformation indikerer en nøjagtighedsbegrænsning for en bevægelsesvektor inkluderet i det kodede billeddata ved at indikere, at nøjagtighedsbegrænsningen er variabel fra 1/4 pixelnøjagtighed til 1/2 pixelnøjagtighed eller 1 pixelnøjagtighed,
35 hvor det kodede billeddata overføres uden skalerbar kodning.

8. Modtagerindretning omfattende:

- 5 en modtageenhed konfigureret til at modtage en transportstrøm i et forudbestemt format, idet transportstrømmen omfatter en videoelementærstrøm inklusive kodet billeddata og rumlig hjælpeinformation, en hændelsesinformationstabel, og en programafbildningstabel, idet den rumlige hjælpeinformation tilvejebringes som en supplerende udvidelsesinformation, SEI, meddelelse i videoelementærstrømmen; og
- 10 en behandlingsenhed konfigureret til at anvende nedskaleringsbehandling af en rumlig opløsning til det kodede billeddata ved at anvende den rumlige hjælpeinformation og at opnå displaybilleddata, der har en ønsket opløsning,
- kendetegnet ved at** programafbildningstabellen omfatter en
- 15 videoelementærsløjfe omfattende rumlig nedskaleringsinformation, der indikerer et tilgængeligt forhold i nedskalering af den rumlige opløsning, hvor hændelsesinformationstabellen omfatter rumlig opløsningsinformation af det kodede billeddata,
- 20 hvor behandlingsenheden er konfigureret til at styre nedskaleringsbehandlingen for at opnå displaybilleddataet baseret på den rumlige nedskaleringsinformation og den rumlige opløsningsinformation, og hvor den rumlige hjælpeinformation indikerer en nøjagtighedsbegrænsning for en bevægelsesvektor inkluderet i det kodede billeddata ved at indikere,
- 25 pixel eller 1 pixelnøjagtighed, hvor det kodede billeddata tilvejebringes uden skalerbar kodning.

- 9.** Modtageindretning ifølge krav 8, hvor videoelementærsløjfen omfatter tidsmæssig nedskaleringsinformation, der indikerer et tilgængeligt forhold i
- 30 nedskalering af den tidsmæssige opløsning, og hvor behandlingsenheden styrer nedskaleringsbehandlingen for at opnå displaybilleddataet baseret på den tidsmæssige nedskaleringsinformation.

10. Modtagefremgangsmåde omfattende trinnene:

at modtage en transportstrøm i et forudbestemt format, idet transportstrømmen omfatter en videoelementærstrøm inklusive kodet billeddata og rumlig hjælpeinformation, en hændelsesinformationstabel, og en programafbildningstabel, idet den rumlige hjælpeinformation

5 tilvejebringes som en supplerende udvidelsesinformation, SEI, meddelelse i videoelementærstrømmen; og

at anvende nedskaleringsbehandling af en rumlig opløsning til det kodede billeddata baseret på den rumlige hjælpeinformation, og at opnå displaybilleddata, der har en ønsket opløsning,

10 **kendetegnet ved at** programafbildningstabellen omfatter en videoelementærsløjfe omfattende rumlig nedskaleringsinformation, der indikerer et tilgængeligt forhold ved nedskalering af den rumlige opløsning, hvor hændelsesinformationstabellen omfatter rumlig opløsningsinformation af det kodede billeddata,

15 hvor nedskaleringsbehandlingen for at opnå displaybilleddataet styres baseret på den rumlige nedskaleringsinformation og den rumlige opløsningsinformation, og

hvor den rumlige hjælpeinformation indikerer en nøjagtighedsbegrænsning for en bevægelsesvektor inkluderet i det kodede billeddata ved at indikere,

20 at nøjagtighedsbegrænsningen er variabel fra 1/4 pixelnøjagtighed til 1/2 pixel eller 1 pixelnøjagtighed,

hvor det kodede billeddata tilvejebringes uden skalerbar kodning.

DRAWINGS

FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5


IN CASE WHERE NO LIMIT IS PROVIDED FOR MV



- PIXEL AFTER SPACE-FREQUENCY CONVERSION REDUCTION DECODING APPLIED
(= SAMPLING PIXELS IN ENTIRE PREDICTED IMAGE)
- △ PIXEL TO BE INTERPOLATED IN ACCORDANCE WITH MV1
(= INTERPOLATION PIXEL IN PREDICTED BLOCK)


FIG. 6

IN CASE WHERE LIMIT IS PROVIDED FOR MV



- PIXEL AFTER SPACE-FREQUENCY CONVERSION REDUCTION DECODING APPLIED
(= SAMPLING PIXELS IN ENTIRE PREDICTED IMAGE)
- △ PIXEL TO BE INTERPOLATED IN ACCORDANCE WITH MV2
(= INTERPOLATION PIXEL IN PREDICTED BLOCK)

FIG. 7




(a) 120fps

DECODE ALL OF ENCODED PICTURES

Half picture rate flag


Quarter picture rate flag



(b) 60fps

DECODE ONLY

Half picture rate flag = 1



(c) 30fps

DECODE ONLY

Quarter picture rate flag = 1

FIG. 8





FIG. 9


HEAD ACCESS UNIT OF GOP




(a)



ACCESS UNIT OTHER THAN HEAD ACCESS UNIT OF GOP



(b)



□ : ESSENTIAL
 □ : NOT ESSENTIAL

FIG. 10

Syntax	No. of Bits	Format
user_data_unregistered (size) {		
uuid_iso_iec_11578	128	uimslbf
for(i = 16; i < payloadSize; i++) {		
user_data_payload_byte	8	bslbf
}		
}		

(a)

Syntax	No. of Bits	Format
userdata_for_downscaling_spatial () {		
userdata_id	16	uimslbf
downscaling_spatial_length	8	bslbf
constrained_to_half_pixel_MV_flag	1	bslbf
constrained_to_integer_pixel_MV_flag	1	bslbf
reserved	6	0x3f
}		

(b)

FIG. 11

Semantics definition of downscaling_spatial

constrained_to_half_pixel_MV_flag (1bit)	
1	Motion vector precision is restricted to half pixel
0	No restriction to Motion vector
constrained_to_integer_pixel_MV_flag (1bit)	
1	Motion vector precision is restricted to integer pixel
0	No restriction to Motion vector

FIG. 12

Syntax	No. of Bits	Format
user_data_unregistered (size) {		
uuid_iso_iec_11578	128	uimsbfb
for(i = 16; i < payloadSize; i++) {		
user_data_payload_byte	8	bsbfb
}		
}		

(a)

Syntax	No. of Bits	Format
userdata_for_picture_temporal() {		
userdata_id	16	uimsbfb
picture_temporal_pickup_length	8	bsbfb
half picture rate flag	1	bsbfb
quarter picture rate flag	1	bsbfb
reserved	6	0x3f
}		

(b)

FIG. 13

Semantics definition of picture_temporal_pickup

half picture rate flag (1bit)	
1	current picture is decoded by the desired decoder which can display the half picture rate
0	current picture is not decoded by the desired decoder which can display the half picture rate
quarter picture rate flag (1bit)	
1	current picture is decoded by the desired decoder which can display the quarter picture rate
0	current picture is not decoded by the desired decoder which can display the quarter picture rate

FIG. 14

Syntax	No. of Bits	Format
downscaling_descriptor() {		
downscaling_descriptor_tag	8	uimslbf
downscaling_descriptor_length	8	uimslbf
reserved	2	0x3
downscaling_type	2	bslbf
if(downscaling_type == 01) {		
temporal_downscaling_factor	2	bslbf
reserved	2	0x3
}		
else if(downscaling_type == 10) {		
reserved	2	0x3
spatial_downscaling_factor	2	bslbf
}		
else if(downscaling_type == 11) {		
temporal_downscaling_factor	2	bslbf
spatial_downscaling_factor	2	bslbf
}		
else() {		
reserved	4	0xf
}		
}		

FIG. 15

Syntax	No. of Bits	Format
downscaling_descriptor() {		
downscaling_descriptor_tag	8	uimsbfb
downscaling_descriptor_length	8	uimsbfb
reserved	2	0x3
spatial_resolution_class_type	3	bslbf
temporal_resolution_class_type	3	bslbf
reserved	2	0x3
downscaling_type	2	bslbf
if(downscaling_type == 01) {		
temporal_downscaling_factor	2	bslbf
reserved	2	0x3
}		
else if(downscaling_type == 10) {		
reserved	2	0x3
spatial_downscaling_factor	2	bslbf
}		
else if(downscaling_type == 11) {		
temporal_downscaling_factor	2	bslbf
spatial_downscaling_factor	2	bslbf
}		
else() {		
reserved	4	0xf
}		
}		

FIG. 16

Semantics definition of `downscaling_descriptor()`

<code>downscaling_type</code> (2bits)	
00	reserved
01	temporal_downscaling
10	spatial_downscaling
11	both temporal and spatial_downscaling
<code>temporal_downscaling_factor</code> (2bits) INDICATE TEMPORAL-DIRECTION DOWNSCALE (MAXIMUM PERFORMANCE)	
00	ratio 1 (no downscaling)
01	ratio $\frac{1}{2}$ (half)
10	ratio $\frac{1}{4}$ (quarter)
11	reserved
<code>spatial_downscaling_factor</code> (2bits) INDICATE SPATIAL-DIRECTION DOWNSCALE (MAXIMUM PERFORMANCE)	
00	ratio 1 (no downscaling)
01	ratio $\frac{1}{2}$ (half in both horizontal and vertical)
10	ratio $\frac{1}{4}$ (quarter in both horizontal and vertical)
11	reserved
<code>Spatial resolution class type</code> (3bits)	
000	reserved
001	1920 x 1080
010	3840 x 2160
011	7680 x 4320
1xx	reserved
<code>Temporal resolution class type</code> (3bits)	
000	reserved
001	24Hz, 25Hz, 29.97Hz, 30Hz
010	50Hz, 59.94Hz, 60Hz
011	100Hz, 120Hz
100	200Hz, 240Hz
others	reserved

FIG. 17

Syntax of Super High Resolution descriptor

Syntax	No. of Bits	Format
Super High Resolution descriptor() {		
Super High Resolution _tag	8	uimsbfb
Super High Resolution _length	8	uimsbfb
Spatial resolution class type	3	bsbfb
Temporal resolution class type	3	bsbfb
Backward_compatible_type	2	bsbfb
lower_capable_decoder_support_flag	1	bsbfb
reserved	7	0x7f
}		

FIG. 18

Semantics definition of Super High Resolution descriptor

Spatial resolution class type (3bits)	
000	reserved
001	1920 x 1080
010	3840 x 2160
011	7680 x 4320
1xx	reserved
Temporal resolution class type (3bits)	
000	reserved
001	24Hz, 25Hz, 29.97Hz, 30Hz
010	50Hz, 59.94Hz, 60Hz
011	100Hz, 120Hz
100	200Hz, 240Hz
others	reserved
Backward_compatible_type (2bits)	
00	non-compatible
01	spatially backward compatible
10	temporally backward compatible
11	reserved
lower_capable_decoder_support_flag (1bit)	
1	the encoded stream has a support for lower capable decoder
0	no support for lower capable decoder

FIG. 19




FIG. 20

