



US009884648B1

(12) **United States Patent**
Grattan et al.

(10) **Patent No.:** **US 9,884,648 B1**
(45) **Date of Patent:** **Feb. 6, 2018**

(54) **VEHICLE STRUCTURE**

(56) **References Cited**

(71) Applicant: **Nissan North America, Inc.**, Franklin, TN (US)

(72) Inventors: **Patrick Dean Grattan**, Wixom, MI (US); **Christopher Robert Hartley**, West Bloomfield, MI (US); **Gunnar Mason**, Holly, MI (US); **Matthew Michael Gapinski**, Wes Bloomfield, MI (US)

(73) Assignee: **Nissan North America, Inc.**, Franklin, TN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/338,837**

(22) Filed: **Oct. 31, 2016**

(51) **Int. Cl.**
B62D 21/15 (2006.01)
B62D 25/08 (2006.01)
B62D 27/06 (2006.01)

(52) **U.S. Cl.**
CPC **B62D 21/155** (2013.01); **B62D 21/152** (2013.01); **B62D 25/082** (2013.01); **B62D 27/06** (2013.01)

(58) **Field of Classification Search**
CPC B62D 21/15; B62D 21/152; B62D 21/155; B62D 25/08; B62D 25/2018; B62D 27/06; B60R 2021/0023
USPC 296/187.1
See application file for complete search history.

U.S. PATENT DOCUMENTS

| | | |
|----------------|---------|-------------------------|
| 6,460,889 B2 | 10/2002 | Iyanagi et al. |
| 7,461,850 B2 | 12/2008 | Kurth |
| 8,007,032 B1 | 8/2011 | Craig |
| 8,646,793 B1 | 2/2014 | Lam et al. |
| 8,870,205 B2 | 10/2014 | Corby et al. |
| 8,870,267 B2 | 10/2014 | Zischke et al. |
| 8,876,194 B2 | 11/2014 | Dix et al. |
| 9,016,768 B2 | 4/2015 | Makino et al. |
| 9,022,403 B2 | 5/2015 | Lam et al. |
| 9,079,619 B2 | 7/2015 | Gupta et al. |
| 9,120,507 B1 * | 9/2015 | Alwan B62D 21/152 |
| 9,174,679 B2 | 11/2015 | Klamser et al. |
| 9,180,913 B2 | 11/2015 | Ameloot et al. |

(Continued)

FOREIGN PATENT DOCUMENTS

| | | | | |
|----|-------------------|---------|-------|-------------|
| DE | 2853965 A1 * | 7/1980 | | B62D 21/152 |
| DE | 102012007889 A1 * | 10/2013 | | B62D 21/152 |


(Continued)

Primary Examiner — Gregory A Blankenship
(74) *Attorney, Agent, or Firm* — Global IP Counselors, LLP

(57) **ABSTRACT**

A push arm has a rear surface and a front surface. A rear surface of the push arm is located adjacent to and spaced apart from a front suspension structure defining a gap therebetween. The push arm extends forward and laterally outward such that the front surface of the push arm is located laterally outboard of and spaced apart from a front end of a first side member of a vehicle frame. A support bracket has a front section releasably attached to the push arm and a rear section releasably attached to a first cross-member of the vehicle frame adjacent to an intersection of the first side member and the first cross-member. The support bracket is configured such that in response to an off-center impact event against the front surface of the push arm, the support bracket guiding movement of the push arm in a rearward direction.

12 Claims, 35 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,199,669 B2 12/2015 Jones et al.
9,254,724 B2 2/2016 Corby et al.
9,457,746 B1 * 10/2016 Baccouche B60R 19/34
2013/0081897 A1 * 4/2013 Dandekar B62D 21/11
180/291
2014/0117717 A1 * 5/2014 Parkila B60R 19/24
296/187.09
2014/0292031 A1 10/2014 Nydam et al.
2015/0246691 A1 * 9/2015 Volz B62D 21/152
296/187.1
2015/0251702 A1 9/2015 Volz et al.
2015/0274209 A1 * 10/2015 Basappa B60R 19/26
180/271
2015/0321700 A1 11/2015 Onoda et al.
2015/0336525 A1 * 11/2015 Nam B60R 19/04
296/187.1

FOREIGN PATENT DOCUMENTS

EP 1612126 B1 9/2009
FR 2924396 A1 * 6/2009 B62D 21/155

* cited by examiner




FIG. 1




FIG. 2







FIG. 3






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 33




FIG. 34




FIG. 35




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59

1

VEHICLE STRUCTURE

BACKGROUND

Field of the Invention

The present invention generally relates to a vehicle structure. More specifically, the present invention relates to an off-center support structure attached to portions of a vehicle frame that responds to and absorbs impact force during an off-center impact test.

Background Information

Vehicle structures are routinely being redesigned to include structural features that absorb impact forces in response to impact events. Recently introduced impact event tests include an off-center impact test (also referred to as a small overlap test) where a vehicle is provided with velocity in a vehicle longitudinal direction (forward momentum) such that a front corner of the vehicle (approximately 25 percent of the overall width of the vehicle) impacts a fixed, rigid barrier. FIGS. 1, 2 and 3 schematically show an example of a conventional vehicle V undergoing an impact event with a fixed barrier B in accordance with the off-center impact test.

FIG. 1 shows the conventional vehicle V approaching the rigid barrier B in the off-center impact test. FIG. 2 shows the conventional vehicle V just after initial impact with the rigid barrier B showing initial deformation and forward momentum being transformed into rotational displacement about the rigid barrier B. FIG. 3 shows the conventional vehicle V undergoing further deformation and rotation as a result of the impact event.

SUMMARY

One object of the disclosure is to provide a vehicle frame with additional structural elements that absorb and redirect impact energy during an off-center impact test.

In view of the state of the known technology, one aspect of the present disclosure is to provide a vehicle structure with a vehicle frame, a front suspension structure, a push arm and a support bracket. The vehicle frame has a first side member, a second side member and a first cross-member. The first side member and the second side member have respective front ends. The first side member and the second side member extend rearward from the front ends. The first cross-member extends in a vehicle lateral direction from the first side member to the second side member at a location rearward of the front ends. The first cross-member further is rigidly fixed to each of the first side member and the second side member. The front suspension structure is coupled to the first side member adjacent to an intersection of the first side member and the first cross-member. The push arm has a rear surface and a front surface. The rear surface of the push arm is located adjacent to and spaced apart from the front suspension structure defining a gap therebetween. The push arm extends forward and laterally outward such that the front surface of the push arm is located laterally outboard of and spaced apart from the front end of the first side member. The support bracket has a front section releasably attached to the push arm and a rear section releasably attached to the first cross-member of the vehicle frame adjacent to the intersection of the first side member and the first cross-member. The support bracket is configured such that in response to an off-center impact event against the

2

front surface of the push arm, the support bracket initially guides movement of the push arm in a rearward direction relative to the support bracket.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the attached drawings which form a part of this original disclosure:

FIG. 1 is a schematic view of a conventional moving vehicle showing its response to a small overlap test where a front corner of the vehicle is aligned with a fixed, rigid barrier for eventual impact with the barrier;

FIG. 2 is another schematic view of the conventional vehicle showing its response to the small overlap test at the beginning of an impact event with the front corner of the conventional vehicle impacting the barrier and beginning to undergo deformation;

FIG. 3 is still another schematic view of the conventional vehicle showing its response to the small overlap test with the conventional vehicle undergoing further deformation during the impact event;

FIG. 4 is a schematic view of a moving vehicle being subjected to a small overlap test where approximately 25 percent of the front of the vehicle aligned with a fixed, rigid barrier for eventual impact with the barrier in accordance with an embodiment;

FIG. 5 is another schematic view of the vehicle depicted in FIG. 4 showing an initial response to the impact event of the small overlap test with a front corner of the vehicle impacting the barrier and beginning to undergo deformation in accordance with the embodiment;

FIG. 6 is still another schematic view of the vehicle depicted in FIGS. 4 and 5 showing a subsequent response to the impact event of the small overlap test with the moving vehicle undergoing further deformation during the impact event in accordance with the embodiment;

FIG. 7 is a perspective view of the vehicle having an off-center impact reinforcement structure 12 in accordance with the embodiment;

FIG. 8 is a bottom view (looking upward) of a frame from the vehicle depicted in FIG. 7, but with the off-center impact reinforcement structure removed, showing a first side member, a second side member, a first cross-member and a second cross-member of the frame in accordance with the embodiment;

FIG. 9 is another bottom view (looking upward) of a portion of the frame depicted in FIG. 8, but with the off-center impact reinforcement structure installed to the frame, showing a push arm assembly, a first structure (a first diagonal structure), a secondary reinforcement cross-member, a second structure (a second diagonal structure), a gap maintaining structure, a bulkhead structure and a stop structure of the off-center impact reinforcement structure in accordance with the embodiment;

FIG. 10 is a perspective view of a driver's front side of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly in accordance with the embodiment;

FIG. 11 is another perspective view showing an underside of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly, the first structure and the second structure in accordance with the embodiment;

FIG. 12 is an exploded view of a portion of the frame and the off-center impact reinforcement structure, showing the various elements of the push arm assembly as depicted in

3

FIG. 11, including a front plate, a main body, a pivot bracket, an energy absorbing structure and a support bracket in accordance with the embodiment;

FIG. 13 is a side view of the driver's front side of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly in accordance with the embodiment;

FIG. 14 is another perspective view showing an upper side of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly in accordance with the embodiment;

FIG. 15 is a bottom view of a front portion of the frame and portions of the off-center impact reinforcement structure, showing the push arm assembly, the first structure and the secondary reinforcement cross-member in accordance with the embodiment;

FIG. 16 is a perspective view of a portion of the driver's front side of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly and an intersection of the first side member and the first cross-member in accordance with the embodiment;

FIG. 17 is a perspective view showing an upper side of the frame and the off-center impact reinforcement structure, showing details of the push arm assembly and the secondary reinforcement cross-member 74 in accordance with the embodiment;

FIG. 18 is a bottom view of a front portion of driver's side of the frame and portions of the off-center impact reinforcement structure, showing details of the push arm assembly in accordance with the embodiment;

FIG. 19 is another bottom view of the front portion of the frame and portions of the off-center impact reinforcement structure, showing the push arm assembly and the first structure with the support bracket installed to the push arm assembly in accordance with the embodiment;

FIG. 20 is another bottom view of the front portion of the frame and portions of the off-center impact reinforcement structure, showing the push arm assembly with the support bracket removed showing the pivot bracket and the energy absorbing structure in accordance with the embodiment;

FIG. 21 is a top view of the front portion of the off-center impact reinforcement structure, showing the pivot bracket and the energy absorbing structure of the push arm assembly in accordance with the embodiment;

FIG. 22 is a top perspective view of the front portion of the off-center impact reinforcement structure, showing the pivot bracket and the energy absorbing structure of the push arm assembly in accordance with the embodiment;

FIG. 23 is a bottom view of a portion of the push arm assembly showing the support bracket in accordance with the embodiment;

FIG. 24 is a bottom view of the front portion of the frame and portions of the off-center impact reinforcement structure, showing the push arm assembly and the first structure with the support bracket and a bracket of the first structure in phantom showing the pivot bracket, the energy absorbing structure and a gap defined between the first cross-member and a beam of the first structure in accordance with the embodiment;

FIG. 25 is another bottom view of the front portion of the frame and portions of the off-center impact reinforcement structure, showing the push arm assembly with the support bracket, the pivot bracket and the energy absorbing structure removed showing vehicle suspension structures otherwise concealed by the push arm assembly in accordance with the embodiment;

4

FIG. 26 is a bottom view of a front portion of the vehicle including the frame and off-center impact reinforcement structure during an initial stage of an impact event where the push arm assembly initially makes contact with a fixed barrier in accordance with the embodiment;

FIG. 27 is another bottom view of the front portion of the vehicle similar to FIG. 26 showing the frame and off-center impact reinforcement structure during a second stage of the impact event where the push arm assembly begins to deform and undergo pivoting movement in accordance with the embodiment;

FIG. 28 is another bottom view of the front portion of the vehicle similar to FIG. 26 and 27 showing the frame and off-center impact reinforcement structure during a third stage of the impact event where the push arm assembly continues to deform and undergo pivoting movement in accordance with the embodiment;

FIG. 29 is a bottom view of a front portion of the push arm assembly of the off-center impact reinforcement structure with the support bracket removed showing the energy absorbing structure and pivot bracket prior to the impact event depicted in FIGS. 26-28, in accordance with the embodiment;

FIG. 30 is another bottom view of the front portion of the push arm assembly with the support bracket removed showing the energy absorbing structure and pivot bracket during an initial stage of the impact event depicted in FIGS. 26-28, in accordance with the embodiment;

FIG. 31 is another bottom view of the front portion of the push arm assembly with the support bracket removed showing the energy absorbing structure and pivot bracket during a second stage of the impact event depicted in FIGS. 26-28, in accordance with the embodiment;

FIG. 32 is another bottom view of the front portion of the push arm assembly with the support bracket removed showing the energy absorbing structure and pivot bracket during a final stage of the impact event depicted in FIGS. 26-28, in accordance with the embodiment;

FIG. 33 is another bottom view of the front portion of the frame and the off-center impact reinforcement structure showing the push arm assembly and the first structure with the support bracket and the bracket of the first structure in phantom showing the energy absorbing structure and pivot bracket after the impact event depicted in FIGS. 26-28, in accordance with the embodiment;

FIG. 34 is a front perspective view of the frame and the off-center impact reinforcement structure with portions thereof cut away showing the secondary reinforcement cross-member in accordance with the embodiment;

FIG. 35 is another bottom view of a mid-vehicle portion of the frame and the off-center impact reinforcement structure showing the first structure, the secondary reinforcement cross-member, the second structure, the gap maintaining structure and the stop structure in accordance with the embodiment;

FIG. 36 is a top view of the gap maintaining structure showing details of an upper attachment bracket fixed to the second cross-member, a first lower attachment bracket and a second lower attachment bracket in accordance with the embodiment;

FIG. 37 is a perspective bottom view of the mid-vehicle portion of the frame and the off-center impact reinforcement structure showing the first structure, the secondary reinforcement cross-member, the second structure and the gap maintaining structure in accordance with the embodiment;

FIG. 38 is a perspective view of the first structure and the secondary reinforcement cross-member shown removed

5

from the frame and the off-center impact reinforcement structure in accordance with the embodiment;

FIG. 39 is an exploded view of portions of the frame including the second cross-member, the first structure, the second structure and portions of the gap maintaining structure in accordance with the embodiment;

FIG. 40 is a perspective view of the first lower attachment bracket of the gap maintaining structure shown removed from the vehicle in accordance with the embodiment;

FIG. 41 is an exploded perspective view of the first lower attachment bracket of the gap maintaining structure shown removed from the vehicle in accordance with the embodiment;

FIG. 42 is an exploded perspective view of the second cross-member showing details of a bulkhead within the second cross-member in accordance with the embodiment;

FIG. 43 is a perspective view of the second cross-member showing further details of the bulkhead within the second cross-member in accordance with the embodiment;

FIG. 44 is another exploded perspective view of the second cross-member showing details of the bulkhead in accordance with the embodiment;

FIG. 45 is a perspective top view of the second cross-member showing an upper surface of the upper attachment bracket and the first lower attachment bracket in accordance with the embodiment;

FIG. 46 is a perspective bottom view of a portion of the second side member of the frame and features of a the second structure coupled thereto in accordance with the embodiment;

FIG. 47 is another perspective bottom view of another portion of a rear portion of the second side member of the frame and features of a rear attachment portion of the second structure with one of the brackets in phantom revealing details of a stop bracket in accordance with the embodiment;

FIG. 48 is a perspective view of brackets of the rear attachment portion shown removed from the second side member and the second structure in accordance with the embodiment;

FIG. 49 is another perspective view of two of the brackets of the rear attachment portion shown removed from the second side member and the second structure in accordance with the embodiment;

FIG. 50 is an exploded perspective view of two of the brackets of the rear attachment portion depicted in FIG. 49 in accordance with the embodiment;

FIG. 51 is an exploded perspective view of a portion of the second structure shown removed from the second side member, showing a hollow beam and an end plate thereof in accordance with the embodiment;

FIG. 52 is a top view of the hollow beam and the end plate depicted in FIG. 51 in accordance with the embodiment;

FIG. 53 is a perspective bottom view of the second cross-member and the upper attachment bracket with the hollow beam removed showing recessed areas and fasteners of the upper attachment bracket in accordance with the embodiment;

FIG. 54 is a bottom view of a portion of the second cross-section and the hollow beam of the second structure in accordance with the embodiment;

FIG. 55 is a bottom perspective view of a secondary diagonal structure and a corresponding rear attachment structure coupled to the first side member in accordance with the embodiment;

6

FIG. 56 an exploded perspective view of the secondary diagonal structure and the corresponding rear attachment structure depicted in FIG. 55 in accordance with the embodiment;

FIG. 57 is a perspective side view of the first side member of the frame showing the stop structure fixed thereto in accordance with the embodiment;

FIG. 58 is another perspective side view similar to FIG. 57, showing the stop structure with an outer plate removed showing various plate members that define the stop member in accordance with the embodiment; and

FIG. 59 is a bottom view of the frame and the off-center impact reinforcement structure during an impact event where the front wheel has moved into contact with the stop structure.

DETAILED DESCRIPTION OF EMBODIMENTS

Selected embodiments will now be explained with reference to the drawings. It will be apparent to those skilled in the art from this disclosure that the following descriptions of the embodiments are provided for illustration only and not for the purpose of limiting the invention as defined by the appended claims and their equivalents.

Referring initially to FIG. 4-9, a vehicle 10 is illustrated in accordance with a first embodiment. The vehicle 10 is provided with an off-center impact reinforcement structure 12 (shown in FIG. 9) that is configured to absorb and re-direct forces during an impact event such as an off-center impact test (also referred to as a small overlap test) described further below.

The Insurance Institute for Highway Safety (IIHS) has developed various tests where vehicles are provided with forward velocity and impacted against fixed, rigid barriers, like the rigid barrier B depicted in FIGS. 1-3. In the IIHS offset tests, the conventional vehicle C is aimed at the rigid barrier B such that approximately 25 percent of the front area of the conventional vehicle C impacts the rigid barrier B. In other words, as indicated in FIGS. 1-3, only a front corner of the conventional vehicle C impacts the rigid barrier 13. This IIHS test is also known as a frontal offset, narrow offset, or small overlap test. In such tests, a front bumper assembly of the conventional vehicle C is either not impacted, or undergoes only limited contact with the rigid barrier B during the impact event. Therefore, other structures at the front of the conventional vehicle C impact the rigid barrier B and absorb at least some of the kinetic energy associated with the rapid deceleration of the vehicle C that results from the impact event. When the vehicle C is provided with velocity and impacts the rigid barrier B, the rapid deceleration of the vehicle C transforms the kinetic energy associated with the mass and velocity of the vehicle C into deformation of the vehicle C and counter movement of the vehicle C. As is well known, kinetic energy is a function of mass times velocity. During the small offset test, the kinetic energy of the vehicle C is partially absorbed and partially transformed into other forms of kinetic energy, such as rotary motion. It should be understood that the kinetic energy associated with the forward velocity of the vehicle C (and in the description below) is transformed into an impacting force upon impact due to the rapid deceleration of the vehicle C. Consequently, hereinbelow, the terms impact force and impacting force as used herein correspond to the kinetic energy applied to the vehicle 10 during the small overlap test (the impact event), as described below with respect to the various embodiments.

The test developed by the IIHS is represented schematically in FIGS. 1-3. During the impact event, a variety of structures undergo deformation. This deformation is not explicitly depicted in FIGS. 2 and 3 with any degree of accuracy because such deformation varies from conventional vehicle to conventional vehicle, depending upon the overall design of the front structure of the conventional vehicle C. Instead, in FIG. 3, the conventional vehicle C is depicted with a generic degree of deformation as a result of the impact event. However, the conventional vehicles tested by the IIHS using the small overlap test have a relatively consistent response in that during the impact event with the rigid barrier B, the rear end R of the conventional vehicle C undergoes some rotation and swings laterally away from the rigid barrier B, as indicated in FIG. 3.

In other words, the forward velocity F_F of the conventional vehicle C as it moves is transformed upon impact with the rigid barrier B. The velocity F_F results in an equal and opposite reaction force acting on the vehicle C as the vehicle C suddenly decelerates. It is desirable to move the vehicle laterally outward from the barrier and avoid unnecessary loading of the dash-wall and/or A-pillar.

The force directing features of the off-center impact reinforcement structure 12 of the vehicle 10 as described hereinbelow are such that during an impact event (such as a small overlap test), the impact forces are absorbed and transmitted to various structures within the vehicle 10, as shown in FIGS. 4, 5 and 6. Specifically, in FIG. 4 the vehicle 10 is provided with a forward velocity V_{F1} and is subjected to a small overlap test where approximately 25 percent of the front of the vehicle is aligned with the rigid barrier B. In FIG. 5 the vehicle 10 undergoes an initial response to the impact event of the small overlap test with a front corner of the vehicle impacting the barrier and beginning to undergo deformation. Hence, the forward velocity V_{F1} is reduced to a velocity V_{F2} with some of the impact energy causing the vehicle 10 to move laterally with a velocity V_{L1} , as shown in FIG. 5. In FIG. 6, the vehicle 10 undergoes a subsequent response to the impact event in that one or more of the features of the off-center impact reinforcement structure 12 has functioned properly and caused the vehicle 10 to move laterally with the forward velocity V_{F2} is reduced to a velocity V_{F3} and a lateral velocity V_{L2} that is greater than the V_{L1} . In other words, the off-center impact reinforcement structure 12 is configured to absorb impact energy and direct that force to various portions of the vehicle, and the off-center impact reinforcement structure 12 is also configured to move the vehicle 10 in a lateral direction away from the barrier B.

It should be understood from the drawings and the description herein, that during an impact event, such as the small overlap test, the reaction forces experienced by the vehicle 10 as it impacts the rigid barrier B are significant. These significant reaction forces are exponentially greater than the forces the structures of the vehicle 10 undergo during normal operating usage of the vehicle 10. In other words, the impact events referred to herein are intended as destructive tests. Further, the impact events of the small overlap tests are configured such that the vehicle 10 impacts the rigid barrier B at portions of the vehicle 10 outboard of some of the vehicle's structures (not a central area of the vehicle 10), as described in greater detail below.

In the various embodiments described below, the vehicle 10 includes combinations of features of the off-center impact reinforcement structure 12 shown in FIG. 9 and described further below.

FIG. 7 shows one embodiment of the vehicle 10. In FIG. 7, the vehicle 10 is depicted as a pickup truck that includes a body structure 14 that defines, for example, an engine compartment 16, a passenger compartment 18 and a cargo area 20. The body structure 14 is installed to and rests on a frame 22. The frame 22 is shown removed from the vehicle 10 in FIGS. 8 and 9. Specifically, FIG. 8 shows only the frame 22 with the off-center impact reinforcement structure 12 removed, and FIG. 9 shows the frame 22 with the off-center impact reinforcement structure 12 installed thereto.

In FIG. 7, the depicted pickup truck that defines the vehicle 10 is a heavy duty vehicle intended to haul large and/or heavy materials. The frame 22 is therefore a rigid, strong structure able to withstand heavy duty usage. However, it should be understood from the drawings and the description herein, that the frame 22 and the off-center impact reinforcement structure 12 described below can be configured for smaller vehicles or larger vehicles and is not limited to usage in a heavy duty vehicle such as the vehicle 10. In other words, the off-center impact reinforcement structure 12 can be used on any size vehicle that includes a frame such as the frame 22 where the body structure 14 attaches to and is supported by the frame 22. It should also be understood from the drawings and description, that the off-center impact reinforcement structure 12 can also be employed with a unibody vehicle. A unibody vehicle is a vehicle that does not typically include a separate frame such as the frame 22. Rather, the unibody vehicle includes various structural elements welded together. Elements of the unibody vehicle serve as frame elements functionally equivalent to the elements of the frame 22. For example, U.S. Pat. No. 8,870,267 assigned to Nissan North America, discloses a unibody vehicle body structure. The front structural support portions (30) disclosed in U.S. Pat. No. 8,870,267 are basically vehicle side members, such as those of the frame 22 (described in greater detail below). U.S. Pat. No. 9,180,913, also assigned to Nissan North America, also discloses a unibody vehicle body structure and further discloses an engine cradle. The elements of the off-center impact reinforcement structure 12 can be installed to portions of the unibody vehicle disclosed in U.S. Pat. No. 8,870,267 and portions of the engine cradle of U.S. Pat. No. 8,870,267. Both U.S. Pat. No. 8,870,267 and U.S. Pat. No. 9,180,913 are incorporated herein by reference in their entirety. Since unibody vehicles are conventional structures, further description is omitted for the sake of brevity.

For clarity, the off-center impact reinforcement structure 12 has also been removed from the frame 22 in FIG. 8. The off-center impact reinforcement structure 12 is shown in FIG. 9 installed to specific portions of the frame 22.

In FIG. 8 several directions relative to the frame 22 (and the vehicle 10) are shown in order to define orientations of the various features of the vehicle 10 and the off-center impact reinforcement structure 12. Specifically, the vehicle 10 and the frame 22 define a longitudinal center line C_L that extends in a lengthwise direction of the vehicle 10 along a central portion of the vehicle 10. At a left-hand side of FIG. 8, a forward direction F_D is indicated by the depicted arrow, and at a right-hand side of FIG. 8 a rearward direction R_D is indicated by the depicted arrow. As well, inboard directions I_D and outboard directions O_D relative to the longitudinal center line C_L are also shown in FIG. 8.

As shown in FIG. 8, the frame 22 includes a first side member 30, a second side member 32, a first cross-member 34, a second cross-member 36 and a third cross-member 38 and an optional front cross-member 40. FIG. 8 shows an

underside of the frame 22. In other words, the depiction of the frame 22 is taken from below the frame 22 looking upward. The frame 22 is made of heavy gauge steel, but can alternatively be made of other materials depending upon the overall design of the vehicle 10. It should therefore be understood that the first side member 30 extends along and under a driver's side of the vehicle 10, and the second side member 32 extends along and under a passenger's side of the vehicle 10.

The first side member 30 is an elongated beam (a first side member) that has multiple contours and shapes. Specifically, the first side member 30 has a front end 30a and a rear end 30b. The first side member 30 also has a first portion 30c, a second portion 30d and a third portion 30e. The first portion 30c extends in the rearward direction R_D from the front end 30a to a location proximate the second cross-member 36. The first portion 30c is generally straight. The second portion 30d has a curved shape such that just rearward of the first portion 30c, the second portion 30d gradually curves in the outboard direction O_D . The third portion 30e is generally straight, but can include contours and curves, depending upon the overall design of the vehicle 10.

Similarly, the second side member 32 is an elongated beam (a second side member) that has multiple contours and shapes that are symmetrical to the first side member 30. Specifically, the second side member 32 has a front end 32a and a rear end 32b. The second side member 32 also has a first portion 32c, a second portion 32d and a third portion 32e. The first portion 32c extends in the rearward direction R_D from the front end 32a to a location proximate the second cross-member 36. The first portion 32c is generally straight. The second portion 32d has a curved shape such that just rearward of the first portion 32c, the second portion 32d gradually curves in the outboard direction O_D .

The first portions 30c and 32c of the first and second side members 30 and 32 are a first distance away from one another, and the third portions 30e and 32e are a second distance away from one another, with the second distance being greater than the first distance.

The first and second side members 30 and 32 each include vehicle body attachment flanges 42 and 44 (cabin attachment flanges). The attachment flanges 42 and 44 are welded to the first and second side members 30 and 32 and are dimensioned and shaped to attach to the body structure 14 of the vehicle 10. The attachment flanges 42 extend from outboard sides of the first portions 30c and 32c of the first and second side members 30 and 32 forward of the first cross-member 34. The attachment flanges 44 extend from outboard sides of the second portions 30d and 32d of the first and second side members 30 and 32 rearward of the second cross-member 36.

Although not shown in FIG. 8, the third portions 30e and 32e of the first and second side members 30 and 32 can also include body attachment flanges configured for attachment to structures that define the cargo area 20 of the vehicle 10. Further, the third portions 30e and 32e can be at the same level above the ground as the first portions 30c and 32c, or can be raised above the ground at a level higher than the first portions 30c and 32c, with the second portions 30d and 32d including an upward curvature.

As shown in FIG. 8, each of the first portions 30c and 32c of the first and second side members 30 and 32 further include front suspension structures such as coil spring supports 46, first suspension structures 48 and second suspension structures 50.

The coil spring supports 46 are rigidly fixed (i.e. welded) to respective ones of the first and second side members 30

and 32. The coil spring supports 46 are dimensioned and shaped to support lower ends of front suspension coil springs in a conventional manner. Since front suspension coil springs are conventional structures, further description is omitted for the sake of brevity.

The first suspension structures 48 are defined by pairs of flanges welded to lower surfaces of the first and second side members 30 and 32. Similarly, the second suspension structures 50 are defined by pairs of flanges welded to lower surfaces of the first and second side members 30 and 32 rearward and spaced apart from the first suspension structures 48. The first suspension structures 48 are adjacent to or aligned with the first cross-member 34. The second suspension structures 50 are adjacent to or aligned with the second cross-member 36.

The first suspension structures 48 and the second suspension structures 50 are configured to support a lower control arm 52 for pivotal movement about pivot bolts 54. The lower control arm 52 is part of the steering and suspension structure of the vehicle 10. Since steering and suspension structures (and, in particular, control arm structures) are conventional vehicle components, further description is omitted for the sake of brevity.

The engine compartment 16 of the body structure 14 is approximately located in the space above and between the first portions 30c and 32c of the first and second side members 30 and 32. A front portion of the passenger compartment 18 is located in the space above and between the second portions 30d and 32d of the first and second side member rearward of the engine compartment 16. The remainder of the passenger compartment 18 and the cargo area 20 of the body structure 14 are located above the third portions 30e and 32e of the first and second side members 30 and 32.

As shown in FIGS. 9, 10, 13, 14 and 16, the first cross-member 34 is rigidly attached to the first side member 30 and rigidly attached to the second side member 32. The first cross-member 34 can be co-planar with the first and second side members 30 and 32, or can be located above or below the first and second side members 30 and 32. However, in the depicted embodiment the first cross-member 34 is located below the first and second side members 30 and 32.

The first cross-member 34 has a first end 34a, a second end 34b and mid-section 34c that extends from the first end 34a to the second end 34b. The first end 34a of the first cross-member is fixed to the first side member 30 via a plurality of reinforcement brackets 60, 62 and 64 shown in FIGS. 10, 13, 14 and 16. The reinforcement brackets 60, 62 and 64 have differing surfaces, with some of those surfaces being welded to the first side member 30 and some of those surfaces, such as surfaces 60a, 60b and 60c, extending downward with the reinforcement brackets 60, 62 and 64 being welded to the first end 34a of the first cross-member 34 along or below the surfaces 60a, 62a and 64a. The reinforcement brackets 60, 62 and 64 are considered to be part of the first cross-member 34, but can also be considered part of the first side member 30. The reinforcement brackets 60, 62 and 64, along with the first side member 30 and the first cross-member 34 define an intersection 66 of the first side member 30 and the first cross-member 34.

In the depicted embodiment, the first cross-member 34 extends in a vehicle lateral direction from the first portion 30c of the first side member 30 to the first portion 32c of the second side member 30 at a location rearward of the front ends 30a and 32a. The first cross-member is further rigidly fixed to each of the first side member 30 and the second side

11

member 32. As shown in FIGS. 8 and 9, the first cross-member 34 extends perpendicular to the first portion 30c of the first side member 30 and the first portion 32c of the second side member 32.

As shown in FIGS. 13 and 14, an upper surface 34d of the mid-section 34c of the first cross-member 34 is vertically spaced apart from an upper surface 30f of the first side member 30 (the first side member) in the area of the first portion 30c. Specifically, the upper surface 34d of the mid-section 34c of the first cross-member 34 is below the upper surface 30f of the first side member 30 in the area of the first portion 30c. As shown in FIG. 13, the upper surface of the first side member 30 defines a plane P_1 . The upper surface 34d of the mid-section 34c of the first cross-member 34 extends along a plane P_2 . As shown in FIG. 13, the plane P_1 is vertically above the plane P_2 .

The second end 34b of the first cross-member 34 is also fixed to the second side member 32 in a manner consistent with the attachment of the first end 34a to the first side member 30. Since the attachment of the second end 34b to the second side member 32 is basically the same as the attachment of the first end 34a to the first side member 30, further description of the attachment of the first cross-member 34 to the second side member 32 is omitted for the sake of brevity.

The second cross-member 36 extends in the vehicle lateral direction and is rigidly fixed to areas of each of the first side member 30 and the second side member 32 rearward of the first cross-member 34. The second cross-member 36 can be welded to each of the first portions 30c and 32c of the first and second side members 30 and 32. However, as is described below with reference to FIGS. 37, 39 and 42, the second cross-member 36 can be attached to the first and second side members 30 and 32 via mechanical fasteners (not shown). Further, the second cross-member 36 is vertically aligned with the first portions 30c and 32c of the first and second side members 30 and 32 and extends in a direction perpendicular to each of the first and second side members 30 and 32. The second cross-member 36 is also parallel to the first cross-member 34.

An engine receiving space is defined in the area confined between the first and second cross-members 30 and 32, and between the first and second side members 34 and 36.

The third cross-member 38 extends between forward ends of each of the third portions 30e and 32e of the first and second side members 30 and 32. The third cross-member 38 is welded to each of the first and second side members 30 and 32 and can serve as an attachment structure for a rear portion of the body structure 14 (at a mid-portion of the passenger compartment 18), and/or can serve as an attachment structure for the structure that defines the cargo area 20.

The optional front cross-member 40 is welded or otherwise rigidly fixed to the front ends 30a and 32a of the first and second side members 30 and 32. A bumper structure (not shown) can be attached to the optional front cross-member 40. Alternatively, the bumper structure (not shown) can be attached to the front ends 30a and 32a of the first and second side members 30 and 32 replacing the optional front cross-member 40.

A description of the off-center impact reinforcement structure 12 is now provided with specific reference to FIGS. 9-60.

With initial reference to FIG. 9, the off-center impact reinforcement structure 12 basically includes a push arm assembly 70, a first structure 72 (a first diagonal structure), a secondary reinforcement cross-member 74, a second struc-

12

ture 76 (a second diagonal structure), a gap maintaining structure 78, a bulkhead structure 80 (shown in FIGS. 36 and 42-44) and a stop structure 82 (a tire catching structure). Each of the push arm assembly 70, the first structure 72, the secondary reinforcement cross-member 74, the second structure 76, the gap maintaining structure 78, the bulkhead structure 80 and the stop structure 82 is described separately below. In the depicted embodiment, the off-center reinforcement structure 12 is installed to the vehicle 10 with the push arm assembly 70 installed to a driver's side of the vehicle 10 with the first and second structures 70 and 72 extending rearward and laterally toward the passenger's side of the vehicle 10. However, it should be understood from the drawings and the description herein that the off-center reinforcement structure 12 can be installed with the push arm assembly 70 installed to the passenger's side of the vehicle 10, or, alternatively two of the off-center reinforcement structures 12 can be incorporated into the vehicle 10 with one the push arm assembly 70 being installed at each of the driver's side and the passenger's side of the vehicle 10.

As shown in FIGS. 9-34, the push arm assembly 70 is coupled to the frame 22 (the vehicle frame) proximate the intersection 66 of the first side member 30 and the first cross-member 34. The push arm assembly 70 extends in a forward and laterally outboard direction from the intersection 66 of the first side member 30 and the first cross-member 34. The push arm assembly 70 defines an angle α_1 relative to the first portion 32c of the first side member 30, as shown in FIGS. 9 and 10. The angle α_1 is between 25 and 45 degrees. In the depicted embodiment, the angle α_1 is approximately 35 degrees.

As shown in an exploded view in FIG. 12, the push arm assembly 70 basically includes a main body 90, a front end plate 92, a energy absorbing structure 94, a pivot bracket 96, a support bracket 98 and an attachment bracket 100.

The main body 90 is a hollow elongated beam element having a front end 90a and a rear end 90b. The front end 90a is shaped to conform the front end plate 92 (described in greater detail below). Specifically, the front end 90a has two portions that are angularly offset from one another in correspondence with the shape of the front end plate 92. The rear end 90b of the main body 90 has offset end surfaces. Specifically, a lower portion 90c of the rear end 90b of the main body 90 extends rearward and is formed with an angle α_2 relative to a lengthwise direction of the main body 90 and an upper portion 90d is formed with an angle α_3 relative to a lengthwise direction of the main body 90. The purpose of the lower portion 90c and the upper portion 90d is further understood in the description of the pivot bracket 98, described below.

The front end plate 92 of the push arm assembly 70 is fixedly attached (for example, welded) to the front end 90a. The front end plate 92 defines a front surface having a first section 92a and a second section 92b. In other words, the first and second sections 92a and 92b together define the front surface of the front end plate 92. The front end plate 92 (and the front end 90a of the main body 90 of the push arm assembly 70) extends forward and laterally outward such that the front surface (both the first portion 92a and the second portion 92b) of the push arm assembly 70 is located laterally outboard of and spaced apart from the front end 30a of the first side member 30.

The second section 92b of the front end plate 92 is located between the first section 92a and the first side member 30. Further, the second section 92b of the front end plate 92 is located inboard of the first section 92a and extends forward

of the first section **92a**. As shown in FIG. 9, the first section **92a** of the front end plate **92** extends in a direction perpendicular to a lengthwise direction of the vehicle frame **22** in a non-impacted state, where the lengthwise direction is parallel the longitudinal center line C_L of the vehicle **10**. An obtuse angle α_4 is defined between the first section **92a** and the second section **92b** of the push arm assembly **70** is between 110 and 135 degrees. As shown in the FIG. 9, the obtuse angle α_4 is defined between the first section **92a** and the second section **92b** of the front surface of the push arm is 125 degrees.

As shown in FIG. 20, the rear end **90a** of the main body **90** is spaced apart from the intersection **66** of first side member **30** and the first cross-member **34** defining a gap G_1 therebetween. More specifically, the main body **90**, the energy absorbing structure **94** and the pivot bracket **96** are all spaced apart (non-contacting) from the intersection **66** of the first side member **30** and the first cross-member **34**.

As shown by comparing FIG. 20 (with the energy absorbing structure **94** and the pivot bracket **96** removed) and FIG. 24 (with the energy absorbing structure **94** and the pivot bracket **96** installed), the rear end **90a** of the main body **90** is shaped to receive the energy absorbing structure **94** and the pivot bracket **96**. More specifically, the energy absorbing structure **94** and the pivot bracket **96** are located within the gap G_1 with the vehicle **10** in a non-impacted state, and are spaced apart from the intersection **66**.

As shown in FIGS. 12, 20-22 and 34, the energy absorbing structure **94** includes a plurality of cup-shaped members including a first cup-shaped member **104**, a second cup-shaped member **106** and a third cup-shaped member **108**. The first, second and third cup-shaped members **104**, **106** and **108** can also be U-shaped members that are nested within one another in a manner described below.

Specifically, at least the first and second cup-shaped members **104** and **106** have similar conforming shapes. For instance, the first cup-shaped member **104** has two side walls **104a** and **104b**, and an end wall **104c** that extends between the two side walls **104a** and **104b**, thereby defining an overall U-shape as viewed in cross-section in FIGS. 20 and 21. The second cup-shaped member **106** has two side walls **106a** and **106b**, and an end wall **106c** that extends between the two side walls **106a** and **106b**, thereby also defining an overall U-shape. The third cup-shaped member **108** is shown as a flat plate member in cross-section but can also have side walls (not shown).

The first, second and third cup-shaped members **104**, **106** and **108** are attached to one another such that the end wall **104c** is spaced apart from the end wall **106c**, and the third cup-shaped member **108** is further spaced apart from the end walls **104c** and **106c**; as shown in FIGS. 20, 21 and 22. Specifically, the side walls **104a** and **104b** of the first cup-shaped member **104** are fixedly attached to the side walls **106a** and **106b** of the second cup-shaped member **106** via welds **W** such the end walls **104c** and **106c** are spaced apart from one another in the non-impacted state. The third cup-shaped member **108** is fixed via welds **W** to inner surfaces of the side walls **106a** and **106b** within the second cup-shaped member **106** such that the third cup-shaped member **108** being spaced apart from the end wall **106c**.

The pivot bracket **96** is attached to both the energy absorbing structure **94** and the rear end **90b** of the main body **90** via welds **W**, as shown in FIG. 22. The pivot bracket **96** has an overall triangular shape and is dimensioned to contact the lower portion **90c** of the rear end **90b** of the main body **90** of the push arm assembly **70**, and contact a lower surface of the upper portion **90d** of the rear end **90b** of the main body

90 of the push arm assembly **70**. Specifically, as shown in FIG. 20, a first edge **96a** of the pivot bracket **96** contacts an edge of the lower portion **90c** of the rear end **90b** of the main body **90** of the push arm assembly **70**. As shown in FIG. 22, an upper surface **96b** of the pivot bracket **96** contacts the upper portion **90d** of the rear end **90b** of the main body **90** of the push arm assembly **70** and is welded thereto. The upper surface **96b** also abuts the first cup-shaped member **104** of the energy absorbing structure **94**. The pivot bracket **96** also has a rear surface **96c** within the gap G_1 that is spaced apart from the intersection **66** and from the first cross-member **34** in the non-impacted state. However, as is explained in greater detail below, in response to an impact event, the rear surface **96c** can move into contact with the first cross-member **34**.

As shown in FIG. 20 with the support bracket **98** removed, the rear end **90b** of the main body **90**, the energy absorbing structure **94** and the pivot bracket **96** are all spaced apart from the pivot bolt **54** and the first suspension structure **48** in the non-impacted state. As described in greater detail below, the support bracket **98** is designed to be removable from the vehicle **10** in order to gain access to the pivot bolt **54** in the event that steering adjustments or repairs are need to the front suspension structures of the vehicle **10**.

Further, the pivot arm assembly **70**, including the main body **90**, the front end plate **92**, the energy absorbing structure **94** and the pivot bracket **96** can also be removed from the vehicle **10** for servicing and easy access to mechanical components of the vehicle **10** that may be covered or partially covered by the pivot arm assembly **70**.

As shown in FIGS. 9, 11, 13-15 and 18-19, the support bracket **98** is attached to the main body **90** of the push arm assembly **70** and first cross-member **34** via removable mechanical fasteners F_1 . The support bracket **98** has a contoured shape. For example, an underside surface **98a** as viewed in FIGS. 10, 15, 18-19 and 23 gives the appearance that the support bracket **98** is generally flat. However, as shown in perspective views in FIGS. 12-14, the support bracket **98** has a truncated U-shape with side portions **98b** and **98c** that extend upward from the underside surface **98a** and extend along opposite sides of the rear end **90b** of the main body **90**. The support bracket **98** has a front portion **98d** and a rear portion **98e**. The support bracket **98** is formed with two parallel elongated slots **98s** that extend from proximate the front portion **98d** rearward toward the rear portion **98e**. The slots **98s** are angularly offset from the center line C_L of the vehicle **10**. Specifically, the slots **98s** extend in directions that are parallel (or in alignment with) a lengthwise direction of the main body **90** of the push arm assembly **70**. The support bracket **98** also includes two apertures **98f**.

The mechanical fasteners F_1 inserted through the slots **98s** and the apertures **98f** rigidly attach the support bracket **98** to the frame **22** and the off-center impact reinforcement structure **12**. Specifically, the mechanical fasteners F_1 in the slots **98s** thread into a nut or threaded aperture formed in the main body **90** of the push arm assembly **70**. The mechanical fasteners F_1 inserted through the apertures **98f** are threaded into nuts or threaded apertures of the first cross-member **34** and/or threaded apertures in a forward portion of the first structure **72**. By removing the mechanical fasteners F_1 , the support bracket **98** is held in place covering the pivot bolt **54** of the first suspension structure **48**, the energy absorbing structure **94** and the pivot bracket **96** of the push arm assembly **70**, as shown in FIGS. 9, 11, 15, and 23. However, with the support bracket **98** removed from the off-center impact reinforcement structure **12**, the pivot bolt **54** of the

15

first suspension structure **48**, the energy absorbing structure **94** and the pivot bracket **96** of the push arm assembly **70** are exposed, as shown in FIGS. **20**, **24** and **25**.

As is described in greater detail below, in response to an off-center impact event the push arm assembly **70** can undergo limited rearward movement that is initially guided by movement of the mechanical fasteners F_1 which are configured to slide along the length of the elongated slots **98s**. In other words, impact force pushing on the push arm assembly **70** causes the main body **90** to move relative to the support bracket **98** during initial stages of an impact event. The slots **98s** are specifically configured to allow movement of the main body **90** with respect to the support bracket **98**, thereby absorbing impact energy, and causing deformation of the energy absorbing structure **94**, as described in greater detail below. Further, since the connection between the main body **90** and the support bracket **98** allows for limited movement due to the slots **98s**, the attachment of the support bracket **98** to the first cross-member **34** has greater strength than the connection between the support bracket **98** and the push arm assembly **70**.

As shown in FIGS. **10**, **12-14**, **16-17** and **60**, the attachment bracket **100** extends upward from a mid-section **90e** of main body **90** of the push arm assembly **70** to the first side member **30** at a location forward of the intersection **66** of the first side member **30** and the first cross-member **34**. In other words, the attachment bracket **100** extends downward from the first side member **30** to the upper surface of the main body **90** of the push arm assembly **70**.

Upper ends of the attachment bracket **100** can include hooks that are inserted into apertures of the first side member **30** during installation. Mechanical fasteners are then installed through separate apertures for fixedly attaching the attachment bracket **100** to the first side member **30**.

The attachment bracket **100** is also fixedly attached to the upper surface of the main body **90** of the push arm assembly **70**. Consequently, the push arm assembly **70** is supported such that the push arm assembly **70** is located below the first side member **30**. The attachment bracket **100** does not need to be a structural element of the off-center impact reinforcement structure **12**. Rather, the attachment bracket **100** can be made of a thin sheet metal material that supports the main body **90** of the push arm assembly **70** in a non-impacted state. However, in response to an impact event, the attachment bracket **100** releases the push arm assembly **70** in a manner described in greater detail below.

A description of the first structure **72** (a first diagonal structure) is now provided with specific reference to FIGS. **9**, **15**, **19**, **24** and **37-38**. The first structure **72** extends from the first cross-member **34** rearward to a mid-portion **36a** of the second cross-member located forward of the second structure **76**. More specifically, the first structure **72** is coupled to the first cross-member **34** at a location that is rearward of and adjacent to, but inboard relative to the intersection **66** of the first cross-member **34** and the first side member **30**. The first structure **72** (also referred to as a diagonal structure) is neither parallel to nor perpendicular to either the first cross-member **34** or the first side member **30**. Rather, the first structure **72** extends at an oblique angle rearward from the first cross-member **34** to the mid-portion **36a** of the second cross-member **36**.

The first structure **72** basically includes a hollow beam **112**, and a bracket **114**. The hollow beam **112** has a front end **112a** with an end plate **116** shaped to conform to an adjacent surface of the first cross-member **34**. However, the end plate **116** is spaced apart from the adjacent surface of the first cross-member **34** defining a gap G_2 therebetween, as shown

16

in FIG. **24**. The hollow beam **112** also has a rear end **112b** that is described in greater detail below along with the second structure **76** and the gap maintaining structure **78**.

As shown in FIG. **38**, associated with the first structure **72** are two secondary members, the secondary reinforcement cross-member **74** and a bracket **120**.

As shown in FIGS. **9**, **11**, **34**, **35**, **37** and **38**, the bracket **120** extends from the first cross-member **30** to the second cross-member **32**. The bracket **120** is positioned adjacent to the second side member **32**. The secondary reinforcement cross-member **74** extends from the hollow beam **112** to the bracket **120**. The secondary reinforcement cross-member **74** is an optional feature that is parallel to the first cross-member **34**. The secondary reinforcement cross-member **74** is shaped to extend upward to a level that is higher above the ground than both the first cross-member **34** and the second cross-member **36**, as shown in FIG. **34**. The secondary reinforcement cross-member **74** is positioned such that it extends immediately in front of a power plant **M** of the vehicle **10**. The power plant **M** can be an internal combustion engine, such as a diesel or gasoline powered engine, a hybrid engine or an electric motor, depending upon the vehicle design. The secondary reinforcement cross-member **74** extends upward from bracket **120** and the hollow beam **112** such that a central portion of the secondary reinforcement cross-member **74** extends in front of the power plant **M**. During an impact event, the mass of the power plant **M**, due to the laws of physics, will continue with forward momentum while the vehicle **10** impacts the barrier **B** and forward movement of the vehicle **10** is reduced or stopped. The secondary reinforcement cross-member **74** can be contacted by the power plant **M** during the impact event, thereby limiting forward movement of the power plant **M**.

A description of the effects of an off-center impact event (a small overlap test) on the push arm assembly **70** of the off-center impact reinforcement structure **12** is now provided with specific reference to FIGS. **4-6** and **26-33**. As described above, in an off-center impact event, for instance, during a small overlap test, the vehicle **10** is provided with velocity and aimed to impact the fixed barrier **B**, as shown in FIG. **4**. In FIG. **5** as the vehicle **10** impacts the fixed barrier **B** and the vehicle **10** absorbs impact energy. The absorption of impact energy includes distribution of the impact energy to various portions of the frame **22** via the features of the off-center impact reinforcement structure **12**. As the impact event progress, as shown in FIGS. **5** and **6**, the off-center impact reinforcement structure **12** absorbs a portion of the impact energy and distributes the impact energy in a manner described below.

As shown in FIG. **26** the small overlap test is designed such that the vehicle **10** makes contact with the barrier **B** in the area of the front end plate **92** of the push arm assembly **70**. Initially, impact energy is directed diagonally (rearward and laterally) from the front end plate **92** in the direction of the gap maintaining structure **78** (a cross-car direction) as indicated by the large arrow superimposed over portions of the off-center impact reinforcement structure **12** in FIG. **26**. The impact energy of the small overlap test is such that the front end plate **92** transmits impact force through the main body **90** causing the main body **90** to move rearward resulting in the impact energy being directed rearward and laterally, as shown in FIG. **27**. Several impact absorbing changes occur as the main body **90** moves rearward relative to the frame **22**, as explained further below. As shown in FIG. **27**, the main body **90** begins to rotate about the intersection **66** of the first side member **30** and the first cross-member **34**. As also shown in FIG. **27**, the impact

17

force is largely directed in a vehicle lateral direction, as indicated by the large arrow superimposed over the push arm assembly 70 in FIG. 27. The rotation of the main body 90 causes at least a portion of the impact energy from the small overlap test to push the vehicle 10 laterally away from the barrier B. Further, as shown in FIG. 28, rotation of the main body 90 causes the main body 90 and the barrier B to press against a front wheel T of the vehicle 10, causing the front wheel T to contact the stop structure 80, as is described in greater detail below. As shown in FIG. 28, once the front wheel T contacts the stop structure 80, impacting force is directed rearward and laterally (another cross-car direction) as indicated by the large arrow superimposed over the front wheel T. Further, as shown in FIG. 28, in the final stages of the impact event, the push arm assembly 70, and in particular, the main body 90, has pivoted such that the main body 90 is parallel to or in alignment with the first cross-member 34.

As shown in FIG. 29-33, as the main body 90 is pushed rearward by contact with the barrier B, the main body 90 slides rearward relative to the support bracket 98, as shown in FIG. 33. In FIGS. 29-32 the support bracket 98 is removed to show movement of the main body 90 and compression of the energy absorbing structure 94. During the small overlap test, the support bracket 98 is installed. The support bracket 98 is shown in phantom in FIG. 33. In the initial stages of the impact event, impact force is such that the fasteners F_1 that attached the main body 90 to the support bracket 98, slide along the slots 98e. The slots 98e are oriented and dimensioned to direct the rearward movement of the main body 90 in a direction toward the intersection 66 of the first side member 30 and the first cross-member 34. Hence, in the initial moments of the impact event (the small overlap test), the main body 90 slides rearward toward the intersection 66 as directed by the orientation of the slots 98e.

As the main body 90 is urged to move toward the intersection 66, the gap G_1 between rear end 90b of the main body and first cross-member 34 at the intersection 66 begins to close, as shown in FIG. 30-33. As a result of the closing of the gap G_1 , the pivot bracket 96 contacts the first cross-member 34 inboard of the intersection 66 providing the main body 90 with a pivot point about which the front end plate 92 of the main body 90 begins to rotate rearward and laterally outboard away from the first side member 30. Once the main body 90 begins to pivot about the pivot bracket 96, the energy absorbing structure 94 absorbs a portion of the impact energy and is deformed, as shown in FIGS. 30-33. The cup-shape of the first and second cup-shaped members 104 and 106 is such that contact with the bolt 54 securing the lower control arm 52 to the first side member 30 is avoided, thereby maintaining attachment between the first side member 30 and the lower control arm 52. In other words, the shape and configuration of the elements that define the energy absorbing structure 94 protect the bolt 54 and prevent the lower control arm 52 from being released from the first side member 30 during the impact event. As shown in the sequence depicted in FIGS. 30-33, the energy absorbing structure 94 is configured such that in response to the impact event of the small overlap test (the off-center impact event) against the front end plate 92 of the push arm assembly 70, the push arm assembly 70 via the main body 90 imparts impact force to the energy absorbing structure 94 pushing the energy absorbing structure 94 into contact with the front suspension structure 48 such that the energy absorbing structure 94 is deformed absorbing impact energy. The deformation of the energy absorbing structure 94 can take many forms. For example,

18

the side walls 106a and 106b can deform and move away from one another (diverging movement) or can deform and move toward one another (converging movement). It is also possible for one of the side walls 106a and 106b to move toward the other, while the other remains unmoved. Further, one or both of the side walls 106a and 106b can be provided with a notch or score-line (not shown) that encourages a direction of deformation during the impact event.

Further, the pivot bracket 96 is configured and positioned such that in response to the off-center impact event against the push arm assembly 70, the main body 90 moves the pivot bracket 96 into contact with the first cross-member 34 and imparts impact force to the pivot bracket 96 pushing the energy absorbing structure 94 into contact with the front suspension structure 48. Further, the push arm assembly 70 pivots about the contact area between the pivot bracket 96 and the first cross-member 34 providing a pivot point about which the front surface 92a and 92b of the push arm assembly 70 pivots.

As is described further below, impact energy is further transmitted through the first cross-member 34 to the first structure 72, the second cross-member 36, through the gap maintaining structure 78 and thereafter to the second structure 76. Description of the further transmitted impact force follows the description of the second structure 76, the gap maintaining structure 78 and the bulkhead structure 80.

A description of the second structure 76, the gap maintaining structure 78 and the bulkhead structure 80 is now provided with specific reference to FIGS. 35-56. The second structure 76, the gap maintaining structure 78 and the bulkhead structure 80 are inter-related structures and therefore are described together.

The second structure 76 is another diagonal structure that extends from the mid-portion 36c of the second cross-member 36 to a portion of the second side member 32 adjacent to the body attachment flange 44 and rearward of the second cross-member 36, as shown in FIGS. 35 and 37. The second structure 76 basically includes a beam 130 (FIGS. 39, 46, 51 and 52), an end plate 132 (FIGS. 39 and 51), a rear attachment structure 134 (FIGS. 46-50) and a secondary diagonal structure 136 (FIGS. 35 and 37).

The gap maintaining structure 78 includes an upper attachment bracket 140, a first lower attachment bracket 142 and a second lower attachment bracket 144.

The bulkhead structure 80 is defined relative to the second cross-member 34, which includes an upper portion 150 and a lower portion 152. The bulkhead structure 80 includes a first reinforcement bracket 154 and a second reinforcement bracket 156 that are installed to a hollow interior of the second cross-section member 34 between the upper portion 150 and the lower portion 152, as described below.

As shown in FIGS. 39, 46, 51 and 52, the beam 130 of the second structure 76 has a forward end 130a and a rearward end 130b. An upper wall of the forward end 130a of the beam 130 includes a first slot 130c and a second slot 130d shown in FIG. 52. The first and second slots 130c and 130d are aligned with one another and are configured to receive mechanical fasteners extending from the upper attachment bracket 140, as is described in greater detail below. The end plate 132 is fixedly attached to the rearward end 130b of the beam 130 by, for example, welding techniques. The end plate 132, as shown in FIGS. 39 and 51, has two surfaces, with the surface 132a extending in a vehicle longitudinal direction parallel to the center line C_L of the vehicle 10. A description of the end plate 132 and its relationship to the rear attachment structure 134 is provided below. A description of the secondary diagonal structure 136 is included after

a description of the bulkhead structure **80**, the gap maintaining structure **78** and the rear attachment structure **134**.

As shown removed from the frame **22** in FIGS. **42** and **44**, the second cross-member **36** includes the upper portion **150** and the lower portion **152**. The upper portion **150** includes a reinforcement **150a** that is welded to outer surfaces of the upper portion **150**. The lower portion **152** has a first upright wall **152a**, a horizontal wall **152b** and a second upright wall **152c**, as shown in FIG. **44**. The first and second upright walls **152a** and **152c** are parallel to one another with a recessed area being defined between them above the horizontal wall **152b**, as shown in FIG. **44**.

The first reinforcement bracket **154** has a first upright portion **154a**, a first horizontal portion **154b** and a second upright portion **154c** that together define the plurality of surface sections perpendicular to the first upright wall **152a** and the second upright wall **152c**. The second reinforcement bracket **156** defines a third upright portion **156a** and a second horizontal portion **156b** that installed within the recess or hollow area of the lower portion **152** of the second cross-member **36**. The third upright portion **156a** and the second horizontal portion **156b** both define additional surface sections perpendicular to the first upright wall **152a** and the second upright wall **152c** of the second cross-member **36**.

The first reinforcement bracket **154** of the bulkhead structure **80** is welded within the recessed area of the lower portion **150** via welds **W**. The second reinforcement bracket **156** is welded to the lower portion **152** with the recessed area and is further welded to an upper surface of the first reinforcement bracket **154**. After the first and second reinforcement brackets **154** and **156** are welded in place, the upper portion **150** is welded to the lower portion **152** thereby completing the second cross-member **36**. In the completed second cross-member **36**, the bulkhead structure **80** is installed within a hollow interior of the second cross-member **34** between the upper portion **150** and the lower portion **152**.

Thereafter, the second cross-member **36** can be installed to the first and second side member **30** and **32** and held in place by fasteners (not shown). As discussed further below, the bulkhead structure **80** reinforces the second cross-member **36** such that in response to an impact event, the second cross-member **36** resists being crushed or deforming. Impact forces on one side of second cross-member **36** in FIG. **44**, will be first transmitted through reinforcement brackets **154** and **156** and then transmitted to the other side of second cross-member **36**. Reinforcement brackets **154** and **156** transmit a column load from one side of second cross-member **36** to the other side of second cross-member **36** and improve the strength of second cross-member **36**.

As shown in FIG. **36**, the upper attachment bracket **140** of the gap maintaining structure **78** is welded to an upper surface **36b** of the second cross-member **36**. As is discussed further below, the welds **W** that fix the upper attachment bracket **140** to the second cross-member **36** can be tuned to have a predetermined level of strength. Specifically, during normal operating conditions of the vehicle **10**, the welds **W** fixing the upper attachment bracket **140** to the second cross-member **36** have more than enough strength to retain the upper attachment bracket **140** in position. The upper attachment bracket **140** extends rearward away from the second cross-member **36**. However, during an impact event, where impact forces acting on the first structure **72** are transmitted to the second cross-member **36** (as described further below) the welds **W** between the upper attachment bracket **140** to the second cross-member **36** can be tuned to

release the upper attachment bracket **140** from the second cross-member **36**. One method of tuning the strength of welds **W** is to alter the overall length of one or more of the welds **W**.

As shown in FIG. **36**, the upper attachment bracket **140** of the gap maintaining structure **78** includes recessed areas **140a** and **140b**. The recessed area **140a** is dimensioned and configured to receive the forward end **130a** of the beam **130** of the second structure **76** and the recessed area **140b** is dimensioned and configured to receive a forward end of the secondary diagonal structure **136**, as described further below. It should be understood from the drawings that FIG. **36** shows an upper surface of the upper attachment bracket **140**, and that the recessed areas **140a** and **140b** define concaved areas of an underside surface of the upper attachment bracket **140** that is not visible in FIG. **36**. Rather, FIG. **36** shows convex areas corresponding to the recessed areas **140a** and **140b**.

FIG. **53** shows a lower surface of the upper attachment bracket **140** extending rearward from the second cross-member **36**. The secondary diagonal structure **136** is installed to the upper attachment bracket **140** within the recessed area **140b**. The recessed area **140a** is visible in FIG. **52**. Fasteners F_2 are installed to threaded the upper attachment bracket **140** in order to receive the forward end **130a** of the beam **130** of the second structure **76**.

The welds **W** that fix the upper attachment bracket **140** to the second cross-member **36** are provided with a first shear strength. The mechanical fasteners F_2 are provided with a second shear strength stronger than the first shear strength such that in response to the off-center impact event, the welds **W** release the upper attachment bracket **140** from the second cross-member **36** with the upper attachment bracket **140** remaining above the second cross-member **36** supporting the second structure **76** thereby limiting vertical movement of the second structure **76** relative to the second cross-member **36**.

The first lower attachment bracket **142** of the gap maintaining structure **78** is shown removed from the vehicle **10** in FIGS. **40** and **41**. The first lower attachment bracket **142** includes a U-shaped portion **142a**, a first angled portion **142b** and a second angled portion **142c**. As shown in FIG. **40**, the U-shaped portion **142a**, the first angled portion **142b** and the second angled portion **142c** are welded together. The U-shaped portion **142a** defines a recessed area that receives the rear end **112b** of the hollow beam **112**, as shown in FIGS. **35** and **36**.

The second lower attachment bracket **144** is attached to the mid portion **36a** of the second cross-member **36** via mechanical fasteners (not shown) or welding techniques. The second lower attachment bracket **144** has side walls **144a** and **144b** that contact opposite lateral sides of the hollow beam **112** of the first structure **72**, as shown in FIGS. **37** and **38**.

With the off-center impact reinforcement structure **12** installed to the frame **22** in the non-impacted state, there are several gaps maintained between the various elements of the first structure **72**, the second cross-member **36** and the second structure **74**. Specifically, as shown in FIG. **36** (in phantom) a gap G_3 is defined between the rear end **112b** and an adjacent front surface of the second cross-member **36**. Further, a gap G_4 is defined between a rear surface of the second cross-member **36** and a forward end **130a** of the beam **130** of the second structure **76**. Also, a gap G_5 is defined between a side surface of the beam **130** of the second structure **76** and a front end of the secondary diagonal structure **136**.

The gaps G_3 , G_4 and G_5 are maintained during normal operation of the vehicle **10** in the non-impacted state by the gap maintaining structure **78**. Specifically, the rear end **112b** of the hollow beam **112** is restricted against lateral movement being confined between the side walls **144a** and **144b** of the second lower attachment bracket **144**. Further, movement of the rear end **112b** of the hollow beam **112** is also limited by engagement with the recessed area defined by the U-shaped portion **142a** of the first lower attachment bracket **142**. Thus, the gap G_3 is maintained between the second cross-member **36** and the rear end **112b** of the hollow beam **112**.

It should be understood from the drawings and the description herein that the rear end **112b** of the hollow beam **112** can be welded to the second lower attachment bracket **144** or can be fixed thereto via mechanical fasteners. Alternatively, the hollow beam **112** can merely be retained in place by contact with the second lower attachment bracket and the first lower attachment bracket **142**. In the depicted embodiment, the rear end **112b** of the hollow beam **112** is not fixed to the first lower attachment bracket **142**, but rather is configured to move relative to the first lower attachment bracket **142** during an impact event, as is described further below.

The gap G_4 is maintained via a connection between the upper attachment bracket **140** and the forward end **130a** of the beam **130**. Specifically, the slots **130c** and **130d** are fitted to the fasteners F_2 of the upper attachment bracket **140**, as shown in phantom in FIG. **36**. The fasteners F_2 of the upper attachment bracket **140** are also shown in FIGS. **39** and **53**. The slots **130c** and **130d** are elongated, as shown in FIGS. **36** and **52**. Therefore, once the beam **130** is slid on to the fasteners F_2 , and moved to the position shown in FIG. **16**, the beam **130** is able to undergo sliding movement relative to the upper attachment bracket **140**. However, contact between the fasteners F_2 , and the beam **130** prevents or limits vertical movement of the beam **130** during normal operation of the vehicle **10**. As shown in FIGS. **51** and **54**, the beam **130** additionally includes a large slot **130e** and an aperture **130f**. As shown in FIG. **54**, once the beam **130** is slid on to the fasteners F_2 , the fasteners F_2 can be accessed by tools via the slot **130e** and the aperture **130f** and tightened to secure the beam **130** to the upper attachment bracket **140**.

It should be understood from the drawings and the description herein, that each of the upper attachment bracket **140**, the first lower attachment bracket **142** and the second lower attachment bracket **144** includes a recess or recessed area that retains a beam member of one of the first structure **72** and the second structure **76** in the non-impacted state. Further, the recess or recessed area of each of the upper attachment bracket **140**, the first lower attachment bracket **142** and the second lower attachment bracket **144** guides movement of the corresponding beam member of one of the first structure **72** and the second structure **76** in response to an impact event, as is described in further below.

The secondary diagonal structure **136** is a hollow beam member, as shown in FIGS. **35** and **55**. The forward end of the secondary diagonal structure **136** is attached to the upper attachment bracket **140** via two of the fasteners F_2 . The rearward end of the secondary diagonal structure **136** includes an end plate **136a** welded in place to the secondary diagonal structure **136**. The rearward end of the secondary diagonal structure **136** is coupled to the first side member **30** in a manner consistent with the attachment of the beam **130** to the second side member **32**. Description of the attachment structure fixing of the rearward end of the secondary diago-

nal structure **136** to the first side member **30** is provided below with a description of the rear attachment structure **134**.

The rear attachment structure **134** includes structural members that couple the rearward end **130b** of the beam **130** to the second side member **32**. Specifically, the rear attachment structure **134** includes a first bracket **160**, a second bracket **162** and a stopper bracket **164**. The secondary diagonal structure **136** is coupled to the first side member **30** using structures that are identical, except that they are mirror images thereof. Therefore, the description below of the coupling between the beam **130** to the second side member **32** (FIGS. **46-50**) applies equally to the coupling of the secondary diagonal structure **136** to the first side member **30** (FIGS. **55** and **56**). More specifically, the shape and installation of the first bracket **160**, the second bracket **162** and the stopper bracket **164** to the second side member **32** also applies to installation to the first side member **30**, except that the coupling to the first side member **30** is applied to the secondary diagonal structure **136**.

As shown in FIGS. **35** and **46-50**, the first bracket **160** is welded to an underside surface of the second side member **32**. The second bracket **162** is welded to an inboard side surface of the second side member **32**, with the stopper bracket **164** welded within a recess defined within the second bracket **162**. As shown in FIGS. **46** and **47** (and FIG. **55** with respect to the secondary diagonal structure **136**), the rearward end **130b** of the beam **130** extends into a pocket defined between the first bracket **160** and the second bracket **162**. Further, the beam **130** can be fixed to the second bracket by mechanical fasteners (not shown) or by welds (not shown) that are tuned to release the beam **130** in response to an impact event. Hence, the beam **130** is prevented from lateral, vertical and horizontal movement in the non-impacted state. A gap G_6 is maintained between the surface **132a** of the end plate **132** of the beam **130** and the stopper bracket **164** in the non-impacted state. However, as described below, in response to an impact event, the gap G_6 can be closed bringing the surface **132a** of end plate **132** of the beam **130** into contact with the stopper bracket **164**.

As shown in FIG. **35**, when fully installed in the non-impacted state, the beam **130** of the second structure **76** defines an angle α_6 relative to the second cross-member **36** that is between 35 and 60 degrees. In the depicted embodiment, the angle α_6 is between 40 and 50 degrees, and is preferably approximately 45 degrees.

A description is now provided of the stop structure **82** with specific reference to FIGS. **35** and **57-59**. As shown in FIGS. **35** and **57**, the stop structure **82** is installed to the first side member **30** adjacent to (but forward of) the third cross-member **38**. The stop structure **82** is also rigidly fixed to the body attachment flange **44**.

As shown in FIG. **58**, the stop structure **82** (a tire catcher) basically includes a lower plate **170**, an upper plate **172**, a reinforcement plate **174** (a mid-plate) and an outer plate **176** (a main plate). As shown in FIG. **58**, the lower plate **170**, the upper plate **172** and the reinforcement plate **174** are all horizontally oriented and are spaced apart from one another. The lower plate **170** defines a bottom of the stop structure **82** and the upper plate **172** defines a top of the stop structure **82**. The reinforcement plate **174** is located between the upper plate **172** and the lower plate **170**.

The outer plate **176** has first section **176a** attached to the first side member **30**, a second section **176b** defining a stop surface and a third section **176c** that wraps around the lower plate **170**, the upper plate **172** and the reinforcement plate **174** forming a box-like structure, with the reinforcement

23

plate 174 being concealed by the outer plate 176 or enclosed within the outer plate 176. The outer plate 176 is vertically oriented and the lower plate 170, the upper plate 172 and the reinforcement plate 174 are generally horizontally oriented in the non-impacted state. The plates of the stop structure 82 are welded to one another and welded to the first side member 30.

As shown in FIG. 35, at least the third section 176c of the outer plate 176 is rigidly attached to the body attachment flange 44 (a cabin attachment flange) via, for example, welding techniques.

As shown in FIG. 35, the second section 176b (the stop surface) is a forward facing surface. The second section 176b (the stop surface) of the stop structure 82 defines an angle as relative to a vehicle longitudinal direction that is between 110 and 130 degrees. In the depicted embodiment, the angle α_5 is approximately 120 degrees. The angle is selected such that in response to an off-center impact event that directs an impacting force to a front surface area of the front wheel T, the front wheel T pivots relative to the wheel support structure 48 and moves a rear surface area of the front wheel T into contact with the second section 176 (the stop surface) with the stop structure 82 absorbing at least a portion of the impacting force restricting further pivoting movement of the front wheel T, as shown in FIG. 59.

A further description of the effects of the off-center impact event (the small overlap test) on the push arm assembly 70 of the off-center impact reinforcement structure 12 is now provided with reference to all drawings.

As the push arm assembly 70 is being impacted, the gap G_1 between the main body 90 of the push arm assembly 70 closes causing the pivot bracket 96 to move into contact with the first cross-member 32, and collapsing the energy absorbing structure 94. The first cross-member 32 can undergo some deformation thereby closing the gap G_2 between the first cross-member 32 and hollow beam 112 of the first structure 72. Impact forces transmitted through the hollow beam 112 of the first structure 72 cause the end plate 116 at the rear end 112b of the hollow beam 112 to move toward the second cross-member 36, thereby closing the gap G_3 .

The hollow beam 112 is guided to move toward the second cross-member 36 during the impact event due to the recessed areas of the first and second lower attachment brackets 142 and 144. Specifically, the first and second lower attachment brackets 142 and 144 being rigidly fixed to the second cross-member 36 and having the U-shaped portion 142a and the side walls 144a and 144b, limit or prevent lateral in an inboard or outboard direction, and further limit or prevent vertical movement of the hollow beam 112 relative to the second cross-member 36. Therefore, impact forces close the gap G_3 thereby directing the impact force against the second cross-member 36.

Once the gap G_3 closes, the impact force is thereafter transmitted from the hollow beam 112 to the second cross-member 36. Within the second cross-member 36, the bulkhead structure 80 limits and/or prevents the second cross-member 36 from collapsing, although the second cross-member 36 can undergo limited overall bending deformation. Consequently, the second cross-member 36 bends such that force is transmitted through the second cross-member 36 via the upper attachment bracket 140.

Rearward movement of the second cross-member 36 and the upper attachment bracket 140 subsequently can do two things. First, the linearly aligned first and second slots 130c and 130d allow the beam 130 to slide relative to the fasteners F2 that are fixed to the upper attachment bracket 140, thereby closing the gap G_4 . Second, the welds W fixing the

24

upper attachment bracket 140 to the second cross-member 36 can release the upper attachment bracket 140 from fixed attachment to the second cross-member 36. Since the upper attachment bracket 140 remains above the second cross-member 36 even after release by the Welds W, the upper attachment bracket 140 can undergo some lateral movement relative to the second cross-member 36. However, the upper attachment bracket 140 prevents downward movement of the beam 130 since the fasteners F₂ remain fixed to the upper attachment bracket 140 and to the beam 130. Further, the gap G_5 defined between the beam 130 of the second structure 76 and the front end of the secondary diagonal structure 136 can also close.

Next, impact forces are transferred from the second cross-member 36 to the beam 130 and optionally to the secondary diagonal structure 136. Each of the beam 130 and the secondary diagonal structure 136 can undergo limited rearward movement due to the gap G_6 between the surface 132a of the end plate 132 of the beam 130 and the stopper bracket 164. Specifically, sliding movement of the beam 130 relative to the first and second brackets 160 and 162 causes the gap G_6 to close such that impact energy is transmitted from the beam 130 through the stopper bracket 164 and to the second side member 32. Similarly, the secondary diagonal structure 136 can transmit some of the impact energy to the first side member 30.

Further, during the impact event as impact forces from the stationary barrier B act on the push arm assembly 70, the impact forces also act on the front wheel T causing deformation of at least one of the first side member 30, the front suspension structure 48 and/or the lower control arm 52. The force acting on the front wheel T urge the front wheel T into contact with the stop structure 82.

The various movements of the components of the off-center impact reinforcement structure 12 have the effect of distributing the impact forces of the impact event throughout the frame 22 of the vehicle 10. The off-center impact reinforcement structure 12 also causes the vehicle 10 to move laterally away from the fixed barrier B during the impact event.

The various features of the vehicle 10, other than the off-center impact reinforcement structure 12 are conventional components that are well known in the art. Since such components are well known in the art, these structures will not be discussed or illustrated in detail herein. Rather, it will be apparent to those skilled in the art from this disclosure that the components can be any type of structure and/or programming that can be used to carry out the present invention.

General Interpretation of Terms

In understanding the scope of the present invention, the term "comprising" and its derivatives, as used herein, are intended to be open ended terms that specify the presence of the stated features, elements, components, groups, integers, and/or steps, but do not exclude the presence of other unstated features, elements, components, groups, integers and/or steps. The foregoing also applies to words having similar meanings such as the terms, "including", "having" and their derivatives. Also, the terms "part," "section," "portion," "member" or "element" when used in the singular can have the dual meaning of a single part or a plurality of parts. Also as used herein to describe the above embodiment(s), the following directional terms "forward", "rearward", "above", "downward", "vertical", "horizontal", "below" and "transverse" as well as any other similar

25

directional terms refer to those directions of a vehicle equipped with the vehicle structure. Accordingly, these terms, as utilized to describe the present invention should be interpreted relative to a vehicle equipped with the vehicle structure.

The term “configured” as used herein to describe a component, section or part of a device includes structure that is constructed to carry out the desired function.

The terms of degree such as “substantially”, “about” and “approximately” as used herein mean a reasonable amount of deviation of the modified term such that the end result is not significantly changed.

While only selected embodiments have been chosen to illustrate the present invention, it will be apparent to those skilled in the art from this disclosure that various changes and modifications can be made herein without departing from the scope of the invention as defined in the appended claims. For example, the size, shape, location or orientation of the various components can be changed as needed and/or desired. Components that are shown directly connected or contacting each other can have intermediate structures disposed between them. The functions of one element can be performed by two, and vice versa. The structures and functions of one embodiment can be adopted in another embodiment. It is not necessary for all advantages to be present in a particular embodiment at the same time. Every feature which is unique from the prior art, alone or in combination with other features, also should be considered a separate description of further inventions by the applicant, including the structural and/or functional concepts embodied by such feature(s). Thus, the foregoing descriptions of the embodiments according to the present invention are provided for illustration only, and not for the purpose of limiting the invention as defined by the appended claims and their equivalents.

What is claimed is:

1. A vehicle structure comprising:

a vehicle frame having a first side member, a second side member and a first cross-member, the first side member and the second side member having respective front ends, the first side member and the second side member extending rearward from the front ends, the first cross-member extending in a vehicle lateral direction from the first side member to the second side member at a location rearward of the front ends, the first cross-member further being rigidly fixed to each of the first side member and the second side member;

a front suspension structure coupled to the first side member adjacent to an intersection of the first side member and the first cross-member;

a push arm having a rear surface and a front surface, the rear surface of the push arm being located adjacent to and spaced apart from the front suspension structure defining a gap therebetween, the push arm extending forward and laterally outward such that the front surface of the push arm is located laterally outboard of and spaced apart from the front end of the first side member; and

a support bracket having a front section releasably attached to the push arm and a rear section releasably attached to the first cross-member of the vehicle frame adjacent to the intersection of the first side member and the first cross-member, the support bracket being configured such that in response to an off-center impact event against the front surface of the push arm, the

26

support bracket initially guides movement of the push arm in a rearward direction relative to the support bracket.

2. The vehicle structure according to claim 1, wherein the support bracket and the push arm are configured such that in response to the off-center impact event the push arm moves relative to the support bracket in a rearward direction toward the front suspension structure.

3. The vehicle structure according to claim 2, wherein the push arm is configured such that in response to the off-center impact event, after moving in the rearward direction relative to the support bracket, the push arm pivots relative to the intersection of the first side member and the first cross-member such that the front surface of the push arm pivots about an area along the front suspension structure with the front surface moving rearward and laterally away from the first side member.

4. The vehicle structure according to claim 1, wherein the support bracket conceals a portion of the intersection of the first side member and the first cross-member, and a portion of the front suspension.

5. The vehicle structure according to claim 1, wherein the support bracket is releasably attached to the push arm and the first cross-member of the vehicle frame via removable mechanical fasteners.

6. The vehicle structure according to claim 1, wherein the front section of the support bracket includes elongated slots that extend in a direction parallel to a lengthwise direction of the push arm.

7. The vehicle structure according to claim 6, wherein the support bracket is releasably attached to the push arm via removable mechanical fasteners that extend through a forward portion of the elongated slots in a non-impacted state, and in response to the off-center impact event rearward movement of the push arm is initially guided by movement of the mechanical fasteners along the elongated slots.

8. The vehicle structure according to claim 7, wherein the rear section of the support bracket attachment to the first cross-member has greater strength than the front section attachment to the push arm such that in response to the off-center impact event against the front surface of the push arm, the front section of the support bracket releases attachment of the push arm via the mechanical fasteners after rearward movement of the push arm along the elongated slots.

9. The vehicle structure according to claim 1, wherein the support bracket located beneath the first cross-member and a rear portion of the push arm in the non-impacted state.

10. The vehicle structure according to claim 1, wherein the support bracket is attached to a bottom surface of the first cross-member and is attached to the bottom surface of a rear portion of the push arm.

11. The vehicle structure according to claim 10, wherein the support bracket is attached to the bottom surface of the first cross-member via removable mechanical fasteners.

12. The vehicle structure according to claim 10, wherein the support bracket is attached to the bottom surface of the rear portion of the push arm via removable mechanical fasteners in the non-impacted state.

* * * * *