



(12) **United States Patent**  
**Parsons et al.**

(10) **Patent No.:** **US 10,729,948 B2**  
(45) **Date of Patent:** **\*Aug. 4, 2020**

(54) **GOLF CLUB HEADS AND METHODS TO MANUFACTURE GOLF CLUB HEADS**

(58) **Field of Classification Search**  
CPC ..... A63B 53/047; A63B 53/0475; A63B 2053/0491; A63B 2053/0416;  
(Continued)

(71) Applicant: **Parsons Xtreme Golf, LLC**,  
Scottsdale, AZ (US)

(56) **References Cited**

(72) Inventors: **Robert R. Parsons**, Scottsdale, AZ (US); **Michael R. Nicolette**, Scottsdale, AZ (US); **Bradley D. Schweigert**, Anthem, AZ (US)

U.S. PATENT DOCUMENTS

1,133,129 A 3/1915 Govan  
2,007,377 A \* 7/1935 Link ..... A63B 53/04  
473/350

(73) Assignee: **PARSOND XTREME GOLF, LLC**,  
Scottsdale, AZ (US)

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

DE 297 15 997 3/1998  
GB 2 249 031 4/1992

(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **15/462,281**

International Search Report and Written Opinion received in connection with corresponding application No. PCT/US2015/016668, dated May 14, 2015 (8 pages).

(22) Filed: **Mar. 17, 2017**

(Continued)

(65) **Prior Publication Data**

US 2017/0340928 A1 Nov. 30, 2017  
US 2018/0214748 A9 Aug. 2, 2018

*Primary Examiner* — Sebastiano Passaniti

**Related U.S. Application Data**

(57) **ABSTRACT**

(63) Continuation-in-part of application No. 15/209,364, filed on Jul. 13, 2016, which is a continuation of (Continued)

Embodiments of golf club heads and methods to manufacture golf club heads are generally described herein. In one example, a golf club head may include a body portion with a toe portion, a heel portion, a top portion, a sole portion, a back portion, and a front portion having a face portion with a face portion thickness extending between a front surface and a back surface. The body portion may be associated with a body portion volume. The golf club head may also include an interior cavity. The interior cavity may include an elastic polymer material. Other examples and embodiments may be described and claimed.


(51) **Int. Cl.**

**A63B 53/04** (2015.01)  
**A63B 60/02** (2015.01)  
**A63B 60/54** (2015.01)

**19 Claims, 21 Drawing Sheets**

(52) **U.S. Cl.**

CPC ..... **A63B 53/047** (2013.01); **A63B 53/0475** (2013.01); **A63B 53/0466** (2013.01);  
(Continued)



**Related U.S. Application Data**

application No. PCT/US2015/016666, filed on Feb. 19, 2015, which is a continuation of application No. 14/618,501, filed on Feb. 10, 2015, now Pat. No. 9,427,634, which is a continuation of application No. 14/589,277, filed on Jan. 5, 2015, now Pat. No. 9,421,437, which is a continuation of application No. 14/513,073, filed on Oct. 13, 2014, now Pat. No. 8,961,336, which is a continuation of application No. 14/498,603, filed on Sep. 26, 2014, now Pat. No. 9,199,143, and a continuation-in-part of application No. 15/188,718, filed on Jun. 21, 2016, now Pat. No. 9,610,481, and a continuation-in-part of application No. 29/587,027, filed on Dec. 8, 2016, now abandoned, and a continuation-in-part of application No. 29/594,025, filed on Feb. 15, 2017, now Pat. No. Des. 802,068, and a continuation-in-part of application No. 14/711,596, filed on May 13, 2015, now Pat. No. 9,675,853, and a continuation-in-part of application No. 15/263,018, filed on Sep. 12, 2016, now Pat. No. 9,878,220, which is a continuation of application No. 15/043,090, filed on Feb. 12, 2016, now Pat. No. 9,468,821, and a continuation-in-part of application No. 15/360,707, filed on Nov. 23, 2016, which is a continuation of application No. 15/043,106, filed on Feb. 12, 2016, now Pat. No. 9,533,201.

(60) Provisional application No. 62/343,739, filed on May 31, 2016, provisional application No. 62/433,661, filed on Dec. 13, 2016, provisional application No. 61/948,839, filed on Mar. 6, 2014, provisional application No. 61/952,470, filed on Mar. 13, 2014, provisional application No. 61/992,555, filed on May 13, 2014, provisional application No. 62/010,836, filed on Jun. 11, 2014, provisional application No. 62/011,859, filed on Jun. 13, 2014, provisional application No. 62/032,770, filed on Aug. 4, 2014, provisional application No. 62/041,538, filed on Aug. 25, 2014, provisional application No. 62/118,403, filed on Feb. 19, 2015, provisional application No. 62/159,856, filed on May 11, 2015, provisional application No. 62/209,780, filed on Aug. 25, 2015, provisional application No. 62/277,636, filed on Jan. 12, 2016, provisional application No. 62/275,443, filed on Jan. 6, 2016, provisional application No. 62/276,358, filed on Jan. 8, 2016, provisional application No. 62/321,652, filed on Apr. 12, 2016, provisional application No. 62/343,739, filed on May 31, 2016, provisional application No. 61/942,515, filed on Feb. 20, 2014, provisional application No. 61/945,560, filed on Feb. 27, 2014.

(52) **U.S. Cl.**  
 CPC ..... A63B 53/0487 (2013.01); A63B 60/02 (2015.10); A63B 60/54 (2015.10); A63B 2053/0408 (2013.01); A63B 2053/0412 (2013.01); A63B 2053/0416 (2013.01); A63B 2053/0445 (2013.01); A63B 2053/0479 (2013.01); A63B 2053/0491 (2013.01); A63B 2209/00 (2013.01)

(58) **Field of Classification Search**  
 CPC ..... A63B 2053/0445; A63B 2209/00; A63B 53/0466; A63B 2053/0412; A63B 2053/0408; A63B 53/0487; A63B 2053/0479; A63B 60/02; A63B 60/54

USPC ..... 473/324–350, 287–292  
 See application file for complete search history.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

D164,469	S	9/1951	Behrendt	
3,020,048	A	2/1962	Carroll	
D203,936	S	3/1966	Long	
3,266,805	A	8/1966	Bulla	
D215,101	S	9/1969	Sabat	
3,845,955	A *	11/1974	Solheim	A63B 53/04 473/226
D234,963	S	4/1975	Hirata	
D239,550	S	4/1976	Timbrook	
D240,054	S	5/1976	Meissler	
D261,167	S	10/1981	Swamson	
4,420,156	A *	12/1983	Campau	A63B 53/04 473/291
4,523,759	A	6/1985	Igarashi	
4,545,580	A	10/1985	Tomita et al.	
4,621,813	A *	11/1986	Solheim	A63B 53/04 473/290
4,653,756	A *	3/1987	Sato	A63B 53/04 473/327
D294,617	S	3/1988	Perkins	
4,754,977	A	7/1988	Sahm	
4,803,023	A	2/1989	Enomoto et al.	
4,824,116	A	4/1989	Nagamoto et al.	
4,883,274	A *	11/1989	Hsien	A63B 53/04 473/335
4,988,104	A	1/1991	Shiotani et al.	
5,011,151	A *	4/1991	Antonious	A63B 53/04 473/242
5,028,049	A	7/1991	McKeighen	
5,050,879	A *	9/1991	Sun	A63B 53/04 473/338
5,158,296	A	10/1992	Lee	
5,176,384	A	1/1993	Sata et al.	
5,203,565	A *	4/1993	Murray	A63B 53/04 473/242
5,213,328	A	5/1993	Long et al.	
D336,672	S	6/1993	Gorman	
5,244,211	A	9/1993	Lukasiewicz	
D353,862	S	12/1994	Saito	
D357,520	S	4/1995	Helmstetter et al.	
5,419,559	A	5/1995	Melanson et al.	
5,419,560	A	5/1995	Bamber	
D361,353	S	6/1995	Simmons	
5,425,535	A	6/1995	Gee	
5,447,311	A	9/1995	Viollaz et al.	
5,451,056	A	9/1995	Manning	
D362,884	S	10/1995	Blough et al.	
D362,885	S	10/1995	Blough et al.	
D362,887	S	10/1995	Blough et al.	
D370,514	S	6/1996	Blough et al.	
5,540,437	A	7/1996	Bamber	
5,547,426	A *	8/1996	Wood	A63B 53/04 473/290
5,637,045	A	6/1997	Igarashi	
5,647,808	A	7/1997	Hosokawa	
5,649,873	A	7/1997	Fuller	
5,669,830	A	9/1997	Bamber	
D389,541	S	1/1998	Huan-Chiang	
D395,476	S	6/1998	Pond et al.	
5,766,091	A	6/1998	Humphrey et al.	
5,766,092	A	6/1998	Mimeur et al.	
5,769,735	A	6/1998	Hosokawa	
5,772,527	A	6/1998	Liu	
D399,277	S	10/1998	Ezaki	
5,827,132	A	10/1998	Bamber	
5,833,551	A *	11/1998	Vincent	A63B 53/04 473/350
D408,485	S	4/1999	Takahashi et al.	
5,899,821	A	5/1999	Hsu et al.	
5,935,016	A	8/1999	Antonious	
D414,535	S	9/1999	Mertens	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,001,031	A	12/1999	San Juan		D617,406	S	6/2010	Carlyle et al.	
D421,080	S	2/2000	Chen		D618,293	S	6/2010	Foster et al.	
D421,472	S *	3/2000	Peterson	D21/759	7,744,484	B1	6/2010	Chao	
D426,276	S	6/2000	Besnard et al.		7,744,486	B2	6/2010	Hou et al.	
6,077,171	A	6/2000	Yoneyama		7,744,487	B2	6/2010	Tavares et al.	
6,162,133	A	12/2000	Peterson		D620,063	S *	7/2010	Llewellyn	D21/759
6,165,081	A	12/2000	Chou		D621,893	S	8/2010	Nicolette et al.	
D442,659	S	5/2001	Kubica et al.		7,775,905	B2 *	8/2010	Beach	A63B 53/0466 473/256
D443,008	S	5/2001	Kubica et al.		7,794,333	B2	9/2010	Wallans et al.	
6,231,458	B1	5/2001	Cameron et al.		7,798,917	B2	9/2010	Nguyen et al.	
6,238,302	B1	5/2001	Helmstetter et al.		7,803,068	B2	9/2010	Clausen et al.	
D445,862	S	7/2001	Ford		7,815,521	B2	10/2010	Ban et al.	
6,290,609	B1	9/2001	Takeda		7,846,040	B2	12/2010	Ban	
D449,866	S	10/2001	Miller		D633,967	S	3/2011	Carlyle et al.	
6,482,104	B1 *	11/2002	Gilbert	A63B 53/04 473/287	7,938,738	B2	5/2011	Roach	
D469,833	S	2/2003	Roberts et al.		D643,490	S	8/2011	Wada et al.	
D475,107	S	5/2003	Madore		8,062,150	B2	11/2011	Gilbert et al.	
D475,211	S	6/2003	Neil		8,088,025	B2	1/2012	Wahl et al.	
D476,048	S	6/2003	Cleveland et al.		8,092,319	B1	1/2012	Cackett et al.	
D478,949	S	8/2003	DeLaCruz		8,105,180	B1	1/2012	Cackett et al.	
6,638,182	B2	10/2003	Kosmatka		D658,248	S	4/2012	Nunez et al.	
6,695,712	B1 *	2/2004	Iwata	A63B 53/04 473/291	8,221,262	B1	7/2012	Cackett et al.	
6,695,714	B1	2/2004	Bliss et al.		8,246,487	B1	8/2012	Cackett et al.	
6,702,693	B2	3/2004	Bamber		8,328,662	B2	12/2012	Nakamura et al.	
6,780,123	B2	8/2004	Hasebe		8,376,878	B2	2/2013	Bennett et al.	
D497,963	S	11/2004	Toulon et al.		8,393,976	B2	3/2013	Soracco et al.	
6,811,496	B2	11/2004	Wahl et al.		D681,142	S	4/2013	Fossum et al.	
D499,779	S	12/2004	Mahaffey et al.		8,414,422	B2	4/2013	Peralta et al.	
6,830,519	B2	12/2004	Reed et al.		8,449,406	B1	5/2013	Frame et al.	
6,849,005	B2 *	2/2005	Rife	A63B 53/047 473/350	8,506,420	B2	8/2013	Hocknell et al.	
6,855,067	B2	2/2005	Solheim et al.		8,545,343	B2	10/2013	Boyd et al.	
D502,975	S	3/2005	Schweigert et al.		8,574,094	B2	11/2013	Nicolette et al.	
D503,204	S	3/2005	Nicolette et al.		8,657,700	B2	2/2014	Nicolette et al.	
D507,320	S	7/2005	Roberts et al.		8,663,026	B2	3/2014	Blowers et al.	
D508,545	S	8/2005	Roberts et al.		8,690,710	B2	4/2014	Nicolette et al.	
6,923,733	B2	8/2005	Chen		D707,316	S	6/2014	Aguayo et al.	
D514,183	S	1/2006	Schweigert et al.		D707,317	S	6/2014	Aguayo et al.	
D516,650	S	3/2006	Wolfe et al.		8,753,230	B2	6/2014	Stokke et al.	
D518,863	S	4/2006	Motoyoshi et al.		8,827,832	B2	9/2014	Breier et al.	
D523,501	S	6/2006	Nicolette et al.		8,827,833	B2	9/2014	Amano et al.	
D523,917	S	6/2006	Wolfe et al.		8,845,455	B2	9/2014	Ban et al.	
D524,859	S	7/2006	Yu et al.		D716,387	S	10/2014	Aguayo et al.	
7,121,956	B2	10/2006	Lo		D716,388	S	10/2014	Aguayo et al.	
7,128,663	B2	10/2006	Bamber		D722,352	S	2/2015	Nicolette et al.	
7,153,222	B2	12/2006	Gilbert et al.		D723,120	S	2/2015	Nicolette et al.	
D534,595	S	1/2007	Hasebe		8,961,336	B1	2/2015	Parsons et al.	
7,156,751	B2	1/2007	Wahl et al.		D726,265	S	4/2015	Nicolette	
7,169,057	B2 *	1/2007	Wood	A63B 53/0475 473/290	9,044,653	B2	6/2015	Wahl et al.	
7,182,698	B2	2/2007	Tseng		9,199,143	B1	12/2015	Parsons et al.	
7,207,900	B2	4/2007	Nicolette et al.		D748,214	S	1/2016	Nicolette et al.	
D543,601	S	5/2007	Kawami		D748,749	S	2/2016	Nicolette et al.	
7,281,991	B2	10/2007	Gilbert et al.		9,295,887	B2 *	3/2016	Radcliffe	A63B 53/047
D555,219	S	11/2007	Lin		9,314,677	B2 *	4/2016	Stites	A63B 53/0466
7,303,486	B2	12/2007	Imamoto		D756,471	S	5/2016	Nicolette et al.	
D559,932	S	1/2008	Belmont		9,421,437	B2	8/2016	Parsons et al.	
7,351,164	B2	4/2008	Schweigert et al.		9,427,634	B2	8/2016	Parsons et al.	
7,396,299	B2	7/2008	Nicolette et al.		9,517,393	B2	12/2016	Cardani et al.	
D584,370	S	1/2009	Cleveland et al.		2002/0037775	A1	3/2002	Keelan	
D594,518	S	6/2009	Schweigert		2002/0107087	A1	8/2002	Fagot	
7,568,985	B2 *	8/2009	Beach	A63B 53/0466 473/336	2003/0139222	A1 *	7/2003	Vadersen	A63B 53/047 473/291
7,588,502	B2	9/2009	Nishino		2003/0139226	A1	7/2003	Cheng et al.	
D604,783	S	11/2009	Nicolette et al.		2003/0176231	A1	9/2003	Hasebe	
7,611,424	B2	11/2009	Nagai et al.		2004/0204263	A1	10/2004	Fagot et al.	
D606,605	S	12/2009	Wada et al.		2004/0266550	A1	12/2004	Gilbert et al.	
D607,070	S	12/2009	Wada et al.		2005/0009632	A1	1/2005	Schweigert et al.	
D607,071	S	12/2009	Wada et al.		2005/0014573	A1 *	1/2005	Lee	A63B 53/0475 473/291
7,658,686	B2	2/2010	Soracco		2005/0043117	A1	2/2005	Gilbert et al.	
D612,438	S	3/2010	Carlyle et al.		2005/0119066	A1	6/2005	Stites et al.	
D612,439	S	3/2010	Carlyle et al.		2005/0164802	A1 *	7/2005	Wood	A63B 53/0475 473/287
					2005/0239569	A1	10/2005	Best et al.	
					2005/0277485	A1	12/2005	Hou et al.	
					2006/0111200	A1	5/2006	Poynor	
					2007/0032308	A1	2/2007	Fagot et al.	
					2007/0225084	A1	9/2007	Schweigert et al.	
					2008/0058113	A1	3/2008	Nicolette et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0188322	A1	8/2008	Anderson et al.	
2008/0300065	A1	12/2008	Schweigert	
2008/0318705	A1	12/2008	Clausen et al.	
2008/0318706	A1	12/2008	Larson	
2009/0029790	A1	1/2009	Nicolette et al.	
2009/0075751	A1*	3/2009	Gilbert .....	A63B 53/047 473/332
2009/0131199	A1*	5/2009	Gilbert .....	A63B 53/047 473/332
2010/0093460	A1	4/2010	Gilbert et al.	
2010/0130306	A1	5/2010	Schweigert	
2010/0178999	A1	7/2010	Nicolette et al.	
2011/0111883	A1	5/2011	Cackett	
2011/0165963	A1	7/2011	Cackett et al.	
2011/0269567	A1	11/2011	Ban et al.	
2011/0294596	A1	12/2011	Ban	
2013/0137532	A1	5/2013	Deshmukh et al.	
2013/0225319	A1	8/2013	Kato	
2013/0281226	A1	10/2013	Ban	
2013/0288823	A1	10/2013	Hebreo	
2013/0303303	A1	11/2013	Ban	
2013/0310192	A1	11/2013	Wahl et al.	
2013/0316842	A1	11/2013	Demkowski	
2014/0080621	A1	3/2014	Nicolette et al.	
2014/0080632	A1*	3/2014	Deshmukh .....	A63B 53/0466 473/342
2014/0128175	A1	5/2014	Jertson et al.	
2014/0274441	A1	9/2014	Greer	
2014/0274442	A1	9/2014	Honea et al.	
2014/0274451	A1	9/2014	Knight et al.	
2015/0151175	A1*	6/2015	Lytle .....	A63B 53/047 473/291
2015/0182816	A1*	7/2015	Radcliffe .....	A63B 53/047 473/324
2015/0231454	A1	8/2015	Parsons et al.	
2015/0231806	A1	8/2015	Parsons et al.	

FOREIGN PATENT DOCUMENTS

JP	H10-127832	5/1998
JP	H10-277187	10/1998
JP	2001-346924	12/2001
JP	2002143356	5/2002
JP	2004-313777	11/2004
WO	92/15374	9/1992

OTHER PUBLICATIONS

U.S. Appl. No. 29/512,313, Nicolette, "Golf Club Head," filed Dec. 18, 2014.

Kozuchowski, Zak, "Callaway Mack Daddy 2 PM Grind Wedges" (<http://www.golfwrz.com/276203/callaway-mack-daddy-2-pm-grind-wedges/>), www.golfwrz.com, GolfWRX Holdings, LLC, published Jan. 21, 2015.

Wall, Jonathan, "Details: Phil's Prototype Mack Daddy PM-Grind Wedge," (<http://www.pgatour.com/equipmentreport/2015/01/21/callaway-wedge.html>), www.pgatour.com, PGA Tour, Inc., published Jan. 21, 2015.

Taylor Made Golf Company, Inc., [https://taylormadegolf.com/on/demandware.static/-/Sites-TMaG-Library/default/v1459859109590/docs/productspecs/TM\\_S2013\\_Catalog18.pdf](https://taylormadegolf.com/on/demandware.static/-/Sites-TMaG-Library/default/v1459859109590/docs/productspecs/TM_S2013_Catalog18.pdf), published Jan. 2013.

RocketBladez Press Release, "GolfBalled", [http://golfballed.com/index.php?option=com\\_content&view=article&id=724:taylormade-](http://golfballed.com/index.php?option=com_content&view=article&id=724:taylormade-) . . . Oct. 13, 2017, published Jan. 3, 2013.

International Search Report and Written Opinion received in connection with corresponding application No. PCT/US17/23401, dated Sep. 22, 2017 (13 pages).

International Search Report and Written Opinion Received in Connection With Corresponding PCT Application Serial No. PCT/US2017/028401, dated Jun. 27, 2019.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3






FIG. 4






FIG. 7






FIG. 8








FIG. 11




FIG. 12






FIG. 13






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25



2600




FIG. 26

2700




FIG. 27




FIG. 28




FIG. 29








FIG. 30








FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40






FIG. 41

## GOLF CLUB HEADS AND METHODS TO MANUFACTURE GOLF CLUB HEADS

### CROSS REFERENCE

This application claims the benefit of U.S. Provisional Application No. 62/343,739, filed May 31, 2016, and U.S. Provisional Application No. 62/433,661, filed Dec. 13, 2016. This application is a continuation-in-part of U.S. patent application Ser. No. 15/188,718, filed Jun. 21, 2016, a continuation-in-part of U.S. patent application Ser. No. 29/587,027, filed Dec. 8, 2016, and a continuation-in-part of U.S. patent Ser. No. 29/594,025, filed Feb. 15, 2017. The disclosures of the referenced applications are incorporated herein by reference.

### COPYRIGHT AUTHORIZATION

The present disclosure may be subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the present disclosure and its related documents, as they appear in the Patent and Trademark Office patent files or records, but otherwise reserves all applicable copyrights.

### FIELD

The present disclosure generally relates to golf equipment, and more particularly, to golf club heads and methods to manufacturing golf club heads.

### BACKGROUND

Various materials (e.g., steel-based materials, titanium-based materials, tungsten-based materials, etc.) may be used to manufacture golf club heads. By using multiple materials to manufacture golf club heads, the position of the center of gravity (CG) and/or the moment of inertia (MOI) of the golf club heads may be optimized to produce certain trajectory and spin rate of a golf ball.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a front view of a golf club head according to an embodiment of the apparatus, methods, and articles of manufacture described herein.

FIG. 2 depicts a rear view of the example golf club head of FIG. 1.

FIG. 3 depicts a top view of the example golf club head of FIG. 1.

FIG. 4 depicts a bottom view of the example golf club head of FIG. 1.

FIG. 5 depicts a left view of the example golf club head of FIG. 1.

FIG. 6 depicts a right view of the example golf club head of FIG. 1.

FIG. 7 depicts a cross-sectional view of the example golf club head of FIG. 1 along line 7-7.

FIG. 8 depicts a cross-sectional view of the example golf club head of FIG. 1 along line 8-8.

FIG. 9 depicts a cross-sectional view of the example golf club head of FIG. 1 along line 9-9.

FIG. 10 depicts another rear view of the example golf club head of FIG. 1.

FIG. 11 depicts a top view of a weight portion associated with the example golf club head of FIG. 1.

FIG. 12 depicts a side view of a weight portion associated with the example golf club head of FIG. 1.

FIG. 13 depicts a side view of another weight portion associated with the example golf club head of FIG. 1.

FIG. 14 depicts a rear view of a body portion of the example golf club head of FIG. 1.

FIG. 15 depicts a cross-sectional view of a face portion of the example golf club head of FIG. 1.

FIG. 16 depicts a cross-sectional view of another face portion of the example golf club head of FIG. 1.

FIG. 17 depicts one manner in which the example golf club head described herein may be manufactured.

FIG. 18 depicts another cross-sectional view of the example golf club head of FIG. 1 along line 18-18.

FIG. 19 depicts a front view of a face portion of the example golf club head of FIG. 1.

FIG. 20 depicts a back view of the face portion of FIG. 19.

FIG. 21 depicts a cross-sectional view of an example channel of the face portion of FIG. 19.

FIG. 22 depicts a cross-sectional view of another example channel of the face portion of FIG. 19.

FIG. 23 depicts a cross-sectional view of yet another example channel of the face portion of FIG. 19.

FIG. 24 depicts a cross-sectional view of yet another example channel of the face portion of FIG. 19.

FIG. 25 depicts a back view of another example face portion of the example golf club head of FIG. 1.

FIG. 26 depicts a back view of yet another example face portion of the example golf club head of FIG. 1.

FIG. 27 depicts a back view of yet another example face portion of the example golf club head of FIG. 1.

FIG. 28 depicts a cross-sectional view of the example golf club head of FIG. 1.

FIG. 29 depicts another manner in which an example golf club head described herein may be manufactured.

FIG. 30 depicts yet another manner in which an example golf club head described herein may be manufactured.

FIG. 31 depicts a rear view of a golf club head according to an embodiment of the apparatus, methods, and articles of manufacture described herein.

FIG. 32 depicts a rear view of the golf club head of FIG. 31.

FIG. 33 depicts a front view of a golf club head according to an embodiment of the apparatus, methods, and articles of manufacture described herein.

FIG. 34 depicts a rear view of the example golf club head of FIG. 33.

FIG. 35 depicts a rear perspective view of the example golf club head of FIG. 33.

FIG. 36 depicts an enlarged view of area 36 of the example golf club head of FIG. 35.

FIG. 37 depicts a perspective toe-side view of the example golf club head of FIG. 33.

FIG. 38 depicts a perspective heel-side view of the example golf club head of FIG. 33.

FIG. 39 depicts yet another manner in which an example golf club head described herein may be manufactured.

FIG. 40 depicts yet another manner in which an example golf club head described herein may be manufactured.

FIG. 41 depicts an example of curing a bonding agent.

For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures may not be depicted to scale. For example, the dimensions of some of the elements in the figures may be

exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure.

#### DESCRIPTION

In general, golf club heads and methods to manufacture golf club heads are described herein. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In the example of FIGS. 1-14, a golf club head **100** may include a body portion **110** (FIG. 14), and two or more weight portions, generally shown as a first set of weight portions **120** (e.g., shown as weight portions **121**, **122**, **123**, and **124**) and a second set of weight portions **130** (e.g., shown as weight portions **131**, **132**, **133**, **134**, **135**, **136**, and **137**). The body portion **110** may include a toe portion **140**, a heel portion **150**, a front portion **160**, a back portion **170**, a top portion **180**, and a sole portion **190**. The body portion **110** may be made of a first material whereas the first and second sets of weight portions **120** and **130**, respectively, may be made of a second material. The first and second materials may be similar or different materials. For example, the body portion **110** may be partially or entirely made of a steel-based material (e.g., 17-4 PH stainless steel, Nitronic® 50 stainless steel, maraging steel or other types of stainless steel), a titanium-based material, an aluminum-based material (e.g., a high-strength aluminum alloy or a composite aluminum alloy coated with a high-strength alloy), any combination thereof, and/or other suitable types of materials. The first and second sets of weight portions **120** and **130**, respectively, may be partially or entirely made of a high-density material such as a tungsten-based material or other suitable types of materials. Alternatively, the body portion **110** and/or the first and second sets of weight portions **120** and **130**, respectively, may be partially or entirely made of a non-metal material (e.g., composite, plastic, etc.). The apparatus, methods, and articles of manufacture are not limited in this regard.

The golf club head **100** may be an iron-type golf club head (e.g., a 1-iron, a 2-iron, a 3-iron, a 4-iron, a 5-iron, a 6-iron, a 7-iron, an 8-iron, a 9-iron, etc.) or a wedge-type golf club head (e.g., a pitching wedge, a lob wedge, a sand wedge, an n-degree wedge such as 44 degrees (°), 48°, 52°, 56°, 60°, etc.). Although FIGS. 1-10 may depict a particular type of club head, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of club heads (e.g., a driver-type club head, a fairway wood-type club head, a hybrid-type club head, a putter-type club head, etc.). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The toe portion **140** and the heel portion **150** may be on opposite ends of the body portion **110**. The heel portion **150** may include a hosel portion **155** configured to receive a shaft (not shown) with a grip (not shown) on one end and the golf club head **100** on the opposite end of the shaft to form a golf club.

The front portion **160** may include a face portion **162** (e.g., a strike face). The face portion **162** may include a front surface **164** and a back surface **166**. The front surface **164** may include one or more grooves **168** extending between the toe portion **140** and the heel portion **150**. While the figures may depict a particular number of grooves, the apparatus, methods, and articles of manufacture described herein may include more or less grooves. The face portion **162** may be used to impact a golf ball (not shown). The face portion **162** may be an integral portion of the body portion **110**. Alternatively, the face portion **162** may be a separate piece or an

insert coupled to the body portion **110** via various manufacturing methods and/or processes (e.g., a bonding process such as adhesive, a welding process such as laser welding, a brazing process, a soldering process, a fusing process, a mechanical locking or connecting method, any combination thereof, or other suitable types of manufacturing methods and/or processes). The face portion **162** may be associated with a loft plane that defines the loft angle of the golf club head **100**. The loft angle may vary based on the type of golf club (e.g., a long iron, a middle iron, a short iron, a wedge, etc.). In one example, the loft angle may be between five degrees and seventy-five degrees. In another example, the loft angle may be between twenty degrees and sixty degrees. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As illustrated in FIG. 14, the back portion **170** may include a back wall portion **1410** with one or more exterior weight ports along a periphery of the back portion **170**, generally shown as a first set of exterior weight ports **1420** (e.g., shown as weight ports **1421**, **1422**, **1423**, and **1424**) and a second set of exterior weight ports **1430** (e.g., shown as weight ports **1431**, **1432**, **1433**, **1434**, **1435**, **1436**, and **1437**). Each exterior weight port may be associated with a port diameter. In one example, the port diameter may be about 0.25 inch (6.35 millimeters). Any two adjacent exterior weight ports of the first set of exterior weight ports **1420** may be separated by less than the port diameter. In a similar manner, any two adjacent exterior weight ports of the second set of exterior weight ports **1430** may be separated by less than the port diameter. The first and second exterior weight ports **1420** and **1430** may be exterior weight ports configured to receive one or more weight portions. In particular, each weight portion of the first set **120** (e.g., shown as weight portions **121**, **122**, **123**, and **124**) may be disposed in a weight port located at or proximate to the toe portion **140** and/or the top portion **180** on the back portion **170**. For example, the weight portion **121** may be partially or entirely disposed in the weight port **1421**. In another example, the weight portion **122** may be disposed in a weight port **1422** located in a transition region between the top portion **180** and the toe portion **140** (e.g., a top-and-toe transition region). Each weight portion of the second set **130** (e.g., shown as weight portions **131**, **132**, **133**, **134**, **135**, **136**, and **137**) may be disposed in a weight port located at or proximate to the toe portion **140** and/or the sole portion **190** on the back portion **170**. For example, the weight portion **135** may be partially or entirely disposed in the weight port **1435**. In another example, the weight portion **136** may be disposed in a weight port **1436** located in a transition region between the sole portion **190** and the toe portion **140** (e.g., a sole-and-toe transition region). As described in detail below, the first and second sets of weight portions **120** and **130**, respectively, may be coupled to the back portion **170** of the body portion **110** with various manufacturing methods and/or processes (e.g., a bonding process, a welding process, a brazing process, a mechanical locking method, any combination thereof, or other suitable manufacturing methods and/or processes).

Alternatively, the golf club head **100** may not include (i) the first set of weight portions **120**, (ii) the second set of weight portions **130**, or (iii) both the first and second sets of weight portions **120** and **130**. In particular, the back portion **170** of the body portion **110** may not include weight ports at or proximate to the top portion **180** and/or the sole portion **190**. For example, the mass of the first set of weight portions **120** (e.g., 3 grams) and/or the mass of the second set of weight portions **130** (e.g., 16.8 grams) may be integral

part(s) the body portion **110** instead of separate weight portion(s). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The first and second sets of weight portions **120** and **130**, respectively, may have similar or different physical properties (e.g., color, shape, size, density, mass, volume, etc.). As a result, the first and second sets of weight portions **120** and **130**, respectively, may contribute to the ornamental design of the golf club head **100**. In the illustrated example as shown in FIG. **11**, each of the weight portions of the first and second sets **120** and **130**, respectively, may have a cylindrical shape (e.g., a circular cross section). Alternatively, each of the weight portions of the first set **120** may have a first shape (e.g., a cylindrical shape) whereas each of the weight portions of the second set **130** may have a second shape (e.g., a cubical shape). In another example, the first set of weight portions **120** may include two or more weight portions with different shapes (e.g., the weight portion **121** may be a first shape whereas the weight portion **122** may be a second shape different from the first shape). Likewise, the second set of weight portions **130** may also include two or more weight portions with different shapes (e.g., the weight portion **131** may be a first shape whereas the weight portion **132** may be a second shape different from the first shape). Although the above examples may describe weight portions having a particular shape, the apparatus, methods, and articles of manufacture described herein may include weight portions of other suitable shapes (e.g., a portion of or a whole sphere, cube, cone, cylinder, pyramid, cuboidal, prism, frustum, or other suitable geometric shape). While the above examples and figures may depict multiple weight portions as a set of weight portions, each set of the first and second sets of weight portions **120** and **130**, respectively, may be a single piece of weight portion. In one example, the first set of weight portions **120** may be a single piece of weight portion instead of a series of four separate weight portions. In another example, the second set of weight portions **130** may be a single piece of weight portion instead of a series of seven separate weight portions. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIGS. **12** and **13**, for example, the first and second sets of weight portions **120** and **130**, respectively, may include threads, generally shown as **1210** and **1310**, respectively, to engage with correspondingly configured threads in the weight ports to secure in the weight ports of the back portion **170** (generally shown as **1420** and **1430** in FIG. **14**). For example, each weight portion of the first and second sets of weight portions **120** and **130**, respectively, may be a screw. The first and second sets of weight portions **120** and **130**, respectively, may not be readily removable from the body portion **110** with or without a tool. Alternatively, the first and second sets of weight portions **120** and **130**, respectively, may be readily removable (e.g., with a tool) so that a relatively heavier or lighter weight portion may replace one or more of the weight portions of the first and second sets **120** and **130**, respectively. In another example, the first and second sets of weight portions **120** and **130**, respectively, may be secured in the weight ports of the back portion **170** with epoxy or adhesive so that the first and second sets of weight portions **120** and **130**, respectively, may not be readily removable. In yet another example, the first and second sets of weight portions **120** and **130**, respectively, may be secured in the weight ports of the back portion **170** with both epoxy and threads so that the first and second sets of weight portions **120** and **130**, respectively,

may not be readily removable. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As mentioned above, the first and second sets of weight portions **120** and **130**, respectively, may be similar in some physical properties but different in other physical properties. As illustrated in FIGS. **11-13**, for example, each of the weight portions of the first and second sets **120** and **130**, respectively, may have a diameter **1110** of about 0.25 inch (6.35 millimeters) but the first and second sets of weight portions **120** and **130**, respectively, may be different in height. In particular, each of the weight portions of the first set **120** may be associated with a first height **1220** (FIG. **12**), and each of the weight portion of the second set **130** may be associated with a second height **1320** (FIG. **13**). The first height **1220** may be relatively shorter than the second height **1320**. In one example, the first height **1220** may be about 0.125 inch (3.175 millimeters) whereas the second height **1320** may be about 0.3 inch (7.62 millimeters). In another example, the first height **1220** may be about 0.16 inch (4.064 millimeters) whereas the second height **1320** may be about 0.4 inch (10.16 millimeters). Alternatively, the first height **1220** may be equal to or greater than the second height **1320**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIG. **10**, for example, the golf club head **100** may be associated with a ground plane **1010**, a horizontal midplane **1020**, and a top plane **1030**. In particular, the ground plane **1010** may be a tangential plane to the sole portion **190** of the golf club head **100** when the golf club head **100** is at an address position (e.g., the golf club head **100** is aligned to strike a golf ball). A top plane **1030** may be a tangential plane to the top portion of the **180** of the golf club head **100** when the golf club head **100** is at the address position. The ground and top planes **1010** and **1030**, respectively, may be substantially parallel to each other. The horizontal midplane **1020** may be vertically halfway between the ground and top planes **1010** and **1030**, respectively.

To provide optimal perimeter weighting for the golf club head **100**, the first set of weight portions **120** (e.g., weight portions **121**, **122**, **123**, and **124**) may be configured to counter-balance the weight of the hosel **155**. For example, as shown in FIG. **10**, the first set of weight portions **120** (e.g., weight portions **121**, **122**, **123** and **124**) may be located near the periphery of the body portion **110** and extend from the top portion to a transition region **145** between the top portion **180** and the toe portion **140**, and from the transition region **145** to the toe portion **140**. In other words, the first set of weight portions **120** may be located on the golf club head **100** at a generally opposite location relative to the hosel **155**. According to one example, at least a portion of the first set of weight portions **120** may be located near the periphery of the body portion **110** and extend through the transition region **145**. According to another example, at least a portion of the first set of weight portions **120** may extend near the periphery of the body portion **110** and extend along a portion of the top portion **180**. According to another example, at least a portion of the first set of weight portions **120** may extend near the periphery of the body portion **110** and extend along a portion of the toe portion **140**. The first set of weight portions **120** may be above the horizontal midplane **1020** of the golf club head **100**. At least a portion of the first set of weight portions **120** may be near the toe portion **140** to increase the moment of inertia of the golf club head **100** about a vertical axis of the golf club head **100** that extends through the center of gravity of the golf club head **100**.

Accordingly, the first set of weight portions **120** may be near the periphery of the body portion **110** and extend through the top portion **180**, the toe portion **140** and/or the transition region **145** to counter-balance the weight of the hosel **155** and/or increase the moment of inertia of the golf club head **100**. The locations of the first set of weight portions **120** (i.e., the locations of the first set of exterior weight ports **1420**) and the physical properties and materials of construction of the weight portions of the first set of weight portions **120** may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic characteristics of the golf club head **100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The second set of weight portions **130** (e.g., weight portions **131**, **132**, **133**, **134**, **135**, **136**, and **137**) may be configured to place the center of gravity of the golf club head **100** at an optimal location and optimize the moment of inertia of the golf club head about a vertical axis that extends through the center of gravity of the golf club head **100**. Referring to FIG. **10**, all or a substantial portion of the second set of weight portions **130** may be generally near the sole portion **190**. For example, the second set of weight portions **130** (e.g., weight portions **131**, **132**, **133**, **134**, **135**, **136**, and **137**) may be near the periphery of the body portion **110** and extend from the sole portion **190** to the toe portion **140**. As shown in the example of FIG. **10**, the weight portions **131**, **132**, **133**, and **134** may be located near the periphery of the body portion **110** and extend along the sole portion **190** to lower the center of gravity of the golf club head **100**. The weight portions **135**, **136** and **137** may be located near the periphery of the body portion **110** and extend from the sole portion **190** to the toe portion **140** through a transition region **147** between the sole portion **190** and the toe portion **140** to lower the center of gravity and increase the moment of inertia of the golf club head **100** about a vertical axis that extends through the center of gravity. To lower the center of gravity of the golf club head **100**, all or a portion of the second set of weight portions **130** may be located closer to the sole portion **190** than to the horizontal midplane **1020**. For example, the weight portions **131**, **132**, **133**, **134**, **135**, and **136** may be closer to the sole portion **190** than to the horizontal midplane **1020**. The locations of the second set of weight portions **130** (i.e., the locations of the second set of exterior weight ports **1430**) and the physical properties and materials of construction of the weight portions of the second set of weight portions **130** may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic characteristics of the golf club head **100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Turning to FIGS. **7-9**, for example, the first and second sets of weight portions **120** and **130**, respectively, may be located away from the back surface **166** of the face portion **162** (e.g., not directly coupled to each other). That is, the first and second sets of weight portions **120** and **130**, respectively, and the back surface **166** may be partially or entirely separated by an interior cavity **700** of the body portion **110**. As shown in FIG. **14**, for example, each exterior weight port of the first and second sets of exterior weight ports **1420** and **1430** may include an opening (e.g., generally shown as **720** and **730**) and a port wall (e.g., generally shown as **725** and **735**). The port walls **725** and **735** may be integral portions of the back wall portion **1410** (e.g., a section of the back wall

portion **1410**). Each of the openings **720** and **730** may be configured to receive a weight portion such as weight portions **121** and **135**, respectively. The opening **720** may be located at one end of the weight port **1421**, and the port wall **725** may be located or proximate to an opposite end of the weight port **1421**. In a similar manner, the opening **730** may be located at one end of the weight port **1435**, and the port wall **735** may be located at or proximate to an opposite end of the weight port **1435**. The port walls **725** and **735** may be separated from the face portion **162** (e.g., separated by the interior cavity **700**). The port wall **725** may have a distance **726** from the back surface **166** of the face portion **162** as shown in FIG. **9**. The port wall **735** may have a distance **736** from the back surface **166** of the face portion **162**. The distances **726** and **736** may be determined to optimize the location of the center of gravity of the golf club head **100** when the first and second sets of weight ports **1420** and **1430**, respectively, receive weight portions as described herein. According to one example, the distance **736** may be greater than the distance **726** so that the center of gravity of the golf club head **100** is moved toward the back portion **170**. As a result, a width **740** of a portion of the interior cavity **700** below the horizontal midplane **1020** may be greater than a width **742** of the interior cavity **700** above the horizontal midplane **1020**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As discussed herein, the center of gravity (CG) of the golf club head **100** may be relatively farther back away from the face portion **162** and relatively lower towards a ground plane (e.g., one shown as **1010** in FIG. **10**) with all or a substantial portion of the second set of weight portions **130** being closer to the sole portion **190** than to the horizontal midplane **1020** and the first and second sets of weight portions **120** and **130**, respectively being away from the back surface **166** than if the second set of weight portions **130** were directly coupled to the back surface **166**. The locations of the first and second sets of weight ports **1420** and **1430** and the physical properties and materials of construction of the weight portions of the first and second sets of weight portions **120** and **130**, respectively, may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic characteristics of the golf club head **100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

While the figures may depict weight ports with a particular cross-section shape, the apparatus, methods, and articles of manufacture described herein may include weight ports with other suitable cross-section shapes. In one example, the weight ports of the first and/or second sets of weight ports **1420** and **1430** may have U-like cross-section shape. In another example, the weight ports of the first and/or second set of weight ports **1420** and **1430** may have V-like cross-section shape. One or more of the weight ports associated with the first set of weight portions **120** may have a different cross-section shape than one or more weight ports associated with the second set of weight portions **130**. For example, the weight port **1421** may have a U-like cross-section shape whereas the weight port **1435** may have a V-like cross-section shape. Further, two or more weight ports associated with the first set of weight portions **120** may have different cross-section shapes. In a similar manner, two or more weight ports associated with the second set of weight portions **130** may have different cross-section shapes. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The first and second sets of weight portions **120** and **130**, respectively, may be similar in mass (e.g., all of the weight portions of the first and second sets **120** and **130**, respectively, weigh about the same). Alternatively, the first and second sets of weight portions **120** and **130**, respectively, may be different in mass individually or as an entire set. In particular, each of the weight portions of the first set **120** (e.g., shown as **121**, **122**, **123**, and **124**) may have relatively less mass than any of the weight portions of the second set **130** (e.g., shown as **131**, **132**, **133**, **134**, **135**, **136**, and **137**). For example, the second set of weight portions **130** may account for more than 50% of the total mass from exterior weight portions of the golf club head **100**. As a result, the golf club head **100** may be configured to have at least 50% of the total mass from exterior weight portions disposed below the horizontal midplane **1020**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the golf club head **100** may have a mass in the range of about 220 grams to about 330 grams based on the type of golf club (e.g., a 4-iron versus a lob wedge). The body portion **110** may have a mass in the range of about 200 grams to about 310 grams with the first and second sets of weight portions **120** and **130**, respectively, having a mass of about 20 grams (e.g., a total mass from exterior weight portions). Each of the weight portions of the first set **120** may have a mass of about one gram (1.0 g) whereas each of the weight portions of the second set **130** may have a mass of about 2.4 grams. The sum of the mass of the first set of weight portions **120** may be about 3 grams whereas the sum of the mass of the first set of weight portions **130** may be about 16.8 grams. The total mass of the second set of weight portions **130** may weigh more than five times as much as the total mass of the first set of weight portions **120** (e.g., a total mass of the second set of weight portions **130** of about 16.8 grams versus a total mass of the first set of weight portions **120** of about 3 grams). The golf club head **100** may have a total mass of 19.8 grams from the first and second sets of weight portions **120** and **130**, respectively (e.g., sum of 3 grams from the first set of weight portions **120** and 16.8 grams from the second set of weight portions **130**). Accordingly, the first set of weight portions **120** may account for about 15% of the total mass from exterior weight portions of the golf club head **100** whereas the second set of weight portions **130** may be account for about 85% of the total mass from exterior weight portions of the golf club head **100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

By coupling the first and second sets of weight portions **120** and **130**, respectively, to the body portion **110** (e.g., securing the first and second sets of weight portions **120** and **130** in the weight ports on the back portion **170**), the location of the center of gravity (CG) and the moment of inertia (MOI) of the golf club head **100** may be optimized. In particular, as described herein, the first and second sets of weight portions **120** and **130**, respectively, may lower the location of the CG towards the sole portion **190** and further back away from the face portion **162**. Further, the MOI may be higher as measured about a vertical axis extending through the CG (e.g., perpendicular to the ground plane **1010**). The MOI may also be higher as measured about a horizontal axis extending through the CG (e.g., extending towards the toe and heel portions **150** and **160**, respectively, of the golf club head **100**). As a result, the club head **100** may provide a relatively higher launch angle and a relatively lower spin rate than a golf club head without the first and second sets of weight portions **120** and **130**, respectively.

The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Alternatively, two or more weight portions in the same set may be different in mass. In one example, the weight portion **121** of the first set **120** may have a relatively lower mass than the weight portion **122** of the first set **120**. In another example, the weight portion **131** of the second set **130** may have a relatively lower mass than the weight portion **135** of the second set **130**. With relatively greater mass at the top-and-toe transition region and/or the sole-and-toe transition region, more weight may be distributed away from the center of gravity (CG) of the golf club head **100** to increase the moment of inertia (MOI) about the vertical axis through the CG.

Although the figures may depict the weight portions as separate and individual parts, each set of the first and second sets of weight portions **120** and **130**, respectively, may be a single piece of weight portion. In one example, all of the weight portions of the first set **120** (e.g., shown as **121**, **122**, **123**, and **124**) may be combined into a single piece of weight portion (e.g., a first weight portion). In a similar manner, all of the weight portions of the second set **130** (e.g., **131**, **132**, **133**, **134**, **135**, **136**, and **137**) may be combined into a single piece of weight portion as well (e.g., a second weight portion). In this example, the golf club head **100** may have only two weight portions. While the figures may depict a particular number of weight portions, the apparatus, methods, and articles of manufacture described herein may include more or less number of weight portions. In one example, the first set of weight portions **120** may include two separate weight portions instead of three separate weight portions as shown in the figures. In another example, the second set of weight portions **130** may include five separate weight portions instead of seven separate weight portions as shown in the figures. Alternatively as mentioned above, the apparatus, methods, and articles of manufacture described herein may not include any separate weight portions (e.g., the body portion **110** may be manufactured to include the mass of the separate weight portions as integral part(s) of the body portion **110**). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring to FIGS. 7-9, for example, the body portion **110** may be a hollow body including the interior cavity **700** extending between the front portion **160** and the back portion **170**. Further, the interior cavity **700** may extend between the top portion **180** and the sole portion **190**. The interior cavity **700** may be associated with a cavity height **750** ( $H_C$ ), and the body portion **110** may be associated with a body height **850** ( $H_B$ ). While the cavity height **750** and the body height **850** may vary between the toe and heel portions **140** and **150**, the cavity height **750** may be at least 50% of a body height **850** ( $H_C > 0.5 * H_B$ ). For example, the cavity height **750** may vary between 70-85% of the body height **850**. With the cavity height **750** of the interior cavity **700** being greater than 50% of the body height **850**, the golf club head **100** may produce relatively more consistent feel, sound, and/or result when the golf club head **100** strikes a golf ball via the face portion **162** than a golf club head with a cavity height of less than 50% of the body height. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the interior cavity **700** may be unfilled (i.e., empty space). The body portion **110** with the interior cavity **700** may weight about 100 grams less than the body portion **110** without the interior cavity **700**. Alternatively, the interior cavity **700** may be partially or entirely filled with an

elastic polymer or elastomer material (e.g., a viscoelastic urethane polymer material such as Sorbothane® material manufactured by Sorbothane, Inc., Kent, Ohio), a thermoplastic elastomer material (TPE), a thermoplastic polyurethane material (TPU), and/or other suitable types of materials to absorb shock, isolate vibration, and/or dampen noise. For example, at least 50% of the interior cavity **700** may be filled with a TPE material to absorb shock, isolate vibration, and/or dampen noise when the golf club head **100** strikes a golf ball via the face portion **162**.

In another example, the interior cavity **700** may be partially or entirely filled with a polymer material such as an ethylene copolymer material to absorb shock, isolate vibration, and/or dampen noise when the golf club head **100** strikes a golf ball via the face portion **162**. In particular, at least 50% of the interior cavity **700** may be filled with a high density ethylene copolymer ionomer, a fatty acid modified ethylene copolymer ionomer, a highly amorphous ethylene copolymer ionomer, an ionomer of ethylene acid acrylate terpolymer, an ethylene copolymer comprising a magnesium ionomer, an injection moldable ethylene copolymer that may be used in conventional injection molding equipment to create various shapes, an ethylene copolymer that can be used in conventional extrusion equipment to create various shapes, and/or an ethylene copolymer having high compression and low resilience similar to thermoset polybutadiene rubbers. For example, the ethylene copolymer may include any of the ethylene copolymers associated with DuPont™ High-Performance Resin (HPF) family of materials (e.g., DuPont™ HPF AD1172, DuPont™ HPF AD1035, DuPont® HPF 1000 and DuPont™ HPF 2000), which are manufactured by E.I. du Pont de Nemours and Company of Wilmington, Del. The DuPont™ HPF family of ethylene copolymers are injection moldable and may be used with conventional injection molding equipment and molds, provide low compression, and provide high resilience. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Turning to FIG. **15**, for example, the face portion **162** may include a first thickness **1510** ( $T_1$ ), and a second thickness **1520** ( $T_2$ ). The first thickness **1510** may be a thickness of a section of the face portion **162** adjacent to a groove **168** whereas the second thickness **1520** may be a thickness of a section of the face portion **162** below the groove **168**. For example, the first thickness **1510** may be a maximum distance between the front surface **164** and the back surface **166**. The second thickness **1520** may be based on the groove **168**. In particular, the groove **168** may have a groove depth **1525** ( $D_{groove}$ ). The second thickness **1520** may be a maximum distance between the bottom of the groove **168** and the back surface **166**. The sum of the second thickness **1520** and the groove depth **1525** may be substantially equal to the first thickness **1510** (e.g.,  $T_2 + D_{groove} = T_1$ ). Accordingly, the second thickness **1520** may be less than the first thickness **1510** (e.g.,  $T_2 < T_1$ ).

To lower and/or move the CG of the golf club head **100** further back, weight from the front portion **160** of the golf club head **100** may be removed by using a relatively thinner face portion **162**. For example, the first thickness **1510** may be about 0.075 inch (1.905 millimeters) (e.g.,  $T_1 = 0.075$  inch). With the support of the back wall portion **1410** to form the interior cavity **700** and filling at least a portion of the interior cavity **700** with an elastic polymer material, the face portion **162** may be relatively thinner (e.g.,  $T_1 < 0.075$  inch) without degrading the structural integrity, sound, and/or feel of the golf club head **100**. In one example, the first thickness **1510** may be less than or equal to 0.060 inch (1.524

millimeters) (e.g.,  $T_1 \leq 0.060$  inch). In another example, the first thickness **1510** may be less than or equal to 0.040 inch (1.016 millimeters) (e.g.,  $T_1 < 0.040$  inch). Based on the type of material(s) used to form the face portion **162** and/or the body portion **110**, the face portion **162** may be even thinner with the first thickness **1510** being less than or equal to 0.030 inch (0.762 millimeters) (e.g.,  $T_1 \leq 0.030$  inch). The groove depth **1525** may be greater than or equal to the second thickness **1520** (e.g.,  $D_{groove} \geq T_2$ ). In one example, the groove depth **1525** may be about 0.020 inch (0.508 millimeters) (e.g.,  $D_{groove} = 0.020$  inch). Accordingly, the second thickness **1520** may be about 0.010 inch (0.254 millimeters) (e.g.,  $T_2 = 0.010$  inch). In another example, the groove depth **1525** may be about 0.015 inch (0.381 millimeters), and the second thickness **1520** may be about 0.015 inch (e.g.,  $D_{groove} = T_2 = 0.015$  inch). Alternatively, the groove depth **1525** may be less than the second thickness **1520** (e.g.,  $D_{groove} < T_2$ ). Without the support of the back wall portion **1410** and the elastic polymer material to fill in the interior cavity **700**, a golf club head may not be able to withstand multiple impacts by a golf ball on a face portion. In contrast to the golf club head **100** as described herein, a golf club head with a relatively thin face portion but without the support of the back wall portion **1410** and the elastic polymer material to fill in the interior cavity **700** (e.g., a cavity-back golf club head) may produce unpleasant sound (e.g., a tinny sound) and/or feel during impact with a golf ball. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Based on manufacturing processes and methods used to form the golf club head **100**, the face portion **162** may include additional material at or proximate to a periphery of the face portion **162**. Accordingly, the face portion **162** may also include a third thickness **1530**, and a chamfer portion **1540**. The third thickness **1530** may be greater than either the first thickness **1510** or the second thickness **1520** (e.g.,  $T_3 > T_1 > T_2$ ). In particular, the face portion **162** may be coupled to the body portion **110** by a welding process. For example, the first thickness **1510** may be about 0.030 inch (0.762 millimeters), the second thickness **1520** may be about 0.015 inch (0.381 millimeters), and the third thickness **1530** may be about 0.050 inch (1.27 millimeters). Accordingly, the chamfer portion **1540** may accommodate some of the additional material when the face portion **162** is welded to the body portion **110**.

As illustrated in FIG. **16**, for example, the face portion **162** may include a reinforcement section, generally shown as **1605**, below one or more grooves **168**. In one example, the face portion **162** may include a reinforcement section **1605** below each groove. Alternatively, face portion **162** may include the reinforcement section **1605** below some grooves (e.g., every other groove) or below only one groove. The face portion **162** may include a first thickness **1610**, a second thickness **1620**, a third thickness **1630**, and a chamfer portion **1640**. The groove **168** may have a groove depth **1625**. The reinforcement section **1605** may define the second thickness **1620**. The first and second thicknesses **1610** and **1620**, respectively, may be substantially equal to each other (e.g.,  $T_1 = T_2$ ). In one example, the first and second thicknesses **1610** and **1620**, respectively, may be about 0.030 inch (0.762 millimeters) (e.g.,  $T_1 = T_2 = 0.030$  inch). The groove depth **1625** may be about 0.015 inch (0.381 millimeters), and the third thickness **1630** may be about 0.050 inch (1.27 millimeters). The groove **168** may also have a groove width. The width of the reinforcement section **1605** may be greater

than or equal to the groove width. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Alternatively, the face portion 162 may vary in thickness at and/or between the top portion 180 and the sole portion 190. In one example, the face portion 162 may be relatively thicker at or proximate to the top portion 180 than at or proximate to the sole portion 190 (e.g., thickness of the face portion 162 may taper from the top portion 180 towards the sole portion 190). In another example, the face portion 162 may be relatively thicker at or proximate to the sole portion 190 than at or proximate to the top portion 180 (e.g., thickness of the face portion 162 may taper from the sole portion 190 towards the top portion 180). In yet another example, the face portion 162 may be relatively thicker between the top portion 180 and the sole portion 190 than at or proximate to the top portion 180 and the sole portion 190 (e.g., thickness of the face portion 162 may have a bell-shaped contour). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Different from other golf club head designs, the interior cavity 700 of the body portion 110 and the location of the first and second sets of weight portions 120 and 130, respectively, along the perimeter of the golf club head 100 may result in a golf ball traveling away from the face portion 162 at a relatively higher ball launch angle and a relatively lower spin rate. As a result, the golf ball may travel farther (i.e., greater total distance, which includes carry and roll distances).

As described herein, the interior cavity 700 may be partially or fully filled with an elastic polymer material to provide structural support for the face portion 162. In particular, the elastic polymer material may also provide vibration and/or noise dampening for the body portion 110 when the face portion 162 strikes a golf ball. Alternatively, the elastic polymer material may only provide vibration and/or noise dampening for the body portion 110 when the face portion 162 strikes a golf ball. In one example, the body portion 110 of the golf club head 100 (e.g., an iron-type golf club head) may have a body portion volume ( $V_b$ ) between about 2.0 cubic inches (32.77 cubic centimeters) and about 4.2 cubic inches (68.83 cubic centimeters). The volume of the elastic polymer material filling the interior cavity ( $V_e$ ), such as the interior cavity 700, may be between 0.5 and 1.7 cubic inches (8.19 and 27.86 cubic centimeters, respectively). A ratio of the elastic polymer material volume ( $V_e$ ) to the body portion volume ( $V_b$ ) may be expressed as:

$$0.2 \leq \frac{V_e}{V_b} \leq 0.5$$

Where:

$V_e$  is the elastic polymer material volume in units of  $\text{in}^3$ , and

$V_b$  is the body portion volume in units of  $\text{in}^3$ .

In another example, the ratio of the elastic polymer material volume ( $V_e$ ) to the body portion volume ( $V_b$ ) may be between about 0.2 and about 0.4. In yet another example, the ratio of the elastic polymer material volume ( $V_e$ ) to the body portion volume ( $V_b$ ) may be between about 0.25 and about 0.35. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Based on the amount of elastic polymer material filling the interior cavity, for example, the thickness of the face portion may be between about 0.025 inches (0.635 millime-

ters) and about 0.075 inches (1.905 millimeters). In another example, the thickness of the face portion ( $T_f$ ) may be between about 0.02 inches (0.508 millimeters) and about 0.09 inches (2.286 millimeters). The thickness of the face portion ( $T_f$ ) may depend on the volume of the elastic polymer material in the interior cavity ( $V_e$ ), such as the interior cavity 700. The ratio of the thickness of the face portion ( $T_f$ ) to the volume of the elastic polymer material ( $V_e$ ) may be expressed as:

$$0.01 \leq \frac{T_f}{V_e} \leq 0.2$$

Where:

$T_f$  is the thickness of the face portion in units of inches, and

$V_e$  is the elastic polymer material volume in units of  $\text{in}^3$ .

In one example, the ratio of the thickness of the face portion ( $T_f$ ) to the volume of the elastic polymer material ( $V_e$ ) may be between 0.02 and 0.09. In another example, the ratio of the thickness of the face portion ( $T_f$ ) to the volume of the elastic polymer material ( $V_e$ ) may be between 0.04 and 0.14. The thickness of the face portion ( $T_f$ ) may be the same as  $T_1$  and/or  $T_2$  mentioned above. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The thickness of the face portion ( $T_f$ ) may depend on the volume of the elastic polymer material in the interior cavity ( $V_e$ ), such as the interior cavity 700, and the body portion volume ( $V_b$ ). The volume of the elastic polymer material ( $V_e$ ) may be expressed as:

$$V_e = a * V_b + b + c * T_f$$

$$a \approx 0.48$$

$$b \approx -0.38$$

$$0 \leq c \leq 10$$

Where:

$V_e$  is the elastic polymer material volume in units of  $\text{in}^3$ ,

$V_b$  is the body portion volume in units of  $\text{in}^3$ , and

$T_f$  is the thickness of the face portion in units of inches.

As described herein, for example, the body portion volume ( $V_b$ ) may be between about 2.0 cubic inches (32.77 cubic centimeters) and about 4.2 cubic inches (68.83 cubic centimeters). In one example, the thickness of the face portion ( $T_f$ ) may be about 0.03 inches (0.762 millimeters). In another example, the thickness of the face portion ( $T_f$ ) may be about 0.06 inches (1.524 millimeters). In yet another example, the thickness of the face portion ( $T_f$ ) may be about 0.075 inches (1.905 millimeters). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Further, the volume of the elastic polymer material ( $V_e$ ) when the interior cavity is fully filled with the elastic polymer material, may be similar to the volume of the interior cavity ( $V_c$ ). Accordingly, when the interior cavity is fully filled with an elastic polymer material, the volume of the elastic polymer material ( $V_e$ ) in any of the equations provided herein may be replaced with the volume of the interior cavity ( $V_c$ ). Accordingly, the above equations expressed in terms of the volume of the interior cavity ( $V_c$ ) may be expressed as:



15

$$0.2 \leq \frac{V_c}{V_b} \leq 0.5$$

$$0.01 \leq \frac{V_f}{V_c} \leq 0.2$$

$$V_c = a \cdot V_b + b + c \cdot T_f$$

$$a \cong 0.48$$

$$b \cong -0.38$$

$$0 \leq c \leq 10$$

Where:

$V_c$  is the volume of the interior cavity in units of in<sup>3</sup>,

$V_b$  is the body portion volume in units of in<sup>3</sup>, and

$T_f$  is the thickness of the face portion in units of inches.

FIG. 17 depicts one manner in which the example golf club head described herein may be manufactured. In the example of FIG. 17, the process 1700 may begin with providing two or more weight portions, generally shown as the first and second sets of weight portions 120 and 130, respectively (block 1710). The first and second sets of weight portions 120 and 130, respectively, may be made of a first material such as a tungsten-based material. In one example, the weight portions of the first and second sets 120 and 130, respectively, may be tungsten-alloy screws.

The process 1700 may provide a body portion 110 having the face portion 162, the interior cavity 700, and the back portion 170 with two or more exterior weight ports, generally shown as 1420 and 1430 (block 1720). The body portion 110 may be made of a second material, which is different than the first material. The body portion 110 may be manufactured using an investment casting process, a billet forging process, a stamping process, a computer numerically controlled (CNC) machining process, a die casting process, any combination thereof, or other suitable manufacturing processes. In one example, the body portion 110 may be made of 17-4 PH stainless steel using a casting process. In another example, the body portion 110 may be made of other suitable type of stainless steel (e.g., Nitronic® 50 stainless steel manufactured by AK Steel Corporation, West Chester, Ohio) using a forging process. By using Nitronic® 50 stainless steel to manufacture the body portion 110, the golf club head 100 may be relatively stronger and/or more resistant to corrosion than golf club heads made from other types of steel. Each weight port of the body portion 110 may include an opening and a port wall. For example, the weight port 1421 may include the opening 720 and the port wall 725 with the opening 720 and the port wall 725 being on opposite ends of each other. The interior cavity 700 may separate the port wall 725 of the weight port 1421 and the back surface 166 of the face portion 162. In a similar manner, the weight port 1435 may include the opening 730 and the port wall 735 with the opening 730 and the port wall 735 being on opposite ends of each other. The interior cavity 700 may separate the port wall 735 of the weight port 1435 and the back surface 166 of the face portion 162.

The process 1700 may couple each of the first and second sets of weight portions 120 and 130 into one of the two or more exterior weight ports (blocks 1730). In one example, the process 1700 may insert and secure the weight portion 121 in the exterior weight port 1421, and the weight portion 135 in the exterior weight portion 1435. The process 1700 may use various manufacturing methods and/or processes to secure the first and second sets of weight portions 120 and 130, respectively, in the exterior weight ports such as the

16

weight ports 1421 and 1435 (e.g., epoxy, welding, brazing, mechanical lock(s), any combination thereof, etc.).

The process 1700 may partially or entirely fill the interior cavity 700 with an elastic polymer material (e.g., Sorbothane® material) or a polymer material (e.g., an ethylene copolymer material such as DuPont™ HPF family of materials) (block 1740). In one example, at least 50% of the interior cavity 700 may be filled with the elastic polymer material. As mentioned above, the elastic polymer material may absorb shock, isolate vibration, and/or dampen noise in response to the golf club head 100 striking a golf ball. In addition or alternatively, the interior cavity 700 may be filled with a thermoplastic elastomer material and/or a thermoplastic polyurethane material. As illustrated in FIG. 18, for example, the golf club head 100 may include one or more weight ports (e.g., one shown as 1431 in FIG. 14) with a first opening 1830 and a second opening 1835. The second opening 1835 may be used to access the interior cavity 700. In one example, the process 1700 (FIG. 17) may fill the interior cavity 700 with an elastic polymer material by injecting the elastic polymer material into the interior cavity 700 from the first opening 1830 via the second opening 1835. The first and second openings 1830 and 1835, respectively, may be same or different in size and/or shape. While the above example may describe and depict a particular weight port with a second opening, any other weight ports of the golf club head 100 may include a second opening (e.g., the weight port 720). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring back to FIG. 17, the example process 1700 is merely provided and described in conjunction with other figures as an example of one way to manufacture the golf club head 100. While a particular order of actions is illustrated in FIG. 17, these actions may be performed in other temporal sequences. For example, two or more actions depicted in FIG. 17 may be performed sequentially, concurrently, or simultaneously. In one example, blocks 1710, 1720, 1730, and/or 1740 may be performed simultaneously or concurrently. Although FIG. 17 depicts a particular number of blocks, the process may not perform one or more blocks. In one example, the interior cavity 700 may not be filled (i.e., block 1740 may not be performed). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Referring back to FIGS. 1-14, the face portion 162 may include a non-smooth back surface to improve adhesion and/or mitigate delamination between the face portion 162 and the elastic polymer material used to fill the interior cavity 700 (e.g., FIG. 7). Various methods and/or processes such as an abrasive blasting process (e.g., a bead blasting process, a sand blasting process, other suitable blasting process, or any combination thereof) and/or a milling (machining) process may be used to form the back surface 166 into a non-smooth surface. For example, the back surface 166 may have with a surface roughness (Ra) ranging from 0.5 to 250 μm (0.012 to 6.3 μm). The apparatus, methods, and articles of manufacture are not limited in this regard.

As illustrated in FIGS. 19-21, for example, a face portion 1900 may include the front surface 1910, and the back surface 2010. The front surface 1910 may include one or more grooves, generally shown as 1920, extending longitudinally across the front surface 1910 (e.g., extending between the toe portion 140 and the heel portion 150 of FIG. 1). The front surface 1910 may be used to impact a golf ball (not shown).

The back surface **2010** may also include one or more channels, generally shown as **2020**. The channels **2020** may extend longitudinally across the back surface **2010**. The channels **2020** may be parallel or substantially parallel to each other. The channels **2020** may engage with the elastic polymer material used to fill the interior cavity **700**, and serve as a mechanical locking mechanism between the face portion **1900** and the elastic polymer material. In particular, a channel **2100** may include an opening **2110**, a bottom section **2120**, and two sidewalls, generally shown as **2130** and **2132**. The bottom section **2120** may be parallel or substantially parallel to the back surface **2010**. The two sidewalls **2130** and **2132** may be converging sidewalls (i.e., the two sidewalls **2130** and **2132** may not be parallel to each other). The bottom section **2120** and the sidewalls **2130** and **2132** may form two undercut portions, generally shown as **2140** and **2142**. That is, a width **2115** at the opening **2110** may be less than a width **2125** of the bottom section **2120**. A cross section of the channel **2100** may be symmetrical about an axis **2150**. While FIG. **21** may depict flat or substantially flat sidewalls, the two sidewalls **2130** and **2132** may be curved (e.g., convex relative to each other).

Instead of flat or substantially flat sidewalls as shown in FIG. **21**, a channel may include other types of sidewalls. As illustrated in FIG. **22**, for example, a channel **2200** may include an opening **2210**, a bottom section **2220**, and two sidewalls, generally shown as **2230** and **2232**. The bottom section **2220** may be parallel or substantially parallel to the back surface **2010**. The two sidewalls **2230** and **2232** may be stepped sidewalls. The bottom section **2220** and the sidewalls **2230** and **2232** may form two undercut portions, generally shown as **2240** and **2242**. That is, a width **2215** at the opening **2210** may be less than a width **2225** of the bottom section **2220**. A cross section of the channel **2200** may be symmetrical about an axis **2250**.

Instead of being symmetrical as shown in FIGS. **21** and **22**, a channel may be asymmetrical. As illustrated in FIG. **23**, for another example, a channel **2300** may include an opening **2310**, a bottom section **2320**, and two sidewalls, generally shown as **2330** and **2332**. The bottom section **2320** may be parallel or substantially parallel to the back surface **2010**. The bottom section **2320** and the sidewall **2330** may form an undercut portion **2340**.

Referring to FIG. **24**, for example, a channel **2400** may include an opening **2410**, a bottom section **2420**, and two sidewalls, generally shown as **2430** and **2432**. The bottom section **2420** may not be parallel or substantially parallel to the back surface **2010**. The two sidewalls **2430** and **2432** may be parallel or substantially parallel to each other but one sidewall may be longer than the other sidewall. The bottom section **2420** and the sidewall **2432** may form an undercut portion **2440**.

In the example as shown in FIG. **25**, a face portion **2500** may include a back surface **2510** with one or more channels, generally shown as **2520**, extending laterally across the back surface **2510** (e.g., extending between the top portion **180** and the sole portion **190** of FIG. **1**). In another example as depicted in FIG. **26**, a face portion **2600** may include a back surface **2610** with one or more channels, generally shown as **2620**, extending diagonally across the back surface **2610**. Alternatively, a face portion may include a combination of channels extending in different directions across a back surface of the face portion (e.g., extending longitudinally, laterally, and/or diagonally). Turning to FIG. **27**, for yet another example, a face portion **2700** may include a back surface **2710** with one or more channels, generally shown as **2720**, **2730**, and **2740**, extending in different directions

across the back surface **2710**. In particular, the face portion **2700** may include a plurality of channels **2720** extending longitudinally across the back surface **2710**, a plurality of channels **2730** extending laterally across the back surface **2710**, and a plurality of channels **2740** extending diagonally across the back surface **2710**.

Referring to FIG. **28**, for example, the golf club head **100** may include the face portion **162**, a bonding portion **2810**, and an elastic polymer material **2820**. The bonding portion **2810** may provide connection, attachment and/or bonding of the elastic polymer material **2820** to the face portion **162**. The bonding portion **2810** may be a bonding agent, a combination of bonding agents, a bonding structure or attachment device, a combination of bonding structures and/or attachment devices, and/or a combination of one or more bonding agents, one or more bonding structures and/or one or more attachment devices. For example, the golf club head **100** may include a bonding agent to improve adhesion and/or mitigate delamination between the face portion **162** and the elastic polymer material used to fill the interior cavity **700** of the golf club head **100** (e.g., FIG. **7**). In one example, the bonding portion **2810** may be low-viscosity, organic, solvent-based solutions and/or dispersions of polymers and other reactive chemicals such as MEGUM™, ROBOND™, and/or THIXON™ materials manufactured by the Dow Chemical Company, Auburn Hills, Mich. In another example, the bonding portion **2810** may be LOC-TITE® materials manufactured by Henkel Corporation, Rocky Hill, Conn. The bonding portion **2810** may be applied to the back surface **166** to bond the elastic polymer material **2820** to the face portion **162** (e.g., extending between the back surface **166** and the elastic polymer material **2820**). For example, the bonding portion **2810** may be applied when the interior cavity **700** is filled with the elastic polymer material **2820** via an injection-molding process. The apparatus, methods, and articles of manufacture are not limited in this regard.

FIG. **29** depicts one manner in which the interior cavity **700** of the golf club head **100** or any of the golf club heads described herein is partially or entirely filled with an elastic polymer material or an elastomer material. The process **2900** may begin with heating the golf club head **100** to a certain temperature (block **2910**). In one example, the golf club head **100** may be heated to a temperature ranging between 150° C. to 250° C., which may depend on factors such as the vaporization temperature of the elastic polymer material to be injected in the interior cavity **700**. The elastic polymer material may then be heated to a certain temperature (block **2920**). The elastic polymer material may be a non-foaming and injection-moldable thermoplastic elastomer (TPE) material. Accordingly, the elastic polymer material may be heated to reach a liquid or a flowing state prior to being injected into the interior cavity **700**. The temperature to which the elastic polymer material may be heated may depend on the type of elastic polymer material used to partially or fully fill the interior cavity **700**. The heated elastic polymer material may be injected into the interior cavity **700** to partially or fully fill the interior cavity **700** (block **2930**). The elastic polymer material may be injected into the interior cavity **700** from one or more of the weight ports described herein (e.g., one or more weight ports of the first and second sets of weight ports **1420** and **1430**, respectively, shown in FIG. **14**). One or more other weight ports may allow the air inside the interior cavity **700** displaced by the elastic polymer material to vent from the interior cavity **700**. In one example, the golf club head **100** may be oriented horizontally as shown in FIG. **14** during the injection

molding process. The elastic polymer material may be injected into the interior cavity **700** from weight ports **1431** and **1432**. The weight ports **1421**, **1422** and/or **1423** may serve as air ports for venting the displaced air from the interior cavity **700**. Thus, regardless of the orientation of the golf club head **100** during the injection molding process, the elastic polymer material may be injected into the interior cavity **700** from one or more lower positioned weight ports while one or more upper positioned weight ports may serve as air vents. The mold (i.e., the golf club head **100**) may then be cooled passively (e.g., at room temperature) or actively so that the elastic polymer material reaches a solid state and adheres to the back surface **166** of the face portion **162**. The elastic polymer material may directly adhere to the back surface **166** of the face portion **162**. Alternatively, the elastic polymer material may adhere to the back surface **166** of the face portion **162** with the aid of the one or more structures on the back surface **166** and/or a bonding agent described herein (e.g., the bonding portion **2810** shown in FIG. **28**). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As discussed above, the elastic polymer material may be heated to a liquid state (i.e., non-foaming) and solidifies after being injection molded in the interior cavity **700**. An elastic polymer material with a low modulus of elasticity may provide vibration and noise dampening for the face portion **162** when the face portion **162** impacts a golf ball. For example, an elastic polymer material that foams when heated may provide vibration and noise dampening. However, such a foaming elastic polymer material may not have sufficient rigidity to provide structural support to a relatively thin face portion because of possible excessive deflection and/or compression of the elastic polymer material when absorbing the impact of a golf ball. In one example, the elastic polymer material that is injection molded in the interior cavity **700** may have a relatively high modulus of elasticity to provide structural support to the face portion **162** and yet elastically deflect to absorb the impact forces experienced by the face portion **162** when striking a golf ball. Thus, a non-foaming and injection moldable elastic polymer material with a relatively high modulus of elasticity may be used for partially or fully filling the interior cavity **700** to provide structural support and reinforcement for the face portion **162** in addition to providing vibration and noise dampening. That is, the non-foaming and injection moldable elastic polymer material may be a structural support portion for the face portion **162**. The apparatus, methods, and articles of manufacture are not limited in this regard.

FIG. **30** depicts one manner in which a bonding agent as described herein may be applied to a golf club head prior to partially or fully injecting an elastic polymer in the interior cavity **700**. In the example of FIG. **30**, the process **3000** may begin with injecting a bonding agent on the back surface **166** of the face portion **162** (block **3010**). The bonding agent may be injected on the back surface **166** prior to or after heating the golf club head as described above depending on the properties of the bonding agent. The bonding agent may be injected through one or more of the first set of weight ports **1420** and/or the second set of weight ports **1430**. The bonding agent may be injected on the back surface **166** through several or all of the first set of weight ports **1420** and the second set of weight ports **1430**. For example, an injection instrument such as a nozzle or a needle may be inserted into each weight port until the tip or outlet of the instrument is near the back surface **166**. The bonding agent may then be injected on the back surface **166** from the outlet of the instrument. Additionally, the instrument may be

moved, rotated and/or swiveled while inside the interior cavity **700** so that the bonding agent is injected onto an area of the back surface **166** surrounding the instrument. For example, the outlet of the injection instrument may be moved in a circular pattern while inside a weight port to inject the bonding agent in a corresponding circular pattern on the back surface **166**. Each of the first set of weight ports **1420** and the second set of weight ports **1430** may be utilized to inject a bonding agent on the back surface **166**. However, utilizing all of first weight ports **1420** and/or the second set of weight ports **1430** may not be necessary. For example, using every other adjacent weight port may be sufficient to inject a bonding agent on the entire back surface **166**. In another example, weight ports **1421**, **1422**, **1431**, **1433** and **1436** may be used to inject the bonding agent on the back surface **166**. The apparatus, methods, and articles of manufacture are not limited in this regard.

The process **3000** may also include spreading the bonding agent on the back surface **166** (block **3020**) after injection of the bonding agent onto the back surface **166** so that a generally uniform coating of the bonding agent is provided on the back surface **166**. According to one example, the bonding agent may be spread on the back surface **166** by injecting air into the interior cavity **700** through one or more of the first set of weight ports **1420** and the second set of weight ports **1430**. The air may be injected into the interior cavity **700** and on the back surface **166** by inserting an air nozzle into one or more of the first set of weight ports **1420** and the second set of weight ports **1430**. According to one example, the air nozzle may be moved, rotated and/or swiveled at a certain distance from the back surface **166** so as to uniformly blow air onto the bonding agent to spread the bonding agent on the back surface **166** for a uniform coating or a substantially uniform coating of the bonding agent on the back surface **166**. The apparatus, methods, and articles of manufacture are not limited in this regard.

The example process **3000** is merely provided and described in conjunction with other figures as an example of one way to manufacture the golf club head **100**. While a particular order of actions is illustrated in FIG. **30**, these actions may be performed in other temporal sequences. Further, two or more actions depicted in FIG. **30** may be performed sequentially, concurrently, or simultaneously. The process **3000** may include a single action of injecting and uniformly or substantially uniformly coating the back surface **166** with the bonding agent. In one example, the bonding agent may be injected on the back surface **166** by being converted into fine particles or droplets (i.e., atomized) and sprayed on the back surface **166**. Accordingly, the back surface **166** may be uniformly or substantially uniformly coated with the bonding agent in one action. A substantially uniform coating of the back surface **166** with the bonding agent may be defined as a coating having slight non-uniformities due to the injection process or the manufacturing process. However, such slight non-uniformities may not affect the bonding of the elastic polymer material or the elastomer material to the back surface **166** with the bonding agent as described herein. For example, spraying the bonding agent on the back surface **166** may result in overlapping regions of the bonding agent having a slightly greater coating thickness than other regions of the bonding agent on the back surface **166**. The apparatus, methods, and articles of manufacture are not limited in this regard.

As described herein, any two or more of the weight portions may be configured as a single weight portion. In the example of FIGS. **31** and **32**, a golf club head **3100** may include a body portion **3110** and two or more weight

portions, generally shown as a first set of weight portions **3120** (e.g., shown as weight portions **3121**, **3122**, **3123**, and **3124**) and a second weight portion **3130**. The body portion **3110** may include a toe portion **3140**, a heel portion **3150**, a front portion (not shown), a back portion **3170**, a top portion **3180**, and a sole portion **3190**. The front portion may be similar in many respects to the front portion **160** of the golf club head **100**. Accordingly, details of the front portion of the golf club head **3100** are not provided.

The body portion **3110** may be made of a first material whereas the first set of weight portions **3120** and the second weight portion **3130** may be made of a second material. The first and second materials may be similar or different materials. For example, the body portion **3110** may be partially or entirely made of a steel-based material (e.g., 17-4 PH stainless steel, Nitronic® 50 stainless steel, maraging steel or other types of stainless steel), a titanium-based material, an aluminum-based material (e.g., a high-strength aluminum alloy or a composite aluminum alloy coated with a high-strength alloy), any combination thereof, and/or other suitable types of materials. The first set of weight portions **3120** and the second weight portion **3130** may be partially or entirely made of a high-density material such as a tungsten-based material or other suitable types of materials. Alternatively, the body portion **3110** and/or the first set of weight portions **3120** and the second weight portion **3130** may be partially or entirely made of a non-metal material (e.g., composite, plastic, etc.). The apparatus, methods, and articles of manufacture are not limited in this regard.

The golf club head **3100** may be an iron-type golf club head (e.g., a 1-iron, a 2-iron, a 3-iron, a 4-iron, a 5-iron, a 6-iron, a 7-iron, an 8-iron, a 9-iron, etc.) or a wedge-type golf club head (e.g., a pitching wedge, a lob wedge, a sand wedge, an n-degree wedge such as 44 degrees (°), 48°, 52°, 56°, 60°, etc.). Although FIGS. **31** and **32** may depict a particular type of club head, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of club heads (e.g., a driver-type club head, a fairway wood-type club head, a hybrid-type club head, a putter-type club head, etc.). The apparatus, methods, and articles of manufacture described herein are not limited in this regard. The toe portion **3140** and the heel portion **3150** may be on opposite ends of the body portion **3110**. The heel portion **3150** may include a hosel portion **3155** configured to receive a shaft (not shown) with a grip (not shown) on one end and the golf club head **3100** on the opposite end of the shaft to form a golf club.

The back portion **3170** may include a back wall portion **3210** with one or more exterior weight ports along a periphery of the back portion **3170**, generally shown as a first set of exterior weight ports **3220** (e.g., shown as weight ports **3221**, **3222**, **3223**, and **3224**) and a second weight port **3230**. Each exterior weight port of the first set of weight ports **3220** may be associated with a port diameter. In one example, the port diameter may be about 0.25 inch (6.35 millimeters). Any two adjacent exterior weight ports of the first set of exterior weight ports **3220** may be separated by less than the port diameter. The first set of weight ports **3220** and the second weight port **3230** may be exterior weight ports configured to receive one or more weight portions.

Each weight portion of the first set of weight portions **3120** (e.g., shown as weight portions **3121**, **3122**, **3123**, and **3124**) may be disposed in a weight port of the first set of weight ports **3220** (e.g., shown as weight ports **3221**, **3222**, **3223**, and **3224**) located at or proximate to the toe portion **3140** and/or the top portion **3180** on the back portion **3170**. For example, the weight portion **3121** may be partially or

entirely disposed in the weight port **3221**. In another example, the weight portion **3122** may be disposed in a weight port **3222** located in a transition region between the top portion **3180** and the toe portion **3140** (e.g., a top-and-toe transition region). The configuration of the first set of weight ports **3220** and the first set of weight portions **3120** is similar to many respects to the golf club head **100**. Accordingly, a detailed description of the configuration of the first set of weight ports **3220** and the first set of weight portions **3120** is not provided.

The second weight port **3230** may be a recess extending from the toe portion **3140** or a location proximate to the toe portion **3140** to the sole portion or a location proximate to the sole portion **3190** and through the transition region between the toe portion **3140** and the sole portion **3190**. Accordingly, as shown in FIG. **31**, the second weight port **3230** may resemble an L-shaped recess. The second weight portion **3130** may resemble the shape of the second weight port **3230** and may be configured to be disposed in the second weight port **3230**. The second weight portion **3130** may be partially or fully disposed in the weight port **3230**. The second weight portion **3130** may have any shape such as oval, rectangular, triangular, or any geometric or non-geometric shape. The second weight port **3230** may be shaped similar to the second weight portion **3130**. However, portions of the second weight portion **3130** that are inserted in the second weight port **3230** may have similar shapes as the weight port **3230**. As described in detail herein, any of the weight portions described herein, including the weight portions **3120** and the second weight portion **3130** may be coupled to the back portion **3170** of the body portion **3110** with various manufacturing methods and/or processes (e.g., a bonding process, a welding process, a brazing process, a mechanical locking method, any combination thereof, or other suitable manufacturing methods and/or processes).

The second weight portion **3130** may be configured to place the center of gravity of the golf club head **100** at an optimal location and optimize the moment of inertia of the golf club head about a vertical axis that extends through the center of gravity of the golf club head **3100**. All or a substantial portion of the second weight portion **3130** may be generally near the sole portion **3190**. For example, the second weight portion **3130** may be near the periphery of the body portion **3110** and extend from the sole portion **3190** to the toe portion **3140**. As shown in the example of FIG. **32**, the second weight portion **3130** may be located near the periphery of the body portion **3110** and partially or substantially extend along the sole portion **3190** to lower the center of gravity of the golf club head **3100**. A portion of the second weight portion **3130** may be located near the periphery of the body portion **3110** and extend from the sole portion **3190** to the toe portion **3140** through a transition region **3147** between the sole portion **3190** and the toe portion **3140** to lower the center of gravity and increase the moment of inertia of the golf club head **3100** about a vertical axis that extends through the center of gravity. To lower the center of gravity of the golf club head **3100**, all or a portion of the second weight portion **3130** may be located closer to the sole portion **3190** than to a horizontal midplane **3260** of the golf club head **3100**. The location of the second weight portion **3130** (i.e., the location of the weight port **3230**) and the physical properties and materials of construction of the weight portions of the second weight port **3130** may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic

characteristics of the golf club head **3100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The weight portions of the first set of weight portions **3120** may have similar or different physical properties (e.g., color, shape, size, density, mass, volume, etc.). In the illustrated example as shown in FIG. **32**, each of the weight portions of the first set of weight portions **3120** may have a cylindrical shape (e.g., a circular cross section). Alternatively, each of the weight portions of the first set of weight portions **3120** may have different shapes. Although the above examples may describe weight portions having a particular shape, the apparatus, methods, and articles of manufacture described herein may include weight portions of other suitable shapes (e.g., a portion of or a whole sphere, cube, cone, cylinder, pyramid, cuboidal, prism, frustum, or other suitable geometric shape). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In the example of FIGS. **33-38**, a golf club head **3300** may include a body portion **3310**, and two or more weight portions, generally shown as a first set of weight portions **3320** (e.g., shown as weight portions **3321** and **3322**) and a second set of weight portions **3330** (e.g., shown as weight portions **3331**, **3332**, **3333**, **3334**, **3335**, **3336**, **3337**, **3338** and **3339**). The body portion **3310** may include a toe portion **3340**, a heel portion **3350**, a front portion **3360**, a back portion **3370**, a top portion **3380**, and a sole portion **3390**. The heel portion **3350** may include a hosel portion **3355** configured to receive a shaft (not shown) with a grip (not shown) on one end and the golf club head **3300** on the opposite end of the shaft to form a golf club. The golf club head **3300** may be manufactured by any of the methods described herein and illustrated in FIG. **17**. The apparatus, methods, and articles of manufacture are not limited in this regard.

The body portion **3310** may be made of a first material whereas the first and second sets of weight portions **3320** and **3330**, respectively, may be made of a second material. The first and second materials may be similar or different materials. The materials from which the golf club head **3300**, weight portions **3320** and/or weight portions **3330** are constructed may be similar in many respects to any of the golf club heads and the weight portions described herein such as the golf club head **100**. The apparatus, methods, and articles of manufacture are not limited in this regard.

The golf club head **3300** may be an iron-type golf club head (e.g., a 1-iron, a 2-iron, a 3-iron, a 4-iron, a 5-iron, a 6-iron, a 7-iron, an 8-iron, a 9-iron, etc.) or a wedge-type golf club head (e.g., a pitching wedge, a lob wedge, a sand wedge, an n-degree wedge such as 44 degrees (°), 48°, 52°, 56°, 60°, etc.). Although FIGS. **33-38** may depict a particular type of club head, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of club heads (e.g., a driver-type club head, a fairway wood-type club head, a hybrid-type club head, a putter-type club head, etc.). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The front portion **3360** may include a face portion **3362** (e.g., a strike face). The face portion **3362** may include one or more grooves **3368** extending between the toe portion **3340** and the heel portion **3350**. While the figures may depict a particular number of grooves, the apparatus, methods, and articles of manufacture described herein may include more or less grooves. The face portion **3362** may be used to impact a golf ball (not shown). The face portion **3362** may be an integral portion of the body portion **3310**. Alterna-

tively, the face portion **3362** may be a separate piece or an insert coupled to the body portion **3310** via various manufacturing methods and/or processes (e.g., a bonding process such as adhesive, a welding process such as laser welding, a brazing process, a soldering process, a fusing process, a mechanical locking or connecting method, any combination thereof, or other suitable types of manufacturing methods and/or processes). The face portion **3362** may be associated with a loft plane that defines the loft angle of the golf club head **3300**. The loft angle may vary based on the type of golf club (e.g., a long iron, a middle iron, a short iron, a wedge, etc.). In one example, the loft angle may be between five degrees and seventy-five degrees. In another example, the loft angle may be between twenty degrees and sixty degrees. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As illustrated in FIG. **34**, the back portion **3370** may include a back wall portion **3510** with one or more exterior weight ports along a periphery of the back portion **3370**, generally shown as a first set of exterior weight ports **3520** (e.g., shown as weight ports **3521** and **3522**) and a second set of exterior weight ports **3530** (e.g., shown as weight ports **3531**, **3532**, **3533**, **3534**, **3535**, **3536**, **3537**, **3538** and **3539**). Each exterior weight port may be defined by an opening in the back wall portion **3510**. Each exterior weight port may be associated with a port diameter. In one example, the port diameter may be about 0.25 inch (6.35 millimeters). The weight ports of the first set of exterior weight ports **3520** may be separated by less than the port diameter or the port diameter of any of the two adjacent weight ports of the first set of exterior weight ports **3520**. In a similar manner, any two adjacent exterior weight ports of the second set of exterior weight ports **3530** may be separated by less than the port diameter or the port diameter of any of the two adjacent weight ports of the second set of exterior weight ports **3530**. The first set of exterior weight ports **3520** and the second set of exterior weight ports **3530**, respectively, may be exterior weight ports configured to receive one or more weight portions of the first set of weight portions **3320** and/or the second set of weight portions **3330** similar to the example of the golf club head **100** as discussed herein. The first and second sets of weight portions **3320** and **3330**, respectively, may be coupled to the back portion **3370** of the body portion **3310** with various manufacturing methods and/or processes (e.g., a bonding process, a welding process, a brazing process, a mechanical locking method, any combination thereof, or other suitable manufacturing methods and/or processes).

Alternatively, the golf club head **3300** may not include (i) the first set of weight portions **3320**, (ii) the second set of weight portions **3330**, or (iii) both the first and second sets of weight portions **3320** and **3330**. In particular, the back portion **3370** of the body portion **3310** may not include weight ports at or proximate to the top portion **3370** and/or the sole portion **3390**. For example, the mass of the first set of weight portions **3320** (e.g., 3 grams) and/or the mass of the second set of weight portions **3330** (e.g., 16.8 grams) may be integral part(s) the body portion **3310** instead of separate weight portion(s). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The first and second sets of weight portions **3320** and **3330**, respectively, may have similar or different physical properties (e.g., color, shape, size, density, mass, volume, etc.). As a result, the first and second sets of weight portions **3320** and **3330**, respectively, may contribute to the ornamental design of the golf club head **3300**. The physical

properties of the first and second sets of weight portions **3320** and **3330** may be similar in many respect to any of the weight portions described herein, such as the weight portions shown in the example of FIG. **11**. Furthermore, the devices and/or methods by which the first and second set of weight portions **3320** and **3330** are coupled to the golf club head **3300** may be similar in many respect to any of the weight portions described herein, such as the weight portions shown in the example of FIGS. **12** and **13**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

As illustrated in FIG. **34**, golf club head **3300** may be associated with a ground plane **3710**, a horizontal midplane **3720**, and a top plane **3730**. In particular, the ground plane **3710** may be a plane that may be substantially parallel with the ground and be tangential to the sole portion **3390** of the golf club head **3300** when the golf club head **3300** is at an address position (e.g., the golf club head **3300** is aligned to strike a golf ball). A top plane **3730** may be a tangential to the top portion of the **3380** of the golf club head **3300** when the golf club head **3300** is at the address position. The ground and top planes **3710** and **3730**, respectively, may be substantially parallel to each other. The horizontal midplane **3720** may be located at half the vertical distance between the ground and top planes **3710** and **3730**, respectively.

To provide optimal perimeter weighting for the golf club head **3300**, the first set of weight portions **3320** (e.g., weight portions **3321** and **3322**) may be configured to counter-balance the weight of the hosel **3355** and/or increase the moment of inertia of the golf club head **3300** about a vertical axis (not shown) of the golf club head **3300** that extends through the center of gravity (not shown) of the golf club head **3300**. For example, as shown in FIG. **34**, the first set of weight portions **3320** (e.g., weight portions **3321** and **3322**) may be located near the periphery of the body portion **3310** and extend in a transition region **3345** (shown in FIG. **34**) between the top portion **3380** and the toe portion **3340**. In another example, the first set of weight portions **3320** (e.g., weight portions **3321** and **3322**) may be located near the periphery of the body portion **3310** and extend proximate to the toe portion **3340**. The locations of the first set of weight portions **3320** and the physical properties and materials of construction of the weight portions of the first set of weight portions **3320** may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic characteristics of the golf club head **3300**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The second set of weight portions **3330** (e.g., weight portions **3331**, **3332**, **3333**, **3334**, **3335**, **3336**, **3337**, **3338** and **3339**) may be configured to place the center of gravity of the golf club head **3300** at an optimal location and/or optimize the moment of inertia of the golf club head about a vertical axis (not shown) that extends through the center of gravity of the golf club head **3300**. Referring to FIG. **34**, all or a substantial portion of the second set of weight portions **3330** may be near the sole portion **3390**. For example, the second set of weight portions **3330** (e.g., weight portions **3331**, **3332**, **3333**, **3334**, **3335**, **3336**, **3337**, **3338** and **3339**) may extend at or near the sole portion **3390** between the toe portion **3340** and the heel portion **3350** to lower the center of gravity of the golf club head **100**. A greater number of the weight portions **3331**, **3332**, **3333**, **3334**, **3335**, **3336**, **3337**, **3338** and **3339** may be closer to the toe portion **3340** than the heel portion **3350** to increase the moment of inertia of the golf club head **3300** about a vertical axis that extends

through the center of gravity. Some of the weight portions of the second set of weight portions **3330** may be located at the toe portion. To lower the center of gravity of the golf club head **3300**, all or a portion of the second set of weight portions **3330** may be located closer to the sole portion **3390** than to the horizontal midplane **3720**. The golf club head **3300** may have a greater number of weight portions below the horizontal midplane **3720** than above the horizontal midplane **3720**. The golf club head **3300** may have a greater number of weight portions near the toe portion **3340** than the heel portion **3350**. The locations of the second set of weight portions **3330** and the physical properties and materials of construction of the weight portions of the second set of weight portions **3330** may be determined to optimally affect the weight, weight distribution, center of gravity, moment of inertia characteristics, structural integrity and/or other static and/or dynamic characteristics of the golf club head **3300**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

While the figures may depict weight ports with a particular cross-section shape, the apparatus, methods, and articles of manufacture described herein may include weight ports with other suitable cross-section shapes. The weight ports of the first and/or second sets of weight ports **3520** and **3530** may have cross-sectional shapes that are similar to the cross-sectional shapes of any of the weight ports described herein. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The first and second sets of weight portions **3320** and **3330**, respectively, may be similar in mass (e.g., all of the weight portions of the first and second sets **3320** and **3330**, respectively, weigh about the same). Alternatively, the first and second sets of weight portions **3320** and **3330**, respectively, may be different in mass individually or as an entire set. In particular, each of the weight portions of the first set **3320** (e.g., shown as **3321** and **3322**) may have relatively less mass than any of the weight portions of the second set **3330** (e.g., shown as **3331**, **3332**, **3333**, **3334**, **3335**, **3336**, **3337**, **3338** and **3339**). For example, the second set of weight portions **3330** may account for more than 50% of the total mass from exterior weight portions of the golf club head **3300**. In another example, the second set of weight portions **3330** may account for between 55% to 75% of the total mass from the exterior weight portions of the golf club head **3300**. In yet another example, the second set of weight portions **3330** may account for between 60% to 90% of the total mass from the exterior weight portions of the golf club head **3300**. As a result, the golf club head **3300** may be configured to have at least 50% of the total mass from exterior weight portions disposed below the horizontal midplane **3720**. In one example, the total mass from exterior weight portions may be greater below the horizontal midplane **3720** than the total mass from exterior weight portions above the horizontal midplane **3720**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the golf club head **3300** may have a mass in the range of about 220 grams to about 330 grams based on the type of golf club (e.g., a 4-iron versus a lob wedge). The body portion **3310** may have a mass in the range of about 200 grams to about 310 grams with the first and second sets of weight portions **3320** and **3330**, respectively, having a mass of about 16-24 grams (e.g., a total mass from exterior weight portions). Each of the weight portions of the first set **3320** may have a mass of about one gram (1.0 g) whereas each of the weight portions of the second set **3330** may have a mass of about 2.4 grams. The total mass of the second set of weight portions **3330** may weigh more than

five times as much as the total mass of the first set of weight portions 3320. Accordingly, the first set of weight portions 3320 may account for about 15% of the total mass from exterior weight portions of the golf club head 3300 whereas the second set of weight portions 3330 may account for about 85% of the total mass from exterior weight portions of the golf club head 3300. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

By coupling the first and second sets of weight portions 3320 and 3330, respectively, to the body portion 3310 (e.g., securing the first and second sets of weight portions 3320 and 3330 in the weight ports on the back portion 3370), the location of the center of gravity (CG) and the moment of inertia (MOI) of the golf club head 3300 may be optimized. In particular, the first and second sets of weight portions 3320 and 3330, respectively, may lower the location of the CG towards the sole portion 3390 and further back away from the face portion 3362. Further, the MOI may be higher as measured about a vertical axis extending through the CG (e.g., perpendicular to the ground plane 3710). The MOI may also be higher as measured about a horizontal axis extending through the CG (e.g., extending towards the toe and heel portions 3350 and 3360, respectively, of the golf club head 3300). As a result, the club head 3300 may provide a relatively higher launch angle and a relatively lower spin rate than a golf club head without the first and second sets of weight portions 3320 and 3330, respectively. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Alternatively, two or more weight portions in the same set may be different in mass. In one example, the weight portion 3321 of the first set 3320 may have a relatively lower mass than the weight portion 3322 of the first set 3320. In another example, the weight portion 3331 of the second set 3330 may have a relatively lower mass than the weight portion 3335 of the second set 3330. With relatively greater mass at the top-and-toe transition region and/or the sole-and-toe transition region, more weight may be distributed away from the center of gravity (CG) of the golf club head 3300 to increase the moment of inertia (MOI) about the vertical axis through the CG.

Although the figures may depict the weight portions as separate and individual parts, each set of the first and second sets of weight portions 3320 and 3330, respectively, may be a single piece of weight portion. In one example, all of the weight portions of the first set 3320 (e.g., shown as 3321 and 3322) may be combined into a single piece of weight portion (e.g., a first weight portion). In a similar manner, all of the weight portions of the second set 3330 (e.g., 3331, 3332, 3333, 3334, 3335, 3336, 3337, 3338, 3339) may be combined into a single piece of weight portion as well (e.g., a second weight portion) similar to the example of FIG. 32. While the figures may depict a particular number of weight portions, the apparatus, methods, and articles of manufacture described herein may include more or less number of weight portions. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The body portion 3310 of the golf club head 3300 may be a hollow body including the interior cavity (not shown) similar to the golf club head 100. Further, the interior cavity may be unfilled, partially filled with a polymer material or entirely filled with a polymer material similar to the golf club head 100 as discussed in detail herein. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

For example, as shown in FIGS. 34-38, the back wall portion 3510 includes a channel 3610 that may extend in a direction from the toe portion 3340 to the heel portion 3350 and have any length. The channel 3610 may extend parallel (not shown) to the horizontal midplane 3720 or extend at an angle relative to the horizontal midplane 3720 as shown in the example of FIG. 34. In one example shown in FIGS. 34-38, the channel 3610 extends from the toe portion edge 3341 of the toe portion 3340 at a location at or above the horizontal midplane 3720 to the heel portion edge 3351 of the heel portion 3350 at a location below the horizontal midplane 3720. In the examples of FIGS. 34-38, the channel 3610 includes a toe-end portion 3612 at the toe portion edge 3341 and a heel-end portion 3614 at the heel portion edge 3351. The channel 3610 may include a toe-end opening 3613 (shown in FIG. 37) at the toe portion edge 3341 and a heel-end opening 3615 (shown in FIG. 38) at the heel portion edge 3351. The channel 3610 may partially extend between the toe portion 3340 and the heel portion 3350. Accordingly, the channel 3610 may not include the toe-end opening 3613 and the heel-end opening 3615. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, as shown in FIG. 36, the top channel width ( $W_{CT}$ ) 3616 and the bottom channel width ( $W_{CB}$ ) 3617 may decrease from the toe-end portion 3612 to the heel-end portion 3614. The bottom channel width 3617 may correspond to the width of the bottom portion 3618 of the channel 3610. The bottom portion 3618 may have any configuration. For example, as shown in FIGS. 34-36, the bottom portion 3618 may be flat or planar. In another example, the bottom portion 3618 may be curved (not shown). In another example, the bottom portion 3618 may have a V-shaped cross section (not shown). In yet another example, the configuration of the bottom portion 3618 may vary from the toe-end portion 3612 to the heel-end portion 3614. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the top channel width 3616 may be between 0.22 inch (0.55 cm) and 0.65 inch (1.66 cm) at toe-end portion 3612, and between 0.15 inch (0.38 cm) and 0.46 inch (1.16 cm) at the heel-end portion 3614. In another example, the top channel width 3616 may be between 0.30 inch (0.77 cm) and 0.57 inch (1.44 cm) at toe-end portion 3612, and between 0.21 inch (0.54 cm) and 0.40 inch (1.01 cm) at the heel-end portion 3614. In another example, the top channel width 3616 may be between 0.37 inch (0.94 cm) and 0.5 inch (1.27 cm) at toe-end portion 3612, and between 0.26 inch (0.66 cm) and 0.35 inch (0.89 cm) at the heel-end portion 3614. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the bottom channel width 3617 may be between 0.13 inch (0.32 cm) and 0.38 inch (0.95 cm) at toe-end portion 3612, and between 0.04 inch (0.11 cm) and 0.13 inch (0.32 cm) at the heel-end portion 3614. In another example, the bottom channel width 3617 may be between 0.18 inch (0.44 cm) and 0.33 inch (0.83 cm) at toe-end portion 3612, and between 0.06 inch (0.15 cm) and 0.11 inch (0.28 cm) at the heel-end portion 3614. In another example, the bottom channel width 3617 may be between 0.21 inch (0.54 cm) and 0.29 inch (0.73 cm) at toe-end portion 3612, and between 0.07 inch (0.18 cm) and 0.1 inch (0.25 cm) at the heel-end portion 3614. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, as shown in FIGS. 33-38, the top channel width 3616 and the bottom channel width 3617 may

decrease from the toe-end portion **3612** to the heel-end portion **3614**. In one example, the top channel width **3616** and the bottom channel width **3617** may increase from the toe-end portion **3612** to the heel-end portion **3614**. In another example, the top channel width **3616** and the bottom channel width **3617** may remain constant from the toe-end portion **3612** to the heel-end portion **3614**. In another example, the top channel width **3616** and the bottom channel width **3617** may vary independently from the toe-end portion **3612** to the heel-end portion **3614**. In another example, the top channel width **3616** and/or the bottom channel width **3617** may vary from the toe-end portion **3612** to the heel-end portion **3614** by between 25% and 75%. In another example, the top channel width **3616** and/or the bottom channel width **3617** may vary from the toe-end portion **3612** to the heel-end portion **3614** by between 35% and 65%. In another example, the top channel width **3616** and/or the bottom channel width **3617** may vary from the toe-end portion **3612** to the heel-end portion **3614** by between 40% and 60%. In another example, the top channel width **3616** and/or the bottom channel width **3617** may decrease continuously and uniformly from the toe-end portion **3612** to the heel-end portion **3614** (shown in FIGS. **35** and **36**). In another example, the top channel width **3616** and/or the bottom channel width **3617** may increase continuously and uniformly from the toe-end portion **3612** to the heel-end portion **3614** (not shown). In another example, the top channel width **3616** and/or the bottom channel width **3617** may change in a discontinuous or step-wise manner (not shown) from the toe-end portion **3612** to the heel-end portion **3614** (not shown). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The channel **3610** includes side walls **3619** and **3621**. Each side wall **3619** and **3621** may form a generally right angle (i.e., may be 90° or slightly offset from 90° relative to the bottom portion **3618**), an acute angle or an obtuse angle with the bottom portion **3618** of the channel **3610**. For example, as shown in FIG. **36**, each of the side walls **3618** and **3619** forms an obtuse angle (i.e., greater than 90°) with the bottom portion **3618**. Accordingly, the channel **3610** defines a valley-shaped channel or groove such that the top channel width **3616** is greater than the bottom channel width **3617** from the toe-end portion **3612** to the heel-end portion **3614**. In one example, the angle between the sidewalls **3618** and **3619** and the bottom portion **3618** may be between 90° and 160°. In another example, the angle between the sidewalls **3618** and **3619** and the bottom portion **3618** may be between 100° and 150°. In another example, the angle between the sidewalls **3618** and **3619** and the bottom portion **3618** may be between 110° and 140°. In another example, the angle between the sidewalls **3618** and **3619** and the bottom portion **3618** may be between 120° and 140°. The side walls **3619** and **3621** may form any angle with the bottom portion **3618**. The areas of joiner between the sidewalls **3619**, **3621** and the bottom portion **3618** may include a chamfer or a transition region. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The channel side walls **3618** and **3619** may also define the depth ( $D_c$ ) **3623** of the channel **3610**. The depth **3623** of the channel **3610** may be generally constant or may vary from the toe-end portion **3612** to the heel-end portion **3614**. In one example, the depth **3623** of the channel **3610** may decrease from the toe-end portion **3612** to the heel-end portion **3614**. In another example, as shown in FIG. **36**, the depth **3623** of the channel **3610** may increase from the toe-end portion **3612** to the heel-end portion **3614**. In one example, the depth

**3623** of the channel **3610** may be between 0.04 inch (0.09 cm) and 0.11 inch (0.28 cm) at the toe-end portion **3612** and between 0.06 inch (0.16 cm) and 0.19 inch (0.48 cm) at the heel-end portion **3614**. In another example, the depth **3623** of the channel **3610** may be between 0.05 inch (0.13 cm) and 0.09 inch (0.24 cm) at the toe-end portion **3612** and between 0.09 inch (0.22 cm) and 0.16 inch (0.41 cm) at the heel-end portion **3614**. In another example, the depth **3623** of the channel **3610** may be between 0.06 inch (0.16 cm) and 0.08 inch (0.21 cm) at the toe-end portion **3612** and between 0.11 inch (0.27 cm) and 0.14 inch (0.37 cm) at the heel-end portion **3614**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The channel **3610** may define a portion of the body portion **3310** from which mass has been removed to form the channel **3610**. The removed mass defined by the channel **3610** may be transferred to other portions of the body portion **3310** to impart certain characteristics to the golf club head **3300**. At least a portion of the removed mass defined by the channel **3610** may be transferred below the horizontal midplane **3720** of the body portion **3310** to lower the center of gravity of the golf club head **3300** while maintaining or substantially maintaining the overall mass of the body portion **3310**. Further, at least a portion of the removed mass defined by the channel **3610** may be transferred below the horizontal midplane **3720** of the body portion **3310** and closer to the toe portion **3340** than the heel portion **3350** to increase the MOI of the golf club head **3300**. In one example, the removed mass defined by the channel **3610** may be incorporated into the body portion **3310** below the horizontal midplane **3720** by increasing the volume of the body portion **3310** below the horizontal midplane **3720**. In other words, the volume and hence the mass of the body portion **3310** below the horizontal midplane **3720** may be increased. In another example, the removed mass defined by the channel **3610** may be incorporated into the body portion **3310** as additional weight portions as compared to a golf club head that does not have the channel **3610**. For example, the golf club head **3300** includes a greater number of weight portions of the second set of weight portions **3330** below the horizontal midplane **3720** as compared to the golf club head **100**. The increased mass below the horizontal midplane **3720** and/or toward the toe portion **3340** lowers the center of gravity and/or increases the MOI of the golf club head **3300**, respectively. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The masses of the weight portions of the first set of weight portions **3320** and/or the second set of weight portions **3330** may vary. The mass of each weight portion may be increased and/or decreased by changing the length, diameter and/or the material of construction of the weight portions. For example, the mass of a weight portion may be increased by increasing the length of the weight portion without increasing the diameter of the weight portion so that the weight portion can be used in any of the weight ports of the body portion **3310**. In another example, the mass of a weight portion may be increased by using a denser material for the weight portion. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

In one example, the masses of the second set of weight portions **3330** may decrease from the toe portion **3340** to the heel portion **3350** to increase the MOI of the golf club head **3300**. In one example, each of the weight portions of the second set of weight portions **3330** may have a reduced mass relative to an adjacent weight portion of the second set of weight portions **3330** in a direction from the toe portion **3340** to the heel portion **3350**. For example, the weight



portion 3338 may have a smaller mass than the weight portion 3339, the weight portion 3337 may have a smaller mass than the weight portion 3338, the weight portion 3336 may have a smaller mass than the weight portion 3337, the weight portion 3335 may have a smaller mass than the weight portion 3336, the weight portion 3334 may have a smaller mass than the weight portion 3335, the weight portion 3333 may have a smaller mass than the weight portion 3334, the weight portion 3332 may have a smaller mass than the weight portion 3333, and the weight portion 3331 may have a smaller mass than the weight portion 3332. In another example, groups of weight portions of the second set of weight portions 3330 may have similar masses and yet have a smaller overall mass than an adjacent group of weight portions in a direction from the toe portion 3340 to the heel portion 3350. For example, each of the weight portions 3331, 3332 and 3333 may have similar masses and yet have an overall mass that is less than the overall mass of the weight portions 3334, 3335 and 3336. Each of the weight portions 3334, 3335 and 3336 may have similar masses and yet have an overall mass that is less than the overall mass of the weight portions 3337, 3338 and 3339. Accordingly, the masses of the weight portions of the second set of weight portions 3330 may decrease in a direction from the toe portion 3340 to the heel portion 3350 in any manner. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

The configuration of the channel 3610, such as width, depth, volume, cross-sectional shape and any of the other characteristics described herein may vary as the channel 3610 extends from the toe-end portion 3612 to the heel-end portion 3614. Accordingly, the mass that is removed from the body portion 3310 due to the presence of the channel 3610 may similarly vary. According to another example, the masses of the weight portions of the second set of weight portions 3330 may correspondingly vary in a direction from the toe portion 3340 to the heel portion 3350 at a similar rate or a substantially similar rate as the variation in the channel configuration from the toe portion 3340 to the heel portion 3350. In another example, all of the weight portions of the second set of weight portions 3330 may have similar masses. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

FIG. 39 depicts one manner by which the interior cavity 700 of the golf club head 100 or any of the golf club heads described herein such as the golf club 3300 may be partially or entirely filled with an elastic polymer material or an elastomer material (e.g., an elastic polymer material 2820 of FIG. 28 such as a TPE material). The process 3900 may begin with bonding a bonding agent to the back surface 166 of the face portion 162 of the golf club head 100 (block 3910). The bonding agent may have an initial bonding state, which may be a temporary bonding state, and a final bonding state, which may be a permanent bonding state. The initial bonding state and the final bonding states may be activated when the bonding agent is exposed to heat, radiation, and/or other chemical compounds. For example, as described in detail herein, the bonding agent may be an epoxy having an initial cure state and a final cure state that are activated by the epoxy being heated to different temperatures for a period of time, respectively, by conduction, convection and/or radiation. In another example, the bonding agent may be a bonding material that is activated to an initial bonding state and a final bonding state by being exposed to different doses and/or duration of ultraviolet radiation, respectively. In another example, the bonding agent may be a bonding material that is activated to an initial bonding state and a

final bonding state by being exposed to different compounds or different amounts of the same compound, respectively. According to the process 3900, the bonding agent may be bonded to the back surface of the face portion by being activated to the initial bonding state. Elastic polymer material is then injected in the interior cavity 700 of the golf club head 100 (block 3920). The process 3900 then includes bonding the elastic polymer material to the bonding agent (block 3930). Bonding the elastic polymer material to the bonding agent includes activating the bonding agent to the final bonding state to permanently bond the elastic polymer material to the bonding agent and to permanently bond the bonding agent to the back surface 166 of the face portion 162. The example process 3900 is merely provided and described in conjunction with other figures as an example of one way to manufacture the golf club head 100. While a particular order of actions is illustrated in FIG. 39, these actions may be performed in other temporal sequences. Further, two or more actions depicted in FIG. 39 may be performed sequentially, concurrently, or simultaneously.

FIG. 40 depicts one manner by which the interior cavity 700 of the golf club head 100 or any of the golf club heads described herein may be partially or entirely filled with an elastic polymer material or an elastomer material (e.g., an elastic polymer material 2820 of FIG. 28 such as a TPE material). The process 4000 may begin with applying a bonding agent (e.g., a bonding portion 2810 of FIG. 28) to the back surface 166 of the face portion 162 of the golf club head 100 (block 4010). The bonding agent may be any type of adhesive and/or other suitable materials. In one example, the bonding agent may be an epoxy. Prior to applying the bonding agent, the golf club head 100 may be cleaned to remove any oils, other chemicals, debris or other unintended materials from the golf club head 100 (not shown). The bonding agent may be applied on the back surface 166 as described herein depending on the properties of the bonding agent. The bonding agent may be applied to the back surface 166 of the face portion 162 through one or more of the first set of weight ports 1420 and/or the second set of weight ports 1430. For example, the bonding agent may be in liquid form and injected on the back surface 166 through several or all of the first set of weight ports 1420 and the second set of weight ports 1430. An injection instrument (not shown) such as a nozzle or a needle may be inserted into each weight port until the tip or outlet of the injection instrument is near the back surface 166. The bonding agent may then be injected on the back surface 166 from the outlet of the injection instrument. Additionally, the injection instrument may be moved, rotated and/or swiveled while inside the interior cavity 700 so that the bonding agent may be injected onto an area of the back surface 166 surrounding the injection instrument. For example, the outlet of the injection instrument may be moved in a circular pattern while inside a weight port to inject the bonding agent in a corresponding circular pattern on the back surface 166. Each of the first set of weight ports 1420 and the second set of weight ports 1430 may be utilized to inject a bonding agent on the back surface 166. However, utilizing all of first weight ports 1420 and/or the second set of weight ports 1430 may not be necessary. For example, using every other adjacent weight port may be sufficient to inject a bonding agent on the entire back surface 166. In another example, weight ports 1421, 1422 1431, 1433 and 1436 may be used to inject the bonding agent on the back surface 166. The apparatus, methods, and articles of manufacture are not limited in this regard.

The process 4000 may also include spreading or overlaying the bonding agent on the back surface 166 (not shown)

after injecting the bonding agent onto the back surface 166 so that a generally uniform coating of the bonding agent is provided on the back surface 166. According to one example, the bonding agent may be spread on the back surface 166 by injecting air into the interior cavity 700 through one or more of the first set of weight ports 1420 and/or the second set of weight ports 1430. The air may be injected into the interior cavity 700 and on the back surface 166 by inserting an air nozzle into one or more of the first set of weight ports 1420 and/or the second set of weight ports 1430. According to one example, the air nozzle may be moved, rotated and/or swiveled at a certain distance from the back surface 166 so as to uniformly blow air onto the bonding agent to spread the bonding agent on the back surface 166 for a uniform coating or a substantially uniform coating of the bonding agent on the back surface 166. In one example, the golf club head 100 may be pivoted back and forth in one or several directions so that the bonding agent is spread along a portion or substantially the entire area of the back surface 166 of the face portion 162. In one example, the golf club head 100 may be vibrated with the back surface 166 of the face portion 162 in a generally horizontal orientation so that the bonding agent may spread or overlay on the back surface 166 in a uniform coating manner or a substantially uniform coating manner. The apparatus, methods, and articles of manufacture are not limited in this regard.

The example process 4000 is merely provided and described in conjunction with other figures as an example of one way to manufacture the golf club head 100. While a particular order of actions is illustrated in FIG. 40, these actions may be performed in other temporal sequences. Further, two or more actions depicted in FIG. 40 may be performed sequentially, concurrently, or simultaneously. The process 4000 may include a single action (not shown) of injecting and uniformly or substantially uniformly coating the back surface 166 with the bonding agent. In one example, the bonding agent may be injected on the back surface 166 by being converted into fine particles or droplets (i.e., atomized) and sprayed on the back surface 166. Accordingly, the back surface 166 may be uniformly or substantially uniformly coated with the bonding agent in one action. A substantially uniform coating of the bonding agent on the back surface 166 may be defined as a coating having slight non-uniformities due to the injection process or the manufacturing process. However, such slight non-uniformities may not affect the bonding of the elastic polymer material or elastomer material to the back surface 166 with the bonding agent as described herein. For example, spraying the bonding agent on the back surface 166 may result in overlapping regions of the bonding agent having a slightly greater coating thickness than other regions of the bonding agent on the back surface 166. The apparatus, methods, and articles of manufacture are not limited in this regard.

In one example as shown in FIG. 41, the bonding agent may be an epoxy having different curing states based on the temperature and the amount of time to which the epoxy may be exposed. The bonding agent may have an uncured state, an initial cure state, and a final cure state. In one example, the uncured state may be a liquid state, the initial cure state may be gel or a semi-solid/semi-liquid state, and the final cure state may be a solid state. The bonding agent may transition from the uncured state to the initial cure state when the bonding agent is heated to a temperature between an initial cure state temperature ( $Temp_i$ ) and a final cure state temperature ( $Temp_f$ ) for a period of time. Accordingly, an initial cure state temperature range may be defined by temperatures that are greater than or equal to the initial cure

state temperature  $Temp_i$  and less than the final cure state temperature  $Temp_f$ . The bonding agent may transition from the initial cure state to the final cure state when the bonding agent may be heated to a temperature greater than or equal to the final cure state temperature  $Temp_f$  for a period of time. Accordingly, a final cure state temperature range may be defined by temperatures that are greater than or equal to the final cure state temperature  $Temp_f$ . As shown in FIG. 41, the initial cure state temperature  $Temp_i$  and the final cure state temperature  $Temp_f$  may vary based on the amount of time that the bonding agent may be heated. In particular, a transition from the uncured state to the initial cure state and a transition from the initial cure state to the final cure state may be dictated by certain temperature and time profiles based on the properties of the bonding agent. At a temperature below the initial cure temperature  $Temp_i$ , the bonding agent may be in the uncured state (e.g., a liquid state). In the initial cure state, the bonding agent may form an initial bond with an object and become pliable to be manipulated (e.g., moved, spread, overlay, etc.) without obtaining full cross linking or forming a permanent bond. In other words, the bonding agent may form an initial bond with an object and be manipulated without forming a permanent bond. In the final cure state, the bond of the bonding agent (e.g., cross linking for a bonding agent that includes epoxy) may be complete or become permanently set.

The bonding agent may be applied to the back surface 166 of the face portion 162 when the bonding agent is in the uncured state, which may be a liquid state. Subsequently, the golf club head 100 and/or the bonding agent may be heated to a first temperature  $Temp_1$  that is greater than or equal to the initial cure state temperature  $Temp_i$  and less than the final cure state temperature  $Temp_f$  to change the bonding agent from an uncured state to an initial cure state (i.e., an initial cure state temperature range) (block 4020). Accordingly, the bonding agent may form an initial bond with the back surface 166 of the face portion 162. After bonding the bonding agent to the back surface 166, the golf club head may be cooled for a period of time at ambient or room temperature (not shown). Accordingly, the bonding agent may be in an initial cured state and bonded to the back surface 166 of the face portion 162 so that the bonding agent may be bonded to the back surface 166 during the injection molding of an elastic polymer material in the interior cavity 700. Ambient or room temperature may be defined as a room temperature ranging between 5° C. (41° F.) to 40° C. (104° F.). The first temperature  $Temp_1$  and duration by which the golf club head and/or the bonding agent heated to the first temperature  $Temp_1$  may depend on the curing or bonding properties of the bonding agent. The apparatus, methods, and articles of manufacture are not limited in this regard.

After the bonding agent is bonded to the back surface 166 of the face portion 162, the golf club head 100 may be heated (i.e., pre-heating the golf club head 100) prior to receiving the elastic polymer material (not shown). The golf club head 100 may be heated so that when the elastic polymer material is injected in the golf club head 100, the elastic polymer material is not cooled by contact with the golf club head and remains in a flowing liquid form to fill the internal cavity 700. The temperature to which the golf club head is heated, which may be referred to herein as a third temperature, may be similar to the temperature of the elastic polymer material when being injected into the internal cavity 700. However, the temperature to which the golf club head is heated may be less than the final cure temperature  $Temp_f$  of the bonding agent. Accordingly, the bonding agent may not transition from the initial cure state to the final cured state during the

injection molding process. Further, the pre-heating temperature of the golf club head **100** may be determined so that excessive cooling of the golf club head **100** may not be necessary after injection molding the elastic polymer material in the internal cavity **700**. Prior to being injected into the internal cavity **700**, the elastic polymer material may also be heated to a liquid state (not shown). The temperature to which the elastic polymer material may be heated may depend on the type of elastic polymer material used to partially or fully fill the interior cavity **700**. Further, the temperature to which the elastic polymer material is heated may be determined so that shrinkage of the elastic polymer material is reduced during the injection molding process. However, as described herein, the elastic polymer material may be heated to a temperature that is less than the final cure temperature  $Temp_c$  of the bonding agent. The apparatus, methods, and articles of manufacture are not limited in this regard.

As described herein, the cavity **700** may be partially or fully filled with the elastic polymer material by injecting the elastic polymer material in the cavity **700** (block **4030**). The injection speed of the elastic polymer material may be determined so that the interior cavity **700** may be slowly filled to provide a better fill while allowing air to escape the interior cavity **700** and allowing the injected elastic polymer material to rapidly cool. For example, the elastic polymer material may be a non-foaming and injection-moldable thermoplastic elastomer (TPE) material. The elastic polymer material may be injected into the interior cavity **700** from one or more of the weight ports described herein (e.g., one or more weight ports of the first and second sets of weight ports **1420** and **1430**, respectively, shown in FIG. **14**). One or more other weight ports may allow the air inside the interior cavity **700** displaced by the elastic polymer material to vent from the interior cavity **700**. In one example, the golf club head **100** may be oriented horizontally as shown in FIG. **14** during the injection molding process. The elastic polymer material may be injected into the interior cavity **700** from weight ports **1431** and **1432**. The weight ports **1421**, **1422** and/or **1423** may serve as air ports for venting the displaced air from the interior cavity **700**. Thus, regardless of the orientation of the golf club head **100** during the injection molding process, the elastic polymer material may be injected into the interior cavity **700** from one or more lower positioned weight ports while one or more upper positioned weight ports may serve as air vents.

According to one example, any one of the weight ports or any air vent on the golf club head **100** that may be used as air ports for venting the displaced air may be connected to a vacuum source (not shown) during the injection molding process. Accordingly, air inside the interior cavity **700** and displaced by the elastic polymer material may be removed from the interior cavity **700** by the vacuum source. Thus, a possibility of having trapped air pockets in the interior cavity **700** and/or a non-uniform filling of the interior cavity **700** with the elastic polymer material may be reduced. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

After the elastic polymer material is injected in the cavity **700**, the golf club head **100** may be heated to a second temperature  $Temp_2$  that is greater than or equal to the final cure temperature  $Temp_c$  of the bonding agent to reactivate the bonding agent to bond the elastic polymer material to the bonding agent (i.e., a final cure state temperature range) (block **4040**). The second temperature  $Temp_2$  and the duration by which the golf club head **100** is heated to the second temperature  $Temp_2$  may depend on the properties of the

bonding agent as shown in FIG. **41** to form a permanent bond between the golf club head **100** and the bonding agent and between the elastic polymer material and the bonding agent. The golf club head **100** may be then cooled at ambient or room temperature (not shown). According to one example, the characteristic time (CT) of the golf club head may be measured (not shown) after manufacturing the golf club head as discussed herein. CT measurements may determine if the golf club head conforms to CT rules established by one or more golf governing bodies.

The heating and cooling processes described herein may be performed by conduction, convection, and/or radiation. For example, all of the heating and cooling processes may be performed by using heating or cooling systems that employ conveyor belts that move the golf club head **100** through a heating or cooling environment for a period of time as discussed herein. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

An elastic polymer material with a low modulus of elasticity, such as a foaming elastic polymer material, may provide vibration and noise dampening for the face portion **162** when the face portion **162** impacts a golf ball. An elastic polymer material with a higher modulus of elasticity, such as a non-foaming elastic polymer material, may provide structural support to the face portion **162** in addition to providing vibration and noise dampening. Accordingly, a thin face portion **162** may be provided when the interior cavity **700** is filled with a non-foaming elastic polymer material since the elastic polymer material may provide structural support to the thin face portion **162**. In one example, the elastic polymer material that is injection molded in the interior cavity **700** may have a relatively high modulus of elasticity to provide structural support to the face portion **162** and yet elastically deflect to absorb the impact forces experienced by the face portion **162** when striking a golf ball. Thus, a non-foaming and injection moldable elastic polymer material with a relatively high modulus of elasticity may be used for partially or fully filling the interior cavity **700** to provide structural support and reinforcement for the face portion **162** in addition to providing vibration and noise dampening. That is, the non-foaming and injection moldable elastic polymer material may be a structural support portion for the face portion **162**. The apparatus, methods, and articles of manufacture are not limited in this regard.

While the above examples may describe an iron-type or a wedge-type golf club head, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of golf club heads.

The terms “and” and “or” may have both conjunctive and disjunctive meanings. The terms “a” and “an” are defined as one or more unless this disclosure indicates otherwise. The term “coupled” and any variation thereof refer to directly or indirectly connecting two or more elements chemically, mechanically, and/or otherwise. The phrase “removably connected” is defined such that two elements that are “removably connected” may be separated from each other without breaking or destroying the utility of either element.

The term “substantially” when used to describe a characteristic, parameter, property, or value of an element may represent deviations or variations that do not diminish the characteristic, parameter, property, or value that the element may be intended to provide. Deviations or variations in a characteristic, parameter, property, or value of an element may be based on, for example, tolerances, measurement errors, measurement accuracy limitations and other factors. The term “proximate” is synonymous with terms such as

“adjacent,” “close,” “immediate,” “nearby”, “neighboring”, etc., and such terms may be used interchangeably as appearing in this disclosure.

The apparatus, methods, and articles of manufacture described herein may be implemented in a variety of embodiments, and the foregoing description of some of these embodiments does not necessarily represent a complete description of all possible embodiments. Instead, the description of the drawings, and the drawings themselves, disclose at least one embodiment, and may disclose alternative embodiments.

As the rules of golf may change from time to time (e.g., new regulations may be adopted or old rules may be eliminated or modified by golf standard organizations and/or governing bodies such as the United States Golf Association (USGA), the Royal and Ancient Golf Club of St. Andrews (R&A), etc.), golf equipment related to the apparatus, methods, and articles of manufacture described herein may be conforming or non-conforming to the rules of golf at any particular time. Accordingly, golf equipment related to the apparatus, methods, and articles of manufacture described herein may be advertised, offered for sale, and/or sold as conforming or non-conforming golf equipment. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

Although certain example apparatus, methods, and articles of manufacture have been described herein, the scope of coverage of this disclosure is not limited thereto. On the contrary, this disclosure covers all apparatus, methods, and articles of articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

What is claimed is:

1. A golf club head comprising:

a body portion having a toe portion, a heel portion, a top portion, a sole portion, a back portion, a front portion having a face portion, an interior cavity at least partially filled with an elastic polymer material, and a channel on the back portion having a length extending from a first channel opening at a toe portion edge of the toe portion to a second channel opening at a heel portion edge of the heel portion, the channel having a width extending between the top portion and the sole portion and a depth extending between the back portion and the front portion, the length of the channel, the width of the channel and the depth of the channel defining a volume of the channel;

wherein the volume of the channel decreases from the first channel opening to the second channel opening, and wherein a mass of the body portion below the channel decreases in a direction from the toe portion to the heel portion according to the decrease in the volume of the channel from the first channel opening to the second channel opening.

2. A golf club head as defined in claim 1, wherein the channel extends from the toe portion at or above a horizontal midplane of the body portion to the heel portion at or below the horizontal midplane of the body portion.

3. A golf club head as defined in claim 1, wherein the body portion comprises a plurality of ports on the back portion below the channel.

4. A golf club head as defined in claim 1, wherein the body portion includes a plurality of ports on the back portion, and wherein a greater number of the ports of the plurality of ports are closer to the toe portion than the heel portion.

5. A golf club head as defined in claim 1, wherein the body portion includes a plurality of ports on the back portion,

wherein a greater number of the ports of the plurality of ports are below the channel than above the channel.

6. A golf club head as defined in claim 1 further comprising a plurality of ports on the back portion and a plurality of weight portions, wherein each port of the plurality of ports is configured to receive a weight portion of the plurality of weight portions.

7. A golf club head as defined in claim 1, wherein a face portion thickness comprises a thickness between about 0.02 inch (0.508 mm) and about 0.09 inch (2.286 mm).

8. A golf club head as defined in claim 1 further comprising a plurality of weight portions on the back portion, wherein masses of the weight portions decrease from the toe portion to the heel portion.

9. A golf club head comprising:

a body portion having a toe portion, a heel portion, a top portion, a sole portion, a back portion, a front portion having a face portion, and a channel on the back portion having a length extending from a first channel opening at a toe portion edge of the toe portion at or above a horizontal midplane of the body portion to a second channel opening at a heel portion edge of the heel portion at or below the horizontal midplane of the body portion, the channel having a width extending between the top portion and the sole portion and a depth extending between the back portion and the front portion, the length of the channel, the width of the channel and the depth of the channel defining a volume of the channel;

a plurality of weight portions on the back portion; wherein the volume of the channel decreases from the first channel opening to the second channel opening; wherein the plurality of weight portions below the horizontal midplane decrease in mass in a direction from the toe portion to the heel portion according to the decrease in the volume of the channel from the first channel opening to the second channel opening; wherein the volume of the body portion below the channel decreases in a direction from the toe portion to the heel portion according to the decrease in the volume of the channel from the first channel opening to the second channel opening; and

wherein the body portion comprises an interior cavity at least partially filled with an elastic polymer material.

10. A golf club head as defined in claim 9, wherein the plurality of weight portions are below the channel.

11. A golf club head as defined in claim 9, wherein a greater number of the weight portions of the plurality of weight portions are closer to the toe portion than the heel portion.

12. A golf club head as defined in claim 9, wherein a greater number of the weight portions of the plurality of weight portions are below the channel than above the channel.

13. A golf club head as defined in claim 9, wherein a face portion thickness comprises a thickness between about 0.02 inch (0.508 mm) and about 0.09 inch (2.286 mm).

14. A golf club head as defined in claim 9, wherein masses of the weight portions decrease from the toe portion to the heel portion.

15. A golf club head comprising:

a body portion having a toe portion, a heel portion, a top portion, a sole portion, a back portion, a front portion having a face portion with a face portion thickness extending between a front surface and a back surface, an interior cavity, and a channel on the back portion having a length extending from a first channel opening

39

at a toe portion edge of the toe portion at or above a horizontal midplane of the body portion to a second channel opening at a heel portion edge of the heel portion at or below the horizontal midplane of the body portion, the channel having a width extending between the top portion and the sole portion and a depth extending between the back portion and the front portion, the length of the channel, the width of the channel and the depth of the channel defining a volume of the channel, the body portion being associated with a body portion volume; and  
 an elastic polymer material in the interior cavity, the elastic polymer material being associated with an elastic polymer material volume,  
 wherein the elastic polymer material volume is related to the body portion volume by the equation  $0.2 \leq V_e / V_b \leq 0.5$ , where  $V_e$  is the elastic polymer material volume in units of  $\text{in}^3$ , and  $V_b$  is the body portion volume in units of  $\text{in}^3$ ;  
 wherein the volume of the channel decreases from the first channel opening to the second channel opening, and wherein a mass of the body portion and the body portion volume below the channel decrease in a direction from the toe portion to the heel portion according to the

40

decrease in the volume of the channel from the first channel opening to the second channel opening.  
 16. A golf club head as defined in claim 15, wherein the face portion thickness is related to the elastic polymer material volume by the equation  $0.01 \leq T_f / V_e \leq 0.2$ , where  $T_f$  is the face portion thickness in units of inches, and  $V_e$  is the elastic polymer material volume in units of  $\text{in}^3$ .  
 17. A golf club head as defined in claim 15, wherein the interior cavity is associated with an interior cavity volume, and wherein the interior cavity volume is related to the body portion volume by the equation  $0.2 \leq V_c / V_b \leq 0.5$ , where  $V_c$  is the interior cavity volume in units of  $\text{in}^3$ , and  $V_b$  is the body portion volume in units of  $\text{in}^3$ .  
 18. A golf club head as defined in claim 15, further comprising a plurality of ports below the channel and a plurality of weight portions, wherein each port of the plurality of ports is configured to receive a weight portion of the plurality of weight portions.  
 19. A golf club head as defined in claim 15, further comprising a plurality of weight portions on the back portion, wherein masses of the weight portions decrease from the toe portion to the heel portion.

\* \* \* \* \*