## **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(5:	1) International Patent Classification <sup>7</sup> :	A1	(11) International Publication Number:	WO 00/44327
	A61F 15/00		(43) International Publication Date:	3 August 2000 (03.08.00)

(21) International Application Number: PCT/GB00/00208

(22) International Filing Date: 26 January 2000 (26.01.00)

(30) Priority Data:

9901711.3 26 January 1999 (26.01.99) GB 9917443.5 23 July 1999 (23.07.99) GB 9917445.0 23 July 1999 (23.07.99) GB

(71) Applicant (for all designated States except US): EUROGENE LIMITED [GB/GB]; 12 St. James's Square, London SW1Y 4RB (GB).

(72) Inventor; and


- (75) Inventor/Applicant (for US only): BARKER, Stephen, George, Edward [GB/GB]; The Vascular Unit, Dept. of Surgery, Sir Jules Thorn Building, The Middlesex Hospital, Mortimer Street, London W1N 8AA (GB).
- (74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published

With international search report.

(54) Title: PROTECTIVE COVER FOR INJURED LIMBS



#### (57) Abstract

A device which comprises an enclosure of a plastics material, having an opening at an end thereof with fastening means to enable the opening to be closed around a limb or stump with an affected part contained within the enclosure, and including a fluid-absorbent material within the enclosure. The device is particularly suitable for use in the treatment of leg ulcers.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
$\mathbf{BF}$	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	$\mathbf{PL}$	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		
					-		

WO 00/44327 PCT/GB00/00208

#### PROTECTIVE COVER FOR INJURED LIMBS

#### Field of the Invention

5

10

15

20

25

30

This invention relates to a device for the protection of wounds on the human body and is concerned primarily with a device for protecting open wounds, such as ulcers, burns or traumatised or gangrenous tissue, for example on the hands, lower limbs and the feet.

#### Background of the Invention

In the United Kingdom at least, approx. 0.5 to 1% of the population at any one time suffers with venous and/or arterial ulceration affecting the lower limbs. Despite often vigorous treatments, either in hospital or by nurses in the community, leg ulcers may remain for several years. Often, even when healed, ulcers can recur and/or remain unhealed for many years. They also cause social problems, since the odour caused by infection is severe, and isolates the sufferer.

Typically, such a wound requires cleaning and dressing from twice daily to twice weekly, using expensive lotions and dressings, e.g. compression bandages, which often prove to have limited efficacy. The treatment is often very labour-intensive, in hospitals and even more so to the district nursing service.

In summary, the treatment of leg ulcers is expensive and often, has little or no effect. In addition, there are other types of wounds on limbs or stumps that require effective care. These include ulcers or wounds caused by diabetes, skin cancer or rheumatoid arthritis.

For example, a typical treatment for hand wounds and, in particular, burns is to clean the 'wound', then place the hand into a plastic bag and tip in either liquid paraffin or Flamazine (a topical antibiotic cream). In concept, the 'bag' protects the hand from trauma/secondary contamination, allows free movement of fingers ('auto-physiotherapy') and hence part-prevention of contractures, and allows visualisation of the hand. Often, a bag cannot easily be found, the medication cannot easily be found, and tape, to secure the bag, is wrapped so tightly that getting the bag off is difficult. Furthermore, all these same problems are encountered when the bag needs changing, especially if this is to be done in the home environment.

By way of example, an Accident & Emergency Department serving a catchment population of 180,000, sees between 1 and 3 persons per week having such hand wounds. Each requires once or twice daily dressings for an average of 10-12 days.

GB-A-2265314 discloses a protective article for securing around a body part, specifically an arm or leg. It comprises an inflatable protective shield formed from a breathable thermoplastic polyester urethane film, with a sealable cuff.

### Summary of the Invention

5

According to the invention, a device comprises an enclosure of a plastics material, having an opening at an end thereof with fastening means to enable the opening to be closed around a limb (or stump) with an affected part contained within the enclosure, and including a fluid-absorbent material within the enclosure. Such a device can facilitate the protection (and potentially also healing), of wounds by providing a beneficial environment around the wound.

10

15

20

According to a preferred aspect of the invention, a device that may be fitted around the end of a limb comprises an enclosure generally defined by a gas-impermeable or, perhaps, water vapour-permeable plastic material, the enclosure having an opening with fastening means, to enable the opening to be closed around a limb with an affected part contained within the enclosure, and another part, e.g. the opposed end of the enclosure having an internal lining of a fluid-absorbent material. An extra fluid-absorbent pad (or pads) may be positioned within and attached to the enclosure. An active filter (e.g. of charcoal) may be provided in association with means to vent gases through the wall of the enclosure and to reduce odours.

#### Description of the Invention

A device of this invention is intended to be applied around the end of limbs or limb stumps. For convenience, it may be described herein as a glove, sock or boot. In particular, a device intended to be fitted around a leg may be shaped as a sock or boot.

25

A device of the invention is intended for therapeutic use. It may be included within a sterile pack, for 'field' use.

The plastics material of the enclosure may comprise, for example, a 75  $\mu m$  ethyl methyl acrylate film. Such material is pliable and has a soft feel, for patient comfort.

30

In a preferred embodiment, the plastic material of the enclosure comprises a multi-layered construction of plastics, e.g. 3, 5 or 7 layers. There may be one or more intermediate layers of PVDC, EVOH or other material that resists the passage of gas. The plastic material may include a layer which is absorbent to odours, especially for use with leg ulcers. Such materials are used in the food-packaging industry. The

5

10

15

20

25

30

outer layers will conveniently be of EVA or LDPE; such materials allow the enclosure to be formed from two sheets which are welded around their peripheral edges. A different material may be used, which is water-vapour permeable, but still has antiodour properties.

The enclosure is preferably at least partially transparent, so that the wound is visible to the patient, nurse or physician. This is very practical in hospitals, since it avoids the need for the wound to be exposed on a consultant's visit, when that may not be otherwise considered necessary.

The absorbent lining material may be paper-based or, preferably, is of super-absorbent material. It is suitably attached to the enclosure by transverse weld lines. The opening in the enclosure may also include an internal absorbent lining, forming a "cuff". The fluid-absorbent material is provided in order to reduce the degree of excoriation of the limb part or stump, caused by the continual presence of water.

The fluid-absorbent pad(s) may be of a kind known for their super-absorbency. The active filter may comprise a charcoal material and may incorporate a valve adapted to relieve internal pressures that would otherwise cause ballooning of the enclosure.

The enclosure may also include a connection through which oxygen or other gases may be introduced into the enclosure. Hyperbaric oxygen is useful when a wound is infected by certain anaerobic organisms.

For use on the foot, the outer part of the enclosure opposite to the open end may have a reinforced part. More specifically, an external non-slip layer may be provided.

If desired, the device may include within, or have attached on to it, a capsule or pouch containing an agent such as liquid paraffin or Flamazine, and which may have a breakable seal, allowing release of the agent as required. Alternatively, an agent of this type may be applied when the device is changed.

A device according to this invention may be used to treat open wounds on the feet or legs of a body. For this purpose, the wound is first simply cleaned and the relevant limb enclosed within the device, to provide a substantially air-tight enclosure around the wound.

A device according to this invention can provide a warm and moist environment with adequate oxygenation, whilst maintaining the wound clean, without gross contamination occurring. The device is capable of containing odours. It can be

5

10

15

20

25

30

tolerated by the patient who can be kept mobile (if appropriate) whilst wearing the device and avoiding aggravation of the condition.

The device is simple enough that, as necessary, it can be reapplied by the patient, perhaps more than once a day. However, it may be unnecessary to change the device so often, once again saving nursing care.

The invention will now be described by way of example only with reference to the accompanying drawings. In the drawings:

Fig. 1 shows a wound-protecting boot embodying the invention, in flat form and in side elevation;

Fig. 2 shows the embodiment of Fig. 1 in section on X-X;

Fig. 3 shows a wound-protecting glove/sock embodying the invention, in flat form and in side elevation;

Fig. 4 shows the embodiment of Fig. 3 in section on Y-Y;

Fig. 5 is a part view of the attachment tape viewed from Z in Fig. 3;

Fig. 6 shows an alternative arrangement for the cuff of the embodiment of Fig. 3; and

Fig. 7 shows the alternative cuff construction of Fig. 6 in section.

Figs. 1 and 2 show a boot device for the protection and treatment of open wounds, and particularly for the protection and treatment of venous ulcerative disease of the lower limbs or gangrenous tissue. The boot is formed from two superimposed sheets of plastics material A and B, joined together by means of heat-sealing along edges C. The edges of the sheets are not sealed at the top end D which thus forms an opening for entry of a limb into the boot. In one construction, a single sheet is used with the side opposed to the end D folded over rather than being welded. The fold could, of course, be along another side.

The sheets each comprise a barrier film of the type which is used in the food packaging industry and for ostomy applications. Such films are generally multi-layered with a middle barrier layer being of, for example, a PVDC or a EVOH material. The sheets are mostly transparent, to allow the relevant area to be visually inspected.

The inner surfaces of the sheets A and B at the open end D include an absorbent layer E extending from the line E1 to the end D and secured by line welds E2 and E3. The end D may be fastened by pulling snugly around the limb and securing by means of a tab D2. This tab may have a peel-off paper layer covering an

WO 00/44327 PCT/GB00/00208

5

adhesive which can be pressed onto the outer surface of the boot, thus providing a snug fit around the limb.

The lower end of the boot has a similar lining F of comfortable, absorbent material on the inside surface. This lining extends between a securing weld F1 and the edge weld C, with an intermediate weld connection F2.

5

10

15

20

25

30

The inside surface of the boot includes a pad (or pads) of a super-absorbent material G retained by an overlaid porous paper membrane H and secured by a peripheral weld J. A small aperture K in the side is closed internally by a charcoal filter pad L which prevents the boot from ballooning and controls odour. A further aperture M in the side is closed by a rubber diaphragm N acting as a valve which permits oxygenation if required and by a suitable connection.

A reinforcing strip of plastics material P is provided adjacent the top D. This strip may include identifying markings.

The transparent plastics enclosure allows the wound to be inspected. The enclosure provides a warm environment and retains moisture. Excessive moisture is absorbed by the pad material F in the foot part of the boot, and by the material E in the upper part.

Oxygenation may be enhanced by feed through the diaphragm N, and this may be particularly desirable for the treatment of anaerobic organisms. Odour is controlled by the charcoal filter L (which also permits the interior to breathe) as well as by the inherent odour-absorbing properties of the middle laminate layer of the plastics material.

In use, the boot will normally be changed on a once or twice daily basis, and the wound area cleaned using saline. The boot is then applied and secured by the adhesive tab(s) D2 around, for example, the leg. In hospital, this procedure may take up to 5 minutes of a nurse's time; conventional dressings for leg ulcers often take 20-30 minutes to change.

The construction permits the patient to change his or her own device, at home. It also allows the patient to be freely ambulatory, especially if the outer surface at the foot includes a non-slip coating or layer.

Figs. 3 and 4 show a glove/sock device for the protection and treatment of open wounds and burns. The glove/sock is formed from two sheets of plastics material 1a and 1b joined together by means of heat-sealing or radio frequency-welding along the edges 1c. The edges of the sheets are not sealed at the (shaped)

WO 00/44327

5

10

15

20

25

30

PCT/GB00/00208

6

top and 1e which thus forms an opening for entry of a limb into the device. The other end 1d is formed by folding over the sheets which may then be formed from one piece.

The inner surfaces of the sheets at the open end 1e include a comfortable, absorbent paper layer 2 secured by line welds 2a. The end 1e may be fastened by pulling snugly around the limb and securing by means of a tab(s) T having a portion T3 attached to the cuff. The tab(s) T have a peel-off paper layer T1 removed by a pull-tab T2 and covering an adhesive which can be pressed onto the outer surface of the glove, thus providing a snug fit around the wrist.

As shown in Figs. 6 and 7, the inside surface of the glove may include a partially or fully circumferential pad 5 of a super-absorbent material retained by an overlaid porous paper membrane and secured by a peripheral weld 5a.

Especially for the treatment of burns, the glove may include burstable sachets within the enclosure, containing Flamazine or any other suitable agent. Alternatively, sachets of such material, ready for use, may be attached to the outside of the glove.

In use, the glove will normally be changed on a regular basis and perhaps several times per day, and the affected area cleaned using saline. The glove/sock is then applied and secured by the adhesive tab(s) T around for example, the wrist. The mostly transparent, soft plastic allows the wound to be inspected. The plastic provides a warm environment and retains moisture, excessive moisture being (super-) absorbed by the pad material 5 and by the material 2.

Whether the invention is embodied by the relatively simple glove/sock of Figs. 3-7 or by the boot of Figs. 1-2, such devices are simple and economical to construct, and easy to use. They can readily be constructed in a range of different sizes.

Remarkably, devices of the invention may have a beneficial therapeutic effect. This has been demonstrated in the case of a leg ulcer that had been treated by conventional methods for several months; after this time, the wound remained unsightly and produced a disgusting odour. After just one week's usage of the boot illustrated in Figs. 1-2, by the simple protocol described above, i.e. without dressings, both appearance and odour had improved; after another 10 days, infection had gone, and the wound had evidently started to heal.

More particularly, the boot has been used on 8 patients, one bilaterally, making a total of 9 legs. The mean age of the patients was 70 years (range 40-88 years). In

WO 00/44327 PCT/GB00/00208

7

5 patients, the boot was used for one week. In two cases, it was discontinued after 3 days.

The aetiology of the ulcers was: 3 mixed arterio-venous, 1 secondary to pressure necrosis, 1 'trash foot' secondary to drug abuse, 1 venous and 2 arterial. 3 patients were diabetic.

5

10

15

20

The length of time patients had had their ulcers ranged from 2 weeks to 6 years. Previous ulcer treatment had been simple dressings in all cases, Granuflex being used in 6 cases, jelonet in one and dry dressings in 1, all associated with additional gauze and crepe bandages.

The time taken to clean the ulcers ranged from 15 to 30 minutes per dressing change, which averaged 2 or 3 dressings per day. Wound swabs were taken in all cases. *Pseudomonas* was grown from 4 ulcers and *Staphylococcus aureus* from 3 limbs.


In each case, it took no more than 6 minutes to remove the boot, clean the ulcer and re-apply. There was an obvious improvement in 4 ulcers, with one limb becoming appropriate for application of a split skin graft (previously, the limb had been considered more likely to be amputated). In 2 cases, there was no discernible difference. The odour from infected ulcers was markedly improved in all cases.


5 Patients said the boot was comfortable or very comfortable to wear, 2 said it was uncomfortable (one had boots bilaterally) and one patient was unable to comment due to medical health. Fluid collection was the only problem, and can be readily rectified by the provision of absorbent padding.


5

### **CLAIMS**


- 1. A device which comprises an enclosure of a plastics material, having an opening at an end thereof with fastening means to enable the opening to be closed around a limb or stump with an affected part contained within the enclosure, and including a fluid-absorbent material within the enclosure.
- A device according to claim 1, wherein the enclosure is gas-impermeable.
- 3. A device according to claim 1, wherein the enclosure is of a multi-layer plastics construction including a gas-impermeable layer.
- 4. A device according to claim 3, wherein the construction includes an odour-10 absorbent layer.
  - 5. A device according to any of claims 2 to 4, wherein the enclosure includes means to vent gases through its wall.
  - 6. A device according to claim 5, wherein the venting means is in association with an active filter.
- 15 7. A device according to any preceding claim, wherein the enclosure is water vapour-permeable.
  - 8. A device according to any preceding claim, which is in the general shape of a sock or boot.
  - 9. A device according to claim 8, which additionally comprises a non-slip sole.
- 20 10. A device according to any preceding claim, for use in therapy.







SUBSTITUTE SHEET (RULE 26)



## INTERNATIONAL SEARCH REPORT

Int. mail Application No PCT/GB 00/00208

A. CLASS	FICATION OF SUBJECT MATTER A61F15/00						
11C /	A01F15/UU						
According t	o International Patent Classification (IPC) or to both national classific	ation and IPC					
B. FIELDS	<b>SEARCHED</b>						
	ocumentation searched (classification system followed by classificati	on symbols)					
IPC 7	A61F						
Documenta	tion searched other than minimum documentation to the extent that a	such documents are included in the fields a	earched				
Electronic o	ata base consulted during the international search (name of data ba	se and, where practical, search terms used	0				
	,	,,,,,	7				
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT						
Category °	Citation of document, with indication, where appropriate, of the rel	evant passages	Relevant to claim No.				
· ***							
P,X	DE 298 16 198 U (SIEWERT RONALD F	R)	1,7-10				
	25 February 1999 (1999-02-25)						
	page 5, paragraph 2 -page 6, para	agraph 2;					
	claims 13-16; figures						
χ	US 4 178 924 A (BAXTER SAMUEL H)		1,8-10				
	18 December 1979 (1979-12-18)		_,0 _0				
	column 2, line 25 -column 3, line	<b>≥ 10</b> ;					
	claims; figures						
χ	US 3 741 203 A (LIMAN P)		1,8-10				
<b> </b>	26 June 1973 (1973-06-26)		1,0-10				
	column 6, line 31 -column 8, line	e 52;					
	claims; figures						
٨	IIS 2 477 427 A (LABIDUS DOV)		1 5 6 0				
A	US 3 477 427 A (LAPIDUS ROY) 11 November 1969 (1969-11-11)		1,5,6,8, 10				
	the whole document		10				
	##4 460 mm mm						
Furt	her documents are listed in the continuation of box C.	Patent family members are listed	in annex.				
° Special ca	tegories of cited documents:	"T" fater document published after the inte	emational films data				
"A" docum	ent defining the general state of the art which is not	or priority date and not in conflict with	the application but				
considered to be of particular relevance invention							
filing date annot be considered novel or cannot be considered to							
which which	nt which may view doubts on promy casin(s) or is cited to establish the publication date of another n or other special reason (as specified)	involve an inventive step when the do "Y" document of particular relevance; the	dalmed invention				
"O" document referring to an oral disclosure, use, exhibition or cannot be considered to involve an inventive step when the document is combined with one or more other such docu-							
"P" docume	other means ments, such combination being obvious to a person skilled "P" document published prior to the international fling date but in the art.						
later t	later than the priority date claimed "&" document member of the same patent family						
Date of the	actual completion of the international search	Date of mailing of the international sea	arch report				
2	3 March 2000	31/03/2000					
N							
Name and I	European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer					
	NL – 2280 HV Rijewijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni,	Dougkas V					
	nalling address of the ISA  European Patent Office, P.B. 5818 Patentiaan 2	31/03/2000 Authorized officer					
		Douskas, K					

### INTERNATIONAL SEARCH REPORT

information on patent family members

Int. mail Application No PCT/GB 00/00208

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 29816198	U	25-02-1999	DE 19921203 A EP 0966892 A	30-12-1999 29-12-1999
US 4178924	A	18-12-1979	NONE	
US 3741203	A	26-06-1973	NONE	
US 3477427	Α	11-11-1969	NONE	<del></del>

Form PCT/ISA/210 (patent family annex) (July 1992)