



(11) **EP 1 914 343 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
12.09.2012 Bulletin 2012/37

(51) Int Cl.:
D06P 1/52 (2006.01) D06P 5/22 (2006.01)
D06P 5/30 (2006.01)

(21) Application number: **08001346.9**

(22) Date of filing: **31.10.2000**

(54) **Coating for treating substrates for ink jet printing, method for treating said substrates, and articles produced therefrom**

Beschichtung zur Behandlung von Substraten für Tintenstrahldruck , Verfahren zur Behandlung dieser Substrate und daraus hergestellte Artikel

Revêtement pour traiter des substrats pour impression par jet d'encre , procédé de traitement de ces substrats et articles produits

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

(30) Priority: **30.10.2000 US 702093**
04.11.1999 US 163741 P

(43) Date of publication of application:
23.04.2008 Bulletin 2008/17

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
00982068.9 / 1 240 383

(73) Proprietor: **KIMBERLY-CLARK WORLDWIDE, INC.**
Neenah, WI 54956 (US)

(72) Inventors:
• **Bagwell, Alison Salyer**
Alpharetta,
Georgia 30040 (US)

- **Branham, Kelly Dean**
Woodstock, GA 30188 (US)
- **Farris-Kister, Mary Elizabeth Cumming,**
Georgia 30040 (US)
- **Zelazoski, Leonard Eugene**
Kennesaw,
Georgia 30144 (US)

(74) Representative: **Beacham, Annabel Rose et al**
Dehns
St Bride's House
10 Salisbury Square
London
EC4Y 8JD (GB)

(56) References cited:
EP-A- 0 534 660 EP-A- 0 605 730
WO-A-99/54541 US-A- 5 073 448
US-A- 5 279 885

EP 1 914 343 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Field of the Intention

5 [0001] The present invention relates to coatings for treating ink jet printable substrates, which are intended to receive images when printed by ink jet printing devices. In particular, the present invention relates to coatings for treating textile substrates for ink jet printing, methods for treating said substrates, and articles produced therefrom. Such methods facilitate the use of such substrates in commonly available ink jet or laser printing devices, such as wide or narrow format ink jet and laser printers

Background of the Invention

10 [0002] Ink jet printing is a non-impact and non-contact printing method in which an electronic signal controls and directs droplets or a stream of ink that can be deposited on a wide variety of substrates. Ink jet printing is extremely versatile in terms of the variety of substrates that can be treated, as well as the print quality and the speed of operation that can be achieved. In addition, ink jet printing is digitally controllable. For these reasons, ink jet methodology has been widely adopted for industrial marking and labeling. In addition, ink jet methodology has also found widespread use in architectural and engineering design applications, medical imaging, office printing (of both text and graphics), geographical imaging systems (e.g., for seismic data analysis and mapping), signage, in display graphics (e.g., photographic reproduction, business and courtroom graphics, graphic arts), and the like. Finally, ink jet printing has now also been used to create an image on a variety of textile substrates. The use of ink-jet printing to create an image on textile fabrics has allowed for the rapid visualization of an aesthetic design on fabric without the use of expensive and often wasteful screen printing techniques. Such ink-jet printing methodology allows a designer or production facility to visualize a finished design in significantly less time than is usually necessary to burn a screen image of the design by typical screen printing methodology.

25 [0003] Both dyes and pigments have been used as colorants for such ink jet ink formulations. However, such materials do not always adhere well to substrates to which the ink is applied. For example, dyes may dissolve upon a substrate's contact with water. Thus images applied employing ink jet methodology may tend to run or smear upon repeated contact, or may be actually removed from the printed surface if exposed to substantial quantities of aqueous media (e.g., if an ink jet printed article is laundered). Moreover, images applied employing ink jet methodology may also tend to fade or washout upon prolonged exposure to visible, ultraviolet and/or infrared light. Furthermore, dyes applied to textile substrates may experience severe dye bleed upon application to the substrate. Finally, the color intensity of the image printed on a textile substrate using ink-jet methodology is often lacking in vibrancy.

30 [0004] The nature of textile substrates also poses specific problems when printing or imaging via ink jet print methods, which are not found with common ink jet substrates (e.g. paper or coated paper). For instance, the textile fibers can vary widely in composition, with each composition presenting a unique set of conditions for acceptable printing of the substrate. For example, cotton substrates may be very absorbent, such as in the case of aqueous-based inks. When ink is ejected from the ink channel of an ink jet printing device, it is rapidly absorbed into the fibers of the cotton substrate. Since these fibers are much larger than the fibers typically found in paper substrates, the color density or appearance of color brightness is significantly diminished due to the lack of retention of the colorant at the surface of the fibers. In addition, bleeding, mottle of the print pattern, and loss of image sharpness or clarity can often result from printing on the textile fabric itself.

35 [0005] Conversely, synthetic fibers such as polyester may be poorly wet by the aqueous inks and such inks may be only retained in the interstitial spaces between the fibers. This limited ink retention also causes the print-quality related problems outlined above.

40 [0006] Furthermore, the permanence of the printed image on textile fabrics is often achieved commercially by some post-printing curing process such as heating, steaming, or chemical fixation. These processes tend to be inefficient, requiring further washing and drying steps to remove unfixed colorant from the fabric. It is therefore desirable to enhance the permanence of the printed image on ink jet printable substrates, either in the presence or absence of a post-printing curing process step.

45 [0007] Polymeric materials are typically used commercially to modify the properties of both natural and synthetic textile fibers and substrates. These polymeric treatments may alter textile appearance or hand, reduce shrinking, reduce flammability, or alter other properties of the fiber or substrate. Treatments may even be employed to enhance the ease of printing and/or print performance when commercial printing processes, such as rotary screen printing, are employed. For instance, polyethylene oxide has been used to pretreat a starting cloth material so as to create an adequate textile substrate for ink-jet printing. As disclosed in U.S. Patent number 5,781,216 to Haruta et al., the use of polyethylene oxide treated textile substrates are described as being highly capable of providing images of great color depth with sufficient brightness and sharpness, but free of objectionable color bleed. While Haruta discloses such a polyethylene

oxide pretreatment with a cationizing agent, to thereby enhance the coloring ability of images, Haruta requires such treatment to thereafter be cured by additional heating, washing and drying steps.

[0008] Use of cationic polymers as part of a latex saturant in a hydroentangled fibrous web is disclosed in PCT US 98 12712 to Harris et al., which was published as WO99/00541. As described in WO99/00541, latex saturation is typically

5 followed by a drying step or other curing aids.
[0009] EP 0605730 discloses printed cloths. The cloths are preferably pretreated before being dyed to prevent bleeding of the dye liquid. Such a treatment may involve a softening and water repellent agent. Fixing agents such as sodium carbonate or sodium bicarbonate, hydrotropes and sizing agents may also be used. Urea is listed as one possible hydrotrope and water soluble quaternized cationic polymers are listed as possible sizing agents.

10 [0010] Use of imbibing solutions with sodium bicarbonate, sodium carbonate and urea are also known. Such imbibing solutions are typically used by textile mills in ink pastes along with other additives such as thickeners, and not in conjunction with coating treatments on the textile substrates themselves prior to being printed. The ink pastes are then rotary screen printed down onto the fabric substrates. However, an ink jet paste delivery system can not be used for ink jet printing because of the physical constraints of the ink jet printer technology. The salts in the pastes will corrode the ink jet printer heads. Use of ink pastes are also a wasteful process. Furthermore, even with the use of such pastes in a convention screen printing process, the process experiences a large amount of dye wash off following printing.

15 [0011] Accordingly, there is still a need in the art for ink jet printable substrate coatings and treatment methods which provide for high optical density with a minimum amount of bleeding on the substrate during and after imaging from ink jet printers. There is also a need in the art for such ink jet printable substrate treatment methods which can be applied to textile fabric substrates. In this regard, there is still a need in the art for methods for treating fabrics for receiving ink-jet ink formulations, which methods allow for improved colorfastness and color intensity in a wide variety of textile substrates. Finally, there is still a need in the art for such substrates which are not dependent upon an ink curing step for construction.

25 **Summary of the Invention**

[0012] In accordance with the present invention, it has been discovered that the color density and quality of the printed image, and the adhesion properties and/or colorfastness of acid and reactive dye-based ink jet ink formulations when applied to a variety of ink jet printable substrates, can be improved by treating the substrates with coating formulations used in conjunction with imbibing solutions. In particular, a wide array of textile fabric substrates can be treated to improve the colorfastness and washfastness of ink jet ink formulations. The treatment formulations include an aqueous coating formulation containing solids and comprising a cationic polymer or copolymer, a cationic or non-ionic fabric softener, urea and either sodium bicarbonate, sodium carbonate, or a combination thereof for reactive dye based inks. In particular, the treatment formulations include % cationic polymers or copolymers, and 5-20 % fabric softeners. Alternatively, the formulations may also include 0-80% of a polymeric latex binder so as to increase washfastness. These percentages are based on solids. Total solids content for the formulations typically range from 10-50 %. In an alternate embodiment, use of cationic polymer coatings in conjunction with a separate imbibing solution of either sodium bicarbonate or sodium carbonate and urea for reactive dye classes may be used. The present methods provide pathways to the fixation of dyes, irrespective of chemical class or textile fabric substrate, and do so without the need of any further ink curing process beyond drying under ambient conditions. In addition, efficacy of post printing processes such as steaming or curing may be enhanced by such formulations, reducing dye waste and further enhancing color vibrancy. Also, fixation of pigment or colorant may be enhanced by these formulations.

40 [0013] These and other features and advantages of the present invention will become apparent after a review of the following detailed description of the disclosed embodiments and the appended claims.

45 **Brief Description of the Drawings**

[0014]

50 FIGS.1A-1C illustrate exemplary cationic polymers for use in treatment formulations for substrates in accordance with the present inventive methods.

FIG.2 illustrates a schematic view of a dip and squeeze process for treating ink jet printable substrates.

55 **Detailed Description of the Invention**

[0015] In accordance with the present invention, there are provided aqueous coatings and methods to improve the adhesion properties and/or colorfastness/color density and washfastness of ink jet printable substrates in the absence

of a heating or post treatment curing step, said methods including treating a textile substrate with an aqueous coating formulation including cationic polymers or copolymers and cationic or non-ionic fabric softeners. In a desirable method, the method comprises treating a textile substrate with an aqueous coating formulation including 5-95 % cationic polymers or copolymers, and 5-20 % fabric softeners. As has been stated earlier, these percentages are percent of total solids, unless otherwise stated. For the purposes of this application, the percent of the total solids is calculated by dividing the dry parts value for a particular component by the total dry parts of all of the components of the formulation. The present invention is further directed to a treated ink jet printable substrate wherein the treatment comprises an aqueous coating formulation of cationic polymers or copolymers and cationic or non-ionic fabric softeners. A desirable embodiment of the present invention is a treated ink jet printable substrate wherein the aqueous coating treatment comprises 5-95 % cationic polymers or copolymers, and 5-20 % fabric softeners.

[0016] The cationic copolymers function in the formulation to attract and fix oppositely charged anionic dye molecules to the substrates, and in particular, textile fabric substrates. The polymers or copolymers may contain reactive residues or groups capable of crosslinking to the textile fibers, with themselves, or with other components present in the formulation. Such cationic resins may incorporate charge groups in the main polymer chains or polymer backbones, or as side groups in the polymer chains. An exemplary list of the structural formulas of such cationic polymers are illustrated in Figs. 1A-1C. The cationic polymers for use in the coatings may include but are not limited to, polymers and copolymers of diallyldialkylammonium monomers such as diallyldimethylammonium chloride, cationic acrylate and acrylamide such as acryloxyethyl dimethylammonium chloride or acrylamidoethyl dimethylammonium chloride monomers, quarternized vinylpyridine such as methyl vinylpyridine chloride, and polyalkylamine polymers and copolymers. Co-monomers in such systems may consist of ones which modify the flexibility, hydrophobicity, or mechanical properties of the polymer molecule. In addition, reactive and/or self-condensing monomers may be included to enhance adhesion to the textile fiber or other components in the formulation. Other examples of cationic polymers with charged groups in the main chain include epihalohydrin-amine polymers such as Reten™ 204 LS and Kymene™ 557 LX polymers of Hercules Incorporated, of Wilmington, Delaware. A specific example of a preferred cationic polymer resin is CP 7091 RV available from ECC International of Roswell, Georgia, with CP 7091 RV being a poly(diallyldimethylammonium chloride-co-diacetone acrylamide).

[0017] Suitable fabric softeners which may be used in accordance with the present inventive coatings/methods include, but are not limited to, Varisoft 222 of the Witco Corporation of Greenwich, Connecticut, Adogen 432 also of the Witco Corporation, Accosoft 550-75 of the Stepan Company of Northfield, Illinois, Alubrasoft Super 100 and Alubrasoft 116 of the BASF Corporation, Specialty Chemicals Division of Mt. Olive, New Jersey, and Ahcovel Base N-62 of ICI Surfactants or Hodgson Textiles Chemical of Mt. Holly, North Carolina. The fabric softeners are cationic or nonionic and provide the attributes of print quality and image brightness to the printed textile substrate. The fabric softener most suitable to a particular textile fabric substrate varies by fabric substrate. For instance, it has been found that the fabric softener Varisoft 222 performs better with cotton/banner fabric samples while Adogen 432 performs better with nylon/lycra samples.

[0018] In another embodiment of the present invention, the previously described coating treatments or formulations for ink jet printable substrates also include a latex binder in order to further enhance the adhesion and/or waterfastness of colorants on the textile fabric substrates. It has been found that coated ink jet receptive substrates including a latex binder provide high color density and saturation, superior print quality, reduction of wicking or bleeding, and enhanced ink absorption. Furthermore, the coating or treatment formulations provide a waterfast printed image when printing via an ink jet printing process, without the necessity of post-printing curing steps such as heating, steaming, chemical fixation, or radiation. Likewise, the present invention is also directed to a treated ink jet printable substrate wherein the treatment comprises an aqueous coating formulation of cationic polymers or copolymers, cationic or non-ionic fabric softeners, and a latex binder. A desirable embodiment of the present invention is a treated ink jet printable substrate wherein the aqueous treatment formulation comprises 5-95 % cationic polymers or copolymers, 5-20 % fabric softeners and 0-80% latex binder.

[0019] The treatment or coating formulations in this alternate embodiment consist primarily of cationic polymers and copolymers, cationic or non-ionic fabric softeners and a water-insoluble polymer in the form of a latex dispersion or emulsion. In particular, the treating formulation may include 0-80 % polymeric latex binder depending on the textile fabric substrate. The latex reinforcing polymers may be either nonionic or cationic. By way of example only, the latex materials may include vinylacetate, ethylene-vinylacetate, acrylate, styrene, and styrene-acrylate resins and other cationic or nonionic latexes. These resins may include reactive or self cross-linking groups in addition to inherent cationic functionality.

[0020] The aqueous coating formulations may also include other additives which effect the appearance or tactile properties of the finished substrate, such as optical brighteners. It should be recognized that all of the stated percentages are based on solids unless otherwise noted. Total solids content for the formulations typically range from 5-50 %, but desirably range from 5-32 %. More desirably the total solids content for the formulations range from 25-28 %.

[0021] Treatment formulations (compositions) for the textile substrates are made by adding the above components from stock solutions or dispersions, or as solids where appropriate, and mixing to homogeneity. Application of the

treatment formulation to the textile substrates may be carried out by any known means to those having ordinary skill in the art. For instance, fabric substrates may be treated by a standard padding (dip and squeeze) method and dried in a forced air oven, although any suitable drying means of textiles known to those skilled in the art may be employed. As can be seen in FIG.2 showing a schematic view of a dip and squeeze process 10 for treating ink jet printable substrates, a textile substrate 20 is unwound from the incoming roll 30 and is then dipped in a saturator tank/bath 40 for sufficient time for it to become saturated with the treating formulation. The textile substrate is then run through a pressurized nip roll set 44 and 48. The pressure on the rolls should be in the range of 69-828 KPa (10-120 psig) but desirably in the range of 69-448,5 KPa (10-65 psig), depending on the type of textile fabric substrate utilized, and the total solids content of the treatment formulations used. The pressurized nip rolls squeeze the coating evenly onto the substrate so as to penetrate the surface of the substrate. The rolls may be either rubber or steel, however a set of rolls in which at least one roll being rubber is desirable. Following passage through the nip pressure rolls, the textile substrate is coursed through a drying means 50. The drying means may include a tenter frame for holding the textile substrate, and may itself encompass multiple consecutive drying means depending on the nature of the substrate to be dried. The drying temperature is desirably in the range from 200° F to 325° F (93.3 to 162.8° C), desirably between 220 to 250° F (104.4 to 121.1 °C). The typical time for drying is between about 30 seconds and 3 minutes. Following drying, the finished treated textile substrate is taken up on a wind up roll 52. The textile substrate may be rolled up for storage or moved to a second lamination process in preparation for ink jet printing. The textile substrate may be laminated to a carrier backing for ease of printing.

[0022] Using this application method, dry pick-up ratios of the textile substrate may vary from 0.5% to 50%. Desirably, the dry pick-up ratios may vary from 3 to 20%. More desirably, the dry pick-up ratios may vary from 6 to 15%. Wet pick-up ratios for the textile substrates are typically between 30-150%. Desirably such wet pick-up ratios are between 80-120%. Desirably for Dacron banners, the wet pick up ratios are between 40-120 %. These terms are defined by equations which follow.

[0023] Substrates which may be treated in accordance with the present inventive methods are varied and include paper, fabric, films, and the like, although textile fabric substrates are preferred. Such fabrics may include cotton, silk, wool, polyester, rayon, nylon, and blends thereof. Furthermore, the disclosed ink jet substrates may provide the benefits disclosed herein with or without further post-printing curing steps involving the use of heat, radiation or pressure. Ideally such treated substrates provide adhesion and/or colorfastness of the colorant with only ambient or room temperature curing or drying of the printed image. It should be noted however, that while not being necessary for the process, a post printing curing step may further enhance the colorfastness and washfastness of the printed image on the substrate. The basis weight of the various fabrics which may be treated by these formulations may range from 2 ounces per square yard (osy) to 9 osy (67.7 to 304.65 g/m²).

[0024] Dye classes which may be used in ink jet printers to be printed on such substrates include acid dyes, reactive dyes, direct dyes, azoic dyes, sulfur dyes, modified dyes, polymeric dyes, copolymerized dyes or other classes of colorants known to those skilled in the art. Furthermore, pigment colorants may be used in the ink jet printers to be printed on such substrates. Additionally, it has been found that when such substrate is printed with ink jet inks containing additives, such as those described in U.S. Application bearing Serial Number 09/109,681 filed July 2, 1998 and U.S. Patent No. 5,897,694, such substrate treatments may be enhanced so as to provide enhanced colorfastness and washfastness.

[0025] In a further embodiment of the present invention, such previously described treatment formulations may be used in a method to treat banner textile fabric substrates. Such substrate materials include 100% cotton, 100 % polyester, 100% silk, nylon, rayon and blended materials, such as blends of cotton and polyester, as well as nonwoven materials. For instance, it has been found that the pretreatment of banner textile fabric substrate with an aqueous coating formulation including cationic polymers, fabric softeners, and latex polymer binders in accordance with the previously described methods enable the banner substrates to be ink jet printable, with improved colorfastness/ color density and washfastness, and with reduced color bleed. Likewise, the present invention is also directed to a treated ink jet printable banner substrate wherein the treatment comprises a formulation of cationic polymers or copolymers, fabric softeners, and an optional latex binder. A desirable embodiment of the present invention is a treated ink jet printable banner substrate wherein the aqueous treatment formulation includes between 5-95 % cationic polymers or copolymers, between 5-20 % cationic or non-ionic fabric softeners and between 0-80% latex binder.

[0026] In accordance with yet another embodiment of the present invention, there are provided articles produced by the above described methods, employing treated textile substrates as described herein. Such articles may include for example banners, wall coverings and other home furnishing products. Thus according to the present invention, ink jet printed images applied to a treated substrate as described herein, resists removal of said image from said substrate, even upon repeated contact of the printed substrate with water. Such repetitive contact can be the result of normal handling of an article, accidental exposure to liquid, and routine laundering of the article. When articles according to the present invention comprise a treated substrate containing an ink jet image printed thereon, the resulting image adheres sufficiently to said substrate to resist removal therefrom upon washing of said article. The present invention including

EP 1 914 343 B1

each of the various embodiments is further described by the examples which follow. Such examples however, are not to be construed as limiting in any way either the spirit or the scope of the present invention.

Preliminary Examples

5
 [0027] Textile substrate samples were first printed with a test pattern using a commercial ink jet printer utilizing commercial ink jet inks containing acid, reactive, and/or direct dyes. Color density, color bleed, and print quality were evaluated on the samples as printed. These textiles included cotton poplin textile substrates. Duplicates of both sets of samples were washed using a washing method as described. Color density, color bleed, print quality or appearance, and color
 10 permanence were evaluated using the washed samples. Data from the preliminary examples is expressed in Table 1 which follows.

TABLE 1

INK	INK ADDITIVE	FABRIC TREATMENT	HEAT TREATMENT	COLORFAST EVAL WATER DELTA E	DETERG. DELTA E
Encad GA	none	none	none	< 56	<82
Encad GA	none	0.5% CP 7091 RV	none	< 29	< 66
Encad GA	none	1.0 % CP 7091 RV	none	< 28	< 50
Encad GA	none	2.0% CP 7091 RV	none	< 27	< 32

[0028] CP 7091 RV= is a diallyldimethylammonium chloride/diacetone acrylamide copolymer, ECC International. Encad GA inks employ standard monomeric dyes. Samples were hand washed. The sampling tested magenta inks. Delta E was calculated in the samples utilizing the spectrodensitometer and equation described below. The sampling was produced using a dip and squeeze method, as previously described. As can be seen, the coating in the Preliminary Examples only included cationic polymer in the aqueous formulation. Percent represents percent solution.

[0029] A second more rigorous set of tests and examples were run on a variety of fabric substrates. These textile fabric substrates include the materials listed in Table 2.

Table 2

FABRIC	STYLE	Construction	SOURCE	BASIS WEIGHT (OZ/YD²)	BASIS WEIGHT SI UNITS (G/M²)
Polyester poplin	PP 6248	Plain Weave	Fisher Textiles	3.8	128.8
Polyester satin	PS241	Satin	"	4.1	139.0
250 Denier Dacron Poly.	250 Dacron	Plain Weave	"	3.2	108.5
Cotton Poplin	9680	"	Lorber Indust.	6.5	220.39
Cotton Jersey	5118	Knit	"	8.2	277.9
Cotton Sheeting		Plain Weave	Cranston Mills	7.0	237.2
.16 mm Silk Charmeuse	12104	Satin	U.S. Silk, Inc.	2.0	67.8
Silk crepe decline. 18 mm	14654	Crepe	"	2.3	78.0
Polyester Georgette	NOFU7-6058A	Crepe Georgette	Scher Fabrics,	3.8	128.8
Polyester stretch crepe		Knit	Inc. "	3.2	108.5
Poly./lycra Blend	55153	Knit	Guilford Mills	5.5	186.4
Nylon/lycra blend	56062	Knit	"	4.0	135.6

EP 1 914 343 B1

(continued)

FABRIC	STYLE	Construction	SOURCE	BASIS WEIGHT (OZ/YD²)	BASIS WEIGHT SI UNITS (G/M²)
Rayon	YWSR 1352	Crepe	U.S. Silk, Inc.	3.5	118.6

[0030] U.S. Silk, Inc. is located in New York, NY. Guilford Mills is located in New York, NY. Scher Fabrics, Inc. is located in New York, NY. Cranston Mills is located in Cranston, RI. Lorber Industries is located in Gardena, CA. Fisher Textiles is located in Indian Trail, NC.

Conditions for Second Set of Examples

Printing Steps

[0031] In each of the following examples, treated textile samples were printed using an Encad Pro E (@ 300dpi) ink jet printer obtained from Encad Inc. of San Diego, California. Encad GA, GS, or GO inks were employed using 4-Pass Enhanced Print Mode, that is with the printer passing over the textile substrate four times. In some instances, as noted as double strike in data tables, the printing head was preheated and option identified as number "7" was selected on the printer. This option enabled more ink to be expelled from the printer onto the substrates. Dyes in the inks consisted of reactive, acid, and/or dyes and are described in Table 3 .

TABLE 3

Inks Used		
<u>GS Ink</u>		
<u>Color</u>	<u>Order#</u>	<u>Dyes</u>
Cyan	209489	Direct
Magenta	208163-2	Acid /Reactive
Yellow	208163-3	Acid
Black	208163-4	Direct
<u>GO Ink</u>		
<u>Color</u>	<u>Order#</u>	
Cyan	208165-1	Pigment
Magenta	208165-2	Pigment
Yellow	208165-3	Pigment
Black	208165-4	Pigment
<u>GA Ink</u>		
<u>Color</u>	<u>Order#</u>	<u>Dyes</u>
Cyan	209491	Direct
Magenta	209490	Acid
Yellow	208164-3	Acid
Black	208164-4	Direct

[0032] Sample sizes were typically 11 by 15 inches (27.9 by 38.1 cm). Additionally, a floral three color print, using lavender, green and magenta was used for testing, of approximately 14 by 25 inches (35.6 by 63.5 cm) in size. Where it was difficult to distinguish between shades of green, a neutral portion (that is free of ink) of the sample was also evaluated.

Color Measurements

[0033] L* a* b* color values measurements (CIE 1976 Commission Internationale de l'Eclairage) and optical density were made of the printed textile substrates using an X-Rite 938 Spectrodensitometer (D65/10°) using CMY filters, in accordance with the operator's manual. The X-Rite spectrodensitometer was obtained from the X-Rite Corporation of Grandville, Michigan. Average optical densities were taken as the sum of the average of three measurements using each filter. Delta E is calculated in accordance with the following equation:

$$\Delta E = \text{SQRT} [(L^*_{\text{standard}} - L^*_{\text{sample}})^2 + (a^*_{\text{standard}} - a^*_{\text{sample}})^2 + (b^*_{\text{standard}} - b^*_{\text{sample}})^2]$$

[0034] The higher the Delta E, the greater the change in color intensity. Unless the color's intensity is increased by a curing step, a large increase in delta E would typically be indicative of fading. The testing was in accordance with ASTM DM 224-93 and ASTM E308-90. Where values for delta E are less than 3.0, it is generally accepted that such color change cannot be observed with the human eye. A detailed description of spectrodensitometer testing is available in Color Technology in the Textile Industry, 2nd Edition, Published 1997 by AATCC (American Association of Textile Chemists & Colorists).

Washing Method for Textile Samples

[0035] When indicated, textile samples were washed using the following method. Samples were placed in an appropriate size beaker or container such as a one liter beaker. Samples were then placed under cold running water (between approximately 10-20° C) for approximately two minutes. The cold water was then drained from the textile samples. The beakers were then refilled with hot water (between approximately 40-50° C), and one ounce (28.3 g) of detergent (Synthrapol ® per gallon (3.79 l) of water was added to the beakers).

[0036] The textile samples were then washed out for approximately five minutes and then rinsed and drained of remaining water. Finally, the textile samples were rinsed with warm water (of between approximately 25-30° C) for two minutes followed by a rinse with cold water (of between approximately 10-20° C) for approximately one more minute.

[0037] Typically, although not necessarily required for curing, a second set of samples were printed and subsequently steamed using a laboratory steamer for comparison. For the purposes of the examples, if a colorfastness level is characterized as poor, bleeding or wicking has occurred. If a washfastness level has been characterized as poor, the image has washed out. If a colorfastness and washfastness level has been characterized as good, the color vibrancy and image retention is noticeably better than the poor level. If the colorfastness and washfastness levels are characterized as excellent, the color properties and vibrancy are the highest levels with the highest color density.

Examples

[0038] It should be noted that for each of the following examples, the textile substrate had been laminated to an adhesive coated paper backing which was obtained from American Builtrite, Inc. under the designation ProtecRite ® 6798 prior to printing to enable the substrate to be easily coursed through the printer. The substrates were then removed from the backing prior to washing. Adhesive coated backing papers identified by the designation 6798 include a paper having a nominal thickness of 5.4 ml (137.2 µm), an initial adhesion value of 27 oz/in (300 g/cm), a tensile strength of 16 lbs/in (2.86 kg/cm), and an elongation capability of 10 %. The batch formulations utilized are described in the following example summaries.

[0039] **Example 1. (Comparative)** Cationic copolymer CP 7091 RV (ECC International), poly(diallyldimethylammonium chloride-co-diacetone acrylamide), was obtained in a 49.3% stock solution in water. 20.3 wet parts of this solution (10 dry parts, or approximately 90-91 % of the total dry parts) were added to 70.3 parts water with mixing. 1.1 wet part (1 dry part, or approximately 9 % of the total dry parts) Varisoft® 222 fabric softener (90% in water) was added and the entire solution was mixed until homogeneous. This formulation was used to treat 100% cotton poplin via a padding application and dried as previously described. A portion of this sample was laminated to an adhesive paper carrier, printed with an ink jet printer and dried under ambient conditions. The properties of the sample were evaluated for quality of the printed image, ink retention, and color density or saturation under the following conditions: 1) immediately after printing, 2) after printing and washing, 3) after printing and steaming, 4) after printing, steaming and washing. The printed samples exhibited superior image quality with little or no bleed, excellent ink retention, and excellent color density. Samples that were steamed exhibited excellent enhancement of color and appearance. Washfastness of steamed samples and samples not post-treated with steam exhibited moderate retention of color when washed. This Example utilized the GS ink set.

5 [0040] **Example 21. (Comparative)** 50.7 wet parts cationic copolymer CP 7091 RV (ECC International) (49.3% in water)(25 dry parts, or approximately 18-19 % of the total dry parts) was added to 656.0 parts water with mixing. 90.6 wet parts Airflex® 540 latex emulsion (ethylene-vinyl acetate copolymer, 55.2% in water)(50 dry parts, or approximately 37 % of the total dry parts), 114.9 wet parts PrintRite® 591 acrylic emulsion (BF Goodrich, 43.5% in water)(50 dry parts, or approximately 37 % of the total dry parts), and 212.8 wet parts Varisoft® 222 fabric softener (4.7% in water) (10 dry parts, or approximately 7 % of the total dry parts) were added and the entire solution was mixed until homogeneous. This formulation was used to treat 100% cotton poplin via a padding application and dried. The sample was printed and evaluated using the process described in Example 1. The printed sample exhibited superior image quality with little or no bleed, excellent ink retention, and excellent color density. Samples that were not steamed exhibited good retention of color when washed. Samples that were steamed exhibited excellent enhancement for color and appearance. Permanence of color to washing was dramatically increased compared to untreated samples. Little measurable washout was detected. The Example utilized the GS ink set.

10 [0041] **Example 24. (Comparative)** 10.1 wet parts cationic copolymer CP 7091 RV (ECC International) (49.3% in water)(5 dry parts, or approximately 45 % of the total dry parts) was added to 48.8 parts water with mixing. 11.5 wet parts PrintRite® 591 acrylic emulsion (BF Goodrich, 43.5% in water)(5 dry parts, or approximately 45 % of the total dry parts), and 21.3 wet parts Varisoft® 222 fabric softener (4.7% in water) (1 dry part, or approximately 9 % of the total dry parts) were added and the entire solution was mixed until homogeneous. This formulation was used to treat 100% cotton poplin via a padding application and dried. The sample was printed and evaluated using the process described in Example 1. The printed sample exhibited superior image quality with little or no bleed, excellent ink retention, and excellent color density. Samples that were not steamed exhibited good retention of color when washed. Samples that were steamed exhibited excellent enhancement for color and appearance. Washfastness of steamed samples and samples not post-treated with steam exhibited moderate retention of color when washed. The Example utilized the GS ink set.

15 [0042] **Example 28. (Comparative)** 10.1 wet parts cationic copolymer CP 7091 RV (ECC International) (49.3% in water)(5 dry parts, or approximately 45 % of the total dry parts) was added to 51.2 parts water with mixing. 9.1 wet parts Airflex® 540 latex emulsion (ethylene-vinyl acetate copolymer, 55.2% in water)(5 dry parts, or approximately 45 % of the total dry parts), and 21.3 wet parts Varisoft® 222 fabric softener (4.7% in water)(1 dry part, or approximately 9 % of the total dry parts) were added and the entire solution was mixed until homogeneous. This formulation was used to treat 100% cotton poplin via a padding application and dried. The sample was printed and evaluated using the process described in Example 1. The printed sample exhibited superior image quality with little or no bleed, excellent ink retention, and excellent color density. Samples that were not steamed exhibited good retention of color when washed. Samples that were steamed exhibited excellent enhancement for color and appearance. Permanence of color to washing was dramatically increased compared to untreated samples. The Example utilized the GS ink set.

20 [0043] The present invention relates to treatments/coating formulations and related methods for treating textile substrates which enhance the color brilliance, adhesion, and/or waterfastness/detergentfastness of inkjet reactive dye, acid dye, and pigment based inks on textile fabric substrates when textile post treatment is desired (i.e. a heating step, such as steaming, oven heating, ironing, or other form of curative step), which utilizes an imbibing solution in conjunction with a substrate coating. For the purposes of this application, an imbibing solution shall mean a solution used to saturate a fabric such that it penetrates the interstitial spaces of the fabric. The coating solution (or treatment, as has earlier been described) itself may include the imbibing solution, or in the alternative, the coating solution and imbibing solution may be applied in separate application steps.

25 [0044] The treatment or coating formulations in the present invention consist primarily of cationic polymers, cationic or non-ionic fabric softeners, and other additives similar to those previously described. However, in conjunction with these coating formulations, an imbibing solution is used to further treat the fabric substrate. For example, in a first embodiment utilizing the imbibing solution with reactive ink sets, an imbibing solution consisting of either sodium bicarbonate or sodium carbonate and urea, (for added color brilliance with post-treatment) is used with a aqueous coated fabric treatment. The imbibing solution is desirably applied at a level of between 5-20 % by weight, more desirably 5-10 % by weight, depending on fabric type, and by using a standard saturation/padding method. When the imbibing solution is made a part of the aqueous coating composition, desirably, the sodium bicarbonate, sodium carbonate, or combination is present in the imbibing/coating solution in an amount between 3 and 10 percent of the total solids. Desirably, the urea is present in the combined imbibing/coating solution in an amount between 5 and 12 percent of the total solids. Other additives may be included in the combined coating/imbibing solution such as wetting agents, and defoamers. If additives are present in the formulation, they are desirably present in an amount between 0.1 and 1 percent of the total solids. For instance, the wetting agent Q2-511 may be included in the combined coating/imbibing solution. Optionally, dye fixatives may also be included in the coating formulation at less than 5 % of the total solids.

30 [0045] When the imbibing solution is applied as a separate solution following the coating formulation application, the sodium bicarbonate/sodium carbonate is also desirably present in an amount between 30 and 40 percent of the total solids. The urea is present in the separate imbibing solution in an amount between 50 and 70 percent solids. When the imbibing solution is used as a separate solution from the coating formulation, it may also include a wetting agent in

EP 1 914 343 B1

solution as well as other additives in the same amounts as the prior embodiment. Water is present in solution in an amount between 10 and 90 percent of the solution. As has been stated, this imbibing solution embodiment is desirably used with the reactive colorant classes, including those which may be applied via ink jet printing processes such as the monochlorotriazines and/or vinyl sulfones.

[0046] Textile substrates for use with the treatment methods may include cotton, silk, linen, polyester, rayon, nylon, and blends thereof. Conventionally, reactive dyes are used for cotton substrates and acid dyes are used for silk and nylon substrates. However, because of the coating treatment and fixation treatment (imbibing solution) associated with it, the invention allows for the fixation of classes of dyes on substrates that they are not normally associated with, or which would not be done commercially because the fixation is not normally facile or efficient. As demonstrated by the set of examples which follow, the disclosed ink jet receptive substrates that have been further treated with an imbibing solution provide high color density and saturation, superior print quality, reduction of wicking or bleeding, and enhanced ink absorption. Furthermore, the coating or treatment formulations provide a color enhanced waterfast/detergentfast printed image when printed with an ink jet printing process with post-printing treatment steps, such as heating, steaming, chemical fixation, or radiation curing. With a conventional steaming process, minimal dye washout occurs, thus minimal dyewaste occurs.

[0047] The present invention is further described by the set of examples which follow. Such examples, however, are not meant to be construed as limiting.

EXAMPLE CONDITIONS:

[0048] A series of coatings were created including cationic polymers, fabric softeners, latex binders, other additives and water. The coatings are identified below with the respective content percentages. It should be noted that certain coatings included an imbibing solution within their formulation while others did not, and an imbibing solution was therefore utilized in a separate application step. Batch sizes are expressed in grams.

First Coating (similar to that used in the previous Example 21), referred to as Types A, B & D in the examples which follow, for use with cotton fabrics

[0049]

ORDER OF ADDITION INGREDIENTS	% TOTAL DRY SOLIDS	PARTS	WET PARTS	BATCH SIZE (GRAMS)
CP7091RV	49.30	18.50	37.53	18.01
AirFlex 540	55.17	37.00	67.07	32.19
PrintRite 591	43.50	37.00	85.06	40.83
Varisoft 475	10.00	7.40	74.00	35.52
j Water			569.69	273.45
	12	100	833.33	400

Separate Imbibing Solution referred to as Type C for use with cotton fabrics

[0050]

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
Sodium Bicarbonate	63.40	3.00	4.73	22.70
Urea	95.00	5.00	5.26	30.81
Q2-5211	100.00	0.20	0.20	1.17
Water			58.34	341.49
	12	8.2	68.33	Approx. 400

[0051] The Dyeset concentrations (Polyamines), designated as Dyeset Conc. in the tables that follow, were obtained

EP 1 914 343 B1

from Sybron Chemicals of Wellford, South Carolina, along with Dyeset NOZ and Dyeset NFS. Such materials are dye fixatives for reactive dyes. The Q2-5211 which is a wetting agent, was obtained from Dow Coming. The sodium bicarbonate can be obtained from VWR of Norcross, Georgia and Baker Chemical, and the Urea can be obtained from Baker Chemical.

5 **[0052]** The "Combo", which is a combination of a coating and imbibing solution, referred to in the examples which follow as Type E, for use with cotton fabrics.

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP709IRV	49.30	16.50	33.47	16.06
AirFlex 540	55.17	35.00	63.44	30.45
PrintRite 591	43.50	35.00	80.46	38.62
Varisoft 475	10.00	5.40	54.00	25.92
Sodium Bicarb	63.40	3.00	4.73	2.27
Urea	95.00	5.00	5.26	2.53
Q2-5211	100.00	0.20	0.20	0.10
Water			591.97	284.15
	12	100	833.33	400

Coating (similar to that of Previous Example 21), referred to in the following examples as Type F, used for cotton fabrics

25 **[0053]**

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP709IRV	49.30	17.50	35.50	17.04
AirFlex 540	55.17	36.00	65.25	31.32
PrintRite 591	43.50	36.00	82.76	39.72
Varisoft 475	10.00	7.40	74.00	35.52
Dyeset NOZ	12.20	3.00	24.59	11.80
Q2-5211	100.00	0.20	0.20	0.10
Water			551.23	264.59
	12	100	833.33	400

Coating, referred to in the examples that follow as Type G, used for cotton

45 **[0054]**

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP709IRV	49.30	17.50	35.50	17.04
AirFlex 540	55.17	36.00	65.25	31.32
PrintRite 591	43.50	36.00	82.76	39.72
Varisoft 475	10.00	7.40	74.00	35.52
Dyeset NFS	36.70	3.00	8.17	3.92
Q2-521	100.00	0.20	0.20	0.10
Water			567.65	272.47

EP 1 914 343 B1

(continued)

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
	12	100	833.33	400

Coating, referred to in the following examples as Type H for cotton fabrics.

[0055]

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP709IRV	49.30	17.50	35.50	17.04
AirFlex 540	55.17	36.00	65.25	31.32
PrintRite 591	43.50	36.00	82.76	39.72
Varisoft475	10.00	7.40	74.00	35.52
Dyeset Conc.	47.60	3.00	6.30	3.03
Q2-5211	100.00	0.20	0.20	0.10
Water			569.52	273.37
	12	100	833.33	400

Coating, referred to in the following examples as Type I for cotton fabrics

[0056]

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP7091 RV	49.30	15.50	31.44	15.09
AirFlex 540	55.17	34.00	61.63	29.58
PrintRite 591	43.50	34.00	78.16	37.52
Varisoft 475	10.00	5.40	54.00	25.92
Dyeset Conc	47.60	3.00	6.30	3.03
Sodium Bicarb	63.40	3.00	4.73	2.27
Urea	95.00	5.00	5.26	2.53
Q2-5211	100.00	0.20	0.20	0.10
Water			591.81	284.07
	12	100	833.33	400

Coating, referred to in the examples that follow as Type J for cotton fabrics.

[0057]

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP7091 RV	49.30	15.50	31.44	15.09
AirFlex 540	55.17	34.00	61.63	29.58
PrintRite 591	43.50	34.00	78.16	37.52
Varisoft 475	10.00	5.40	54.00	25.92
Dyeset NOZ	12.20	3.00	24.59	11.80

EP 1 914 343 B1

(continued)

5

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
Sodium Bicarb	63.40	3.00	4.73	2.27
Urea	95.00	5.00	5.26	2.53
Q2-5211	100.00	0.20	0.20	0.10
Water			573.52	275.29
	12	100	833.33	400

10

Coating referred to in the following examples as Type K for cotton fabrics.

15

[0058]

20

ORDER OF ADDITION INGREDIENTS	% TOTAL SOLIDS	DRY PARTS	WET PARTS	BATCH SIZE
CP7091RV	49.30	15.50	31.44	15.09
AirFlex 540	55.17	34.00	61.63	29.58
PrintRite 591	43.50	34.00	78.16	37.52
Varisoft 475	10.00	5.40	54.00	25.92
Dyeset NFS	36.70	3.00	8.17	3.92
Sodium Bicarb	63.40	3.00	4.73	2.27
Urea	95.00	5.00	5.26	2.53
Q2-5211	100.00	0.20	0.20	0.10
Water			589.94	283.17
	12	100	833.33	400

25

30

[0059] It should be noted that the above coatings can be used on a variety of textiles including silk and nylon.

35

Reactive Dye Examples

Example 1

40

[0060] In this and the following examples, 11 by 15 inch (27.9 by 38.1 cm) fabric samples were evaluated. In example 1, the samples were first coated and then imbibed. In particular, the fabric was first coated through a dip and nip procedure/padding as has been previously described, using coating A and then dried in a forced air oven at 100°C for 30 seconds. Following this step the fabric sample was imbibed in a dip and nip/padding method using imbibing solution C and dried again in the oven at 100°C for 30 seconds. For each example (except where otherwise noted) four fabric sample sheets were tested. In order to achieve good hand attributes, the goal for percent dry pickup was between 7 and 9. The percent dry pickup was calculated in accordance with the following series of equations. These equations are described in Wellington Sears Handbook of Industrial Textiles, by Sabit Adanur, PH.D. copyright 1995, p.179.

45

50

$$\text{Wet pickup (\%)} = \frac{\text{Weight of formulation picked up}}{\text{Weight of dry fabric}} \times 100$$

55

$$\text{Add-on (\%)} = \text{Concentration of Formulation (\%)} \times \text{Wet Pickup (\%)}$$

[0061] From this the following equation was utilized to arrive at the values in the charts for % dry-pickup.

EP 1 914 343 B1

$$\% \text{ Dry Pickup} = ((\text{Wet/Basis Weight}) \times 100) - 100 \times \% \text{ Solids (TS)}$$

Results of Example 1

[0062]

OBJECTIVE: TO IMBIBE COTTON POPLIN FABRIC USING TYPE A COATING AND SEPARATE IMBIBING SOLUTION. T.S. OF 11.6 IN PERCENT			
#	BW Dry in grms/m ²	Wet weight in grams	% Pickup Dry
1	14.1	24.29	8.4
2	14.1	24.21	8.4
3	14.3	24.74	8.5
4	14.3	25.28	9.0
*T.S. represents total solids (percent), BW represents basis weight.			

Example 2

[0063] In this example fabric samples were imbibed first using imbibing solution Type C and then coated with Coating Type B using the procedures described in previous Example 1.

OBJECTIVE: TO IMBIBE COTTON POPLIN USING TYPE B WITH T.S. 11.6/T.S. 10.6						
Imbibing Step T.S. 11.6				Coating Step T.S. 10.6		
SAMPLE #	BW in grms/m ²	Wet weight in grms	% Dry Pickup	BW in grms/m ² .	Wet weight in grms	% Dry Pickup
1	10.85	22.71	12.6	12.42	22.20	8.4
2	10.87	22.88	12.7	12.38	21.35	7.7
3	10.8	22.16	12.2	12.34	22.22	8.5
4	10.9	22.46	12.3	11.74	20.94	8.3

Example 3 (Comparative)

[0064] In this example fabric samples were imbibed only with solution Type C.

OBJECTIVE: TO IMBIBE COTTON POPLIN WITH SOLUTION TYPE C WITH T.S. OF 12			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.83	21.92	11.8
2	10.58	21.63	12.1
3	9.69	19.75	12.1
4	9.7	20.6	12.9

Example 4 (Comparative)

[0065] In this example fabric samples were coated only with Type D coating.

EP 1 914 343 B1

OBJECTIVE: TO COAT FABRIC SAMPLES ONLY WITH TYPE D/ T.S. 10.6.			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	9.73	18.46	9.5
2	9.84	18.54	9.3
3	10.73	20.79	9.9
4	10.76	20.93	10.1

Example 5

[0066] In this example fabric samples were coated with the Combo Type E solution.

OBJECTIVE: TO TREAT FABRICS WITH THE COMBO SOLUTION/T.S. 11.4, TYPE E			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.97	21.14	10.6
2	10.74	20.47	10.3
3	10.75	20.62	10.5

Example 6

[0067] In this example fabric samples were coated with Type F coating.

OBJECTIVE: TYPE F COATING; DYESET NOZ T.S. 11.1			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.84	21.7	11.1
2	11.02	21.29	10.3
3	10.87	21.26	10.7

Example 7

[0068] In this example fabric samples were treated with Type G coating

OBJECTIVE: TYPE G /DYESET NFS AND T.S. 11.68			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.84	21.1	11.1
2	10.85	20.7	10.6
3	10.77	20.7	10.8

Example 8

[0069] In this example fabric samples were treated with Type H coating.

OBJECTIVE: TYPE H /DYESET CONC T.S. 11.2			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.86	21.1	10.5
2	10.86	21.3	10.6

EP 1 914 343 B1

(continued)

OBJECTIVE: TYPE H /DYESET CONC T.S. 11.2			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
3	10.86	20.6	10.4

Example 9

[0070] In this example fabric samples were treated with Type I coating.

OBJECTIVE: TYPE I /CONC T.S. 11.4			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.6	20.9	11.1
2	10.9	21.4	10.9
3	10.8	21.2	10.9

Example 10

[0071] In this example fabric samples were treated with Type J coating.

TYPE J / NOZ/T.S. 11			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	10.98	21.4	10.5
2	10.78	21.2	10.6
3	10.72	20.73	10.2

Example 11

[0072] In this example fabric samples were treated with Type K coating.

OBJECTIVE: TYPE K /NFS			
Sample #	BW in grms/m ²	Wet weight in grms	% Dry Pickup
1	12.2	24.1	11.7
2	12.2	23.8	11.4
3	10.7	20.8	11.3

Reactive Dye Example Results

[0073] Each of the samples were exposed on half of their area to D65/10° illuminant (standard day light) to determine whether any yellowing occurs. A sample of each was also printed using the TX-1500 printer of Encad and a reactive ink set available from Kimberly-Clark Printing Technology, Inc. of Escondido, California under the designations 17960-17970. Prior to printing, the fabric sample was first laminated to a backing as has been previously described in the first example set. Examples of reactive dyes used included reactive blue 49 and black 5 available from companies such as DyStar and BASF corporation. The reactive dye sets utilize vinyl sulfones and monochlorotriazines.

[0074] Since reactive dyes are typically not ink-jetted because of the level of particulates and other salt components in the dyes, a reactive dye set was developed for testing with the coatings. It is surmised that other reactive dye sets could also be used in conjunction with the coatings, such as those dyes available from Ciba. The dyed samples were dried overnight in the dark.

[0075] Type A was demonstrated to work well only after it had been steamed. Exposing Type A to a water wash was

acceptable before steaming but detergent wash demonstrated considerable washout. Type B was demonstrated to work well without steaming but had some redepositing problems onto the fabric. Type C was demonstrated as having the most washout of all samples tested without steaming and having a visually impaired appearance. After steaming the results for Type C were very much improved. Type D demonstrated positive results across all samples but failed the water spot test and printed samples. Only after washing and/or after steam and washing did Type D sample pass water spot testing. Type E demonstrated very acceptable results with water spotting occurring on printed sample only. Type E demonstrated poor results in detergent washing with no post processing steps. Type F demonstrated positive visual appearances as did Type H samples. Type G samples failed most testing. Types I, J and K each demonstrated relatively the same positive results, although type K was shown to be a better performer in terms of appearance and washability.

[0076] For the purposes of this application the water spot test comprised AATTC Test Method 104-1994. Essentially in this test, a drop of water is placed on a substrate and then rubbed down using a glass rod. The substrate is then observed to see if a water spot remains after the water dries. If a white circle appears then a water spot is considered to have been left.

[0077] Other reactive dye ink sets may be used with these coatings including those available from Kimberly-Clark Printing Technology, Inc. under the designations, TXCR-500 Black, TXCR-520 Red, TXCR-523 Medium Red, TXCR-526 Scarlet, TXCR-530 Orange, TXCR-540 Yellow, TXCR-545 Golden Yellow, TXCR-550 Green, TXCR-560 Turquoise, TXCR-565 Medium Turquoise, TXCR-570 Blue, and TXCR-580 Gray. These reactive dye ink sets were tested with the above coatings by printing them through a Colorspan DM XII 12-color printer/ 600 dpi.

[0078] Alternatively, instead of using reactive dye sets, acid dye ink sets may be used with acid dye fixation solutions (Imbibing solutions). Textile substrates which can use the acid dye sets include ones such as those with fibers that are dyeable with acid dyes, blended yarns, as long as the ratio is at least 15% between nylon and other material such as Lycra, and polyamides. Such acid dye sets are available from Kimberly-Clark Printing Technology, Inc. under the designation 17972-17975. Additional acid dye sets are available from Kimberly-Clark Printing Technology, Inc. under the designations 7287-20-2 Black, 7287-27-2 Gray, 6869-184-5 Violet, 7287-21-1 Blue, 7287-24-2 Lt. Blue, 7287-10-1 Turquoise, and 7287-25-1 Green, 6869-186-3B Magenta, 7287-24-1 Lt. Magenta, 6869-184-10 Scarlet, 7287-15-1 Orange, 7287-6-1 Yellow. Such inks were tested with the above described coatings using the Colorspan DM XII printer previously described.

[0079] By using such dye sets, an inkjet solution to a conventional screen printing process using acid dyes and a treated substrate is provided. Providing a digital alternative to this market will greatly reduce the cost for the manufacturing of textiles and will allow for more custom-made products to be produced.

Pigment Ink Examples

[0080] It should also be recognized that Pigmented Ink Formulations may also be used in conjunction with the coating and imbibing solution formulations. It is particularly desirable to use Pigmented Ink formulations available from Kimberly-Clark Printing Technology, Inc. under the designations 17976-17979. Examples of the pigment dispersions include Acryjet Cyan, magenta, yellow and black available from the Rhom and Haas Corporation.

[0081] The coating/ treatment formulations and methods which are the subject of this invention, provide ink jet printable textile substrates which possess characteristics of print and image quality, a noticeable color enhancement, color quality and density, ink retention capacity, and waterfastness and detergentfastness properties. Such formulations can be used to prepare articles of manufacture as previously described.

Claims

1. An aqueous coating formulation containing solids, for enhancing image visualization and retention of reactive dye-based inks, comprising:
 - a) urea;
 - b) an ingredient selected from sodium bicarbonate, sodium carbonate or combinations thereof; **characterised in that** it further comprises
 - c) a cationic polymer or copolymer; and
 - d) a cationic or non-ionic fabric softener.
2. The aqueous coating formulation of claim 1 wherein said cationic polymer or copolymer is present in an amount between 5 to 95% of the total solids.
3. The aqueous coating formulation of claim 1 wherein said fabric softener is present in an amount between 5 to 20%

of the total solids.

4. The aqueous coating formulation of claim 1 further comprising a latex binder.

5 5. The aqueous coating formulation of claim 4 wherein said latex binder is present in an amount between 0 to 80% of the total solids.

10 6. The aqueous coating formulation of claim 1 wherein the sodium bicarbonate, sodium carbonate or combination thereof is present in an amount between 3 and 10% of the total solids.

7. The aqueous coating formulation of claim 1 wherein the urea is present in an amount between 5 and 12% of the total solids.

15 8. The aqueous coating formulation of claim 1 further including additives selected from the group including wetting agents, defoamers, and surfactants.

9. The aqueous coating formulation of claim 8 wherein said additives are present in an amount between 0.1 and 1% of the total solids.

20 10. A method of treating a substrate so as to improve the adhesion, color fastness and wash fastness of a reactive dye-based ink jet printed onto the substrate, which will be exposed to a post-treatment step following printing, the method comprising the steps of:

a) providing a substrate; and either

25 b1) treating the substrate with an aqueous coating formulation comprising a cationic polymer or copolymer, a cationic or non-ionic fabric softener, urea, and an ingredient selected from sodium bicarbonate, sodium carbonate or combinations thereof; or

30 b2) treating the substrate with an aqueous coating formulation comprising a cationic polymer or copolymer, and a cationic or non-ionic fabric softener; and then treating the substrate with an aqueous imbibing solution of urea, and an ingredient selected from sodium bicarbonate, sodium carbonate or combinations thereof.

11. The method of claim 10 wherein in step b1) said cationic polymer or copolymer is present in said aqueous coating formulation in an amount between 5 to 95% of the total solids.

35 12. The method of claim 10 wherein in step b1) said fabric softener is present in said aqueous coating formulation in an amount between 5 to 20% of the total solids.

13. The method of claim 10 wherein in step b1) said aqueous coating formulation further includes a latex binder.

40 14. The method of claim 13 wherein said latex binder is present in said aqueous coating formulation in an amount between 0 to 80% of the total solids.

45 15. The method of claim 10 wherein in step b1) said urea is present in said aqueous coating formulation in an amount between 5 to 12% of the total solids.

16. The method of claim 10 wherein in step b1) said sodium bicarbonate, sodium carbonate or combinations thereof is present in said aqueous coating formulation in an amount between 3 to 10% of the total solids.

50 17. The method of claim 10 further comprising the steps of:

c) drying the substrate;

d) printing on the substrate with a reactive dye-based ink; and

e) post-treating the printed substrate of step d).

55 18. A substrate produced in accordance with the method of claim 10 or claim 17.

Patentansprüche

- 5
1. Wässrige Beschichtungsformulierung, welche Feststoffe enthält, zum Verstärken von Bildvisualisierungen und zum Zurückhalten von Reaktivfarbstoff-basierten Farben, welche umfasst:
- a) Harnstoff
 b) einen Inhaltsstoff, welcher ausgewählt ist aus Natriumbikarbonat, Natriumkarbonat oder Kombinationen davon;
dadurch gekennzeichnet, dass sie des Weiteren umfasst
 10 c) ein kationisches Polymer oder Copolymer; und
 d) einen kationischen oder nicht-ionischen Stoff-Weichmacher.
2. Wässrige Beschichtungsformulierung gemäß Anspruch 1, wobei das kationische Polymer oder Copolymer in einer Menge von zwischen 5 bis 95% des Gesamtfeststoffgehalts vorhanden ist.
- 15
3. Wässrige Beschichtungsformulierung gemäß Anspruch 1, wobei der Stoff-Weichmacher in einer Menge von zwischen 5 bis 20% des Gesamtfeststoffgehalts vorhanden ist.
- 20
4. Wässrige Beschichtungsformulierung gemäß Anspruch 1, welche des Weiteren ein Latex-Bindemittel umfasst.
5. Wässrige Beschichtungsformulierung gemäß Anspruch 4, wobei das Latex-Bindemittel in einer Menge von zwischen 0 bis 80% des Gesamtfeststoffgehalts vorhanden ist.
- 25
6. Wässrige Beschichtungsformulierung gemäß Anspruch 1, wobei das Natriumbikarbonat, Natriumkarbonat oder eine Kombination davon in einer Menge von zwischen 3 und 10% des Gesamtfeststoffgehalts vorhanden ist.
7. Wässrige Beschichtungsformulierung gemäß Anspruch 1, wobei der Harnstoff in einer Menge von zwischen 5 und 12% des Gesamtfeststoffgehalts vorhanden ist.
- 30
8. Wässrige Beschichtungsformulierung gemäß Anspruch 1, welche des Weiteren Zusatzstoffe beinhaltet, welche ausgewählt sind aus der Gruppe beinhaltend Feuchtmacher, Entschäumer und Tenside.
- 35
9. Wässrige Beschichtungsformulierung gemäß Anspruch 8, wobei die Zusatzstoffe in einer Menge von zwischen 0,1 und 1% des Gesamtfeststoffgehalts vorhanden sind.
- 40
10. Verfahren zum Behandeln eines Substrats, um die Adhäsion, Farbfestigkeit und Waschbeständigkeit einer Reaktivfarbstoff-basierten Farbe zu verbessern, die mittels eines Druckers auf das Substrat gedruckt ist, und die einem Nachbehandlungsschritt nachfolgend dem Drucken ausgesetzt wird, wobei das Verfahren die Schritte umfasst:
- a) Bereitstellen eines Substrats; und entweder
 b1) Behandeln des Substrats mit einer wässrigen Beschichtungsformulierung, welche ein kationisches Polymer oder Copolymer, einen kationischen oder nicht-ionischen Stoffweichmacher, Harnstoff und einen Inhaltsstoff umfasst, welcher ausgewählt ist aus Natriumbikarbonat, Natriumkarbonat oder Kombinationen davon; oder
 b2) Behandeln des Substrats mit einer wässrigen Beschichtungsformulierung, welche ein kationisches Polymer oder Copolymer, und einen kationischen oder nicht-ionischen Stoffweichmacher umfasst; und dann Behandeln des Substrats mit einer wässrigen Aufsauglösung aus Harnstoff und einem Inhaltsstoff, welcher ausgewählt ist aus Natriumbikarbonat, Natriumkarbonat oder Kombinationen davon.
- 45
11. Verfahren gemäß Anspruch 10, wobei in Schritt b1) das kationische Polymer oder Copolymer in der wässrigen Beschichtungsformulierung in einer Menge von zwischen 5 und 95% des Gesamtfeststoffgehalts vorhanden ist.
- 50
12. Verfahren gemäß Anspruch 10, wobei in Schritt b1) der Stoffweichmacher in der wässrigen Beschichtungsformulierung in einer Menge von zwischen 5 und 20% des Gesamtfeststoffgehalts vorhanden ist.
- 55
13. Verfahren gemäß Anspruch 10, wobei in Schritt b1) die wässrige Beschichtungsformulierung des Weiteren ein Latex-Bindemittel umfasst.
14. Verfahren gemäß Anspruch 13, wobei das Latex-Bindemittel in der wässrigen Beschichtungsformulierung in einer

EP 1 914 343 B1

Menge von zwischen 0 und 80% des Gesamtfeststoffgehalts vorhanden ist.

5 15. Verfahren gemäß Anspruch 10, wobei in Schritt b1) der Harnstoff in der wässrigen Beschichtungsformulierung in einer Menge von zwischen 5 und 12% des Gesamtfeststoffgehalts vorhanden ist.

16. Verfahren gemäß Anspruch 10, wobei in Schritt b1) das Natriumbikarbonat, Natriumkarbonat oder die Kombinationen davon in der wässrigen Beschichtungsformulierung in einer Menge von zwischen 3 und 10% des Gesamtfeststoffgehalts vorhanden sind.

10 17. Verfahren gemäß Anspruch 10, welches des Weiteren die Schritte umfasst:

c) Trocknen des Substrats;

d) Drucken auf das Substrat mit einer Reaktivfarbstoff-basierten Farbe; und

e) Nachbehandeln des bedruckten Substrats des Schritts d).

15 18. Substrat, welches in Übereinstimmung mit dem Verfahren nach Anspruch 10 oder Anspruch 17 hergestellt wurde.

20 Revendications

1. Formulation de revêtement laqueux contenant des solides, pour améliorer la visualisation d'image et la rétention d'encres à base de colorants réactifs, comprenant :

25 a) de l'urée ;

b) un ingrédient choisis parmi du bicarbonate de sodium, du carbonate de sodium ou des combinaisons de ceux-ci ; **caractérisée en ce qu'elle** comprend en outre

c) un polymère ou un copolymère cationique ; et

d) un assouplissant d'étoffe cationique ou non ionique.

30 2. Formulation de revêtement aqueux selon la revendication 1, dans laquelle ledit copolymère ou polymère cationique est présent en une quantité entre 5 et 95 % du total des solides.

3. Formulation de revêtement aqueux selon la revendication 1, dans laquelle ledit assouplissant d'étoffe est présent en une quantité entre 5 et 20 % du total des solides.

35 4. Formulation de revêtement aqueux selon la revendication 1, comprenant en outre un liant de latex.

5. Formulation de revêtement aqueux selon la revendication 4, dans laquelle ledit liant de latex est présent en une quantité entre 0 et 80 % du total des solides.

40 6. Formulation de revêtement aqueux selon la revendication 1, dans laquelle le bicarbonate de sodium, le carbonate de sodium ou une combinaison de ceux-ci est présent en une quantité entre 3 et 10 % du total des solides.

45 7. Formulation de revêtement aqueux selon la revendication 1, dans laquelle l'urée est présente en une quantité entre 5 et 12 % du total des solides.

8. Formulation de revêtement aqueux selon la revendication 1, incluant en outre des additifs choisis parmi le groupe incluant des agents de mouillage, des agents antimousse et des tensioactifs.

50 9. Formulation de revêtement aqueux selon la revendication 8, dans laquelle lesdits additifs sont présents en une quantité entre 0,1 et 1 % du total des solides.

55 10. Procédé de traitement d'un substrat de manière à améliorer l'adhérence, la solidité de la couleur et la résistance au lavage d'un jet d'encre à base de colorants réactifs imprimé sur le substrat, qui sera exposé à une étape de post-traitement après l'impression, le procédé comprenant les étapes de :

a) fournir un substrat et soit

b1) traiter le substrat avec une formulation de revêtement aqueux comprenant un copolymère ou un polymère

EP 1 914 343 B1

cationique, un assouplissant d'étoffe cationique ou non ionique, de l'urée, et un ingrédient choisi parmi du bicarbonate de sodium, du carbonate de sodium ou des combinaisons de ceux-ci ; soit

b2) traiter le substrat avec une formulation de revêtement aqueux comprenant un copolymère ou un polymère cationique, et un assouplissant d'étoffe cationique ou non ionique ; et ensuite traiter le substrat avec une solution d'imprégnation aqueuse d'urée, et un ingrédient choisi parmi du bicarbonate de sodium, du carbonate de sodium ou des combinaisons de ceux-ci.

5
10
11. Procédé selon la revendication 10, dans lequel à l'étape b1), ledit copolymère ou polymère cationique est présent dans ladite formulation de revêtement aqueux en une quantité entre 5 et 95 % du total des solides.

12. Procédé selon la revendication 10, dans lequel à l'étape b1), ledit assouplissant d'étoffe est présent dans ladite formulation de revêtement aqueux en une quantité entre 5 et 20 % du total des solides.

15
13. Procédé selon la revendication 10, dans lequel à l'étape b1), ladite formulation de revêtement aqueux inclut en outre un liant de latex.

14. Procédé selon la revendication 13, dans lequel ledit liant au latex est présent dans ladite formulation de revêtement aqueux en une quantité entre 0 et 80 % du total des solides.

20
15. Procédé selon la revendication 10, dans lequel à l'étape b1), ladite urée est présente dans ladite formulation de revêtement aqueux en une quantité entre 5 et 12 % du total des solides.

25
16. Procédé selon la revendication 10, dans lequel à l'étape b1), lesdits bicarbonate de sodium, carbonate de sodium ou combinaisons de ceux-ci est présent dans ladite formulation de revêtement aqueux en une quantité entre 3 et 10 % du total des solides.


17. Procédé selon la revendication 10 comprenant en outre les étapes de :

30 c) sécher le substrat ;

d) imprimer sur le substrat avec une encre à base de colorants réactifs ; et

e) post-traiter le substrat imprimé de l'étape d).

18. Substrat produit conformément au procédé de la revendication 10 ou de la revendication 17.




A, B = O, NH, N—

R₁, R₂ = quaternary ammonium, hydrophilic,
hydrophobic, reactive, or self condensing group

R₃ = H, alkyl, or alkoxy group

X = halogen or other counter ion


FIG. 1A




$a = 1$ to 99%, $b = (100-a)\%$, $c = 0$ to $100-(a+b)\%$

R₁, R₂ - as above

FIG. 1B



$a = 1$ to 99%, $b = (100-a)\%$



for CP 7091 RV, $a \sim 90$; $b \sim 10$

FIG. 1C




FIG. 2

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5781216 A, Haruta [0007]
- US 9812712 W, Harris [0008]
- WO 9900541 A [0008]
- EP 0605730 A [0009]
- US 10968198 A [0024]
- US 5897694 A [0024]

Non-patent literature cited in the description

- **SABIT ADANUR**. Wellington Sears Handbook of Industrial Textiles. 1995, 179 [0060]