



US00RE49994E

(19) **United States**
(12) **Reissued Patent**
Lee et al.

(10) **Patent Number:** **US RE49,994 E**
(45) **Date of Reissued Patent:** ***Jun. 4, 2024**

(54) **SPINAL FUSION IMPLANTS AND DEVICES AND METHODS FOR DEPLOYING SUCH IMPLANTS**

(58) **Field of Classification Search**
CPC A61F 2/442; A61F 2/446; A61F 2/4455;
A61F 2/4601; A61F 2/4611; A61B
17/8852
See application file for complete search history.

(71) Applicant: **Spinal Elements, Inc.**, Carlsbad, CA (US)

(56) **References Cited**

(72) Inventors: **James Lee**, Los Gatos, CA (US); **Jeffrey L. Emery**, Emerald Hills, CA (US); **Timothy McGrath**, Fond du Lac, WI (US); **Laurent Schaller**, Genoa, NV (US); **Andrew Huffmaster**, Fremont, CA (US); **Ebrahim Mohammad Quddus**, Fremont, CA (US)

U.S. PATENT DOCUMENTS

2,002,021 A 5/1935 Rouse
3,807,390 A 4/1974 Ostrowski et al.
(Continued)

(73) Assignee: **Spinal Elements, Inc.**, Carlsbad, CA (US)

FOREIGN PATENT DOCUMENTS

DE 42 22 121 9/1993
DE 197 10 392 7/1999
(Continued)

(*) Notice: This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Official Communication in European Application No. 08730402.8, dated Feb. 18, 2013.

(21) Appl. No.: **17/206,771**

(Continued)

(22) Filed: **Mar. 19, 2021**

Primary Examiner — Matthew J Kasztejna

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **10,231,843**
Issued: **Mar. 19, 2019**
Appl. No.: **15/276,147**
Filed: **Sep. 26, 2016**

(57) **ABSTRACT**

Methods and apparatus are disclosed for distracting tissue. The devices and methods may include insertion of first and second elongated members into the space between two tissue layers, with an augmenting elongated member inserted therebetween to form a distraction device between the tissues to be distracted. The distraction device defines a generally annular configuration, with a locking member secured to one of the elongated members at a plurality of locations to maintain the distraction device in the generally annular configuration. The augmenting elongated member may be shorter than the first and second elongated members such that a window is defined between the proximal and distal ends of the augmenting elongated member when the distraction device and the first and second elongated mem-


U.S. Applications:

(63) Continuation of application No. 13/803,322, filed on Mar. 14, 2013, now Pat. No. 9,480,574.

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61B 17/88 (2006.01)
(Continued)

(Continued)

(52) **U.S. Cl.**
CPC **A61F 2/446** (2013.01); **A61B 17/8852** (2013.01); **A61F 2/442** (2013.01);
(Continued)



bers are in the generally annular configuration. Bone graft material or bone filler may be introduced into the interior of the distraction device through the window.

35 Claims, 14 Drawing Sheets

(51) **Int. Cl.**

A61F 2/46 (2006.01)

A61F 2/30 (2006.01)

(52) **U.S. Cl.**

CPC *A61F 2/4455* (2013.01); *A61F 2/4601* (2013.01); *A61F 2/4611* (2013.01); *A61F 2002/3008* (2013.01); *A61F 2002/30092* (2013.01); *A61F 2002/30242* (2013.01); *A61F 2002/30383* (2013.01); *A61F 2002/30462* (2013.01); *A61F 2002/30507* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,846,175	A	7/1989	Frimberger
4,862,891	A	9/1989	Smith
4,863,476	A	9/1989	Shepperd
4,898,161	A	2/1990	Grundei
5,059,193	A	10/1991	Kuslich
5,129,889	A	7/1992	Hahn et al.
5,192,327	A	3/1993	Brantigan
5,201,742	A	4/1993	Hasson
5,219,358	A	6/1993	Bendel et al.
5,267,994	A	12/1993	Gentelia et al.
5,306,310	A	4/1994	Siebels
5,342,394	A	8/1994	Matsuno et al.
5,345,945	A	9/1994	Hodgson et al.
5,366,490	A	11/1994	Edwards et al.
5,374,267	A	12/1994	Siegal
5,383,884	A	1/1995	Summers
5,397,304	A	3/1995	Truckai
5,397,364	A	3/1995	Kozak et al.
5,423,806	A	6/1995	Dale et al.
5,433,739	A	7/1995	Sluijter et al.
5,445,639	A	8/1995	Kuslich et al.
5,470,043	A	11/1995	Marts et al.
5,487,757	A	1/1996	Truckai et al.
5,500,012	A	3/1996	Brucker et al.
5,540,696	A	7/1996	Booth, Jr. et al.
5,549,679	A	8/1996	Kuslich
5,554,163	A	9/1996	Shturman
5,571,147	A	11/1996	Sluijter et al.
5,571,189	A	11/1996	Kuslich
5,599,346	A	2/1997	Edwards et al.
5,697,909	A	12/1997	Eggers et al.
5,716,416	A	2/1998	Lin
5,718,707	A	2/1998	Mikhail
5,755,661	A	5/1998	Schwartzman
5,755,732	A	5/1998	Green et al.
5,755,797	A	5/1998	Baumgartner
5,782,832	A	7/1998	Larsen et al.
5,788,713	A	8/1998	Dubach et al.
5,851,214	A	12/1998	Larsen et al.
5,865,809	A	2/1999	Moening et al.
5,871,501	A	2/1999	Leschinsky et al.
5,885,217	A	3/1999	Gisselberg et al.
5,916,166	A	6/1999	Reiss et al.
5,919,235	A	7/1999	Husson et al.
5,980,471	A	11/1999	Jafari
5,980,504	A	11/1999	Sharkey et al.
6,007,570	A	12/1999	Sharkey et al.
6,019,765	A	2/2000	Thornhill et al.
6,039,761	A	3/2000	Li et al.
6,059,829	A	5/2000	Schlöpfer et al.
6,099,514	A	8/2000	Sharkey et al.
6,126,660	A	10/2000	Dietz
6,126,682	A	10/2000	Sharkey et al.
6,183,517	B1	2/2001	Suddaby
6,224,630	B1	5/2001	Bao et al.
6,228,022	B1	5/2001	Friesem et al.
6,231,609	B1	5/2001	Mehdizadeh
6,245,072	B1	6/2001	Zdeblick
6,245,107	B1	6/2001	Ferree
6,277,112	B1	8/2001	Underwood et al.
6,332,895	B1	12/2001	Suddaby
6,375,635	B1	4/2002	Moutafis et al.
6,375,682	B1	4/2002	Fleischmann et al.
6,387,130	B1	5/2002	Stone et al.
6,409,766	B1	6/2002	Brett
6,419,704	B1	7/2002	Ferree
6,436,142	B1	8/2002	Paes et al.
6,454,806	B1	9/2002	Cohen et al.
6,468,270	B1	10/2002	Hovda et al.
6,488,710	B2	12/2002	Besselink
6,491,690	B1	12/2002	Goble et al.
6,500,205	B1	12/2002	Michelson
6,530,926	B1	3/2003	Davison
6,551,319	B2	4/2003	Lieberman
6,554,833	B2	4/2003	Levy et al.
6,558,383	B2	5/2003	Cunningham et al.
6,558,386	B1	5/2003	Cragg
6,558,390	B2	5/2003	Cragg
6,562,033	B2	5/2003	Shah et al.
6,582,431	B1	6/2003	Ray
6,592,625	B2	7/2003	Cauthen
6,595,998	B2	7/2003	Johnson et al.
6,602,248	B1	8/2003	Sharps et al.
6,607,505	B1	8/2003	Thompson et al.
6,607,530	B1	8/2003	Carl et al.
6,620,196	B1	9/2003	Trieu
6,656,178	B1	12/2003	Veldhuizen et al.
6,670,505	B1	12/2003	Collins et al.
6,676,665	B2	1/2004	Foley et al.
6,714,822	B2	3/2004	King et al.
6,726,684	B1	4/2004	Woloszko et al.
6,733,496	B2	5/2004	Sharkey et al.
6,749,605	B2	6/2004	Ashley et al.
6,764,491	B2	7/2004	Frey et al.
6,767,347	B2	7/2004	Sharkey et al.
6,773,432	B1	8/2004	Clayman et al.
6,821,276	B2	11/2004	Lambrecht et al.
6,830,570	B1	12/2004	Frey et al.
6,878,155	B2	4/2005	Sharkey et al.
6,923,811	B1	8/2005	Carl et al.
6,939,351	B2	9/2005	Eckman
6,953,458	B2	10/2005	Loeb
6,964,667	B2	11/2005	Shaolian et al.
6,976,949	B2	12/2005	Winkler et al.
7,004,970	B2	2/2006	Cauthen, III et al.
7,008,432	B2	3/2006	Schlöpfer et al.
7,025,765	B2	4/2006	Balbierz et al.
7,052,516	B2	5/2006	Cauthen, III et al.
7,056,321	B2	6/2006	Pagliuca et al.
7,069,087	B2	6/2006	Sharkey et al.
7,087,055	B2	8/2006	Lim et al.
7,087,058	B2	8/2006	Cragg
7,114,501	B2	10/2006	Johnson et al.
7,124,761	B2	10/2006	Lambrecht et al.
7,144,397	B2	12/2006	Lambrecht et al.
7,179,225	B2	2/2007	Shluzas et al.
7,204,853	B2	4/2007	Gordon et al.
7,211,055	B2	5/2007	Diederich et al.
7,241,297	B2	7/2007	Shaolian et al.
7,252,686	B2	8/2007	Carrison et al.
7,267,687	B2	9/2007	McGuckin, Jr.
7,282,020	B2	10/2007	Kaplan
7,309,336	B2	12/2007	Ashley et al.
7,318,823	B2	1/2008	Sharps et al.
7,318,826	B2	1/2008	Teitelbaum et al.
7,322,962	B2	1/2008	Forrest
7,331,956	B2	2/2008	Hovda et al.
7,331,963	B2	2/2008	Bryan et al.
RE40,156	E	3/2008	Sharps et al.
7,618,458	B2	11/2009	Biedermann et al.
7,682,378	B2	3/2010	Truckai et al.

(56)		References Cited					
U.S. PATENT DOCUMENTS				2003/0083747	A1	5/2003	Winterbottom et al.
7,753,912	B2	7/2010	Raymond et al.	2003/0158545	A1	8/2003	Hovda et al.
7,758,647	B2	7/2010	Arnin et al.	2003/0158553	A1	8/2003	Michelson
7,771,432	B2	8/2010	Schwab et al.	2003/0187453	A1	10/2003	Schlapfer et al.
7,776,051	B2	8/2010	Colleran et al.	2003/0204189	A1	10/2003	Cragg
7,824,445	B2	11/2010	Biro et al.	2003/0220650	A1	11/2003	Major et al.
7,887,568	B2	2/2011	Ahlgren	2004/0002762	A1	1/2004	Hawkins
7,901,460	B2	3/2011	Sherman	2004/0010315	A1	1/2004	Song
7,922,767	B2	4/2011	Sack et al.	2004/0015218	A1	1/2004	Finch et al.
7,947,078	B2	5/2011	Siegal	2004/0024463	A1	2/2004	Thomas, Jr. et al.
7,963,915	B2	6/2011	Bleich	2004/0049180	A1	3/2004	Sharps et al.
8,021,429	B2	9/2011	Viker	2004/0059333	A1	3/2004	Carl et al.
8,025,697	B2	9/2011	McClellan, III et al.	2004/0064144	A1	4/2004	Johnson et al.
8,083,796	B1	12/2011	Raiszadeh et al.	2004/0073216	A1	4/2004	Lieberman
8,123,750	B2	2/2012	Norton et al.	2004/0087994	A1	5/2004	Suddaby
8,128,662	B2	3/2012	Altarac et al.	2004/0092988	A1	5/2004	Shaolian et al.
8,137,401	B2	3/2012	Stad et al.	2004/0102774	A1	5/2004	Trieu
8,142,507	B2*	3/2012	McGuckin, Jr. A61F 2/441 606/90	2004/0106940	A1	6/2004	Shaolian et al.
8,246,622	B2	8/2012	Siegal et al.	2004/0116922	A1	6/2004	Hovda et al.
8,252,001	B2	8/2012	Quimo et al.	2004/0127893	A1	7/2004	Hovda
8,252,054	B2	8/2012	Greenhalgh et al.	2004/0133280	A1	7/2004	Trieu
8,377,070	B2	2/2013	Gauthier	2004/0148028	A1	7/2004	Ferree et al.
8,394,102	B2	3/2013	Garabedian et al.	2004/0153064	A1	8/2004	Foley et al.
8,454,617	B2	6/2013	Schaller et al.	2004/0167625	A1	8/2004	Beyar et al.
8,454,622	B2	6/2013	Blain et al.	2004/0193158	A1	9/2004	Lim et al.
8,470,043	B2	6/2013	Schaller et al.	2004/0230198	A1	11/2004	Manzi et al.
8,579,980	B2	11/2013	DeLurio et al.	2004/0230309	A1	11/2004	DiMauro et al.
8,591,583	B2	11/2013	Schaller et al.	2004/0249464	A1	12/2004	Bindseil et al.
8,628,577	B1	1/2014	Jimenez	2004/0260305	A1	12/2004	Gorensek et al.
8,632,591	B2	1/2014	Vila et al.	2005/0021030	A1	1/2005	Pagliuca et al.
8,663,332	B1	3/2014	To et al.	2005/0021041	A1	1/2005	Michelson
8,685,031	B2	4/2014	Kleiner et al.	2005/0033292	A1	2/2005	Teitelbaum et al.
8,764,806	B2	7/2014	Abdou	2005/0038517	A1	2/2005	Carrison et al.
8,906,028	B2	12/2014	Kleiner	2005/0049623	A1	3/2005	Moore et al.
8,968,408	B2	3/2015	Schaller et al.	2005/0065610	A1	3/2005	Pisharodi
8,974,464	B2	3/2015	Johnson et al.	2005/0070911	A1	3/2005	Carrison et al.
8,979,860	B2	3/2015	Voellmicke et al.	2005/0080425	A1	4/2005	Bhatnagar et al.
8,986,385	B2	3/2015	Hall	2005/0090833	A1	4/2005	DiPoto
9,034,041	B2	5/2015	Wolters et al.	2005/0090899	A1	4/2005	DiPoto
9,039,771	B2	5/2015	Glerum et al.	2005/0107878	A1	5/2005	Conchy
9,161,773	B2	10/2015	Schaller et al.	2005/0113832	A1	5/2005	Molz, IV et al.
9,308,022	B2	4/2016	Chitre et al.	2005/0119750	A1	6/2005	Studer
9,351,851	B2	5/2016	Huffmaster et al.	2005/0131540	A1	6/2005	Trieu
9,480,574	B2	11/2016	Lee et al.	2005/0131541	A1	6/2005	Trieu
9,566,170	B2	2/2017	Schell et al.	2005/0137601	A1	6/2005	Assell et al.
9,642,712	B2	5/2017	Schaller et al.	2005/0137605	A1	6/2005	Assell et al.
9,827,031	B2	11/2017	Emery et al.	2005/0149049	A1	7/2005	Assell et al.
9,955,961	B2	5/2018	Huffmaster et al.	2005/0165420	A1	7/2005	Cha
10,022,243	B2	7/2018	Emery et al.	2005/0182414	A1	8/2005	Manzi et al.
10,231,843	B2	3/2019	Lee et al.	2005/0182416	A1	8/2005	Lim et al.
10,258,228	B2	4/2019	Genovese et al.	2005/0187537	A1	8/2005	Loeb et al.
10,285,821	B2	5/2019	Schaller et al.	2005/0203527	A1	9/2005	Carrison et al.
10,314,605	B2	6/2019	Huffmaster et al.	2005/0222683	A1	10/2005	Berry
10,426,629	B2	10/2019	Schaller et al.	2005/0228391	A1	10/2005	Levy et al.
10,575,963	B2	3/2020	Schaller et al.	2005/0234493	A1	10/2005	Carr et al.
10,709,577	B2	7/2020	Lorang et al.	2005/0240171	A1	10/2005	Forrest
10,758,286	B2	9/2020	Ammerman et al.	2005/0251134	A1	11/2005	Woloszko et al.
11,224,453	B2	1/2022	Huffmaster et al.	2005/0251177	A1	11/2005	Saadat et al.
11,298,043	B2	4/2022	Bankiewicz et al.	2005/0256525	A1	11/2005	Culbert et al.
11,471,145	B2	10/2022	Pacheco-Serrant et al.	2005/0261683	A1	11/2005	Veldhuizen et al.
11,564,811	B2	1/2023	Lorang et al.	2005/0261684	A1	11/2005	Shaolian et al.
11,583,327	B2	2/2023	McHale et al.	2005/0261692	A1	11/2005	Carrison et al.
2001/0023348	A1	9/2001	Ashley et al.	2005/0273173	A1	12/2005	Gordon et al.
2001/0029377	A1	10/2001	Aebi et al.	2005/0278027	A1	12/2005	Hyde, Jr.
2001/0031981	A1	10/2001	Evans et al.	2005/0278036	A1	12/2005	Leonard et al.
2002/0019637	A1	2/2002	Frey et al.	2006/0015131	A1	1/2006	Kierce et al.
2002/0026197	A1	2/2002	Foley et al.	2006/0025797	A1	2/2006	Lock et al.
2002/0128716	A1	9/2002	Cohen et al.	2006/0030933	A1	2/2006	DeLegge et al.
2002/0147444	A1	10/2002	Shah et al.	2006/0036241	A1	2/2006	Siegal
2002/0156530	A1	10/2002	Lambrecht et al.	2006/0041258	A1	2/2006	Galea
2002/0173813	A1	11/2002	Peterson et al.	2006/0041295	A1	2/2006	Osyпка
2003/0009223	A1	1/2003	Fehling et al.	2006/0047178	A1	3/2006	Winkler et al.
2003/0014047	A1	1/2003	Woloszko et al.	2006/0052793	A1	3/2006	Heinz
2003/0040796	A1	2/2003	Ferree	2006/0058826	A1	3/2006	Evans et al.
2003/0065358	A1	4/2003	Frecker et al.	2006/0058876	A1	3/2006	McKinley
				2006/0074425	A1	4/2006	Sutterlin et al.
				2006/0085070	A1	4/2006	Kim
				2006/0089646	A1	4/2006	Bonutti
				2006/0116689	A1	6/2006	Albans

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
2006/0129244	A1	6/2006	Ensign et al.	2008/0009877	A1	1/2008	Sankaran et al.
2006/0136064	A1	6/2006	Sherman	2008/0015639	A1	1/2008	Bjork et al.
2006/0149268	A1	7/2006	Truckai et al.	2008/0021435	A1	1/2008	Miller et al.
2006/0161162	A1	7/2006	Lambrecht et al.	2008/0027407	A1	1/2008	Miller et al.
2006/0178666	A1	8/2006	Cosman et al.	2008/0033465	A1	2/2008	Schmitz et al.
2006/0189999	A1	8/2006	Zwirkoski	2008/0058707	A1	3/2008	Ashley et al.
2006/0195091	A1	8/2006	McGraw et al.	2008/0065080	A1	3/2008	Assell et al.
2006/0195094	A1	8/2006	McGraw et al.	2008/0065092	A1	3/2008	Assell et al.
2006/0206116	A1	9/2006	Yeung	2008/0065093	A1	3/2008	Assell et al.
2006/0217811	A1	9/2006	Lambrecht et al.	2008/0065094	A1	3/2008	Assell et al.
2006/0224154	A1	10/2006	Shadduck et al.	2008/0071356	A1	3/2008	Greenhalgh et al.
2006/0224241	A1	10/2006	Butler et al.	2008/0086157	A1	4/2008	Stad et al.
2006/0229625	A1	10/2006	Truckai et al.	2008/0114367	A1	5/2008	Meyer
2006/0235418	A1	10/2006	Gil et al.	2008/0147113	A1	6/2008	Nobis et al.
2006/0241577	A1	10/2006	Balbierz et al.	2008/0161809	A1	7/2008	Schmitz et al.
2006/0247600	A1	11/2006	Yeung et al.	2008/0177259	A1	7/2008	Wu
2006/0247784	A1	11/2006	Kim	2008/0183204	A1	7/2008	Greenhalgh et al.
2006/0265076	A1	11/2006	Carter et al.	2008/0221687	A1	9/2008	Viker
2006/0265077	A1	11/2006	Zwirkoski	2008/0228135	A1	9/2008	Snoderly
2006/0287726	A1	12/2006	Segal et al.	2008/0234687	A1	9/2008	Schaller et al.
2006/0287727	A1	12/2006	Segal	2008/0249628	A1	10/2008	Altarac et al.
2006/0287729	A1	12/2006	Segal et al.	2008/0287995	A1	11/2008	Gauthier
2006/0287730	A1	12/2006	Segal et al.	2008/0294171	A1	11/2008	Boehm, Jr. et al.
2007/0010848	A1	1/2007	Leung et al.	2008/0300636	A1	12/2008	Carli et al.
2007/0016273	A1	1/2007	Scarborough et al.	2009/0012612	A1	1/2009	White et al.
2007/0027545	A1	2/2007	Carls et al.	2009/0024217	A1	1/2009	Levy et al.
2007/0032791	A1	2/2007	Greenhalgh	2009/0105711	A1	4/2009	Mitchell et al.
2007/0050030	A1	3/2007	Kim	2009/0143716	A1	6/2009	Lowry et al.
2007/0050032	A1	3/2007	Gittings et al.	2009/0157187	A1	6/2009	Richelsoph
2007/0055259	A1	3/2007	Norton et al.	2009/0171390	A1	7/2009	Sankaran
2007/0055262	A1	3/2007	Tomita et al.	2009/0198241	A1	8/2009	Phan
2007/0055275	A1	3/2007	Schaller	2009/0198245	A1	8/2009	Phan
2007/0060935	A1	3/2007	Schwardt et al.	2009/0234454	A1	9/2009	Siegal
2007/0067035	A1	3/2007	Falahee	2010/0030216	A1	2/2010	Arcenio
2007/0093822	A1	4/2007	Dutoit et al.	2010/0114179	A1	5/2010	Moore et al.
2007/0093899	A1	4/2007	Dutoit et al.	2010/0131005	A1	5/2010	Conlon
2007/0118219	A1	5/2007	Hyde, Jr.	2010/0179578	A1	7/2010	Tannoury et al.
2007/0123888	A1	5/2007	Bleich et al.	2010/0185291	A1	7/2010	Jimenez et al.
2007/0123903	A1	5/2007	Raymond et al.	2010/0198263	A1	8/2010	Siegal et al.
2007/0123986	A1	5/2007	Schaller et al.	2010/0228091	A1	9/2010	Widenhouse et al.
2007/0149978	A1	6/2007	Shezifi et al.	2010/0249798	A1	9/2010	Sournac et al.
2007/0149990	A1	6/2007	Palmer et al.	2010/0262147	A1	10/2010	Siegal et al.
2007/0162032	A1	7/2007	Johnson et al.	2010/0262242	A1	10/2010	Chavatte et al.
2007/0162062	A1	7/2007	Norton et al.	2010/0268234	A1	10/2010	Aho et al.
2007/0162127	A1	7/2007	Peterman et al.	2010/0286782	A1	11/2010	Schaller et al.
2007/0162135	A1	7/2007	Segal et al.	2010/0298864	A1	11/2010	Castro
2007/0168041	A1	7/2007	Kadiyala	2011/0015638	A1	1/2011	Pischl et al.
2007/0168043	A1	7/2007	Ferree	2011/0015747	A1	1/2011	McManus et al.
2007/0173939	A1	7/2007	Kim et al.	2011/0112455	A1	5/2011	Rocklin
2007/0175959	A1	8/2007	Shelton, IV et al.	2011/0125266	A1	5/2011	Rodgers et al.
2007/0191837	A1	8/2007	Trieu	2011/0144440	A1	6/2011	Cropper et al.
2007/0198021	A1	8/2007	Wales	2011/0172722	A1	7/2011	Verhulst et al.
2007/0198025	A1	8/2007	Trieu et al.	2011/0208306	A1	8/2011	Farris
2007/0208426	A1	9/2007	Trieu	2011/0230965	A1	9/2011	Schell et al.
2007/0213704	A1	9/2007	Truckai et al.	2011/0245926	A1	10/2011	Kitchen
2007/0213733	A1	9/2007	Bleich et al.	2011/0307063	A1	12/2011	Schaller et al.
2007/0213734	A1	9/2007	Bleich et al.	2012/0022651	A1	1/2012	Akyuz et al.
2007/0213735	A1	9/2007	Saadat et al.	2012/0071977	A1	3/2012	Oglaza et al.
2007/0225703	A1	9/2007	Schmitz et al.	2012/0071980	A1	3/2012	Purcell et al.
2007/0233143	A1	10/2007	Josse et al.	2012/0089231	A1	4/2012	Prestigiacomo
2007/0255286	A1	11/2007	Trieu	2012/0123426	A1	5/2012	Quimo
2007/0255406	A1	11/2007	Trieu	2012/0136442	A1	5/2012	Kleiner
2007/0255703	A1	11/2007	Maruyama et al.	2012/0136448	A1	5/2012	Seifert et al.
2007/0260252	A1	11/2007	Schmitz et al.	2012/0150241	A1	6/2012	Ragab et al.
2007/0260270	A1	11/2007	Assell et al.	2012/0232552	A1	9/2012	Morgenstern Lopez et al.
2007/0260315	A1	11/2007	Foley et al.	2012/0232664	A1	9/2012	Ulrich, Jr. et al.
2007/0265652	A1	11/2007	Assell et al.	2012/0277861	A1	11/2012	Steele et al.
2007/0265691	A1	11/2007	Swanson	2012/0283748	A1	11/2012	Ortiz et al.
2007/0276406	A1	11/2007	Mahoney et al.	2012/0296171	A1	11/2012	Lovell et al.
2007/0299521	A1	12/2007	Glenn et al.	2013/0053863	A1	2/2013	Juravic et al.
2008/0009826	A1	1/2008	Miller et al.	2013/0110239	A1	5/2013	Siegal et al.
2008/0009828	A1	1/2008	Miller et al.	2013/0116791	A1	5/2013	Theofilos
2008/0009847	A1	1/2008	Ricart et al.	2013/0144391	A1	6/2013	Siegal et al.
2008/0009875	A1	1/2008	Sankaran et al.	2013/0158667	A1	6/2013	Tabor et al.
2008/0009876	A1	1/2008	Sankaran et al.	2013/0204374	A1	8/2013	Milella, Jr.
				2013/0238098	A1	9/2013	Schaller et al.
				2013/0282143	A1	10/2013	Perkins et al.
				2013/0304070	A1	11/2013	Nelson et al.
				2014/0058513	A1	2/2014	Gahman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0067073	A1	3/2014	Hauck
2014/0163326	A1	6/2014	Forsell
2014/0163560	A1	6/2014	Fenn et al.
2014/0235949	A1	8/2014	Smith
2014/0236296	A1	8/2014	Wagner et al.
2014/0249629	A1	9/2014	Moskowitz et al.
2014/0257297	A1	9/2014	Koogle, Jr. et al.
2014/0257484	A1	9/2014	Flower et al.
2014/0277481	A1	9/2014	Lee et al.
2014/0316427	A1	10/2014	Yoon et al.
2015/0012000	A1	1/2015	Siegal et al.
2015/0051701	A1	2/2015	Glerum et al.
2015/0100124	A1	4/2015	Whipple
2015/0112437	A1	4/2015	Davis et al.
2015/0112438	A1	4/2015	McLean
2015/0148908	A1	5/2015	Marino et al.
2015/0367487	A1	12/2015	Nino et al.
2016/0007979	A1	1/2016	Bhagat et al.
2016/0206442	A1	7/2016	Dvorak et al.
2016/0287409	A1	10/2016	Ziemek
2016/0367332	A1	12/2016	Shah et al.
2017/0007349	A1	1/2017	Solar et al.
2017/0135704	A1	5/2017	Abbasi
2017/0303938	A1	10/2017	Rindal et al.
2019/0167440	A1	6/2019	Lee et al.
2019/0216482	A1	7/2019	Huffmaster et al.
2019/0216612	A1	7/2019	Schaller et al.
2020/0345401	A1	11/2020	McHale et al.
2021/0113252	A1	4/2021	Ammerman et al.
2021/0154024	A1	5/2021	Lorang et al.
2021/0169459	A1	6/2021	Pacheco-Serrant et al.
2022/0031471	A1	2/2022	Hessler et al.
2022/0110650	A1	4/2022	Huffmaster et al.
2023/0051745	A1	2/2023	Pacheco-Serrant et al.
2023/0124332	A1	4/2023	Lorang et al.

FOREIGN PATENT DOCUMENTS

DE	197 10 392	C1	7/1999
EP	0 682 910		11/1995
EP	1 157 676		11/2001
EP	1 157 676	A1	11/2001
FR	2900814	A1	5/2006
FR	2 900 814		11/2007
JP	2002-28171		1/2002
JP	2002-028171		1/2002
WO	WO 95/025485		9/1995
WO	WO 98/017190		4/1998
WO	WO 98/034552		8/1998
WO	WO 98/34552	A1	8/1998
WO	WO 99/021500		5/1999
WO	WO 99/21500		5/1999
WO	WO 99/047058		9/1999
WO	WO 00/074605		12/2000
WO	WO 00/74605	A1	12/2000
WO	WO 01/001895		1/2001
WO	WO 03/024344		3/2003
WO	WO 2005/048856		6/2005
WO	WO 2006/042334		4/2006
WO	WO 2006/047587		5/2006

WO	WO 2006/047587	A2	5/2006
WO	WO 2006/072941		7/2006
WO	WO 2006/072941	A2	7/2006
WO	WO 2007/009107		1/2007
WO	WO 2007/079237		7/2007
WO	WO 2007/100914		9/2007
WO	WO 2008/021972		2/2008
WO	WO 2008/036505		3/2008
WO	WO 2008/036505	A2	3/2008
WO	WO 2008/063435		5/2008
WO	WO 2008/084479		7/2008
WO	WO 2008/084479	A2	7/2008
WO	WO 2008/103832		8/2008
WO	WO 2008/112308		9/2008
WO	WO 2010/008353		1/2010
WO	WO 2010/008353	A1	1/2010
WO	WO 2011/150350		12/2011
WO	WO 2012/048187		4/2012
WO	WO 2012/178018		12/2012
WO	WO 2013/043850		3/2013
WO	WO 2014/158680		10/2014
WO	WO 2019/148083		8/2019
WO	WO 2019/178575		9/2019

OTHER PUBLICATIONS

International Search Report and Written Opinion in International Application No. PCT/US2008/054590, dated Aug. 22, 2008.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2008/054590, dated Aug. 28, 2009.

International Search Report and Written Opinion in International Application No. PCT/US2019/015386, dated May 23, 2019.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2019/015386, dated Aug. 13, 2020.

International Search Report and Written Opinion in International Application No. PCT/US2019/022632, dated May 30, 2019.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2019/022632, dated Oct. 1, 2020.

International Preliminary Report on Patentability and Written Opinion in International Application No. PCT/US2014/019246, dated Sep. 24, 2015.

Office Communication for U.S. Appl. No. 13/804,847, dated Jul. 13, 2015.

Office Communication for U.S. Appl. No. 13/804,847, dated Oct. 16, 2015.

Extended European Search Report for European Patent Application No. 11787510.4, dated Oct. 15, 2013.

International Search Report and Written Opinion for PCT Patent Application No. PCT/US2011/038377, dated Aug. 25, 2011.

International Search Report and Written Opinion for PCT Patent Application No. PCT/US2013/068906, dated Feb. 6, 2014.

International Search Report and Written Opinion in International Application No. PCT/US2014/019246, dated Aug. 19, 2014.

Office Action dated Jul. 2, 2015 for U.S. Appl. No. 13/803,322.

Office Action dated Apr. 4, 2016 for U.S. Appl. No. 13/803,322.

* cited by examiner




FIG. 1




FIG. 1A




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17







FIG. 18






FIG. 22




FIG. 23



FIG. 24



FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32









FIG. 33



**SPINAL FUSION IMPLANTS AND DEVICES
AND METHODS FOR DEPLOYING SUCH
IMPLANTS**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

The present application is a reissue of U.S. Pat. No. 10,231,843 which issued Mar. 19, 2019, from U.S. patent application Ser. No. 15/276,147, filed Sep. 26, 2016, which is a continuation of U.S. patent application Ser. No. 13/803,322, filed Mar. 14, 2013, now U.S. Pat. No. 9,480,574, the contents of which are incorporated herein by reference.

BACKGROUND

Field of the Disclosure

The present invention generally relates to apparatus and methods employed in minimally invasive surgical procedures and more particularly to various aspects of apparatus and methods for separating and/or supporting tissue layers, especially in the disc space of the spine.

Description of Related Art

A variety of physical conditions involve two tissue surfaces that, for diagnosis or treatment of the condition, need to be separated or distracted or maintained in a separated condition from one another and then supported in a spaced-apart relationship. Such separation or distraction may be to gain exposure to selected tissue structures, to apply a therapeutic pressure to selected tissues, to return or reposition tissue structures to a more normal or original anatomic position and form, to deliver a drug or growth factor, to alter, influence or deter further growth of select tissues or to carry out other diagnostic or therapeutic procedures. Depending on the condition being treated, the tissue surfaces may be opposed or contiguous and may be bone, skin, soft tissue, or a combination thereof.

One location of the body where tissue separation is useful as a corrective treatment is in the spinal column. Developmental irregularities, trauma, tumors, stress and degenerative wear can cause defects in the spinal column for which surgical intervention is necessary. Some of the more common defects of the spinal column include vertebral compression fractures, degeneration or disruption of an intervertebral disc and intervertebral disc herniation. These and other pathologies of the spine are often treated with implants that can restore vertebral column height, immobilize or fuse adjacent vertebral bones, or function to provide flexibility and restore natural movement of the spinal column. Accordingly, different defects in the spinal column require different types of treatment, and the location and anatomy of the spine that requires corrective surgical procedures determines whether an immobilizing implantable device or a flexible implantable device is used for such treatment.

In a typical spinal corrective procedure involving distraction of tissue layers, damaged spinal tissue is removed or relocated prior to distraction. After the damaged tissue has been removed or relocated, adjacent spinal tissue layers,

such as adjacent bone structures, are then distracted to separate and restore the proper distance between the adjacent tissue layers. Once the tissue layers have been separated by the proper distance, an immobilizing or flexible device, depending on the desired treatment, is implanted between the tissue layers. In the past, the implantable treatment devices have been relatively large cage-like devices that require invasive surgical techniques which require relative large incisions into the human spine. Such invasive surgical techniques often disrupt and disturb tissue surrounding the surgical site to the detriment of the patient.

Therefore, there remains a need for implantable treatment devices and methods that utilize minimally invasive procedures.

Such methods and devices may be particularly needed in the area of intervertebral or disc treatment. The intervertebral disc is divided into two distinct regions: the nucleus pulposus and the annulus fibrosus. The nucleus lies at the center of the disc and is surrounded and contained by the annulus. The annulus contains collagen fibers that form concentric lamellae that surround the nucleus and insert into the endplates of the adjacent vertebral bodies to form a reinforced structure. Cartilaginous endplates are located at the interface between the disc and the adjacent vertebral bodies.

The intervertebral disc is the largest avascular structure in the body. The cells of the disc receive nutrients and expel waste by diffusion through the adjacent vascularized endplates. The hygroscopic nature of the proteoglycan matrix secreted by cells of the nucleus operates to generate high intra-nuclear pressure. As the water content in the disc increases, the intra-nuclear pressure increases and the nucleus swells to increase the height of the disc. This swelling places the fibers of the annulus in tension. A normal disc has a height of about 10-15 mm.

There are many causes of disruption or degeneration of the intervertebral disc that can be generally categorized as mechanical, genetic and biochemical. Mechanical damage includes herniation in which a portion of the nucleus pulposus projects through a fissure or tear in the annulus fibrosus. Genetic and biochemical causes can result in changes in the extracellular matrix pattern of the disc and a decrease in biosynthesis of extracellular matrix components by the cells of the disc. Degeneration is a progressive process that usually begins with a decrease in the ability of the extracellular matrix in the central nucleus pulposus to bind water due to reduced proteoglycan content. With a loss of water content, the nucleus becomes desiccated resulting in a decrease in internal disc hydraulic pressure, and ultimately to a loss of disc height. This loss of disc height can cause the annulus to buckle with non-tensile loading and the annular lamellae to delaminate, resulting in annular fissures. Herniation may then occur as rupture leads to protrusion of the nucleus.

Proper disc height is necessary to ensure proper functionality of the intervertebral disc and spinal column. The disc serves several functions, although its primary function is to facilitate mobility of the spine. In addition, the disc provides for load bearing, load transfer and shock absorption between vertebral levels. The weight of the person generates a compressive load on the discs, but this load is not uniform during typical bending movements. During forward flexion, the posterior annular fibers are stretched while the anterior fibers are compressed. In addition, a translocation of the nucleus occurs as the center of gravity of the nucleus shifts away from the center and towards the extended side.

Changes in disc height can have both local and global effects. Decreased disc height results in increased pressure in the nucleus, which can lead to a decrease in cell matrix synthesis and an increase in cell necrosis and apoptosis. In addition, increases in intra-discal pressure create an unfavorable environment for fluid transfer into the disc, which can cause a further decrease in disc height.

Decreased disc height also results in significant changes in the global mechanical stability of the spine. With decreasing height of the disc, the facet joints bear increasing loads and may undergo hypertrophy and degeneration, and may even act as a source of pain over time. Decreased stiffness of the spinal column and increased range of motion resulting from loss of disc height can lead to further instability of the spine, as well as back pain.

Radicular pain may result from a decrease in foraminal volume caused by decreased disc height. Specifically, as disc height decreases, the volume of the foraminal canal, through which the spinal nerve roots pass, decreases. This decrease may lead to spinal nerve impingement, with associated radiating pain and dysfunction.

Finally, adjacent segment loading increases as the disc height decreases at a given level. The discs that must bear additional loading are now susceptible to accelerated degeneration and compromise, which may eventually propagate along the destabilized spinal column.

In spite of all of these detriments that accompany decreases in disc height, where the change in disc height is gradual many of the ill effects may be "tolerable" to the spine and patient and may allow time for the spinal system to adapt to the gradual changes. However, the sudden decrease in disc volume caused by the surgical removal of the disc or disc nucleus may increase the local and global problems noted above.

Many disc defects are treated through a surgical procedure, such as a discectomy in which the nucleus pulposus material is removed. During a total discectomy, a substantial amount (and usually all) of the volume of the nucleus pulposus is removed and immediate loss of disc height and volume can result. Even with a partial discectomy, loss of disc height can ensue. Discectomy alone is the most common spinal surgical treatment, frequently used to treat radicular pain resulting from nerve impingement by disc bulge or disc fragments contacting the spinal neural structures.

The discectomy may be followed by an implant procedure in which a prosthesis is introduced into the cavity left in the disc space when the nucleus material is removed. Thus far, the most common prosthesis is a mechanical device or a "cage" that is sized to restore the proper disc height and is configured for fixation between adjacent vertebrae. These mechanical solutions take on a variety of forms, including solid kidney-shaped implants, hollow blocks filled with bone growth material, push-in implants and threaded cylindrical cages.

A challenge in the use of a posterior procedure to install spinal prosthesis devices is that a device large enough to contact the end plates and expand the space between the end plates of the same or adjacent vertebra must be inserted through a limited space. In the case of procedures to increase intervertebral spacing, the difficulties are further increased by the presence of posterior osteophytes, which may cause "fish mouthing" or concavity of the posterior end plates and result in very limited access to the disc. A further challenge in degenerative disc spaces is the tendency of the disc space to assume a lenticular shape, which requires a relatively larger implant than often is easily introduced

without causing trauma to the nerve roots. The size of rigid devices that may safely be introduced into the disc space is thereby limited.

While cages of the prior art have been generally successful in promoting fusion and approximating proper disc height, typically these cages have been inserted from the posterior approach, and are therefore limited in size by the interval between the nerve roots. Further, it is generally difficult to implant from the posterior approach a cage that accounts for the natural lordotic curve of the lumbar spine.

It is desirable to reduce potential trauma to the nerve roots and yet still allow restoration or maintenance of disc space height in procedures involving vertebrae fusion devices and disc replacement, containment of the nucleus of the disc or prevention of herniation of the nucleus of the disc. In general minimally invasive surgical techniques reduce surgical trauma, blood loss and pain. However, despite the use of minimally invasive techniques, the implantation of cage devices for treating the spine typically involves nerve root retraction, an inherently high risk procedure. It is therefore desirable to reduce the degree of invasiveness of the surgical procedures required to implant the device, which may also serve to permit reduction in the pain, trauma, and blood loss as well as the avoidance and/or reduction of the nerve root retraction.

In minimally invasive procedures, to monitor placement, it is useful that implant devices inserted into spinal tissue be detectable using fluoroscopic imaging systems. However if a device is visible using X-ray technology, then the device can interfere with the detection and monitoring of spinal tissues, such as bone growing into the disc space after a vertebral fusion procedure. Additional advances would also be useful in this area.

SUMMARY

There are several aspects of the present subject matter which may be embodied separately or together in the devices and systems described and claimed below. These aspects may be employed alone or in combination with other aspects of the subject matter described herein, and the description of these aspects together is not intended to preclude the use of these aspects separately or the claiming of such aspects separately or in different combinations as set forth in the claims appended hereto.

In one aspect, a tissue distraction device includes first and second elongated members. The first and second elongated members are insertable between tissue layers and adapted to define a structure in situ having a dimensional aspect in a direction extending between the tissue layers. The tissue distraction device also includes an augmenting elongated member insertable between and in contact with the first and second elongated members to spread the first and second elongated members apart to increase the dimensional aspect of at least a portion of the structure in situ. The augmenting, first, and second elongated members are sufficiently flexible to change between a generally linear configuration and a generally less linear configuration. A locking member is configured to be secured to one of the elongated members at a plurality of locations to lock the augmenting, first, and second elongated members in the generally less linear configuration.

In another aspect, a tissue distraction device includes first and second elongated members defining a generally annular configuration. An augmenting member is fully received

5

between the first and second elongated members and having a linear extent less than the linear extents of the first and second elongated members.

In yet another aspect, a method is provided for assembling a structure in vivo between two body tissue layers comprising first and second elongated members, an augmenting elongated member, and a locking member secured to one of the elongated members at a first location. The method includes delivering the first and second elongated members toward a location between two body tissue layers in a generally linear configuration to define at least a portion of a structure having a dimensional aspect in a direction extending generally from one of the body tissue layers to the other body tissue layer. The configurations of the first and second elongated members is changed to a generally less linear configuration. The augmenting elongated member is inserted between and in contact with the first and second elongated members to spread the first and second elongated members apart to increase the dimensional aspect of at least a portion of the structure. The locking member is secured to one of the elongated members at a second location to lock the first and second elongated members in the generally less linear configuration.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a distraction device or support structure according to the present disclosure;

FIG. 1A is a side elevational view of a distraction device or support structure according to the present disclosure having a non-uniform thickness;

FIG. 2 is a perspective view of the distraction device of FIG. 1, deployed within a vertebral disc space;

FIG. 3 is a top plan view of the lower elongated member of the distraction device of FIG. 1;

FIG. 4 is a perspective view of an augmenting member of the distraction device of FIG. 1;

FIGS. 5-7 are perspective views of a proximal end portion of the upper elongated member of the distraction device of FIG. 1, with an associated anchor member being shown in different positions;

FIG. 8 is an end view of the two elongated members and the augmenting member of the distraction device of FIG. 1, in a disassembled condition;

FIG. 9 is an end view of the two elongated members and augmenting member of FIG. 8, in an assembled condition;

FIG. 10 is a side view of proximal ends of the two elongated members and augmenting member of FIG. 8, in a partially assembled condition;

FIG. 11 is a side view of proximal ends of the two elongated members and augmenting member of FIG. 8, in an assembled condition;

FIG. 12 is a top plan view of the elongated members of the distraction device of FIG. 1 at least partially positioned within a deployment cannula;

FIG. 13 is an end view of the elongated members and cannula of FIG. 12;

FIG. 14 is a cross-sectional top plan view of the augmenting elongated member of the distraction device of FIG. 1;

FIG. 15 is an end view of the distraction device of FIG. 1, with a locking member thereof in an unlocked condition;

FIG. 16 is an end view of the distraction device of FIG. 1, with a locking member thereof in a locked condition;

6

FIG. 17 is a cross-sectional top plan view of a proximal end of the augmenting elongated member of the distraction device of FIG. 1, with a locking member thereof in an initial condition;

FIG. 18 is a cross-sectional top plan view of a proximal end of the augmenting elongated member of the distraction device of FIG. 1, with a locking member thereof in a locked condition;

FIG. 19 is perspective view of a delivery device suitable for delivering the distraction device of claim 1 to a work space;

FIG. 20 is a cross-sectional view of the delivery device of FIG. 19;

FIG. 21 is a perspective view of a shearing assembly of the delivery device of FIG. 19;

FIG. 22 is a perspective view of a pusher device suitable for use with the delivery device of FIG. 19;

FIG. 23 is a perspective view of an extraction device suitable for use with the delivery device of FIG. 19;

FIGS. 24 and 25 are perspective views of disc space sizing devices for determining the proper distraction device to deploy to a vertebral disc space;

FIG. 26 is a perspective view of a funnel for use in delivering a bone filler material to the open interior of the distraction device of FIG. 1;

FIG. 27 is a perspective view of a tamp for use in combination with the funnel of FIG. 26;

FIGS. 28-33 are perspective views illustrating a method of deploying the distraction device of FIG. 1 to a disc space;

FIG. 34 is a top plan view of an alternative embodiment of an elongated member or distraction device according to the present disclosure;

FIG. 35 is a top plan view of the elongated member or distraction device of FIG. 34, with a fixture or fastener securing the proximal and distal ends of the elongated member or distraction device;

FIG. 36 is a perspective view of a distraction device having an elongated member with shape memory properties;

FIG. 37 is a top plan view of an elongated member or distraction device configured to maintain a generally annular configuration without a separate locking member or fastener or fixture; and

FIG. 38 is a top plan view of the elongated member or distraction device of FIG. 37, in a generally annular configuration.

DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The embodiments disclosed herein are for the purpose of providing a description of the present subject matter, and it is understood that the subject matter may be embodied in various other forms and combinations not shown in detail. Therefore, specific embodiments and features disclosed herein are not to be interpreted as limiting the subject matter as defined in the accompanying claims.

The devices and methods of the present invention provide multiple features of distraction devices, distraction device support structures and deployment systems that can be used to actively separate tissue layers by engaging them and forcing them apart, or to support the separation of tissue layers separated by the distraction device itself or by other devices or processes or a combination of these.

As used herein, the terms "distraction device" and "support structure" are intended to have a general meaning and is not limited to devices that only actively separate tissue layers, only support tissue layers or only both actively

separate and support tissue layers. For example, the distraction device and support structure in general can be used to actively separate layers of tissue and then be removed after such separation, or the distraction device and the support structure could be used to support layers of tissue that have been previously separated by a different device. Alternatively, the distraction device and support structure can be used to actively separate the layers of tissue and remain in place to support the layers of tissue in order to maintain such separation. Unless more specifically set forth in the claims, as used herein, “distraction device” and “support structure” encompass any and all of these. In addition, it should be noted that the references to “first” and “second” members or devices are for convenience in the written description. They may be combined to provide a single distraction assembly or structure of selected distraction height, and the assembly is not limited to any particular number of “devices” or “members.” In keeping with the broader aspects of the present invention the specific number of “devices” or “members” can be varied according to the intended usage or design considerations.

It should also be understood that various embodiments of the device, system and method of the present invention are illustrated for purposes of explanation in vertebral fusion procedures and/or replacement of removed discs. However, in its broader aspects, the various features of the present invention are not limited to these particular applications and may be used in connection with other tissue layers, such as soft tissue layers, although it has particular utility and benefit in treatment of vertebral conditions within intervertebral discs or disc spaces.

One embodiment of a distraction device or support structure or implant **10** is shown in FIGS. **1** and **2**. The distraction device **10** shown in FIGS. **1** and **2** is comprised of a first or lower elongated member **12**, a second or upper elongated member **14**, an augmenting elongated member **16**, and a locking member **18**. The augmenting elongated member **16** cooperatively interacts with the first and second elongated members **12** and **14** to increase a dimensional aspect of the distraction device or support structure **10**. The distraction device **10** is preferably comprised of elongated members made of biocompatible materials (including metals and polymers) that are suitable for long term implantation into human tissue where treatment is needed. The biocompatible materials may, for example, be calcium phosphate, tricalcium phosphate, hydroxyapatite, polyetheretherketone (PEEK), nylon, Nitinol (NiTi) or any other suitable biocompatible material. Suitable biocompatible material may also include PEEK with carbon fibers, polyethylenes of low, medium and or high densities, as well as nylons and blends of materials that contain nylons. It is also within the scope of the present disclosure for the elongated members to be at least partially comprised of one or more bioabsorbable materials, such as polyglycolic acid (PGA) or poly-L lactic acid (PLLA), for example. To the extent not contradicted by the present disclosure, elongated members according to the present disclosure may be manufactured, configured, and function generally according to the disclosure of U.S. Patent Application Publication No. 2008/0234687 to Schaller et al., which is incorporated herein by reference.

Elongated members according to the present disclosure may be manufactured using a number of techniques, including machining or milling techniques. Milling can include cutting elongated members from solid blocks or rods of PEEK or other suitable material. Elongated members may also be manufactured using molding techniques. Molding techniques include co-molding various materials together to

form an elongated member, as well as molding a second material over a first material. Elongated members may also be manufactured by injection molding or extrusion processes. In addition, the elongated members of the present invention may be manufactured with electrical discharge machining processes and by rapid prototyping methods including fused deposition modeling (FDM) and stereo lithography (SLA) techniques.

Preferably, the elongated members which form the distraction device **10** have a generally linear configuration for insertion into tissue or between tissue layers. FIG. **3** shows the first or lower elongated member **12** in a generally linear configuration (with the understanding that the second or upper elongated member **14** may be substantially identical to or a mirror image of the first elongated member **12**) and FIG. **4** shows the augmenting elongated member **16** in a generally linear configuration. The distal ends of the elongated members can have chamfer or incline or wedge features to ease the passage of the elongated member through tissue such as bone or vertebral disc material. For example, FIGS. **1** and **2** show a chamfer or incline feature **20** visible on the upper surface **22** of the distal end **24** of the second elongated element **14**. It should be understood that the lower surface **26** of the distal end **28** of the first elongated element **12** may include a similar chamfer feature.

When deployed into or between tissue, the elongated members change configuration, preferably by flexing or bending, to a generally less linear configuration to define the distraction device or support structure **10**. In a preferred embodiment, which is shown in FIGS. **1** and **2**, the distraction device **10** is generally annular, with the first and second elongated members **12** and **14** also being generally annular and the augmenting elongated member **16** being generally arcuate, but non-annular, as will be described in greater detail herein. The elongated members of the distraction device **10** may include features that add flexibility to the elongated member to assist in bending or changing the configuration of the elongated member from a generally linear configuration to a less linear configuration and vice versa. For example, the elongated members may include lateral teeth **30** and intermediate slots or indents **32** (FIGS. **3** and **4**) that aid in relieving stress and add flexibility to the elongated member. When the elongated member is deployed in spinal tissue, the slots **32** may also provide gaps for the introduction of bone graft materials, cements, or pharmaceutical compounds to the spinal tissues.

In some embodiments, the elongated members may also be designed with additional features that limit or control the nature of the bending or shape change that the elongated members may experience. For example, FIGS. **3** and **4** show a plurality of T-shaped members **34** on one lateral side of the elongated member (i.e., the lateral side opposite the aforementioned teeth **30** and slots **32**, if provided), with the T-shaped members **34** having longitudinal extensions on their outer edge such that adjacent T-shaped members **34** almost touch each other, leaving a relatively narrow opening or aperture **36** at a more central location between adjacent T-shaped members **34**. When the elongated member is bent toward the lateral side having the T-shaped members **34**, the longitudinal extensions on adjacent T-shaped members **34** come into contact and provide resistance to further bending, thereby acting as a stop to limit further curvature. In contrast, the teeth **30** on the opposite lateral side of the elongated member lack such longitudinal projections and, therefore, the elongated member can be bent to a much greater degree in this direction before the teeth **30** come into contact with adjacent teeth **30** to limit further curvature.

Also, it should be noted that by providing the T-shaped members **34** and intermediate opening or apertures **36**, increased flexibility is provided that allows the elongated member to bend toward the opposite side (i.e., upwardly in the orientation of FIG. **3** or to the right in the orientation of FIG. **4**).

Additional features may be added to enhance or limit the flexibility of the elongated members of the distraction devices, including grooves, slots, channels, and pockets and teeth or other extensions or members of various shapes. The slots, grooves, channels, and pockets may be placed, for example, in a linear pattern or spirally around the body of the elongated member. Through holes or apertures may also assist in providing flexibility as well as serve as lumens for various wires or filaments, as will be discussed in greater detail. The placement of a greater number of these features in one region of an elongated member can make that region more or less flexible than other regions of the device with fewer or different flexibility enhancing or limiting features. In this manner, selected regions of the elongated member will be easier or more difficult to bend or deflect to assist the shaping of the distraction device **10** in a desired configuration, such as a circular, rectangular, or oval shape. Alternatively, the flexibility features can be located uniformly along a segment or the whole of the elongated member to provide regions of uniform flexibility.

Flexibility of the elongated members may also be achieved or varied by fabricating the device from a combination of materials with different degrees of flexibility. For instance, by located more rigid material on one side of an elongated member, the elongated member may be easier to bend or deflect toward that side. Particularly, if the elongated member is preformed into a desired in situ configuration (e.g., a curved configuration) and temporarily straightened for insertion, the more rigid material may tend to retain the desired configuration to a greater degree than the other material and form the desired configuration when the elongated member is introduced into the work space. Also, the elongated member can have alternating or different sections along its length that are made of different materials having different rigidity.

In another aspect of the present disclosure, the elongated members preferably have the ability to recover from temporary deformation. As noted previously, the elongated member(s) may be pre-set or pre-formed into a desired in situ shape and then temporarily reshaped, such as by straightening, for insertion. In this aspect, for instance, a pre-shaped elongated member may tend to recover its shape more quickly or completely in body-temperature spinal tissue after being in a less-curved condition during shipping and storage inside of a deployment cannula. In other embodiments, due to plastic creep or other material characteristics, the elongated members may not recover their original shape after extended deformation in the cannula, and an external force may be used to shape the elongated member after it is at least partially inserted into the work space.

In a specific example, elongated members manufactured from polymeric materials such as PEEK may be pre-shaped by placing the elongated member in a metal fixture or jig having a desired shape, such as an annular or arcuate shape, and then heating the elongated member to relieve the bending stress. For instance, the elongated member can be treated for about 5 minutes at about 160° C. For many polymeric materials, such as PEEK, the pre-shaping process biases the elongated member toward a desired shape yet still allows the elongated member to be deformed either in the

cannula or in situ after the elongated member is inserted into a work space. In some embodiments, such as where the elongated members are comprised at least in part of PEEK, the elongated members do not have shape memory material properties. Consequently, in some embodiments, particularly when PEEK is used, the elongated member does not return to its original shape without the additional application of an external force to shape the member. Such external force may be applied, for example, by a pull wire, as will be described in more detail.

In some embodiments, the deformation of the elongated members is constrained in a first axis and allowed in a plane at an angle to the first axis to allow deflection in a different plane. For instance, in FIG. **2**, a generally annular distraction device **10** is shown in a vertebral disc. As used herein, the term “annular” is not limited to substantially circular distraction devices and elongated members, but may include other closed shapes, such as ovals and rectangles, or substantially closed versions of such shapes. The distraction device **10** is formed by the aforementioned three elongated members **12**, **14**, and **16** and is relatively rigid in the direction (e.g., a vertical direction when standing) extending between two tissues layers, i.e. the adjacent vertebra. The distraction device **10** is resistant to deflection in a direction parallel to the longitudinal axis of the spine due to the relatively solid, continuous structure of the elongated members along this axis. Consequently, due to the structure of the elongated members forming the distraction device **10** of FIG. **2**, no deflection or only limited deflection is allowed in the direction of distraction. In certain embodiments, the distraction device or implant **10** does not substantially compress under vertical forces that the human spine normally endures, such as, but not limited to, up to about 1000 N. In contrast, the elongated members are relatively more flexible in the plane perpendicular to the direction of distraction to allow the elongated members to be shaped as desired, such as curved or deflected to conform to the shape of the space into which they are implanted.

Looking more particularly at the augmenting elongated member **16**, it is configured to be inserted and slid between the first and second elongated members **12** and **14** to increase the height of or otherwise augment the distraction device **10**. The degree of height increase of the distraction device **10** is dependent upon the height of the augmenting elongated member **16**. For instance, a thicker augmenting elongated member (i.e., an augmenting elongated member having a relatively great height) will cause a greater increase in the height of the distraction device than a thinner augmenting elongated member (i.e., an augmenting elongated member having a relatively small height). In embodiments inserted into the disc space to distract adjacent vertebral bodies, the height of the distraction device **10** (which is generally equal to the combined heights of the bodies of the constituent elongated members) is preferably sufficient to restore the disc to its normal height or thereabout, which will depend on the size of the patient and the disc's location in the spinal column. The height of the distraction device **10** can be, for example, from about 5 mm to about 15 mm. More particularly, the height can be from about 7.5 mm to about 13.5 mm, or about 9 mm to about 12 mm and ranges therein. For relatively short individuals or children, the disc size and, consequently, the height of the support structure can be, for example, from about 5 mm to about 7 mm. For relatively tall individuals, the disc height and, consequently, the height of the support structure can be, for example, from about 9 mm to about 15 mm or greater potentially. In other applications, the dimensions (including the heights) of the individual

11

elongated members and the resulting distraction device may vary without departing from the scope of the present disclosure.

In one embodiment, the thickness of the augmenting elongated member can be different along its length to cause different amounts of additional distraction along the length of the distraction device. For instance, the proximal portion of the augmenting member may be thicker (taller) than the distal portion of the augmenting member, in which case the increase in the height of the proximal portion of the distraction device will be greater than the augmentation in the height of the distal portion of the device. The ability to create a greater increase in height in one region of a distraction device allows for adjustments in the curvature of the spine of a patient. For instance, a collapsed disc in the lumbar region of the spine can result in the loss of the normal lordosis in the lumbar region of the spine. The insertion of an augmenting elongated member of variable thickness/height between upper and lower elongated members deployed in a collapsed lumbar disc can restore the lumbar disc to the more normal morphology of a greater height on its anterior region as compared to its posterior region. In such a situation, the augmenting member may have a greater height at its central region between the distal and proximal ends than at either the proximal end or distal end. FIG. 1A illustrates an exemplary distraction device 10A having a non-uniform thickness.

Preferably, once augmented, the height of the distraction device 10 is fixed and is not adjustable or variable, while the augmenting member 16 is preferably fixed in position between the first and second elongated members 12 and 14 and not removable. The first and second elongated members 12 and 14 may have corresponding contoured surfaces or features that mechanically or frictionally cooperate or mate to assist in maintaining the positions of the first and second elongated members 12 and 14 relative to each other and within a work space to increase the stability of the distraction device 10. For example, in one embodiment, the upper surface 22 of the second elongated element 14 (as shown in greater detail in FIGS. 5-7) and the lower surface 26 of the first elongated element 12 include protrusions or ribs or teeth 38 or is otherwise textured, which may be advantageous when the first and second elongated members 12 and 14 are in their generally less linear configuration to define the distraction device 10. In particular, such textured surfaces may be advantageous in that contact between the protrusions 38 and the tissue to be distracted and/or supported may help to anchor the elongated member (and, hence, the distraction device 10) in position. For example, when the distraction device 10 contacts a vertebral body, the protrusions 38 may dig into the vertebral body for improved traction, thereby decreasing the risk of movement of the distraction device 10 after implantation.

The top side or surface 40 of the first elongated member 12 may contain a contoured portion 42 (FIGS. 3, 8, and 9), while the bottom side or surface 44 of the second elongated member 14 may also include a contoured portion 46, as shown in FIGS. 8 and 9. The augmenting elongated member 16 also may include a bottom contoured portion or surface 48 and a top contoured portion or surface 50, as shown in FIGS. 4, 8, and 9. In the illustrated embodiment, the contoured portions 48 and 50 of the augmenting elongated member 16 are protrusions or raised ribs that are configured to mate with the contoured portions 42 and 46, respectively, of the first and second elongated members 12 and 14. In the illustrated embodiment, the contoured portions 42 and 46 of the first and second elongated members 12 and 14 are

12

indentations or slots or grooves in the top surface 40 of the first elongated member 12 and the bottom surface 44 of the second elongated member 14. Alternatively, the bottom and top surfaces of the augmenting elongated member may include indentations or slots or grooves that are configured to mate with a protrusion or rib on the top surface of the first elongated member and the bottom surface of the second elongated member, respectively.

As shown in FIGS. 8 and 9, the cooperation between the raised ribs and grooves in the facing surfaces between of the elongated members also can function as a guide or guide track that directs the augmenting elongated member 16 between the first and second elongated members 12 and 14. As seen in FIGS. 10 and 11, the proximal ends 52 and 54 of the first and second elongated members 12 and 14 can also be ramped or widened to provide a larger opening, thereby easing the entry of the augmenting elongated member 16 (which may have a tapered or wedge-shaped distal end 56, as noted above) between the first and second elongated members 12 and 14. Furthermore, any of the elongated members may have additional mating or guiding surfaces which provide added stability to the resulting distraction device or implant support structure 10.

In a preferred embodiment, the raised ribs 48 and 50 and grooves 42 and 46 are configured to prevent vertical separation of the elongated members. For example, the illustrated raised ribs 48 and 50 are generally T-shaped, while the grooves 42 and 46 have relatively narrow necked-down portions 58. As the augmenting elongated member 16 is inserted between the first and second elongated members 12 and 14, the relatively wide heads 60 of the raised ribs 48 and 50 are received by the grooves 42 and 46, with the necked-down portions 58 positioned between the wide heads 60 and the body of the augmenting elongated member 16. By such a configuration, the rib heads 60 and the necked-down portions 58 of the grooves 42 and 46 prevent the elongated members from being vertically separated after at least partial insertion of the augmenting elongated member 16 between the first and second elongated members 12 and 14. This locking mechanism may assist in preventing the elongated members from slipping relative to one another in response to the stresses a patient's normal movements place on the implant 10.

FIGS. 10 and 11 also show another optional locking feature for securing the elongated members together. In the illustrated embodiment, the first and second elongated members 12 and 14 include recesses 62 into which locking protrusions 64 of the augmenting member 16 can enter to lock the augmenting member 16 into a desired longitudinal orientation relative to the first and second elongated members 12 and 14. When fully engaged, all three elongated members are substantially locked against relative movement. Preferably, the locking protrusions 64 enter into the recesses 62 to lock the elongated members together when the augmenting elongated member 16 has been fully inserted between the other two elongated members 12 and 14, but it is also within the scope of the present disclosure for the elongated members to lock together prior to the augmenting elongated member 16 being fully received between the other two elongated members 12 and 14. For example, the elongated members may be configured such that the augmenting elongated member 16 is not advanced fully into the space between the other two elongated members 12 and 14, but is instead locked in place with a portion (e.g., a proximal end) remaining outside of the space between the other two elongated members 12 and 14.

13

The guiding of the locking protrusions 64 into the recesses 62 may be assisted by locating them along the contoured surfaces of the associated elongated member. As seen in FIGS. 3 and 4, for example, the recess 62 and groove 42 in the upper surface 40 of the first elongated member 12 are aligned, thereby allowing the groove 42 to act as a guide in which the locking protrusion 48 on the bottom surface 66 of the augmenting elongated member 16 slides distally to seat within the recess 62, as shown in FIG. 11. FIG. 4 shows how the protrusion 64 and raised rib 50 of the upper surface 68 of the augmenting elongated member 16 are similarly aligned, as may be the protrusion 64 and raised rib 48 of the lower surface 66 of the augmenting elongated member 16.

As illustrated, the locking protrusions 64 may be cylindrically shaped, but it may be otherwise shaped without departing from the scope of the present disclosure. If provided as a cylinder, the diameter of the locking protrusion 64 may be greater than the width of the associated raised rib 48, 50 (FIG. 4) and of the associated groove 42, 46 at the point 70 it meets the recess 62 into which the protrusion 64 is to be seated (FIG. 3). By such a configuration, the protrusion 64 may be pressed into the recess 62, but will resist being retracted therefrom due to the relatively narrow entry point 70. The portion 72 of the groove 42, 46 immediately distal the recess 62 may also be relatively narrow, thereby preventing over-advancement of the protrusion 64 beyond the recess 62.

The locking protrusions 64 may be any suitable size or material, such as cylinders or pins made of a radiopaque material (e.g., tantalum or gold or platinum) with a diameter ranging from about 0.25 mm to about 2 mm. By providing the locking protrusions 64 as radiopaque members, they assist the surgeon in positioning the elongated members in situ. For a similar effect, the interlocking recesses 62 may be lined with tantalum or another radiopaque material. In other embodiments, other portions of the elongated members may be radiopaque to further assist in determining the locations of the elongated members in situ. In one exemplary embodiment, the elongated members are manufactured from radiolucent materials, such as PEEK (which may be a preferred material), polyetherketoneketone (PEKK), nylon and ultra-high molecular weight polyethylenes (UMPE). By providing discrete radiopaque regions or markers in known locations within the elongated members, the surgeon may determine the locations and relative orientations of the elongated members in situ.

In addition to the foregoing features, the elongated members may further include internal cavities or passages or lumen for receiving various wires or filaments. For example, as described above, the shape of the distraction device 10 may be assisted, controlled, and/or adjusted as the elongated members are being deployed between the tissues to be distracted. The forces required to control the shape of the elongated members are preferably compatible with typical hand-held delivery systems and tools. For instance, the shape of an elongated member may be controlled with pull wire systems deployed either inside the elongated member and/or outside the elongated member. In the illustrated embodiment, the shape of the first and second elongated members 12 and 14 is controlled during insertion by applying a greater force to one side of the elongated members than is applied to the other side using a pull wire 74 (FIGS. 12 and 13). The application of unequal force causes the elongated members 12 and 14 to curve in a particular direction (i.e., to the left in the orientation of FIG. 12).

In the embodiment of FIGS. 12 and 13, the pull wire 74 passes through both the first and second elongated members

14

12 and 14. The pull wire 74 may pass through a wire lumen 76, 78 of each of the first and second elongated members 12 and 14 like those shown in FIGS. 8 and 9 or, alternatively, through a wire channel or slot that is not fully enclosed. As shown in FIG. 13, the pull wire 74 passes out of the distal end of one wire lumen, and then loops back into the other wire lumen. The pull wire 74 may be a single wire or filament or a braid or weave comprising multiple wires or filaments and may be made of any flexible material that can be used to exert a force along the length of the first and second elongated members 12 and 14, such as steel, Nitinol, fiber (both synthetic and natural), or the like. In the illustrated example shown in FIGS. 8, 9, 12, and 13, the pull wire 74 is on the left side of the first and second elongated members 12 and 14 (when considered from the proximal ends of the elongated members) such that a proximally directed force (e.g., pulling one or both of the ends of the wire 74, will cause the first and second elongated members 12 and 14 to curve to the left. Alternatively, systems in which a push or a distally directed force, applied through a rigid pusher or the like could be provided to the first and second elongated members 12 and 14 to cause them to curve in a desired direction.

In systems such as the one illustrated in FIGS. 12 and 13, which include a pull wire 74 that passes through both the first and second elongated members 12 and 14, the pull wire 74 also tends to prevent the first and second members 12 and 14 from separating during deployment into the work space. In particular, a pull wire 74 extending through both the first and second elongated members 12 and 14 may also allow pull force to be exerted to maintain the position of the first and second elongated members 12 and 14 adjacent to the distal end 80 of a deployment cannula 82 while the augmenting member 16, is being inserted between the first and second elongated members 12 and 14. In particular, the insertion of the augmenting elongated member 16 between the first and second elongated members 12 and 14 can create a repulsive force that tends to push the first and second elongated members 12 and 14 away from both the cannula 82 and the augmenting member 16. The force exerted by the pull wire 74 and the force of friction between the surfaces of the first and second elongated members 12 and 14 and the surrounding tissues, such as the endplates of the vertebrae above and below a disc, can also serve to resist this repulsive force.

In other embodiments, including the illustrated embodiment, a separate mechanism may be provided to maintain the position of the first and second elongated members 12 and 14 with respect to the deployment cannula 82 while the augmenting elongated member 16 is inserted therebetween. As shown in FIGS. 5-7 and 12, an anchoring or tethering system or wires 84 can be used to hold the first and second elongated members 12 and 14 aligned with the distal end 80 of the delivery cannula 82 while the augmenting elongated member 16 is inserted between the first and second elongated members 12 and 14. The illustrated tethering system includes a pair of anchor wires or cables or filaments 84, each of which attaches to the proximal end region 52, 54 of one of the first and second elongated members 12 and 14. As best shown in FIGS. 5-7, each anchor wire 84 may include an enlarged end 88 (e.g., a generally spherical or ball-shaped end piece) that is at least partially received within a cavity 90 defined within the proximal end 52, 54 of the associated elongated member (FIG. 5). The thinner proximal or body portion of the anchor wire 84 extends through a retaining hole 92 (FIGS. 6 and 7) communicating with the cavity 90 while the enlarged end 88 is positioned within the cavity 90.

15

The diameter of each retaining hole **92** is smaller than that of the associated enlarged end **88** to resist removal of the enlarged end **88** from the cavity **90** in a proximal direction.

The anchor wires **84** may provide little resistance to the deployment of the first and second elongated members **12** and **14**, permitting the first and second elongated members **12** and **14** to exit the distal end **80** of the deployment cannula **82**. The length and tension of the anchor wires **84** are adjustable to provide increased tension after the first and second elongated members **12** and **14** have exited the cannula **82**. The anchor wires **84** keep the first and second elongated members **12** and **14** in close proximity to the distal end **80** of the cannula **82**, thereby allowing the insertion of the augmenting elongated member **16** between the first and second elongated members **12** and **14** without having to increase the tension on the pull wire **74**. This may be advantageous, as applying excessive tension to the pull wire **74** may move the first and second elongated members **12** and **14** to an undesirable curved configuration during insertion of the augmenting elongated member **16** therebetween.

After the implant **10** has been deployed and properly positioned, the anchor wires **84** may be detached from the first and second elongated members **12** and **14**. In one embodiment, after the pull wire **84** has been removed from the implant **10** (e.g., by cutting it and applying a proximally directed force to both of its ends), a distally directed force may be applied to the implant **10** (e.g., pushing the implant **10** approximately 2 mm further from its deployed position) while the tension in the anchor wires **84** is maintained. Doing so effectively increases the tension on the anchor wires **84**, which increased tension will cause the enlarged ends **88** of the anchor wires **84** to enter (FIG. **6**) and pull through (FIG. **7**) the smaller retaining holes **92** in the elongated members, thereby detaching the anchor wires **84** from the implant **10**. Alternatively, a looped anchor wire (or wires) may be formed, such that a loop passes through holes or slots or openings in both of the first and second elongated members **12** and **14**. The loop may then be cut by the user or break automatically like a mechanical fuse at the completion of insertion by the user cutting or otherwise severing the loop. In another embodiment, the loop may be configured to pull through or to cut through portions of the first and second elongated members **12** and **14** to detach without the loop being cut or severed.

As shown in FIG. **13**, when the augmenting member **16** is positioned within the cannula **82**, the pull wire **74** and anchor wires **84** may extend proximally beyond the augmenting elongated member **16** by occupying the space between the corners of the augmenting elongated member **16** and the corners of the cannula **82**.

As noted above, the augmenting elongated member **16** may include a locking feature or mechanism or member in the form of a locking wire or cable or tether or filament **18**, which is illustrated in FIGS. **12-18**. The locking member **18** extends between a fixed end **94** (FIGS. **14**, **17**, and **18**) and a free end **96**. The fixed end **94** (which may be an enlarged ball or sphere) is secured at or adjacent to the proximal end **98** of the augmenting elongated member **16**, positioned within an interior cavity or pocket **100** defined in the augmenting elongated member **16** at or adjacent to its proximal end **98**. The interior cavity **100** may also receive a spacer or backstop **102**, which will be described in greater detail herein.

An interior passage or lumen or cavity **104** communicates with the interior cavity **100**, with the locking member **18** extending distally from the fixed end **94** through the interior passage **104**. The interior passage **104** leads to the distal end

16

56 of the augmenting elongated member **16**, where the locking member **18** exits the augmenting elongated member **16** and loops back toward the proximal end **98** of the augmenting elongated member **16**, as shown in FIG. **12**. The lateral side of the augmenting elongated member **16** includes a lateral groove **106** (best seen in FIG. **18**) through which the locking member **18** extends as it loops back toward the proximal end **98** of the augmenting elongated member **16**. The lateral groove **106** is located on the side of the augmenting elongated member **16** that will face radially inwardly when the distraction device **10** is fully deployed, such that the lateral groove **106** and the portion of the locking member **18** positioned therein communicate with the open interior or resident volume **108** defined by the generally annular distraction device **10**.

At or adjacent to the proximal end **98** of the augmenting elongated member **16**, the locking member **18** reenters the interior of the augmenting elongated member **16** from the lateral groove **106** via a bore **110** extending from one lateral side of the augmenting elongated member **16** toward the other lateral side, as shown in FIG. **17**. As shown in FIG. **17**, the bore **110** may extend all the way between the two lateral sides of the augmenting elongated member **16**, but it is also within the scope of the present disclosure for the bore **110** to extend only partially through the width of the augmenting elongated member **16**.

In the illustrated embodiment, the bore **110** causes the locking member **18** to reenter the interior cavity **100** of the augmenting elongated member **16** in a region directly adjacent to the spacer **102**, but separated from the fixed end **94** of the locking member **18** by the spacer **102**. This portion of the locking member **18** extends along the width of the spacer **102** until it reaches a longitudinally extending bore **112** that communicates with the laterally extending bore **110**, as best shown in FIG. **18**. The free end **96** of the locking member **18** extends through the longitudinally extending bore **112** and exits the proximal end **98** of the augmenting elongated member **16** (FIG. **17**), where it is accessible to apply tension to the locking member **18**. For example, FIG. **15** shows the locking member **18** in an un-tensioned or moderately tensioned condition, while FIG. **16** shows the locking member **18** in a tensioned condition, with a pulling force applied to the portion of the free end **96** of the locking member **18** extending proximally out of the longitudinally extending bore **112**. Applying tension to the free end **96** of the locking member **18** also causes the locking member **18** to separate from the lateral groove **106** and move through the open interior or resident volume **108** of the distraction device **10**, as can be understood by comparing FIG. **17** to FIGS. **14** and **18**.

The proximal end **98** of the illustrated augmenting elongated member **16** also includes a fastener **114** (e.g., a set screw) positioned within a longitudinal fastener bore **116** in communication with the spacer **102**, with a portion of the free end **96** of the locking member **18** positioned between the fastener **114** and the spacer **102**. The fastener **114** extends between an outer end **118** and an inner end **120** (FIGS. **17** and **18**). The outer end **118** is configured to allow advancement of the fastener **114** in a distal direction into the fastener bore **116** toward the spacer **102**. In a preferred embodiment, the outer perimeter of the fastener **114** and the surface of the fastener bore **116** include matching threads, in which case the outer end **118** of the fastener **114** is configured to accept a torque delivery tool or driver that rotates the fastener **114** to advance it distally into the fastener bore **116**. In other embodiments, the fastener **114** may be advanced into the fastener bore **116** by non-rotational movement.

17

The inner end **120** of the fastener **114** is configured to have a cutting or shearing surface that severs the locking member **18** when brought into contact therewith with sufficient force. In the illustrated embodiment, the spacer **102** includes a retaining surface **122** and a cutting surface **124** facing the fastener **114** and separated by a step, with the cutting surface **124** positioned adjacent to and proximal of the retaining surface **122** (i.e., closer to the fastener **114**), as shown in FIGS. **17** and **18**. When the fastener **114** is sufficiently advanced into the fastener bore **116** (preferably, when it has been fully advanced into the fastener bore **116**, which may be one full rotation when the fastener **114** is a threaded set screw), the inner end **120** of the fastener **114** comes into contact with the cutting surface **124** of the spacer **102**, thereby severing the extra slack of the locking member **18** therebetween (FIG. **18**) while maintaining the tension of the locking member **18**. In contrast, the inner end **120** of the fastener **114** remains spaced away from the retaining surface **122** of the spacer **102**, but sufficiently close so as to press the locking member **18** against the retaining surface **122**, thereby effectively securing the locking member **18** to the spacer **102** of the augmenting elongated member **16** at that location.

By so securing the locking member **18** to the augmenting elongated member **16** at two locations (both of which are at or adjacent to the proximal end **98** of the augmenting elongated member **16** in the illustrated embodiment), the locking member **18** prevents the configuration of the augmenting elongated member **16** from changing. Locking the augmenting elongated member **16** into a particular configuration also effectively locks the first and second elongated members **12** and **14** (as well as the distraction device **10**) into their current configuration, due to the locking relationship between the various elongated members, as described above. Preferably, the distraction device **10** is shaped into its final configuration prior to the fastener **114** locking the locking member **18** in place, thereby locking the distraction device **10** in its final configuration for long-term residence within the work space, as will be described in greater detail herein.

While the locking member **18** is described and illustrated as being associated with and secured to the augmenting elongated member **16**, it should be understood that the locking member **18** may be associated with one of the other elongated members **12** and **14** and secured to multiple locations of either to lock the distraction device **10** in a particular configuration. Furthermore, it is also within the scope of the present disclosure for a plurality of similarly or differently configured locking members to be provided and associated with one or more of the elongated members. Additionally, rather than the locking member **18** being secured at multiple locations to an individual elongated member, it is also within the scope of the present disclosure for the locking member **18** to be secured at one location of one of the elongated members and at a second location of one of the other elongated members. For example, the locking member **18** may be secured to the augmenting elongated member **16** at a fixed end **94** and extend from the proximal end **98** of the augmenting elongated member **16** to exit the distal end **56** of the augmenting elongated member **16**, as described above. After exiting the distal end **56** of the augmenting elongated member **16**, the free end **96** of the locking member **18** may be secured to one of the other elongated members by any suitable means, rather than being secured at a second location of the augmenting elongated member **16**. It should be understood that so securing the locking member **18** at separate locations of different elongated members will have a similar effect to securing the

18

locking member **18** to separate locations of the same elongated member, in that the resulting distraction device **10** will be locked into a particular configuration.

The wires or cables or filaments or tethers described herein may consist of materials suitable for sterilization and compatible for temporary contact with animal, including human tissue. Metal wires may be made from stainless steel, Nitinol, or other suitable metal wires, for example. Non-metal wires may be made from natural fibers and polymeric fibers including polyethylene, UHPE, Victrex, PET, or similar medical-grade polymers.

Tensile forces may be applied to the wires or cables or filaments or lines described herein by any suitable source. In a preferred embodiment, the tensile forces are applied via a delivery device **126** (FIGS. **19** and **20**), of which the deployment cannula **82** is the distal end. To the extent not contradicted by the present disclosure, delivery devices according to the present disclosure may be manufactured and configured generally according to the disclosure of U.S. Patent Application Publication No. 2008/0234687 to Schaller et al., which is incorporated herein by reference.

In the illustrated embodiment, the free ends of the various lines pass through the deployment cannula **82** to be attached to various attachment points located within the delivery device **126**. The lines may be attached to the delivery device **126** by any of a number of suitable means, including releasable mechanical features such as screws, clamps, crimps, and ferrules and other like means. The lines may also be attached by knotting, gluing or pinching them to the delivery device **126**.

In the illustrated embodiment, the pull wire **74** is associated with a slider **128** that is received within a central opening or cavity **130** of the delivery device **126** that is substantially coaxial with the deployment cannula **82**. The slider **128** is movable along the longitudinal axis of the delivery device **126** within the central cavity **130** to adjust the tension in the pull wire **74**, thereby adjusting the curvature of the first and second elongated members **12** and **14**, as described above. In the illustrated embodiment, the outer surface of the slider **128** is threaded to engage threads of the central cavity **130**, such that rotation of the slider **128** about its central axis will advance it proximally and distally through the central cavity **130**. It is also within the scope of the present disclosure for the slider **128** to move with respect to the remainder of the delivery device **126** without rotating (e.g., by translational movement). If the slider **128** is configured to rotate while moving through the central cavity **130**, an insertion knob **132** may be associated with the slider **128** and extend outside of the central cavity **130** to be rotated in order to rotate and move the slider **128** through the central cavity **130**.

In the illustrated embodiment, the anchor wires **84** are associated with a capstan or spool or spindle **134**, with the capstan **134** controlling the tension on the anchor wires **84**. The capstan **134** may also limit the total amount of line released to hold the deployed first and second elongated members **12** and **14** at the desired location in close proximity to the distal end **80** of the cannula **82**. The tension in the anchor wires **84** may also be controlled by other means such as springs, resilient means, sliding mechanisms, rotating mechanisms, moving mechanisms, pulleys, stretchable lines and the like.

The free end **96** of the locking member **18** may also be adjustably secured to a rotary mechanism (similar to the pull wire **74** and the anchor wires **84**) or to a non-rotational

component of the delivery device **126** or may extend through the delivery device **126** without being secured thereto.

As described above, after the distraction device **10** has been deployed, the pull wire **74** may be severed and removed. In the illustrated embodiment, the delivery device **126** includes a shearing assembly **136** (FIG. **21**) for severing or cutting the pull wire **74** (or any of the other wires, as desired). The shearing assembly **136** includes a stationary member **138** that is fixedly secured to the delivery device **126** and a movable member **140** that is rotatably secured to the stationary member **138** (e.g., by a cap **142**). The pull wire **74** (or any other wire to be severed by the shearing assembly **136**) extends through the stationary and movable members **138** and **140**. When it is desirable to sever the pull wire **74** (or any of the other wires or filaments described herein, such as the anchor wires **84**), the movable member **140** is rotated with respect to the stationary member **138** to cut or shear or otherwise sever the pull wire **74**. Another portion of the pull wire **74** may be secured at another location of the delivery device **126**, such that proximal movement of the delivery device **126** (e.g., removing the delivery device **126** from the work space) will cause the pull wire **74** to withdraw from the first and second elongated member **12** and **14**.

A tool kit may include a number of related components and tools (illustrated in FIGS. **22-27**) that may be used in connection with the delivery device **126**. For example, FIG. **22** shows a pusher device or plunger **144** that may be used to push the augmenting elongated member **16** out of the deployment cannula **82** and into place between the first and second elongated members **12** and **14**. The insertion knob **132** and slider **128** (if provided) may have central openings through which the pusher device **144** may extend to contact the proximal end **98** of the augmenting elongated member **16**. In one embodiment, the distal end of the pusher device **144** is configured to engage and rotate the fastener **114** of the augmenting elongated member **16**, as described above. In other embodiments, a separate device may be employed to advance the fastener **114** to the point that it severs and secures the free end **96** of the locking member **18**.

FIG. **23** shows an extraction device **146** that may be used independently or in combination with the delivery device **126** to remove the distraction device **10** or an individual elongated member from the work space, if necessary.

FIGS. **24** and **25** show disc space sizing devices or paddles **148** and **150** that may be used prior to introduction of the delivery device **126** to the disc space. According to conventional usage, the disc space sizing devices **148** and **150** are inserted into the disc space to determine the minimum and proper heights of the disc space. When the minimum and proper heights have been determined, the appropriate delivery device may be selected from a kit that includes a plurality of delivery devices of varying heights.

FIGS. **26** and **27** show a funnel **152** and tamp **154** that may be used after the delivery device **126** has been removed from a work space to deliver a bone filler material **156** (FIG. **2**) into the open interior or resident volume **108** of the distraction device **10**, as will be described in greater detail herein. As used herein, "resident volume" refers generally to a structural characteristic of the support structure. The resident volume is a volume that is generally defined by the distraction device. The resident volume is preferably, but not necessarily, a volume completely enclosed by the distraction device, but can also be any volume generally defined by the distraction device. This term does not necessarily mean that the resident volume is an open or void volume or cavity and does not preclude a situation in which the resident volume

is, at some point in time, filled with another material, such as bone graft, cement, therapeutic drugs or the like. It also does not preclude the resident volume from containing undisturbed human tissue that is located or remains within the resident volume during or after deployment of the distraction device. For example, if the distraction device is employed to separate adjoining soft tissue layers, such as subcutaneous fat and underlying muscle tissue, the resident volume of the distraction device support structure may be hollow or void of tissue after separation. On the other hand, if inserted into a spinal disc space, the resident volume may contain undisturbed disc tissue such as a portion of the nucleus pulposus or bone graft material placed before or after installation.

FIGS. **28-33** illustrate an exemplary method of inserting the distraction device **10** into a vertebral disc space, with FIG. **2** showing the fully installed distraction device **10**. According to the illustrated method, an access port is made through the annulus of a vertebral disc using instruments and endoscopic or minimally invasive procedures generally known to those skilled in the art. The access port may be relatively small (e.g., no larger than the size of the deployment cannula **82**), such that the procedure may be minimally invasive, with the resulting tissue distraction height being greater than the height of the access port. The location of the access port may vary without departing from the scope of the present disclosure, but it is preferred for the location of the access port be chosen so as to decrease the risk of nerve damage. In one embodiment (which is illustrated in FIG. **28**), the access port is positioned so as to facilitate a transforaminal lumbar interbody fusion ("TLIF") approach, but other approaches may also be practiced without departing from the scope of the present disclosure. For example, according to another approach, the access port may be positioned so as to facilitate deployment of the elongated members through Kambin's triangle, which is defined by the exiting nerve root (the hypotenuse of the triangle), the superior border of the inferior vertebra (the base of the triangle), and the traversing nerve root (the height of the triangle). While this approach results in an access port that is positioned at a different location than in the illustrated TLIF approach, it should be understood that the method of inserting the elongated members so as to define the implant in situ (described below in greater detail) may be substantially the same.

Optionally, all or a portion of the nucleus pulposus is removed and the endplates of the adjacent vertebrae are scraped to cause bleeding and promote the fusion of bone graft material to the vertebral endplates. Sizing paddles **148**, **150** (FIGS. **24** and **25**) or like apparatus, may be slipped through the access port to determine the minimum disc height and the desired final disc height. Based on the minimum and desired final disc height measurement from the sizing paddles **148**, **150**, the physician chooses the deployment cannula and distraction device sizes. The maximum outer dimension of the deployment cannula **82** used to deliver the distraction device **10** is preferably similar or slightly smaller in height than the minimum disc height measured. Accounting for the cannula wall thickness and any gap between the cannula **82** and the top-to-bottom height of the first and second elongated members **12** and **14**, the first and second elongated members **12** and **14** together are selected so as to be slightly less in height, top to bottom, than the minimum disc height.

When the appropriate deployment cannula **82** and distraction device **10** have been selected, a distal end **80** of the deployment cannula **82** is advanced through the access port

and into the disc space (FIG. 28). The deployment cannula 82 may be part of a delivery device 126 of the type illustrated in FIGS. 19 and 20 and described above or any other suitable delivery device. The first and second elongated members 12 and 14 are pre-loaded at a distal region of the deployment cannula 82 in a generally linear configuration for simultaneous insertion into the disc space. The augmenting elongated member 16 may be similarly pre-loaded in the deployment cannula 82 in a generally linear configuration, but positioned proximally of the first and second elongated members 12 and 14 for insertion after the first and second elongated members 12 and 14.

Because the first and second elongated members 12 and 14 together clear the minimum disc height, they can be pushed out of the deployment cannula 82 and into the disc space easily using the delivery device 126 or the like. For delivery, the physician begins to push in the first and second elongated members 12 and 14 simultaneously out of the cannula 82 little by little, for example by using a pusher or plunger or other suitable actuating means, such as a rotary actuator. Between pushes, the physician may check the curvature of the partially inserted first and second elongated members 12 and 14 (FIG. 29) using X-ray or other visualization techniques to observe the position of the elongated members via radiopaque portions thereof (such as radiopaque markers embedded within the elongated members). By tensioning the pull wire 74, as described above, the physician adjusts the curvature of the first and second elongated members 12 and 14 in real time to closely follow the inner wall of the disc annulus.

By the time the first and second elongated members 12 and 14 are entirely out of the cannula 82 and within the disc space, the distal or leading ends 28 and 24 of the first and second elongated members 12 and 14 may be adjacent to and/or in contact with the proximal ends 52 and 54 of the first and second elongated members 12 and 14. If not, additional tension may be applied to the pull wire 74 until the distal or leading end 28 and 24 of the first and second elongated members 12 and 14 are adjacent to and/or in contact with the proximal ends 52 and 54 of the first and second elongated member 12 and 14. As shown in FIG. 30, the fully inserted first and second elongated members 12 and 14 define a generally less linear or generally annular configuration prior to the augmenting elongated member 16 being inserted therebetween.

With the first and second elongated members 12 and 14 fully deployed from the cannula 82 and in the generally annular configuration of FIG. 30, they are held to the leading or distal end 80 of the cannula 82 by the tension in the pull wire 74 and/or the anchor wires 84. The physician then advances the augmenting elongated member 16 out of the cannula 82 (or, if the augmenting elongated member 16 is not pre-loaded in the cannula 82, the physician loads the augmenting elongated member 16 into the delivery system and then advances it out of the cannula 82). The augmenting elongated member 16 is received between the first and second elongated members 12 and 14 and follows the path or generally less linear shape defined by the first and second elongated members 12 and 14 until it has been at least partially (but most preferably fully) inserted therebetween. The locking features described above, if provided, may assist the augmenting elongated member 16 in following the path defined by the first and second elongated member 12 and 14, while also preventing the first and second elongated members 12 and 14 from disengaging with the augmenting elongated member 16. While inserting the augmenting elongated member 16, the physician should be careful to main-

tain the cannula 82 in place, as the location of the cannula 82 effects the placement of the first and second elongated members 12 and 14 and, hence, the resulting distraction device 10. The physician may check the alignment of all of the elongated members during insertion of the augmenting elongated member 16 using X-ray or other visualization techniques.

When first advanced out of the cannula 82, the augmenting elongated member 16 begins to wedge itself in between the first and second elongated members 12 and 14. Depending on the thickness (height) of the augmenting elongated member 16, some slack may need to be given at this point to the pull wire 74 and/or the anchor wires 84 to allow them to separate in a vertical direction (i.e., in a direction between the surfaces to be distracted or along the axis of the spine or the direction of distraction) to allow further advancement of the augmenting elongated member 16.

Once the physician confirms that the tip of the augmenting elongated member 16 is wedged securely and the raised ribs 48 and 50 and associated grooves 42 and 46 (if provided) of the three elongated members are engaged, the augmenting elongated member 16 is advanced slowly while checking for changes in the curvature of the distraction device 10. As before, the curvature can be adjusted in real time using the pull wire 74. In a preferred embodiment, the curvature may be adjusted automatically by developing tension in the pull wire 74 via a screw or rotational mechanism incorporated into or associated with the slider 128. The augmenting elongated member 16 is preferably pushed in all the way until its back face is flush with the back faces of the first and second elongated members 12 and 14 (FIG. 31), at which point the augmenting elongated member 16 may be fully locked in place with respect to the first and second elongated members 12 and 16.

The physician then makes a final check of the implant placement and desired distraction. If satisfied, the physician detaches the pull wire 74 and anchor wires 84 from the implant 10 (as described above) and may remove the cannula 82 and associated delivery device 126. Even with the pull wire 74 detached from the implant 10, the reaction force applied to the implant 10 by the tissues being distracted should be sufficient to maintain the implant 10 in the illustrated generally annular configuration.

As shown in FIG. 31, the augmenting elongated member 16 may have a linear extent that is less than the linear extents of the first and second elongated members 12 and 14 in the insertion or longitudinal direction (i.e., in a dimension extending between the proximal and distal ends of the elongated members). Thus, when the augmenting elongated member 16 has been fully inserted between the first and second elongated members 12 and 14 (such that their back faces are substantially flush), the augmenting elongated member 16 will define a generally less linear configuration that extends over a lesser arc than the generally complete circle defined by the first and second elongated members 12 and 14. In particular, the augmenting elongated member 16 defines a generally arcuate, non-annular configuration when fully inserted, such that a window 158 is defined between the proximal and distal ends 98 and 56 of the augmenting elongated member 16 (which define lateral sides of the window 158) and the distal ends 28 and 24 of the first and second elongated members 12 and 14 (which define lower and upper sides of the window 158, respectively).

The locking member 18, as described above, may separate from the lateral groove 106 in which it sits during (or after) insertion of the augmenting elongated member 16 to extend through the open interior or resident volume 108 defined by

the implant **10**. At this point, it may be advantageous for the locking member **18** to not be fully tensioned, otherwise it may obstruct the window **158**, as shown in FIG. **16**. As described above, the reaction forces applied to the fully expanded implant **10** by the opposing tissue surfaces should be sufficient to maintain the shape of the implant **10** even without shaping force being applied by the pull wire **74** or the locking member **18**. However, it may be preferred for some amount of tension to be applied to the locking member **18** to remove it from the resident volume **108** and position it in the window **158**, but with sufficient slackness that the locking member **18** does not extend across the middle of the window **158**. Instead, it may be preferred for the locking member **18** to hang slack within the window **158**, as shown in FIGS. **15** and **31**, to allow a funnel **152** (FIG. **32**) to extend through the window **158** and access the resident volume **108** without contacting the locking member **18**.

As shown in FIG. **32**, if bone graft material or bone filler material **156** is needed, it can be injected or otherwise introduced into the open interior or resident volume **108** defined by the implant **10** via the window **158** defined in the side wall of the implant **10**. In the illustrated embodiment, the distal end of a funnel **152** is inserted through the window **158** and then bone graft material or bone filler material **156** is advanced through the funnel **152** and into the resident volume **108** using a tamp **154** of the type shown in FIG. **27** or the like. FIG. **32** shows the resident volume **108** being substantially entirely filled with bone graft material or bone filler material **156**, but it is also within the scope of the present disclosure for the resident volume **108** to be only partially filled with bone graft material or bone filler material **108**. An advantage of implants according to the present disclosure is that, unlike most other expandable cages, bone graft material or bone filler material it meant to be placed through the window defined in the side wall of the implant and make full contact on the two tissue surfaces to be distracted. Some expandable cage-type implants include bone graft material within the cage as it is introduced into the disc space, and then expand the cage, which tends to leave voids between the bone graft material and the tissue surfaces to be distracted. Voids in bone graft are undesirable, as they may inhibit fusion or the rate of fusion between vertebral endplates.

When the desired amount of bone graft material or bone filler material **156** has been introduced into the resident volume **108**, the physician withdraws the funnel **152** and then applies a proximally directed force to the free end **96** of the locking member **18** (FIG. **33**). Tension is applied to the locking member **18** until it is taut or tightly drawn across the middle of the window **158** (FIG. **16**). Then, the fastener **114** of the augmenting elongated member **16** is advanced so as to sever the free end **96** of the locking member **18**, while securing the locking member **18** to the augmenting elongated member **16** at a second location, as described in greater detail above. The fastener **114** may be advanced by a driver device **160** (FIG. **33**) that pushes or rotates or otherwise actuates the fastener **114** so as to move it distally with respect to the augmenting elongated member **16** into contact with the locking member **18**.

The free end **96** of the locking member **18** being secured and severed, the severed portion may be removed from the disc space, along with the driver device **160**, leaving only the fully deployed implant **10** in the disc space, as shown in FIG. **2**. Thereafter, the access port may be closed, along with any other access points opened to reach the disc space.

It should be understood that the above-described elongated members, distraction device, deployment tools, and

methods are merely exemplary. For example, FIGS. **34** and **35** illustrate an alternative embodiment of an elongated member or distraction device **162** employing a different locking mechanism or member **164** (FIG. **35**). In the illustrated embodiment, the elongated member or distraction device **162** is moved from a generally linear configuration to a generally less linear configuration (e.g., as described above using a pull wire or the like) with the elongated member or distraction device **162** assuming an arcuate, but not closed loop or annular, shape. The gap **166** between the proximal and distal ends **168** and **170** of the elongated member or distraction device **162** may be used to introduce bone graft material or the like into the resident volume **172** defined by the elongated member or distraction device **162**. When the surgeon desires to close the gap **166**, the proximal and distal ends **168** and **170** are drawn together (e.g., using a closure tool **174** that engages the proximal and distal ends **168** and **170** to bring them toward each other) and a fastener or fixture **164** is secured to the ends **168** and **170** to prevent them from separating. In one embodiment, the fastener or fixture **164** comprises a staple with two prongs **176** and **178** that are received within cavities **180** and **182** of the proximal and distal ends **168** and **170** to close the gap **166** and maintain the elongated member or distraction device **162** in a generally annular configuration.

In other embodiments, a separate fastener or fixture is not required to maintain the elongated member or distraction device in a generally annular configuration. For example, FIG. **36** shows a distraction device **184** in which one of the constituent elongated members (shown as the augmenting elongated member **186**) includes an embedded wire or tube or elongated element **188** made of a material having shape memory properties, such as Nitinol or a shape memory polymer. The embedded element **188** preferably has a natural or pre-set shape, for example, the illustrated arcuate or annular configuration. When the augmenting elongated member **186** is present in a deployment cannula, it is constrained to a generally linear configuration, allowing for an easy and minimally invasive deployment of the elongated members into the work space. Because of the shape memory properties of the embedded element **188**, the augmenting elongated member **186** will return to its natural curved or annular shape once the constraint is removed (i.e., once the distal end of the augmenting elongated member **186** exits the distal end portion of the cannula and enters the work space). Rather than being embedded within the augmenting elongated member **186**, the shape memory material may instead be secured to an outer surface (e.g., a lateral side) of the augmenting elongated member **186**. In other embodiments, one or both of the upper and lower elongated members **190** and **191** includes shape memory properties in addition to (or instead of) the augmenting elongated member **186** having shape memory properties. By providing one or more of the elongated members with shape memory properties, the need to use a locking member or fastener or fixture to secure the resulting distraction device in its generally less linear, deployed configuration is avoided.

FIGS. **37** and **38** illustrate another embodiment of an elongated member or distraction device **192** that may maintain a generally less linear, deployed configuration without the need for a separate fixture or fastener or locking member. The illustrated elongated member or distraction device **192** includes an integrally formed locking projection or extension **194** at its distal end **196** and a similarly shaped cavity or pocket **198** along a lateral side **200** at or adjacent to its proximal end **202**. The cavity **198** is preferably associated with the lateral side **200** of the elongated member or

25

distraction device **192** toward which the elongated member or distraction device **192** curves when deployed in a work space. In the illustrated embodiment, the elongated member or distraction device **192** may be moved from a generally linear configuration to a generally less linear configuration (e.g., as described above using a pull wire or the like) with the elongated member or distraction device **192** assuming an arcuate, but not closed loop or annular, shape with a gap between the proximal and distal ends **202** and **196**. The gap between the proximal and distal ends **202** and **196** of the elongated member or distraction device **192** may be used to introduce bone graft material or the like into the resident volume **204** defined by the elongated member or distraction device **192**. When the surgeon desires to close the gap, the locking projection **194** is pressed into and retained by the cavity **198**, as shown in FIG. **38**. In the illustrated embodiment, the locking projection **194** is generally conical, which may promote retention of the projection **194** within the cavity **198**, but other locking projection configurations (e.g., an enlarged spherical shape) may also be employed without departing from the scope of the present disclosure.

It will be understood that the embodiments described above are illustrative of some of the applications of the principles of the present subject matter. Numerous modifications may be made by those skilled in the art without departing from the spirit and scope of the claimed subject matter, including those combinations of features that are individually disclosed or claimed herein. For these reasons, the scope hereof is not limited to the above description but is as set forth in the following claims, and it is understood that claims may be directed to the features hereof, including as combinations of features that are individually disclosed or claimed herein.

The invention claimed is:

1. A tissue distraction device comprising:

first and second elongated members, each elongated member defining a closed loop in a separate plane in a deployed configuration, *wherein the first elongated member comprises a first elongated member proximal end and a first elongated member distal end*; and an augmenting elongated member **[fully]** *comprising an augmenting elongated member proximal end and an augmenting elongated member distal end, wherein the augmenting elongated member is configured to be moved toward the first elongated member distal end to be fully received between the first and second elongated members in the deployed configuration and [having a length that is less than the length of each of the first and second elongated members] wherein the augmenting elongated member distal end stops short of the first elongated member distal end in the deployed configuration.*

2. The tissue distraction device of claim **1**, wherein the augmenting, first, and second elongated members cooperate to define a window into an interior of the tissue distraction device.

3. The tissue distraction device of claim **2**, wherein the window is configured to allow for the introduction of a bone filler material into the interior of the tissue distraction device through the window.

4. The tissue distraction device of claim **2**, further comprising a locking member secured to the augmenting elongated member at a plurality of locations to lock the augmenting elongated member in a generally arcuate configuration, wherein a portion of the locking member extends across the window.]

26

5. The tissue distraction device of claim **4**, further comprising a fastener, wherein the locking member extends between a fixed end and a free end,

the fixed end of the locking member is secured at or adjacent to a proximal end of the augmenting elongated member, and

the fastener secures the free end of the locking member to the augmenting elongated member at or adjacent to the proximal end of the augmenting elongated member.]

6. The tissue distraction device of claim **1**, wherein the first, second, and augmenting elongated members combine to define a structure having a non-uniform thickness configured to adjust the lordotic angle of **[the]** a spine.

7. The tissue distraction device of claim **1**, wherein

[each of the first and second elongated members extends between proximal and distal ends and includes a lateral side, and]

one **[of the ends]** *end* of the first elongated member **[contacts the]** *approaches* a lateral side of the first elongated member adjacent to the other end of the first elongated member, and

one **[of the ends]** *end* of the second elongated member **[contacts the]** *approaches* a lateral side of the second elongated member adjacent to the other end of the second elongated member.

8. The tissue distraction device of claim **1**, wherein each elongated member is generally rectangular in cross-sectional shape **[and defined by elongated upper and lower surfaces, proximal and distal ends, and elongated lateral side surfaces].**

9. The tissue distraction device of claim **[8]** *I*, wherein each of the elongated members includes

a longitudinally extending wall,

a plurality of **[similarly shaped]** first teeth extending laterally from the *longitudinally extending* wall in one direction, and

a plurality of **[similarly shaped]** second teeth extending laterally from the *longitudinally extending* wall in an opposite direction **[and differently configured from said first teeth].**

10. A tissue distraction device comprising:

first and second elongated members insertable between tissue layers and adapted to define a structure in situ having a **[dimensional aspect]** dimension in a direction extending between the tissue layers; and

an augmenting elongated member insertable between and in contact with said first and second elongated members to spread the first and second elongated members apart to increase the dimension of at least a portion of the structure in situ, wherein

[each elongated member is generally rectangular in cross-sectional shape and defined by elongated upper and lower surfaces, proximal and distal ends, and elongated lateral side surfaces,

each elongated member is] *the first and second elongated members are sufficiently flexible to change between a generally linear first configuration and a second configuration that is less linear than the first configuration, wherein the first elongated member comprises a first elongated member proximal end and a first elongated member distal end, and wherein*

the augmenting elongated member [has a length that is less than the length of each of the first and second elongated members] comprises an augmenting elongated member proximal end and an augmenting elongated member distal end, wherein the augmenting

27

elongated member is configured to be moved toward the first elongated member distal end to be received between the first and second elongated members in the deployed configuration and the augmenting elongated member distal end stops short of the first elongated member distal end in the deployed configuration.

11. The tissue distraction device of claim 10, wherein each of the elongated members includes

a longitudinally extending wall,

a plurality of [similarly shaped] first teeth extending laterally from the *longitudinally extending* wall in one direction, and

a plurality of [similarly shaped] second teeth extending laterally from the *longitudinally extending* wall in an opposite direction [and differently configured from said first teeth].

12. The tissue distraction device of claim 10, wherein [the proximal end of each of the first and second elongated members is ramped, and]

the [distal end of the augmenting elongated member] *augmenting elongated member distal end* is tapered to engage and separate the first and second elongated members when the augmenting elongated member is inserted therebetween.

13. The tissue distraction device of claim 10, wherein the augmenting elongated member is configured to cooperate with said first and second elongated members to define a window into an interior of the tissue distraction device when the augmenting elongated member is inserted between and in contact with said first and second elongated members and the elongated members are in the second configuration.

[14. The tissue distraction device of claim 13, further comprising a locking member configured to be secured to the augmenting elongated member at a plurality of locations to lock the augmenting elongated member in the second configuration in which a portion of the locking member extends across the window.]

[15. The tissue distraction device of claim 14, further comprising a fastener, wherein

the locking member extends between a fixed end and a free end,

the fixed end of the locking member is secured at or adjacent to a proximal end of the augmenting elongated member, and

the fastener is configured to secure the free end of the locking member to the augmenting elongated member at or adjacent to the proximal end of the augmenting elongated member when the augmenting elongated member is in the second configuration.]

16. The tissue distraction device of claim 10, wherein the first, second, and augmenting elongated members are configured to combine to define a structure having a non-uniform thickness configured to adjust the lordotic angle of [the] a spine.

17. The tissue distraction device of claim 10, wherein one [of the ends] *end* of the first elongated member is configured to [contact one of the lateral sides] *approach a lateral side* of the first elongated member adjacent to the other end of the first elongated member when the first elongated member is in the second configuration, and

one [of the ends] *end* of the second elongated member is configured to [contact one of the lateral sides] *approach a lateral side* of the second elongated member adjacent to the other end of the second elongated member when the second elongated member is in the second configuration.

28

18. The tissue distraction device of claim 10, wherein each of the first and second elongated members is configured to define [a closed loop] *an annular shape* in the second configuration.

19. The tissue distraction device of claim 18, wherein the augmenting elongated member is configured to define a generally arcuate configuration in the second configuration.

20. The tissue distraction device of claim 10, wherein each of the first and second elongated members is configured to define [a closed loop] *an annular shape* in the second configuration,

the augmenting elongated member is configured to cooperate with said first and second elongated members to define a window into an interior of the tissue distraction device in the second configuration, and

the window is configured to allow for the introduction of a bone filler material into the interior of the tissue distraction device in the second configuration through the window.

21. *A tissue distraction device comprising:*

first and second elongated members insertable between tissue layers and adapted to define a structure in situ having a dimension in a direction extending between the tissue layers, wherein the first elongated member comprises a first elongated member proximal end and a first elongated member distal end; and

an augmenting elongated member comprising an augmenting elongated member proximal end and an augmenting elongated member distal end, wherein the augmenting elongated member is insertable between and in contact with said first and second elongated members to spread the first and second elongated members apart to increase the dimension of at least a portion of the structure in situ in a deployed configuration, wherein the augmenting elongated member is configured to be moved toward the first elongated member distal end to be received between the first and second elongated members in the deployed configuration and the augmenting elongated member distal end stops short of the first elongated member distal end in the deployed configuration.

22. *The tissue distraction device of claim 21, wherein the augmenting, first, and second elongated members cooperate to define a window.*

23. *The tissue distraction device of claim 22, wherein the window is configured to allow for the introduction of a bone filler material through the window.*

24. *The tissue distraction device of claim 21, wherein the first, second, and augmenting elongated members combine to define a structure having a non-uniform thickness configured to adjust the lordotic angle of a spine.*

25. *The tissue distraction device of claim 21, wherein one end of the first elongated member approaches a lateral side of the first elongated member adjacent to the other end of the first elongated member, and one end of the second elongated member approaches a lateral side of the second elongated member adjacent to the other end of the second elongated member.*

26. *The tissue distraction device of claim 21, wherein each elongated member is generally rectangular in cross-sectional shape.*

27. *The tissue distraction device of claim 21, wherein each of the elongated members includes*

a longitudinally extending wall,

a plurality of first teeth extending laterally from the longitudinally extending wall in one direction, and

29

a plurality of second teeth extending laterally from the longitudinally extending wall in an opposite direction.

28. The tissue distraction device of claim 1, wherein the augmenting, first, and second elongated members cooperate to define a window which is adjacent to the augmenting elongated member distal end.

29. The tissue distraction device of claim 10, wherein the augmenting, first, and second elongated members cooperate to define a window which is adjacent to the augmenting elongated member distal end.

30. The tissue distraction device of claim 21, wherein the augmenting, first, and second elongated members cooperate to define a window which is adjacent to the augmenting elongated member distal end.

31. The tissue distraction device of claim 1, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the augmenting elongated member distal end defines a lateral side of the window.

32. The tissue distraction device of claim 10, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the augmenting elongated member distal end defines a lateral side of the window.

33. The tissue distraction device of claim 21, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the augmenting elongated member distal end defines a lateral side of the window.

34. The tissue distraction device of claim 1, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the first and second elongated members define lower and upper sides of the window.

30

35. The tissue distraction device of claim 10, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the first and second elongated members define lower and upper sides of the window.

5 36. The tissue distraction device of claim 21, wherein the augmenting, first, and second elongated members cooperate to define a window, wherein the first and second elongated members define lower and upper sides of the window.

10 37. The tissue distraction device of claim 1, wherein a window is defined between the augmenting elongated member proximal end and the augmenting elongated member distal end, which define lateral sides of the window, and the first elongated member distal end and the second elongated member distal end, which define lower and upper sides of the window.

15 38. The tissue distraction device of claim 10, wherein a window is defined between the augmenting elongated member proximal end and the augmenting elongated member distal end, which define lateral sides of the window, and the first elongated member distal end and the second elongated member distal end, which define lower and upper sides of the window.

20 39. The tissue distraction device of claim 21, wherein a window is defined between the augmenting elongated member proximal end and the augmenting elongated member distal end, which define lateral sides of the window, and the first elongated member distal end and the second elongated member distal end, which define lower and upper sides of the window.

* * * * *