




(12) **DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION**

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2017/05/23  
 (87) Date publication PCT/PCT Publication Date: 2018/02/01  
 (85) Entrée phase nationale/National Entry: 2019/01/18  
 (86) N° demande PCT/PCT Application No.: JP 2017/019251  
 (87) N° publication PCT/PCT Publication No.: 2018/020800  
 (30) Priorité/Priority: 2016/07/28 (JP2016-148728)

(51) Cl.Int./Int.Cl. *B65D 47/20* (2006.01)  
 (71) Demandeur/Applicant:  
 YOSHINO KOGYOSHO CO., LTD., JP  
 (72) Inventeur/Inventor:  
 MAEDA, SHINYA, JP  
 (74) Agent: FASKEN MARTINEAU DUMOULIN LLP

(54) Titre : RECIPIENT DE DISTRIBUTION  
 (54) Title: DISCHARGE CONTAINER



(57) **Abrégé/Abstract:**

A dispensing container provided with: a double-layered container body (2) with an inner layer (21) forming a content-holding space (S), and an outer layer (22) surrounding the inner layer (21); a dispensing cap (3) that has a dispensing port (33a) and is fitted on the mouth (22a) of the double-layered container body (2); and a check valve structure that is disposed on the inside of the dispensing cap (3) and allows flow of contents from the holding space (S) to the dispensing port (33a) while inhibiting reverse flow from the dispensing port (33a) to the holding space (S). The check valve structure has a cylindrical partitioning wall (43) that partitions and forms a flow channel for the contents, and a valve body (45) with a single-swing structure that is provided on the partitioning wall (43) via a hinge part (44). The space on the inside of the partitioning wall (43) on the dispensing port (33a)-side of the valve body (45) forms a liquid-storing space (L) in which some of the contents remaining after dispensing of the contents is stored.

## ABSTRACT

A discharge container includes: a double-walled container body (2) including an inner layer body (21) and an outer layer body (22); a discharge cap (3) having a discharge outlet (33a), the discharge cap (3) being attached to a mouth (22a) of the double-walled container body (2); and a check valve structure. The check valve structure has a tubular partition wall (43) defining a flow path of the content and a valve body (45) which is provided on the partition wall (43) with a hinge portion (44) and has a single swing structure, and space inside the partition wall (43) rather on the discharge outlet (33a) side than on the valve body (45) side serves as a liquid reservoir space (L) where part of remaining content is stored after the discharge of the content.

## DISCHARGE CONTAINER

### TECHNICAL FIELD

The present disclosure relates to a discharge container that contains a  
5 content in a double-walled container body having an inner layer and  
discharges the content from a discharge outlet of a discharge cap attached to a  
mouth, and in particular relates for example to a discharge container  
containing a relatively highly viscous content containing some solid content,  
such as sauce or miso.

10

### BACKGROUND

Conventionally, a discharge container is known, which is configured  
such that a discharge cap is attached to a mouth of a container body containing  
a content and the content contained in the container body can be discharged  
15 from a discharge outlet of the discharge cap by pushing (squeezing) a trunk of  
the container body.

Further, as such a discharge container, one configured such that a  
valve body is provided inside a discharge cap to allow a flow of a content  
from a container body toward a discharge outlet while preventing backflow of  
20 the content from the discharge outlet toward the container body and  
preventing a flow of ambient air from the discharge outlet side into the  
container body.

For example, JP 2014-105016 A (PTL 1) describes a container in  
which a container body includes an outer layer body (outer container) and an  
25 inner layer body (inner container) that is deformable in a volume-reducing  
manner and is held inside the outer layer body, and a check valve (valve body)  
having a three-point support structure that opens and closes a flow path of the  
content is provided inside the discharge cap (dispensing plug).

Using a discharge container having such a structure, when a content  
30 is discharged by squeezing the trunk of the container (squeezing) and then the  
squeeze on the trunk is released, while the check valve prevents the content or  
the ambient air from being flown from the discharge outlet into the container

body, the original shape of the outer layer body can be recovered with the inner layer body being deformed in a volume-reducing manner by introducing the ambient air into the space between the outer layer body and the inner layer body from the intake hole provided in the discharge cap. With such a structure, the content can be discharged without being replaced with the ambient air. Accordingly, the content left inside the container body is hardly exposed to the air, which can retard spoilage and deterioration of the content.

#### CITATION LIST

10 Patent Literature

PTL 1: JP 2014-105016 A

#### SUMMARY

##### **Technical Problem**

15 Here, the discharge container as described above is often used in applications of containing a liquid content such as soy sauce or cosmetics; however, there is also a demand for discharge containers which can be used in applications of containing a relatively highly viscous content containing some solid content, such as sauce or miso.

20 However, when the discharge container as described above is used, the solid content contained in the content would be caught in a clearance of the check valve, thus the check valve would not close, the ambient air would enter the containment space through the open check valve, and so the content would be spoiled or deteriorated. Further, in the case of a highly viscous content, the check valve having a three-point support structure (three-piece valve structure) as described above hardly opens and would require excessive force for squeezing.

25 It could therefore be helpful to provide a discharge container of which check valve structure normally works so that spoilage and deterioration of the content due to the entry of ambient air into the containment space can be retarded even when the container contains a relatively highly viscous content containing some solid content.



### **Solution to Problem**

The present disclosure is to solve the above problem, and a discharge container of the present disclosure includes: a double-walled container body including an inner layer body which defines a containment space for a content and is deformable in a volume-reducing manner and an outer layer body surrounding the inner layer body; a discharge cap having a discharge outlet through which the content is discharged, the discharge cap being attached to a mouth of the double-walled container body; and a check valve structure which is disposed inside the discharge cap and allows a flow of the content from the containment space toward the discharge outlet and prevents backflow from the discharge outlet toward the containment space. The check valve structure has a tubular partition wall defining a flow path of the content from the containment space toward the discharge outlet and a valve body which is provided on the partition wall with a hinge portion and has a single swing (half-swing) structure swung on the hinge portion, and space inside the partition wall rather on the discharge outlet side than on the valve body side serves as a liquid reservoir space where part of remaining content is stored after the discharge of the content.

Further, the discharge container of the present disclosure preferably includes a valve member having the partition wall and the valve body, and a valve retaining member retaining the valve member inside the discharge cap.

For the discharge container of the present disclosure, the viscosity of the content is preferably 100 mPa·s or more.

Further, for the discharge container of the present disclosure, the diameter of a piece of solid content contained in the content is preferably less than 1.5 mm.

### **Advantageous Effect**

The present disclosure provides a discharge container of which check valve structure normally works so that spoilage and deterioration of the content due to the entry of the ambient air into the containment space can be retarded even when the container contains a relatively highly viscous content containing some solid content.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawing, FIG 1 is a side view of a discharge container of one embodiment of the present disclosure.

5

## DETAILED DESCRIPTION

One embodiment of the present disclosure will now be described with reference to the drawing. As depicted in FIG. 1, a discharge container 1 of this embodiment includes a double-walled container body 2, a discharge cap 3 attached to the double-walled container body 2, a valve member 4, and a valve retaining member 5. Note that in the description, the claims, the abstract, and the drawing, the side where a cap body 37 to be described is situated is the upper side (upper side in FIG. 1), and the side where the double-walled container body 2 is situated is the lower side (lower side in FIG. 1).

15 The double-walled container body 2 includes an inner layer body 21 and an outer layer body 22. The double-walled container body 2 in this embodiment can be formed by biaxial stretch blow molding of a preform shaped like a test tube, in which a synthetic resin material of the inner layer body 21 and a synthetic resin material of the outer layer body 22 are stacked. However, the method of forming the double-walled container body is not limited to this. For example, the double-walled container body 2 may be formed by extrusion blow molding a cylindrical multi-layer parison formed by stacking a synthetic resin material of the inner layer body 21 and a synthetic resin material of the outer layer body 22. In addition, the double-walled container body 2 is not necessarily a delamination container, and may be formed by assembling the outer layer body 22 and the inner layer body 21 which have been separately formed.

As a material of the inner layer body 21 included in the double-walled container body 2, ethylene vinyl alcohol copolymer (EVOH) or nylon is used. Further, as a material of the outer layer body 22, low density polyethylene (LDPE) or high density polyethylene resin (HDPE) is used. In particular, when LDPE is used, high squeezability of the container can be

30

obtained. However, without limitation to this aspect, for example, when a delamination container is formed by biaxial stretch blow molding, the inner layer body 21 may use polypropylene (PP) as a material, and the outer layer body 22 may use polyethylene terephthalate (PET) as a material. Further, as materials of the inner layer body 21 and the outer layer body 22, other resins having low compatibility with each other can be used.

The inner layer body 21 is formed to be deformable in a volume-reducing manner, and in this embodiment, the inner layer body 21 can be obtained by being delaminated from the outer layer body 22 of the double-walled container body 2 formed in a stacked manner. The inner layer body 21 defines a containment space S where a content is contained inside. Note that between the inner layer body 21 and the outer layer body 22, an adhesive strip can be provided which extends vertically and partially bonds the inner layer body 21 and the outer layer body 22.

The outer layer body 22 may have a bottle shape having a cylindrical mouth 22a, a restorable flexible trunk 22b, and a bottom that stops the lower end of a trunk 22b. A region ranging from the mouth 22a to the trunk 22b may be provided with a sealing step portion 22c having a larger diameter than an upper end portion of the mouth 22a.

Further, as depicted in FIG. 1, an outer circumferential surface of the mouth 22a is provided with a male threaded portion 22d. Further, the mouth 22a is provided with a through hole 22e for taking air to and from the space between the outer layer body 22 and the inner layer body 21 and the outer layer body 22, and the outer circumferential surface of the mouth 22a is provided with a groove portion 22f which forms a vertical cutout in the male threaded portion 22d.

In this embodiment, the groove portion 22f forming a vertical cutout in the male threaded portion 22d is adapted to be used as a ventilation path; however, the present disclosure is not limited to this aspect. Instead of providing the groove portion 22f, a clearance between the male threaded portion 22d and a female threaded portion 31a may be used as a ventilation path.

The discharge cap 3 includes an outer circumferential wall 31 surrounding the mouth 22a, and the female threaded portion 31a corresponding to the male threaded portion 22d of the mouth 22a is formed on an inner circumferential surface of the outer circumferential wall 31. Further, a top wall 32 is integrally connected to the upper end of the outer circumferential wall 31. Further, the top wall 32 is provided with a discharge tube 33 for a content, which tube forms a discharge outlet 33a. A lower surface of the top wall 32 is provided with a ring-shaped upper fitting groove 34. Moreover, an ambient air introduction hole 35 extending through the top wall 32 is provided on the radially outside of the upper fitting groove 34. Note that a lower part of the outer circumferential wall 31 abuts the entire circumference of the sealing step portion 22c in an airtight manner.

The discharge cap 3 has the cap body 37 provided to be openable and closable using the hinge 36. The cap body 37 is formed like a closed-topped tube having a diameter similar to the diameter of the discharge cap 3, and the cap body 37 is connected to the outer circumferential wall 31 using the hinge 36 so as to cover the discharge tube 33. A ceiling wall 37a of the cap body 37 is provided with a tubular sealing wall 38 extending downward, and when the cap body 37 is closed, the sealing wall 38 fits to the outside of the discharge tube 33 to close the discharge outlet 33a. A lug portion 39 is provided on the cap body 37 on the side opposite to the hinge 36 so as to be caught by a finger for an opening operation on the cap body 37. Note that in this example, the discharge tube 33 is provided in a position deviated from the center of the top wall 32 to the opposite side of the hinge 36; however, the position is not limited to this, and the discharge tube 33 can be provided at a central position of the top wall 32.

The valve member 4 is retained in the discharge cap 3 using the valve retaining member 5 installed inside the discharge cap 3. Here, the valve retaining member 5 is made of a synthetic resin and includes a partition wall portion 51 placed to cover the upper opening of the inner layer body 21, and an outer tube portion 52 standing from the outer periphery of the partition wall portion 51. A tubular retainer tube 53 is provided on the partition wall portion 51, and an end portion of the retainer tube 53 is provided with a ring



wall 54 shaped like a flange inclined radially inside. An opening 54a serving as a flow path of a content is formed in the ring wall 54. The ring wall 54 serves as a valve seat portion for the valve body 45 to be described, and the outer peripheral portion of the valve body 45 abuts the entire circumference of the upper surface of the ring wall 54, thus the opening 54a is closed. A vent hole 55 serving as an air flow path is formed in an outer peripheral portion of the partition wall portion 51. A ring-shaped lower fitting groove 56 is provided on the upper surface of the partition wall portion 51.

The valve member 4 is formed from a soft material such as for example rubber or elastomer, and is elastically deformable. In this example, the valve member 4 is formed from low density polyethylene (LDPE). The valve member 4 includes a cylindrical base portion 41, a ring-shaped flange portion 42 provided inside the base portion 41, a cylindrical partition wall 43 hanging down from the inner periphery of the flange portion 42, and the valve body 45 which is provided on the partition wall 43 with a hinge portion 44 and has a single swing structure swung on the hinge portion 44. The partition wall 43 is placed inside the retainer tube 53, and defines a flow path of content from the containment space S to the discharge outlet 33a. Further, space inside the partition wall 43, rather on the discharge outlet 33a side than on the valve body 45 side serves as a liquid reservoir space L where part of remaining content is stored after the discharge of the content. Thus, the partition wall 43, the valve body 45, and the ring wall 54 serving as a valve seat portion form a check valve structure which allows a flow of the content from the containment space S toward the discharge outlet 33a and prevents backflow from the discharge outlet 33a toward the containment space S.

In this example, as depicted in FIG. 1, the valve body 45 is formed like a disk having larger diameter than the opening 54a of the ring wall 54 serving as a valve seat portion, and the valve body 45 is integrally connected to an inner circumferential surface of the partition wall 43 using the hinge portion 44 constituted by a single coupling piece. The valve body 45 swings up and down on the hinge portion 44 by being supported on the partition wall 43 at one point by the hinge portion 44. Thus, the valve body 45 has a so-called single-point swing structure; however, the present disclosure is not

limited to this. For example, another single swing structure may be used in which the hinge portion 44 is constituted by two or more coupling pieces connecting the partition wall 43 and the valve body 45, and the valve body 45 swings on the plurality of coupling pieces.

5 As depicted in FIG. 1, a lower surface of the valve body 45 abuts the entire circumference of the upper surface of the ring wall 54 in a normal state (closed state), so that the opening 54a is closed, and the ambient air etc. is prevented from flowing from the discharge outlet 33a side into the  
10 containment space S. On the other hand, when the trunk 12 is squeezed and the containment space S is pressurized, as indicated by a dash dot dot line in FIG. 1, the valve body 45 swings on the hinge portion 44 so as to move upward away from the upper surface of the ring wall 54, thus the valve body 45 opens the opening 54a. Accordingly, the valve body 45 is swingable  
15 between a closed position where the opening 54a is closed and an open position where the opening 54a is opened.

Note that an outer circumferential surface of the base portion 41 is integrally provided with an ambient air introduction valve 46 which is in resilient contact with the lower surface of the top wall 32 to close the ambient  
20 air introduction hole 35 in a normal state, and moves away from the lower surface of the top wall 32 to communicate the ambient air introduction hole 35 to the through hole 22e when the pressure between the outer layer body 13 and the inner layer body 14 is low. In the illustrated example, the ambient air  
25 introduction valve 46 is formed to have a thin ring shape from the same material as the partition wall 43, and is adapted to be in resilient contact with the lower surface of the top wall 32 on its outer periphery.

Further, a hemispherical projection 47 is integrally provided on the center of an upper surface of the valve body 45, and the projection 47 allows the outer peripheral portion of the valve body 45 to abut the ring wall 54 serving as a valve seat portion while ensuring a certain rigidity.

30 When a content is discharged using the discharge container 1, the cap body 37 is opened and the discharge container 1 is brought into an inverted position, and the trunk 22b is then squeezed. The content in the containment

space S pressurized by squeezing the trunk 22b pushes open the valve 45 and passes through the opening 54a and the liquid reservoir space L inside the partition wall 43, and is discharged from the discharge outlet 33a through the discharge tube 33. In this manner, the content contained in the containment  
5 space S can be discharged. After the content is discharged, when the squeeze is released, the valve body 45 returns to the original position, and the valve body 45 abuts the upper surface of the ring wall 54 serving as a valve seat portion to close the opening 54a. At this point of time, part of the content left without being discharged is stored in the liquid reservoir space L, thus a  
10 liquid seal is formed. Further, even in the case where solid content contained in the content is caught between the valve body 45 and the ring wall 54, and the opening 54a cannot be completely closed, the content remains in the liquid reservoir space L due to the surface tension or the viscosity of the content; the content covers the inside of the partition wall, so that the content  
15 serves as a sealant to cover the inside of the partition wall 43 above the valve body 45. Therefore, the ambient air from the discharge outlet 33a does not enter the containment space S through the liquid reservoir space L. Note that the present disclosure can be used in applications of containing contents containing some solid content, including, for example, sauces such as pasta  
20 sauce, pizza sauce, and pork cutlet sauce; ketchup; mayonnaise; and chunky liquid seasonings such as dressing and liquid miso. In particular, when a relatively highly viscous content is contained, more reliable liquid sealing can be achieved, which is a significant effect.

More specifically, the viscosity of the content is preferably 100  
25 mPa·s or more. The viscosity of the content was measured using a Brookfield viscometer manufactured by TOKYO KEIKI INC. (using a No. 2 rotor, rotation speed: 60 rpm, after 20 s, room temperature) under conditions where solid content was dispersed in the content.

Further, a piece of solid content contained in the content is preferably  
30 less than 1.5 mm in diameter. Thus, the content easily stays in the liquid reservoir space L even when solid content is caught between the valve body 45 and the ring wall 54 and the opening 54a is not completely closed, which ensures that liquid sealing can be formed more reliably. Accordingly, the



functionality of the check valve structure can be prevented from being reduced for a long period of time. From a similar point of view, a piece of solid content contained in the content is more preferably 1 mm or less in diameter.

5           Note that in this embodiment, the valve body 45 which had a single swing structure and was provided on the partition wall 43 with the hinge portion 44 was used as the check valve structure. The valve body 45 having a single swing structure opens wider than three-point support valve structure, so that even when the viscosity of the content is relatively high, excessive  
10           force is not required for squeezing and the content can easily be discharged.

          The technical scope of the present disclosure is not limited to the above embodiment, and various modifications can be made without departing from the spirit of the present disclosure. For example, in the above  
15           embodiment, the valve body 45 and the partition wall 43 are integrally formed from the same material; however, without limitation to this, a valve body formed as a separate body can be swingably assembled with the partition wall  
43.

          Further, in the above embodiment, the discharge cap 3 is threadedly engaged with the mouth 22a of the double-walled container body 2; however,  
20           without limitation to this, for example, engagement portions allowing for mutual undercut engagement may be provided and may be engaged by capping etc. Moreover, in the above embodiment, the cap body 37 opens and closes around the hinge 36; however, without limitation to this, the cap body 37 may be threadedly engaged with the discharge cap 3 by screw engagement.

25           Further in the foregoing embodiment, the ambient air introduction hole 35 is provided on the top wall 32 of the discharge cap 3, and the ambient air introduction hole 35 is opened and closed using the ambient air introduction valve 46 projecting from the base portion 41 of the base valve member 4; and the vent hole 55 serving as an air flow path is formed in an  
30           outer peripheral portion of the valve retaining member 5. However, this disclosure is not limited to this aspect. For example, instead of providing the ambient air introduction valve 46, the air flow path from the ambient air



introduction hole 35 to the through hole 22e may be partly narrowed to make the air between the outer layer body 22 and the inner layer body 21 difficult from leaking out. This structure can achieve both appropriate content discharge functions in squeezing and ambient air admission functions in releasing the squeeze. Alternatively, a hole for introducing ambient air may be formed in the trunk 22b or the bottom of the double-walled container body 2 and a valve body that opens and closes the hole may be provided to achieve another structure in which ambient air is introduced into the space between the outer layer body 22 and the inner layer body 21. Further, when a pinched-off portion is formed in the bottom of the double-walled container body 2, ambient air may be introduced into the space between the outer layer body 22 and the inner layer body 21 for example through a slit provided in the pinched-off portion.

#### 15 REFERENCE SIGNS LIST

	1	Discharge container
	2	Double-walled container body
	3	Discharge cap
	4	Valve member
20	5	Valve retaining member
	21	Inner layer body
	22	Outer layer body
	22a	Mouth
	22b	Trunk
25	22c	Sealing step portion
	22d	Male threaded portion
	22e	Through hole
	22f	Groove portion
	31	Outer circumferential wall
30	31a	Female threaded portion
	32	Top wall
	33	Discharge tube
	33	Discharge outlet

	34	Upper fitting groove
	35	Ambient air introduction hole
	36	Hinge
	37	Cap body
5	37a	Ceiling wall
	38	Sealing wall
	39	Lug portion
	41	Base portion
	42	Flange portion
10	43	Partition wall
	44	Hinge portion
	45	Valve body
	46	Ambient air introduction valve
	47	Projection
15	51	Partition wall portion
	52	Outer tube portion
	53	Retainer tube
	54	Ring wall
	54a	Opening
20	55	Vent hole
	56	Lower fitting groove
	L	Liquid reservoir space
	S	Containment space

## CLAIMS

1. A discharge container comprising:
  - a double-walled container body including an inner layer body which defines a containment space for a content and is deformable in a volume-reducing manner and an outer layer body surrounding the inner layer body;
  - a discharge cap having a discharge outlet through which the content is discharged, the discharge cap being attached to a mouth of the double-walled container body; and
  - a check valve structure which is disposed inside the discharge cap and allows a flow of the content from the containment space toward the discharge outlet and prevents backflow from the discharge outlet toward the containment space,
  - wherein the check valve structure has a tubular partition wall defining a flow path of the content from the containment space toward the discharge outlet and a valve body which is provided on the partition wall with a hinge portion and has a single swing structure swung on the hinge portion, and
  - space inside the partition wall rather on the discharge outlet side than on the valve body side serves as a liquid reservoir space where part of remaining content is stored after the discharge of the content.
2. The discharge container according to claim 1, further comprising a valve member having the partition wall and the valve body, and a valve retaining member retaining the valve member inside the discharge cap.
3. The discharge container according to claim 1 or 2, wherein a viscosity of the content is 100 mPa·s or more.
4. The discharge container according to any one of claims 1 to 3, wherein a diameter of a piece of solid content contained in the content is less than 1.5 mm.

FIG. 1

