

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 July 2006 (13.07.2006)

PCT

(10) International Publication Number
WO 2006/073403 A1

(51) International Patent Classification:
B65D 75/58 (2006.01)

(21) International Application Number:
PCT/US2005/000453

(22) International Filing Date: 7 January 2005 (07.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OKLAHOMA PACKAGING, LLC** [US/US]; 27567 East 191 Street, South Haskell, Oklahoma 74336 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WILKES, Kenneth, R.** [US/US]; 825C Merrimon Avenue, Asheville, NC 28804 (US).

(74) Agents: **BLAKELY, Roger, W.** et al.; Blakely, Sokoloff, Taylor & Zafman, 12400 Wilshire Blvd., 7th Floor, Los Angeles, CA 90025-1026 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TRIANGULARLY SHAPED FLEXIBLE BOTTLE WITH FITMENT, AND METHOD OF FABRICATION



(57) Abstract: A triangularly shaped flexible bottle having a gusseted body section, and a neck section (27) comprised of narrowed portions of the side panels (21, 23) and gusset (22) of the body section, with a fitment (28) in the neck section. The bottle has a flat bottom (25) that may be created by tapering the webs forming the bottom at about 30 degrees. The body has a triangular cross section when filled, but may be contoured in the vertical direction. A process for fabricating the bottle is also disclosed which involves feeding webs, including a side gusset, creating perimeter seals around only the top portion of the bottle, inserting the fitment from the input end of the machine in the direction of web travel, forming the remainder of the perimeter seams, detaching the nascent bottle from the web, and sealing the neck section of the bottle to the fitment by clamping the neck section with a heated clamp, and preferably repeating the seal operation at a different radial angle. Sealing the fitment by application of ultrasonic energy is also disclosed.

WO 2006/073403 A1

TRIANGULARLY SHAPED FLEXIBLE BOTTLE
WITH FITMENT, AND METHOD OF FABRICATIONBACKGROUND OF THE INVENTION

"Stand-up" plastic pouches or bottles for holding liquids
5 and other pourable products are becoming more popular, in part
because of the desire to minimize solid waste, in part because of
cost, and in part for other reasons. An early stand-up pouch
design (US Patent 3,380,646) was devised by the Doyen Brothers in
France. That pouch design, including many variants, is still in
10 use today. It is, in fact, the dominant style. The basic Doyen
design consists of two flat sheets seamed together along their
sides, with a "W" fold running along the bottom. When the pouch
is filled, the "W" opens and provides a base on which the pouch
can stand. The original Doyen design showed the top being sealed
15 straight across, but subsequent modifications include fitments to
allow the pouch to be reclosed after opening.

One difficulty in adding a fitment to a Doyen pouch (and to
many other pouch designs as well) is that, according to prior art
fitment sealing methods, the fitment must be of the "canoe" style
20 to create a joint that can be reliably sealed. The canoe type of
fitment is an attempt to minimize the change in direction of
pouch material as it comes into contact with the fitment, and in
so doing, improve the integrity of the joint where the two sides
of the pouch come together at the fitment. However, even the use
25 of a canoe shaped fitment does not completely solve the
difficulties in sealing a fitment into a pouch, and a more

reliable sealing means is desirable. The present invention, in one of its aspects, provides such a means.

A "canoe" style fitment is characterized by having a sealing surface that includes relatively sharp changes in direction
5 around the sealing periphery so as to permit the pieces of material being sealed to the fitment to approach the fitment sealing surface (laterally) at relatively shallow angles. Or, put another way, as two webs separate to go around the fitment in opposite directions, the angle of divergence is relatively small.
10 Canoe style fitments are illustrated in, e.g., US Patent No. 5,660,477, US Patent No. 4,415,085, and US Patent No. 4,732,299.

There are at least two other shortcomings of Doyen style pouches with fitments, as compared with the present invention. One is that, because the Doyen body tapers from the bottom to the
15 top, and the present invention has a body that approximates a rectangular parallelepiped, for a given volume contained, the bottle of the present invention requires substantially less material to fabricate. Since material cost is a large part of the cost of flexible packaging, this is a significant factor.
20 Another shortcoming of the Doyen style (and other ungusseted styles), compared to the present invention is that, because the upper body is fabricated from two flat sheets, when the pouch is partly full, the weight of the fitment tends to cause the top of the pouch to fold over, rather than stand erect.

25 Gusseted bottles (but without fitment) have been made in the past (see US Patents 6,193,416, Kawamata et al., 6,126,315,

Ichikawa et al., and 5,918,984, LaFleur et al.) Obviously, without a fitment, these prior art containers do not have the utility of the present invention.

US Patent No. 5,660,477, Ichikawa, discloses a gusseted
5 pouch with a fitment. The fitment shown has flanges protruding
from the central section; these create even more sealing problems
than a conventional canoe style fitment. Additionally, because
of the way the top of the pouch is configured, i.e., the gussets
are closed at the top, the fitment weight tends to cause this
10 pouch to fold over when partly full, in a manner very much like a
Doyen pouch with fitment.

SUMMARY OF THE INVENTION

The invented bottle which could, but preferably does not, utilize canoe style fitments is fabricated from flexible films (i.e., thin plastic, foil, paper, or the like) fed as webs from rolls of material. The bottle includes a gusseted body section that opens so as to form a triangular cross section. The gusset is terminated at the bottom of the bottle to form a substantially flat base, providing stability when the bottle is partially or wholly filled. The top portion of the bottle includes a fitment passing through a necked down portion of the bottle. The fitment is preferably sealed to the neck in two or more sealing operations carried out at different radial angles, preferably, but not necessarily, 90°, thus assuring an adequate seal between the fitment and the bottle neck around the entire periphery of the fitment.

For purposes of clarity, as pictured herein the fitment is illustrated without a closure. It will be appreciated that threaded, snap, and/or other types of closures are contemplated even though none is shown in the figures.

As opposed to requiring the use of canoe style fitments, as mentioned in the Background section of this Specification, the present invention permits, and preferably utilizes, "cylindrical base" fitments. The sealing surface (or "base") of a cylindrical base style fitment (as that term is used in the present application) is preferably (but not necessarily) substantially

parallel to the axis of the fitment, as in the canoe style, but does not include external corners at sharply acute angles around its circumference, as do canoe style fitments. Rather, the circumference is preferably comprised of smooth and preferably
5 convex curves. Having the circumference comprised of smooth curves is intended to facilitate the sealing of web material to the base of the fitment with two overlapping sealing steps applied from different directions. The cross sectional shape of the sealing area of a cylindrical base fitment is preferably
10 circular, but may be oval, or have some other curved shape. While the word "cylindrical" is used herein to help define a "non-canoe" style of fitment, it should be understood that the fitment may be tapered somewhat (axially) to facilitate insertion or for other reasons.

15 Alternatively, instead of the sealing surface area of a cylindrical base fitment being comprised of smooth curves, the sealing surface of a cylindrical base fitment (as that term is used in this specification) may include intersections at an angle, provided that the angle is not so acute as to make a
20 second sealing step difficult or impractical. Intersection angles that are greater than about 90° are generally deemed to be satisfactory, hence the term "cylindrical base", as used in this specification, refers to the base (i.e., the sealing surface) of a fitment wherein the webs of material surrounding and sealed to
25 the fitment diverge at angles greater than about 90° as they separate to encircle the fitment. Figure 15, which is a

fragmentary sectional view of a cylindrical base fitment,
illustrates the approximate

minimum angle of approach of surfaces of what is termed here
as a "cylindrical base" fitment. The base of a cylindrical base
5 style of fitment could, for example, have a hexagonal shape (in
cross section).

The preferred method of fabricating the invented bottle
generally comprises:

1. feeding two or more webs of material in face to face
10 contact into a fabricating machine, one of the webs being folded
to form a gusset;
2. creating perimeter seals for the bottle around a part of
the circumference, including the neck portion of the bottle, and
shaping the bottle by cutting away areas at the edges of the
15 webs,
3. separating at least one of the incoming webs from the
remainder of the webs upstream of the neck portion and inserting
a fitment into the neck portion of the bottle, the insertion
motion being through what eventually will become the bottom of
20 the bottle,
4. forming the remainder of the perimeter seals of the
bottle,
5. severing the bottle from the web,

6. clamping the bottle material to the fitment with a heated clamping means to create a seal between the bottle material and the fitment,

7. Clamping the bottle material to the fitment with a heated clamp a second time, the second clamping being at a different radial angle.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1A is an exploded end on view of the webs of the constituent material as fed into the fabricating machine (one-up configuration).

5 Figure 1B is an exploded end on view of the webs of the constituent material as fed into the fabricating machine (two-up configuration).

Figure 2 is a flattened top view of a bottle according to the invention, without fitment.

10 Figure 3 is a trimetric view of a completed and filled bottle according to the invention.

Figure 3A is a trimetric view of a representative fitment for use in the invented bottle.

15 Figures 4 through 9 are schematic views of various steps of the presently preferred fabricating process, as performed in a fabricating machine. The Figures marked "A" are top views of the web during the process step, whereas those marked "B" are side views at the same point in time.

20 Figure 10 depicts a seam pattern made by the seaming iron in accordance with one embodiment of the fabricating machine.

Figure 11A is a top view of the seaming clamp used to create a seal between the bottle neck and the fitment, in an open condition.

Figure 11B is a top view of the seaming clamp used to create a seal between the bottle neck and the fitment, in the closed condition.

Figure 12 depicts an alternate seaming pattern made by the
5 seaming iron.

Figure 13 is a flattened plan view of an alternate embodiment of the invented bottle that includes a handle portion.

Figure 14 is a plan view of a flattened bottle according to another embodiment of the invention, without the fitment.

10 Figure 15 is a fragmentary sectional view of the base section of a fitment which could be used in connection with the invention.

DETAILED DESCRIPTION OF THE INVENTION

The invented bottle is intended to be fabricated from webs of flexible heat sealable plastic, foil, paper, or similar material. Two or three webs may be involved in "one-up" fabrication, or two to four webs may be involved in "two-up" fabrication. The number of webs used in each case is a matter of convenience.

There are many different web material compositions that could be suitable for the invented bottle, depending on the circumstances, and all of the webs do not necessarily have the same composition. It may, for example, be desirable to have some portions of the completed bottle stiffer than others, which can be accomplished by having differing compositions, or by differing web thicknesses. Or, it may be desired that one or more faces of the bottle be foil, while the others are plastic. Other factors may also dictate differences in web composition.

In addition to any requirements that may be imposed on the materials by the proposed use of the bottle, in order to be amenable to the preferred method of manufacture as described below, a composite sheet is generally used. It is preferable that the sheets (or webs) have one heat sealable surface, and the other not heat sealable. In other words, the sheets used should be such that one face of a first sheet is heat sealable to an abutting face of a second sheet, whereas the second face of the first sheet will not form a bond to the second face of the second sheet (at least not at the temperatures and pressures used to

bond the first faces). It will be appreciated that the preferred method of manufacture could be modified to permit the use of materials, both faces of which are heat sealable.

One material that has been found to work well for fabricating
5 items such as the invented bottle is a polyester sheet having a coating of low density polyethylene on one face. Many other materials are also suitable, the one mentioned being merely illustrative. The low density polyethylene coating has the property of being able to be sealed to a like coating on another
10 sheet, but the polyester base sheet will not seal to another sheet of polyester. This selective sealing property of the film used permits gussets in the web to be conveniently formed, (i.e., without sealing the inside faces of the gussets to each other), yet permitting other laminations to be sealed to the gussets, as will
15 be described below.

In the description which follows, the invented bottle is described as though it were fabricated from three webs (in a "one-up" configuration), but it will be appreciated that it is contemplated that fabrication in accordance with the method
20 described could be accomplished using as few as two webs. Or, alternatively, the bottle can be fabricated "two-up" using two to four webs. For descriptive purposes, the webs during the course of fabrication will be referred to as "top", "bottom", and "center", corresponding to their relative positions when passing
25 through the first stages of fabrication. After fabrication, what were originally the top and bottom webs (sometimes called

laminations), will form two side panels of the completed bottle, and will also form part of the top and bottom portions of the bottle. The center web (the gusset) will form the other side panel, and also be part of the top and bottom portions of the bottle. The neck, being a part of the top portion of the bottle, is formed from extensions of the front, back, and gusseted side panel.

Figure 1A shows the relative positions of the various webs (in a "one-up" configuration) as they pass through the fabrication process. For clarity, the webs are shown separated and the seams not made. The constituent webs are top web 11, bottom web 12, and center web 13. The center web is folded, and forms a gusset in the finished product. The numeral 13C indicates the inner extent of the gusset fold.

While the webs 11, 12, and 13 are discussed herein as if they were separate pieces of material at the outset, it will be appreciated that any number of the seams between the webs could be "pre-made", as by folding one or more of the source webs to create the effect of a seam or seams. For example, if it were desired to fabricate the invented bottle from two webs instead of three, the bottom and center webs could be a single folded web, instead of two separate webs.

It will be appreciated that when the bottle is complete, and contains liquid, the gusset will be open, and the bottle will have a substantially triangular shape in cross section. Also, as will be noted below, even though the cross section is

substantially triangular, the body of the bottle may be shaped with pleasing curves in the vertical direction. When partially or completely full, the invented bottle is remarkably stable.

The faces of the top and bottom webs 11 and 12 that are
5 coated with sealable material, (i.e. the low density polyethylene in the case of the illustrative web material) face toward the interior of the bottle, whereas the coated face of the center web 13 faces outward of the gusset. Hence, it will be appreciated that when a sandwich including all of the webs is subjected to
10 heat and pressure, only those faces which are coated with low density polyethylene will form seams, and the inside surface of the gusset (which is not coated) will not adhere.

Figure 2 depicts the outline of a completed bottle, (except without the fitment), and with the gusset folded. What can be
15 seen is top web 11, and the seam pattern 15. Section 1 is a portion of what will become the bottom, Section 2 is what will become the front panel, section 3 is a portion of the transition section, and section 4 is a portion of the bottle neck (where the fitment is placed). The dashed line 13C indicates the fold of
20 the gusset. The edges of the webs at section 1 preferably taper inward at approximately a 30° angle, terminating at approximately the inside edge of the gusset. Alternatively, the bottom could be cut straight across, without the 30° cuts. A bottle made in this manner would unfold to a flat bottom, as does the 30° cut
25 embodiment, but it has been found that such a bottom does not

contribute to quite as stable a structure as does the 30° cut bottom.

Figure 3 is a trimetric view of one embodiment of a completed bottle as it would appear filled (partially or
5 completely) with liquid or other flowable product. Side panel 21 (a part of web 11 during fabrication) is visible, as is transition section 26, neck 27, and fitment 28. The gusset 13 which was the center web 13 during fabrication can be seen as side panel 23. The other side panel (22) cannot be seen. Figure
10 3A is a trimetric view of a representative fitment 28, with the numeral 28A indicating the base of the fitment. A round base is illustrated, but as noted above, other shapes are also contemplated.

A presently preferred method of fabricating the invented
15 bottle is illustrated in Figures 4 through 9. The "A" portion of each figure is a plan view showing the webs at a particular stage in the fabrication process as the webs pass through the fabricating machine, while the "B" portion is a side view. In order to promote clarity, all figures are somewhat schematic in
20 nature. Since fabrication is a continuous repetitive process, the point in the process where explanation starts is somewhat arbitrary.

In general terms, the fabrication process proceeds as follows:

1. The perimeter seams which form the top portion of a bottle are formed (by the application of heat and pressure, or alternatively by ultrasonic or other means), and at the same time the extra material around the neck and the transition section is removed by "notching" the edges of the webs.
5
2. The fitment is inserted.
3. The partially formed bottle is then moved forward and attached to a suitable transport mechanism, for example the "turret" illustrated in the drawings.
10
4. The remainder of the perimeter seams are formed (i.e., the bottom portion - as well as the top portion for the next bottle) and the bottle is detached from the web.
5. The nascent bottles are moved to the next station (i.e., the turret is rotated) and the joint between the neck of the bottle and the fitment is sealed in two operations, the bottle being turned (preferably about) 90 degrees between sealing operations. Alternatively, of course, the sealing mechanisms (or possibly a single mechanism) could apply the pressure from differing angles.
15
20

For greater detail of the fabrication process, first refer to Figure 4, where the webs 11, 12, and 13 are seen being fed into the fabricating machine around a pair of idler rolls 40. A first nascent bottle 41 is seen being held at the end of an arm 47 of turret 42 at station A (the holding means (48) will be
25

described later). At the time depicted in Figure 4, the top portion of the perimeter seams for bottle 41 have been formed, and the fitment 28 has been placed, but the bottom portion of the bottle is still unseamed. Partially completed bottles 43 and 44
5 are attached to the turret at stations B and C. Turret 42 is rotatable by means not shown.

The next step, as shown in Figure 5, seaming iron 51 has closed on the web, and is forming the top portion of the perimeter seams (15) for the next bottle (52), as well as the
10 bottom portion of the perimeter seams for the bottle 41. When seaming iron 51 clamps the webs together, as noted previously, the inside surface of the gusset (not being coated) will not adhere, but seams will be formed between the gusset material and the top and bottom webs (since these abutting faces are coated
15 with sealable material).

Figure 10 illustrates an exemplary pattern of the perimeter seams 15 formed by seaming iron 51. The numeral 15A indicates the seams for the top portion of one bottle, while 15B indicates the seams for the bottom portion of the prior bottle. For
20 clarity, only the seams made at one closing of seaming iron 51 are shown in the figure.

At the same time as the perimeter seams are being formed by seaming iron 51 (as illustrated in Figure 5), a notching means - which may be integral with the seaming iron - cuts the extraneous
25 material (indicated by the numeral 53) from around the neck and transition areas of the bottle being formed, and also severs the

web between bottles 41 and 52. The extraneous material (53) is commonly removed from the area by a vacuum system, and is discarded.

After the perimeter seams have been formed as described in the preceding paragraphs, and the web severed, the turret is rotated so that bottle 41, which was at station A, is rotated 60° (counterclockwise as viewed in the drawings) to station B. As the turret rotates, the seaming iron 51 members separate, as do the rollers comprising idler rolls 40. This is illustrated in Figure 6.

When the idler rolls 40 are far enough apart, fitment driver 71 drives mandrel 72 (which has a fitment 28 positioned on its end) in through the open bottom of the bottle in process, and positions the fitment in the neck portion of the bottle (Figure 7). Fitment handling and positioning on the mandrels such as mandrel 72 is known in the art and therefore is not further described. The fitment should fit reasonably closely to the neck portion of the bottle so that wrinkles do not appear when the neck is sealed to the fitment. The maximum looseness of fit depends in great measure on the particular circumstances, but in general, if the inner circumference of the neck is more than about 3% larger than the circumference of the base of the fitment, there is a danger of wrinkling. It may be desired to taper the base of fitment 28 somewhat as an aid to fitting it into the neck,

After the fitment 28 is in place, clamp 81 (Figure 8) clamps the bottle neck 27 to the fitment 28. Clamp 81 is preferably heated so that a first (at least temporary) bonding of the bottle material to the fitment is accomplished. Clamp 81 is then moved
5 to engage the fitment with an arm of the turret (Figure 9). The end 48 of the arm on which the bottle is held, is preferably split, is compliant, and has a slightly larger diameter at its end than the hole in the fitment (so as to hold the fitment from the inside). As the clamp 81 moves the nascent bottle to the
10 position shown in Figure 9, the idler rolls 40 turn as the material feeds.

After the bottle is in position and held by end 48, mandrel 72 is retracted. The clamp 81 is then released and moved back to its at rest position and a new fitment is positioned on the end
15 of mandrel 72 (not illustrated).

At the end of the step described in connection with Figure 9, the nascent bottle 52 that is held by an arm of the turret at station A is in same condition as bottle 41 was just before the step described in connection with Figure 4. The next step,
20 therefore, is to repeat the step of Figure 4 by closing the idler rolls 40, following which the seaming iron 51 will create another set of perimeter seals, etc.

Stepping back to the time just after the rotation of the turret 42 to the position shown in Figure 7, bottles 41, 43, and
25 44 can be seen attached at the ends of the arms 47 of the turret at stations B, C, and D. Bottle 44 is pulled off the turret leg

at this time (by means not shown) and transferred to a packing station or to a bottle filling station.

A heated clamp 111 (as shown in Figures 11A and 11B) is located at each of stations B and C. When the turret is stopped during the steps of Figures 7, 8, 9, 4, and 5, both clamps 111 are closed around the base 28A of fitment 28 of the bottles which are then at stations B and C, as indicated in Figure 11B, creating seals between the neck and the fitment. Just before the turret begins to turn again (Figure 7), the clamps open (Figure 11A) to allow the turret to move. For clarity, the clamps 111 are not shown in Figures 4-9.

Alternatively, instead of using heat and pressure, as applied by heated clamp 111, to seal the bottle neck to the fitment, the seals can be effected by applying ultrasonic energy to the interface. Similarly, the perimeter seams also may be made by using ultrasonic energy. Ultrasonic sealing is well known, and need not be described further.

The ends of the turret arms 47 are rotatable with respect to the arms, and, to effect such rotation, each end includes a gear or friction wheel 45 that engages a mating rack or friction pad 46 fastened to the machine frame between stations B and C. The length of the rack 46 is such that each arm end (and attached bottle) turns about 90° between stations B and C. The heated clamps 111 at stations B and C (which are heated hot enough, and apply sufficient clamping pressure to form a seal between the web material and the fitment) therefore provide a uniform seal

between the neck of the bottle 27 and the fitment 28 around the circumference.

The use of two heated clamps to apply pressure to the sealing area at different radial angles assures that the needed
5 sealing pressure is exerted on the fitment at all areas around the entire circumference, and thereby provides complete and reliable sealing. It will be appreciated that since clamp 81 can be utilized to provide the first sealing step, adequate two-step sealing can be achieved, if desired, using only clamp 81 and one
10 clamp 111. In such case, turning of the bottle between sealing steps would not be necessary.

As an alternate, instead of turning the bottles, two clamps 111 could be positioned so as to apply clamping force from different directions. Yet another alternate method of sealing,
15 that would be suitable for use with symmetrical fitments, would be to use only one heated clamp, actuating it twice, and causing it move angularly between actuations.

Figure 12 depicts an alternate configuration of the seaming pattern for the perimeter seams. In the case of Figure 12, the
20 portion 2 (as shown in Figure 2) is formed at the same time as portion 1 is formed, rather than at the time portions 3 and 4 are formed. Forming the seams in this manner will involve some differences in timing of the process, as will be apparent to those skilled in the art, but can be accommodated, if deemed
25 convenient.

Figure 13 shows a flattened bottle as in Figure 2, but with a handle 134 adjacent to the neck portion. Hole 133 provides a place to hook a finger so as to enable a user to easily hold the bottle.

5 Figure 14 is intended to show that the body of the invented bottle need not be simply cylindrical (when filled). While a horizontal cross section of the body is triangular, the body (vertically) may have a pleasing shape, as illustrated in Figure 14, where a bottle 141 is shown with its sides notched out (as
10 indicated by the numeral 142) providing an "hour glass" or other desirable shape. The notching preferably is accomplished at the same time as material 53 is cut away. The bottle of Figure 14 is shown in the same condition as the bottle of Figure 2, namely flat, and without fitment inserted.

15 For explanatory purposes, Figures 4-9 and 13 show a "turret" type of device for holding the bottles at spaced stations A, B, C, and D, and transporting them between stations. It will be appreciated by those skilled in the art that other suitable transport means could be used to accomplish the same function,
20 i.e., a chain running around a pair of sprockets, a carousel, pallets travelling down a track, or other means.

At the outset, reference was made to the possibility of fabricating the invented bottle "two-up". Figure 1B depicts a web configuration that could be used for "two-up" production.
25 Webs 11A, and 12A correspond to webs 11 and 12 of Figure 1A, but two gussets 13A and 13B are shown instead of the single gusset 13

of Figure 1A. It will be appreciated that by slitting the web configuration depicted in Figure 1B down the middle, two webs of the configuration shown in Figure 1A will be created. Hence, the web configuration shown in Figure 1B can result in two lines proceeding side by side, utilizing two turrets, two fitment arms, etc. Of course, at some point during fabrication, preferably just before attachment of the nascent bottles to the turret, the web must be slit into two parallel webs. Slitting webs is a common procedure in the art, and, accordingly, need not be discussed in detail.

What has been described is a novel flexible bottle, with a fitment, and a method for fabricating same. These have been described in detail with reference to specific embodiments. Persons skilled in the art will, no doubt, utilize the principles disclosed herein in connection with embodiments differing in some details from those described, but nevertheless within the spirit of the invention as defined in the below claims. Such changed embodiments, as well as such changes in the process of making the invented bottle as will occur to those skilled in the art, are intended to be covered by the following claims, which define the invention.

I claim:

1. A triangularly shaped bottle fabricated from flexible webs and including a fitment which comprises:

a bottom section;

a body section comprising a front side panel, a rear side panel,

5 and one gusseted side panel, each of said front side panel, rear side panel and gusseted side panel having predetermined widths;

a neck section formed from extended portions of said front and

10 rear side panels and extended portions of said gusseted side panel, the widths of said extended portions of said front and rear side panels and said gusseted side panel being reduced at said neck section;

a tapered transition section between said body section and said neck section; and

15 a fitment positioned within said neck section, and sealed to said extended portions of said front and rear side panels and to said extended portions of said gusseted side panel.

2. A triangularly shaped bottle as recited in claim 1 wherein said neck section is sealed to said fitment by applying heat and pressure to said neck section against said

fitment at least two times and from at least two different angular directions.

3. A triangularly shaped bottle as recited in claim 2 wherein at least two of said applications of heat and pressure are applied from directions which differ by about 90 degrees.

4. A triangularly shaped bottle as recited in claim 1 wherein said neck section is sealed to said fitment by applying ultrasonic energy to the interface between said neck section and said fitment.

5. A triangularly shaped bottle as recited in claim 1 wherein the side edges of said front side panel, said rear side panel, and said gusseted side panel are contoured.

6. A triangularly shaped bottle as recited in claim 1 wherein said bottom portion is formed from extended portions of said front and rear side panels and said gusseted side panel, the edges of said extended portions tapering at an angle of about 30 degrees.

7. A triangularly shaped bottle as recited in claim 1 and further including a handle portion extending from said transition and neck sections.

8. A triangularly shaped bottle fabricated from flexible webs and including a fitment having a cylindrical base which comprises:

a bottom section;

5 a body section comprising a front side panel, a rear side panel, and one gusseted side panel, each of said front side panel, rear side panel and gusseted side panel having predetermined widths;

10 a neck section formed from extended portions of said front and rear side panels and extended portions of said gusseted side panel, the widths of said extended portions of said front and rear side panels and gusseted side panel being reduced at said neck section;

15 a tapered transition section between said body section and said neck section; and

a fitment having a cylindrical base positioned within said neck section, said cylindrical base being sealed to said extended portions of said front and rear side panels and to said extended portions of said gusseted side panel.

9. A triangularly shaped bottle as recited in claim 8 wherein said neck section is sealed to said cylindrical base by the application of heat and pressure.

10. A triangularly shaped bottle as recited in claim 9 wherein said heat and pressure is applied more than one time, and at least two of said applications of heat and pressure are applied from directions which differ by about 90 degrees.

11. A triangularly shaped bottle as recited in claim 8 wherein said neck section is sealed to said fitment by applying ultrasonic energy to the interface between said neck section and said cylindrical base.

12. A triangularly shaped bottle as recited in claim 8 wherein the side edges of said front side panel, said rear side panel, and said gusseted side panel are contoured.

13. A triangularly shaped bottle as recited in claim 8 wherein said bottom portion is formed from extended portions of said front and rear panels and said gusseted side panel, the edges of said extended portions tapering at an angle of about 30 degrees.

14. A triangularly shaped bottle as recited in claim 8 and further including a handle portion extending from said transition and neck sections.

15. A method of fabricating a triangularly shaped flexible bottle that includes a neck section containing a fitment, a transition section, a body section, and a bottom section, which method comprises the steps of:

- 5 feeding a web into a fabricating machine, said web being comprised of flexible films, said web including i) one folded gusset, said gusset having an upper face and a lower face, and ii) top and bottom laminations, said top and bottom laminations abutting the upper and lower faces of said folded gusset;
- 10 forming perimeter seams at the sides of at least said neck section and said transition section, but not including said bottom section, said neck section being the portion of said bottle fed into said machine first, said perimeter seams attaching said top lamination to the upper face of said gusset, and
- 15 attaching said bottom lamination to the lower face of said gusset;
- cutting away the material outside said perimeter seams in the regions of said neck section and said transition section;
- inserting a fitment into said neck section through the unseamed
- 20 bottom section, said insertion being in the direction said web is being fed;

forming perimeter seams around the portions of said bottle not
formed in the prior perimeter seaming step, said perimeter
seams attaching said top lamination to the upper face of said
25 gusset, and attaching said bottom lamination to the lower
faces of said gusset;

severing said bottle from said web; and
sealing said neck section to said fitment.

16. A method of fabricating a triangularly shaped
flexible bottle as recited in claim 15 wherein said sealing of
said neck section to said fitment is accomplished by applying heat
and pressure on said neck section against said fitment.

17. A method of fabricating a triangularly shaped
flexible bottle as recited in claim 16, wherein the step of
applying heat and pressure to the interface between said neck
section and said fitment is performed more than one time, at least
5 two of said times said heat and pressure are applied being at at
different radial angles.

18. A method of fabricating a triangularly shaped
flexible bottle as recited in claim 17 wherein said different
radial angle is about 90 degrees.

19. A method of fabricating a triangularly shaped flexible bottle as recited in claim 15 wherein said sealing of said neck section to said fitment is accomplished by applying ultrasonic energy to said neck section against said fitment.

FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 3A




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11A

FIG. 11B




FIG. 12




FIG. 13




FIG. 14





FIG. 15



INTERNATIONAL SEARCH REPORT

International Application No
PCT/US2005/000453

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65D75/58

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2003/202719 A1 (WILKES KENNETH R) 30 October 2003 (2003-10-30) claims; figures	1-19
Y	US 6 409 386 B1 (TRANI GIORGIO ET AL) 25 June 2002 (2002-06-25) column 1, line 32 - line 57; figure 1	1-19

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

7 September 2005

Date of mailing of the international search report

29/09/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bridault, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US2005/000453

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2003202719 A1	30-10-2003	AU 2003224903 A1	17-11-2003
		EP 1501736 A1	02-02-2005
		WO 03093126 A1	13-11-2003
		US 2005026761 A1	03-02-2005

US 6409386 B1	25-06-2002	NONE	
