



(51) International Patent Classification:

H04N 19/176 (2014.01) H04N 19/112 (2014.01)
H04N 7/12 (2006.01) H04N 19/119 (2014.01)
H04N 19/103 (2014.01)

(21) International Application Number:

PCT/US2021/062691

(22) International Filing Date:

09 December 2021 (09.12.2021)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

17/358,797 25 June 2021 (25.06.2021) US

(71) Applicant: TENCENT AMERICA LLC [US/US]; 2747
Park Boulevard, Palo Alto, California 94306 (US).

(72) Inventors: **LI, Guichun**; c/o TENCENT AMERICA LLC, 2747 Park Boulevard, Palo Alto, California 94306 (US). **LI, Xiang**; c/o TENCENT AMERICA LLC, 2747 Park Boulevard, Palo Alto, California 94306 (US). **ZHU, Bin**; c/o TENCENT AMERICA LLC, 2747 Park Boulevard, Palo Alto, California 94306 (US). **LIU, Shan**; c/o TENCENT AMERICA LLC, 2747 Park Boulevard, Palo Alto, California 94306 (US).

(74) Agent: **MA, Johnny** et al.; ArentFox Schiff LLP, 1717 K Street, Washington, DC 20006 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD,

(54) Title: METHOD AND APPARATUS FOR VIDEO CODING

	R01	R02	R03	R04	R05	R06	R07	R08	R09
R10	S11	S12	S13	S14					
R20	S21	S22	S23	S24					
R30	S31	S32	S33	S34					
R40	S41	S42	S43	S44					
R50									
R60									
R70									




FIG. 1A

(Related Art)

(57) Abstract: Aspects of the disclosure include methods, apparatuses, and non-transitory computer-readable storage mediums for video encoding/decoding. An apparatus includes processing circuitry that decodes prediction information of a current block in a coded video bitstream. The prediction information comprises at least one reference picture index used in low delay inter bi-prediction for the current block. Each of the at least one reference picture index has a same value. The processing circuitry determines a first reference picture in a first reference picture list and a second reference picture in a second reference picture list based on the at least one reference picture index. The current block is coded using the low delay inter bi-prediction. The first reference picture list is identical to the second reference picture list. The first reference picture is identical to the second reference picture. The processing circuitry reconstructs the current block based on the first and second reference pictures.



ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW,
SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

METHOD AND APPARATUS FOR VIDEO CODING

INCORPORATION BY REFERENCE

[0001] This present application claims the benefit of priority to U.S. Patent Application No. 17/358,797, "METHOD AND APPARATUS FOR VIDEO CODING," filed on June 25, 2021, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] The present disclosure describes embodiments generally related to video coding.

BACKGROUND

[0003] The background description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent the work is described in this background section, as well as aspects of the description that may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present disclosure.

[0004] Video coding and decoding can be performed using inter-picture prediction with motion compensation. Uncompressed digital video can include a series of pictures, each picture having a spatial dimension of, for example, 1920 x 1080 luminance samples and associated chrominance samples. The series of pictures can have a fixed or variable picture rate (informally also known as frame rate) of, for example, 60 pictures per second or 60 Hz. Uncompressed video has significant bitrate requirements. For example, 1080p60 4:2:0 video at 8 bit per sample (1920x1080 luminance sample resolution at 60 Hz frame rate) requires close to 1.5 Gbit/s bandwidth. An hour of such video requires more than 600 GBytes of storage space.

[0005] One purpose of video coding and decoding can be the reduction of redundancy in the input video signal, through compression. Compression can help reduce the aforementioned bandwidth or storage space requirements, in some cases by two orders of magnitude or more. Both lossless and lossy compression, as well as a combination thereof can be employed. Lossless compression refers to techniques where an exact copy of the original signal can be reconstructed from the compressed original signal. When using lossy compression, the reconstructed signal may not be identical to the original signal, but the distortion between original and reconstructed signals is small enough to make the reconstructed signal useful for the

intended application. In the case of video, lossy compression is widely employed. The amount of distortion tolerated depends on the application; for example, users of certain consumer streaming applications may tolerate higher distortion than users of television distribution applications. The compression ratio achievable can reflect that: higher allowable/tolerable distortion can yield higher compression ratios.

[0006] A video encoder and decoder can utilize techniques from several broad categories, including, for example, motion compensation, transform, quantization, and entropy coding.

[0007] Video codec technologies can include techniques known as intra coding. In intra coding, sample values are represented without reference to samples or other data from previously reconstructed reference pictures. In some video codecs, the picture is spatially subdivided into blocks of samples. When all blocks of samples are coded in intra mode, that picture can be an intra picture. Intra pictures and their derivations such as independent decoder refresh pictures, can be used to reset the decoder state and can, therefore, be used as the first picture in a coded video bitstream and a video session, or as a still image. The samples of an intra block can be exposed to a transform, and the transform coefficients can be quantized before entropy coding. Intra prediction can be a technique that minimizes sample values in the pre-transform domain. In some cases, the smaller the DC value after a transform is, and the smaller the AC coefficients are, the fewer the bits that are required at a given quantization step size to represent the block after entropy coding.

[0008] Traditional intra coding such as known from, for example MPEG-2 generation coding technologies, does not use intra prediction. However, some newer video compression technologies include techniques that attempt, from, for example, surrounding sample data and/or metadata obtained during the encoding and/or decoding of spatially neighboring, and preceding in decoding order, blocks of data. Such techniques are henceforth called “intra prediction” techniques. Note that in at least some cases, intra prediction is only using reference data from the current picture under reconstruction and not from reference pictures.

[0009] There can be many different forms of intra prediction. When more than one of such techniques can be used in a given video coding technology, the technique in use can be coded in an intra prediction mode. In certain cases, modes can have submodes and/or parameters, and those can be coded individually or included in the mode codeword. Which

codeword to use for a given mode, submode, and/or parameter combination can have an impact in the coding efficiency gain through intra prediction, and so can the entropy coding technology used to translate the codewords into a bitstream.

[0010] A certain mode of intra prediction was introduced with H.264, refined in H.265, and further refined in newer coding technologies such as joint exploration model (JEM), versatile video coding (VVC), and benchmark set (BMS). A predictor block can be formed using neighboring sample values belonging to already available samples. Sample values of neighboring samples are copied into the predictor block according to a direction. A reference to the direction in use can be coded in the bitstream or may be predicted itself.

[0011] Referring to FIG. 1A, depicted in the lower right is a subset of nine predictor directions known from H.265's 33 possible predictor directions (corresponding to the 33 angular modes of the 35 intra modes). The point where the arrows converge (101) represents the sample being predicted. The arrows represent the direction from which the sample is being predicted. For example, arrow (102) indicates that sample (101) is predicted from a sample or samples to the upper right, at a 45 degree angle from the horizontal. Similarly, arrow (103) indicates that sample (101) is predicted from a sample or samples to the lower left of sample (101), in a 22.5 degree angle from the horizontal.

[0012] Still referring to FIG. 1A, on the top left there is depicted a square block (104) of 4 x 4 samples (indicated by a dashed, boldface line). The square block (104) includes 16 samples, each labelled with an "S", its position in the Y dimension (e.g., row index) and its position in the X dimension (e.g., column index). For example, sample S21 is the second sample in the Y dimension (from the top) and the first (from the left) sample in the X dimension. Similarly, sample S44 is the fourth sample in block (104) in both the Y and X dimensions. As the block is 4 x 4 samples in size, S44 is at the bottom right. Further shown are reference samples that follow a similar numbering scheme. A reference sample is labelled with an R, its Y position (e.g., row index) and X position (column index) relative to block (104). In both H.264 and H.265, prediction samples neighbor the block under reconstruction; therefore no negative values need to be used.

[0013] Intra picture prediction can work by copying reference sample values from the neighboring samples as appropriated by the signaled prediction direction. For example, assume

the coded video bitstream includes signaling that, for this block, indicates a prediction direction consistent with arrow (102)—that is, samples are predicted from a prediction sample or samples to the upper right, at a 45 degree angle from the horizontal. In that case, samples S41, S32, S23, and S14 are predicted from the same reference sample R05. Sample S44 is then predicted from reference sample R08.

[0014] In certain cases, the values of multiple reference samples may be combined, for example through interpolation, in order to calculate a reference sample; especially when the directions are not evenly divisible by 45 degrees.

[0015] The number of possible directions has increased as video coding technology has developed. In H.264 (year 2003), nine different direction could be represented. That increased to 33 in H.265 (year 2013), and JEM/VVC/BMS, at the time of disclosure, can support up to 65 directions. Experiments have been conducted to identify the most likely directions, and certain techniques in the entropy coding are used to represent those likely directions in a small number of bits, accepting a certain penalty for less likely directions. Further, the directions themselves can sometimes be predicted from neighboring directions used in neighboring, already decoded, blocks.

[0016] FIG. 1B shows a schematic (105) that depicts 65 intra prediction directions according to JEM to illustrate the increasing number of prediction directions over time.

[0017] The mapping of intra prediction directions bits in the coded video bitstream that represent the direction can be different from video coding technology to video coding technology; and can range, for example, from simple direct mappings of prediction direction to intra prediction mode, to codewords, to complex adaptive schemes involving most probable modes, and similar techniques. In all cases, however, there can be certain directions that are statistically less likely to occur in video content than certain other directions. As the goal of video compression is the reduction of redundancy, those less likely directions will, in a well working video coding technology, be represented by a larger number of bits than more likely directions.

[0018] Motion compensation can be a lossy compression technique and can relate to techniques where a block of sample data from a previously reconstructed picture or part thereof (reference picture), after being spatially shifted in a direction indicated by a motion vector (MV

henceforth), is used for the prediction of a newly reconstructed picture or picture part. In some cases, the reference picture can be the same as the picture currently under reconstruction. MVs can have two dimensions X and Y, or three dimensions, the third being an indication of the reference picture in use (the latter, indirectly, can be a time dimension).

[0019] In some video compression techniques, an MV applicable to a certain area of sample data can be predicted from other MVs, for example from those related to another area of sample data spatially adjacent to the area under reconstruction, and preceding that MV in decoding order. Doing so can substantially reduce the amount of data required for coding the MV, thereby removing redundancy and increasing compression. MV prediction can work effectively, for example, because when coding an input video signal derived from a camera (known as natural video) there is a statistical likelihood that areas larger than the area to which a single MV is applicable move in a similar direction and, therefore, can in some cases be predicted using a similar MV derived from MVs of a neighboring area. That results in the MV found for a given area to be similar or the same as the MV predicted from the surrounding MVs, and that in turn can be represented, after entropy coding, in a smaller number of bits than what would be used if coding the MV directly. In some cases, MV prediction can be an example of lossless compression of a signal (namely: the MVs) derived from the original signal (namely: the sample stream). In other cases, MV prediction itself can be lossy, for example because of rounding errors when calculating a predictor from several surrounding MVs.

[0020] Various MV prediction mechanisms are described in H.265/HEVC (ITU-T Rec. H.265, "High Efficiency Video Coding", December 2016). Out of the many MV prediction mechanisms that H.265 offers, described herein is a technique henceforth referred to as "spatial merge."

[0021] Referring to FIG. 1C, a current block (111) can include samples that have been found by the encoder during the motion search process to be predictable from a previous block of the same size that has been spatially shifted. Instead of coding that MV directly, the MV can be derived from metadata associated with one or more reference pictures, for example from the most recent (in decoding order) reference picture, using the MV associated with either one of five surrounding samples, denoted A0, A1, and B0, B1, B2 (112 through 116, respectively). In

H.265, the MV prediction can use predictors from the same reference picture that the neighboring block is using.

SUMMARY

[0022] Aspects of the disclosure provide apparatuses for video encoding/decoding. An apparatus includes processing circuitry that decodes prediction information of a current block in a current picture that is a part of a coded video bitstream. The prediction information comprises at least one reference picture index used in low delay inter bi-prediction for the current block. Each of the at least one reference picture index has a same value. The processing circuitry determines a first picture in a first reference picture list and a second reference picture in a second reference picture list based on the at least one reference picture index included in the prediction information. The current block is coded using low delay inter bi-prediction. The first reference picture list is identical to the second reference picture list. The first reference picture is identical to the second reference picture. The processing circuitry reconstructs the current block based on the first reference picture and the second reference picture.

[0023] In one embodiment, the at least one reference picture index is a single reference picture index associated with one of the first reference picture list and the second reference picture list, and the processing circuitry determines the single reference picture index as a reference picture index of the other one of the first reference picture list and the second reference picture list.

[0024] In one embodiment, the prediction information includes a syntax element indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list, and the syntax element is included in one of a sequence level parameter, a picture level parameter, and a slice level parameter.

[0025] In one embodiment, based on the current block being coded in one of a plurality of merge modes, each bi-prediction candidate in a merge candidate list of the current block has a same reference picture index for the first reference picture list and the second reference picture list. The plurality of merge modes includes a regular merge mode, an affine merge mode, a merge mode with motion vector difference, an advanced motion vector prediction, and a geometric partitioning mode.

[0026] In one embodiment, the processing circuitry determines that a tool configured to reference a reference picture temporally located after the current picture is disabled based on the prediction information indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list.

[0027] In one embodiment, the prediction information includes one of the first reference picture list and the second reference picture list.

[0028] In one embodiment, the at least one reference picture index includes two identical reference picture indices, and the prediction information includes the first reference picture list, the second reference picture list, and the two identical reference picture indices.

[0029] Aspects of the disclosure provide methods for video encoding/decoding. In the method, prediction information of a current block in a current picture that is a part of a coded video bitstream is decoded. The prediction information comprising at least one reference picture index used in low delay inter bi-prediction for the current block. A first reference picture in a first reference picture list and a second reference picture in a second reference picture list are determined for the current block based on at least one reference picture index included in the prediction information. The current block is coded using the low delay inter bi-prediction. The first reference picture list is identical to the second reference picture list. The first reference picture is identical to the second reference picture. The current block is reconstructed based on the first reference picture and the second reference picture.

[0030] Aspects of the disclosure also provide non-transitory computer-readable mediums storing instructions which when executed by at least one processor cause the at least one processor to perform any one or a combination of the methods for video decoding.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] Further features, the nature, and various advantages of the disclosed subject matter will be more apparent from the following detailed description and the accompanying drawings in which:

[0032] FIG. 1A is a schematic illustration of an exemplary subset of intra prediction modes;

[0033] FIG. 1B is an illustration of exemplary intra prediction directions;

[0034] FIG. 1C is a schematic illustration of a current block and its surrounding spatial merge candidates in one example;

[0035] FIG. 2 is a schematic illustration of a simplified block diagram of a communication system in accordance with an embodiment;

[0036] FIG. 3 is a schematic illustration of a simplified block diagram of a communication system in accordance with an embodiment;

[0037] FIG. 4 is a schematic illustration of a simplified block diagram of a decoder in accordance with an embodiment;

[0038] FIG. 5 is a schematic illustration of a simplified block diagram of an encoder in accordance with an embodiment;

[0039] FIG. 6 shows a block diagram of an encoder in accordance with another embodiment;

[0040] FIG. 7 shows a block diagram of a decoder in accordance with another embodiment;

[0041] FIG. 8 shows an exemplary graphical presentation of a random-access configuration in accordance with one embodiment;

[0042] FIG. 9 shows an exemplary graphical presentation of a low-delay configuration in accordance with one embodiment;

[0043] FIG. 10 shows an exemplary flowchart in accordance with an embodiment; and

[0044] FIG. 11 is a schematic illustration of a computer system in accordance with an embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

[0045] **I. Video Decoder and Encoder Systems**

[0046] FIG. 2 illustrates a simplified block diagram of a communication system (200) according to an embodiment of the present disclosure. The communication system (200) includes a plurality of terminal devices that can communicate with each other, via, for example, a network (250). For example, the communication system (200) includes a first pair of terminal devices (210) and (220) interconnected via the network (250). In the FIG. 2 example, the first pair of terminal devices (210) and (220) performs unidirectional transmission of data. For example, the terminal device (210) may code video data (e.g., a stream of video pictures that are

captured by the terminal device (210)) for transmission to the other terminal device (220) via the network (250). The encoded video data can be transmitted in the form of one or more coded video bitstreams. The terminal device (220) may receive the coded video data from the network (250), decode the coded video data to recover the video pictures and display video pictures according to the recovered video data. Unidirectional data transmission may be common in media serving applications and the like.

[0047] In another example, the communication system (200) includes a second pair of terminal devices (230) and (240) that performs bidirectional transmission of coded video data that may occur, for example, during videoconferencing. For bidirectional transmission of data, in an example, each terminal device of the terminal devices (230) and (240) may code video data (e.g., a stream of video pictures that are captured by the terminal device) for transmission to the other terminal device of the terminal devices (230) and (240) via the network (250). Each terminal device of the terminal devices (230) and (240) also may receive the coded video data transmitted by the other terminal device of the terminal devices (230) and (240), and may decode the coded video data to recover the video pictures and may display video pictures at an accessible display device according to the recovered video data.

[0048] In the FIG. 2 example, the terminal devices (210), (220), (230) and (240) may be illustrated as servers, personal computers and smart phones but the principles of the present disclosure may be not so limited. Embodiments of the present disclosure find application with laptop computers, tablet computers, media players and/or dedicated video conferencing equipment. The network (250) represents any number of networks that convey coded video data among the terminal devices (210), (220), (230) and (240), including for example wireline (wired) and/or wireless communication networks. The communication network (250) may exchange data in circuit-switched and/or packet-switched channels. Representative networks include telecommunications networks, local area networks, wide area networks and/or the Internet. For the purposes of the present discussion, the architecture and topology of the network (250) may be immaterial to the operation of the present disclosure unless explained herein below.

[0049] FIG. 3 illustrates, as an example for an application for the disclosed subject matter, the placement of a video encoder and a video decoder in a streaming environment. The disclosed subject matter can be equally applicable to other video enabled applications, including,

for example, video conferencing, digital TV, storing of compressed video on digital media including CD, DVD, memory stick, and the like.

[0050] A streaming system may include a capture subsystem (313) that can include a video source (301), for example a digital camera, creating for example a stream of video pictures (302) that are uncompressed. In an example, the stream of video pictures (302) includes samples that are taken by the digital camera. The stream of video pictures (302), depicted as a bold line to emphasize a high data volume when compared to encoded video data (304) (or coded video bitstreams), can be processed by an electronic device (320) that includes a video encoder (303) coupled to the video source (301). The video encoder (303) can include hardware, software, or a combination thereof to enable or implement aspects of the disclosed subject matter as described in more detail below. The encoded video data (304) (or encoded video bitstream (304)), depicted as a thin line to emphasize the lower data volume when compared to the stream of video pictures (302), can be stored on a streaming server (305) for future use. One or more streaming client subsystems, such as client subsystems (306) and (308) in FIG. 3 can access the streaming server (305) to retrieve copies (307) and (309) of the encoded video data (304). A client subsystem (306) can include a video decoder (310), for example, in an electronic device (330). The video decoder (310) decodes the incoming copy (307) of the encoded video data and creates an outgoing stream of video pictures (311) that can be rendered on a display (312) (e.g., display screen) or other rendering device (not depicted). In some streaming systems, the encoded video data (304), (307), and (309) (e.g., video bitstreams) can be encoded according to certain video coding/compression standards. Examples of those standards include ITU-T Recommendation H.265. In an example, a video coding standard under development is informally known as Versatile Video Coding (VVC). The disclosed subject matter may be used in the context of VVC.

[0051] It is noted that the electronic devices (320) and (330) can include other components (not shown). For example, the electronic device (320) can include a video decoder (not shown) and the electronic device (330) can include a video encoder (not shown) as well.

[0052] FIG. 4 shows a block diagram of a video decoder (410) according to an embodiment of the present disclosure. The video decoder (410) can be included in an electronic device (430). The electronic device (430) can include a receiver (431) (e.g., receiving circuitry).

The video decoder (410) can be used in the place of the video decoder (310) in the FIG. 3 example.

[0053] The receiver (431) may receive one or more coded video bitstreams to be decoded by the video decoder (410); in the same or another embodiment, one coded video bitstream at a time, where the decoding of each coded video bitstream is independent from other coded video bitstreams. The coded video bitstream may be received from a channel (401), which may be a hardware/software link to a storage device which stores the encoded video data. The receiver (431) may receive the encoded video data with other data, for example, coded audio data and/or ancillary data streams, that may be forwarded to their respective using entities (not depicted). The receiver (431) may separate the coded video bitstream from the other data. To combat network jitter, a buffer memory (415) may be coupled in between the receiver (431) and an entropy decoder / parser (420) ("parser (420)" henceforth). In certain applications, the buffer memory (415) is part of the video decoder (410). In others, it can be outside of the video decoder (410) (not depicted). In still others, there can be a buffer memory (not depicted) outside of the video decoder (410), for example to combat network jitter, and in addition another buffer memory (415) inside the video decoder (410), for example to handle playout timing. When the receiver (431) is receiving data from a store/forward device of sufficient bandwidth and controllability, or from an isosynchronous network, the buffer memory (415) may not be needed, or can be small. For use on best effort packet networks such as the Internet, the buffer memory (415) may be required, can be comparatively large and can be advantageously of adaptive size, and may at least partially be implemented in an operating system or similar elements (not depicted) outside of the video decoder (410).

[0054] The video decoder (410) may include the parser (420) to reconstruct symbols (421) from the coded video bitstream. Categories of those symbols include information used to manage operation of the video decoder (410), and potentially information to control a rendering device such as a render device (412) (e.g., a display screen) that is not an integral part of the electronic device (430) but can be coupled to the electronic device (430), as was shown in FIG. 4. The control information for the rendering device(s) may be in the form of Supplemental Enhancement Information (SEI messages) or Video Usability Information (VUI) parameter set fragments (not depicted). The parser (420) may parse / entropy-decode the coded video

bitstream that is received. The coding of the coded video bitstream can be in accordance with a video coding technology or standard, and can follow various principles, including variable length coding, Huffman coding, arithmetic coding with or without context sensitivity, and so forth. The parser (420) may extract from the coded video bitstream, a set of subgroup parameters for at least one of the subgroups of pixels in the video decoder, based upon at least one parameter corresponding to the group. Subgroups can include Groups of Pictures (GOPs), pictures, tiles, slices, macroblocks, Coding Units (CUs), blocks, Transform Units (TUs), Prediction Units (PUs) and so forth. The parser (420) may also extract from the coded video bitstream information such as transform coefficients, quantizer parameter values, MVs, and so forth.

[0055] The parser (420) may perform an entropy decoding / parsing operation on the video bitstream received from the buffer memory (415), so as to create symbols (421).

[0056] Reconstruction of the symbols (421) can involve multiple different units depending on the type of the coded video picture or parts thereof (such as: inter and intra picture, inter and intra block), and other factors. Which units are involved, and how, can be controlled by the subgroup control information that was parsed from the coded video bitstream by the parser (420). The flow of such subgroup control information between the parser (420) and the multiple units below is not depicted for clarity.

[0057] Beyond the functional blocks already mentioned, the video decoder (410) can be conceptually subdivided into a number of functional units as described below. In a practical implementation operating under commercial constraints, many of these units interact closely with each other and can, at least partly, be integrated into each other. However, for the purpose of describing the disclosed subject matter, the conceptual subdivision into the functional units below is appropriate.

[0058] A first unit is the scaler / inverse transform unit (451). The scaler / inverse transform unit (451) receives a quantized transform coefficient as well as control information, including which transform to use, block size, quantization factor, quantization scaling matrices, etc. as symbol(s) (421) from the parser (420). The scaler / inverse transform unit (451) can output blocks comprising sample values that can be input into aggregator (455).

[0059] In some cases, the output samples of the scaler / inverse transform (451) can pertain to an intra coded block; that is: a block that is not using predictive information from

previously reconstructed pictures, but can use predictive information from previously reconstructed parts of the current picture. Such predictive information can be provided by an intra picture prediction unit (452). In some cases, the intra picture prediction unit (452) generates a block of the same size and shape of the block under reconstruction, using surrounding already reconstructed information fetched from the current picture buffer (458). The current picture buffer (458) buffers, for example, partly reconstructed current picture and/or fully reconstructed current picture. The aggregator (455), in some cases, adds, on a per sample basis, the prediction information that the intra prediction unit (452) has generated to the output sample information as provided by the scaler / inverse transform unit (451).

[0060] In other cases, the output samples of the scaler / inverse transform unit (451) can pertain to an inter coded, and potentially motion compensated block. In such a case, a motion compensation prediction unit (453) can access reference picture memory (457) to fetch samples used for prediction. After motion compensating the fetched samples in accordance with the symbols (421) pertaining to the block, these samples can be added by the aggregator (455) to the output of the scaler / inverse transform unit (451) (in this case called the residual samples or residual signal) so as to generate output sample information. The addresses within the reference picture memory (457) from where the motion compensation prediction unit (453) fetches prediction samples can be controlled by MVs, available to the motion compensation prediction unit (453) in the form of symbols (421) that can have, for example X, Y, and reference picture components. Motion compensation also can include interpolation of sample values as fetched from the reference picture memory (457) when sub-sample exact MVs are in use, MV prediction mechanisms, and so forth.

[0061] The output samples of the aggregator (455) can be subject to various loop filtering techniques in the loop filter unit (456). Video compression technologies can include in-loop filter technologies that are controlled by parameters included in the coded video bitstream (also referred to as coded video bitstream) and made available to the loop filter unit (456) as symbols (421) from the parser (420), but can also be responsive to meta-information obtained during the decoding of previous (in decoding order) parts of the coded picture or coded video bitstream, as well as responsive to previously reconstructed and loop-filtered sample values.

[0062] The output of the loop filter unit (456) can be a sample stream that can be output to the render device (412) as well as stored in the reference picture memory (457) for use in future inter-picture prediction.

[0063] Certain coded pictures, once fully reconstructed, can be used as reference pictures for future prediction. For example, once a coded picture corresponding to a current picture is fully reconstructed and the coded picture has been identified as a reference picture (by, for example, the parser (420)), the current picture buffer (458) can become a part of the reference picture memory (457), and a fresh current picture buffer can be reallocated before commencing the reconstruction of the following coded picture.

[0064] The video decoder (410) may perform decoding operations according to a predetermined video compression technology in a standard, such as ITU-T Rec. H.265. The coded video bitstream may conform to a syntax specified by the video compression technology or standard being used, in the sense that the coded video bitstream adheres to both the syntax of the video compression technology or standard and the profiles as documented in the video compression technology or standard. Specifically, a profile can select certain tools as the only tools available for use under that profile from all the tools available in the video compression technology or standard. Also necessary for compliance can be that the complexity of the coded video bitstream is within bounds as defined by the level of the video compression technology or standard. In some cases, levels restrict the maximum picture size, maximum frame rate, maximum reconstruction sample rate (measured in, for example megasamples per second), maximum reference picture size, and so on. Limits set by levels can, in some cases, be further restricted through Hypothetical Reference Decoder (HRD) specifications and metadata for HRD buffer management signaled in the coded video bitstream.

[0065] In an embodiment, the receiver (431) may receive additional (redundant) data with the encoded video. The additional data may be included as part of the coded video bitstream(s). The additional data may be used by the video decoder (410) to properly decode the data and/or to more accurately reconstruct the original video data. Additional data can be in the form of, for example, temporal, spatial, or signal noise ratio (SNR) enhancement layers, redundant slices, redundant pictures, forward error correction codes, and so on.

[0066] FIG. 5 shows a block diagram of a video encoder (503) according to an embodiment of the present disclosure. The video encoder (503) is included in an electronic device (520). The electronic device (520) includes a transmitter (540) (e.g., transmitting circuitry). The video encoder (503) can be used in the place of the video encoder (303) in the FIG. 3 example.

[0067] The video encoder (503) may receive video samples from a video source (501) (that is not part of the electronic device (520) in the FIG. 5 example) that may capture video image(s) to be coded by the video encoder (503). In another example, the video source (501) is a part of the electronic device (520).

[0068] The video source (501) may provide the source video bitstream to be coded by the video encoder (503) in the form of a digital video sample stream that can be of any suitable bit depth (for example: 8 bit, 10 bit, 12 bit, ...), any colorspace (for example, BT.601 Y CrCb, RGB, ...), and any suitable sampling structure (for example Y CrCb 4:2:0, Y CrCb 4:4:4). In a media serving system, the video source (501) may be a storage device storing previously prepared video. In a videoconferencing system, the video source (501) may be a camera that captures local image information as a video bitstream. Video data may be provided as a plurality of individual pictures that impart motion when viewed in sequence. The pictures themselves may be organized as a spatial array of pixels, wherein each pixel can comprise one or more samples depending on the sampling structure, color space, etc. in use. A person skilled in the art can readily understand the relationship between pixels and samples. The description below focuses on samples.

[0069] According to an embodiment, the video encoder (503) may code and compress the pictures of the source video sequence into a coded video bitstream (543) in real time or under any other time constraints as required by the application. Enforcing appropriate coding speed is one function of a controller (550). In some embodiments, the controller (550) controls other functional units as described below and is functionally coupled to the other functional units. The coupling is not depicted for clarity. Parameters set by the controller (550) can include rate control related parameters (picture skip, quantizer, lambda value of rate-distortion optimization techniques, ...), picture size, group of pictures (GOP) layout, maximum MV allowed reference

area, and so forth. The controller (550) can be configured to have other suitable functions that pertain to the video encoder (503) optimized for a certain system design.

[0070] In some embodiments, the video encoder (503) is configured to operate in a coding loop. As an oversimplified description, in an example, the coding loop can include a source coder (530) (e.g., responsible for creating symbols, such as a symbol stream, based on an input picture to be coded, and a reference picture(s)), and a (local) decoder (533) embedded in the video encoder (503). The decoder (533) reconstructs the symbols to create the sample data in a similar manner as a (remote) decoder also would create (as any compression between symbols and coded video bitstream is lossless in the video compression technologies considered in the disclosed subject matter). The reconstructed sample stream (sample data) is input to the reference picture memory (534). As the decoding of a symbol stream leads to bit-exact results independent of decoder location (local or remote), the content in the reference picture memory (534) is also bit exact between the local encoder and remote encoder. In other words, the prediction part of an encoder "sees" as reference picture samples exactly the same sample values as a decoder would "see" when using prediction during decoding. This fundamental principle of reference picture synchronicity (and resulting drift, if synchronicity cannot be maintained, for example because of channel errors) is used in some related arts as well.

[0071] The operation of the "local" decoder (533) can be the same as of a "remote" decoder, such as the video decoder (410), which has already been described in detail above in conjunction with FIG. 4. Briefly referring also to FIG. 4, however, as symbols are available and encoding/decoding of symbols to a coded video bitstream by an entropy coder (545) and the parser (420) can be lossless, the entropy decoding parts of the video decoder (410), including the buffer memory (415) and the parser (420) may not be fully implemented in the local decoder (533).

[0072] An observation that can be made at this point is that any decoder technology except the parsing/entropy decoding that is present in a decoder also necessarily needs to be present, in substantially identical functional form, in a corresponding encoder. For this reason, the disclosed subject matter focuses on decoder operation. The description of encoder technologies can be abbreviated as they are the inverse of the comprehensively described

decoder technologies. Only in certain areas a more detail description is required and provided below.

[0073] During operation, in some examples, the source coder (530) may perform motion compensated predictive coding, which codes an input picture predictively with reference to one or more previously-coded picture from the video bitstream that were designated as "reference pictures". In this manner, the coding engine (532) codes differences between pixel blocks of an input picture and pixel blocks of reference picture(s) that may be selected as prediction reference(s) to the input picture.

[0074] The local video decoder (533) may decode coded video data of pictures that may be designated as reference pictures, based on symbols created by the source coder (530). Operations of the coding engine (532) may advantageously be lossy processes. When the coded video data may be decoded at a video decoder (not shown in FIG. 5), the reconstructed video bitstream typically may be a replica of the source video bitstream with some errors. The local video decoder (533) replicates decoding processes that may be performed by the video decoder on reference pictures and may cause reconstructed reference pictures to be stored in the reference picture cache (534). In this manner, the video encoder (503) may store copies of reconstructed reference pictures locally that have common content as the reconstructed reference pictures that will be obtained by a far-end video decoder (absent transmission errors).

[0075] The predictor (535) may perform prediction searches for the coding engine (532). That is, for a new picture to be coded, the predictor (535) may search the reference picture memory (534) for sample data (as candidate reference pixel blocks) or certain metadata such as reference picture MVs, block shapes, and so on, that may serve as an appropriate prediction reference for the new pictures. The predictor (535) may operate on a sample block-by-pixel block basis to find appropriate prediction references. In some cases, as determined by search results obtained by the predictor (535), an input picture may have prediction references drawn from multiple reference pictures stored in the reference picture memory (534).

[0076] The controller (550) may manage coding operations of the source coder (530), including, for example, setting of parameters and subgroup parameters used for encoding the video data.

[0077] Output of all aforementioned functional units may be subjected to entropy coding in the entropy coder (545). The entropy coder (545) translates the symbols as generated by the various functional units into a coded video bitstream, by lossless compressing the symbols according to technologies such as Huffman coding, variable length coding, arithmetic coding, and so forth.

[0078] The transmitter (540) may buffer the coded video bitstream(s) as created by the entropy coder (545) to prepare for transmission via a communication channel (560), which may be a hardware/software link to a storage device which would store the encoded video data. The transmitter (540) may merge coded video data from the video coder (503) with other data to be transmitted, for example, coded audio data and/or ancillary data streams (sources not shown).

[0079] The controller (550) may manage operation of the video encoder (503). During coding, the controller (550) may assign to each coded picture a certain coded picture type, which may affect the coding techniques that may be applied to the respective picture. For example, pictures often may be assigned as one of the following picture types:

[0080] An Intra Picture (I picture) may be one that may be coded and decoded without using any other picture in the sequence as a source of prediction. Some video codecs allow for different types of intra pictures, including, for example Independent Decoder Refresh (“IDR”) Pictures. A person skilled in the art is aware of those variants of I pictures and their respective applications and features.

[0081] A predictive picture (P picture) may be one that may be coded and decoded using intra prediction or inter prediction using at most one MV and reference index to predict the sample values of each block.

[0082] A bi-directionally predictive picture (B Picture) may be one that may be coded and decoded using intra prediction or inter prediction using at most two MVs and reference indices to predict the sample values of each block. Similarly, multiple-predictive pictures can use more than two reference pictures and associated metadata for the reconstruction of a single block.

[0083] Source pictures commonly may be subdivided spatially into a plurality of sample blocks (for example, blocks of 4x4, 8x8, 4x8, or 16x16 samples each) and coded on a block-by-block basis. Blocks may be coded predictively with reference to other (already coded) blocks as

determined by the coding assignment applied to the blocks' respective pictures. For example, blocks of I pictures may be coded non-predictively or they may be coded predictively with reference to already coded blocks of the same picture (spatial prediction or intra prediction). Pixel blocks of P pictures may be coded predictively, via spatial prediction or via temporal prediction with reference to one previously coded reference picture. Blocks of B pictures may be coded predictively, via spatial prediction or via temporal prediction with reference to one or two previously coded reference pictures.

[0084] The video encoder (503) may perform coding operations according to a predetermined video coding technology or standard, such as ITU-T Rec. H.265. In its operation, the video encoder (503) may perform various compression operations, including predictive coding operations that exploit temporal and spatial redundancies in the input video bitstream. The coded video data, therefore, may conform to a syntax specified by the video coding technology or standard being used.

[0085] In an embodiment, the transmitter (540) may transmit additional data with the encoded video. The source coder (530) may include such data as part of the coded video bitstream. Additional data may comprise temporal/spatial/SNR enhancement layers, other forms of redundant data such as redundant pictures and slices, SEI messages, VUI parameter set fragments, and so on.

[0086] A video may be captured as a plurality of source pictures (video pictures) in a temporal sequence. Intra-picture prediction (often abbreviated to intra prediction) makes use of spatial correlation in a given picture, and inter-picture prediction makes uses of the (temporal or other) correlation between the pictures. In an example, a specific picture under encoding/decoding, which is referred to as a current picture, is partitioned into blocks. When a block in the current picture is similar to a reference block in a previously coded and still buffered reference picture in the video, the block in the current picture can be coded by a vector that is referred to as a MV. The MV points to the reference block in the reference picture, and can have a third dimension identifying the reference picture, in case multiple reference pictures are in use.

[0087] In some embodiments, a bi-prediction technique can be used in the inter-picture prediction. According to the bi-prediction technique, two reference pictures, such as a first reference picture and a second reference picture that are both prior in decoding order to the

current picture in the video (but may be in the past and future, respectively, in display order) are used. A block in the current picture can be coded by a first MV that points to a first reference block in the first reference picture, and a second MV that points to a second reference block in the second reference picture. The block can be predicted by a combination of the first reference block and the second reference block.

[0088] Further, a merge mode technique can be used in the inter-picture prediction to improve coding efficiency.

[0089] According to some embodiments of the disclosure, predictions, such as inter-picture predictions and intra-picture predictions are performed in the unit of blocks. For example, according to the HEVC standard, a picture in a sequence of video pictures is partitioned into coding tree units (CTU) for compression, the CTUs in a picture have the same size, such as 64x64 pixels, 32x32 pixels, or 16x16 pixels. In general, a CTU includes three coding tree blocks (CTBs), which are one luma CTB and two chroma CTBs. Each CTU can be recursively quad-tree split into one or multiple coding units (CUs). For example, a CTU of 64x64 pixels can be split into one CU of 64x64 pixels, or 4 CUs of 32x32 pixels, or 16 CUs of 16x16 pixels. In an example, each CU is analyzed to determine a prediction type for the CU, such as an inter prediction type or an intra prediction type. The CU is split into one or more prediction units (PUs) depending on the temporal and/or spatial predictability. Generally, each PU includes a luma prediction block (PB), and two chroma PBs. In an embodiment, a prediction operation in coding (encoding/decoding) is performed in the unit of a prediction block. Using a luma prediction block as an example of a prediction block, the prediction block includes a matrix of values (e.g., luma values) for pixels, such as 8x8 pixels, 16x16 pixels, 8x16 pixels, 16x8 pixels, and the like.

[0090] FIG. 6 shows a diagram of a video encoder (603) according to another embodiment of the disclosure. The video encoder (603) is configured to receive a processing block (e.g., a prediction block) of sample values within a current video picture in a sequence of video pictures, and encode the processing block into a coded picture that is part of a coded video bitstream. In an example, the video encoder (603) is used in the place of the video encoder (303) in the FIG. 3 example.

[0091] In an HEVC example, the video encoder (603) receives a matrix of sample values for a processing block, such as a prediction block of 8x8 samples, and the like. The video encoder (603) determines whether the processing block is best coded using intra mode, inter mode, or bi-prediction mode using, for example, rate-distortion optimization. When the processing block is to be coded in intra mode, the video encoder (603) may use an intra prediction technique to encode the processing block into the coded picture; and when the processing block is to be coded in inter mode or bi-prediction mode, the video encoder (603) may use an inter prediction or bi-prediction technique, respectively, to encode the processing block into the coded picture. In certain video coding technologies, merge mode can be an inter picture prediction submode where the MV is derived from one or more MV predictors without the benefit of a coded MV component outside the predictors. In certain other video coding technologies, a MV component applicable to the subject block may be present. In an example, the video encoder (603) includes other components, such as a mode decision module (not shown) to determine the mode of the processing blocks.

[0092] In the FIG. 6 example, the video encoder (603) includes the inter encoder (630), an intra encoder (622), a residue calculator (623), a switch (626), a residue encoder (624), a general controller (621), and an entropy encoder (625) coupled together as shown in FIG. 6.

[0093] The inter encoder (630) is configured to receive the samples of the current block (e.g., a processing block), compare the block to one or more reference blocks in reference pictures (e.g., blocks in previous pictures and later pictures), generate inter prediction information (e.g., description of redundant information according to inter encoding technique, MVs, merge mode information), and calculate inter prediction results (e.g., prediction block) based on the inter prediction information using any suitable technique. In some examples, the reference pictures are decoded reference pictures that are decoded based on the encoded video information.

[0094] The intra encoder (622) is configured to receive the samples of the current block (e.g., a processing block), in some cases compare the block to blocks already coded in the same picture, generate quantized coefficients after transform, and in some cases also intra prediction information (e.g., an intra prediction direction information according to one or more intra encoding techniques). In an example, the intra encoder (622) also calculates intra prediction

results (e.g., prediction block) based on the intra prediction information and reference blocks in the same picture.

[0095] The general controller (621) is configured to determine general control data and control other components of the video encoder (603) based on the general control data. In an example, the general controller (621) determines the mode of the block, and provides a control signal to the switch (626) based on the mode. For example, when the mode is the intra mode, the general controller (621) controls the switch (626) to select the intra mode result for use by the residue calculator (623), and controls the entropy encoder (625) to select the intra prediction information and include the intra prediction information in the bitstream; and when the mode is the inter mode, the general controller (621) controls the switch (626) to select the inter prediction result for use by the residue calculator (623), and controls the entropy encoder (625) to select the inter prediction information and include the inter prediction information in the bitstream.

[0096] The residue calculator (623) is configured to calculate a difference (residue data) between the received block and prediction results selected from the intra encoder (622) or the inter encoder (630). The residue encoder (624) is configured to operate based on the residue data to encode the residue data to generate the transform coefficients. In an example, the residue encoder (624) is configured to convert the residue data from a spatial domain to a frequency domain, and generate the transform coefficients. The transform coefficients are then subject to quantization processing to obtain quantized transform coefficients. In various embodiments, the video encoder (603) also includes a residue decoder (628). The residue decoder (628) is configured to perform inverse-transform, and generate the decoded residue data. The decoded residue data can be suitably used by the intra encoder (622) and the inter encoder (630). For example, the inter encoder (630) can generate decoded blocks based on the decoded residue data and inter prediction information, and the intra encoder (622) can generate decoded blocks based on the decoded residue data and the intra prediction information. The decoded blocks are suitably processed to generate decoded pictures and the decoded pictures can be buffered in a memory circuit (not shown) and used as reference pictures in some examples.

[0097] The entropy encoder (625) is configured to format the bitstream to include the encoded block. The entropy encoder (625) is configured to include various information according to a suitable standard such as HEVC. In an example, the entropy encoder (625) is

configured to include the general control data, the selected prediction information (e.g., intra prediction information or inter prediction information), the residue information, and other suitable information in the bitstream. Note that, according to the disclosed subject matter, when coding a block in the merge submode of either inter mode or bi-prediction mode, there is no residue information.

[0098] FIG. 7 shows a diagram of a video decoder (710) according to another embodiment of the disclosure. The video decoder (710) is configured to receive coded pictures that are part of a coded video bitstream, and decode the coded pictures to generate reconstructed pictures. In an example, the video decoder (710) is used in the place of the video decoder (310) in the FIG. 3 example.

[0099] In the FIG. 7 example, the video decoder (710) includes an entropy decoder (771), an inter decoder (780), a residue decoder (773), a reconstruction module (774), and an intra decoder (772) coupled together as shown in FIG. 7.

[0100] The entropy decoder (771) can be configured to reconstruct, from the coded picture, certain symbols that represent the syntax elements of which the coded picture is made up. Such symbols can include, for example, the mode in which a block is coded (such as, for example, intra mode, inter mode, bi-predicted mode, the latter two in merge submode or another submode), prediction information (such as, for example, intra prediction information or inter prediction information) that can identify certain sample or metadata that is used for prediction by the intra decoder (772) or the inter decoder (780), respectively, residual information in the form of, for example, quantized transform coefficients, and the like. In an example, when the prediction mode is inter or bi-predicted mode, the inter prediction information is provided to the inter decoder (780); and when the prediction type is the intra prediction type, the intra prediction information is provided to the intra decoder (772). The residual information can be subject to inverse quantization and is provided to the residue decoder (773).

[0101] The inter decoder (780) is configured to receive the inter prediction information, and generate inter prediction results based on the inter prediction information.

[0102] The intra decoder (772) is configured to receive the intra prediction information, and generate prediction results based on the intra prediction information.

[0103] The residue decoder (773) is configured to perform inverse quantization to extract de-quantized transform coefficients, and process the de-quantized transform coefficients to convert the residual from the frequency domain to the spatial domain. The residue decoder (773) may also require certain control information (to include the Quantizer Parameter (QP)), and that information may be provided by the entropy decoder (771) (data path not depicted as this may be low volume control information only).

[0104] The reconstruction module (774) is configured to combine, in the spatial domain, the residual as output by the residue decoder (773) and the prediction results (as output by the inter or intra prediction modules as the case may be) to form a reconstructed block, that may be part of the reconstructed picture, which in turn may be part of the reconstructed video. It is noted that other suitable operations, such as a deblocking operation and the like, can be performed to improve the visual quality.

[0105] It is noted that the video encoders (303), (503), and (603), and the video decoders (310), (410), and (710) can be implemented using any suitable technique. In an embodiment, the video encoders (303), (503), and (603), and the video decoders (310), (410), and (710) can be implemented using one or more integrated circuits. In another embodiment, the video encoders (303), (503), and (603), and the video decoders (310), (410), and (710) can be implemented using one or more processors that execute software instructions.

[0106] II. Inter Prediction In VVC

[0107] For each inter-predicted CU, motion parameters can include motion vectors, reference picture indices, reference picture list usage index, and additional information needed for the new coding feature of VVC to be used for inter-predicted sample generation. The motion parameters can be signaled in an explicit or implicit manner. When a CU is coded with a skip mode, the CU can be associated with one PU and does not have significant residual coefficients, coded motion vector delta, or reference picture index. In a merge mode, motion parameters of a CU can be obtained from neighboring CUs, including spatial and temporal candidates, and additional candidates introduced in VVC. The merge mode can be applied to any inter-predicted CU, not only for the skip mode. An alternative to the merge mode is explicit transmission of motion parameters, where motion vector, corresponding reference picture index for each

reference picture list, reference picture list usage flag, and other needed information can be signaled explicitly per each CU.

[0108] Beyond the inter coding features in HEVC, a number of new and refined inter prediction coding tools are introduced in VVC, such as extended merge prediction, merge mode with MVD (MMVD), symmetric MVD (SMVD) signaling, affine motion compensated prediction, subblock-based temporal motion vector prediction (SbTMVP), adaptive motion vector resolution (AMVR), motion field storage (e.g., 1/16th luma sample MV storage and 8x8 motion field compression), bi-prediction with CU-level weight (BCW), bi-directional optical flow (BDOF), decoder side motion vector refinement (DMVR), geometric partitioning mode (GPM), and combined inter and intra prediction (CIIP).

[0109] III. Prediction Structures And Reference Picture Lists

[0110] FIG. 8 shows a graphical representation of a random-access configuration according to an embodiment of the disclosure. For a random-access prediction structure configuration, a hierarchical B structure can be used for encoding. In FIG. 8, a number associated with each picture represents an encoding order. An intra-picture can be encoded at intervals in accordance with an intra-period configuration option or based on other encoder configurations such as scene change detection. The first intra-picture of a video sequence is encoded as an instantaneous decoding refresh (IDR) picture and the other intra pictures can be encoded as non-IDR intra pictures (“Open GOP”). Pictures located between successive intra pictures in a display order can be encoded as B-pictures. An inter-predicted picture (referred to as a ‘Generalized P and B picture’ in FIG. 8 and descriptions below) can be used as the lowest temporal layer that can refer to intra- or inter-pictures for inter prediction. The second and third temporal layers include referenced B pictures, while the highest temporal layer contains non-referenced B picture only. The reference picture list combination can be used for management and entropy coding of the reference picture index.

[0111] FIG. 9 shows a graphical presentation of a low-delay configuration according to an embodiment of the disclosure. A number associated with each picture represents an encoding order.

[0112] Low-delay configurations, including low-delay B and low-delay P, can be used for real-time encoding applications, such as video conferencing, video chatting, live video streaming, and the like.

[0113] For the low-delay coding conditions, only the first picture in a video sequence is encoded as an IDR picture. Subsequent pictures are each encoded using a P-slice for the low-delay P mode or a B-slice for the low-delay B mode. For both modes, the P or B slices only reference pictures preceding a current picture in a display order. For the low-delay B mode, both reference lists RefPicList0 and RefPicList1 are identical.

[0114] In the low-delay B mode, an intra frame is followed by B frames in a temporal order, where each B frame can have up to two reference picture lists. Each inter prediction coding block can use uni-prediction or bi-prediction. The two reference lists, reference list L0 and reference list L1, are identical. When the bi-prediction is used for a coding block, two different previously coded pictures can be referenced, one in each reference list.

[0115] In the low-delay P mode, an intra frame is followed by P frames in a temporal order, where each P frame can only have one reference picture list. Each inter predicted coding block can only use one previously coded picture as a reference picture.

[0116] **IV. Same Reference Picture Constraint**

[0117] Compared with the low-delay P configuration, the low-delay B mode can have the benefit of using bi-prediction coding tools, such as GPM, BCW, and the like. However, the cost of signaling two reference picture lists and two reference picture indices may be expensive for certain applications with bandwidth constraints. On the other hand, two different reference pictures can be used in the low-delay B mode for certain applications. This may cause an error resilience issue when the network is not stable.

[0118] Aspects of this disclosure include methods of reference picture signaling in low delay applications, such as video conferencing, video chatting, live video streaming, and the like. This disclosure includes methods of enabling the inter bi-prediction for low delay use cases with a reduced reference picture signaling cost.

[0119] According to some aspects of the disclosure, an optional constraint that uses a same reference picture for both reference lists in the inter bi-prediction can be added to the low-

delay B mode, in order to alleviate the error resilience issue caused by two different reference pictures in the low-delay B mode and reduce the reference index signaling cost.

[0120] In one embodiment, in the low-delay B configuration, a constraint flag can be signaled, for example at a high level syntax element, to indicate that each inter bi-prediction coded block uses a same reference picture for both predictions. When the constraint flag is enabled, only one reference index is signaled. The signaled reference index corresponds to one of the two reference lists (e.g. reference list 0), and a reference index corresponding to the other reference list (e.g. reference list 1) can be inferred to be equal to the signaled one. For example, when the constraint flag is enabled, reference index signaling for a bi-predicted block may only signal a reference index for one reference list.

[0121] In one embodiment, the constraint flag can be signaled at a sequence level such as in a sequence parameter set and can be referred to as `sps_same_ref_pic_for_bi_prediction`. In an example, when `sps_same_ref_pic_for_bi_prediction` is equal to 1, each inter bi-prediction coded block in a sequence can only use a same reference picture for both reference lists. When reference indices need to be signaled in a bitstream for a bi-prediction coded block, only one reference index is signaled. The signaled reference index can correspond to the reference list 0 (L0) and referred to as `ref_idx_0` for example. A reference index corresponding to the reference list 1 (L1) can be inferred to be equal to `ref_idx_0` and referred to as `ref_idx_1` for example.

[0122] In one embodiment, for merge mode based coding tools, such as regular merge mode, affine merge mode, MMVD, GPM, and the like, when each of a plurality of inter bi-prediction coded blocks uses the same reference picture for both predictions, for example when `sps_same_ref_pic_for_bi_prediction` is equal to 1, a pruning can be applied to remove all bi-prediction candidates that have different reference index values between L0 and L1, in order to reduce a merge index signaling cost.

[0123] In some embodiments, the constraint flag can be signaled at various levels, such as a picture level or a slice level. In one example, the constraint flag signaled in a picture parameter set can be referred to as `pps_same_ref_pic_for_bi_prediction`.

[0124] In one embodiment, the constraint flag can be signaled before a syntax element (e.g., tool on/off flag) for a tool that is configured to reference one future reference picture and one past reference picture. The future reference picture is a picture temporally located after a

current picture in a list of picture order count (POC) identifiers and the past reference picture is a picture temporally located before the current picture in the list of POC identifiers. In one example, when the constraint flag is on (or true), the syntax element (e.g., tool on/off flag) can be inferred to be false without being signaled. Examples of such a tool include DMVR, BDOF, and SMVD.

[0125] According to aspects of the disclosure, the constraint flag can be signaled at various levels, such as an SPS level parameter, a picture level parameter, a slice level parameter, and the like.

[0126] In one embodiment, each of a plurality of inter bi-prediction coded blocks uses the same reference picture for both predictions, for example when `sps_same_ref_pic_for_bi_prediction` is equal to 1, only one of the two reference lists can be signaled. In an example, the other reference list can be inferred to be identical to the signaled reference list.

[0127] According to aspects of the disclosure, an encoder constraint can be applied to an encoder in order to ensure that a same reference picture is used for both reference list L0 and reference list L1 in the inter bi-prediction. Under this constraint, two reference lists L0 and L1 are identical, and two reference indices `ref_index_0` and `ref_index_1` are also identical. In an example, both the two reference indices `ref_index_0` and `ref_index_1` can be signaled to a decoder. Thus, an encoding speed can be increased.

[0128] V. Flowchart

[0129] FIG. 10 shows a flow chart outlining an exemplary process (1000) according to an embodiment of the disclosure. In various embodiments, the process (1000) is executed by processing circuitry, such as the processing circuitry in the terminal devices (210), (220), (230) and (240), the processing circuitry that performs functions of the video encoder (303), the processing circuitry that performs functions of the video decoder (310), the processing circuitry that performs functions of the video decoder (410), the processing circuitry that performs functions of the intra prediction module (452), the processing circuitry that performs functions of the video encoder (503), the processing circuitry that performs functions of the predictor (535), the processing circuitry that performs functions of the intra encoder (622), the processing circuitry that performs functions of the intra decoder (772), and the like. In some embodiments,

the process (1000) is implemented in software instructions, thus when the processing circuitry executes the software instructions, the processing circuitry performs the process (1000).

[0130] The process (1000) may generally start at step (S1010), where the process (1000) decodes prediction information of a current block in a current picture that is a part of a coded video bitstream. The prediction information comprises at least one reference picture index used in low delay inter bi-prediction for the current block. Each of the at least one reference picture index has a same value. Then, the process (1000) proceeds to step (S1020).

[0131] At step (S1020), the process (1000) determines a first reference picture in a first reference picture list and a second reference picture in a second reference picture list for the current block based on the at least one reference picture index included in the prediction information. The current block is coded using the low delay inter bi-prediction. The first reference picture list is identical to the second reference picture list. The first reference picture is identical to the second reference picture. Then, the process (1000) proceeds to step (S1030).

[0132] At step (S1030), the process (1000) reconstructs the current block based on the first reference picture and the second reference picture. Then, the process (1000) terminates.

[0133] In one embodiment, the at least one reference picture index is a single reference picture index associated with one of the first reference picture list and the second reference picture list, and the process (1000) determines the single reference picture index as a reference picture index of the other one of the first reference picture list and the second reference picture list.

[0134] In one embodiment, the prediction information includes a syntax element indicating that for the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list, and the syntax element is included in one of a sequence level parameter, a picture level parameter, and a slice level parameter.

[0135] In one embodiment, based on the current block being coded in one of a plurality of merge modes, each bi-prediction candidate in a merge candidate list of the current block has a same reference picture index for the first reference picture list and the second reference picture list. The plurality of merge modes includes a regular merge mode, an affine merge mode, a merge mode with motion vector difference, an advanced motion vector prediction, and a geometric partitioning mode

[0136] In one embodiment, the process (1000) determines that a tool configured to reference a reference picture temporally located after the current picture is disabled based on the prediction information indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list.

[0137] In one embodiment, the prediction information includes one of the first reference picture list and the second reference picture list.

[0138] In one embodiment, the at least one reference picture index includes two identical reference picture indices, and the prediction information includes the first reference picture list, the second reference picture list, and the two identical reference picture indices.

[0139] VI. Computer System

[0140] The techniques described above, can be implemented as computer software using computer-readable instructions and physically stored in one or more computer-readable media. For example, FIG. 11 shows a computer system (1100) suitable for implementing certain embodiments of the disclosed subject matter.

[0141] The computer software can be coded using any suitable machine code or computer language, that may be subject to assembly, compilation, linking, or like mechanisms to create code comprising instructions that can be executed directly, or through interpretation, micro-code execution, and the like, by one or more computer central processing units (CPUs), Graphics Processing Units (GPUs), and the like.

[0142] The instructions can be executed on various types of computers or components thereof, including, for example, personal computers, tablet computers, servers, smartphones, gaming devices, internet of things devices, and the like.

[0143] The components shown in FIG. 11 for computer system (1100) are exemplary in nature and are not intended to suggest any limitation as to the scope of use or functionality of the computer software implementing embodiments of the present disclosure. Neither should the configuration of components be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary embodiment of a computer system (1100).

[0144] Computer system (1100) may include certain human interface input devices. Such a human interface input device may be responsive to input by one or more human users

through, for example, tactile input (such as: keystrokes, swipes, data glove movements), audio input (such as: voice, clapping), visual input (such as: gestures), olfactory input (not depicted). The human interface devices can also be used to capture certain media not necessarily directly related to conscious input by a human, such as audio (such as: speech, music, ambient sound), images (such as: scanned images, photographic images obtain from a still image camera), video (such as two-dimensional video, three-dimensional video including stereoscopic video).

[0145] Input human interface devices may include one or more of (only one of each depicted): keyboard (1101), mouse (1102), trackpad (1103), touch screen (1110), data-glove (not shown), joystick (1105), microphone (1106), scanner (1107), and camera (1108).

[0146] Computer system (1100) may also include certain human interface output devices. Such human interface output devices may be stimulating the senses of one or more human users through, for example, tactile output, sound, light, and smell/taste. Such human interface output devices may include tactile output devices (for example tactile feedback by the touch-screen (1110), data-glove (not shown), or joystick (1105), but there can also be tactile feedback devices that do not serve as input devices), audio output devices (such as: speakers (1109), headphones (not depicted)), visual output devices (such as screens (1110) to include CRT screens, LCD screens, plasma screens, OLED screens, each with or without touch-screen input capability, each with or without tactile feedback capability—some of which may be capable to output two dimensional visual output or more than three dimensional output through means such as stereographic output; virtual-reality glasses (not depicted), holographic displays and smoke tanks (not depicted)), and printers (not depicted). These visual output devices (such as screens (1110)) can be connected to a system bus (1148) through a graphics adapter (1150).

[0147] Computer system (1100) can also include human accessible storage devices and their associated media such as optical media including CD/DVD ROM/RW (1120) with CD/DVD or the like media (1121), thumb-drive (1122), removable hard drive or solid state drive (1123), legacy magnetic media such as tape and floppy disc (not depicted), specialized ROM/ASIC/PLD based devices such as security dongles (not depicted), and the like.

[0148] Those skilled in the art should also understand that term “computer readable media” as used in connection with the presently disclosed subject matter does not encompass transmission media, carrier waves, or other transitory signals.

[0149] Computer system (1100) can also include a network interface (1154) to one or more communication networks (1155). The one or more communication networks (1155) can for example be wireless, wireline, optical. The one or more communication networks (1155) can further be local, wide-area, metropolitan, vehicular and industrial, real-time, delay-tolerant, and so on. Examples of the one or more communication networks (1155) include local area networks such as Ethernet, wireless LANs, cellular networks to include GSM, 3G, 4G, 5G, LTE and the like, TV wireline or wireless wide area digital networks to include cable TV, satellite TV, and terrestrial broadcast TV, vehicular and industrial to include CANBus, and so forth. Certain networks commonly require external network interface adapters that attached to certain general purpose data ports or peripheral buses (1149) (such as, for example USB ports of the computer system (1100)); others are commonly integrated into the core of the computer system (1100) by attachment to a system bus as described below (for example Ethernet interface into a PC computer system or cellular network interface into a smartphone computer system). Using any of these networks, computer system (1100) can communicate with other entities. Such communication can be uni-directional, receive only (for example, broadcast TV), uni-directional send-only (for example CANbus to certain CANbus devices), or bi-directional, for example to other computer systems using local or wide area digital networks. Certain protocols and protocol stacks can be used on each of those networks and network interfaces as described above.

[0150] Aforementioned human interface devices, human-accessible storage devices, and network interfaces can be attached to a core (1140) of the computer system (1100).

[0151] The core (1140) can include one or more Central Processing Units (CPU) (1141), Graphics Processing Units (GPU) (1142), specialized programmable processing units in the form of Field Programmable Gate Areas (FPGA) (1143), hardware accelerators for certain tasks (1144), graphics adapters (1150), and so forth. These devices, along with Read-only memory (ROM) (1145), Random-access memory (1146), internal mass storage (1147) such as internal non-user accessible hard drives, SSDs, and the like, may be connected through the system bus (1148). In some computer systems, the system bus (1148) can be accessible in the form of one or more physical plugs to enable extensions by additional CPUs, GPU, and the like. The peripheral devices can be attached either directly to the core's system bus (1148), or through a

peripheral bus (1149). In an example, the screen (1110) can be connected to the graphics adapter (1150). Architectures for a peripheral bus include PCI, USB, and the like.

[0152] CPUs (1141), GPUs (1142), FPGAs (1143), and accelerators (1144) can execute certain instructions that, in combination, can make up the aforementioned computer code. That computer code can be stored in ROM (1145) or RAM (1146). Transitional data can be also be stored in RAM (1146), whereas permanent data can be stored for example, in the internal mass storage (1147). Fast storage and retrieve to any of the memory devices can be enabled through the use of cache memory, that can be closely associated with one or more CPU (1141), GPU (1142), mass storage (1147), ROM (1145), RAM (1146), and the like.

[0153] The computer readable media can have computer code thereon for performing various computer-implemented operations. The media and computer code can be those specially designed and constructed for the purposes of the present disclosure, or they can be of the kind well known and available to those having skill in the computer software arts.

[0154] As an example and not by way of limitation, the computer system having architecture (1100), and specifically the core (1140) can provide functionality as a result of processor(s) (including CPUs, GPUs, FPGA, accelerators, and the like) executing software embodied in one or more tangible, computer-readable media. Such computer-readable media can be media associated with user-accessible mass storage as introduced above, as well as certain storage of the core (1140) that are of non-transitory nature, such as core-internal mass storage (1147) or ROM (1145). The software implementing various embodiments of the present disclosure can be stored in such devices and executed by core (1140). A computer-readable medium can include one or more memory devices or chips, according to particular needs. The software can cause the core (1140) and specifically the processors therein (including CPU, GPU, FPGA, and the like) to execute particular processes or particular parts of particular processes described herein, including defining data structures stored in RAM (1146) and modifying such data structures according to the processes defined by the software. In addition or as an alternative, the computer system can provide functionality as a result of logic hardwired or otherwise embodied in a circuit (for example: accelerator (1144)), which can operate in place of or together with software to execute particular processes or particular parts of particular processes described herein. Reference to software can encompass logic, and vice versa, where

appropriate. Reference to a computer-readable media can encompass a circuit (such as an integrated circuit (IC)) storing software for execution, a circuit embodying logic for execution, or both, where appropriate. The present disclosure encompasses any suitable combination of hardware and software.

[0155] While this disclosure has described several exemplary embodiments, there are alterations, permutations, and various substitute equivalents, which fall within the scope of the disclosure. It will thus be appreciated that those skilled in the art will be able to devise numerous systems and methods which, although not explicitly shown or described herein, embody the principles of the disclosure and are thus within the spirit and scope thereof.

Appendix A: Acronyms

ALF: Adaptive Loop Filter

AMVP: Advanced Motion Vector Prediction

APS: Adaptation Parameter Set

ASIC: Application-Specific Integrated Circuit

ATMVP: Alternative/Advanced Temporal Motion Vector Prediction

AV1: AOMedia Video 1

AV2: AOMedia Video 2

BMS: Benchmark Set

BV: Block Vector

CANBus: Controller Area Network Bus

CB: Coding Block

CC-ALF: Cross-Component Adaptive Loop Filter

CD: Compact Disc

CDEF: Constrained Directional Enhancement Filter

CPR: Current Picture Referencing

CPU: Central Processing Unit

CRT: Cathode Ray Tube

CTB: Coding Tree Block

CTU: Coding Tree Unit
CU: Coding Unit
DPB: Decoder Picture Buffer
DPCM: Differential Pulse-Code Modulation
DPS: Decoding Parameter Set
DVD: Digital Video Disc
FPGA: Field Programmable Gate Area
JCCR: Joint CbCr Residual Coding
JVET: Joint Video Exploration Team
GOP: Groups of Pictures
GPU: Graphics Processing Unit
GSM: Global System for Mobile communications
HDR: High Dynamic Range
HEVC: High Efficiency Video Coding
HRD: Hypothetical Reference Decoder
IBC: Intra Block Copy
IC: Integrated Circuit
ISP: Intra Sub-Partitions
JEM: Joint Exploration Model
LAN: Local Area Network
LCD: Liquid-Crystal Display
LR: Loop Restoration Filter
LRU: Loop Restoration Unit
LTE: Long-Term Evolution
MPM: Most Probable Mode
MV: Motion Vector
OLED: Organic Light-Emitting Diode
PBs: Prediction Blocks
PCI: Peripheral Component Interconnect
PDPC: Position Dependent Prediction Combination

PLD: Programmable Logic Device
PPS: Picture Parameter Set
PU: Prediction Unit
RAM: Random Access Memory
ROM: Read-Only Memory
SAO: Sample Adaptive Offset
SCC: Screen Content Coding
SDR: Standard Dynamic Range
SEI: Supplementary Enhancement Information
SNR: Signal Noise Ratio
SPS: Sequence Parameter Set
SSD: Solid-state Drive
TU: Transform Unit
USB: Universal Serial Bus
VPS: Video Parameter Set
VUI: Video Usability Information
VVC: Versatile Video Coding
WAIP: Wide-Angle Intra Prediction

WHAT IS CLAIMED IS:

1. A method of video decoding in a decoder, comprising:
decoding prediction information of a current block in a current picture that is a part of a coded video bitstream, the prediction information comprising at least one reference picture index used in low delay inter bi-prediction for the current block, each of the at least one reference picture index having a same value;
determining a first reference picture in a first reference picture list and a second reference picture in a second reference picture list for the current block based on the at least one reference picture index included in the prediction information, the current block being coded using the low delay inter bi-prediction, the first reference picture list being identical to the second reference picture list, and the first reference picture being identical to the second reference picture; and
reconstructing the current block based on the first reference picture and the second reference picture.
2. The method of claim 1, wherein the at least one reference picture index is a single reference picture index associated with one of the first reference picture list and the second reference picture list, and the determining includes determining the single reference picture index as a reference picture index of the other one of the first reference picture list and the second reference picture list.
3. The method of claim 1, wherein the prediction information includes a syntax element indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list, the syntax element being included in one of a sequence level parameter, a picture level parameter, and a slice level parameter.
4. The method of claim 1, wherein based on the current block being coded in one of a plurality of merge modes, each bi-prediction candidate in a merge candidate list of the current block has a same reference picture index for the first reference picture list and the second reference picture list, the plurality of merge modes includes a regular merge mode, an affine

merge mode, a merge mode with motion vector difference, an advanced motion vector prediction, and a geometric partitioning mode.

5. The method of claim 1, further comprising:

determining that a tool configured to reference a reference picture temporally located after the current picture is disabled based on the prediction information indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list.

6. The method of claim 1, wherein the prediction information includes one of the first reference picture list and the second reference picture list.

7. The method of claim 1, wherein the at least one reference picture index includes two identical reference picture indices, and the prediction information includes the first reference picture list, the second reference picture list, and the two identical reference picture indices.

8. An apparatus, comprising processing circuitry configured to:

decode prediction information of a current block in a current picture that is a part of a coded video bitstream, the prediction information comprising at least one reference picture index used in low delay inter bi-prediction for the current block, each of the at least one reference picture index having a same value;

determine a first reference picture in a first reference picture list and a second reference picture in a second reference picture list for the current block based on the at least one reference picture index included in the prediction information, the current block being coded using the low delay inter bi-prediction, the first reference picture list being identical to the second reference picture list, and the first reference picture being identical to the second reference picture; and

reconstruct the current block based on the first reference picture and the second reference picture.

9. The apparatus of claim 8, wherein the at least one reference picture index is a single reference picture index associated with one of the first reference picture list and the second reference picture list, and the processing circuitry is further configured to:

determine the single reference picture index as a reference picture index of the other one of the first reference picture list and the second reference picture list.

10. The apparatus of claim 8, wherein the prediction information includes a syntax element indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list, the syntax element being included in one of a sequence level parameter, a picture level parameter, and a slice level parameter.

11. The apparatus of claim 8, wherein based on the current block being coded in one of a plurality of merge modes, each bi-prediction candidate in a merge candidate list of the current block has a same reference picture index for the first reference picture list and the second reference picture list, the plurality of merge modes includes a regular merge mode, an affine merge mode, a merge mode with motion vector difference, an advanced motion vector prediction, and a geometric partitioning mode.

12. The apparatus of claim 8, wherein the processing circuitry is further configured to:

determine that a tool configured to reference a reference picture temporally located after the current picture is disabled based on the prediction information indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list.

13. The apparatus of claim 8, wherein the prediction information includes one of the first reference picture list and the second reference picture list.

14. The apparatus of claim 8, wherein the at least one reference picture index includes two identical reference picture indices, and the prediction information includes the first reference picture list, the second reference picture list, and the two identical reference picture indices.

15. A non-transitory computer-readable storage medium storing instructions which when executed by at least one processor cause the at least one processor to perform:

decoding prediction information of a current block in a current picture that is a part of a coded video bitstream, the prediction information comprising at least one reference picture index used in low delay inter bi-prediction for the current block, each of the at least one reference picture index having a same value;

determining a first reference picture in a first reference picture list and a second reference picture in a second reference picture list for the current block based on the at least one reference picture index included in the prediction information, the current block being coded using the low delay inter bi-prediction, the first reference picture list being identical to the second reference picture list, and the first reference picture being identical to the second reference picture; and

reconstructing the current block based on the first reference picture and the second reference picture.

16. The non-transitory computer-readable storage medium of claim 15, wherein the at least one reference picture index is a single reference picture index associated with one of the first reference picture list and the second reference picture list, and the stored instructions cause the at least one processor to perform:

determining the single reference picture index as a reference picture index of the other one of the first reference picture list and the second reference picture list.

17. The non-transitory computer-readable storage medium of claim 15, wherein the prediction information includes a syntax element indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list, the syntax element being included in one of a sequence level parameter, a picture level parameter, and a slice level parameter.

18. The non-transitory computer-readable storage medium of claim 15, wherein based on the current block being coded in one of a plurality of merge modes, each bi-prediction candidate in a

merge candidate list of the current block has a same reference picture index for the first reference picture list and the second reference picture list, the plurality of merge modes includes a regular merge mode, an affine merge mode, a merge mode with motion vector difference, an advanced motion vector prediction, and a geometric partitioning mode.

19. The non-transitory computer-readable storage medium of claim 15, wherein the stored instructions cause the at least one processor to perform:

determining that a tool configured to reference a reference picture temporally located after the current picture is disabled based on the prediction information indicating that the first reference picture in the first reference picture list is identical to the second reference picture in the second reference picture list.

20. The non-transitory computer-readable storage medium of claim 15, wherein the prediction information includes one of the first reference picture list and the second reference picture list.

	R01	R02	R03	R04	R05	R06	R07	R08	R09
R10	<u>S11</u>	S12	S13	S14					
<u>R20</u>	S21	<u>S22</u>	S23	<u>S24</u>					
R30	S31	<u>S32</u>	S33	S34					
R40	<u>S41</u>	S42	S43	<u>S44</u>					
R50									
<u>R60</u>									
R70									

104





FIG. 1A

(Related Art)




FIG. 1B
(Related Art)




FIG. 1C
(Related Art)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2021/062691

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - H04N 19/176; H04N 7/12; H04N 19/103; H04N 19/112; H04N 19/119 (2022.01)
 CPC - H04N 19/176; H04N 19/61; H04N 19/103; H04N 19/112; H04N 19/119 (2022.02)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 see Search History document

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
 see Search History document

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
 see Search History document

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO:2020/185466 A1 (TENCENT AMERICA LLC) 17 September 2020 (17.09.2020) entire document	1-20
A	US 2021/0037256 A1 (BEIJING BYTEDANCE NETWORK TECHNOLOGY CO., LTD. et al) 04 February 2021 (04.02.2021) entire document	1-20
A	US 2013/0336407 A1 (QUALCOMM INCORPORATED) 19 December 2013 (19.12.2013) entire document	1-20
A	GIROD et al. "Distributed video coding." Proceedings of the IEEE 93.1 (2005): 71-83. 27 June 2005 (27.06.2005) Retrieved on 04 February 2022 (04.02.2022) from <https://ieeexplore.ieee.org/abstract/document/1369699> entire document	1-20
A	US 9,807,423 B1 (GOOGLE INC.) 31 October 2017 (31.10.2017) entire document	1-20
A	US 2004/0008784 A1 (KIKUCHI et al) 15 January 2004 (15.01.2004) entire document	1-20

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"D" document cited by the applicant in the international application	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"E" earlier application or patent but published on or after the international filing date	"&" document member of the same patent family
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

11 February 2022

Date of mailing of the international search report

MAR 01 2022

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
 P.O. Box 1450, Alexandria, VA 22313-1450
 Facsimile No. 571-273-8300

Authorized officer

Harry Kim

Telephone No. PCT Helpdesk: 571-272-4300