

(12) UK Patent Application (19) GB (11) 2 132 452 A

(21) Application No 8234993

(22) Date of filing 8 Dec 1982

(43) Application published
4 Jul 1984

(51) INT CL³
H04B 17/00

(52) Domestic classification
H4L M

(56) Documents cited
None

(58) Field of search
H4L

(71) Applicant
Racal-Ses Limited
(United Kingdom),
Western Road, Bracknell,
Berkshire


(72) Inventors
Michael Naylor,
David Brash

(74) Agent and/or Address for
Service
Mathisen Macara & Co.,
Lyon House, Lyon Road,
Harrow, Middlesex
HA1 2ET

(54) Radio systems

(57) A radio system employs a method of controlling the transmitted power of a radio signal such that a minimum power level for efficient reception is maintained. Data is simultaneously transmitted between two radio stations (10, 20) using an error correction code. Each block of the code is accompanied by a power bit. The transmitted power bit is set

high or low in dependence upon whether the number of errors in a sample of received blocks, as determined by processing of the received code, is equal to, above or below a predetermined threshold value. At the other station the received power bit is directed to a power control device (18) and used to adjust the output power of the transmitter of that station by continuously variable slope delta demodulation.



GB 2 132 452 A

///




FIG. 1.




FIG. 2.

SPECIFICATION

Radio systems

The present invention relates to radio systems and, more specifically, to radio systems adapted to operate at a minimum effective power transmission level. The invention also relates to methods of controlling the transmitted power of a radio signal.

In order to provide maximum security against reception of a transmitted signal by an unauthorised third party, it is desirable to use the lowest possible transmission power that enables effective reception to be achieved at the desired receiving station. During a normal radio transmission there may occur transient losses in signal strength which are known as "fading". Such fading may arise from cancellation of one incoming wave with another which has travelled from the transmitting radio by a different path. Therefore it is not sufficient merely to set the transmitted power level at a suitable minimum value, as any fading during transmission will cause errors at the receiving station.

Accordingly, the present invention provides a radio system for simultaneous digital communications between two radio stations using data blocks each of which includes a plurality of message bits and at least one non-message bit, each radio station including means for monitoring transmission received from the other radio station and setting the or one non-message bit to be transmitted by the receiving station to the transmitting station to indicate to the transmitting station whether the transmitted signal power is to be increased or decreased to maintain reception, and means at each station for sensing the setting of said non-message bit to adjust the power of the transmitted signal.

The invention further provides a method, for use in a radio system wherein two radio stations are transmitting to each other, of controlling the transmitted power of a radio signal such that a minimum power level to ensure efficient reception is maintained, comprising the steps of detecting at each station the error level in the received transmission from the other station and periodically transmitting to the other station an indication of whether the transmitted power should be increased or decreased in dependence on whether the error level detected immediately prior to transmission of said indication was above or below a predetermined threshold value respectively.

An embodiment of the invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:

Figure 1 represents a radio system in accordance with the present invention; and

Figure 2 represents a block of an error correction code for use in the radio system of Figure 1.

The radio system illustrated schematically in Figure 1 comprises a pair of radio stations 10 and

20 which are capable of simultaneous transmission to each other. The transmission path from the transmitter of radio station 10 to the receiver of radio station 20 is denoted by the line 12 and, similarly, the transmission path from the transmitter of radio station 20 to the receiver at radio station 10 is denoted by the line 14.

The radios 10, 20 may employ any appropriate modulation technique for transmitting digital data in a block format. The radios may employ a static carrier frequency or use a spread spectrum technique. The spread spectrum technique described in our co-pending Patent Application No. 82. may advantageously be used with the present power control technique.

Signals are transmitted between the radio stations 10 and 20 in digital form using an error correcting code, for example a (7,4,1) code. In such an error correcting code the data is transmitted in blocks which may be separated and defined by appropriate synchronisation signals. A typical block as used for transmission in the present system is illustrated in Figure 2. This block consists of eight data bit positions of which the first seven are taken up with any conventional (7,4,1) error correcting code. In such a code the first four bit positions may be regarded as message bits, whilst the following three bits introduce sufficient redundancy to enable the presence of up to one error in the transmitted seven data bit block to be detected. Any suitable technique can be used for converting a message to be transmitted into a digital data stream which is encoded with the selected (7,4,1) error correcting code and transmitted as the first seven bits of each block. At the receiving station the first seven data bits of a received block are decoded by, for example, comparing with the contents of a stored look-up table. During the decoding process it is possible to determine whether there has been one error in transmission of the code block.

Data bit position 8 is taken up by a power bit which is set in dependence on the error level detected in a sample of data received by the transmitting station from the receiving station. This power bit is a feed back signal which enables the station to alter its transmitted power in dependence on the error level in the transmission as received by the other station. The value of the power bit is determined by the error level in a sample of received blocks taken over a time interval of, say, one millisecond. The number of blocks received in such a time interval will clearly vary in dependence on the transmission rate. Assuming that the transmission rate is such that sixteen complete blocks are received in the selected sampling time interval, then if the error level in those sixteen blocks, as determined by the decoding of the data transmitted using the (7,4,1) error correcting code in the receiver, is above a preset error threshold, the power bit to be transmitted in the next sixteen blocks transmitted by the receiving station will be set high. If the detected error level is below the threshold the power bits transmitted in those blocks will be set

low and, if the error level falls exactly on the error threshold, then the power bits of the next sixteen blocks can be set alternately high and low. It will be appreciated that the power bit in a transmitted block relates not to the error level in the transmission in which it is contained but the transmission being received from the other radio station by the station transmitting the power bit.

Both radio stations 10 and 20 include a power bit sensor 16. This power bit sensor detects whether the power bit at position 8 in each received block is a 0 or a 1. The power bit sensor is coupled to a power control device 18, the device 18 sets the transmitted output power from the radio transmitter, if the received power bit is high then the power control device operates to increase the transmitted power level. The power control device 18 is preferably a continuously variable slope delta demodulator which operates so as to continuously change the output power, the received power bit being utilised to govern the rate of change. Thus if the received power bit is 0, indicative of the error level in a sample received by the other radio station being below the threshold, the power control device 18 operates either to increase the rate by which the output power is falling if the previously received power bit was also 0, or, if the previous power bit was 1 and so the output power was increasing, to cause the output power to start to fall. It will be appreciated that the amounts by which the rate of change of output power may be varied in particular conditions can be selected in dependence on the characteristics of the fading which is to be tracked.

If the two radio stations 10, 20 are, for example, 30 kilometers apart, the transmission time between them will be approximately 100 microseconds. Therefore there will be a time delay of approximately 1 millisecond plus 200 microseconds between the time when the blocks making up a sample are transmitted from one radio station and the power bit which provides an indication of whether the error level in the received sample is above or below the threshold value, is received in a block transmitted from the other radio station to the originating radio station.

Typically, fading of a transmitted signal may occur at a rate of the order of 50 times a second. Therefore the duration of a signal fade will be approximately 20 milliseconds. With the above mentioned delay between the error sampling and the time the power bit is returned to the transmitter to enable satisfactory restoration of the minimum power level, it is readily possible to track a fade which has a duration of 20 milliseconds with the present system. In a typical fade the rate of attenuation may rapidly increase particularly towards the point of maximum attenuation of the fade. For this reason it is desirable to use the above mentioned continuously variable slope delta modulation.

The block format which has been illustrated in Figure 2 is not the only one suitable for use in the present system. In particular, it is possible to

employ any type of error correcting code that enables the error level in a sample to be monitored. Moreover the particular order of the data bit positions illustrated is not essential. For example the bit positions may be rotated in each successive block so that the bit position occupied by the power bit is moved by one place in each successive block. Alternatively the bit positions could be 'shuffled' in accordance with a predetermined pseudorandom sequence between successive blocks.

It will be further be appreciated that, although a sixteen block sampling system has been described, any suitable sample size may be employed, provided only that the returned power bit is representative of the received error level. Additionally it would also be possible to employ overlapping samples of blocks so as to prevent too large a number of identical power bits being transmitted.

CLAIMS

1. A radio system for simultaneous digital communications between two radio stations using data blocks each of which includes a plurality of message bits and at least one non-message bit, each radio station including means for monitoring the transmission received from the other radio station and setting the or one non-message bit to be transmitted by the receiving station to the transmitting station to indicate to the transmitting station whether the transmitted signal power is to be increased or decreased to maintain reception, and means at each station for sensing the setting of said non-message bit to adjust the power of the transmitted signal.

2. A system as claimed in Claim 1, wherein each data block comprises a plurality of bits which make up an error correcting code adapted to detect the presence of at least one error in said received plurality of bits in each block, said monitoring means comprising means for utilising said code to determine the error level in a sample of the received blocks in relation to a predetermined threshold value and setting said one non-message bit of a block to be transmitted from the receiving station to a value to indicate that the transmitted signal power is to be increased if the error level exceeds said predetermined threshold value.

3. A system as claimed in claim 2, wherein said error correcting code is a (7,4,1) code.

4. A system as claimed in any one of the preceding claims, wherein the sensing means employs a continuously variable slope delta demodulator to determine the rate at which the transmitted power is to be adjusted in dependence on the setting of the received non-message bits.

5. A method for use in a radio system wherein two radio stations are transmitting to each other, of controlling the transmitted power of a radio signal such that a minimum power level to ensure efficient reception is maintained, comprising the steps of detecting at each station the error level in

the received transmission from the other station and periodically transmitting to the other station an indication of whether the transmitted power should be increased or decreased in dependence
5 on whether the error level detected immediately prior to transmission of said indication was above or below a predetermined value respectively.

6. A method as claimed in Claim 5, wherein digital signals are transmitted between the
10 stations using an error correcting code, each block of said code being accompanied by a bit which is set to provide said indication.

7. A method as claimed in Claim 5 or 6,

wherein the rate and sense of the change in
15 transmitted power is determined by the received indications.

8. A radio system substantially as herein described with reference to the accompanying drawings.

20 9. A method for use in a radio system wherein two radio stations are transmitting to each other, of controlling the transmitted power of a radio signal such that a minimum power level to ensure efficient reception is maintained substantially as
25 herein described with reference to the accompanying drawings.