## UK Patent Application (19) GB (11) 2474201

(43) Date of Reproduction by UK Office

06.04.2011

(21) Application No:

1102127.6

(22) Date of Filing:

14.07.2009

(30) Priority Data:

(31) 12173516

(32) 14.07.2008

(33) US

(86) International Application Data:

PCT/IB2009/053051 En 14.07.2009

(87) International Publication Data: WO2010/007583 En 21.01.2010

(71) Applicant(s):

Kimberly-Clark Worldwide, Inc. 401 North Lake Street, Neenah, WI 54956, **United States of America** 

(72) Inventor(s):

Thomas William Van Den Bogart Cao Hue Chi Pham Yeln Sze Ong Franz Aschenbrenner **Dusan Pavlik Gary M Mastalish** Irina Tsareva Lynn Ann Weggel Anastasia Barlas Priscilla Eng Choo Goh **EunJung Kang** 

(continued on next page)

(51) INT CL:

A61F 13/26 (2006.01) **A61F 13/30** (2006.01)

A61F 13/20 (2006.01) **A61F 13/32** (2006.01)

(56) Documents Cited by ISA: US 5158535 A


US 20040199102 A1

US 20050070839 A1 US 20040054317 A1

(58) Field of Search by ISA: INT CL A61F Other: eKipass

(54) Title of the Invention: Tampon applicator Abstract Title: Tampon applicator

(57) In a tampon applicator, an elongated barrel has an interior chamber for housing a tampon therein, a grip region generally adjacent an outer end of the barrel, a tip region generally adjacent an inner end of the barrel, and a central region extending longitudinally between the grip region and the tip region. A plunger extends into the barrel at the outer end thereof and is moveable relative to the barrel to expel the tampon from the barrel at its inner end. The outer surface of the barrel at the grip region has a different coefficient of friction than at the central region of the barrel. In other embodiments the coefficient of friction of the barrel outer surface at the central region is different from the coefficient of friction at the tip region.



## GB 2474201 A continuation

(74) Agent and/or Address for Service:
Dehns
St. Bride's House, 10 Salisbury Square, LONDON, EC4Y 8JD, United Kingdom