

(12) **United States Patent**
Cooke et al.

(10) **Patent No.:** **US 11,686,888 B1**
(45) **Date of Patent:** ***Jun. 27, 2023**

- (54) **OPTICAL LENS ASSEMBLIES, HEAD-MOUNTED DISPLAYS, AND RELATED METHODS**
- (71) Applicant: **META PLATFORMS TECHNOLOGIES, LLC**, Menlo Park, CA (US)
- (72) Inventors: **John Cooke**, Bothell, WA (US); **Katherine Marie Smyth**, Seattle, WA (US); **Andrew John Ouderkirk**, Kirkland, WA (US)
- (73) Assignee: **Meta Platforms Technologies, LLC**, Menlo Park, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 213 days.
This patent is subject to a terminal disclaimer.
- (21) Appl. No.: **17/180,194**
- (22) Filed: **Feb. 19, 2021**

Related U.S. Application Data

- (63) Continuation of application No. 16/021,580, filed on Jun. 28, 2018, now Pat. No. 10,928,558.
(Continued)
- (51) **Int. Cl.**
G02B 3/14 (2006.01)
G02C 7/06 (2006.01)
(Continued)
- (52) **U.S. Cl.**
CPC **G02B 3/14** (2013.01); **G02B 3/12** (2013.01); **G02B 26/06** (2013.01);
(Continued)

- (58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

60,109 A 11/1866 Woodward
3,571,555 A 3/1971 Townes et al.
(Continued)

FOREIGN PATENT DOCUMENTS

KR 10-2011-0107812 A 10/2011
KR 101675093 B1 11/2016
(Continued)

OTHER PUBLICATIONS


Non-Final Office Action received for U.S. Appl. No. 16/013,837 dated Jan. 23, 2020, 22 pages.
(Continued)

Primary Examiner — Jennifer D. Carruth
(74) *Attorney, Agent, or Firm* — Greenberg Traurig, LLP

(57) **ABSTRACT**

The disclosed optical lens assemblies may include a deformable element, a structural support element, a substantially transparent deformable medium positioned between the deformable element and the structural support element, a compliant peripheral component positioned between peripheral portions of the deformable element and the structural support element, and an actuator configured to displace at least a portion of the compliant peripheral component to deform the deformable element and change at least one optical property of the optical lens assembly. Related head-mounted displays and methods of fabricating such optical lens assemblies are also disclosed.

20 Claims, 12 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 62/650,254, filed on Mar. 29, 2018.
- (51) **Int. Cl.**
G02B 27/01 (2006.01)
G02B 26/06 (2006.01)
G02B 3/12 (2006.01)
G02F 1/1362 (2006.01)
G02B 26/08 (2006.01)
- (52) **U.S. Cl.**
 CPC *G02B 26/0875* (2013.01); *G02B 27/017* (2013.01); *G02B 27/0172* (2013.01); *G02C 7/06* (2013.01); *G02F 1/136277* (2013.01); *G02B 2027/011* (2013.01); *G02B 2027/0107* (2013.01); *G02B 2027/0178* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,797,922	A	3/1974	Plummer	
4,477,158	A	10/1984	Pollock et al.	
5,154,862	A	10/1992	Reagan et al.	
5,225,244	A	7/1993	Aharoni et al.	
5,663,779	A	9/1997	Karasawa	
5,956,183	A	9/1999	Epstein et al.	
6,081,388	A	6/2000	Widl	
6,420,441	B1	7/2002	Allen et al.	
6,918,670	B2	7/2005	Blum et al.	
7,008,054	B1	3/2006	Kurtin et al.	
7,118,219	B2	10/2006	Itagaki	
7,125,508	B2	10/2006	Ide et al.	
7,864,440	B2	1/2011	Berge	
7,866,816	B2	1/2011	Kurtin	
8,210,678	B1	7/2012	Farwig	
8,441,737	B2	5/2013	Buch et al.	
9,292,085	B2	3/2016	Bennett et al.	
10,187,568	B1	1/2019	Tran et al.	
10,409,089	B2	9/2019	Pugh et al.	
10,698,224	B1	6/2020	Cooke et al.	
10,754,145	B1	8/2020	Ouderkirk et al.	
10,881,287	B1	1/2021	Ouderkirk et al.	
10,928,558	B1*	2/2021	Cooke G02B 26/06	
10,928,656	B1	2/2021	Smyth et al.	
10,962,791	B1	3/2021	Ouderkirk et al.	
11,011,739	B1	5/2021	Ouderkirk et al.	
11,048,075	B1	6/2021	Ouderkirk et al.	
2003/0003295	A1	1/2003	Dreher et al.	
2003/0054115	A1	3/2003	Albano et al.	
2003/0067245	A1	4/2003	Pelrine et al.	
2003/0083433	A1	5/2003	James et al.	
2003/0128496	A1	7/2003	Allen et al.	
2004/0096672	A1	5/2004	Lukas et al.	
2006/0024976	A1	2/2006	Waldfried et al.	
2006/0073424	A1	4/2006	Koveshnikov et al.	
2006/0228092	A1	10/2006	Hebrink et al.	
2006/0247404	A1	11/2006	Todd	
2007/0035839	A1	2/2007	Ibuki	
2008/0038561	A1	2/2008	Yoshizawa et al.	
2008/0049431	A1	2/2008	Boek et al.	
2008/0084532	A1	4/2008	Kurtin	
2008/0088793	A1	4/2008	Sverdrup et al.	
2008/0123049	A1	5/2008	Volk	
2008/0144185	A1	6/2008	Wang et al.	
2008/0170299	A1	7/2008	Kawabata	
2008/0171431	A1	7/2008	Yu et al.	
2008/0290435	A1	11/2008	Oliver et al.	
2008/0291394	A1	11/2008	Ishak	
2009/0015786	A1	1/2009	Harris	
2009/0027778	A1	1/2009	Wu et al.	
2009/0096106	A1	4/2009	Vrtis et al.	
2009/0289529	A1	11/2009	Ito et al.	
2009/0304924	A1	12/2009	Gadgil	
2010/0075056	A1	3/2010	Axisa et al.	

2010/0109486	A1	5/2010	Polyakov et al.
2010/0168409	A1	7/2010	Fujita
2010/0202054	A1	8/2010	Niederer
2010/0238400	A1	9/2010	Volk
2011/0075096	A1	3/2011	Ishak et al.
2011/0085131	A1	4/2011	Gupta et al.
2011/0096411	A1	4/2011	Henriksen et al.
2011/0149410	A1	6/2011	Blum
2011/0176105	A1	7/2011	Harris
2011/0179861	A1	7/2011	Grange et al.
2011/0235326	A1	9/2011	Yeh et al.
2011/0294305	A1	12/2011	Jacobs et al.
2012/0029416	A1	2/2012	Parker et al.
2012/0032559	A1	2/2012	Hino et al.
2012/0041553	A1	2/2012	Gupta et al.
2012/0044571	A1	2/2012	Mukawa
2012/0063000	A1	3/2012	Batchko et al.
2012/0087015	A1	4/2012	Nibauer et al.
2012/0092775	A1	4/2012	Duston et al.
2012/0170920	A1	7/2012	Moreau et al.
2012/0229754	A1	9/2012	Iyer et al.
2012/0250151	A1	10/2012	Lee et al.
2012/0287512	A1	11/2012	Egan et al.
2013/0171546	A1	7/2013	White et al.
2013/0176628	A1	7/2013	Batchko et al.
2013/0300635	A1	11/2013	White et al.
2014/0009039	A1	1/2014	Jenninger et al.
2014/0078586	A1	3/2014	Spurgeon et al.
2014/0153102	A1	6/2014	Chang
2014/0186215	A1	7/2014	Shinta et al.
2014/0227548	A1	8/2014	Myrick
2014/0300857	A1	10/2014	Cohen-Tannoudji et al.
2014/0312737	A1	10/2014	Jenninger et al.
2015/0062719	A1	3/2015	Kyung et al.
2015/0116656	A1	4/2015	Stevens et al.
2015/0138110	A1	5/2015	Yairi et al.
2015/0146161	A1	5/2015	Rigato et al.
2015/0302990	A1	10/2015	Ghosh et al.
2015/0323812	A1	11/2015	Ishak et al.
2016/0004099	A1	1/2016	Steven et al.
2016/0091635	A1	3/2016	Ibuki et al.
2016/0187985	A1	6/2016	Lim et al.
2017/0021385	A1	1/2017	Smith et al.
2017/0045649	A1	2/2017	Bolis
2017/0160600	A1	6/2017	Galstian et al.
2017/0177106	A1	6/2017	Kihara
2017/0184848	A1	6/2017	Vallius
2017/0188021	A1	6/2017	Lo et al.
2017/0192595	A1	7/2017	Choi et al.
2017/0261653	A1	9/2017	Peyman
2017/0299956	A1	10/2017	Holland et al.
2017/0317269	A1	11/2017	Zhang et al.
2017/0336641	A1	11/2017	Von Und Zu Liechtenstein
2018/0255250	A1	9/2018	Price et al.
2018/0275394	A1	9/2018	Yeoh et al.
2018/0335649	A1	11/2018	Tsai
2019/0173128	A1	6/2019	Msc0 et al.
2019/0243123	A1	8/2019	Bohn
2019/0296218	A1	9/2019	Ouderkirk et al.
2019/0302479	A1	10/2019	Smyth et al.
2020/0166742	A1	5/2020	Peyman
2020/0251709	A1	8/2020	Lee et al.

FOREIGN PATENT DOCUMENTS

WO	2008/156166	A1	12/2008
WO	2010/078666	A1	7/2010
WO	2010/104904	A2	9/2010
WO	2019/183431	A1	9/2019
WO	2019/190887	A1	10/2019

OTHER PUBLICATIONS

Notice of Allowance received for U.S. Appl. No. 16/013,837 dated Apr. 14, 2020, 14 pages.
 Preinterview First Office Action received for U.S. Appl. No. 15/992,731 dated Sep. 27, 2019, 17 pages.

(56)

References Cited

OTHER PUBLICATIONS

Final Office Action received for U.S. Appl. No. 15/992,731 dated Jun. 2, 2020, 25 pages.

Non-Final Office Action received for U.S. Appl. No. 15/992,731 dated Aug. 24, 2020, 27 pages.

Examiner-Initiated Interview Summary received for U.S. Appl. No. 16/008,635 dated Apr. 20, 2020, 3 pages.

Notice of Allowance received for U.S. Appl. No. 16/008,635 dated May 4, 2020, 32 pages.

Non-Final Office Action received for U.S. Appl. No. 16/059,091 dated Apr. 8, 2020, 54 pages.

Final Office Action received for U.S. Appl. No. 16/059,091 dated Sep. 21, 2020, 18 pages.

Non-Final Office Action received for U.S. Appl. No. 16/106,945 dated Apr. 16, 2020, 59 pages.

Non-Final Office Action received for U.S. Appl. No. 16/041,634 dated Jul. 30, 2020, 24 pages.

Notice of Allowance received for U.S. Appl. No. 16/041,634 dated Aug. 28, 2020, 31 pages.

Preinterview First Office Action received for U.S. Appl. No. 16/018,752 dated Dec. 16, 2019, 19 pages.

Preinterview First Office Action received for U.S. Appl. No. 16/018,746 dated Jul. 14, 2020, 20 pages.

Notice of Allowance Action received for U.S. Appl. No. 16/018,746 dated Sep. 17, 2020, 24 pages.

Preinterview First Office Action received for U.S. Appl. No. 16/021,580 dated Aug. 4, 2020, 48 pages.

Press Kit Home, "Adaptive glasses", accessed at <http://tvc.utah.edu>, as accessed on Mar. 13, 2018, 5 pages.

Billah et al., "Microstructure Evolution and Electrical Characterization of Lanthanum doped Barium Titanate (BaTiO₃) Ceramics", International Conference on Mechanical Engineering, AIP Cont. Proc. 1754, accessed on Jul. 12, 2016, pp. 030006-1-030006-7.

Cao et al., Grain Size and Domain Size Relations in Bulk Ceramic Ferroelectric Materials, *J. Phys. Chem Solids* vol. 57, No. 10, pp. 1499-1505, 1996.

Ding et al., "Surface profiling of an aspherical liquid lens with a varied thickness membrane," *Optics Express* 3122-3132, vol. 25, No. 4 (Feb. 6, 2017).

He et al., Linear Electro-Optic Properties of Orthorhombic PZN-8%PT Single Crystal, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 58, No. 6 (Jun. 1, 2011).

Knapp et al., "Understanding Zirconia Crown Esthetics and Optical Properties" Inclusive magazine accessed at <http://glidewell dental.com/education/inclusive-dental-implant-magazine-volume-2-issue-4/>, as accessed on Jun. 12, 2018, vol. 2, Issue 4, 17 pages.

Optotune, "Focus tunable lenses", accessed at <http://www.optotune.com/technology/focus-tunable-lenses>, accessed on Mar. 13, 2018, 2 pages.

Polight, "How does it work", accessed at <http://www.polight.com/technology-and-products/how-does-it-work/default.aspx>, accessed on Mar. 13, 2018, 3 pages.

UZZOOM Adlens, "Adjustable Lens Glasses: How They Work", accessed at <https://adlens.com/how-it-works/>, accessed on Mar. 28, 2018, 9 pages.

Piezo Technology, "Highly Reliable Multilayer Piezo Actuators", accessed on <https://www.piceramic.com/en/piezo-technology/picma/>, accessed on Mar. 14, 2018, 8 pages.

Piezo Technology, "Displacement Modes of Piezoelectric Actuators", accessed on <https://www.piceramic.com/en/piezo-technology/properties-piezo-actuators/displacement-modes/>, accessed on Mar. 14, 2018, 12 pages.

Jiang et al., "Transparent Electro-Optic Ceramics and Devices", *Proceedings* vol. 5644, *Optoelectronic devices and integration*, accessed at <https://doi.org/10.1117/12.582105>, Jan. 17, 2005, 15 Pages.

Keplinger et al., "Stretchable, Transparent, Ionic Conductors", *Science Magazine*, vol. 341, DOI:10.1126/science.1240228, Accessed on Aug. 30, 2013, pp. 984-987.

Kong et al., "Transparent Ceramic Materials", *Transparent Ceramics, Topics in Mining, Metallurgy, and Materials Engineering*, Ch. 2, DOI: 10.1007/978-3-319-18956-7_2, Springer international Publishing Switzerland 2015, pp. 29-91.

Patra et al., "Comparison on Optical Properties of Pure and Doped Lithium Tetraborate Single Crystals and Glasses", *Solid State Physics: Proceedings of the 56th DAE Solid State Physics Symposium 2011*, AIP Conf. Proc. 1447, Dec. 11, 2012, pp. 1335-1336.

Riegler et al., "Index Matching Silicone for High Brightness LED Packaging", IMAPS International Conference on Device Packaging March 13-16, Scottsdale AZ., Accessed on Mar. 18, 2005, 17 Pages.

Shian et al., Tunable Lenses using Transparent Dielectric Elastomer Actuators, *Optics Express*, vol. 21, No. 7 (Apr. 2, 2013).

Hocking, L.M., "The effect of slip on the motion of a sphere close to a wall and of two adjacent spheres", *Journal of Engineering Math.*, vol. 7 (1973), pp. 207-221.

Wang et al., "A Highly Stretchable, Transparent, and Conductive Polymer", *Science Advances* vol. 3, No. 3, e1602076, Mar. 10, 2017, pp. 1-10.

APC International, Ltd., "Piezoelectric Materials, New Materials, Piezo theory", accessed at www.americanpiezo.com/knowledge-center/piezo-theory/new-materials/html, accessed on Mar. 15, 2018, 1 page.

Zhao et al., "Spherical aberration free liquid-filled tunable lens with variable thickness membrane," *Optics Express* vol. 23, No. 16, accessed at <https://doi.org/10.1364/0.23.021264>, accessed on Aug. 5, 2015, pp. 21264-21278.

Andrew J. Ouder Kirk, et al.; Apparatuses, Systems, and Methods for Adjusting Fluid Lenses; U.S. Appl. No. 16/008,635, filed Jun. 14, 2018.

Katherine Marie Smyth, et al.; Optical Lens Assemblies, Head-Mounted Displays, and Related Methods; U.S. Appl. No. 16/021,650, filed Jun. 28, 2018.

Andrew John Ouder Kirk, et al.; Multi-Element Prescription Lenses With Eye-Tracking; U.S. Appl. No. 16/041,634, filed Jul. 20, 2018.

Andrew John Ouder Kirk, et al.; Electroactive Polymer Devices and Nanovoiced Polymer Materials and Methods and Systems for Fabrication Thereof; U.S. Appl. No. 16/106,945, filed Aug. 21, 2018.

Andrew John Ouder Kirk, et al.; Nanovoiced Electroactive Polymer Devices, Systems, and Methods; U.S. Appl. No. 16/041,858, filed Jul. 23, 2018.

Andrew John Ouder Kirk, et al.; Electroactive Polymer Devices, Systems, And Methods; U.S. Appl. No. 16/059,091, filed Aug. 9, 2018.

Andrew John Ouder Kirk, et al.; Optical Devices, Systems, and Methods of Manufacturing; U.S. Appl. No. 52/646,900, filed Mar. 22, 2018.

Andrew John Ouder Kirk, et al.; Optical Devices, Systems, and Methods of Manufacturing; U.S. Appl. No. 52/650,254, filed Mar. 29, 2018.

Katherine Marie Smyth, et al.; Optical Lens Assemblies and Related Methods; U.S. Appl. No. 16/018,746, filed Jun. 26, 2018.

Katherine Marie Smyth, et al.; Systems and Methods for Actuation of Asymmetric Optical Elements; U.S. Appl. No. 15/992,731, filed May 30, 2018.

Andrew John Ouder Kirk, et al.; Optical Lens Assemblies and Related Methods; U.S. Appl. No. 16/018,752, filed Jun. 26, 2018.

John M. Cooke, et al.; Optical Lens Assemblies, Head-Mounted Displays, and Methods of Altering Optical Properties of Optical Lens Assemblies; U.S. Appl. No. 16/013,837, filed Jun. 20, 2018.

Katherine Marie Smyth, et al.; Optical Lens Assemblies, Head-Mounted Displays, and Related Methods; U.S. Appl. No. 16/016,428, filed Jun. 22, 2018.

Non-Final Office Action received for U.S. Appl. No. 16/106,945 dated Mar. 30, 2021, 111 pages.

Notice of Allowance received for U.S. Appl. No. 16/018,752 dated Mar. 10, 2021, 32 pages.

Communication pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 19715707.6 dated Mar. 22, 2021, 5 page.

Non-Final Office Action received for U.S. Appl. No. 16/016,428 dated Mar. 12, 2021, 56 pages.

(56)

References Cited

OTHER PUBLICATIONS

John M. Cooke, et al.; Optical Lens Assemblies, Head-Mounted Displays, and Related Methods; U.S. Appl. No. 16/021,580, filed Jun. 28, 2018.

Andrew John Ouderkirk, et al.; Electroactive Polymer Devices, Systems, and Methods; U.S. Appl. No. 16/035,562, filed Jul. 13, 2018.

“Adjustable Reading Glasses,” URL: <https://adlens.com/>, retrieved on May 7, 2018, 1 page.

Guha et al., “Creating nanoscale emulsions using condensation”, Nature Communications, vol. 8, No. 1371, Nov. 2017, pp. 1-7.

Merriam-Webster, “Porosity”, URL: <https://www.merriam-webster.com/dictionary/porosity>, retrieved on Apr. 8, 2020, pp. 1-8.

International Search Report and Written Opinion received for PCT Application Serial No. PCT/US2019/023484 dated Jul. 3, 2019, 9 pages.

International Preliminary Report on Patentability received for PCT Application Serial No. PCT/US2019/023484 dated Oct. 1, 2020, 8 pages.

International Search Report and Written Opinion received for PCT Application Serial No. PCT/US2019/023485 dated Jul. 4, 2019, 11 pages.

International Preliminary Report on Patentability received for PCT Application Serial No. PCT/US2019/023485 dated Oct. 8, 2020, 8 pages.

Notice of Allowance received for U.S. Appl. No. 15/972,794 dated Oct. 16, 2020, 22 pages.

Notice of Allowance received for U.S. Appl. No. 15/992,731 dated Nov. 18, 2020, 37 pages.

Final Office Action received for U.S. Appl. No. 16/106,945 dated Nov. 24, 2020, 94 pages.

Final Office Action received for U.S. Appl. No. 16/018,752 dated Nov. 30, 2020, 41 pages.

Notice of Allowance received for U.S. Appl. No. 16/018,746 dated Nov. 3, 2020, 39 pages.

Notice of Allowance received for U.S. Appl. No. 16/021,580 dated Dec. 9, 2020, 68 pages.

Preinterview First Office Action received for U.S. Appl. No. 16/021,650 dated Feb. 1, 2021, 47 pages.

Gurvich, Mark R., “On Characterization of Anisotropic Elastomeric Materials for Structural Analysis”, Rubber Chemistry and Technology, vol. 77, No. 1, 2004, pp. 115-130.

Non-Final Office Action received for U.S. Appl. No. 16/035,562 dated Jun. 10, 2021, 36 pages.

Non-Final Office Action received for U.S. Appl. No. 16/016,428 dated Jun. 16, 2021, 43 pages.

* cited by examiner





FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21

2200




FIG. 22

1

**OPTICAL LENS ASSEMBLIES,
HEAD-MOUNTED DISPLAYS, AND
RELATED METHODS**

CROSS REFERENCE TO RELATED
APPLICATION

This application is a continuation of U.S. Non-Provisional patent application Ser. No. 16/021,580, filed Jun. 28, 2018, titled "OPTICAL LENS ASSEMBLIES, HEAD-MOUNTED DISPLAYS, AND RELATED METHODS," which claims the benefit of U.S. Provisional Application No. 62/650,254, filed Mar. 29, 2018, the entire disclosure of each of which is incorporated herein by this reference.

BACKGROUND

Adjustable-lens systems may be useful in a variety of devices, including eyeglasses, cameras, instrumentation, and virtual or augmented reality ("VR/AR") systems, such as to adjust the focus of a display element (e.g., screen) or of a real-world image viewed by a user. One example of an adjustable-lens system is a "liquid lens" assembly. As accommodative elements, liquid lenses may be varifocal, may have high transmissivity, and with proper optical design can achieve low off-axis aberration and distortion for high image quality over a range of optical powers.

Liquid lenses often include a flexible membrane that is directly coupled to a rigid backplane and a fluid that is disposed between the rigid backplane and the membrane. Inducing a change in fluid pressure may result in a convex or concave lens shape, which may result in a change in optical power. Conventional actuation techniques for liquid lenses typically include applying a force to a force distributor ring positioned on a peripheral portion of a major surface of the flexible membrane, which may cause the change in fluid pressure and resulting shape change. Such techniques, however, typically require the lens' frame to be thick enough to accommodate the actuation mechanism used to apply the force. In addition, deformation profiles achievable by conventional actuation techniques may be limited.

SUMMARY

As will be described in greater detail below, the present disclosure describes optical lens assemblies and head-mounted displays ("HMDs") including a compliant peripheral component positioned between a deformable element and a structural support element, and an actuator configured to displace at least a portion of the compliant peripheral component to deform the deformable element.

In some embodiments, the present disclosure includes optical lens assemblies that may include a deformable element, a structural support element, a substantially transparent deformable medium positioned between the deformable element and the structural support element, a compliant peripheral component positioned between peripheral portions of the deformable element and the structural support element, and an actuator. The actuator may be configured to displace at least a portion of the compliant peripheral component to deform the deformable element and change at least one optical property of the optical lens assembly.

In some examples, the actuator may be configured to displace at least a portion of the compliant peripheral component in a direction along an optical axis of the optical lens assembly, or in a direction that is substantially orthogonal to the optical axis of the optical lens assembly. The

2

actuator may, in some embodiments, include at least a portion of the compliant peripheral component. In one example, the actuator may include an electroactive material that is coupled to, or that forms at least a portion of, the compliant peripheral component. Such an actuator may also include a driver circuit that is configured to apply a voltage to the electroactive material.

In some examples, the actuator may include an electric motor configured to tension a cable. At least a portion of the cable may be within at least one sheath, or the cable may be unsheathed. The actuator may include a shape-memory alloy material. The actuator may include a pump or a piston that is configured to cause an expandable member to expand. The compliant peripheral component may include the expandable member, or the expandable member may be positioned adjacent to at least a portion of the compliant peripheral component.

In some examples, the deformable element may be under an initial mechanical stress prior to actuation by the actuator. A pre-tensioning ring may be coupled to a perimeter of the deformable element to hold the initial mechanical stress. The compliant peripheral component and the actuator may be positioned outside of a substantially transparent aperture of the optical lens assembly. The actuator may be configured to cause the deformable element to deform, via displacement of at least a portion of the compliant peripheral component, into at least one of a substantially convex shape or a substantially concave shape. The compliant peripheral component may be or include a bi-stable element. At least a portion of at least one of the compliant peripheral component or the actuator may serve as an edge seal for at least a portion of a cavity defined by the deformable element and the structural support element. The substantially transparent deformable medium may include at least one of a liquid, a gas, a gel, a foam, or a polymer.

In some embodiments, the present disclosure includes head-mounted displays, which may include a support housing, an optical lens assembly coupled to the support housing, and a display element coupled to the support housing. The optical lens assembly may include a deformable element, a structural support element, a substantially transparent deformable medium positioned between the deformable element and the structural support element, a compliant peripheral component positioned between peripheral portions of the deformable element and the structural support element, and an actuator configured to displace at least a portion of the compliant peripheral component to deform the deformable element and change at least one optical property of the optical lens assembly.

In some examples, the actuator may be configured to displace at least a portion of the compliant peripheral component in a direction along an optical axis of the optical lens assembly, or in a direction that is substantially orthogonal to the optical axis of the optical lens assembly.

In some embodiments, methods of altering at least one optical property of an optical lens assembly are disclosed. In accordance with such methods, at least a portion of a compliant peripheral component that is positioned between peripheral portions of a deformable element and of a structural support element may be displaced with an actuator. As a result of the displacement of the compliant peripheral component, the deformable element may be deformed to change at least one optical property of the optical lens assembly.

In some examples, as a result of the displacement of the compliant peripheral component, at least a portion of a substantially transparent deformable medium that is posi-

tioned within a cavity defined by the deformable element and the structural support element may be displaced. A pressure within the cavity may be altered to deform the deformable element.

Features from any of the above-mentioned embodiments may be used in combination with one another in accordance with the general principles described herein. These and other embodiments, features, and advantages will be more fully understood upon reading the following detailed description in conjunction with the accompanying drawings and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings illustrate a number of example embodiments and are a part of the specification. Together with the following description, these drawings demonstrate and explain various principles of the present disclosure.

FIG. 1 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present application.

FIG. 2 is a cross-sectional side view of the optical lens assembly of FIG. 1 in an actuated state.

FIG. 3 is a perspective view of an HMD according to an embodiment of the present disclosure.

FIG. 4 is a side view of an optical lens assembly according to an embodiment of the present disclosure.

FIG. 5 is a front view of the optical lens assembly of FIG. 4.

FIG. 6 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 7 is a cross-sectional side view of the optical lens assembly of FIG. 6 in an actuated state.

FIG. 8 is a cross-sectional side view of an optical lens assembly according to an embodiment of the present disclosure.

FIG. 9 is a front view of the optical lens assembly of FIG. 8.

FIG. 10 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 11 is a cross-sectional side view of the optical lens assembly of FIG. 10 in an actuated state.

FIG. 12 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 13 is a cross-sectional side view of the optical lens assembly of FIG. 12 in an actuated state.

FIG. 14 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 15 is a cross-sectional side view of the optical lens assembly of FIG. 14 in an actuated state.

FIG. 16 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 17 is a cross-sectional side view of the optical lens assembly of FIG. 16 in an actuated state.

FIG. 18 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 19 is a cross-sectional side view of the optical lens assembly of FIG. 18 in an actuated state.

FIG. 20 is a cross-sectional side view of an optical lens assembly in a neutral, non-actuated state, according to an embodiment of the present disclosure.

FIG. 21 is a cross-sectional side view of the optical lens assembly of FIG. 20 in an actuated state.

FIG. 22 is a flow diagram illustrating a method of altering optical properties of an optical lens assembly, according to an embodiment of the present disclosure.

Throughout the drawings, identical reference characters and descriptions indicate similar, but not necessarily identical, elements. While the example embodiments described herein are susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. However, the example embodiments described herein are not intended to be limited to the particular forms disclosed. Rather, the present disclosure covers all modifications, equivalents, combinations, and alternatives falling within the scope of the appended claims.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

The present disclosure is generally directed to optical lens assemblies, HMDs, and related methods. As will be explained in greater detail below, embodiments of the present disclosure may include optical lens assemblies that are configured for actuation, and therefore changing of at least one optical property, by displacement of a compliant peripheral component positioned between peripheral portions of a deformable element and a structural support element. The displacement of the compliant peripheral component, as opposed to conventional configurations in which a force is applied to a major surface of the deformable element, may, in some embodiments, improve actuation of optical lens assemblies, such as by reducing an actuator size, reducing a thickness of a housing (e.g., frame element), reducing an actuation force, and/or altering deformation profiles of the deformable elements.

The following will provide, with reference to FIGS. 1 and 2, detailed descriptions of example optical lens assemblies that include a compliant peripheral component and an actuator configured to displace at least a portion of the compliant peripheral component to deform a deformable element. The description of FIG. 3 relates to an embodiment of an HMD that includes optical lens assemblies according to the present disclosure. With reference to FIGS. 4-21, the following will provide detailed descriptions of additional embodiments of optical lens assemblies according to the present disclosure. The discussion relating to FIG. 22 will provide a detailed description of a method of altering at least one optical property of an optical lens assembly, according to the present disclosure.

FIG. 1 shows a cross-sectional side view of an optical lens assembly **100** in a neutral, non-actuated state. The optical lens assembly **100** may include a rigid or semi-rigid structural support element **110** and a deformable optical element **120** (including a deformable element **122** and a deformable medium **124**) positioned over the structural support element **110**. In some examples, relational terms such as “over,” “on,” “downward,” etc., may be used for clarity and convenience in understanding the disclosure and accompanying drawings, and may not necessarily connote or depend on any specific preference, orientation, or order, except where the context clearly indicates otherwise. The deformable element **122** may be directly (e.g., bonded, adhered) or indirectly (e.g., via a separate component or material) coupled to the structural support element **110**.

As shown in FIG. 1, in embodiments in which the deformable element **122** is directly coupled to the structural

support element **110**, an outer periphery of the deformable element **122** may define a compliant peripheral component **130** for containing the deformable medium **124** in a cavity defined between the deformable element **122** and the proximal structural support element **110**. In other embodiments, the compliant peripheral component **130** may be a separate, distinct element positioned between and coupled to the deformable element **122** and the structural support element **110**. An actuator component **140** may be positioned adjacent to (e.g., radially outside of) the compliant peripheral component **130**, and may be configured to displace at least a portion of the compliant peripheral component **130** upon actuation of the optical lens assembly **100**. The compliant peripheral component **130** may define an edge seal for containing the deformable medium **124**.

A housing **150** (e.g., an eyeglass frame element, an AR or VR headset frame element, etc.) may support the other components of the optical lens assembly **100**. In some embodiments, the housing **150** may also support a display element **154** (e.g., an electronic display element, etc.) for displaying an image to the user, and/or another optical lens assembly similar to the optical lens assembly **100** illustrated in FIG. 1. In such embodiments, the display element **154** may be positioned adjacent to the deformable element **122** and between the optical lens assembly **100** and the other optical lens assembly. Additionally, FIG. 1 illustrates the structural support element **110** on a side of the optical lens assembly **100** proximate the user's eye and the deformable element **122** on an opposite side of the optical lens assembly **100**. In additional embodiments, the structural support element **110** may be on a side of the optical lens assembly **100** distant from the user's eye and the deformable element **122** may be positioned proximate to the user's eye.

The structural support element **110**, the deformable element **122**, and the deformable medium **124** may each be substantially transparent to allow light to pass to an eye of a user. Accordingly, at least portions of the structural support element **110** and of the deformable optical element **122** may be positioned in a substantially transparent aperture of the optical lens assembly **100**, which may refer to a portion of the optical lens assembly **100** that allows the passage of light to a user's eye.

In some examples, the phrase "substantially transparent" may refer to an element exhibiting greater than about 20% transmissivity and less than about 10% haze in the visible light spectrum. In some examples, the term "substantially," in reference to a given parameter, property, or condition, may generally refer to a degree that one of ordinary skill in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as within acceptable manufacturing tolerances. By way of example, depending on the parameter, property, or condition that is substantially met, the parameter, property, or condition may be at least 90% met, at least 95% met, at least 99% met, etc. In some examples, the phrase "deformable optical element" may refer to an element (including one or more materials or sub-elements) that is configured to be deformed to alter an optical property (e.g., an accommodative property or an adaptive optical property) of the optical lens assembly. In some examples, the term "accommodative" or "accommodation" may refer to changes in an optical power. In some examples, the term "adaptive" may refer to tunability for providing control, compensation, and/or correction of wave front errors such as distortion and aberration(s). In some examples, "aberration" may generally refer to an optical image defect, including any deviation from diffraction-limited optical performance. Aberrations can be chromatic

or monochromatic and may include, for example, tilt, defocus, astigmatism, coma, distortion, field curvature, spherical errors, cylindrical errors, etc.

In FIG. 1, the deformable optical element **120** is shown in a neutral, non-actuated state (e.g., with no applied actuation force). In the non-actuated state, a surface of the deformable element **122** may have a substantially planar shape, and the optical lens assembly **100** may be configured and positioned to not substantially alter an image or view passing through the optical lens assembly **100**. In other words, the non-actuated state may be a substantially zero-optical power state.

The structural support element **110** may be or include a substantially transparent material with a higher relative rigidity than the deformable element **122** and the deformable medium **124**. By way of example, the structural support element **110** may be or include one or more of a glass material, a sapphire material, a crystal material (e.g., quartz), a polycarbonate material, another substantially transparent polymer material, or a substantially transparent non-polymeric material. The structural support element **110** may provide a protective barrier for the user's eye, for the deformable optical element **122**, and for other components of the optical lens assembly **100** (e.g., a display element, an actuator, etc.).

The structural support element **110** may also include an eye-tracking element, which may be configured for estimating an inter-pupillary distance of the user's eyes, a gaze distance, and/or a focal point. The eye-tracking element, if present, may include a selective-transmission element that transmits light having a selected property and that does not transmit light that does not have the selected property. For example, the structural support element **110** may include a coating or material that allows visible light to pass while reflecting non-visible light (e.g., infrared light). In this example, an infrared light source may direct infrared light to the structural support element **110**, which may be reflected onto the user's eye. An infrared camera may then detect infrared light that is reflected from the user's eye and back to the structural support element **110** to track the user's eye(s).

As shown in FIG. 1, the structural support element **110** may be a substantially planar element that does not substantially alter an image viewed through the structural support element **110**. In other embodiments, the structural support element **110** may include a corrective ophthalmic lens (e.g., a positive-optical power lens, a negative-optical power lens, a lens for correction of an aberration, etc.), or another optical lens element. The shape of the structural support element **110** may, in some embodiments, be tailored to or selected in consideration of a specific user to correct vision impairments or to otherwise meet user preferences. Optionally, an anti-reflective coating may be applied to the structural support element **110**. In some examples, the structural support element **110** can be a zero-optical power meniscus lens element for improved anti-reflective properties and integration with potentially non-flat optical eye-tracking and/or ophthalmic optical elements at the structural support element **110**. A zero-optical power curved lens may provide some advantages over a substantially planar lens for some applications, such as for improved anti-reflective properties and/or improved fit to a user's facial contours, for example.

The deformable element **122** may include a substantially transparent, flexible film. By way of example and not limitation, the deformable element **122** may include at least one of a polymer material (e.g., a thermoset polymer, a thermoplastic polymer, an elastomer, a silicone material,

polydimethylsiloxane, a polyurethane elastomer, a fluoropolymer material, polyvinylidene fluoride or a copolymer thereof, a polyolefin material, a polyacrylate material, etc.), a ceramic material, a glass material, a crystalline (e.g., substantially single-crystal) material, or a composite material. The deformable element **122** may be or include a single material or a multi-layer structure. The deformable element **122** may include a barrier material for controlling gas or liquid diffusion, an anti-reflective material, or a combination thereof. In some examples, a material of the deformable element **122** may include a flexible, transparent, water-impermeable material, such as clear and elastic polyolefins, polycycloaliphatics, polyethers, polyesters, polyimides and/or polyurethanes, for example, a polyvinylidene chloride film, including a commercially available film.

In some examples, and depending on the material and configuration selected for the deformable element **122**, the deformable element **122** may be pre-tensioned to induce an initial mechanical stress in the deformable element, such as to achieve a desired profile and response to actuation and/or to reduce the negative effects of so-called “gravity sag.” Gravity sag may refer to a lower portion of the deformable optical element **122** being thicker on average than an upper portion due to gravity urging the deformable element **122** and/or deformable medium **124** downward when the optical lens assembly **100** is in use. In some embodiments, a portion of the housing **150** may be coupled to a perimeter of the deformable element **122** and may act as a pre-tensioning ring to maintain the applied pre-tension and initial mechanical stress in the deformable element **122**. In additional embodiments, a separate pre-tensioning ring may be coupled to a perimeter of the deformable element **122** to maintain the applied pre-tension and initial mechanical stress.

The deformable medium **124** may be a substantially transparent material with mechanical properties that allow for deformation upon actuation of the optical lens assembly **100**. By way of example and not limitation, the deformable medium **124** may be or include a gas (e.g., air, nitrogen, etc.), a liquid (e.g., water, degassed water, mineral oil, saline solution, a high-refractive index liquid, etc.), a polymer material, a gel (e.g., a silicone gel), or a foam (e.g., a silica aerogel), etc.

The compliant peripheral component **130** may be or include, for example, a polymer, a metal, or a composite material. The compliant peripheral component **130** may be positioned outside of the substantially transparent aperture of the optical lens assembly **100**, and may be at least substantially covered by the housing **150**. In some embodiments, the compliant peripheral component **130** may be configured to act in a non-linear, bi-stable manner, such that the compliant peripheral component **130** may not be stable in a flat (in cross-section) position. For example, the compliant peripheral component **130** may have a shape that curves outward in a non-actuated state, and a shape that curves inward in an actuated state. Thus, upon actuation, the compliant peripheral component **130** may snap over-center from bulging outward (as shown in FIG. 1) to bulging inward (as shown in FIG. 2). A bi-stable compliant peripheral component **130** may, in some embodiments and for some applications, advantageously be capable of load-matching to some types of actuators.

The actuator component **140** may, in some embodiments, be an elongated cable or wire positioned around at least a portion of a perimeter of the compliant peripheral component **130**. For example, the actuator component **140** may be or include a metal, polymer, or composite cable or wire. The actuator component **140** may be positioned outside of the

substantially transparent aperture of the optical lens assembly **100**, and may be at least substantially covered by the housing **150**. Applying tension to the actuator component **140** by an actuator may cause the actuator component **140** to be displaced inward, toward and/or against the compliant peripheral component **130**.

FIG. 2 shows the optical lens assembly **100** in an actuated state, with the actuator component **140** applying an actuation force **160** against the compliant peripheral component **130** in a radially inward direction (i.e., in a direction that is substantially orthogonal to an optical axis of the optical lens assembly **100**). The actuator component **140** may be manipulated (e.g., tensioned) by an electromechanical actuator, for example. Example mechanisms for causing the actuator component **140** to apply the actuation force **160** are described below, such as with reference to FIGS. 4, 5, 8, 9, 14, and 15.

Because of the actuation force **160**, at least a portion of the compliant peripheral component **130** may be displaced inward to displace outer portions of the deformable medium **124**, which may cause a central portion of the deformable optical element **120** to axially (i.e., in a direction along an optical axis of the optical lens assembly **100**) bulge outward, as indicated in FIG. 2 by arrow **170**. When actuated, the deformable optical element **120** may have a convex shape, such as to exhibit a positive-optical power. Thus, actuation may change at least one optical property (e.g., a focal distance) of the optical lens assembly **100**. For example, actuation of the optical lens assembly **100** may adjust a user’s view of an image rendered and displayed on the electronic display element **154** (FIG. 1) and/or of a real-world environment through the optical lens assembly **100**. Upon removal of the actuation force **160** against the compliant peripheral component **130** by the actuator component **140**, the compliant peripheral component **130** and the deformable optical element **120** may return to the non-actuated state shown in FIG. 1.

In some examples, the term “electromechanical actuator” may refer to a piezoelectric material or device, an electroactive polymer, an electrostrictive polymer, a shape memory alloy, a voice coil, a pneumatic actuator, an electromagnetic motor (including for example a servo motor, a stepper motor, a DC motor, or a similar motor), a hydraulic actuator, or a combination thereof. In some examples, the term “electroactive” may refer to a property of a material or composite material that deforms in response to an application of electrical energy (e.g., a voltage), and may generate electrical energy when strained or deformed. Example electroactive materials include piezoelectric materials, electrostrictor materials, dielectric elastomers, and ionic polymer conductors. Electroactive materials may function as transducers or as a component of transducers for actuating and deforming the deformable optical element **120**.

FIG. 3 illustrates an example HMD **300** (e.g., AR glasses, VR glasses) capable of incorporating embodiments of the optical lens assemblies described herein. In one example, the HMD **300** may be dimensioned to be worn on a head of a user. The HMD **300** may include a frame element **302** for supporting at least one deformable optical lens assembly **304** according to the present disclosure. In some embodiments, the optical lens assembly(ies) **304** may be tailored to or selected in consideration of a particular user’s eye. In addition to supporting the optical lens assembly(ies) **304**, the frame element **302** may also support other elements, such as an actuator, a driver circuit for the actuator, a power supply element (e.g., a battery), a communication component (e.g., a component for communication via Wi-Fi, BLUETOOTH,

near-field communications, etc.), a display element, a graphics processing unit for rendering an image on the display element, an image sensor (e.g., a camera), an eye-tracking element, etc. As shown in FIG. 3, the optical lens assembly 304 may have an asymmetric shape. In addition, the HMD 300 may have a different shape (e.g., symmetric, circular, etc.) and design than is shown in FIG. 3, such as in the form of a VR headset or another shape that suits user preferences or a particular application. The optical lens assembly(ies) 304 may be or include, for example, any of the optical lens assemblies described in this disclosure.

FIGS. 4 and 5 respectively show a side view and a front view of an optical lens assembly 400 to illustrate an example actuation mechanism for displacing at least a portion of a compliant peripheral component 430 to change an optical property of the optical lens assembly 400. The optical lens assembly 400 may include a structural support element 410, a deformable optical element 420 (including a deformable element 422 and a deformable medium 424), and the compliant peripheral component 430 positioned between peripheral portions of the deformable element 422 and the structural support element 410. An elongated actuator component 440 may be positioned adjacent to (e.g., radially outside) and along a perimeter of the compliant peripheral component 430. Actuation of the actuator component 440 may be accomplished with an actuator 442 operably coupled to the actuator component 440. A housing 450 (e.g., an AR eyeglass frame, a VR headset frame, etc.) may support the other components of the optical lens assembly 400.

As illustrated in FIG. 5, for example, the actuator 442 may include a rotational electromagnetic motor and a spool 444 about which a proximal longitudinal end of the actuator component 440 may be at least partially wound during actuation, to apply a tension to the actuator component 440. An attachment structure 446 may couple a distal longitudinal end of the actuator component 440 to the housing 450. Upon rotation of the spool 444 in a first rotational direction (e.g., clockwise in the view of FIG. 5), a portion of the actuator component 440 may wrap at least partially around the spool 444, which may result in the actuator component 440 effectively shortening within the housing 450 and applying a radially inward actuation force on the compliant peripheral component 430. Upon rotation of the spool 444 in a second, opposite rotational direction (e.g., counter-clockwise in the view of FIG. 5), the actuator component 440 may be effectively lengthened within the housing 450, which may result in the actuator component 440 moving radially outward and relaxing the actuation force applied against the compliant peripheral component 430.

Although FIGS. 4 and 5 illustrate actuation by wrapping the actuator component 440 at least partially around the spool 444, the present disclosure is not limited to such actuation mechanisms. For example, the proximal end of the actuator component may instead be coupled to a linear actuator. In some examples, the actuator component 440 may be or include a shape-memory alloy material that may be shortened or lengthened upon application of sufficient electrical energy (e.g., a voltage).

FIGS. 6-9 illustrate another embodiment of an optical lens assembly 600 according to an embodiment of the present disclosure. The optical lens assembly 600 may include a substantially transparent, rigid or semi-rigid structural support element 610, a deformable optical element 620 (including a deformable element 622 and a deformable medium 624), and a compliant peripheral component 630 positioned between peripheral portions of the structural support element 610 and the deformable element 622. An elongated

actuator component 640 may be positioned around at least a portion of a perimeter of the compliant peripheral component 630. A housing 650 may support the other components of the optical lens assembly 600. A pre-tensioning ring 652 may be coupled to a peripheral portion of the deformable element 622 to maintain an applied pre-tension and initial mechanical stress in the deformable element 622.

As illustrated in FIGS. 8 and 9, a proximal end of the actuator component 640 may be operatively coupled to an actuator 642, such as an electromechanical motor with a rotatable spool 644, for actuation. A distal end of the actuator component 640 may be coupled to the housing 650 via an attachment structure 646 (FIG. 9).

As shown in each of FIGS. 6-9, at least a portion of the actuator component 640 may pass through one or more rigid or semi-rigid sheaths 648. The sheaths 648 may provide a physical barrier between at least portions of the actuator component 640 and the compliant peripheral component 630, such as to protect the compliant peripheral component 630 from wear that might otherwise result from sliding friction upon repeated actuation. In addition, the sheaths 648 may be positioned to provide points or sections where a radially inward actuation force 660 (FIG. 7) may be applied against the compliant peripheral component 630, such as to induce a specific deformation profile of the deformable optical element 620. The sheaths 648 may be radially movable relative to the housing 650.

As illustrated in FIG. 7, actuation of the optical lens assembly 600 may result in application of the actuation force 660 by the actuator component 640 and sheaths 648 against the compliant peripheral component 630. As the compliant peripheral component 630 is forced inward, portions of the deformable medium 624 may be displaced inward and a central portion of the deformable optical element 620 may axially (i.e., in a direction of an optical axis of the optical lens assembly 600) bulge outward, as shown by arrow 670 in FIG. 7.

FIGS. 10 and 11 show another embodiment of an optical lens assembly 1000. The optical lens assembly 1000 may include a substantially transparent, rigid or semi-rigid structural support element 1010, a deformable optical element 1020 (including a deformable element 1022 and a deformable medium 1024), and a compliant peripheral component 1030 positioned between peripheral portions of the structural support element 1010 and the deformable element 1022. An elongated actuator component 1040 may be positioned around at least a portion of a perimeter of the compliant peripheral component 1030. A housing 1050 may support the other components of the optical lens assembly 1000. A pre-tensioning ring 1052 may be coupled to a peripheral portion of the deformable element 1022 to maintain an applied pre-tension and initial mechanical stress in the deformable element 1022.

In this example, the compliant peripheral component 1030 may include an inward protrusion 1032 that may axially collapse when the actuator component 1040 applies a radially inward actuation force 1060 (FIG. 11) against the compliant peripheral component 1030. Upon actuation, the pre-tensioning ring 1052 and a corresponding peripheral portion of the deformable optical element 1020 may be displaced in a direction 1062 toward the structural support element 1010 (e.g., in a downward direction in the perspective of FIG. 11). A radially outer portion of the deformable medium 1024 may be displaced inward, resulting in the deformable element 1022 bulging away from the structural

11

support element **1010**, as shown in FIG. **11** by arrow **1070**, to alter at least one optical property of the optical lens assembly **1000**.

FIGS. **12** and **13** illustrate an optical lens assembly **1200** according to another embodiment of this disclosure. The optical lens assembly **1200** may include a substantially transparent, rigid or semi-rigid structural support element **1210**, a deformable optical element **1220** (including a deformable element **1222** and a deformable medium **1224**), and a compliant peripheral component **1230** positioned between peripheral portions of the structural support element **1210** and the deformable element **1222**. An elongated actuator component **1240** may be positioned and configured to actuate the deformable optical element **1220** to alter at least one optical property of the optical lens assembly **1200**. A housing **1250** may support the other components of the optical lens assembly **1200**. A pre-tensioning ring **1252** may be coupled to a peripheral portion of the deformable element **1222** to maintain an applied pre-tension and initial mechanical stress in the deformable element **1222**.

In this example, the actuator component **1240** may be substantially fully surrounded by portions of the compliant peripheral component **1230**. For example, the actuator component **1240** may be over-molded or otherwise encased by a material of the compliant peripheral component **1230**. The actuator component **1240** may be capable of longitudinally sliding within the material of the compliant peripheral component **1230**, and/or the material of the compliant peripheral component **1230** may be sufficiently elastic to stretch and/or compress upon actuation and inward displacement of the compliant peripheral component **1230**. By way of example, the actuator component **1240** may be or include a loop of a shape-memory alloy that may be configured to shorten in length upon application of sufficient electrical energy (e.g., a voltage).

As illustrated in FIG. **13**, inward displacement of the actuator component **1240** may apply an inward actuation force **1260** on the compliant peripheral component **1230**, which may result in the pre-tensioning ring **1252** and corresponding peripheral portion of the deformable element **1222** moving in a direction **1262** toward the structural support element **1210** (e.g., downward in the perspective of FIG. **13**). Outer portions of the deformable medium **1224** may be displaced radially inward, resulting in an outward bulge of a central portion of the deformable optical element **1220**, as shown by arrow **1270** in FIG. **13**.

FIGS. **14** and **15** show another embodiment of an optical lens assembly **1400**. The optical lens assembly **1400** may include a substantially transparent, rigid or semi-rigid structural support element **1410**, a deformable optical element **1420** (including a deformable element **1422** and a deformable medium **1424**), and a compliant peripheral component **1430** positioned between peripheral portions of the structural support element **1410** and the deformable element **1422**. An elongated actuator component **1440** may be positioned around a perimeter of the compliant peripheral component **1430**, and may be configured to actuate the deformable optical element **1420** to alter at least one optical property of the optical lens assembly **1400**. A housing **1450** may support the other components of the optical lens assembly **1400**. A pre-tensioning ring **1452**, which may be a portion of the housing **1450**, may be coupled to a peripheral portion of the deformable element **1422** to maintain an applied pre-tension and initial mechanical stress in the deformable element **1422**.

In this example, the actuator component **1440** may include an expansible fluid-filled bladder. An actuator **1480**

12

may be configured to apply a pressure to the fluid within the actuator component **1440**. For example, the actuator **1480** may be a pump or piston that may be in fluid communication with an interior of the actuator component **1440**, such as via a conduit **1482**.

As shown in FIG. **15**, when a pressure is increased within the actuator component **1440** by actuation of the actuator **1480**, the actuator component **1440** may expand. In some embodiments, the actuator component **1440** may be constrained in an axial direction (i.e., in a direction of an optical axis of the optical lens assembly **1400**) by the housing **1450**. Accordingly, expansion of the actuator component **1440** may displace an inner portion of the actuator component **1440** inward to apply an actuation force against the compliant peripheral component **1430**, which may result in a central portion of the deformable optical element **1420** bulging outward, as shown by arrow **1470** in FIG. **15**. Upon release of the pressure from the actuator **1480**, the actuator component **1440** may relax and the optical lens assembly **1400** may return to the non-actuated state illustrated in FIG. **14**.

In additional embodiments, the expansible actuator component **1440** may be coupled (e.g., bonded, adhered) to the structural support element **1410** and to the deformable element **1422**, and a separate compliant peripheral component **1430** may be absent. In such embodiments, an inner sidewall of the actuator component **1440** may form a compliant peripheral component that may deform inward upon actuation.

FIGS. **16** and **17** illustrate an optical lens assembly **1600** according to another embodiment of this disclosure. The optical lens assembly **1600** may include a substantially transparent, rigid or semi-rigid structural support element **1610**, a deformable optical element **1620** (including a deformable element **1622** and a deformable medium **1624**), and a compliant peripheral component **1640** positioned between peripheral portions of the structural support element **1610** and the deformable element **1622**. The compliant peripheral component **1640** may be configured to be actuated to deform the deformable optical element **1620** to alter at least one optical property of the optical lens assembly **1600**. The compliant peripheral component **1640** may define an edge seal for containing the deformable medium **1624** within a cavity defined between the structural support element **1610** and the deformable element **1622**. A housing **1650** may support the other components of the optical lens assembly **1600**. A pre-tensioning ring **1652** may be coupled to a peripheral portion of the deformable element **1622** to maintain an applied pre-tension and initial mechanical stress in the deformable element **1622**.

In this example, the compliant peripheral component **1640** may be or include a hydraulically actuated, expanding bellows, which may be configured to expand upon actuation and contract upon release, such as in a direction along an optical axis of the optical lens assembly **1600**. An actuator **1680** (e.g., a pump, a piston) may be in fluid communication with an interior of the compliant peripheral component **1640**, such as via a conduit **1682**.

As illustrated in FIG. **17**, when fluid pressure is applied to an interior of the compliant peripheral component **1640** by the actuator **1680**, the compliant peripheral component **1640** may expand, forcing the pre-tensioning ring **1652** and a peripheral portion of the deformable element **1622** away from the structural support element **1610**, as shown by arrows **1660** in FIG. **17**. In this example, portions of the compliant peripheral component **1640** may be displaced in a direction along an optical axis of the optical lens assembly

1600. Portions of the deformable medium 1624 in a central region of the deformable optical element 1620 may be displaced outward toward the compliant peripheral component 1640, and a central portion of the deformable optical element 1620 may be depressed toward the structural support element 1610, as shown by arrow 1670 in FIG. 17. In this actuated state, the optical lens assembly 1600 may have a concave shape exhibiting a negative-optical power. In addition, if a fluid pressure within the compliant peripheral component 1640 is reduced, such as by withdrawing fluid therefrom by the actuator 1680, the compliant peripheral component 1640 may shorten and the optical lens assembly 1600 may have a convex shape exhibiting a positive-optical power.

FIGS. 18 and 19 show another embodiment of an optical lens assembly 1800. The optical lens assembly 1800 may include a substantially transparent, rigid or semi-rigid structural support element 1810, a deformable optical element 1820 (including a deformable element 1822 and a deformable medium 1824), and a compliant peripheral component 1840 positioned between peripheral portions of the structural support element 1810 and the deformable element 1822. The compliant peripheral component 1840 may be configured to be actuated to deform the deformable optical element 1820 to alter at least one optical property of the optical lens assembly 1800. The compliant peripheral component 1840 may define an edge seal for containing the deformable medium 1824 within a cavity defined between the structural support element 1810 and the deformable element 1822. A housing 1850 may support the other components of the optical lens assembly 1800. A pre-tensioning ring 1852 may be coupled to a peripheral portion of the deformable element 1822 to maintain an applied pre-tension and initial mechanical stress in the deformable element 1822.

In this example, the compliant peripheral component 1840 may include a stack of multiple electroactive materials and interdigitated electrodes. The electroactive materials may be configured to deform (e.g., expand or contract) upon application of a sufficient voltage to the electrodes by a driver circuit 1890. Therefore, the driver circuit 1890 may act as an actuator. By way of example, the electroactive materials of the compliant peripheral component 1840 may include piezoelectric materials, electrostrictor materials, dielectric elastomers, and ionic polymer conductors. By way of example, the electroactive materials may include piezoelectrics including polymers like polyvinylidene fluoride (“PVDF”) and its copolymers, and/or single crystal ceramics like lithium niobate, quartz, $K_{0.5}Na_{0.5}NbO_3$ (“KNN”), barium titanate, lithium niobate, lithium tetraborate, quartz, lead zirconate titanate, $Pb(Mg_{1/3}Nb_{2/3})O_3$ — $PbTiO_3$, and/or $Pb(Zn_{1/3}Nb_{2/3})O_3$ — $PbTiO_3$, etc.

The electrodes of the compliant peripheral component 1840 may include a conductive material, such as a metallic material, a transparent conducting oxide, indium tin oxide, a nanocomposite material, carbon nanotubes, silver nanowires, and/or graphene, for example.

FIG. 19 illustrates the optical lens assembly 1800 in an actuated state. For example, application by the driver circuit 1890 of a sufficient voltage and polarity on the electroactive stack of the compliant peripheral component 1840 may expand the compliant peripheral component 1840 to apply an actuation force 1860 on the pre-tensioning ring 1852 away from the structural support element 1810. In this example, portions of the compliant peripheral component 1840 may be displaced in a direction along an optical axis of the optical lens assembly 1800. Actuation in this manner

may result in a central region of the deformable optical element 1820 deforming toward the structural support element 1810 to result in a concave shape, as shown by arrow 1870 in FIG. 19. Conversely, the application by the driver circuit 1890 of a sufficient voltage of an opposite polarity may cause the compliant peripheral component 1840 to shorten and the deformable optical element 1820 to form a convex shape.

FIGS. 20 and 21 show another embodiment of an optical lens assembly 2000. The optical lens assembly 2000 may include a substantially transparent, rigid or semi-rigid structural support element 2010, a deformable optical element 2020 (including a deformable element 2022 and a deformable medium 2024), and a compliant peripheral component 2040 positioned between peripheral portions of the structural support element 2010 and the deformable element 2022. The compliant peripheral component 2040 may be configured to be actuated to deform the deformable optical element 2020 to alter at least one optical property of the optical lens assembly 2000. The compliant peripheral component 2040 may define an edge seal for containing the deformable medium 2024 within a cavity defined between the structural support element 2010 and the deformable element 2022. A housing 2050 may support the other components of the optical lens assembly 2000. A pre-tensioning ring 2052 may be coupled to a peripheral portion of the deformable element 2022 to maintain an applied pre-tension and initial mechanical stress in the deformable element 2022.

In this example, the compliant peripheral component 2040 may include a single electroactive material or a stack of multiple electroactive materials and electrodes. The electroactive material(s) may be configured to deform inward and/or outward upon application of a sufficient voltage to the electrodes by a driver circuit 2090, as illustrated in FIG. 21. In embodiments including a stack of multiple electroactive materials, the electroactive materials and electrodes may be arranged to be driven by either a parallel driver circuit 2090 (as shown in FIG. 21) or a series driver circuit.

As illustrated in FIG. 21, application of a sufficient voltage by the driver circuit 2090 may cause at least a portion of the compliant peripheral component 2040 to bend radially inward, which may impose an inward actuation force 2060 on an outer portion of the deformable medium 2024, resulting in a central portion of the deformable optical element 2020 bulging to form a convex shape, as shown by arrow 2070 in FIG. 21. Conversely, application of a sufficient voltage of an opposite polarity may result in the compliant peripheral component 2040 bending outward, causing the deformable optical element 2020 to have a concave shape.

FIG. 22 is a flow diagram that illustrates a method 2200 of altering at least one optical property of an optical lens assembly. In operation 2210, a portion of a compliant peripheral component, which may be positioned between peripheral portions of a deformable element and of a structural support element, may be displaced, such as with an actuator. The actuator may, in some examples, displace a portion of the compliant peripheral component in a direction that is along an optical axis, or that is orthogonal to the optical axis (e.g., radially inward) of the optical lens assembly. For example, the actuator may act directly on the compliant peripheral component, rather than or in addition to on a major surface of the deformable element. Thus, actuation and deformation of the optical lens assembly may

be initiated by an actuator interacting directly with (e.g., physically and/or electrically interacting with) the compliant peripheral component.

Referring to operation 2220, as a result of the displacement of the compliant peripheral component, the deformable element may be deformed to change at least one optical property of the optical lens assembly. For example, as discussed above, an actuation force acting on or through the compliant peripheral component may change a fluid pressure in a peripheral portion of a deformable medium between the deformable element and the structural support element, which may result in a central region of the deformable element bulging into a convex shape and/or depressing into a concave shape. Thus, at least a portion of the deformable medium may be displaced within the cavity, and a pressure within the cavity may be altered to deform the deformable element.

Accordingly, disclosed are optical lens assemblies and associated HMDs that include a compliant peripheral component that may be displaced by an actuator to change at least one optical property of the optical lens assemblies or HMDs. Related methods for altering at least one optical property of optical lens assemblies are also disclosed. The disclosed apparatuses and methods may enable improved optical lens assemblies with alternative actuation schemes and mechanisms, such as with reduced actuator sizes, reduced housing thickness, reduced actuation forces, and/or altered deformation profiles.

Embodiments of the present disclosure may include or be implemented in conjunction with an artificial reality system. Artificial reality is a form of reality that has been adjusted in some manner before presentation to a user, which may include, e.g., VR, AR, mixed reality (MR), hybrid reality, or some combination and/or derivatives thereof. Artificial reality content may include completely generated content or generated content combined with captured (e.g., real-world) content. The artificial reality content may include video, audio, haptic feedback, or some combination thereof, any of which may be presented in a single channel or in multiple channels (such as stereo video that produces a three-dimensional effect to the viewer). Additionally, in some embodiments, artificial reality may also be associated with applications, products, accessories, services, or some combination thereof, that are used to, e.g., create content in an artificial reality and/or are otherwise used in (e.g., perform activities in) an artificial reality. The artificial reality system that provides the artificial reality content may be implemented on various platforms, including an HMD connected to a host computer system, a standalone HMD, a mobile device or computing system, or any other hardware platform capable of providing artificial reality content to one or more viewers.

The process parameters and sequence of the steps described and/or illustrated herein are given by way of example only and can be varied as desired. For example, while the steps illustrated and/or described herein may be shown or discussed in a particular order, these steps do not necessarily need to be performed in the order illustrated or discussed. The various example methods described and/or illustrated herein may also omit one or more of the steps described or illustrated herein or include additional steps in addition to those disclosed.

The preceding description has been provided to enable others skilled in the art to best utilize various aspects of the example embodiments disclosed herein. This example description is not intended to be exhaustive or to be limited to any precise form disclosed. Many modifications, combi-

nations, and variations are possible without departing from the spirit and scope of the present disclosure. The embodiments disclosed herein should be considered in all respects illustrative and not restrictive. Reference should be made to the appended claims and their equivalents in determining the scope of the present disclosure.

Unless otherwise noted, the terms “connected to” and “coupled to” (and their derivatives), as used in the specification and claims, are to be construed as permitting both direct and indirect (i.e., via other elements or components) connection. In addition, the terms “a” or “an,” as used in the specification and claims, are to be construed as meaning “at least one of.” Finally, for ease of use, the terms “including” and “having” (and their derivatives), as used in the specification and claims, are interchangeable with and have the same meaning as the word “comprising.”

What is claimed is:

1. An optical lens assembly, comprising:
 - a deformable element including a substantially transparent deformable medium and a compliant peripheral component; and
 - at least one electromechanical actuator configured to displace at least a portion of the compliant peripheral component to deform the deformable element and change at least one optical property of the optical lens assembly, wherein the at least one electromechanical actuator is configured to tension a cable to apply a force with the cable to the compliant peripheral component.
2. The optical lens assembly of claim 1, wherein the electromechanical actuator comprises an electric motor.
3. The optical lens assembly of claim 1, wherein the electromechanical actuator comprises a linear actuator.
4. The optical lens assembly of claim 1, wherein at least a portion of the cable is housed within at least one sheath.
5. The optical lens assembly of claim 1, wherein at least a portion of the cable is unsheathed.
6. The optical lens assembly of claim 1, further comprising a driver circuit configured to apply a voltage to the electromechanical actuator.
7. The optical lens assembly of claim 1, wherein at least a portion of the cable is encased by a material of the compliant peripheral component.
8. The optical lens assembly of claim 1, wherein the electromechanical actuator comprises a spool and at least a portion of the cable is wrapped at least partially around the spool.
9. The optical lens assembly of claim 1, further comprising a housing configured to support the deformable element, wherein a proximal longitudinal end of the cable is coupled to the electromechanical actuator and a distal longitudinal end of the cable is coupled to the housing.
10. The optical lens assembly of claim 9, wherein the housing comprises at least one of an augmented-reality eyeglass frame or a virtual-reality headset frame.
11. The optical lens assembly of claim 1, further comprising a structural support element to which the compliant peripheral component is mounted.
12. The optical lens assembly of claim 1, wherein the deformable element is under an initial mechanical stress prior to actuation by the actuator, further comprising a pre-tensioning ring coupled to a perimeter of the deformable element, wherein the initial mechanical stress in the deformable element is held by the pre-tensioning ring.
13. The optical lens assembly of claim 1, wherein the compliant peripheral component and the electromechanical actuator are positioned outside of a substantially transparent aperture of the optical lens assembly.

17

14. The optical lens assembly of claim 1, wherein the electromechanical actuator is configured to cause the deformable element to deform, via displacement of at least a portion of the compliant peripheral component, into at least one of a substantially convex shape or a substantially concave shape. 5

15. The optical lens assembly of claim 1, wherein the compliant peripheral component comprises a bi-stable element.

16. The optical lens assembly of claim 1, wherein at least a portion of the compliant peripheral component serves as an edge seal for at least a portion of a cavity containing the substantially transparent deformable medium. 10

17. The optical lens assembly of claim 1, wherein the substantially transparent deformable medium comprises at least one of a liquid, a gas, a gel, a foam, or a polymer. 15

18. A head-mounted display, comprising:

a support housing;

an optical lens assembly coupled to the support housing, the optical lens assembly comprising:

a deformable element including a substantially transparent deformable medium positioned and a compliant peripheral component; and

18

an electromechanical actuator configured to displace at least a portion of the compliant peripheral component to deform the deformable element and change at least one optical property of the optical lens assembly by tensioning a cable to apply a force with the cable to the compliant peripheral component; and a display element coupled to the support housing.

19. A method of altering at least one optical property of an optical lens assembly, comprising:

tensioning a cable with an electromagnetic actuator;

displacing, as a result of tensioning the cable, at least a portion of a compliant peripheral component of a deformable optical element; and

deforming, as a result of the displacement of the compliant peripheral component, the deformable optical element to change at least one optical property of the optical lens assembly.

20. The method of claim 19, wherein tensioning the cable with the electromagnetic actuator comprises wrapping a portion of the cable at least partially around a spool of the electromagnetic actuator.

* * * * *