



US 20130013072A1

(19) **United States**

(12) **Patent Application Publication**
de Villiers et al.

(10) **Pub. No.: US 2013/0013072 A1**

(43) **Pub. Date: Jan. 10, 2013**

(54) **INTERVERTEBRAL PROSTHETIC DISC**

Publication Classification

(75) Inventors: **Malan de Villiers**, Wapadrand (ZA);
Ulrich Hähnele, Saxonwold (ZA)

(51) **Int. Cl.**
A61F 2/44 (2006.01)

(73) Assignee: **SpinalMotion, Inc.**, Mountain View, CA (US)

(52) **U.S. Cl.** 623/17.16

(21) Appl. No.: **13/619,180**

(57) **ABSTRACT**


(22) Filed: **Sep. 14, 2012**

Related U.S. Application Data

(63) Continuation of application No. 12/101,664, filed on Apr. 11, 2008, which is a continuation of application No. 10/855,817, filed on May 26, 2004, now Pat. No. 7,442,211.

(60) Provisional application No. 60/473,803, filed on May 27, 2003, provisional application No. 60/473,802, filed on May 27, 2003.

A prosthetic disc for insertion between adjacent vertebrae includes upper and lower plates, a core disposed between the plates, and at least one projection extending from at least one of the upper and lower curved surfaces of the core into at least one recess of one of the inner surfaces of the plates. The recess is oversize with respect to the projection to allow sliding movement of the plate over the core while retaining the core between the plates during such sliding movement. The projection(s) may include a rod extending through an axial hole in the core, multiple surface features of the core, or the like.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 6A




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

INTERVERTEBRAL PROSTHETIC DISC

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of U.S. patent application Ser. No. 12/101,664 (Attorney Docket No. 29850-703.301), filed Apr. 11, 2008, which is a continuation of U.S. patent application Ser. No. 10/855,817 (Attorney Docket No. 29850-703.201), filed May 26, 2004, which claims the priority of U.S. Provisional Application Nos. 60/473,802 (Attorney Docket No. 29850-704.101) and 60/473,803, (Attorney Docket No. 29850-703.101), both of which were filed May 27, 2003; the full disclosures of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] This invention relates to medical devices and methods. More specifically, the invention relates to a prosthetic disc for intervertebral insertion, such as in the lumbar and cervical spine.

[0004] In the event of damage to a lumbar or cervical intervertebral disc, one possible surgical treatment is to replace the damaged disc with a disc prosthesis. Several types of intervertebral disc prostheses are currently available. For example, one type of intervertebral disc prosthesis is provided by Waldemar Link GmbH & Co under the trademark LINK® SB Charite. This prosthesis includes upper and lower prosthesis plates or shells which locate against and engage the adjacent vertebral bodies, and a low friction core between the plates. The core has upper and lower convexly curved surfaces and the plates have corresponding, concavely curved recesses which cooperate with the curved surfaces of the core. This allows the plates to slide over the core to allow required spinal movements to take place. The curved recesses in the plates are surrounded by annular ridges which locate, at the limit of sliding movement of the plates over the core, in opposing upwardly and downwardly facing, peripheral channels surrounding the curved surfaces of the core.

[0005] This type of disc configuration is described in EP 1142544A1 and EP 1250898A1, assigned to Waldemar Link GmbH & Co. A drawback of such configurations is that the provision of the peripheral ribs and channels limits the areas available for bearing and sliding contact between the plates and core, and accordingly the loads which can be transmitted by the prosthesis. As a result of the relatively small bearing areas, it is believed that at least the core will be subject to rapid wear and have a relatively short lifespan. Also, because the core is in effect merely “clamped” between the plates, this configuration does not allow for secure retention of the core. In one alternative arrangement, the curved surfaces of the core carry opposing, elongate keys that locate in elongate grooves in the plates and another alternative arrangement in which the plates have opposing elongate keys that locate in elongate grooves in the opposite curved surfaces of the core. These key and groove arrangements allow the plates to slide over the core within the limits of the length of the grooves, in one direction only. Although allowance is made for some lateral play of the keys in the grooves, very little sliding movement of the plates over the core can take place in the orthogonal vertical plane, and this is considered to be a serious drawback of this design.

[0006] Other currently available intervertebral disc prostheses have similar and/or other drawbacks. Typically, drawbacks include insufficient resistance to wear and tear, restricted range of motion and/or insufficient ability of the prosthesis to adhere to vertebral bone.

[0007] Therefore, a need exists for improved intervertebral disc prostheses. Ideally, such improved prostheses would resist wear and tear, provide a desired range of motion and adhere well to vertebral bone. At least some of these objectives will be met by the present invention.

[0008] 2. Description of the Background Art

[0009] Published US patent applications 2002/0035400A1 and 2002/0128715A1 describe disc implants which comprise opposing plates with a core between them over which the plates can slide. The core receives one or more central posts, which are carried by the plates and which locate in opposite ends of a central opening in the core. Such arrangements limit the load bearing area available between the plates and core.

[0010] Other patents related to intervertebral disc prostheses include U.S. Pat. Nos.: 4,759,766; 4,863,477; 4,997,432; 5,035,716; 5,071,437; 5,370,697; 5,401,269; 5,507,816; 5,534,030; 5,556,431; 5,674,296; 5,676,702; 5,702,450; 5,824,094; 5,865,846; 5,989,291; 6,001,130; 6,022,376; 6,039,763; 6,139,579; 6,156,067; 6,162,252; 6,315,797; 6,348,071; 6,368,350; 6,416,551; 6,592,624; 6,607,558 and 6,706,068. Other patent applications related to intervertebral disc prostheses include U.S. Patent Application Publication Nos.: 2003/0009224; 2003/0074076; 2003/0191536; 2003/0208271; 2003/0135277; 2003/0199982; 2001/0016773 and 2003/0100951. Other related patents include WO 01/01893A1, EP 1344507, EP 1344506, EP 1250898, EP 1306064, EP 1344508, EP 1344493, EP 1417940, EP 1142544, and EP 0333990.

BRIEF SUMMARY OF THE INVENTION

[0011] In one aspect of the present invention, an intervertebral prosthetic disc for insertion between adjacent vertebrae comprises: upper and lower plates having outer surfaces locatable against the respective vertebrae and inner, curved surfaces; a core between the plates, the core having upper and lower curved surfaces complementary in shape to the inner, curved surfaces of the plates to allow the plates to slide over the core; and at least one projection extending from at least one of the upper and lower curved surfaces of the core into at least one recess of one of the inner surfaces of the plates, the recess being oversized with respect to the projection to allow sliding movement of the plate over the core while retaining the core between the plates during such sliding movement.

[0012] Some embodiments further include multiple projections extending from the upper and lower surfaces of the core. For example, the multiple projections may include two elevated rings projecting from a peripheral portion of each of the upper and lower surfaces of the core into ring-shaped recesses on the upper and lower plates. In other embodiments, the multiple projections may comprise multiple surface features projecting from a peripheral portion of each of the upper and lower surfaces of the core into multiple recesses on the upper and lower plates. In yet other embodiments, the multiple projections may comprise respective ends of an elongate, upright element extending axially through the core, the ends projecting beyond the upper and lower core surfaces. For example, the upright element may comprise a rod extending through an axial passage through the core. In some embodi-

ments, such a rod and passage may be complementarily threaded for engagement with one another.

[0013] In some embodiments, the disc further includes at least one fin extending from each of the outer surfaces of the plates to promote attachment of the plates to the vertebrae. In some embodiments, each fin extends from its respective outer surface at a 90° angle. In other embodiments, each fin extends from its respective outer surface at an angle other than 90°. In some embodiments, each fin includes at least one hole for promoting attachment of the plates to the vertebrae. For further promoting attachment of the plates to the vertebrae some embodiments include outer surfaces of the plates that are textured. For example, in some embodiments the textured surfaces comprise multiple serrations.

[0014] The plates may have any of a number of different configurations, sizes, or the like. In one embodiment, the outer surfaces of the plates are flat. In one embodiment, lateral edge portions of the upper and lower plates are adapted to contact one another during sliding movement of the plates over the core.

[0015] In another aspect of the present invention, an intervertebral prosthetic disc for insertion between adjacent vertebrae comprises: upper and lower plates having outer surfaces locatable against the respective vertebrae and inner, curved surfaces, at least one of the inner surfaces having at least one recess; a core between the plates, the core having upper and lower curved surfaces complementary in shape to the inner, curved surfaces of the plates to allow the plates to slide over the core, and an axial passage extending through the core; and a rod extending through the axial passage into the at least one recess in the inner surface(s) of the plate(s). The recess are oversized with respect to the projection to allow sliding movement of the plate over the core while retaining the core between the plates during such sliding movement.

[0016] Optionally, the rod and passage may be complementarily threaded for engagement with one another. In some embodiments, the rod is movably engaged with a first oversized recess on the upper plate and a second oversized recess on the lower plate. In various embodiments, the plates and core may have any of the features or characteristics described above.

[0017] In another aspect of the invention, an intervertebral prosthetic disc for insertion between adjacent vertebrae includes: upper and lower plates having outer surfaces locatable against the respective vertebrae and inner, curved surfaces; a core between the plates, the core having upper and lower curved surfaces complementary in shape to the inner, curved surfaces of the plates to allow the plates to slide over the core; and a flexible tie member extending laterally through the core and having ends outside the core which are engaged with one or both of the plates to retain the core between the plates when the plates slide over the core. The flexible tie member, for example, may extend through a lateral passage through the core and may include ends engaged with at least one of the upper and lower plates. In some embodiments, the flexible tie member comprises a flexible cable or cord.

[0018] In yet another example of the present invention, an intervertebral prosthetic disc for insertion between adjacent vertebrae comprises: upper and lower plates having textured outer surfaces locatable against the respective vertebrae, each of the outer surfaces having at least one vertical fin and an edge portion adapted to contact a corresponding edge portion of the other plate, and inner, curved surfaces; and a core

between the plates, the core having upper and lower curved surfaces complementary in shape to the inner, curved surfaces of the plates to allow the plates to slide over the core. The curved surfaces of the plates and core include formations which cooperate with one another to retain the core between the plates when the plates slide over the core. The formations include recesses and projections received by the recesses, and the recesses and projections are located between a central axis of the relevant curved surface and an outer periphery thereof.

[0019] In some embodiments, for example, the projections may comprise two elevated rings projecting from a peripheral portion of each of the upper and lower surfaces of the core into ring-shaped recesses on the upper and lower plates. In other embodiments, the projections may comprise multiple surface features projecting from a peripheral portion of each of the upper and lower surfaces of the core into multiple recesses on the upper and lower plates. Again, the plates and core may include any of the features described above.

[0020] These and other aspects and embodiments are described more fully below with reference to the drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 shows a cross-sectional anterior view of a prosthetic disc according to one embodiment of the invention, with the prosthesis plates and core in vertical alignment;

[0022] FIG. 2 shows a cross-sectional side view of the disc of FIG. 1, after sliding movement of the plates over the core;

[0023] FIG. 3 shows a cross-sectional side view of the disc of FIG. 1, after translational movement of the plates relative to the core;

[0024] FIG. 4 shows a cross-sectional side view of the disc of FIG. 1, with the plates and core in vertical alignment;

[0025] FIG. 5 shows a plan view of the core of the disc of FIG. 1;

[0026] FIG. 6 shows a plan view of the upper plate of the disc of FIG. 1;

[0027] FIG. 6A shows a plan view of a disc, as in FIGS. 1 and 6, with a fin rotated away from the anterior-posterior axis;

[0028] FIG. 7 shows a cross-sectional anterior view of a prosthetic disc according to another embodiment of the invention;

[0029] FIG. 8 shows a cross-sectional side view of the prosthetic disc of FIG. 7;

[0030] FIG. 9 shows a cross-sectional anterior view of a prosthetic disc according to another embodiment of the invention;

[0031] FIG. 10 shows a cross-sectional side view of the prosthetic disc of FIG. 9; and

[0032] FIG. 11 shows a cross-sectional side view of another embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0033] FIGS. 1-4 illustrate a prosthetic disc **10** for intervertebral insertion between two adjacent spinal vertebrae (not shown). The disc **10** comprises three components, namely an upper plate or shell **12**, a lower plate or shell **14** and a core **16** located between the plates.

[0034] The upper plate **12** includes an outer surface **18** and an inner surface **24** and may be constructed from any suitable material or combination of materials, such as but not limited to cobalt chrome molybdenum, titanium (such as grade 5 titanium) and/or the like. In one embodiment, typically used

in the lumbar spine, the upper plate **12** is constructed of cobalt chrome molybdenum, and the outer surface **18** is treated with aluminum oxide blasting followed by a titanium plasma spray. In another embodiment, typically used in the cervical spine, the upper plate **12** is constructed of titanium, the inner surface **24** is coated with titanium nitride, and the outer surface **18** is treated with aluminum oxide blasting. An alternative cervical spine embodiment includes no coating on the inner surface **24**. In some embodiments, it may be useful to couple two materials together to form the inner surface **24** and the outer surface **18**. For example, the upper plate **12** may be made of an MRI-compatible material, such as titanium, but may include a harder material, such as cobalt chrome molybdenum, for the inner surface **24**. Any suitable technique may be used to couple materials together, such as snap fitting, slip fitting, lamination, interference fitting, use of adhesives, welding and/or the like. Any other suitable combination of materials and coatings may be employed in various embodiments of the invention.

[0035] In some embodiments, the outer surface **18** is planar. Oftentimes, the outer surface **18** will include one or more surface features and/or materials to enhance attachment of the prosthesis **10** to vertebral bone. For example, the outer surface **18** may be machined to have a serrations **20** or other surface features for promoting adhesion of the upper plate **12** to a vertebra. In the embodiment shown (FIG. 6), the serrations **20** extend in mutually orthogonal directions, but other geometries would also be useful. Additionally, the outer surface **18** may be provided with a rough microfinish formed by blasting with aluminum oxide microparticles or the like. In some embodiments, the outer surface may also be titanium plasma sprayed to further enhance attachment of the outer surface **18** to vertebral bone.

[0036] The outer surface **18** may also carry an upstanding, vertical fin **22** extending in an anterior-posterior direction. The fin **22** is pierced by transverse holes **23**. In an alternative embodiment, as shown in FIG. 6A, the fin **22** may be rotated away from the anterior-posterior axis, such as in a lateral-lateral orientation, a posterolateral-anterolateral orientation, or the like. In some embodiments, the fin **22** may extend from the surface **18** at an angle other than 90.degree. Furthermore, multiple fins **22** may be attached to the surface **18** and/or the fin **22** may have any other suitable configuration, in various embodiments. In some embodiments, such as discs **10** for cervical insertion, the fins **22**, **42** may be omitted altogether.

[0037] The lower plate **14** is similar to the upper plate **12** except for the absence of the peripheral restraining structure **26**. Thus, the lower plate **14** has an outer surface **40** which is planar, serrated and microfinished like the outer surface **18** of the upper plate **12**. The lower plate **14** optionally carries a fin **42** similar to the fin **22** of the upper plate. The inner surface **44** of the lower plate **14** is concavely, spherically curved with a radius of curvature matching that of the inner surface **24** of the upper plate **12**. Once again, this surface may be provided with a titanium nitride or other finish.

[0038] The core **16** of the disc **10** is made of a low-friction material, such as polyethylene (Chirulen™). In alternative embodiments, the core **16** may comprise any other suitable material, such as other polymers, ceramics or the like. For wear resistance, the surface zones of the core **16** may be hardened by an appropriate cross-linking procedure. A passage **32** extends axially through the core. The passage is provided with an internally threaded sleeve **33** of titanium or other suitable material. An elongate element in the form of a

round cross-section, threaded rod **34** extends axially through the passage and is in threaded engagement with the sleeve **33**. The length of the rod is greater than the axial dimension of the core, with the result that the opposite ends **36** of the rod project from the curved surfaces **28** and **30** of the core. In the assembled disc **10**, these ends **36** locate in the recesses **26**. The diameter of the rod is less than that of the recesses **26** so there is substantial room for the rod ends to move laterally in the recesses.

[0039] In use, the disc **10** is surgically implanted between adjacent spinal vertebrae in place of a damaged disc. The adjacent vertebrae are forcibly separated from one another to provide the necessary space for insertion. The disc is inserted, normally in a posterior direction, into place between the vertebrae with the fins **22**, **42** of the plates **12**, **14** entering slots cut in the opposing vertebral surfaces to receive them. After insertion, the vertebrae, facets, adjacent ligaments and soft tissues are allowed to move together to hold the disc in place. The serrated and microfinished surfaces **18**, **40** of the plates **12**, **14** locate against the opposing vertebrae. The serrations **20** and fins **22**, **42** provide initial stability and fixation for the disc **10**. With passage of time, enhanced by the titanium surface coating, firm connection between the plates and the vertebrae will be achieved as bone tissue grows over the serrated surface. Bone tissue growth will also take place about the fins **22**, **40** and through the transverse holes **23** therein, further enhancing the connection which is achieved.

[0040] Referring to FIG. 5, the core **16** may be formed with narrow, angularly spaced, blind passages **61** which accommodate titanium pins **64**. In many embodiments, the core **16** itself is transparent to X-radiation and so is invisible in a post-operative X-ray examination. The pins **64** serve as radiographic markers and enable the position of the core **16** to be ascertained during such examination.

[0041] In the assembled disc **10**, the complementary and cooperating spherical surfaces of the plates and core allow the plates to slide or articulate over the core through a fairly large range of angles and in all directions or degrees of freedom, including rotation about the central axis **40**. FIGS. 1 and 4 show the disc **10** with the plates **12**, **14** and core **16** aligned vertically with one another on the axis **40**. FIG. 2 illustrates a situation where maximum anterior flexion of the disc has taken place. Such flexion is enabled by the ability of the ends **36** of the rod to move laterally in all directions and through a fairly large distance, in the recesses **26**. At the position of maximum flexion, the ends **36** of the rod abut the sides of the recesses as illustrated. At the same time, the plates **12**, **14** abut one another at the periphery of their curved surfaces. Similar principles apply to maximum posterior flexure of the plates **12**, **14** over the core, i.e. during spinal extension and/or in the event of maximum lateral flexure.

[0042] FIG. 3 illustrates how the disc **10** can also allow for translational movement of the plates relative to the core. In the illustrated situation there has been lateral translation of the plates relative to the core. The limit of lateral translation (not shown) is again reached when the ends **36** of the rod abut laterally against the sides of the recesses **26**.

[0043] In each case, the cooperating retaining formations, i.e. the ends **36** of the rod and the recesses **26** cooperate with one another to prevent separation of the core from the plates. In other words, the cooperation of the retaining formations ensures that the core is held captive between the plates at all times during flexure of the disc **10**. In other embodiments of this version of the invention, the rod can be mounted fixedly

to the core by means other than the illustrated threaded connection. In other embodiments, the rod may be replaced by separate elements projecting respectively from the upper and lower curved surfaces of the core.

[0044] FIGS. 7 and 8 illustrate another embodiment of the invention. In this embodiment, the core 16 is formed with a lateral passage 50 extending diametrically through it. The passage is provided with a sleeve 52 of titanium or other suitably wear resistant material. A flexible tie means, in this embodiment in the form of a cable 54 of braided titanium construction, passes with clearance through the sleeve 52. The ends of the cable 54 are flexed upwardly and enter passages 56 in the upper plate 12. The extremities of the cable carry crimped retention lugs or ferrules 58 anchored in blind ends of the passages 56.

[0045] The cable 54 holds the core 16 captive during sliding movement of the plates 12, 14 over the core, whether in flexion, extension or translation. The cable can flex through a wide range of angles to allow sliding movement or articulation of the plates relative to the core to take place. The slack in the cable also allows a degree of rotational movement of the plates relative to the core. As illustrated in FIG. 7, the ends of the passage 50 and sleeve 52 are belled to accommodate movements of the cable during sliding movements. Also, surfaces 60 of the plates 12, 14 are inclined to accommodate the cable when sliding has taken place, so that the cable does not act directly on the plates.

[0046] FIGS. 9 and 10 illustrate another embodiment of a prostheses 10. In this embodiment, the curved surfaces 24 of the plates 12, 14 are formed, at positions between the central axis and their peripheries, with continuous, inwardly directed ribs 62 of annular shape. These ribs locate, with considerable clearance, in annular channels 64 provided at corresponding positions in the upper and lower curved surfaces of the core 16. Once again, cooperation between the retaining formations, i.e. the ribs and channels, holds the core captive between the plates when the plates slide over the core during flexion, extension or translation. At the limit of sliding movement in each case, the rib 62 will abut against a side of the channel. The channel may be provided with a wear resistant lining as described previously.

[0047] FIG. 11 illustrates another embodiment of a prosthesis. In this case, the core carries continuous, annular ribs 70 on its upper and lower surfaces which locate with clearance in channels 72 in the plates 12, 14. The ribs 70 may be lined with wear resistant material as described previously.

[0048] In each of the later versions, i.e. those of FIGS. 7 to 11, the core 16 may be provided with radiographic markers as described previously. Also, in each of these versions, the outer surfaces of the plates 12, 14 may have the same configuration as described in relation to the first version of FIGS. 1 to 6.

[0049] In FIGS. 1-6 and 9-11, embodiments are illustrated in which retaining formations are provided that cooperate with one another between both plates and the core. In other embodiments, core retention may be achieved by cooperation between retaining formations which only act between one of the plates, either the upper plate 12 or the lower plate 14, and the core. In one embodiment, for example, there may be a single projection, which extends from the upper (or lower) curved surface of the core and a corresponding recess in the inner surface of the lower (or upper) plate.

[0050] Although the foregoing is a complete and accurate description of the invention, any of a number of modifications, additions or the like may be made to the various embodiments without departing from the scope of the invention. Therefore, nothing described above should be interpreted as limiting the scope of the invention at it is described in the claims.

[0051] While the above is a complete description of the preferred embodiments of the invention, various alternatives, modifications, and equivalents may be used. Therefore, the above description should not be taken as limiting the scope of the invention which is defined by the appended claims.

What is claimed is:

- 1. An intervertebral prosthetic disc for insertion between adjacent vertebrae, the disc comprising:
 - upper and lower plates having outer surfaces locatable against the respective vertebrae and inner bearing surfaces, and lateral portions;
 - a core between the plates, the core having upper and lower surfaces complementary in shape to the inner bearing surfaces of the plates to allow the plates to slide over the core;
 - formations on at least one of the bearing surfaces of the plates and on the core which cooperate with one another to retain the core between the plates when the plates slide over the core, such formations including a rib on at least one of the plates and a channel in the core, wherein the rib is located within the channel to hold the core captive between the plates when the plates slide over the core, and wherein the rib and channel are located between a central axis of the plates and an outer periphery thereof.

* * * * *