



(19) **United States**

(12) **Patent Application Publication**
Hofman et al.

(10) **Pub. No.: US 2012/0200674 A1**

(43) **Pub. Date: Aug. 9, 2012**

(54) **SYSTEM AND METHOD FOR DETERMINING WHETHER TO OPERATE A ROBOT IN CONJUNCTION WITH A ROTARY PARLOR**

(60) Provisional application No. 61/378,871, filed on Aug. 31, 2010, provisional application No. 61/378,871, filed on Aug. 31, 2010.

(75) Inventors: **Henk Hofman**, Lemmer (NL); **Cor de Ruijter**, Staphorst (NL); **Menno Koekoek**, Dronten (NL); **Peter Willem van der Sluis**, IJsselmuiden (NL)

(51) **Int. Cl.**
H04N 13/02 (2006.01)
G06K 9/00 (2006.01)

(52) **U.S. Cl.** **348/46**; 382/110; 901/27

(57) **ABSTRACT**

(73) Assignee: **Technologies Holdings Corp.**, Houston, TX (US)


(21) Appl. No.: **13/449,002**

(22) Filed: **Apr. 17, 2012**

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/095,977, filed on Apr. 28, 2011, Continuation-in-part of application No. 13/095,963, filed on Apr. 28, 2011.

In certain embodiments, a system includes a three-dimensional camera and a processor communicatively coupled to the three-dimensional camera. The processor is operable to determine a first hind location of a first hind leg of a dairy livestock based at least in part on visual data captured by the three-dimensional camera and determine a second hind location of a second hind leg of the dairy livestock based at least in part on the visual data. The processor is further operable to determine a measurement, wherein the measurement is the distance between the first hind location and the second hind location. Additionally, the processor is operable to determine whether the measurement exceeds a minimum threshold.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A






FIG. 5B






FIG. 7




FIG. 8




FIG. 9




FIG. 10

SYSTEM AND METHOD FOR DETERMINING WHETHER TO OPERATE A ROBOT IN CONJUNCTION WITH A ROTARY PARLOR

RELATED APPLICATIONS

[0001] This application is a continuation-in-part application of pending U.S. patent application Ser. No. 13/095,977 entitled “Vision System for Facilitating the Automated Application of Disinfectant to the Teats of Dairy Livestock”, filed Apr. 28, 2011 and U.S. patent application Ser. No. 13/095,963 entitled “Automated System for Applying Disinfectant to the Teats of Dairy Livestock” filed Apr. 28, 2011, which both claim the benefit under 35 U.S.C. §119(e) of the priority of U.S. Provisional Application Ser. No. 61/378,871 entitled “Automated System for Applying Disinfectant to the Teats of Dairy Livestock”, filed Aug. 31, 2010.

TECHNICAL FIELD OF THE INVENTION

[0002] This invention relates generally to dairy farming and more particularly to an system and method for determining whether to operate a robot in conjunction with a rotary parlor.

BACKGROUND OF THE INVENTION

[0003] Over time, the size and complexity of dairy milking operations has increased. Accordingly, the need for efficient and scalable systems and methods that support dairy milking operations has also increased. Systems and methods supporting dairy milking operations, however, have proven inadequate in various respects.

SUMMARY OF THE INVENTION

[0004] According to embodiments of the present disclosure, disadvantages and problems associated with previous systems supporting dairy milking operations may be reduced or eliminated.

[0005] In certain embodiments, a system includes a three-dimensional camera and a processor communicatively coupled to the three-dimensional camera. The processor is operable to determine a first hind location of a first hind leg of a dairy livestock based at least in part on visual data captured by the three-dimensional camera and determine a second hind location of a second hind leg of the dairy livestock based at least in part on the visual data. The processor is further operable to determine a measurement, wherein the measurement is the distance between the first hind location and the second hind location. Additionally, the processor is operable to determine whether the measurement exceeds a minimum threshold.

[0006] Particular embodiments of the present disclosure may provide one or more technical advantages. For example, in some embodiments, the system of the present disclosure includes a camera to facilitate the operation of a robot, allowing the robot to perform a particular function related to milking a dairy livestock. Using a camera may facilitate the performance of a function (e.g., applying disinfectant) from a position to the rear of the dairy livestock, rather than to the side of the dairy livestock as in certain conventional systems. Approaching from the rear of the dairy livestock makes it less likely that the livestock will be distracted by the milking equipment. Furthermore, approaching from the rear of the dairy livestock makes it less likely that the dairy livestock will kick the milking equipment, the vision system, or any other component of the system of the present disclosure.

[0007] Certain embodiments of the present disclosure may include some, all, or none of the above advantages. One or more other technical advantages may be readily apparent to those skilled in the art from the figures, descriptions, and claims included herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] To provide a more complete understanding of the present invention and the features and advantages thereof, reference is made to the following description taken in conjunction with the accompanying drawings, in which:

[0009] FIG. 1 illustrates an example rotary milking system, according to certain embodiments of the present disclosure;

[0010] FIG. 2A-2B illustrate top and perspective views of an example rotary encoder of the system depicted in FIG. 1, according to certain embodiments of the present disclosure;

[0011] FIG. 3 illustrates a detailed view of an example track, robot carriage, and robot arm of the system depicted in FIG. 1, according to certain embodiments of the present disclosure;

[0012] FIG. 4 illustrates an example image signal identifying located edges in depth corresponding to the edges of the hind legs of a dairy cow, according to certain embodiments of the present disclosure;

[0013] FIGS. 5A-5B illustrate example image signals corresponding to an example storage location of a milking claw in the system depicted in FIG. 1, according to certain embodiments of the present disclosure.

[0014] FIGS. 6A-6B illustrate example positions of a robot arm for the generation of an image signal, according to certain embodiments of the present disclosure;

[0015] FIG. 7 illustrates an alternative example rotary milking system, according to certain embodiments of the present disclosure;

[0016] FIG. 8 illustrates an example method for controlling the position of a robot carriage based on the position of a milking stall of an adjacent rotary milking platform, according to certain embodiments of the present disclosure;

[0017] FIG. 9 illustrates an example method for analyzing an image signal to determine if the hind legs of a dairy cow are spaced far enough apart to allow for extension of a robotic arm, according to certain embodiments of the present disclosure; and

[0018] FIG. 10 illustrates an example method for determining whether to operate a robot in conjunction with a rotary milking platform based on detection of a milking claw, according to certain embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 illustrates an example rotary milking system 100, according to certain embodiments of the present disclosure. System 100 includes a rotary milking platform 102 having a number of stalls 104 each configured to hold a dairy cow 106. In order to facilitate the milking of a dairy cow 106, each stall 104 may have an associated milking claw 107 configured for attachment to the teats of the dairy cow 106 located in the milking stall 104. System 100 further includes a track 108 and a robot carriage 110 carrying a robot arm 112, robot carriage 110 being mounted on track 108 such that robot carriage 110 is able to translate laterally along track 108. System 100 further includes a controller 114 operable to

control the movement of robot carriage **110** along track **108** and/or the movement of the robot arm **112** mounted to robot carriage **110**.

[0020] In certain embodiments, rotary milking system **100** may facilitate the performance of one or more operations associated with the milking of a dairy cow **106** located in a milking stall **104** of rotary milking platform **102**. As particular examples, rotary milking system **100** may facilitate (1) the cleaning and/or stimulation of the teats of a dairy cow **106** prior to the attachment of teat cups of a milking claw to the teats of the dairy cow **106** (e.g., using a preparation tool of robot arm **112**), (2) the attachment of the teat cups of the milking claw **107** to the teats of a dairy cow **106** (e.g., using a teat cup attachment of robot arm **112**), and/or (3) the application of disinfectant to the teats of a dairy cow **106** (e.g., using a spray tool of robot arm **112**).

[0021] In association with the performance of one or more of the above-described operations associated with the milking of a dairy cow **106**, controller **114** may perform a number of functions. First, controller **114** may control the movement of robot carriage **110** along track **108** such that robot carriage **110** moves along track **108** at a rate corresponding to the rotational speed of rotary milking platform **102**. As a result, one or more of the above-described operations may be performed while rotary milking platform **102** is in motion. Second, controller **114** may determine whether enough space exists between the legs of a dairy cow **106** (e.g., based on image signal(s) **146** generated by vision system **142**, as described in detail below) to allow a portion of robot arm **112** to extend between the legs and perform one or more of the above-described operations. Third, controller **114** may confirm that the milking claw is detached from the teats of the dairy cow **106** prior to causing a portion of robot arm **112** to extend between the legs of the dairy cow **106** (as one or more of the above-described operations may be performed subsequent to milking of the dairy cow **106**).

[0022] Although a particular implementation of system **100** is illustrated and primarily described, the present disclosure contemplates any suitable implementation of system **100**, according to particular needs. Additionally, although the present disclosure is described with regard to the milking of dairy cows **106**, the present disclosure contemplates that system **100** may be applicable to the milking of any suitable dairy livestock (e.g., cows, goats, sheep, water buffalo, etc.).

[0023] Rotary milking platform **102** may include any suitable combination of structure and materials forming a platform with a number of stalls **104** positioned around the perimeter such that the stalls **104** rotate about a center point as dairy cows **106** in stalls **104** are milked. In the depicted embodiment, milking stalls **104** are arranged in a side-by-side configuration such that a dairy cow **106** in a milking stall **104** faces the middle of rotary milking platform **102**. In this configuration, robot arm **112** may extend and retract from between the hind legs of a dairy cow **106** in order to perform one or more operations associated with the milking of the dairy cow **106**. Each milking stall may **104** may have an associated milking claw **107** configured for attachment to the teats of a dairy cow **106** in order to facilitate the milking of a dairy cow **106** in the milking stall **104**. The milking claw **107** may be stored at a storage location **115** in or adjacent to the associated milking stall **104** when the milking claw is not in use (i.e., when it is not attached to the teats of a dairy cow **106**).

[0024] Although a rotary milking platform **102** having a particular configuration, size, and number of stalls **104** is illustrated, the present disclosure contemplates a rotary milking platform **102** having any suitable configuration, size, and number of stalls **104**, according to particular needs. For example, in one alternative configuration, milking stalls **104** of rotary milking platform **102** may be arranged in a herringbone configuration (where the milking stalls **104** are oriented on a bias relative to the perimeter of milking platform **102**). In this configuration, robot arm **112** may extend and retract from the side of the dairy cow **106** (i.e., between a front leg and a hind leg of a dairy cow **106**) in order to perform one or more operations associated with the milking of the dairy cow **106**. In another alternative configuration, milking stalls **104** of rotary milking platform **102** may be arranged in a tandem configuration (where the front of a dairy cow **106** in a first milking stall **104** is facing the rear of a dairy cow **106** in an adjacent milking stall **104**), and robot arm **112** may extend and retract from the side of the dairy cow **106** (i.e. between a front leg and a hind leg).

[0025] In certain embodiments, a rotary encoder **116** may be configured to generate rotary encoder signals **118** corresponding to the rotational position and/or speed of rotary milking platform **102**. As illustrated in detail in FIGS. 2A-2B, rotary encoder **116** may be positioned relative to rotary milking platform **102** such that a rotary encoder wheel **120** contacts at least a portion of rotary milking platform **102**. Rotary encoder wheel **120** may contact any suitable portion of rotary milking platform **102** such that rotation of rotary milking platform **102** causes rotation of rotary encoder wheel **120**. For example, rotary encoder wheel **120** may contact an inner (or outer) portion of a circular band located beneath the floor of stalls **104** near the outer edge of rotary milking platform **102**.

[0026] In certain embodiments, rotary encoder **116** may comprise any suitable electro-mechanical device operable to convert an angular position of a shaft **122** into an electrical signal comprising a number of pulses (i.e., rotary encoder signals **118**). Because the number of pulses generated by rotary encoder **116** per revolution of rotary milking platform **102** may be known (e.g., 1000 pulses), the pulse count generated by rotary encoder **116** at any given time may correspond to the rotational position of rotary milking platform **102**. Similarly, the frequency of pulses of generated by rotary encoder **116** may correspond to the rotational speed of rotary milking platform **102**.

[0027] Returning to FIG. 1, track **108** may be positioned adjacent to rotary milking platform **102** and may include any suitable combination of structure and materials facilitating the attachment of robot carriage **110** thereto such that robot carriage **110** may move along track **108** adjacent to a rotary milking platform **102**. In one embodiment, track **108** comprises straight rails positioned parallel to one another and the robot carriage translates laterally along track **108** tangent to rotary milking platform **102**. In another embodiment, track **108** may comprise curved rails. Movement of carriage **110** tangent to rotary milking platform **102** may allow the robot arm **112** riding on carriage **110** to track the movement of a dairy cow **106** located in a milking stall **104** of the rotary milking platform **102**. As a result, the robot arm **112** may perform one or more automated functions associated with the milking of the dairy cow **106**. For example, the robot arm **112** may comprise a spray tool for applying disinfectant to the teats of the dairy cow **106**. As another example, the robot arm **112** may comprise a preparation tool for cleaning and/or

stimulating the teats of the dairy cow **106** prior to the attachment of the teat cups of a milking claw **107**. As yet another example, the robot arm **112** may comprise teat cup attacher for attaching the teat cups of milking claw **107** to the teats of the dairy cow **106**. Although system **100** is primarily described as being used in conjunction with milking stalls **104** of a rotary milking platform **102** throughout the remainder of this description, the present disclosure contemplates system **100** being used in conjunction with any suitable type of milking stall, according to particular needs.

[0028] In certain embodiments, an absolute encoder **124** may be coupled to robot carriage **110** and may be configured to generate absolute encoder signals **126** corresponding to the linear position and/or speed of robot carriage **110** on track **108**. For example, absolute encoder **124** may have a structure and operation similar to rotary encoder **116** (discussed above). Because absolute encoder **124** may generate a known number of pulses per distance (e.g., meter) traveled by robot carriage **110**, the count of pulses generated by absolute encoder **124** at any given time may correspond to the linear position of robot carriage **110** on track **108**. Similarly, the frequency of pulses generated by absolute encoder **124** may correspond to the linear speed of robot carriage **110** relative to track **108**.

[0029] FIG. 3 illustrates a detailed view of an example track **108**, robot carriage **110**, and robot arm **112** of system **100**. In the illustrated example, track **108** includes one or more tubular track members **128** each corresponding to one or more rollers **130** of robot carriage **110**. Rollers **130** of robot carriage **110** may roll along track members **128**, permitting robot carriage **110** to translate laterally along track **108**. In certain embodiments, a carriage actuator **132** may be attached to both track **108** and robot carriage **110** such that extension/retraction of carriage actuator **132** causes movement of robot carriage **110** along track **108**. The extension/retraction of carriage actuator **132** may be governed by an actuator drive mechanism **134**, which may include a hydraulic pump, a pneumatic pump, or any other suitable drive mechanism operable to cause extension/retraction of carriage actuator **132**.

[0030] In certain embodiments, the robot arm **112** riding on robot carriage **110** may include a number of arm members **136** pivotally attached to one another. Robot arm **112** may additionally include a number of arm actuators **138** each operable to extend and retract in order to cause movement of robot arm **112**. The extension/retraction of arm actuators **138** may be governed by actuator drive mechanism **134**, described above. Robot arm **112** may additionally include a tool attachment **140** operable to perform one or more functions associated with the milking of a dairy cow **106**. For example, tool attachment **140** may comprise a spray head operable to apply disinfectant to the teats of a dairy cow **106**. As another example, tool attachment **140** may comprise a preparation tool for cleaning and/or stimulating the teats of the dairy cow **106** prior to the attachment of the teat cups of a milking claw **107**. As yet another example, tool attachment **140** may comprise a teat cup attacher operable to attach the teat cups of a milking claw **107** to the teats of a dairy cow **106**.

[0031] In certain embodiments, tool attachment **140** may include a vision system **142** housing a camera **144**. Camera **144** may include any suitable camera operable to generate one or more image signals **146** corresponding to all or a portion of a milking stall **104** and/or all or a portion of a dairy cow **106** located in the milking stall **104**. In some embodiments, camera **144** may be operable to generate still images at particular

points in time. In other embodiments, camera **144** may be operable to generate a continuous video image signal. As one particular example, camera **144** may be a three-dimensional camera operable to generate a three-dimensional video image signal **146** corresponding to the rear of a dairy cow **106**.

[0032] As described in further detail below, image signals **146** generated by vision system **142** (1) may be used by controller **114** (e.g., using vision control logic **156**, described below) to position all or a portion of robot arm **112** relative to a dairy cow **106** such that tool attachment **140** may perform one or more of the above-described functions (e.g., by determining whether enough space exists between the hind legs of the dairy cow **106** to allow the extension of at least a portion of robot arm **112** between the hind legs), and/or (2) may be used by controller **114** (e.g., using milking claw detection logic **158**, described below) to determine whether a milking claw **107** is attached to the teats of dairy cow **106** in milking stall **104** (as it may be desirable to confirm that the milking claw **107** is not attached to the teats of the dairy cow **106** before robot arm **112** performs certain functions associated with the milking of dairy cow **106**).

[0033] Although track **108**, robot carriage **110**, robot arm **112**, and tool attachment **140** are depicted as having a particular configuration, the present disclosure contemplates these components having any suitable configuration, according to particular needs. Furthermore, although robot arm **112** is depicted as having a particular number of members **136** having a particular structure, the present disclosure contemplates any suitable number of members **136**, each having any suitable structure, according to particular needs. Moreover, although robot arm **112** is depicted as having a particular tool attachment **140**, the present disclosure contemplates robot arm **112** having any suitable tool attachment **140** for performing operations associated with the milking of a dairy cow **106**.

[0034] Returning to FIG. 1, various components of system **100** (e.g., rotary encoder **116**, absolute encoder **124**, carriage actuator **132**, tool attachment **140**, and/or vision system **142**) may be communicatively coupled to controller **114** (e.g., via a network facilitating wireless or wireline communication). Controller **114** may control the position of robotic carriage **110** on track **108** (e.g., by controlling the extension/retraction of carriage actuator **132**) such that robot carriage **110** may track the movement of a stall **104** of rotary milking platform **102**. As a result, the robot arm **112** riding on robot carriage **110** may perform one or more functions associated with the milking of a dairy cow **106** located in the stall **104**. In addition, controller **114** may process image signals **146** generated by vision system **142** in order to position all or a portion of robot arm **112** relative to a dairy cow **106** in a milking stall **104** such that tool attachment **140** may perform one or more functions associated with the milking of the dairy cow **106**. Further, controller **114** may process image signals **146** generated by vision system **142** in order to determine whether to extend robot arm **112** between the hind legs of a dairy cow **106** based on whether a milking claw **107** is attached to the teats of the dairy cow **106**.

[0035] Controller **114** may include one or more computer systems at one or more locations. Each computer system may include any appropriate input devices (such as a keypad, touch screen, mouse, or other device that can accept information), output devices, mass storage media, or other suitable components for receiving, processing, storing, and communicating data. Both the input devices and output devices may include fixed or removable storage media such as a magnetic

computer disk, CD-ROM, or other suitable media to both receive input from and provide output to a user. Each computer system may include a personal computer, workstation, network computer, kiosk, wireless data port, personal data assistant (PDA), one or more processors within these or other devices, or any other suitable processing device. In short, controller 114 may include any suitable combination of software, firmware, and hardware.

[0036] Controller 114 may additionally include one or more processing modules 148. The processing modules 148 may each include one or more microprocessors, controllers, or any other suitable computing devices or resources and may work, either alone or with other components of system 100, to provide a portion or all of the functionality of system 100 described herein. Controller 114 may additionally include (or be communicatively coupled to via wireless or wireline communication) one or more memory modules 150. The memory modules 150 may each include any memory or database module and may take the form of volatile or non-volatile memory, including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable local or remote memory component.

[0037] In certain embodiments, it may be desirable for robot carriage 110 to translate along track 108 at a speed corresponding to a milking stall 104 of rotary milking platform 102 such that the robot arm 112 riding on robot carriage may perform one or more functions associated with the milking of a dairy cow 106 in the milking stall 104 while the rotary milking platform 102 is in motion. Accordingly, controller 114 may include position control logic 152, which may include any information, logic, and/or instructions stored and/or executed by controller 114 to control the movement of robot carriage 110 on track 108 relative to a stall 104 of rotary milking platform 102. For example, position control logic 152 may be operable to control the movement of robot carriage 110 on track 108 based on one or more rotary encoder signals 118 generated by rotary encoder 116.

[0038] In certain embodiments, position control logic 152 may determine a desired linear position for robot carriage 110 ($X_{desired}$) based on a comparison of (1) a first rotary encoder signal 118 corresponding to a rotational position of rotary milking platform 102 at which a particular stall 104 is adjacent to a starting linear position of robot carriage 110 on track 108 (X_{start}), and (2) a second rotary encoder signal 118 corresponding to a current position of the particular stall 104 (a position at which the particular stall 104 is adjacent to position located between the starting linear position of robot carriage 110 on track 108 (X_{start}), and an ending linear position of robot carriage 110 on track 108 (X_{end})). For example, the first rotary encoder signal 118 may comprise a count of pulses generated by rotary encoder 116 at the time when the particular stall 104 triggers a proximity switch (or any other suitable sensor) indicating that the particular stall 104 has reached a position adjacent to a starting linear position of robot carriage 110 on track 108 (X_{start}), and the second rotary encoder signal 118 may comprise a current count of pulses generated by rotary encoder 116. As a result, the difference between the second rotary encoder signal 118 and the first rotary encoder signal 118 may correspond to a distance traveled by the particular stall 104 through the area adjacent to track 108.

[0039] Because the outside circumference of rotary milking platform 102 and the number of pulses generated by

rotary encoder 116 per revolution of rotary milking platform 102 may each be known (e.g., 50 meters and 1000 pulses/revolution, respectively), the distance traveled by a milking stall 104 of rotary milking platform 102 per pulse of rotary encoder 116 may also be known (e.g., 50 meters/1000 pulses, or 0.05 meters per pulse). Therefore, the number of pulses generated by rotary encoder 116 between the first rotational position (i.e., the position at which the milking stall 104 is adjacent to X_{start}) and the second rotational position may correspond to the total distance traveled by the milking stall 104 after passing the position adjacent X_{start} . Because robot carriage 110 will need to move from X_{start} the same distance to track the movement of the milking stall 104, the desired linear position for robot carriage 110 ($X_{desired}$) relative to the starting linear position of robot carriage 110 (X_{start}) may be determined as follows:

$$X_{desired} = \frac{EV_2 - EV_1}{A}$$

[0040] where:

[0041] $X_{desired}$ =linear position of robot carriage 110 relative to X_{start} ;

[0042] EV_1 =rotary encoder value (# of pulses) of first rotary encoder signal;

[0043] EV_2 =rotary encoder value (# of pulses) of second rotary encoder signal; and

[0044] A =distance traveled by a milking stall 104 per pulse of rotary encoder 116 ((# of pulses per revolution of rotary milking platform 102)/(outside circumference of rotary milking platform 102))

[0045] Having determined the desired linear position of robot carriage 110 on track 108, position control logic 152 may be further operable to generate a position signal 154 to be communicated to carriage actuator 132 (and/or actuator drive mechanism 134). The position signal 154 may cause extension/retraction of carriage actuator 132 such that robot carriage 108 is moved to the desired linear position ($X_{desired}$). By repeating the above-described calculation of the desired linear position of robot carriage 110 ($X_{desired}$) at regular intervals, position control logic 152 may cause robot carriage 108 to track the movement of the particular stall 104 of milking parlor 102 as the stall moves adjacent to track 108. Moreover, when a next stall 104 reaches a position adjacent to the starting linear position of robot carriage 110 on track 108 (X_{start}) (e.g., triggering the above-described proximity switch), position control logic 152 may cause robot carriage 108 to track the movement of the next stall 104. As a result, position control logic 152 may allow robot carriage 104 to track the movement of each stall 104 of rotary milking platform 104 as each stall moves through the area adjacent to track 108.

[0046] In certain embodiments, position control logic 152 may be further operable to determine an error between the calculated desired linear position for robot carriage 110 ($X_{desired}$) and an actual linear position of robot carriage 110 (X_{actual}). Position control logic 152 may determine the actual linear position of robot carriage 110 (X_{actual}) relative to the starting linear position of robot carriage 110 (X_{start}) based on the number of pulses of an absolute encoder signal 126 generated by absolute encoder 124 (as absolute encoder 124 may generate a known number of pulses per meter of linear movement of carriage 110). If the determined error exceeds a threshold value (e.g., 0.1 meters), position control logic 152

may cause the rotation of rotary milking platform 102 to stop (e.g., by communicating a stopping signal to a rotary drive motor of rotary milking platform 102).

[0047] With robot carriage translating laterally along track 108 at a speed corresponding to that of a milking stall 104 of rotary milking platform 102 (as described above), at least a portion of robot arm 112 may be extended between the legs of a dairy cow 106 in milking stall 104 in order to perform one or more operations associated with the milking of the dairy cow 106. In order to avoid contact between the robot arm 112 and the dairy cow 106, it may be desirable to ensure that the legs of the dairy cow 106, such as the hind legs, are spaced far enough apart to allow for the extension of at least a portion of robot arm 112 there between. Accordingly, controller 114 may additionally include vision control logic 156, which may include any information, logic, and/or instructions stored and/or executed by controller 114 to determine, based on image signal(s) 146 generated by vision system 142, whether the hind legs of a dairy cow 106 are spaced far enough apart to allow for a particular operation by robot arm 112. In a particular embodiment, vision control logic 156 may determine whether the hind legs of a dairy cow 106 are spaced far enough apart by analyzing image signal 146 to find particular edges of the rear of the dairy cow 106. The particular edges may be located by analyzing depth information of the visual data and to determine which portions represent the dairy cow 106 and which portions do not (as the transitions between those portions may represent the particular edges of the rear of the dairy cow 106).

[0048] For example, vision control logic 156 may process an image signal 146 to determine the depth of the pixels in the x-dimension (as reflected by the coordinate system illustrated in FIG. 3), which may represent a distance between camera 144 and a particular object (e.g., the dairy cow 106, a portion of the milking stall 104, etc.) presented in the image signal 146. An example method of determining the depth of pixels may be by measuring the time of flight of a light signal between camera 144 and a particular object captured in image signal 146 in the x-dimension. Vision control logic 156 may then compare the depth information of a cluster of pixels of image signal 146 to the depth information of another cluster of pixels within a portion of image signal 146. Because a cluster of pixels relatively close to camera 144 may signify the dairy cow 106 and a cluster of pixels relatively far away from camera 144 may signify an object other than the dairy cow 106 (e.g., a portion of the milking stall 104 housing the dairy cow 106), a portion of image signal 146 where pixels transition from relatively close to camera 144 to relatively far away from camera 144 (or vice versa) may correspond to an edge location of the dairy cow 106.

[0049] FIG. 4 illustrates an example image signal 146 that may be processed by vision control logic 156 in order to determine whether the hind legs of a dairy cow 106 are spaced far enough apart to allow for a particular operation by robot arm 112. Vision control logic 156, by comparing depth information of the visual data (as described above), may process the image signal 146 to determine hip locations 402, outer hind locations 404, and inner hind locations 406. In particular, vision control logic 156 may begin to determine whether the hind legs of the dairy cow 106 are spaced far enough apart by locating hip location 402a. Vision control logic 156 may do this by comparing the depth locations of pixels of an upper outer area of image signal 146, or any other area of image signal 146 likely to include the hip of the dairy cow 106.

Vision control logic 156 may determine that the cluster of pixels where depth location transitions from being relatively close to camera 144 to relatively far from camera 144 (or vice versa) represents a first edge corresponding to the hip of the dairy cow 106. In certain embodiments, this location may correspond with hip location 402a. Vision control logic 156 may then store the hip location 402a in memory 150 or in any other suitable component of controller 114.

[0050] After determining the hip location 402a of dairy cow 106, vision control logic 156 may attempt to locate the hind leg of the dairy cow 106. For example, vision control logic 156 may analyze a portion of the image signal 146 below the determined hip location 402a in the y-dimension (as reflected by the coordinate system illustrated in FIG. 3) as that location may be likely to include outer hind location 404a. By locating edges in pixel depth in that area of image signal 146 (in a substantially similar manner to that described above), vision control logic 156 may locate outer hind location 404a (which may be stored in memory 150 or in any other suitable component of controller 114). Having determined outer hind location 404a, vision control logic 156 may begin to analyze portions of the image signal 146 to the right of the determined hip location 402a in the z-dimension (as reflected by the coordinate system illustrated in FIG. 3) as the next encountered edge in depth in that direction may correspond to inner hind location 406a (which may be stored in memory 150 or in any other suitable component of controller 114).

[0051] In certain embodiments, vision control logic 156, having determined inner hind location 406a, may analyze portions of image signal 146 above and below (in the y-dimension, as reflected by the coordinate system illustrated in FIG. 3) the determined inner hind location 406a to locate subsequent edges in depth. These additional edges in depth may represent an outline of the inner edge of the hind leg of the dairy cow 106.

[0052] Having determined hip location 402a, outer hind location 404a, inner hind location 406a, and the inner edge of the hind leg of the dairy cow 106, vision control logic 156 may process the opposing side of image signal 146 to determine hip location 402b, outer hind location 404b, inner hind location 406b, and the inner edge of the other hind leg of the dairy cow 106 (in a substantially similar manner to that described above).

[0053] Once the inner edges of each hind leg of the dairy cow 106 have been located, vision control logic 156 may determine whether the hind legs of the dairy cow 106 are far apart enough to allow for the proper operation of at least a portion of robot arm 112 by calculating the distance between the hind legs. For example, vision control logic 156 may calculate the distance between inner hind locations 406a and 406b. As another example, vision control logic 156 may determine an inner-most point along the inner edge of each hind leg of the dairy cow 106 (e.g., the location along each determined inner edge closest to the center of the image signal 146) and calculate the distance between those two points. In certain embodiments, the inner-most point of each hind leg may be calculated within a working area. For example, the working area may be an area between the inner hind edges where robot arm 112 may operate. The measurements of the working area may be based at least in part upon the width and/or height of a portion of robot arm 112 likely to be operating between the hind legs of the dairy cow 106. In such an embodiment, vision control logic 156 may analyze visual data along the detected inner hind edge in a substantially

vertical direction within the working area to determine the inner-most location. If the determined distance between the hind legs exceeds a distance threshold (e.g., a minimum distance allowing for the robot arm 112 to properly operate), vision control logic 156 may determine that the hind legs of the dairy cow 106 are spaced far enough apart to allow for the proper operation of at least a portion of robot arm 112.

[0054] If vision control logic 156 determines that the hind legs of the dairy cow 106 are spaced far enough apart, vision control logic 156 may facilitate the communication of signals to one or more of arm actuators 138, the communicated signals causing extension/retraction of arm actuators 138 such that at least a portion of robot arm 112 (e.g., tool attachment 140) extends toward the space between the hind legs of the dairy cow 106 (e.g., at a predetermined height relative to the milking stall in which the dairy cow 106 is located). Because image signal 146 may comprise a three-dimensional video image (as described above), the image signal 146 may change in real time as camera 144 moves toward the dairy cow 106. Accordingly, the present disclosure contemplates that vision control logic 156 may update, either continuously or at predetermined intervals, the determined leg positions as image signal 146 changes. Furthermore, vision control logic 156, or any other suitable component, may be operable to determine whether a portion of robot arm 112 is in contact with the dairy cow 106. In such an instance, vision control logic 156 may facilitate the communication of signals to one or more of arm actuators 138 to cause extension/retraction of arm actuators 138 such that at least a portion of robot arm 112 is no longer in contact with the dairy cow.

[0055] Although the above-described example embodiment relates to determining whether there is enough space between the hind legs of a dairy cow 106, the present disclosure contemplates that vision control logic 156 performance may determine, in a similar manner, whether there is enough space between a front leg and a hind leg of a dairy cow 106.

[0056] Prior to extending at least a portion of the robot arm 112 between the hind legs of the dairy cow 106 to perform certain functions associated with the milking of the dairy cow 106 (e.g., applying disinfectant to the teats to the dairy livestock 106), it may be desirable to ensure that a milking claw 107 is not attached to the teats of a dairy cow 106. Accordingly, controller 114 may additionally include milking claw detection logic 158, which may include any information, logic, and/or instructions stored and/or executed by controller 114 to determine whether to extend robot arm 112 between the hind legs of a dairy cow 106 based on whether a milking claw 107 is attached to the teats of the dairy cow 106.

[0057] In certain embodiments, milking claw detection logic 158 may determine whether a milking claw 107 is attached to the teats of the dairy cow 106 when a milking stall 104 in which the dairy cow 106 is located enters an area adjacent to track 108 and robot arm 112. For example, milking claw detection logic 158 may receive a trigger (e.g. from a proximity switch or any other suitable sensor associated with the rotary milking platform 102) indicating that the milking stall 104 in which the dairy cow 106 is located has entered an area adjacent to track 108, and may determine whether a milking claw 107 is attached in response to that trigger. Moreover, milking claw detection logic 158 may determine whether a milking claw 107 is attached while rotary milking platform 102 is rotating and while the robot carriage 110 carrying robot arm 112 translates along track 108 at a speed corresponding to that of the stall 104 housing

the dairy cow 106 (as described above). Alternatively, milking claw detection logic 158 may determine whether a milking claw 107 is attached while robot arm 112 remains stationary, and robot carriage 110 may begin to track the movement of the milking stall subsequent to a determination that the milking claw 107 is not attached.

[0058] Milking claw detection logic 158 may determine whether a milking claw 107 is attached using one of at least three different methods. As a first method, milking claw detection logic 158 may access a milking claw detachment signal 147, the milking claw detachment signal 147 indicating whether the milking claw 107 has detached from the teats of the dairy cow. Milking claw detachment signal 147 may be generated by a computer system associated with the rotary milking platform 102. Alternatively, rather than indicating whether the milking claw 107 has detached, milking claw detachment signal 147 may indicate whether the milking claw 107 is attached to the teats of the dairy cow 106. In other embodiments, milking claw detachment signal 147 may indicate other operational data associated with the rotary milking platform 102 from which milking claw detection logic 158 may determine whether milking claw 107 is attached. For example, milking claw detachment signal 147 may indicate whether vacuum pressure is being applied to the milking claw 107 as part of a milking operation, from which milking claw detection logic 158 may determine that milking claw 107 is attached to the teats of the dairy cow. Thus, milking claw detection logic 158 may determine whether the milking claw 107 is attached based on milking claw detachment signal 147.

[0059] As a second method of determining whether milking claw 107 is attached, milking claw detection logic 158 may determine whether the milking claw 107 is present at a storage location 115 (i.e. no longer attached to the teats of the dairy cow) by processing an image signal 146 (e.g., a three-dimensional video image signal), as described above) representing the storage location 115 of a milking stall 104. FIGS. 5A-5B illustrate example snapshots 500a-b of an image signal 146 corresponding to an example storage location 115 of an example milking stall 104, according to certain embodiments of the present disclosure. In particular, FIG. 5A illustrates an example snapshot 500a of an image signal 146 corresponding to storage location 115 when milking claw 107 is present at storage location 115, and FIG. 5B illustrates an example snapshot 500b of an image signal 146 corresponding to storage location 115 when milking claw 107 is not present at storage location 115.

[0060] As one way of determining whether the milking claw 107 is present at the storage location 115 based on an accessed image signal 146, milking claw detection logic 158 may compare the accessed image signal 146 to a reference image signal 160. In certain embodiments, the reference image signal 160 may correspond to storage location 115 when the milking claw 107 is present at storage location 115 (e.g., snapshot 500a of FIG. 5A). The comparison may be performed by comparison of individual depth values of image signal 146 with individual depth values of the reference image signal 160, by correlation of image signal 146 with the reference image signal 160 using any suitable correlation detector, or by any other suitable method. If image signal 146 is sufficiently similar to the reference image signal 160, milking claw detection logic 158 may determine that milking claw 107 is present at storage location 115, and therefore that milking claw 107 is not attached to the teats of the dairy cow. In certain other embodiments, the reference image signal 160

may correspond to storage location 115 when the milking claw 107 is not present at storage location 115 (e.g., snapshot 500b of FIG. 5B). In that case, if image signal 146 is sufficiently similar to the reference image signal 160, milking claw detection logic 158 may determine that milking claw 107 is not present at storage location 115, and therefore that milking claw 107 is attached to the teats of the dairy cow.

[0061] Alternatively, milking claw detection logic 158 may compare an accessed image signal 146 to two reference image signals 160: a first reference image signal 160 that corresponds to storage location 115 when the milking claw 107 is present at storage location 115, and a second reference image signal 160 that corresponds to storage location 115 when the milking claw 107 is not present at storage location 115. Milking claw detection logic 158 may then determine whether image signal 146 is more similar to the first reference image signal 160, in which case milking claw detection logic 158 may determine that milking claw 107 is not attached to the teats of the dairy cow, or to the second reference image signal 160, in which case milking claw detection logic 158 may determine that milking claw 107 is attached to the teats of the dairy cow.

[0062] As another way of determining whether the milking claw 107 is present at the storage location 115 based on an accessed image signal 146, milking claw detection logic 158 may compare the plurality of depth values of image signal 146 to a threshold depth value. Because milking claw 107, when present at storage location 115, may be relatively close to camera 144 as compared to the space located around milking claw 107, and as compared to storage location 115 when milking claw 107 is not present, if many depth values in image signal 146 are smaller (i.e. closer to camera 144) than a threshold depth value, it may indicate that milking claw 107 is present at storage location 115. Conversely, if few depth values in image signal 146 are smaller than a threshold depth value, it may indicate that milking claw 107 is not present at storage location 115. In certain embodiments, milking claw detection logic 158 may count the number of depth values in image signal 146 that are smaller than the threshold depth value. If the counted number is greater than a determined triggering count, milking claw detection logic 158 may determine that milking claw 107 is present at storage location 115, and therefore that milking claw 107 is not attached to the teats of the dairy cow. Otherwise, milking claw detection logic 158 may determine that milking claw 107 is not present at storage location 115, and therefore that milking claw 107 is attached to the teats of the dairy cow. The determined triggering count may be set to one, an arbitrary number, a number based on the resolution of camera 144, a number determined by analyzing one or more reference image signals 160, or any other suitable number.

[0063] In alternative embodiments, milking claw detection logic 158 may count the number of depth values in image signal 146 that exceed the threshold depth value. If the counted number is greater than a determined triggering count, milking claw detection logic 158 may determine that milking claw 107 is not present at storage location 115, and therefore that milking claw 107 is attached to the teats of the dairy cow. Otherwise, milking claw detection logic 158 may determine that milking claw 107 is present at storage location 115, and therefore that milking claw 107 is not attached to the teats of the dairy cow.

[0064] In some embodiments, the threshold depth value may be selected based on the distance between camera 144

and storage location 115. In other embodiments, the threshold depth value may be selected based on a reference image signal 160. For example, using a reference image signal 160 corresponding to storage location 115 when the milking claw 107 is not present at storage location 115, as illustrated in FIG. 5B, the threshold value could be set such that all or substantially all of the depth values in the reference image signal 160 would be greater than the threshold value.

[0065] As a third method of determining whether milking claw 107 is attached, milking claw detection logic 158 may process an image signal 146 (e.g., a three-dimensional video image signal) representing the rear of the dairy cow 106 in order to determine whether the milking claw 107 is attached to the teats of the dairy cow 106. For example, milking claw detection logic 158 may determine whether milking claw 107 is attached by processing the image signal 146 of the rear of the dairy cow 106 using either of the techniques described above—comparing image signal 146 to a reference image signal 160, or comparing the plurality of depth values in image signal 146 to a threshold depth value—or any other suitable technique. In this case, reference image signal 160 may correspond to the rear of the dairy cow when milking claw 107 is attached (i.e. present in the image). Similarity of image signal 146 to reference image signal 160 may then indicate that milking claw 107 is attached. Conversely, reference image signal 160 may correspond to the rear of the dairy cow when milking claw 107 is not attached, in which case similarity to image signal 146 may indicate that milking claw 107 is not attached. Likewise, the threshold depth value may be set based on one or more reference image signals 160 or based on a distance between camera 144 and the expected location of milking claw 107 when attached (e.g. the teats of the cow).

[0066] Because camera 144 of vision system 142 may not generate both of the above-described image signals 146 (i.e., the image signal 146 including storage location 115 and the image signal 146 including the rear of the dairy cow 106) with robot arm 112 in the same position (as both locations may not be in the field of view of camera 144), all or a portion of robot arm 112 may be able to articulate between the different imaging positions. For example, as illustrated in FIGS. 6A-6B, robot arm 112 may be operable to pivot between an imaging position (e.g., a position where an image signal 146 representing storage location 115 may be generated, as illustrated in FIG. 6A) and an operating position (e.g., a position where an image signal 146 representing the rear of the dairy cow 106 may be generated, as illustrated in FIG. 6A). This illustrated articulation of robot arm 112 be accomplished, for example, by rotation of tool attachment 140 about the point of attachment to arm member 136 (e.g. by extension/retraction of arm actuator 138). In certain embodiments (e.g., embodiments in which the attachment of a milking claw is determined by processing an image signal 146 representing the storage location 115, as described above), milking claw detection logic 158 may control the robot arm 112 to pivot to the imaging position (e.g. by communicating a signal to arm actuator 138 to extend or retract) before accessing the image signal 146 upon which the determination is made. Subsequently, after determining that a milking claw 107 is attached, controller 114 may control the robot arm 112 to pivot to the operating position (e.g. by communicating a signal to arm actuator 138 to extend or retract) before accessing the image signal 146 to determine the position of the cow's legs (e.g. using vision control logic 156).

[0067] If, based on one or more of the above-described method, milking claw detection logic 158 determines that a milking claw 107 is not attached, controller 114 may initiate performing further desired operations (e.g. the disinfectant application process) by extending robot arm 112 between the hind legs of dairy cow 106 (e.g. using vision control logic 156). Otherwise, no further action may be performed until a next milking stall 104 enters the area adjacent to track 108 and robot arm 112.

[0068] Particular embodiments of system 100 may provide one or more technical advantages. For example, certain embodiments of system 100 may allow robot carriage 110 to accurately track the movement of a stall 104 of the adjacent rotary milking platform 102. Because the robot carriage 110 may carry a robot arm 112 configured to perform one or more functions associated with the milking of a dairy cow 106 located in the stall 104 of the rotary milking platform 102 (e.g., a robotic arm for applying disinfectant to the teats of the dairy livestock and/or attaching a milking claw to the teats of the dairy livestock), certain embodiments of system 100 may facilitate a reduction in the need for human labor to perform certain functions associated with milking dairy cows 106 using rotary milking platform 102. As a result, certain embodiments of system 100 may reduce the cost associated with certain dairy milking operations. In addition, the automation facilitated by certain embodiments of system 100 may increase the throughput of rotary milking platform 102, thereby increasing the overall milk production of rotary milking platform 102.

[0069] As another example, using vision system 142 may improve the visibility of the dairy cow 106 and may facilitate milking-related operations from a position to the rear of the dairy cow 106. Approaching from the rear of the dairy cow makes it less likely that the cow will be distracted by the milking equipment. Furthermore, approaching from the rear of the dairy cow makes it less likely that the dairy livestock will kick the milking equipment, vision system 142, or any other component of the system of the present disclosure. Additionally, use of vision system 142 may allow for the safe operation of robot arm 112 without disturbing the dairy cow during any portion of the milking operation. For example, vision system 142 may facilitate the detection of a properly spaced working area between the hind legs of the dairy cow, allowing robot arm 112 to extend between the dairy cow's hind legs without coming into contact with the dairy cow. Moreover, by preventing the robot arm 112 from extending between the legs of a dairy cow 106 while a milking claw is attached to the teats of the cow, certain embodiments of system 100 may prevent injury to the cow and/or damage to the robot arm 112 or other components of system 100.

[0070] Although a particular implementation of system 100 is illustrated and primarily described, the present disclosure contemplates any suitable implementation of system 100, according to particular needs. For example, although certain of the above-described functions are described as being performed by position control logic 152, vision control logic 156, or milking claw detection logic 158, the present disclosure contemplates the described functionality as being performed by any suitable logic or combination of logic, according to particular needs. Additionally, although the vision system 142 housing camera 144 is depicted and described above as being positioned on tool attachment 140, the present disclosure contemplates vision system 142 being located separate from tool attachment 140, as depicted in the

alternative example rotary milking system 700 depicted in FIG. 7. In the depicted alternative system 700 embodiments, a standalone vision system 702 housing a camera 704 may be positioned on the ground near robot arm 112. Use of standalone vision system 702 may be advantageous when a storage location 115 of a milking stall 104 would be below the line of sight of a camera mounted on robot arm 112.

[0071] FIG. 8 illustrates an example method 800 for controlling the position of robot carriage 110 based on the position of a stall 104 of an adjacent rotary milking platform 102, according to certain embodiments of the present disclosure. Although method 800 is described with regard to tracking the movement of a single stall 104, the present disclosure contemplates that method 800 could be performed for each stall 104 of a rotary milking platform 102.

[0072] The method begins at step 802. At step 804, controller 114 receives a first rotary encoder signal 118 generated by rotary encoder 116. The first rotary encoder signal 118 may comprise a number of pulses generated by rotary encoder 116 when a particular milking stall 104 of rotary milking platform 102 is located adjacent to the starting linear position of robot carriage 110 on the track 108 positioned adjacent to rotary milking platform 102. At step 806, controller 114 receives a second rotary encoder signal 118 indicating a second rotational position of the particular stall 104 of rotary milking platform 102.

[0073] At step 808, controller 114 determines a desired linear position of robot carriage 110 on track 108 based on the difference between the second rotary encoder signal 118 and the first rotary encoder signal 118 (as described above with regard to FIG. 1). The determined desired linear position of robot carriage 110 is a position corresponding to the second rotational position of the particular stall 104 (i.e., the current position of the particular stall 104).

[0074] At step 810, controller 114 communicates a position signal 154 to a carriage actuator 132 coupled to robot carriage 110 and track 108. The position signal 154 may cause extension/retraction of carriage actuator 132 such that robot carriage 110 is moved along track 108 to the desired linear position.

[0075] At step 812, controller 114 receives an absolute encoder signal 126 generated by absolute encoder 124. The absolute encoder signal 126 corresponds to the actual linear position of robot carriage 110 on track 108 (as absolute encoder 124 may generate a known number of pulses per meter traveled by robot carriage 110). At step 814, controller 114 determines a position error based on a comparison of the actual linear position of the robot carriage 110 and the previously-calculated desired linear position of robot carriage 110. At step 816, controller 114 determines if the position error exceeds a threshold value. If the position error does exceed the threshold value, controller 114 causes the rotation of rotary milking platform 102 to stop (e.g., by communicating a stopping signal to a rotary drive motor of rotary milking platform 102) and the method ends at step 818. Otherwise, the method returns to step 804.

[0076] Although the steps of method 800 have been described as being performed in a particular order, the present disclosure contemplates that the steps of method 800 may be performed in any suitable order, according to particular needs.

[0077] Although the present disclosure has been described with several embodiments, diverse changes, substitutions, variations, alterations, and modifications may be suggested to

one skilled in the art, and it is intended that the disclosure encompass all such changes, substitutions, variations, alterations, and modifications as fall within the spirit and scope of the appended claims.

[0078] FIG. 9 illustrates an example method for analyzing an image signal 146 to determine if the hind legs of a dairy cow 106 are spaced far enough apart to allow for extension of robot arm 112, according to certain embodiments of the present disclosure. The example method may begin at step 900. At step 900, vision control logic 156 may begin to compare pixels of an upper outer area of an image. For example, vision control logic 156 may access image signal 146 generated by camera 144. Vision control logic 156 may compare the pixels of image signal 146 by determining the depth of the pixels. In certain embodiments, the depth may be determined by measuring the time of flight of a light signal between camera 144 and a particular object captured in image signal 146. After collecting the depth information of a particular portion of pixels, the method may proceed to step 904. At step 904, vision control logic 156 may determine whether some pixels are closer than other pixels within a portion of image signal 146. For example, vision control logic 156 may compare the depth information of a group of pixels to determine if some pixels are closer than other pixels. A portion of image signal 146 which transitions from a cluster of pixels further from camera 144 to a cluster of pixels closer to camera 144 (or vice versa) may signify that an edge of the dairy cow 106 has been found. The cluster of pixels with depth information further away from camera 144 may signify that the image data is of an object other than an edge of the dairy cow 106. If vision control logic 156 has determined that some pixels are not closer than other pixels, then the example method may return to step 900 and continue analyzing information captured by camera 144. Otherwise, the example method may proceed to step 908.

[0079] At step 908, vision control logic 156 may associate the location of the cluster of pixels that are closer to camera 144 with an edge of the dairy cow 106. For example, vision control logic 156 may have determined that the cluster of pixels represents a first edge corresponding to the hip of the dairy cow 106. In certain embodiments, this location may correspond with hip location 402a of FIG. 4. Vision control logic 156 may store this association in memory 150 or in any other suitable component of controller 114.

[0080] After finding the hip of the dairy cow 106, vision control logic 156 may attempt to locate the hind leg of the dairy cow 106. To do this, at step 912, vision control logic 156 may compare the depth information of pixels in a lower outer area of image signal 146 or any other portion of image signal 146 that may include the hind legs of the dairy cow 106. For example, vision control logic 156 may traverse pixels of image signal 146 in a downward direction trying to locate the outer edge of a hind leg of a dairy cow 106.

[0081] Vision control logic 156 may then determine the location of an outer edge of a hind leg at step 916. Vision control logic 156 may do this by determining whether some pixels are closer than other pixels. A portion of image signal 146 which transitions from a cluster of pixels further from camera 144 to a cluster of pixels closer to camera 144 (or vice versa) may signify that an edge of the dairy cow 106 has been found. If vision control logic 156 has determined that some pixels are not closer than other pixels, then the example method may return to step 912 and continue analyzing infor-

mation captured by camera 144. Otherwise, the example method may proceed to step 920.

[0082] At step 920, vision control logic 156 may associate the location of the cluster of pixels that are closer to camera 144 than another cluster of pixels within a portion of visual signal 146 with an edge of the dairy cow 106. For example, vision control logic 156 may have determined that the cluster of pixels represents an edge corresponding to an outer edge of a hind leg of the dairy cow 106. In certain embodiments, this location may correspond with outer edge location 404a of FIG. 4. Vision control logic 156 may store this association in memory 150 or in any other suitable component of controller 114.

[0083] Vision control logic 156 may then attempt to determine an inner edge location of a hind leg. At step 924, vision control logic 156 may begin to scan the depth information of pixels along a lower inner area of image signal 146. For example, vision control logic 156 may traverse pixels along the z-dimension (as illustrated in FIG. 3) from outer edge location 404a to the center of image signal 146 trying to locate an inner edge of the hind leg of the dairy cow 106. At step 928, vision control logic 156 may determine whether some pixels are closer than other pixels. For example, vision control logic 156 may compare the depth information of a group of pixels to determine if a cluster of the pixels are closer than another cluster of pixels. If vision control logic 156 has determined that some pixels are not closer than other pixels, then the example method may return to step 924 and continue analyzing information captured by camera 144. Otherwise, the example method may proceed to step 932.

[0084] At step 932, vision control logic 156 may associate the location of the cluster of pixels that are closer to camera 144 with an edge of the dairy cow 106. For example, vision control logic 156 may have determined that the cluster of pixels represents an edge corresponding to an inner edge of a hind leg of the dairy cow 106. In certain embodiments, this location may correspond with inner edge location 406a of FIG. 4. In certain embodiments, vision control logic 156 may determine edge location 406a is the inner-most location of the hind legs of the dairy cow. For example, vision control logic 156 may analyze visual data along the detected inner edge in a substantially vertical direction to determine the inner-most location of the hind leg. The portion of the hind leg closest to the center of the dairy cow in the z-dimension may be considered the inner-most portion. In other embodiments, vision control logic 156 may determine edge location 406a is the inner-most location of the hind legs within the working area of dairy cow 106. For example, the working area may be an area between the inner hind edges where robot arm 112 may operate. The measurements of the working area may be based at least in part upon the width and/or height of a portion of robot arm 112 likely to be operating between the hind legs of the dairy cow 106. In such an embodiment, vision control logic 156 may analyze visual data along the detected inner hind edge in a substantially vertical direction within the working area to determine the inner-most location. Vision control logic 156 may store the association between the determined location and inner edge location 406a in memory 150 or in any other suitable component of controller 114.

[0085] After finding the edges corresponding to a side of the dairy cow 106, vision control logic 156 may determine if data points from both sides of the dairy cow 106 have been collected at step 936. If vision control logic 156 determines that data points from only a single side of the dairy cow 106

has been found, vision control logic 156 may proceed to determine the locations of the other hind leg of the dairy cow 106 at step 900. Otherwise, the example method may proceed to step 940.

[0086] Once edges of the dairy cow 106 are located, at step 940, vision control logic 156 may determine whether the hind legs of the dairy cow 106 are far apart enough to allow for the proper operation of at least a portion of robot arm 112. For example, after detecting the hind legs of the dairy cow, vision control logic 156 may calculate the distance between the hind legs. Vision control logic 156 may use any portion of image signal 146 to calculate the distance between the hind legs. In certain embodiments, vision control logic 156 may calculate the distance between the two inner hind edges of the dairy cow 106. As an example, vision control logic 156 may calculate the distance between inner edge locations 406a and 406b of FIG. 4. Vision control logic 156 may then determine whether the hind legs are far enough apart to properly operate at least a portion of robot arm 112. In certain embodiments, there may be a distance threshold associated with robot arm 112, wherein the distance threshold specifies a minimum distance between a dairy cow's hind legs which allows for the robot arm 112 to properly operate. For example, there may be a distance threshold based at least in part on the width of robot arm 112 and/or any other equipment robot arm 112 may utilize to perform a particular function. If vision control logic 156 determines that the hind legs of the dairy cow 106 are far enough apart, vision control logic 156 may proceed with allowing robot arm 112 to operate between the hind legs of the dairy cow 106 at step 944. Otherwise, vision control logic 156 may not facilitate the instruction of robot arm 112 to proceed with a particular operation between the hind legs of the dairy cow and the example method may end.

[0087] At step 944, vision control logic 156, having determined the positions of each of the hind legs of the dairy cow, may facilitate the communication of signals to one or more of arm actuators 138, the communicated signals causing extension/retraction of arm actuators 138 such that at least a portion of robot arm 112 (e.g., tool attachment 140) extends toward the space between the hind legs of the dairy cow (e.g., at a predetermined height relative to the milking stall in which the dairy cow is located).

[0088] Although the steps of method 900 have been described as being performed in a particular order, the present disclosure contemplates that the steps of method 1000 may be performed in any suitable order, according to particular needs.

[0089] FIG. 10 illustrates an example method 1000 for determining whether to operate a robot in conjunction with a rotary milking platform based on detection of a milking claw 107, according to certain embodiments of the present disclosure. The method begins at step 1002. At step 1004, controller 114 waits for a trigger indicating that a stall in which a dairy cow is located (e.g., a stall 104 of a rotary milking platform 102 positioned adjacent to track 108 and robot arm 112, as illustrated in FIG. 1) has entered an area adjacent to robot arm 112. For example, the trigger may be received from a proximity switch or any other suitable sensor associated with the rotary milking platform. If controller 114 receives the trigger, the method proceeds to step 1006. If not, controller 114 returns to step 1004 and continues to wait for the trigger.

[0090] At step 1006, controller 114 determines whether a milking claw is attached (e.g. milking claw 107, as described in connection with FIG. 1). This determination may be made

using any of the three methods described above (e.g. using milking claw detection logic 158, as described in connection with FIG. 1), or in any other suitable way. In some embodiments, robot arm 112 may translate laterally to keep pace with the rotation of rotary milking platform 102 while making this determination (e.g. using position control logic 152, as described in connection with FIG. 1). If controller 114 determines that a milking claw is attached, the method proceeds to step 1008, where the controller 114 allows the milking stall to rotate by without extending the robotic arm between the legs of the dairy cow. If controller 114 determines that a milking claw is not attached, the method proceeds to step 1010.

[0091] At step 1010, controller 114 determines whether the hind legs of the dairy cow are far apart enough to allow for the proper operation of at least a portion of the robot arm. If it is not already doing so, the robot arm begins to track the rotational movement of the milking stall by moving laterally along a track (e.g. using position control logic 152). As a result, the robot arm may keep pace with a dairy cow located in a milking stall of the rotary milking platform. The positions of the hind legs of the dairy cow and the distance between them may be determined by processing an image signal from a camera (e.g. image signal 146 generated by vision system 142 housing camera 144, as described in connection with FIG. 2) in the manner described above (e.g. using vision control logic 156). If the hind legs are far enough apart (e.g. as determined by vision control logic 156), the method proceeds to step 1012. If not, the method proceeds to step 1008, where the controller 114 allows the milking stall to rotate by without extending the robotic arm between the legs of the dairy cow. In some embodiments, the robot arm may then stop tracking the movement of the stall in order to allow the stall to rotate by.

[0092] At step 1012, controller 114, having determined the positions of each of the hind legs of the dairy cow, may communicate signals to one or more of arm actuators 138, the communicated signals causing extension/retraction of arm actuators 138 such that at least a portion of robot arm 112 (e.g., tool attachment 140) extends toward the space between the hind legs of the dairy cow (e.g., at a predetermined height relative to the milking stall in which the dairy cow is located).

[0093] At step 1014, controller 114 may control the robot arm to perform the desired operation using the tool attachment. For example, a spray tool attachment may initiate the discharge of a disinfectant to the teats of the dairy cow. Once the function has been performed, controller 114 may, at step 1016, communicate signals to one or more of arm actuators 138, such that the robot arm retracts from between the legs of the dairy cow. In some embodiments, the robot arm may then stop tracking the movement of the stall in order to allow the stall to rotate by. The method then either returns to step 1004 (if there are additional dairy cows on which milking operations are to be performed) or ends at step 1018 (if there are no additional dairy cows on which milking operations are to be performed).

[0094] Although the steps of method 1000 have been described as being performed in a particular order, the present disclosure contemplates that the steps of method 1000 may be performed in any suitable order, according to particular needs.

[0095] Although the present disclosure has been described with several embodiments, diverse changes, substitutions, variations, alterations, and modifications may be suggested to one skilled in the art, and it is intended that the disclosure

encompass all such changes, substitutions, variations, alterations, and modifications as fall within the spirit and scope of the appended claims.

What is claimed is:

1. A system comprising:
 - a three-dimensional camera; and
 - a processor communicatively coupled to the three-dimensional camera, the processor operable to:
 - determine a first hind location of a first hind leg of a dairy livestock based at least in part on visual data captured by the three-dimensional camera;
 - determine a second hind location of a second hind leg of the dairy livestock based at least in part on the visual data;
 - determine a measurement, wherein the measurement is the distance between the first hind location and the second hind location; and
 - determine whether the measurement exceeds a minimum threshold.
2. The system of claim 1, further comprising a robotic arm coupled to the three-dimensional camera and wherein the processor is further operable to communicate an instruction to position the robotic arm.
3. The system of claim 2, wherein the processor is further operable to communicate an instruction to position the robotic arm between the hind legs in response to determining that the measurement exceeds the minimum threshold.
4. The system of claim 3, wherein positioning the robotic arm between the hind legs comprises the robotic arm approaching an udder of the dairy livestock from the rear of the dairy livestock.
5. The system of claim 2, wherein the processor is further operable to determine whether a portion of the robotic arm is in contact with the dairy livestock.
6. The system of claim 2, wherein the processor is further operable to prevent the robotic arm from extending between the hind legs of the dairy livestock in response to determining that the measurement is less than the minimum threshold.
7. The system of claim 2, further comprising a first rail coupled to the robotic arm, the first rail operable to facilitate movement of the robotic arm in a direction relative to a movement of the dairy livestock.
8. The system of claim 7, further comprising an encoder operable to determine a displacement measurement of the movement of the dairy livestock.
9. The system of claim 8, wherein movement of the robotic arm is based at least in part on the displacement measurement.
10. The system of claim 1, wherein the first hind location is an inner hind location of the first hind leg and the second hind location is an inner hind location of the second hind leg.
11. The system of claim 1, wherein determining the first hind location comprises:
 - determining a first location based at least in part upon the visual data, wherein the first location is associated with a first hip of the dairy livestock;
 - determining a second location based at least in part upon the visual data, wherein the second location is associated with an outer hind location of the first hind leg of the dairy livestock; and
 - determining a third location based at least in part upon the visual data, wherein the third location is associated with an inner hind location of the first hind leg.
12. The system of claim 11, wherein determining the second hind location comprises:

determining a fourth location based at least in part upon the visual data, wherein the fourth location is associated with a second hip of the dairy livestock;

determining a fifth location based at least in part upon the visual data, wherein the fifth location is associated with an outer hind location of the second hind leg of the dairy livestock; and

determining a sixth location based at least in part upon the visual data, wherein the sixth location is associated with an inner hind location of the second hind leg.

13. The system of claim 1, wherein the distance between the first hind location and the second hind location is in a first dimension oriented in a left-to-right direction relative to the hind legs of the dairy livestock.

14. A method comprising:

determining a first hind location of a first hind leg of a dairy livestock based at least in part on visual data captured by a three-dimensional camera;

determining a second hind location of a second hind leg of the dairy livestock based at least in part on the visual data;

determining a measurement, wherein the measurement is the distance between the first hind location and the second hind location; and

determining whether the measurement exceeds a minimum threshold.

15. The method of claim 14 further comprising communicating an instruction to position a robotic arm, wherein the three-dimensional camera is coupled to the robotic arm.

16. The method of claim 15 further comprising communicating an instruction to position the robotic arm between the hind legs in response to determining that the measurement exceeds the minimum threshold.

17. The method of claim 16, wherein positioning the robotic arm between the hind legs comprises the robotic arm approaching an udder of the dairy livestock from the rear of the dairy livestock.

18. The method of claim 15 further comprising determining whether a portion of the robotic arm is in contact with the dairy livestock.

19. The method of claim 15 further comprising preventing the robotic arm from extending between the hind legs of the dairy livestock in response to determining that the measurement is less than the minimum threshold.

20. The method of claim 15, wherein the robotic arm is coupled to a first rail, the first rail operable to facilitate movement of the robotic arm in a direction relative to a movement of the dairy livestock.

21. The method of claim 20 further comprising determining, using an encoder, a displacement measurement of the movement of the dairy livestock.

22. The method of claim 21, wherein movement of the robotic arm is based at least in part on the displacement measurement.

23. The method of claim 15, wherein the first hind location is an inner hind location of the first hind leg and the second hind location is an inner hind location of the second hind leg.

24. The method of claim 15, wherein determining the first hind location comprises:

determining a first location based at least in part upon the visual data, wherein the first location is associated with a first hip of the dairy livestock;

determining a second location based at least in part upon the visual data, wherein the second location is associated with an outer hind location of the first hind leg of the dairy livestock; and

determining a third location based at least in part upon the visual data, wherein the third location is associated with an inner hind location of the first hind leg.

25. The method of claim **24**, wherein determining the second hind location comprises:

determining a fourth location based at least in part upon the visual data, wherein the fourth location is associated with a second hip of the dairy livestock;

determining a fifth location based at least in part upon the visual data, wherein the fifth location is associated with an outer hind location of the second hind leg of the dairy livestock; and

determining a sixth location based at least in part upon the visual data, wherein the sixth location is associated with an inner hind location of the second hind leg.

26. The method of claim **15**, wherein the distance between the first hind location and the second hind location is in a first

dimension oriented in a left-to-right direction relative to the hind legs of the dairy livestock.

27. A system comprising:

a three-dimensional camera coupled to a robotic arm; and
a processor communicatively coupled to the three-dimensional camera, the processor operable to:

determine, based at least in part on visual data captured by the three-dimensional camera, whether the distance between the hind legs of a dairy livestock exceeds a minimum threshold; and

extend the robotic arm between the hind legs of the dairy livestock in response to determining that the distance exceeds the minimum threshold.

28. The system of claim **27**, wherein the processor is further operable to prevent the robotic arm from extending between the hind legs of the dairy livestock in response to determining that the distance is less than the minimum threshold.

* * * * *