

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 September 2007 (07.09.2007)

PCT

(10) International Publication Number
WO 2007/099351 A1

(51) International Patent Classification:
C09K 5/04 (2006.01)

(21) International Application Number:
PCT/GB2007/000747

(22) International Filing Date: 5 March 2007 (05.03.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0604305.3 3 March 2006 (03.03.2006) GB
0620570.2 17 October 2006 (17.10.2006) GB

(71) Applicant (for all designated States except US): **RPL HOLDINGS LIMITED** [GB/GB]; 8 Murieston Road, Hale, Altrincham, Cheshire CW6 9NW (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **POOLE, John, Edward** [GB/GB]; Wyntonhorpe, Murieston Road, Hale, Altrincham, Cheshire CW6 9NW (GB). **POWELL, Richard** [GB/GB]; 9 Sadlers Wells, Bunbury, Cheshire CW6 9NW (GB).

(74) Agents: **BROWNE, Robin, Forsythe** et al.; Leaman Browne, 5 South Parade, Leeds LS1 5SQ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: REFRIGERANT COMPOSITION

(57) Abstract: A refrigerant composition consists essentially of three hydrofluorocarbon components selected from HFC134a, HFC125 and HFC143a and an additive selected from a saturated or unsaturated hydrocarbon or mixture thereof boiling in the range -50°C and +40°C.



WO 2007/099351 A1

REFRIGERANT COMPOSITION

This invention relates to refrigerant compositions. The invention relates particularly to refrigerant compositions which have no adverse effect on stratospheric ozone. The invention also relates to compositions which are for use both in refrigeration and air conditioning systems designed to use Ozone Depleting Substances (ODS) such as HCFC22 (chlorodifluoromethane) and also for use in new equipment. These refrigerant compositions are compatible with lubricants commonly found in refrigeration and air conditioning systems and also the new synthetic lubricants (eg polyol ester oils).

Although considerable care is taken to prevent leakage of refrigerant to the atmosphere, on occasions this does occur. In some territories the emission of hydrocarbons is regulated to minimise the generation of tropospheric ozone caused by the effect of sunlight on hydrocarbons mixed with oxygen. To minimise the contribution of hydrocarbon to the atmosphere by leakage of the blends which are the subject of this invention, the hydrocarbon content should be preferably less than 5 % more preferably less than 3.5 %.

The compositions of this invention may also be used in equipment designed for non ozone depleting substances.

It is well known that chlorofluorocarbons (CFCs) such as CFC12 and CFC502 and hydrochlorofluorocarbons such as HCFC22 while being energy efficient, non flammable and of low toxicity, migrate to the stratosphere where they are broken down by ultra violet light to attack the ozone layer. It is desirable to replace these Ozone Depleting Substances by non ozone depleting alternatives such as hydrofluorocarbons (HFCs) which are also non flammable, efficient and of low toxicity. There are six main HFCs, namely HFC134a, HFC32, HFC125, HFC143a, HFC227ea and HFC152a, which either individually or blended into mixtures can replace CFCs and HCFCs. While HFC134a, HFC227ea and HFC152a can be used to replace ODS directly, HFC32, HFC143a, and HFC125 are generally found in blends as replacements for ODS. However, HFCs do not have adequate solubility in traditional lubricants such as mineral and alkylbenzene oils so that synthetic oxygen

containing lubricants have been introduced specifically for new equipment. These new lubricants are expensive and hygroscopic.

Refrigerant blends such as R404A, R507, R410A, R407C and others have been commercialised as replacements for CFCs and HCFCs but, because these compositions contain only HFC components, they cannot be used with the traditional lubricants commonly found in use with CFCs and HCFCs. If these blends are to be used to replace CFCs and HCFCs in existing equipment, the major chemical manufacturers recommend that no more than 5% of the traditional lubricant in the system be retained so that a virtually complete change of lubricant to a synthetic oxygen containing lubricant or a full retrofit may be required. This is often costly and technically unsatisfactory.

Although equipment manufacturers have adapted their units to operate with HFC blends, the commercially available products have not been found to be as satisfactory as the CFCs and HCFCs. In particular to ensure adequate oil return, hydrocarbon lubricants, such as mineral oil, have been replaced by oxygen containing lubricants, notably polyol esters and polyalkylene glycols. Unfortunately these materials are liable to absorb atmospheric moisture, especially during maintenance, which can contribute to excessive corrosion and wear in equipment. This can reduce the reliability of the equipment. It is an object of this invention to provide HFC/hydrocarbon blends that enable the continued use of hydrocarbon oils in both existing and new equipment.

In the search for a refrigerant blend that can be readily used to replace R22 in new & existing equipment, it is especially important that the new blend should have an adequate refrigeration capacity. The capacity should be at least 90% of that of the fluid it is replacing, more preferably at least 95% of that of the fluid it is replacing and most preferably equal to or greater than that of the fluid it is replacing under similar operating conditions. This invention relates to refrigerant compositions which have capacities similar to R22 across the range of applications for air conditioning & refrigeration from high to low temperatures where R22 is commonly found.

Some refrigerants, such as R407C, have wide temperature glides ($> 4^{\circ}\text{C}$) in the evaporator and condenser. Equipment manufacturers, based on their experience with

CFC/HCFC single fluids or azeotropes, prefer refrigerants with low glides. A further object of this invention is to provide HFC/hydrocarbon blends that can substitute for HCFC 22 and HFC blends such as R407C in order to allow the continued use of hydrocarbon lubricants in equipment and minimising the temperature glides in the heat exchangers by providing azeotropic and near azeotropic formulations.

Various terms have been used in patent literature to describe refrigerant mixtures. The following definitions are taken from Standard 34 of the American Society of Heating, Refrigerating & Air Conditioning Engineers (ASHRAE);

Azeotrope: an azeotropic blend is one containing two or more refrigerants whose equilibrium vapour and liquid phase compositions are the same at a given pressure. Azeotropic blends exhibit some segregation of components at other conditions. The extent of the segregation depends on the particular azeotrope and the application.

Azeotropic temperature: the temperature at which the liquid and vapour phases of a blend have the same mole fractionation of each component at equilibrium for a specified pressure.

Near azeotrope: a zeotropic blend with a temperature glide sufficiently small that it may be disregarded without consequential error in analysis for a specific application.

Zeotrope: blends comprising multiple components of different volatilities that, when used in refrigeration cycles, change volumetric composition and saturation temperatures as they evaporate (boil) or condense at constant pressure.

Temperature glide: the absolute value of the difference between the starting and ending temperatures of a phase-change process by a refrigerant within a component of a refrigerating system, exclusive of any subcooling or superheating. This term usually describes condensation or evaporation of a zeotrope.

The present invention relates to near azeotropic and zeotropic refrigerant compositions, which are non flammable under all conditions of fractionation as defined under ASHRAE Standard 34, and which can be used to replace ODS in an existing unit without the need to change the lubricant or make any significant change to the system hardware. In new equipment, the refrigerant compositions allow the continued use of hydrocarbon oils although the unit may be modified to optimise the

performance of the new refrigerant, for example by selecting the most appropriate lengths of capillary tubes. Where the ingress of moisture or other problems are experienced with oxygen containing oils, the new compositions allow such oils to be replaced by hydrocarbon oils

It is known in the art that the addition of a small amount of hydrocarbon to a refrigerant composition containing an HFC or HFC mixtures can result in sufficient hydrocarbon being dissolved in the lubricant to be transported around the system so that lubrication of the compressor is maintained at all times. It is obvious that the greater the hydrocarbon content of the composition the greater the ability of the refrigerant to transport the lubricant back to the compressor. However, too high a hydrocarbon content can lead to flammable mixtures. Although flammable refrigerants are acceptable in some applications, this invention relates to non flammable compositions for use in equipment where flammable refrigerants are prohibited. However, it is not well understood how to achieve non flammable compositions under all conditions including fractionation of the refrigerant compositions which can take place during a leak of the refrigerant from the system or during storage. Flammability in both the liquid and gaseous phases needs to be considered.

Not all HFCs are non flammable as defined under ASHRAE Standard 34. HFC143a and HFC32 have not received a non flammable rating by ASHRAE. This invention relates to compositions of refrigerants which not only cover blends of non flammable HFCs with hydrocarbons but also blends of flammable HFCs, non flammable HFCs and hydrocarbons in selected proportions selected so that all such compositions are non flammable during fractionation while providing similar refrigerating effects and thermodynamic performances as the ODS and HFC blends they replace.

While this invention relates to refrigerant compositions which can be used with traditional lubricants such as mineral and alkylbenzene oils, they are also suitable for use with synthetic oxygen containing lubricants.

In formulating HFC/hydrocarbon blends to replace HCFC 22 in specific applications, it is sometimes necessary to use one or more lower boiling HFCs, with one or more higher boiling HFCs. In this context preferred lower boiling HFCs are HFC 143a and HFC 125, and the higher boiling HFC is HFC 134a.

To avoid flammability in the blend, or in a fraction generated by a leak, for example as defined by ASHRAE Standard 34, the total amount of hydrocarbon should be minimised. At the same time the quantity of the hydrocarbon mixture dissolved in the oil needs to be maximised for good oil return, especially at those locations in the circuit where the oil is at its most viscous, for example the evaporator. One of the HFC components of this invention, namely HFC143a, has an ASHRAE safety classification of A2 which makes the amount of HFC143a used and the selection of the hydrocarbon critical to obtaining a non flammable rating of A1 for the blend. A single higher boiling hydrocarbon, such as pentane or iso-pentane, will concentrate in the liquid phase. This is demonstrated by leakage tests conducted on a blend of HFC134a, HFC125 and pentane as shown in Example 1.

The National Institute for Standards & Technology (NIST) programme Refleak – which is widely used to determine the fractionation of refrigerant blends under all conditions as required by ASHRAE Standard 34 - was run for blends comprising HFC134a, HFC143a & R125 with butane and isobutane which produced the results shown in Example 2. Build-up of butane in the liquid phase towards the end of the leakage was significant at over 60% compared to isobutane at about 15%.

Refleak was run also for blends comprising HFC134a, HFC143a & R125 with isobutane only as shown in Example 3. Build-up of isobutane is shown to be considerably less than butane in the liquid phase at worst case fractionation. In patent number EP12380 39B1 Roberts teaches away from the inclusion of 2-methyl propane (isobutane) in blends containing HFCs due to flammability concerns at worst case fractionation. Surprisingly it has been found that the use of isobutane in blends containing HFC134a, HFC143a and HFC125 results in non flammability at worst case fractionation under ASHRAE Standard 34.

This invention enables a flammable HFC such as HFC143a to be used in a non flammable refrigerant blend thereby substantively improving its performance, in particular its capacity

According to the present invention a refrigerant composition consists essentially of:

a hydrofluorocarbon component consisting of a mixture of:

R134a, R125 and R143a

and an additive selected from a saturated or unsaturated hydrocarbon or mixture thereof boiling in the range -50°C and $+40^{\circ}\text{C}$

In preferred embodiments the composition consists of a mixture of the hydrofluorocarbon component and the hydrocarbon component so that no substantial amount of any other components or other gases are present.

In a further preferred embodiment the hydrocarbon is present in an amount of 0.1% to 5% and wherein the composition is non-flammable when completely in the vapour phase.

In a further preferred embodiment the hydrocarbon is present in an amount of 0.1 to 5% and wherein when the composition is in a container where both vapour and liquid present, neither vapour nor liquid phase is flammable.

The hydrocarbon additions may be selected from from the group consisting of 2-methylpropane, propane, 2,2-dimethylpropane, n-butane, 2-methylbutane, cyclopentane, hexane, ethane, 2-methylpentane, 3-methylpentane, 2,2-dimethylbutane, methylcyclopentane, propene, n-butene, isobutene and mixtures thereof.

In a further embodiment, a refrigerant composition which may find application to replace R22 comprises;

(i) from about 10 to 35 weight per cent of HFC134a, preferably 10 to 25 weight per cent of HFC134a; and

(ii) from about 30 to 79.9 weight per cent of HFC125 preferably 46 to 74.7 weight per cent of HFC 125; and

(iii) from about 10 to 30 weight per cent of HFC143a, preferably 15 to 25 weight per cent of HFC143a; and

(iv) from about 0.1 to 5 weight per cent of butane or isobutane or propane, preferably 0.3 to 4 weight per cent of butane or isobutane or propane.

In a further embodiment, a refrigerant composition which may find application to replace R22 comprises:

(i) from about 10 to 35 weight per cent of HFC134a, preferably 10 to 25 weight per cent of HFC134a, most preferably 15 to 20 weight per cent of HFC134a; and

(ii) from about 25 to 79.8 weight per cent of HFC125 preferably 42 to 74.4 weight per cent of HFC 125, most preferably 53 to 67.4 weight per cent of HFC 125; and

(iii) from about 10 to 30 weight per cent of HFC143a, preferably 15 to 25 weight per cent of HFC143a, and most preferably 17 to 22 weight per cent of HFC143a; and

(iv) mixtures of butane from about 0.1 to 5 weight per cent and isobutane from about 0.1 to 5 weight per cent or mixtures of butane (0.1 to 5%) and isopentane (0.1 to 5%) or mixtures of butane (0.1 to 5%) and propane (0.1 to 5%) or mixtures of isobutane (0.1 to 5%) and propane (0.1 to 5%), preferably 0.3 to 4 weight per cent of mixtures of butane (0.3 to 4%) and isobutane (0.3 to 4%) or mixtures of butane (0.3 to 4%) and isopentane (0.3 to 4%) or mixtures of butane (0.3 to 4%) and propane (0.3 to 4%) or mixtures of isobutane (0.3 to 4%) and propane (0.3 to 4%), most preferably a mixture of 0.3 to 3 weight per cent of isobutane and 0.3 to 2 weight per cent of propane or a mixture of 0.3 to 3 weight per cent of butane and 0.3 to 2 weight per cent of propane.

In a further embodiment, a refrigerant composition which may find application to replace R22 comprises:

(i) from about 10 to 35 weight per cent of HFC134a, preferably 10 to 25 weight per cent of HFC134a; and

(ii) from about 20 to 79.7 weight per cent of HFC125 preferably 38 to 74.1 weight per cent of HFC 125; and

(iii) from about 10 to 30 weight per cent of HFC143a, preferably 15 to 25 weight per cent of HFC143a; and

(iv) mixtures of butane from about 0.1 to 5 weight per cent and isobutane from about 0.1 to 5 weight per cent and propane from about 0.1 to 5 weight per cent,

preferably 0.3 to 4 weight per cent of mixtures of butane (0.3 to 4%) and isobutane (0.3 to 4%) and propane (0.3 to 4%)

A composition which may find application as a replacement for R22 consists essentially of:

R134a	16%
R125	60%
R143a	21%
Isobutane	2%
Propane	1%

Yet another composition which may find application as a replacement for R22 consists essentially of:

R134a	16%
R125	60%
R143a	21%
Butane	2%
Propane	1%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.9 to 30%
R143a	10 to 30%
Butane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.7 to 46%
R143a	15 to 25%
Butane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.9 to 30%
R143a	10 to 30%
Isobutane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.7 to 46%
R143a	15 to 25%
Isobutane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.9 to 30%
R143a	10 to 30%
Propane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.7 to 46%
R143a	15 to 25%
Propane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
-------	-----------

R125	79.8 to 25%
R143a	10 to 30%
Butane	0.1 to 5%
Isobutane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.4 to 42%
R143a	15 to 25%
Butane	0.3 to 4%
Isobutane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.8 to 25%
R143a	10 to 30%
Butane	0.1 to 5%
Isopentane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.4 to 42%
R143a	15 to 25%
Butane	0.3 to 4%
Isopentane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.8 to 25%
R143a	10 to 30%
Butane	0.1 to 5%
Propane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.4 to 42%
R143a	15 to 25%
Butane	0.3 to 4%
Propane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.8 to 25%
R143a	10 to 30%
Isobutane	0.1 to 5%
Propane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.4 to 42%
R143a	15 to 25%
Isobutane	0.3 to 4%
Propane	0.3 to 4%

A preferred composition consists essentially of:

R134a	10 to 35%
R125	79.7 to 20%
R143a	10 to 30%
Butane	0.1 to 5%
Isobutane	0.1 to 5%
Propane	0.1 to 5%

A preferred composition consists essentially of:

R134a	10 to 25%
R125	74.1 to 38%
R143a	15 to 25%
Butane	0.3 to 4%
Isobutane	0.3 to 4%
Propane	0.3 to 4%

A preferred composition consists essentially of:

R134a	15 to 20%
R125	67.4 to 53%
R143a	17 to 22%
Isobutane	0.3 to 3%
Propane	0.3 to 2%

A preferred composition consists essentially of:

R134a	15 to 20%
R125	67.4 to 53%
R143a	17 to 22%
Butane	0.3 to 3%
Propane	0.3 to 2%

A preferred composition consists essentially of:

R134a	16%
-------	-----

R125	60%
R143a	21%
Isobutane	2%
Propane	1%

A preferred composition consists essentially of:

R134a	16%
R125	60%
R143a	21%
Butane	2%
Propane	1%

In an embodiment the isobutane is present in an amount of 0.6% to 4% and wherein when the composition is in a container where both vapour and liquid present, neither vapour nor liquid phase is flammable.

In a second, preferred embodiment the hydrocarbon is present in an amount of 0.6 to 3.5%.

In a particularly preferred embodiment, a refrigerant composition which may find application to replace R22 comprises:

R134a	15.7%
R125	63%
R143a	18%
Butane	3.3%

Yet another preferred composition which may find application as a replacement for R22 consists essentially of:

R134a	15.8%
R125	63%
R143a	18%
Isobutane	3.2%

A further preferred refrigerant composition comprises:

R134a	15.9%
R125	63%
R143a	18%
Isobutane	3.1%

A preferred refrigerant composition comprises

R134a	16%
R125	63%
R143a	18%
Isobutane	3%

A further preferred refrigerant composition comprises

R134a	16.1%
R125	63%
R143a	18%
Isobutane	2.9%

Yet another further preferred refrigerant composition comprises

R134a	16.2%
R125	63%
R143a	18%
Isobutane	2.8%

Another further preferred refrigerant composition comprises

R134a	16.3%
R125	63%
R143a	18%
Isobutane	2.7%

A further preferred refrigerant composition comprises

R134a	16.4%
-------	-------

R125	63%
R143a	18%
Isobutane	2.6%

Yet another preferred refrigerant composition comprises

R134a	16.5%
R125	63%
R143a	18%
Isobutane	2.5%

Another preferred refrigerant composition comprises

R134a	16%
R125	64%
R143a	18%
Isobutane	2%

Another preferred refrigerant composition comprises

R134a	15.7%
R125	65%
R143a	16%
Butane	3.3%

A further preferred refrigerant composition comprises

R134a	15.8%
R125	65%
R143a	16%
Isobutane	3.2%

Yet another further preferred refrigerant composition comprises

R134a	15.9%
-------	-------

R125	65%
R143a	16%
Isobutane	3.1%

Yet still another further preferred refrigerant composition comprises

R134a	16%
R125	65%
R143a	16%
Isobutane	3%

A further preferred refrigerant composition comprises

R134a	16.1%
R125	65%
R143a	16%
Isobutane	2.9%

Another preferred refrigerant composition comprises

R134a	16.2%
R125	65%
R143a	16%
Isobutane	2.8%

Yet another preferred refrigerant composition comprises

R134a	16.3%
R125	65%
R143a	16%
Isobutane	2.7%

Yet still another preferred refrigerant composition comprises

R134a	16.4%
-------	-------

R125	65%
R143a	16%
Isobutane	2.6%

A further preferred refrigerant composition comprises

R134a	16.5%
R125	65%
R143a	16%
Isobutane	2.5%

Another preferred refrigerant composition comprises

R134a	15.7%
R125	67%
R143a	14%
Butane	3.3%

Yet another preferred refrigerant composition comprises

R134a	15.8%
R125	67%
R143a	14%
Isobutane	3.2%

Yet still another preferred refrigerant composition comprises

R134a	15.9%
R125	67%
R143a	14%
Isobutane	3.1%

A further preferred refrigerant composition comprises

R134a	16%
-------	-----

R125	67%
------	-----

R143a	14%
-------	-----

Isobutane	3%
-----------	----

Another preferred refrigerant composition comprises

R134a	16.1%
-------	-------

R125	67%
------	-----

R143a	14%
-------	-----

Isobutane	2.9%
-----------	------

Yet another preferred refrigerant composition comprises

R134a	16.2%
-------	-------

R125	67%
------	-----

R143a	14%
-------	-----

Isobutane	2.8%
-----------	------

Yet still another preferred refrigerant composition comprises

R134a	16.3%
-------	-------

R125	67%
------	-----

R143a	14%
-------	-----

Isobutane	2.7%
-----------	------

A further preferred refrigerant composition comprises

R134a	16.4%
-------	-------

R125	67%
------	-----

R143a	14%
-------	-----

Isobutane	2.6%
-----------	------

Another preferred refrigerant composition comprises

R134a	16.5%
-------	-------

R125	67%
R143a	14%
Isobutane	2.5%

Percentages and other proportions referred to in this specification are by weight unless indicated otherwise and are selected to total 100% from within the ranges disclosed.

The invention is further described by means of examples but not in a limitative sense. The following abbreviations are employed.

- AF As Formulated blend composition
- WCF Worst Case Formulation: the WCF is defined as the composition containing the highest (percentage) flammable components within the manufacturing tolerance range and the lowest amount of non flammable component.
- WCFF Worst Case Fractionated Formulation: when a blend undergoes a leak from a package or system, one or more flammable components may concentrate in the liquid or vapour phases due to fractionation. In order to evaluate properly the possible flammability risk of a blend, the worst case formulation (WCF) composition is submitted to a standard leak test as specified by the ASHRAE 34 protocol. This leak test can either be experimental or simulated using a computer program such as NIST's Refleak.

Example 1

A blend containing 88% R134a, 10% R125 and 2% pentane was allowed to undergo a vapour phase leak from a cylinder under isothermal conditions. The weight of the cylinder was monitored and the liquid and vapour phases were analysed by gas-liquid chromatography. The first analysis was made after 2% refrigerant loss. Each subsequent analysis was made after 10% of the refrigerant remaining in the cylinder had leaked as shown in Table 1. The experiment was continued until no liquid remained in the cylinder.

Table 1

LIQUID PHASE				VAPOUR PHASE		
R134a	R125	Pentane	Loss	R134a	R125	Pentane
%Wt	%Wt	%Wt	%Wt	%Wt	%Wt	%Wt
88.85	8.55	2.59	2	83.20	15.06	1.74
87.31	10.53	2.16	10	86.45	11.33	2.22
90.24	6.95	2.81	10	84.79	13.38	1.84
90.65	6.45	2.90	10	85.83	12.23	1.95
90.95	6.08	2.96	10	86.88	11.07	2.04
91.58	5.33	3.09	10	87.44	10.50	2.05
91.99	4.71	3.29	10	88.19	9.67	2.14
91.94	4.73	3.32	10	88.72	9.12	2.16
92.34	4.31	3.34	10	89.73	8.14	2.21
92.69	3.78	2.53	10	90.17	7.49	2.34
93.05	3.13	3.82	10	90.59	6.95	2.46
92.97	3.41	3.62	10	91.28	6.43	2.29
93.14	2.94	3.92	10	91.56	5.98	2.46
93.22	2.78	4.00	10	92.07	5.48	2.45
93.39	2.57	4.03	10	92.48	5.00	2.52
93.48	2.27	4.25	10	92.76	4.63	2.61
93.52	2.15	4.33	10	93.13	4.13	2.74
92.30	1.92	4.78	10	93.33	3.98	2.69
93.41	1.75	4.84	10	93.39	3.56	3.04
93.49	1.59	4.93	10	93.69	3.28	3.03
93.35	1.44	5.21	10	93.83	3.02	3.15
93.25	1.26	5.49	10	94.12	2.81	3.07
93.33	1.23	5.43	10	94.19	2.54	3.26
93.08	1.09	5.82	10	95.25	2.40	3.35
92.82	1.03	6.15	10	94.69	1.44	3.86
92.57	0.88	6.55	10	94.43	2.00	3.57
92.27	0.86	6.87	10	94.24	1.85	3.91
92.01	0.77	7.22	10	94.44	1.68	3.87
91.39	0.76	7.84	10	10	1.59	94.49
90.62	0.58	8.79	10	10	0.87	94.33
89.80	0.54	9.66	10	10	1.31	93.91
87.98	0.53	11.49	10	10	1.16	93.65
85.42	0.45	14.13	10	10	1.09	93.64
84.26	0.39	15.34	10	10	1.02	93.31
			Liquid empty			

Example 2

A blend with an AF composition of 63% R125, 18% 143a, 15.7% R134a and 3.3% isobutane has a WCF composition of 62% R125, 18.9% R143a, 15.7% R134a and 3.4% isobutane. NIST's Refleak programme was used to calculate the fractionation of this WCF blend for a vapour phase isothermal leaks at 54 °C and -34.4 °C. The WCFF compositions under these conditions are shown in Table 2.

Table 2

	AF	WCF	WCFF		WCFF	
			54 °C		-34.4 °C	
			Liquid	Vapour	Liquid	Vapour
R125	63	62	52.8	57.6	62	70
R143a	18	18.9	18.7	19	18.9	18.8
R134a	15.7	15.7	24.7	19.8	15.7	7.4
Isobutane	3.3	3.4	3.83	3.65	3.49	3.73
%wt leaked			82		83	

Example 3

A blend with an AF composition of 63% R125, 18% 143a, 16% R134a 0.6% butane and 2.4% isoobutane has a WCF composition of 62% R125, 18.8% R143a, 16% R134a 0.7% butane and 2.5% isobutane. NIST's Refleak programme was used to calculate the fractionation of this WCF blend for a vapour phase isothermal leaks at 54 °C and -34.4 °C. The WCFF compositions under these conditions are shown in Table 3.

Table 3

	AF	WCF	WCFF		WCFF	
			54 °C		-34.4 °C	
			Liquid	Vapour	Liquid	Vapour
R125	63	62	52.3	57.3	40.8	55.5
R143a	18	18.8	18.7	18.9	16.4	19.5
R134a	16	16	25.1	20.2	40.2	21.7
Butane	0.6	0.7	1.14	0.9	1.1	1.01
Isobutane	2.4	2.5	2.81	2.67	1.49	2.29
Total hydrocarbon	3	3.2	3.95	3.57	2.59	3.3
%wt leaked			82		83.8	

Example 4

Blends of R125, R143a, R134a and R600a were evaluated in a typical hermetic or semi-hermetic air conditioner using NIST's CYCLE D program.

COOLING DUTY DELIVERED	10 kW
EVAPORATOR	
Midpoint evaporating temperature	7 °C
Superheating	5.0 °C
Suction line pressure drop (in saturated temperature)	1.5 °C
CONDENSER	
Midpoint fluid condensing temperature	45.0 °C
Subcooling	5.0 °C
Discharge line pressure drop (in saturated temperature)	1.5 °C
LIQUID LINE/SUCTION LINE HEAT EXCHANGER	
Efficiency	0.3
COMPRESSOR	
Compressor isentropic efficiency	0.7
Compressor volumetric efficiency	0.82
Motor efficiency	0.85
PARASITIC POWER	
Evaporator fan	0.3 kW
Condenser fan	0.4 kW
Controls	0.1 kW

The results of analysing the performances in an air conditioning unit using these operating parameters are shown in Table 4, plus R22 for comparison.

Table 4

Refrigerant	1	2	3	4	5	6	7	8	9	10	11	12	13	14	R22
Weight % 125	60.2	61.8	63	63	63.2	63.5	64.2	64	64.3	65.7	66.5	66.8	67.1	69.2	
Weight % 143a	19.8	18.6	18	18	18	18	17	18	17.4	16.8	17.1	16.3	18.1	16.2	
Weight % 134a	16	16	15.7	16	16	16	16	16	15.1	14.9	15.3	14.1	14	14	
Weight % 600a	4	3.6	3.3	3	2.8	2.5	2.8	2	3.2	2.6	1.1	2.8	0.8	0.6	
Discharge pressure (bar)	19.53	19.63	19.74	19.77	19.81	19.86	19.83	19.96	19.85	20.00	20.24	20.07	20.45	20.53	17.91
Discharge temperature (°C)	76.3	76.2	76.2	76.2	76.2	76.3	76.1	76.3	76.0	76.0	76.2	75.8	76.2	76.0	104.7
COP (system)	2.42	2.42	2.41	2.41	2.41	2.41	2.41	2.41	2.41	2.41	2.40	2.41	2.40	2.40	2.49
Capacity (kW/m ³)	3035	3046	3058	3062	3066	3074	3068	3085	3070	3088	3118	3095	3142	3149	3067
Glide in evaporator (°C)	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.6	1.6	1.6	1.6	1.6	1.5	1.5	0
Glide in condenser (°C)	1.6	1.6	1.6	1.5	1.5	1.5	1.5	1.4	1.5	1.4	1.3	1.4	1.2	1.2	0

Example 5

Blends of R125, R143a, R134a and R600a were evaluated in a typical open compressor refrigeration unit using NIST's CYCLE D program.

COOLING DUTY DELIVERED	10 kW
EVAPORATOR	
Midpoint evaporating temperature	-30 °C
Superheating	5.0 °C
Suction line pressure drop (in saturated temperature)	1.5 °C
CONDENSER	
Midpoint fluid condensing temperature	35.0 °C
Subcooling	5.0 °C
Discharge line pressure drop (in saturated temperature)	1.5 °C
LIQUID LINE/SUCTION LINE HEAT EXCHANGER	
Efficiency	0.3
COMPRESSOR	
Compressor isentropic efficiency	0.7
Compressor volumetric efficiency	0.82
Motor efficiency	0.85
PARASITIC POWER	
Evaporator fan	0.3 kW
Condenser fan	0.4 kW
Controls	0.1 kW

The results of analysing the performances in a refrigerator unit using these operating parameters are shown in Table 5, plus R22 and R502 for comparison.

Table 5

Refrigerant	1	2	3	4	5	6	7	8	9	10	11	12	13	14	R22	R502
Weight % 125	60.2	61.8	63	63	63.2	63.5	64	64.2	64.3	65.7	66.5	66.8	67.1	69.2		
Weight % 143a	19.8	18.6	18	18	18	18	18	17	17.4	16.8	17.1	16.3	18.1	16.2		
Weight % 134a	16	16	15.7	16	16	16	16	16	15.1	14.9	15.3	14.1	14	14		
Weight % 600a	4	3.6	3.3	3	2.8	2.5	2	2.8	3.2	2.6	1.1	2.8	0.8	0.6		
Discharge pressure (bar)	15.34	15.42	15.51	15.52	15.55	15.60	15.67	15.57	15.59	15.71	15.89	15.77	16.06	16.12	14.07	15.46
Discharge temperature (°C)	82.9	82.8	82.7	82.8	82.9	82.9	83.0	82.7	82.5	82.5	82.9	82.2	82.8	82.6	132.4	93.5
COP (system)	1.52	1.51	1.51	1.51	1.51	1.51	1.51	1.51	1.51	1.51	1.51	1.51	1.50	1.50	1.60	1.55
Capacity (kW/m ³)	819	822	825	825	827	828	831	826	829	834	840	837	849	850	872	907
Glide in evaporator (°C)	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.8	1.8	1.9	1.8	1.8	1.8	0.0	0.1
Glide in condenser (°C)	1.8	1.8	1.7	1.7	1.7	1.7	1.6	1.7	1.7	1.6	1.5	1.6	1.4	1.4	0.0	0.0

CLAIMS

1. A refrigerant composition consisting essentially of a hydrofluorocarbon
5 component consisting of:
- R134a, R125 and R143a;
- and an additive selected from a saturated or unsaturated hydrocarbon or mixture thereof boiling in the range -50°C and $+40^{\circ}\text{C}$.
- 10 2. A refrigerant composition as claimed in claim 1 wherein the hydrocarbon additive is selected from the group consisting of 2-methylpropane, propane, 2,2-dimethylpropane, n-butane, 2-methylbutane, cyclopentane, hexane, ethane, 2-methylpentane, 3-methylpentane, 2,2-dimethylbutane, methylcyclopentane, propene, n-butene, isobutene and mixtures thereof.
- 15 3. A composition as claimed in claims 1 or 2 claim wherein the hydrocarbon is present in an amount of 0.1 to 5%.
4. A refrigerant composition as claimed in any of claims 1-3 consisting essentially
20 of:
- | | |
|--------|-------------|
| R134a | 10 to 35% |
| R125 | 79.9 to 30% |
| R143a | 10 to 30% |
| Butane | 0.1 to 5% |

5. A refrigerant composition as claimed in any of claims 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.7 to 46%
5	R143a	15 to 25%
	Butane	0.3 to 4%

6. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

10	R134a	10 to 35%
	R125	79.9 to 30%
	R143a	10 to 30%
	Isobutane	0.1 to 5%

- 15 7. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.7 to 46%
	R143a	15 to 25%
20	Isobutane	0.3 to 4%

8. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 35%
25	R125	79.9 to 30%
	R143a	10 to 30%
	Propane	0.1 to 5%

9. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.7 to 46%
5	R143a	15 to 25%
	Propane	0.3 to 4

10. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

10	R134a	10 to 35%
	R125	79.8 to 25%
	R143a	10 to 30%
	Butane	0.1 to 5%
	Isobutane	0.1 to 5%

15

11. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.4 to 42%
20	R143a	15 to 25%
	Butane	0.3 to 4%
	Isobutane	0.3 to 4%

12. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

25

	R134a	10 to 35%
	R125	79.8 to 25%

R143a	10 to 30%
Butane	0.1 to 5%
Isopentane	0.1 to 5%

5 13. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.4 to 42%
	R143a	15 to 25%
10	Butane	0.3 to 4%
	Isopentane	0.3 to 4%

14. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

15	R134a	10 to 35%
	R125	79.8 to 25%
	R143a	10 to 30%
	Butane	0.1 to 5%
	Propane	0.1 to 5%

20

15. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

25

	R134a	10 to 25%
	R125	74.4 to 42%
	R143a	15 to 25%

Butane 0.3 to 4%

Propane 0.3 to 4%

5 16. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

R134a 10 to 35%

R125 79.8 to 25%

R143a 10 to 30%

Isobutane 0.1 to 5%

10 Propane 0.1 to 5%

17. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

R134a 10 to 25%

15 R125 74.4 to 42%

R143a 15 to 25%

Isobutane 0.3 to 4%

Propane 0.3 to 4%

20 18. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

R134a 10 to 35%

R125 79.7 to 20%

R143a 10 to 30%

25 Butane 0.1 to 5%

Isobutane 0.1 to 5%

Propane 0.1 to 5%

19. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	10 to 25%
	R125	74.1 to 38%
5	R143a	15 to 25%
	Butane	0.3 to 4%
	Isobutane	0.3 to 4%
	Propane	0.3 to 4%

10 20. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	15 to 20%
	R125	67.4 to 53%
	R143a	17 to 22%
15	Isobutane	0.3 to 3%
	Propane	0.3 to 2%

20 21. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	15 to 20%
	R125	67.4 to 53%
	R143a	17 to 22%
	Butane	0.3 to 3%
25	Propane	0.3 to 2%

22. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	16%
	R125	60%
	R143a	21%
	Isobutane	2%
5	Propane	1%

23. A refrigerant composition as claimed in any of claims claim 1-3 consisting essentially of:

	R134a	16%
10	R125	60%
	R143a	21%
	Butane	2%
	Propane	1%

24. A refrigerant composition consisting essentially of:

15	R134a	14 to 17 %
	R125	71.4 to 59%
	R143a	14 to 20%
	Isobutane	0.6 to 4%

20 25. Compositions as claimed in Claim 24 which meet the criteria for safety classifications A1 and A2 of ASHRAE Standard 34.

26. Compositions as claimed in Claim 24 which meet the criteria for safety classification A1 of ASHRAE Standard 34.

25

27. Compositions as claimed in Claim 24 which when allowed to leak under conditions specified by ASHRAE Standard 34 do not generate liquid or vapour mixtures with hydrocarbon contents greater than 5 weight %.

28. Compositions as claimed in Claim 24 which when allowed leak under conditions specified by ASHRAE Standard 34 do not generate liquid or vapour mixtures with hydrocarbon contents greater than 4 weight %.

5

29. Compositions as claimed in any of Claims 24 to 28 in which the weight percent of hydrocarbon does not vary more than 0.5% when the compositions under isothermal vapour leaks at 23 deg C.

10 30. Compositions as claimed in any of Claims 24 to 29 with a hydrocarbon content less than 3.5 by weight %.

31. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

15

R134a	15.7%
R125	63%
R143a	18%
Butane	3.3%

20 32. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

25

R134a	15.8%
R125	63%
R143a	18%
Isobutane	3.2%

33. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	15.9%
-------	-------

R125	63%
R143a	18%
Isobutane	3.1%

5 34. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16%
R125	63%
R143a	18%
10 Isobutane	3%

35. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16.1%
15 R125	63%
R143a	18%
Isobutane	2.9%

20 36. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16.2%
R125	63%
R143a	18%
Isobutane	2.8%

25

37. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16.3%
-------	-------

R125	63%
R143a	18%
Isobutane	2.7%

- 5 38. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16.4%
R125	63%
R143a	18%
10 Isobutane	2.6%

39. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16.5%
R125	63%
15 R143a	18%
Isobutane	2.5%

40. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	16%
20 R125	64%
R143a	18%
Isobutane	2%

41. A refrigerant composition as claimed in any of Claims 24 to 30 consisting essentially of:

R134a	15.7%
R125	65%

R143a	16%
Butane	3.3%

42. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
5 essentially of:

R134a	15.8%
R125	65%
R143a	16%
Isobutane	3.2%

10

43. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	15.9%
R125	65%
R143a	16%
Isobutane	3.1%

15

44. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	16%
R125	65%
R143a	16%
Isobutane	3%

20

45. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
25 essentially of:

R134a	16.1%
R125	65%

R143a	16%
Isobutane	2.9%

46. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
5 essentially of:

R134a	16.2%
R125	65%
R143a	16%
Isobutane	2.8%

10

47. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	16.3%
R125	65%
R143a	16%
Isobutane	2.7%

15

48. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	16.4%
R125	65%
R143a	16%
Isobutane	2.6%

20

49. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
25 essentially of:

R134a	16.5%
R125	65%

R143a	16%
Isobutane	2.5%

50. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
5 essentially of:

R134a	15.7%
R125	67%
R143a	14%
Butane	3.3%

10

51. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	15.8%
R125	67%
R143a	14%
Isobutane	3.2%

15

52. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	15.9%
R125	67%
R143a	14%
Isobutane	3.1%

20

53. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
25 essentially of:

R134a	16%
R125	67%

R143a	14%
Isobutane	3%

54. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
5 essentially of:

R134a	16.1%
R125	67%
R143a	14%
Isobutane	2.9%

10

55. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	16.2%
R125	67%
R143a	14%
Isobutane	2.8%

15

56. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
essentially of:

R134a	16.3%
R125	67%
R143a	14%
Isobutane	2.7%

20

57. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
25 essentially of:

R134a	16.4%
R125	67%

R143a	14%
Isobutane	2.6%

58. A refrigerant composition as claimed in any of Claims 24 to 30 consisting
5 essentially of:

R134a	16.5%
R125	67%
R143a	14%
Isobutane	2.5%

10

59. A refrigerant as claimed in any preceding claim used in an air conditioning unit with a mineral or alkylbenzene oil or synthetic hydrocarbon lubricant.

60. A refrigerant as claimed in any of Claims 1 to 58 used in a refrigeration unit
15 with a mineral oil or alkylbenzene or synthetic hydrocarbon lubricant.

61. A refrigerant as claimed in any of Claims 1 to 58 used in an air conditioning unit with a synthetic oxygen- containing lubricant.

20 62. A refrigerant as claimed in any of Claims 1 to 58 used in a refrigeration unit with a synthetic oxygen containing lubricant.

63. A refrigerant as claimed in claims 61 o 62 in which the lubricant is a polyol ester.

25

64. A refrigerant as claimed in claims 61 or 62 in which the lubricant is a polyether.

65. A refrigerant as claimed in any of Claims 1 to 58 used in an air conditioning unit in which the lubricant is a mixture of hydrocarbon lubricants.

5 66. A refrigerant as claimed in any of Claims 1 to 58 used in refrigeration unit in which the lubricant is a mixture of hydrocarbon lubricants.

67. A refrigerant as claimed in any of Claims 1 to 58 used in an air conditioning unit in which the lubricant is a mixture of oxygen containing lubricants.

10

68. A refrigerant as claimed in claims any of Claims 1 to 58 used in a refrigeration unit in which the lubricant is a mixture of oxygen containing lubricants

69. A refrigerant as claimed in any of Claims 1 to 58 used in an air conditioning
15 unit in which the lubricant is a mixture of hydrocarbon and oxygen containing lubricants.

70. A refrigerant as claimed in any of Claims 1 to 58 used in a refrigerating unit in which the lubricant is a mixture of hydrocarbon and oxygen containing lubricants.

20

25

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2007/000747A. CLASSIFICATION OF SUBJECT MATTER
INV. C09K5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2005/083028 A (RPL HOLDINGS LTD [GB]; POOLE JOHN EDWARD [GB]; POWELL RICHARD [GB]) 9 September 2005 (2005-09-09) * the whole document, particularly claims 38 and 39 *	1-70
X	WO 96/03473 A (ICI PLC [GB]; POWELL RICHARD LLEWELLYN [GB]; CORR STUART [GB]; MURPHY) 8 February 1996 (1996-02-08) * page 4, lines 4-8, Examples 7-9,19-21, claims 8, 9,11,17,18 *	1-70
X	EP 1 193 305 A (HONEYWELL INT INC [US]) 3 April 2002 (2002-04-03) * claims 1 and 5 *	1-70
	----- -/--	

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

18 June 2007

Date of mailing of the international search report

26/06/2007

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nemes, Csaba A.

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2007/000747

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99/36485 A (DU PONT [US]) 22 July 1999 (1999-07-22) * claims 1, 12 and 13 * -----	1-70
X	JP 09 208940 A (SANYO ELECTRIC CO) 12 August 1997 (1997-08-12) * paragraphs [0006], [0007], [0019] * -----	1-70
X	WO 92/01762 A (DU PONT [US]) 6 February 1992 (1992-02-06) * page 24, lines 13-16, claims 2 and 3 * -----	1-70

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/GB2007/000747

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2005083028	A	09-09-2005	CA 2575691 A1	09-09-2005
			EP 1765953 A1	28-03-2007
			KR 20070007320 A	15-01-2007
WO 9603473	A	08-02-1996	AT 205872 T	15-10-2001
			AU 698733 B2	05-11-1998
			AU 2988795 A	22-02-1996
			BR 9508347 A	30-09-1997
			DE 69522811 D1	25-10-2001
			DE 69522811 T2	28-03-2002
			DK 772659 T3	26-11-2001
			EP 0772659 A1	14-05-1997
			ES 2163520 T3	01-02-2002
			JP 10503230 T	24-03-1998
			PT 772659 T	28-02-2002
			EP 1193305	A
WO 9936485	A	22-07-1999	AT 215596 T	15-04-2002
			AU 761993 B2	12-06-2003
			AU 2234299 A	02-08-1999
			BR 9908205 A	28-11-2000
			CN 1288483 A	21-03-2001
			DE 69901160 D1	08-05-2002
			DE 69901160 T2	31-10-2002
			EP 1047747 A1	02-11-2000
			ES 2172979 T3	01-10-2002
			JP 2002509179 T	26-03-2002
JP 9208940	A	12-08-1997	NONE	
WO 9201762	A	06-02-1992	AR 248158 A1	30-06-1995
			AT 115994 T	15-01-1995
			AT 135733 T	15-04-1996
			AT 153367 T	15-06-1997
			BR 9106694 A	08-06-1993
			CA 2086841 A1	27-01-1992
			CA 2148854 A1	27-01-1992
			DE 69106135 D1	02-02-1995
			DE 69106135 T2	24-05-1995
			DE 69118208 D1	25-04-1996
			DE 69118208 T2	05-09-1996
			DE 69126219 D1	26-06-1997
			DE 69126219 T2	11-12-1997
			DK 545942 T3	20-03-1995
			DK 568115 T3	29-04-1996
			DK 602022 T3	01-09-1997
			EP 0545942 A1	16-06-1993
			ES 2066453 T3	01-03-1995
			ES 2085688 T3	01-06-1996
			ES 2102759 T3	01-08-1997
			HK 109995 A	14-07-1995
			JP 2993390 B2	20-12-1999
			JP 8034974 A	06-02-1996
			JP 3086802 B2	11-09-2000
			JP 11323318 A	26-11-1999
			JP 2554455 B2	13-11-1996
			JP 7300579 A	14-11-1995

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/GB2007/000747

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9201762	A	JP 2561988 B2	11-12-1996
		JP 5509113 T	16-12-1993
