



(51) International Patent Classification:

A41D 13/018 (2006.01) A42B 3/00 (2006.01)

(21) International Application Number:

PCT/SE2018/050703

(22) International Filing Date:

28 June 2018 (28.06.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1750847-4 29 June 2017 (29.06.2017) SE

(71) Applicant: HÖVDING SVERIGE AB [SE/SE]; Bergsgatan 33, 214 22 MALMÖ (SE).

(72) Inventor: WENDEL RUP, Heino; Trollsjövägen 159, 237 33 Bjärred (SE).

(74) Agent: STRÖM & GULLIKSSON AB; P.O. Box 4188, SE-203 13 MALMÖ (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,

MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: PROTECTIVE SYSTEM COMPRISING AN AIRBAG SYSTEM WITH AN INFLATABLE HELMET COMMUNICATING WITH AN EXTERNAL DEVICE




Fig. 4

(57) Abstract: A protective system is provided comprising an airbag system (100) for protecting a body part of a user (3) in case of an accident, comprising a control unit (50) and a communication interface (90). The protective system further comprises an external device (200) comprising communication means. The communication interface (90) of the airbag system (100) is configured to communicate with said external device (200) using wireless communication.



PROTECTIVE SYSTEM COMPRISING AN AIRBAG SYSTEM WITH AN INFLATABLE HELMET
COMMUNICATING WITH AN EXTERNAL DEVICE

Technical field

The present disclosure relates to a system for protecting a user's head in case of
5 an abnormal movement, such as a fall or a collision. More specifically, the present
invention relates to a wearable airbag forming an inflatable helmet for protecting the
head of a bicyclist in case of an accident when biking.

Background

10 Airbags for the protection of a person's head are known in the art, for example
through WO2012044245. As opposed to vehicular airbags the airbag of
WO2012044245 is designed to inflate into a complex head protecting shape. The airbag
is designed as a double-bag construction, of which the inflated helmet-shape of the
inner plastic bag is formed by the finger like construction of the outer bag.

15 The airbag mentioned in WO2012044245 is designed to detect if the user is
exposed to an abnormal movement, such as a fall or a collision, for a specific activity,
for example riding a bicycle. For the airbag to protect the user during an accident, the
user has to wear the airbag when doing the specific activity. During the activity the
wearable airbag is activated, constantly monitoring the movements of the user. As
20 inflation is controlled by comparing the current movement with reference movements of
the particular type of activity, it is important to turn off the wearable airbag once the
type of activity is changed, e.g. from cycling to walking or running. Compared to
traditional helmets the wearable airbag is so gently arranged around the neck that a user
may easily forget that he or she is actually wearing it. Hence, deactivation of the
25 wearable airbag may be forgotten. There is thus a need for an airbag that eliminates or
at least mitigates problems arising from this situation.

Summary

An object of the present invention is to provide a new type of airbag system
30 which is improved over prior art and which eliminates or at least mitigates the

drawbacks discussed above. More specifically, an object of the invention is to provide an airbag system that is configured to communicate with an external device.

In a first aspect, a protective system is provided. The protective system comprises an airbag system in the form of an inflatable helmet for protecting a body
5 part of a user in case of an accident, comprising a control unit and a communication interface. The system further comprises an external device comprising communication means, wherein the communication interface of the airbag system is configured to communicate with said external device using wireless communication.

In one embodiment, the wireless communication is short-range wireless
10 communication. The short-range wireless communication may pertain to any of Bluetooth, WLAN, WiFi, NFC, RF-ID or IrDA. This allows for efficient and cheap communication.

The communication interface of the airbag system may be configured to attempt to communicate with said external device. If the communication between the
15 airbag system and the external device is successful, the control unit of the airbag system may be configured to control the airbag system into a first mode. In the first mode the control unit may be configured to alert the user and/or configured to automatically put the airbag system into an active state and/or to alert the user to manually change to an active state. The communication between the airbag system and the external device will
20 only be successful if they are close to each other, i.e. within the range of the wireless communication. In this way the system can determine if the airbag system is close to the external device.

In one embodiment the communication between the airbag system and the external device is successful when a communication is established between the airbag
25 system and the external device. In another embodiment the communication between the airbag system and the external device is successful when a communication is established between the airbag system and the external device and when the external device and the airbag system are within a predetermined distance from each other.

In one embodiment, if the communication between the airbag system and the
30 external device is not successful, the control unit of the airbag system is configured to

automatically put the airbag system in an idle state and/or to alert the user to manually change to an idle state.

In one embodiment, if the communication between the airbag system and the external device is not successful a controller of the external device is configured to
5 control the external device into a safety mode. If the communication between the airbag system and the external device is successful a controller of the external device may be configured to disable a safety mode of the external device. In the safety mode the controller of the external device may be configured to lock the external device so as to prevent the user from using it.

10 The external device may be an electric bicycle and wherein in the safety mode the controller of the electric bicycle may be configured to lock the electric bicycle so as to prevent the user from using it or to reduce the allowed speed of the electrical bicycle.

In one embodiment the external device is a bicycle.

In an alternative embodiment, the external device is a bicycle lock.

15

Brief description of the drawings

The present invention will hereinafter be further explained by means of non-limiting examples with reference to the appended schematic figures where;

Fig. 1 is a schematic view of a user wearing an inflatable helmet having an
20 airbag system according to some embodiments;

Fig. 2 is a schematic view of a user wearing an inflated helmet having an airbag system according to some embodiments;

Fig. 3 is a schematic view of an airbag system according to an embodiment;

Fig. 4 is a schematic view of an airbag system and an external device according
25 to an embodiment;

Figs. 5a-c are schematic views of methods according to different embodiments;
and

Fig. 6 is a schematic view of an airbag system and an external device according
to an embodiment.

30

Detailed Description

The protective system enclosed herein comprises an airbag system 100 for protecting a body part in case of an abnormal movement of a user and at least one external device 200. The external device 200 may for example be a bicycle or a bicycle lock.

5 The airbag system 100 is configured to be used to detect an accident, such as a fall or collision, for example when a user is riding a bicycle. The airbag system 100 may thus be configured for the specific use of riding a bicycle. For the airbag system to protect the user during an accident, the user has to wear the airbag system and have it turned on, or activated when performing the specific activity. It would however be
10 preferred to provide a system that determines if the airbag system is needed and in response to that alert the user and/or change the mode of the airbag system and/or change the mode of the external device.

 Furthermore, having the airbag system set in an activate state when the user is not doing the intended activity, e.g. not cycling, results in an undesirable energy loss
15 since the airbag system is in an active state using battery power to power a sensor(s) and to process the movement data gathered therefrom, although there is no risk for a fall or collision.

 It would thus be beneficial if the computational demanding determination, if a user is about to fall or collide when doing the indented activity, e.g., riding a bicycle, is
20 deactivated when it's not needed so as to reduce the overall energy consumption of the system.

 The system herein aims at determining if the airbag system is needed, in particular if a user is actually performing the intended activity or not. This information may for example be used to change the mode of the airbag system 100 and/or the mode
25 of the external device.

 The system herein aims at determining if the airbag system 100 is needed or not. This is done by differentiating between situations where the airbag system 100 is within a predetermined distance from the external device 200 and when they are far away from each other. This information may for example be used to change the mode of
30 the airbag system 100 and/or the mode of the external device 200.

Before turning to a detailed description of the disclosed embodiments, an exemplifying environment of the airbag system 100 device will be described with reference to Fig. 1 to 3, and an exemplifying environment of the external device 200 will be briefly described with reference to Fig 4.

5

Airbag system

Fig. 1 shows an airbag system 100 according to an embodiment in its non-inflated state. The airbag system 100 comprises an apparel 10 having the shape of a collar which is worn around the neck 2 of a user 3. An idea of the airbag system 100 is to provide a wearable airbag system for protecting a body part in case of an abnormal movement of a user, such as a fall or a collision. The airbag system described herein may for example be used instead of an ordinary rigid helmet, e.g. when bicycling. The airbag system is comfortable to wear, does not affect the user's hair style when worn and does not obstruct vision or hearing when worn in its non- inflated state.

15 The collar 10 is placed around the neck of the user and has for that purpose a sealable opening 12, normally at the front of the collar. Alternatively, the opening 12 may be arranged at the back of the collar 10 or at the shoulder portion of the collar 10. Furthermore, the opening 12 may be totally or partly divideable.

In one embodiment, the opening 12 is sealed using interlocking means (not shown) to connect the ends of the collar 10 e.g. adjacently the user's 3 throat or neck region. The interlocking means facilitates easy dressing and undressing of the collar 10 on the user 3. Furthermore, the position of the different parts of the interlocking means determines if the airbag system 100 is turned on (i.e. having power) or turned off, and if its turned on in an active state or in an idle state.

25 In another embodiment the sealing may be arranged as a zipper, buttons, a Velcro fastening, magnets, hooks, hanks, buckles, safety pins, straps or the like. The collar 10 may be made of any kind of flexible material, such as acetate silk, jeans, fleece, cotton, beaver nylon or any other suitable fabric.

When the airbag system is not worn by the user, the collar 10 can be put in a resting position to allow the user to easier carry the collar 10 for example by putting it in a bag. All electronics in the airbag system is turned off when the airbag system is put

30

in the resting position. In the resting position the collar is connected such that the diameter of the collar is greatly reduce. This prevents the user from being able to have to collar 10 arranged around the neck when the collar is in its resting position.

The collar 10 comprises a folded airbag 20 which is inflated to form a helmet
5 for protecting the head of the user 3 in case of an abnormal movement, e.g. during a cycling accident.

An inflated helmet is schematically shown in Fig. 2. Here, the collar 10 is opened to release the airbag 20 previously enclosed therein. The airbag 20 surrounds the neck 2 and the head 4 of the user 3 and provides an efficient protection for the user 3.

10 The airbag 20 is formed by a flexible material in order to be folded and stored within the collar 10 prior to inflation. The airbag 20 may e.g. comprise an inflatable inner bag surrounded by an outer bag. Inflation of the inner bag leads to expansion of the outer bag and the structure of the outer bag defines the shape of the airbag when the inner bag is inflated. Although not shown in Fig. 1 and 2, the airbag system may also be
15 an one-bag construction.

The inner bag may be made of a fluid impermeable material, such as thermoplastic polyurethane film. Since fluid cannot easily leave a fluid impermeable bag, a person wearing an airbag 20 according to the invention will be protected by said airbag 20 for some time after expansion of the airbag 20, effectively protecting the head
20 of the user for the entire time of the accident. The inner bag may be flexible and expandable such that it may expand the outer bag upon inflation to a high pressure. Hence, the inner bag may be inflated resulting in a relatively high internal pressure which may be maintained for some time.

An example of how the inner and outer bag may be configured is described in
25 WO2012044245 by the same applicant.

As shown in Fig. 3, the airbag system 100 further comprises at least one sensor 80 for detecting movement of the collar 10, i.e. movement of the user 3, and a control unit 50 configured to in response to the information gained by the sensor 80 determine if the movement corresponds to an accident situation. If an accident situation is
30 determined, the control unit 50 trigger inflation of the airbag 20 by means of an inflation device 60. The airbag system 100 further comprises a power source 70, for

example a rechargeable battery or a disposable battery, in order to provide electrical power to the parts of the system 100. The different parts will now be described more in detail.

The inflation device 60 may be any suitable type of airbag inflation device, such as a hybrid generator using a combination of compressed gas and solid fuel, a pyrotechnic airbag inflator which uses hot gases formed by powder, a heated gas inflator or a an inflation device using solid fuel. In an embodiment, the inflation device is a cold gas inflator.

The inflation device 60 is provided with a gas guide 65, for directing the gas into the airbag. The inflation device 60 is clamped, screwed, glued, sewed or the like onto the textile bag and the gas guide 65 is positioned inside the textile bag for directing the gas into the bag for inflating the airbag in a proper manner. The gas guide 65 may be T-shaped for being able to lead the gas into the airbag in a suitable stable way. Alternatively the gas guide 65 may be Y- shaped, I-shaped, arrow-shaped, multiple-part shaped cylindrical shaped or the like.

The inflation of the airbag 20 is controlled by the control unit 50. The control unit 50 controls the inflation of the airbag in case of an abnormal movement and prevents the airbag system from releasing at an undesired occasion. The control unit 50 may be implemented using instructions that enable hardware functionality, for example, by using executable computer program instructions in a general-purpose or special-purpose processor that may be stored on a computer readable storage medium (disk, memory etc.) 52 to be executed by such a processor. The control unit 50 may be configured to read instructions from the memory 52 and to execute these instructions to control the operation of the airbag system 100. The control unit 50 may be implemented using any suitable, publically available processor or Programmable Logic Circuit (PLC). The memory 52 may be implemented using any commonly known technology for computer-readable memories such as ROM, RAM, SRAM, DRAM, FLASH, DDR, SDRAM or some other memory technology.

The control unit 50 may be a dedicated control unit 50 or the control unit 50 may also be configured to control other functions.

The at least one sensor 80 collects data relating to the movement of the collar 10. The sensor 80 may be an accelerometer, a gyro, an air ultrasonic transducer, radar and/or a laser. In one embodiment at least one sensor is an accelerometer measuring acceleration in three dimensions and/or the sensor is a gyro detecting angular speed in three dimensions. Additionally, or alternatively, the at least one sensor 80 may be an ultrasonic transducer, or any device using electromagnetic waves, that measures the distance from the ground to the collar 10.

EP2313814, filed by the same applicant, discloses a method for detecting a bicycle accident without falsely classifying any data samples from normal cycling activities as accident. The system classifies the detected movement into either a “normal class” relating to movement patterns representing riding a bicycle or doing related activities or into an “action class” relating to movement patterns representing a bicycle accident.

The movement data gathered from the at least one sensor 80 is transmitted to the control unit 50. The control unit 50 processes the data and analyses it in order to evaluate if the processed data corresponds to an accident situation. If the data corresponds to pre-stored data indicating an accident situation, the control unit 50 transmits a triggering signal to the inflation device 60 to trigger the inflation of the airbag 20. The airbag 20 will consequently be inflated when the inflation device 60 receives the triggering signal.

The controller is coupled to the memory 52, which saves the measured and processed data. The saved data can be used to review and analyse the activity history of the airbag system. This is particularly useful if the airbag system has been deflated and technicians want to verify that the airbag system was working properly.

The airbag system 100 further comprises a communication interface 90, which is adapted to allow the airbag system 100 to communicate with other devices through the use of different communication technologies. Such communication technologies may be wired or wireless. Examples of such wired technologies are Universal Serial Bus (USB) and Ethernet to name a few. Examples of such wireless technologies are IEEE 802.11, IEEE 802.15, ZigBee, WirelessHART, WIFI, Bluetooth®, W-CDMA/HSPA, GSM, UTRAN and LTE to name a few. It should be noted that other

technologies exist and are taken to be an obvious equivalent for such wireless communication interfaces.

Preferably, the communication interface 90 uses short-range wireless communication such as any of Bluetooth[®], WLAN/WiFi, NFC (Near Field
5 Communication), RF-ID (Radio Frequency Identification) or IrDA (Infrared Data Association).

If the communication interface 90 uses Bluetooth, the communication interface 90 has the benefit that it also can measure the distance between the airbag system 100 and other devices. This distance can for example be used to determine if the airbag
10 system is to be put in an active or idle state.

The airbag system 100 may further comprise a user interface 95. The user interface 95 produces a signal detectable by the user, so as to alert the user 3 with different information. The user interface 95 may be used to alert the user 3 that his/hers external device 200 is nearby in order to remind the user to put the airbag system 100 in an active state and/or to alert that his/her external device 200 is far away and thus
15 remind the user to turn off the airbag system 100. The user interface 95 may also be configured to indicate the status of the airbag system 100, i.e. the battery level, if the battery is in need for charging, if the inner elements of the helmet is intact or not, and if the system 100 is turned on. The user interface 95 may also indicate if the system 100 is
20 turned on in an idle state or an active state.

The alert signal could be in the form of an audible signal such as siren, a haptic signal such as a vibration, a visual signal such as a strobe light or other sensory alarm that could be arranged on a user in the form of an airbag system 100.

The user interface 95 may comprise one or a plurality of light emitting diodes
25 (LED), which indicate information using light signal(s). Different colors of the light or flashing signals may for example indicate different information. The user interface 95 may also comprise a speaker 112 sending out a sound signal, such as a buzz, or a device sending out a vibrating signal or a spoken phrase.

In an embodiment where the user interface 95 comprises a speaker 112, the
30 speaker 112 may be used to send sound signals from an external device 200, transmitted using the communication interface 90. This external device 200 may be a different

external device 200 than the one previously mentioned. These sound signals may e.g. comprise navigational signals directing the user where to turn, possibly using a global positioning system (GPS) 260 of an external device 200 (see Fig. 6).

The airbag system 100 has to be turned on, i.e. having power, in order to work properly. In one embodiment the airbag system 100 is turned on using an on/off-button arranged somewhere on the collar 10. In yet one embodiment, the airbag system 100 is turned on automatically once the collar 10 is placed around the neck 2 of the user 3.

In some embodiments, the airbag system 100 may either be turned on in an activate state or in an idle state. In the active state all parts of the airbag system 100 are active and the airbag is thus allowed to be inflated by a triggering signal. In the idle state the airbag systems 100 is powered up but other functions may be idle. In idle mode, the control unit 50 may be active whereas the inflation device 60 and the sensor(s) 80 is inactivated (i.e. no triggering signal is detected and the airbag is not inflated).

In one embodiment, the idle state and the active state is turned on/off by the interlocking means arranged on the collar 10. The interlocking means comprises a first fastening body and a second fastening body. One end of the first and second fastening body are each connected to the collar 10. The collar 10 is thus easily attached to the neck of the user by attaching the first fastening body and the second fastening body to each other, and the collar 10 is released from the neck of the user 3 by detaching the first and second fastening bodies from each other. In a preferred embodiment, the first and second fastening body are a female and male connector.

The interlocking means is configured to be arranged in a first locking position or a second locking position when the first fastening body and the second fastening body are connected to each other. When the interlocking means is in a first locking position, the system 100 is put into an idle state and when the interlocking means is in a second locking position, the system 100 is put into an active state.

External device

As already mentioned, the protective airbag system 100 further comprises an external device 200, which will now be briefly described with reference to Fig. 4.

In the embodiment shown in Fig. 4 and in the following description, the external device is shown in the form of a bicycle 200. However, the external device mentioned herein is not limited to these examples but may take any possible form as long the device 200 comprises means for communicating within the airbag system 100.

5 If the intended use for the airbag system 100 is riding a bicycle, the external device 200 may for example be a bicycle lock or any other device suitable for attachment on or in conjunction of a bicycle. If the intended use of the airbag system 100 is horse riding, the external device 200 may be a device suitable to be arranged on the horse, for example a saddle or a bridle.

10 The bicycle may be of any type of bicycle having at least one wheel such as a bicycle with one wheel, i.e. a unicycle, an ordinary bicycle having two wheels, a tricycle having three wheels or a quadracycle having four wheels. The bicycle may for example be a utility bicycle, mountain bicycles racing bicycle, hybrid bicycle, BMX bike, a tandem or an electric bicycle.

15 In the embodiment shown in Fig. 5, the bicycle 200 comprises two wheels, a frame, two pedals, a saddle and a front set having a handlebar grip. However, the external device 200 is not limited to any particular kind when it comes to physical design.

The external device 200 may also be a separate device which is configured to
20 be attached to the bicycle.

The external device 200 further comprises means for communication. The external device 200 may comprise a communication interface 290 that communicates with the communication interface 90 arranged in the collar 10. Preferably, the communication interface 290 uses short-range wireless data communication, such as
25 short-range wireless data communication such as, for instance, Bluetooth[®], WLAN/WiFi, NFC (Near Field Communication), RF-ID (Radio Frequency Identification) or IrDA (Infrared Data Association).

If the communication interface 290 uses Bluetooth, the communication interface 290 has the benefit that it also can measure the distance between external
30 device 200 and other devices such as the airbag system 100. This distance can for example be used to determine if a communication is successfully achieved.

In some embodiments, the external device 200 further comprises a controller 250. The controller 250 may be responsible for general device operations of the external device 200, for example controlling the speed and/or the ON-OFF function of the external device. This is particularly true in the embodiments where the external device
5 200 is an electrically powered bicycle.

The controller 250 may be implemented using any suitable, publically available processor or Programmable Logic Circuit (PLC). The controller 250 may be in operative connection with a memory (not shown). The memory may be implemented using any commonly known technology for computer-readable memories such as ROM,
10 RAM, SRAM, DRAM, FLASH, DDR, SDRAM or some other memory technology.

In some embodiments, the external device 200 comprises a user interface 295. The user interface 295 produces a signal detectable by the user, so as to alert the user 3 with different information. The user interface 295 may be used to alert the user 3 that his/her airbag system 100 is turned off or in an idle ON-state and thus remind the user 3
15 to turn on the airbag system 100. The user interface 295 may also be configured to indicate the status of the external device 200 such as the battery level.

Preferably, the user interface 295 may comprise one or a plurality of light emitting diodes (LED), which indicate information using light signal(s). Different colors of the light may for example indicate different information.
20

The alert signal could also be in the form of an audible signal such as siren or a buzz or other sensory alarm that could be arranged on the external device 200.

If the bicycle is an electric bicycle it may also comprises an integrated electric motor (not shown) which can be used for propulsion and a controller for controlling the applied speed. There are many possible types of electric motorized bicycles with several
25 technologies available and these will thus not be described further.

In another embodiment, as is schematically illustrated in Fig. 6, the external device 200 is a mobile phone 210. The user interface 95 of the airbag system 100 comprises a speaker 112, configured to transmit sound signals generated by the mobile phone 210, and transmitted using the communication interface 90. These sound signals
30 may e.g. be streamed audio data, comprising real-time navigational signals directing the

user where to turn, possibly using a global positioning system (GPS) 260 of the mobile phone 210.

Protective system

5 The provision of a protective system comprising an airbag system 100 and an external device 200 which differentiates between when the airbag system 100 and the external device 200 are within a predetermined distance or not solves or at least reduces the problem of having a person riding a bicycle without turning on the airbag system 100 and/or having a person walking around with the airbag system 100 in a powered
10 state. This is done by the fact that the airbag system 100 and the external device 200 in the protective system interacts wirelessly with each other. If the airbag system 100 succeeds in establishing a short-range wireless data communication with the external device 200, one can assume that the user 3 of the airbag system 100 is in the vicinity of the external device 200. The communication may be used to change the mode of the
15 airbag system 100 and/or the mode of the external device 200 depending on the communication status.

 In the embodiment where the external device 200 is a bicycle or a bicycle lock the communication has several benefits, as will now be described.

 The airbag system 100 is intended to be worn when riding a bicycle and is
20 configured to determine if an accident, such as a fall or collision, has occurred when riding the bicycle. In order to reduce the power consumption and the possible risk of the airbag system 100 inflating unintentionally, the airbag system 100 should only be turned on, or turned on in an active state, when the user 3 is riding the bicycle or is in proximity of the bicycle (intending to ride the bike, or if he/she just got off the bike). If
25 the airbag system 100 is turned on, or turned on in an active state, when the user 3 is moving away from his/hers bicycle 200, it would be preferable if the system 100 would be turned off or turned into an idle ON-state.

 Furthermore, if the airbag system 100 is not turned on, or turned on in an idle state, while the user 3 is in proximity of his/hers bicycle 200 it would be beneficial if
30 the bicycle 200 was put in a safety mode where the speed of the bicycle is reduced or

where its not possible to bike at all (due to power cut off in the case of an electric bicycle or by a locking device).

In one embodiment, the communication interface 90 of the airbag system 100 is configured to attempt to communicate with the external device 200 using wireless
5 communication. Additionally, or alternatively, the external device 200 is configured to attempt to communicate with the airbag system 100.

This attempt is conducted at predetermined time intervals, for example every 30 seconds, every minute or every second minute. The attempt may also be more seldom, such as every fifth minute.

10 In some embodiments the communication attempt is only conducted when it is detected that the user 3 of the airbag system 100 is walking and/or not riding a bicycle. In some embodiments the airbag system 100 is configured to determine what activity state the user is in, e.g. if the user is walking or riding a bicycle, based on movement data gathered from at least one sensor, the sensor either being the same as the sensor
15 colleting movement data for triggering of the inflation or an additional sensor. The communication attempt may then be conducted only when the airbag system 100 is in a walking activity state, or when the user is not in a bicycling activity state.

In one embodiment the communication between the airbag system 100 and the external device 200 is considered to be successful if a communication is established
20 between the airbag system 100 and the external device 200. In another embodiment the communication between the airbag system 100 and the external device 200 is successful if a communication is established between the airbag system 100 and the external device 200 and if the airbag system 100 and the external device 200 are within a predetermined distance from each other. The predetermined distance may be measured
25 by the communication interface 90 of the airbag system and/or by the communication means 290 of the external device 200.

The communication between the airbag system 100 and the external device 200 will now be described further with exemplified embodiments with reference to Figs.5a-
b.

30 As seen in the embodiment of Fig. 5a, if the communication between the airbag system 100 and the external device 200 is successful, the control unit 50 of the airbag

system 100 is configured to put the airbag system 100 in a first mode. Depending on configuration the first mode may pertain to different functions.

In the first mode the control unit 50 may be configured to alert the user 3 that he/she should manually turn on, or turn on in an activate state, the airbag system 100 since he/she is in close proximity of the bicycle 200. If the airbag system 100 already is turned on, or turned on in an activate state, the control device 50 may be configured to not alert the user. The alert to the user 3 may be generated by the user interface 95 which produces a signal detectable by the user as described with reference to Fig. 3.

Additionally, or alternatively, the control unit 50 may be configured, in the first mode, to automatically put the airbag system 100 in an active state if the airbag system 100 has an idle ON-state and an active ON-state. In this way the airbag system 100 is always turned on and ready to protect the user 3 in case of a bicycle accident when the bicycle 200 is in proximity to the user 3.

If instead the communication between the airbag system 100 and the external device 200 is not successful, i.e. either the communication establishment fails or the communication is established but the airbag system 100 and the external device 200 is not within the predetermined distance from each other, the control unit 50 of the airbag system 100 is configured to put the airbag system 100 in a second mode. Depending on configuration the second mode may pertain to different functions.

In the second mode the control unit 50 may be configured to alert the user 3 that he/she should manually turn off, or turn the airbag system in an idle state, since he/she is not in close proximity of the bicycle 200. If the airbag system 100 already is turned on in an idle state, the control device 50 may be configured to not alert the user 3.

Additionally, or alternatively, the control unit 50 may be configured, in the second mode, to automatically turn off the airbag system 100 or put the airbag system 100 in an idle state if the airbag system 100 has an idle ON-state and active ON-state. In this way the airbag system 100 is turned off, or turned into an idle ON-state, once the user 3 is not in proximity of the bicycle 200. This reduces battery consumption of the airbag system 100 and eliminates the possible risk of the airbag 20 being inflated unintentional.

In the embodiment shown in Fig. 5b, the state of the external device 200 is changed depending on the communication between the airbag system 100 and the external device 200. As seen in the embodiment of Fig. 5b, if the communication between the airbag system 100 and the external device 200 is successful the controller of the external device 200 is configured to disable the external device 200 from a safety mode, if activated.

If instead the communication between the airbag system 100 and the external device 200 is not successful, i.e. fails, the controller of the external device 200 is configured to put the external device 200 in a safety mode of the external device 200.

Depending on configuration the safety mode may pertain to different functions. In the safety mode the controller 250 of the external device may be configured to alert the user 3 to put on the airbag system 100 in an idle mode. This may for example be done by a light indicator visibly arranged on the external device 200.

Additionally, or alternatively, the controller 250 of the external device 200 may be configured, in the safety mode, to prevent the user 3 from using the external device 200. This may for example be prevented by locking the bicycle by a locking device (not shown) which is locked in a safety mode and unlocked when the safety mode is disabled. Such a locking device may be a smart lock which is able to communicate with the external device 200, so as to open the lock when the safety mode is disabled.

In the embodiment where the external device 200 is a bicycle lock, the locking device is able to communicate with the airbag system 100 so that the safety mode of the external device 200 pertains to locking the bicycle lock. Disabling the safety mode thus means opening the bicycle lock.

In the embodiment where the external device 200 is an electric bicycle, the user could also be prevented from using the bicycle 200 by having a safety mode configured to lock the electric bicycle 200 so as to prevent the user 3 from using it by power cut-off. Alternatively, the safety mode is configured to reduce the maximum allowed speed of the electrical bicycle 200. In this way, if the user 3 is not wearing the airbag system 100, or the system is not turned on in an active state, the bicycle cannot be used or can only be used at a slow speed.

The two embodiments disclosed in Fig. 5a-b can be combined. One such combination is seen in Fig. 5c, showing that if the communication is successful the airbag system 100 is put in a first mode and the external device 200 disables the safety mode, if present. If the communication fails, the airbag system 100 is put in a second mode and the external device 200 is put in a safety mode.

It should be understood that different combinations of the different configurations could be made and that the configurations could be made simultaneously with each other or in a prescribed order, e.g. first put the external device 200 in a safety mode and then put the airbag system 100 in a second mode.

CLAIMS

1. Protective system, comprising:
an airbag system (100) in the form of an inflatable helmet for protecting a body
5 part of a user (3) in case of an accident, comprising a control unit (50) and a
communication interface (90); and
an external device (200) comprising communication means (290),
wherein the communication interface (90) of the airbag system (100) is
configured to communicate with said external device (200) using wireless
10 communication.
2. The protective system according to claim 1, wherein the wireless
communication is short-range wireless communication.
- 15 3. The airbag system according to claim 2, wherein the short-range wireless
communication may pertain to any of Bluetooth, WLAN, WiFi, NFC, RF-ID or IrDA.
4. The protective system according to any of claim 1 to 3, wherein the
communication interface (90) of the airbag system (100) is configured to attempt to
20 communicate with said external device (200).
5. The protective system according to claim 4, wherein the communication
between the airbag system (100) and the external device (200) is successful when a
communication is established between the airbag system (100) and the external device
25 (200).
6. The protective system according to claim 4, wherein the communication
between the airbag system (100) and the external device (200) is successful when a
communication is established between the airbag system (100) and the external device
30 (200), and the external device (200) and the airbag system (100) are within a
predetermined distance from each other.

7. The protective system according to claim 4, wherein the communication between the airbag system (100) and the external device (200) is unsuccessful when communication fails to establish between the airbag system (100) and the external
5 device (200).

8. The protective system according to claim 5, wherein the communication between the airbag system (100) and the external device (200) is unsuccessful when a communication is established between the airbag system (100) and the external device
10 (200), but the external device (200) and the airbag system (100) are not within a predetermined distance from each other.

9. The protective system according to any of claim 4 to 8, wherein if the communication between the airbag system (100) and the external device (200) is not
15 successful, the control unit (50) of the airbag system (100) is configured to put the airbag system (100) in an idle state and/or to alert the user (3) to manually change to an idle state.

10. The protective system according to any of claims 4 to 9, wherein if the
20 communication between the airbag system (100) and the external device (200) is not successful, a controller (250) of the external device (200) is configured to control the external device (200) into a safety mode.

11. The protective system according to any of claim 4 to 10, wherein if the
25 communication between the airbag system (100) and the external device (200) is successful, the control unit (50) of the airbag system (100) is configured to put the airbag system (100) in an active state and/or to alert the user (3) to manually change to an active state.

12. The protective system according to any of claims 4 to 11, wherein if the communication between the airbag system (100) and the external device (200) is successful a controller (250) of the external device (200) is configured to disable a safety mode of the external device (200).

5

13. The protective system according to claim 11 or 12, wherein in the safety mode the controller (250) of the external device (200) is configured to lock the external device (200) so as to prevent the user (3) from using it.

10

14. The protective system according to any of claims 11 to 12, wherein the external device (200) is an electric bicycle and wherein in the safety mode the controller (250) of the electric bicycle (200) is configured to lock the electric bicycle (200) so as to prevent the user (3) from using it or to reduce the allowed speed of the electrical bicycle (200).

15

15. The protective system according to any of claims 1 to 14, wherein the external device (200) is a bicycle.

16. The protective system according to any of claims 1 to 14, wherein the external device (200) is a bicycle lock.

20

17. The protective system according to any of claims 1 to 14, wherein the external device (200) is a mobile phone (210).

18. The protective system according to claim 17, wherein the airbag system (100) comprises a speaker (112), and wherein the mobile phone (210) is configured to stream audio data to said speaker (112).

25

19. The protective system according to claim 18, wherein the audio data is real-time navigation audio.

30




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5a




Fig. 5b




Fig. 5c




Fig. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE2018/050703

A. CLASSIFICATION OF SUBJECT MATTER IPC: see extra sheet According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC: A41D, A42B Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched SE, DK, FI, NO classes as above Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, PAJ, WPI data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 20160207486 A1 (WAHL ANJA ET AL), 21 July 2016 (2016-07-21); whole document --	1-19
X	US 20150173433 A1 (MAZZAROLO GIOVANNI ET AL), 25 June 2015 (2015-06-25); whole document --	1-19
X	US 20110237194 A1 (KOJIMA HIROYUKI ET AL), 29 September 2011 (2011-09-29); whole document -- -----	1-19
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 20-07-2018		Date of mailing of the international search report 20-07-2018
Name and mailing address of the ISA/SE Patent- och registreringsverket Box 5055 S-102 42 STOCKHOLM Facsimile No. + 46 8 666 02 86		Authorized officer Lisa Sellgren Telephone No. + 46 8 782 28 00

Continuation of: second sheet

International Patent Classification (IPC)

A41D 13/018 (2006.01)

A42B 3/00 (2006.01)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SE2018/050703

US	20160207486 A1	21/07/2016	DE	102013217851 A1	12/03/2015
			JP	2016529163 A	23/09/2016
			US	9956933 B2	01/05/2018
			WO	2015032736 A1	12/03/2015
US	20150173433 A1	25/06/2015	AU	2013283575 A1	18/12/2014
			BR	112014029574 A2	27/06/2017
			CA	2877171 A1	03/01/2014
			CN	104411194 B	19/10/2016
			EP	2863767 A1	29/04/2015
			ES	2599667 T3	02/02/2017
			IT	TV20120124 A1	27/12/2013
			JP	6084289 B2	22/02/2017
			JP	2015527499 A	17/09/2015
			KR	20150023422 A	05/03/2015
			RU	2632281 C2	03/10/2017
			RU	2015102092 A	20/08/2016
			WO	2014001189 A1	03/01/2014
US	20110237194 A1	29/09/2011	CA	2733752 C	28/01/2014
			JP	2011201358 A	13/10/2011
			JP	5421166 B2	19/02/2014
			US	8348304 B2	08/01/2013