# (12) UK Patent Application (19) GB (11)

## 2 164 189 A

(43) Application published 12 Mar 1986

- (21) Application No 8422349
- (22) Date of filing 5 Sep 1984
- (71) Applicant
  Dr. Khodayar Rashidi
  17 Springdale Close, Willerby, Hull HU10 6RE
- (72) Inventor

  Dr. Khodayar Rashidi
- (74) Agent and/or Address for Service
  Dr. K. Rashidi, 17 Springdale Close, Willerby, Hull HU10 6RE


- (51) INT CL<sup>4</sup>
  G09F 13/00 H05K 1/14
- (52) Domestic classification G5C EJ H1R AB
- (56) Documents cited


  GB A 2087137 GB 1530816 GB 0521187


  EP 0069571
- (58) Field of search **G5C**

#### (54) Modular-display-system


(57) A modular display system, has a printed circuit mother (or main) board 1, containing the main electronic circuitry and components (4) Fig 3 (not shown) and multi-way connection sockets 2 situated along its top and bottom length that accommodates another set of modular printed circuit boards 3 with light emitting diodes 9 so constructed on its surface as to describe or represent an alpha-numeric character which is then switched ON and/or OFF at regular or random intervals/patterns. The printed circuit mother board 1 is extendable along its length and width by attachment of similar boards to connectors 5 and/or 6, so that a word or a sentence of any height or length can be made up by the connection of the light emitting diode-display modules 3 to the said mother board(s). The whole assembly is then placed behind a frosted screen (7) in a frame (8).












F1G. 4



#### **SPECIFICATION**

#### Modular-display-system

5 This invention relates to a modular display system. Light emitting diodes used in the systems for display of informations are well known and generally used for displaying computer generated characters, whether it be stationary or moving. They have also

10 been used for generating moving pictures in monochrome. Sush systems are generally expensive and require more light emitting diodes than necessary in order to display fixed alpha-numeric characters, such as in advertising a product or displaying a 15 company name etc.

According to the present invention there is provided a printed circuit mother board with expansion facilities, comprising of a rectangular board with multi-way connection sockets placed at regular intervals along

20 its top and bottom length which in turn accommodates another set of printed circuit boards with light emitting diodes so constructed on its surface as to describe an alpha-numeric character that is them made to switch ON and/or OFF by electronic circuitry.

25 A specific embodiment of the invention will now be described by way of example with reference to the accompanying drawings in which:-Figure 1 shows in perspective the mother board with multi-way connection sockets and alpha-numeric

0 character boards. Figure 2 illustrates the method by which the alphanumeric characters, that are made up of a series of light emitting diodes, are plunged into the multi-way connection sockets.

35 Figure 3 shows in cross-section the complete assembly of the modular display system.
Figure 4 shows a typical block diagram of the electronic circuitry to operate the light emitting diodes.

40 Referring to the drawing of Fig. 1, the mother board 1 comprises multi-way connection sockets 2 which accomodates a number of modular printed circuit boards 3 with light emitting diodes 9 so constructed on its surface as to describe an alpha-numeric

45 character. The light emitting diodes 9 on the character display boards 3 are switched ON and/or OFF by the electronic circuitry 4 (see Fig. 3) situated on the mother board 1. The signals from the mother board are fed to the character display boards 3 via the

50 multi-way connection sockets 2, which also acts as means for supporting the character display modules.

In order to make up a word or a sentence (for example, advertising the name of a product or that of a company) which is to be displayed, appropriate

55 alpha-numeric character display modules are pluged side-by-side into the mother board's multi-way connection sockets untill the word is complete. The mother board can also be extended either along its length or width, by connecting more modules of

60 similar type to that of the mother board into connectors 5 and 6 respectively. Referring to Fig. 3 the whole assembly is then placed behind a frosted glass screen 7 and for decorative purposes it is placed inside a frame 8. In order to produce an interesting pattern of

65 lights from the light emitting diodes a typical electro-

nic circuitry is shown in Fig. 4, but many alternatives are possible.

### CLAIMS

 A printed circuit mother board with expansion
 facilities comprising of a rectangular board with multi-way connection sockets placed at regular intervals along its top and bottom length which in turn accommodated another set of printed circuit boards or modules with light emitting diodes so constructed
 on its surface as to describe an alpha-numeric

75 on its surface as to describe an alpha-numeric character that is then made to switch ON and/or OFF by electronic circuitry.

An interchangable display system made of printed circuit board modules as claimed in claim 1,
 consisting of light emitting diodes so constructed on its surface as to describe an alpha-numeric character which can be connected into multi-way connection sockets attached to a main electronic circuit board (or so called mother board) that contains the control
 electronic circuitry.

A modular printed circuit mother board with electronic facilities as claimed in claim 1 wherein extension facilities are provided so that other modules of similar size, shape and electronic circuitry can be fitted along its length and width in order to allow a word or a sentence of any length or height be made up by connection of light emitting diode-display modules which describe an alpha-numeric character on its surface, to the said mother board(s).

95 4. An alpha-numeric display system as claimed in any of the preceding claims that has a number of interchangable printed circuit display modules consisting of light emitting diodes so constructed on its surface as to describe an alpha-numeric character,
100 that will allow a word or a sentence to be made up by fitting the appropriate alpha-numeric display modules side-by-side to make up that word or sentence.

5. A modular alpha-numeric display system as claimed in any of the preceding claims consisting of light emitting diode-display modules, operated by electronic circuitry to either remain ON or OFF continuously or flashed ON and OFF at regular or random intervals/patterns, placed in a picture frame for decorative purposes, either on its own or behind a frosted screen or items of similar nature.

Printed in the United Kingdom for Her Majesty's Stationery Office, 8818935, 3/86 18996. Published at the Patent Office, 25 Southampton Buildings, London WC2A 1AY, from which copies may be obtained.