

SAKO SPECIFICATION SAKO

SAKO TRG SHARPSHOOTING SYSTEM



SAKO TRG based on a series of actions which designated: Short action TRG-22 and Long action TRG-42. Receiver is made by coldhammering method. Three locking lugs makes 60° bolt lift angle possible. The receiver is stabilized with three fastening screws. Optionally available with phosphatized finish. The bolt is black matte on all models.

The MAGAZINE is a detachable reliable center fed box magazine. Plugs for easy removing at the rear corners.

The DOUBLE-STAGE TRIGGER pull is adjustable from 1 to 2.5 kg (2 to 5 lbs). It is also adjustable in length and horizontal or vertical pitch. The entire trigger assembly, including the trigger guard, can be removed from the rifle without disassembling any other part of the rifle.

The SAFETY catch, which is silent in operation, is located inside of the trigger guard. The safety locks the trigger mechanism and locks the bolt in a closed position with the firing pin blocked.

The base of the STOCK is made of aluminium, to which the polyurethane forestock is attached. The buttstock is also made of polyurethane and is reinforced through the use of an aluminium skeleton. Spacers allow the cheek piece to be fully adjustable in height and infinitely adjustable in windage and pitch.

The BUTTPLATE is adjustable both for distance and angle through the use of spacers and is also infinitely adjustable in height and pitch.

The stock is designed for both right and left handed shooters. Phosphatized model can be supplied with 200 g (7 oz) heavier green or Desert Tan color stock.

Sako TRG is supplied without OPEN SIGHTS. A 17 mm integral dovetail is on the top of the receiver for optical day or night sight mounting. Receiver is also drilled and tapped for Picatinny rail mounting. Phosphatized barrel is equipped with groove for emergency sight assembling.

The free-floating BARREL is cold-hammerforged. Optional detachable muzzle brake can be fitted, which also acts as an efficient flash-hider.

SAKO TRG sharpshooting system optional accessories for special purposes like: Suppressor (for cal. 308 Win), foldable bipod, auxiliary steel peep sights for emergency use, match sight mounting set, night sight adapter, different slings and swivels, cleaning sets, transit cases etc.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length without muzzle brake	
TRG-22	308 Win	11"	TRG-22	1150 mm (45 1/4")
TRG-42	300 Win Mag	11"	TRG-42	1200 mm (47 1/4")
TRG-42	338 Lapua Mag	12"	Barrel length	
Magazine			TRG-22	660 mm (26")
TRG-22 10-round detachable magazine			TRG-42	690 mm (27 1/8")
TRG-42 300 Win Mag 7-round detachable magazine			Weight	
TRG-42 338 Lapua Mag 5-round detach. magazine			TRG-22 black	4.7 kg (10 1/4 lbs)
Max cartridge length			TRG-22 green	4.9 kg (10 3/4 lbs)
TRG-22	75 mm (3")		TRG-42 black	5.1 kg (11 1/4 lbs)
TRG-42	95 mm (3 3/4")		TRG-42 green	5.3 kg (11 3/4 lbs)