

## NASA Showroom Spec Miata Rule

### 2010 SSM Car Preparation Specification 01/28/2010

#### 1. PURPOSE AND INTENT

Showroom Spec Miata (SSM) was conceived as an entry-level class with emphasis on simplicity, equality and low cost.

SSM vehicles shall conform to Club Codes and Regulations (CCR), with the exception of the following restrictions or specifically allowed modifications. These rules are not intended as guidelines or suggestions and they will be vigorously enforced.

The Showroom Spec Miata (SSM) class is intended to provide the membership with the opportunity to compete in a production-based car with limited modifications, suitable for racing competition.

The rules are intentionally designed to be more restrictive than the Spec Miata Class.

The vehicle identification number (VIN) shall correspond with the model-year automobile classified. VIN plates or stampings shall remain in place. There must be a minimum of two (2) VIN plates or stampings that correspond with the model year automobile classified.

#### 2. CLASSIFIED CARS AND WEIGHTS

1990 - 1993 Miata 1600 cc @ 2300 lbs. with driver

#### 3. AUTHORIZED MODIFICATIONS

The following items represent the only modifications and safety items permitted and/or required on Showroom Spec Miata automobiles other than safety items as required in the current CCR. No permitted component/modification shall additionally perform a prohibited function. No updating or backdating of cars, models, specifications, and/or components thereof shall be permitted except as specifically authorized.

A Mazda Factory Service Manual (FSM) for the specific make, model, and year of automobile is required to be at the disposal of each entrant. The manual is intended to aid a Scrutineer in identifying parts and the configuration of the automobile.

Overhauled engines must conform to the power and torque specification, and will be sealed by an approved vendor. .

The application and/or use of any painting, coating, plating, heat tape, or impregnating substance (i.e. anti-friction, thermal barrier, oil shedding coatings,

chrome, anodizing, etc.) to any internal engine, transmission, or differential surface or internal or external exhaust manifold or downtube surface is prohibited.

All adjustments shall be at the manufacturer's specification in the FSM and/or within the manufacturer's specified tolerances except as permitted within these rules.

Stock replacement parts may be obtained from sources other than the manufacturer provided they are the exact equivalent of the original parts. The intent of this rule is to allow the competitor to obtain parts from standard industry outlets, e.g., auto parts distributors, rather than from the manufacturer. It is not intended to allow parts that do not meet all dimensional and material specifications of new parts from the manufacturer. Note that OEM "replacement" is not necessarily the same as OEM "equivalent".

All engines, components, and parts must have been offered for sale in a Mazda Miata, sold by a dealer in the United States of America. All engines and their internal components must remain stock, except as provided by these rules and within factory specified tolerances.

### 3.1. Engine Modifications

#### 3.1.1. Induction System

3.1.1.1. All air entering the intake tract shall pass through the unmodified stock air inlet.

3.1.1.2. Cars must use the unmodified stock air box. An unmodified OEM-style filter element must be installed in the air box.

3.1.2. Fluid hoses and clamps, oil filters, fuel filters, and belts (fan, alternator, etc.) may be substituted with others of equivalent OEM specifications.

#### 3.1.3. Fuel System

3.1.3.1. Unleaded fuel filler trap door and restrictor plate in filler neck may be removed.

3.1.3.2. Refer to current CCR and class rules for permitted fuel. All cars are to have fuel test port installed for the collection of fuel samples.

3.1.3.3. The current CCR Section is further restricted for SSM to limit fuel to a maximum of 94 octane. Fuel must be from a commercially mass marketed supplier (e.g. Sunoco, Exxon, Mobil) or independent mass marketer (e.g. Sheetz). Limited use race fuels are not permitted. Pump fuel may be purchased at the track (e.g. Sunoco at Summit Point). The Series Director or Race Director at their discretion may spec the track fuel or a common source close to the track. Also, it is within the power of the Series Director to provide spec fuel to competitors. Competitors will be expected to pay for fuel at market price. Race fuels such as, but not limited to, ERC brand are prohibited. All fuel additives are illegal, per the CCR. Note- event supplemental rules supersede this section.

#### 3.1.4. Ignition/Electrical System

3.1.4.1. Ignition timing is limited to a range of 10 to 16 degrees BTDC.

- 3.1.4.2. Batteries may be replaced with those of an alternate manufacturer provided they are of similar weight and size and are fitted in the standard location. Additional battery hold-down devices may be used and are strongly recommended provided they do not serve any other purpose, i.e. ballast. The combined weight of the battery and hold-down device and/or battery box shall not exceed thirty-five (35) pounds.
- 3.1.4.3. Spark plugs are restricted to the NGK BKR6E-11 (Mazda part number BP03-18-110).
- 3.1.4.4. Ignition wires are restricted to stock NGK(Mazda part number 0000-18-121A), or Taylor (Mazda part number 0000-10-5301).
- 3.1.5. Exhaust System
  - 3.1.5.1. Catalytic converter may be removed and replaced with the replacement pipe part # 0000-06-5423. All other exhaust components shall remain OEM stock except for the required installation of Mazda Motorsports exhaust part #0000-06-5425.
  - 3.1.5.2. Original exhaust system heat shields may be removed. Any heat shielding may be added or removed aft of the stock downpipe, providing that the additional shielding serves no other purpose.
- 3.1.6. Clutch System and Flywheel: All cars shall use either the stock OEM pressure plate Mazdaspeed part #B622-16-220A or the ACT pressure plate (Mazdaspeed part #0000-0205401-SS). The unmodified pressure plate shall be bolted directly to the appropriate stock, unmodified flywheel. Any clutch disk may be used.
  - 3.1.6.1. The OEM flywheel friction surface may be resurfaced, but the minimum flywheel weight (including the pilot bearing) is 17.6 lbs.
- 3.1.7. Any lubricant may be used. Oil additives are unrestricted.
- 3.1.8. Camshafts shall comply with the Official Spec Miata Camshaft Data as supplied by the NASA Tech Department.
- 3.1.9. Cooling System
  - 3.1.9.1. Any radiator may be used, provided it is mounted in the original location, maintains the same plane as the original core and requires no body or structure modifications to install. New openings created by fitting an alternate radiator must be blocked and may not be used for the purpose of ducting air to the engine.
  - 3.1.9.2. The stock cooling fan(s) must be maintained other than the AC fan, which may be removed when the entire AC system is removed.
  - 3.1.9.3. If used, the aftermarket radiator shall be modified, if necessary, to mount the stock OEM cooling fan in the original mounting location(s).
  - 3.1.9.4. Thermostats may be modified, removed, or replaced.
  - 3.1.9.5. All cars may install the Upper Radiator Seal, part # NA75-50-OK7A
  - 3.1.9.6. A radiator screen of one-fourth (1/4) inch minimum mesh may be added in front of the radiator and contained within the bodywork.

- 3.1.9.7. The factory air conditioning systems may be removed. Items that serve a dual purpose, such as the alternator/air conditioning compressor bracket, may not be substituted.
- 3.1.9.8. Engine coolant fluid, coolant/heater hoses and clamps may be substituted. Heater core may be bypassed, but it may not be modified or removed. Heater water control valve(s) may be added or substituted.
  
- 3.1.10. Transmission/Final Drive
  - 3.1.10.1. Transmission and final drive ratios must remain stock for the year of car.
  - 3.1.10.2. Cars may use the stock, unmodified viscous limited slip differential or the MAZDASPEED Motorsports Development limited slip differential, part #QN10-64-A00 (previously TOY1-27-200 & 0000-02- 5501). The stock open differential is also approved for use.
  - 3.1.10.3. Cars may convert to the 99-05 differential housing and the 4.3 differential gear ratio from the 99-05 model years. This conversion includes the driveshaft and half-shafts. The original 90-93 model rear suspension uprights must be retained.
- 3.1.11. Chassis: Suspension modifications are limited to the required addition of the MAZDASPEED Motorsports Development "Spec Miata kit" (part number K-SPEC-M5-SUSP) and those modifications detailed in this area. The following is a breakdown of components supplied within these kits. All parts numbers are MAZDASPEED Motorsports Development parts numbers. No substitution of parts is allowed. The kits must be used in their entirety.
  - 3.1.11.1. Shocks: Front: Bilstein part #0000-04-5225-BL; Rear: Bilstein part #0000-04-5226-BL
  - 3.1.11.2. Springs: Front: Eibach ERS 700 lbs./6" part #0000-04-9700-06; Rear: Eibach ERS 325 lbs./7" part #0000-04-9325-07
  - 3.1.11.3. Coil-Over kit: Front/Rear part # 0000-04-5402AW
  - 3.1.11.4. Anti-Roll Bars: Eibach kit part # 0000-04-5302-EB; Front: 24mm adjustable; Rear: 15mm adjustable
  - 3.1.11.5. All cars shall use either the unmodified Mazdaspeed bump stop (Part #0000-04-5993AW) included with the Mazdaspeed suspension kit or the Fatcat Motorsports Spec Miata kit FCM-MT-KIT-SM along with the 1999 shock hats specified below. Cars built with the original procedure of welding a 63.5 mm centering ring to the outside diameter of 58 mm are grandfathered if the logbook was issued prior to 01/01/2003.
  - 3.1.11.6. Cars may use the bump stops from the Mazdaspeed kit (p/n 0000-04-5993-AW) in conjunction with the 1999-up stock upper mount (p/n: NC10-28-340C), the 1999-up lower mount bushing (p/n: NC10-28-776) and the 1999-up upper mount washer (p/n: NC10-28-774). All other OEM upper mounting hardware shall be discarded. Only Mazda

OEM parts sourced from Mazda or Mazdaspeed are acceptable. OEM equivalent parts are not acceptable.

- 3.1.11.7. Sub-frame braces may be updated to stock 1997 configuration utilizing the MAZDASPEED Motorsports Development Spec Miata kit (Mazda part # NA75-56-3AY).
- 3.1.11.8. Anti-roll bar links may be replaced and may be adjustable, but the attachment points must remain stock. The control arms and specified anti-roll bar may not be modified. One end of the sway bar(s) may be disconnected as a suspension tuning aid. The bar must remain in place and be solidly attached to the suspension on one end.
- 3.1.12. Suspension alignments
  - 3.1.12.1. Caster and toe: unrestricted within the limits of the unmodified factory adjustments
  - 3.1.12.2. Ride height: unrestricted.
  - 3.1.12.3. Camber: Front: Maximum 3 degrees negative (not more negative than three degrees); Rear: Maximum 2.5 degrees negative (not more negative than two and one-half degrees).
- 3.1.13. No relocation or reinforcement of any suspension component or mounting points is permitted.
- 3.1.14. Hardware items (nuts & bolts) may be replaced by similar items performing the same fastening function(s).
- 3.1.15. Manual or power steering racks may be used. Power steering racks may be converted to manual by removing all power steering components and looping or capping hydraulic lines.
- 3.1.16. Towing eyes per CCR are required. Stock towing eyes may be modified or replaced.
- 3.1.17. Hubcaps and wheel trim shall be removed.
- 3.1.18. All chassis/structural/electrical repairs, if performed, shall be in concurrence with factory procedures, specifications, and dimensions. Unless specifically authorized by the manufacturer for repair or allowed by these rules, no reinforcement, i.e., seam welding, material addition, etc., is permitted. No acid dipping of the unibody is permitted. Undercoating removal is permitted.
- 3.1.19. Brakes
  - 3.1.19.1. Backing plates and dirt shields may be removed.
  - 3.1.19.2. Brake lines shall be replaced with steel lines or teflon lined metal braided hose. All four hoses must be of the same size and specification.
  - 3.1.19.3. Cars with antilock braking systems must have the system disabled or removed.
  - 3.1.19.4. Parking brake mechanisms and actuating components may be removed.
  - 3.1.19.5. Brake pads and brake fluid are unrestricted
- 3.1.20. Wheels/Tires: All wheels must be used within the following limitations:
  - 3.1.20.1. Required rim diameter is fifteen (15) inches and rim width is seven (7) inches.

- 3.1.20.2. Minimum weight of wheel is 13.0 lbs. Spacers are permitted providing the effective offset of spacer and rim is a minimum of 25mm. All four wheels must have identical effective offset.
- 3.1.20.3. All wheels must be one-piece metal castings (not multi-piece wheels, bolted, riveted or welded together).
- 3.1.20.4. After market wheel studs are permitted.
- 3.1.20.5. The spec tire is the *The Toyo RA-1* ~~Toyo R888~~ in size 205-50-15, shaved or unshaved. ~~The Toyo RA-1 may be used for the first two events in 2009 of any region's schedule, but only tires with a manufacturer's date prior to December 3, 2008 may be used.~~
- 3.1.20.6. Tire tread (that portion of the tire that contacts the ground under static conditions) shall not protrude beyond the fender opening when viewed from the top perpendicular to the ground. To determine compliance, the vehicle should be rolled through a powdered substance, as raced with driver, in order to indicate the tire tread contact patch under static conditions.
  - 3.1.21. Body/Structure
    - 3.1.21.1. Fenders and wheel openings shall remain unmodified. It is permitted to roll under or flatten any interior lip on the wheel opening for tire clearance. Non-metallic inner fender liners may be removed.
    - 3.1.21.2. Body repair shall be performed using every reasonable effort to maintain stock body contours. Any body repair modification having as its purpose increased clearance is prohibited. Cars shall meet the requirements of current CCR at all times.
    - 3.1.21.3. No air dams, wings, or spoilers are allowed other than the "R" package Miata chin spoiler provided it is mounted in the OEM location.
    - 3.1.21.4. Windshield Clips/Rear Window Straps are permitted and recommended.
    - 3.1.21.5. Convertible tops and attaching hardware shall be completely removed. Cars may compete with the Mazda factory detachable hard top or Snug Top in place (latches shall be replaced with positive fasteners), but it is not mandatory. When no top is used, driver shall wear arm restraints, and the cage must meet the helmet clearance rule.
    - 3.1.21.6. Body side moldings, rocker panel moldings, and wheel opening trim pieces may be removed.
    - 3.1.21.7. The plastic trim on the hood, windshield washer nozzles and tubing, and windshield wiper "wing" may be removed.
    - 3.1.21.8. Hood and trunk clips are permitted. If so equipped, stock hood latches and trunk latches may be disabled or removed.
    - 3.1.21.9. Ducting may be added to provide fresh air to the driver compartment. This ducting shall be located in the driver and/or passenger vent window with no modifications to the bodywork. Ducting shall not extend beyond the plane of the original side windows. Such ducting will serve no other purpose than to provide cool and/or fresh air to the driver.

- 3.1.21.10. To improve driver exit through the window area, the driver and/or passenger vent window and vertical vent window supports may be removed as an assembly
- 3.1.21.11. Radio antennas may be removed. Antennas for two-way radios may be added.
- 3.1.21.12. "Pinch weld" jacking points may be reinforced with lengths of material not to exceed 6" x 6" by 1/8" thick.
- 3.1.22. Driver/Passenger Compartment/Trunk
  - 3.1.22.1. The driver's seat shall be replaced with a one-piece bucket-type race seat. All seat mountings shall be reinforced. Factory seat tracks/brackets may be modified, reinforced, and/or removed to facilitate replacement mountings provided they perform no other function. The OEM passenger seat must be removed, but a replacement seat meeting the specifications of the driver seat may be substituted. To facilitate installation of a safety seat, modification of the center tunnel and its intersection with the floor pan shall be permitted provided that no such modification interferes with the mechanical operation (e.g. exhaust system, transmission, etc.) and only the minimum required removal is performed. Material added shall provide thickness and strength approximately equal to the removed material.
  - 3.1.22.2. Any steering wheel, except wood rimmed types, and its required mounting modifications may be used. Any shift knob may be used.
  - 3.1.22.3. Gauges and instruments, including data systems, may be added, replaced, or removed. They may be installed in the original instrument(s) location using a mounting plate(s), or any other location using a secure method of attachment. The vehicle's "Check Engine" light shall remain functional. Other than modifications made to mount instruments and provide for roll cage installation, the remainder of the dashboard shall remain intact.
  - 3.1.22.4. Any interior or exterior mirrors may be used. Mirrors may be removed.
  - 3.1.22.5. Carpets, center consoles, cargo bins, seat belts, floor mat, radio system, headliners, dome lights, grab handles, sun visors and their insulating and attaching materials may be removed. Other than to provide for the installation of required safety equipment or other authorized modifications, no other driver/passenger compartment alterations or gutting are permitted.
  - 3.1.22.6. The driver/passenger side door window glass, window operating mechanism, and inside door latch/lock operating mechanism may be removed and the inner door structural panel may be removed. The stock side impact beam and the outside door latch/lock operating mechanism shall not be removed or modified.
  - 3.1.22.7. Two way radios may be used.
  - 3.1.22.8. Spare wheels and tires, jacks and tools shall be removed. Spare tire covers and trunk mats and/or trunk carpeting shall be removed.

- 3.1.22.9. Modifications may be made to the foot pedals to improve the comfort and accessibility to the driver. Dead pedal/foot rest and heel stop may be added.
- 3.1.22.10. If ballast is required to meet the required weight it shall be added as follows:
  - 3.1.22.10.1. All ballast shall be securely mounted on the passenger floor.
  - 3.1.22.10.2. Each segment or stack of ballast shall be fastened with a minimum of two (2) one-half (1/2) inch bolts for each fifty (50) pounds of ballast and positive lock nuts of SAE Grade 5 or better and shall utilize 2" or larger diameter, load distributing washers.
  - 3.1.22.10.3. Holes may be drilled in the passenger floorpan for the purposes of mounting the ballast and the floorpan may be reinforced for that purpose only.
- 3.1.22.11. All cars shall run with both door windows fully open (down).
- 3.1.23. Safety
  - 3.1.23.1. Roll cages shall meet all requirements of current CCR.
  - 3.1.23.2. Steering lock mechanisms must be removed.
  - 3.1.23.3. An electrical master ("kill") switch is mandatory
  - 3.1.23.4. Installation of a fire extinguisher or fire system is required.
  - 3.1.23.5. Glass headlights shall be taped. Rear brake lights may be taped with transparent tape. Turn signals, front parking lights, backup lamps, and side marker lights must be taped.
  - 3.1.23.6. Air bag systems shall be disarmed and all airbag components may be removed.
  - 3.1.23.7. In any automobile where allowed removal of seat belts, upholstery, etc., creates an opening between the driver/passenger compartment and an exposed gas tank, or part thereof, including the filler tube, a metal bulkhead which completely fills such opening shall be installed.