



TYPICAL SPECIFICATIONS

ELECTROCHEMICAL SYSTEM: NICKEL-METAL HYDRIDE

NOMINAL VOLTAGE: 1.2

MAXIMUM OFF-LOAD VOLTAGE: 1.5

RATED CAPACITY: 2.2Ah TO 1.0V AT 21°C (70°F)

AVERAGE WEIGHT: 2.1 oz (60 g)

OPERATING TEMP. RANGE: CHARGE: 0°C TO 50°C (32°F TO 122°F), DISCHARGE: -20°C TO 50°C (-4°F TO 122°F)

ANSI DESIGNATION: 1.2H3

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION

TYPICAL USE	LOAD (OHMS)	DAILY PERIOD	END POINT V	MINIMUM AVERAGE DURATION

TYPICAL MPD HOLDER NO. BHC-2, BHCW, BHCL

SEE MANUFACTURER'S SPECIFICATION SHEET FOR FURTHER INFORMATION.

AWI	DURACELL	EVEREADY	IEC	KODAK	MAXELL	NEDA	PANASONIC	RAYOVAC	TOSHIBA	SONY	VARTA	OTHER
		NH35				1.2H3						