



## Safety Data Sheet

Revision Date: 01/16/18

www.restek.com

2 Letter ISO country code/language code: US/EN

### 1. IDENTIFICATION

**Catalog Number / Product Name:** 30238 / Chloroprene Standard  
**Company:** Restek Corporation  
**Address:** 110 Benner Circle  
Bellefonte, Pa. 16823  
**Phone#:** 814-353-1300  
**Fax#:** 814-353-1309  
**Emergency#:** 800-424-9300 (CHEMTREC)  
703-527-3887 (Outside the US)  
**Email:** www.restek.com  
**Revision Number:** 11  
**Intended use:** For Laboratory use only

### 2. HAZARD(S) IDENTIFICATION

#### Emergency Overview:

GHS Hazard  
Symbols:



**GHS Classification:** Carcinogenicity Category 1B  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1  
Flammable Liquid Category 2  
Acute Toxicity - Inhalation Dust / Mist Category 3  
Acute Toxicity - Dermal Category 3  
Acute Toxicity - Oral Category 3

**GHS Signal Word:** Danger

**GHS Hazard:** Highly flammable liquid and vapour.  
Toxic if swallowed, in contact with skin or if inhaled.  
May cause cancer.  
Causes damage to organs.

**GHS Precautions:**

**Safety Precautions:** Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilation and lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wash hands and skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.

**First Aid Measures:** IF SWALLOWED: Immediately call a POISON CENTER/doctor/....  
IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Specific treatment see section 4.  
Rinse mouth.

Take off immediately all contaminated clothing and wash it before reuse.  
In case of fire: Use extinguishing media in section 5 for extinction.

- Storage:** Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.
- Disposal:** Dispose of contents/container according to section 13 of the SDS.
- Single Exposure Target Organs:** Specific target organ toxicity - Single exposure - STOT SE 1: H370 Causes damage to organs. (C >= 10 %; No information to prove exclusion of certain routes of exposure); Specific target organ toxicity - Single exposure - STOT SE 2: H371 May cause damage to organs. (3 % <= C <10 %; Concentration limits for acute toxicity cannot be translated into GHS from the DSD especially when minimum classifications are given)
- Repeated Exposure Target Organs:** Specific target organ toxicity - Repeated exposure - STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure. (Minimum classification, No information to prove exclusion of certain routes of exposure)

### 3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.5
2-Chloro-1,3-butadiene	126-99-8	204-818-0	0.5

### 4. FIRST-AID MEASURES

- Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
- Eyes:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
- Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

### 5. FIRE- FIGHTING MEASURES

- Extinguishing Media:** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.
- Fire and/or Explosion Hazards:** Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back
- Fire Fighting Methods and Protection:** Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.
- Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide, Hydrogen chloride, Phosgene

### 6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions and Equipment:** Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.
- Methods for Clean-up:** Prevent the spread of any spill to minimize harm to human health and the

environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

## 7. HANDLING AND STORAGE

<b>Handling Technical Measures and Precautions:</b>	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling Avoid contact with material. Ground and bond containers when transferring material "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.
<b>Storage Technical Measures and Conditions:</b>	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition Keep away from heat, sparks, and flame Store in a cool place in original container and protect from sunlight Limit quantity of material stored. Avoid exposure to sunlight or ultraviolet (UV) light sources Keep away from food and drinking water.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA
2-Chloro-1,3-butadiene	126-99-8	300 ppm IDLH	None Known	10 ppm TWA; 36 mg/m3 TWA	25 ppm TWA; 90 mg/m3 TWA

### Personal Protection:

<b>Engineering Measures:</b>	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Facilities storing or using this material should be equipped with an eyewash and safety shower.
<b>Respiratory Protection:</b>	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. A supplied air type respirator may be required. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.
<b>Eye Protection:</b>	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear goggles and a Face shield
<b>Skin Protection:</b>	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance, color:</b>	No data available
<b>Odor:</b>	Mild
<b>Physical State:</b>	Liquid
<b>pH:</b>	Not applicable
<b>Vapor Pressure:</b>	No data available
<b>Vapor Density:</b>	1.1 (air = 1)
<b>Boiling Point (°C):</b>	59.4 °C (HSDB) 64.7 °C at 760 mmHg (HSDB)
<b>Melting Point (°C):</b>	-98 °C

Flash Point (°F):	-4
Flammability:	Highly Flammable Extremely Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature (°C):	464 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.791 - 0.792 g/cm <sup>3</sup> at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	ND
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	32.04

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known. Contamination Ultraviolet light Visible light
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Peroxides
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide Hydrogen chloride Phosgene

## 11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity:	None Known

### Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Highly toxic and may be fatal if swallowed.
Ingestion Toxicity:	Toxic if swallowed. May cause target organ failure and/or death. May be fatal if swallowed.

### Long-Term (Chronic) Health Effects:

Carcinogenicity:	Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Toxic! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs").
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Ingestion:	Toxic if swallowed. May cause target organ failure and/or death.

### Component Toxicological Data:

#### NIOSH:

Chemical Name	CAS No.	LD50/LC50
Chloroprene 1,3-Butadiene, 2-chloro-	126-99-8	Inhalation LC50 Rat : 11800 mg/m <sup>3</sup> /4H; Inhalation LC50 Mouse : 2300 mg/m <sup>3</sup> ; Oral LD50 Rat : 450 mg/kg; Oral LD50 Mouse : 146 mg/kg
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h

**Component Carcinogenic Data:****OSHA:**

<b>Chemical Name</b>	<b>CAS No.</b>	
Chloroprene	126-99-8	Present

**ACGIH:**

<b>Chemical Name</b>	<b>CAS No.</b>	
.beta.-Chloroprene	126-99-8	A2 - Suspected Human Carcinogen

**NIOSH:**

<b>Chemical Name</b>	<b>CAS No.</b>	
.beta.-Chloroprene	126-99-8	potential occupational carcinogen

**NTP:**

<b>Chemical Name</b>	<b>CAS No.</b>
No data available	

**IARC:**

<b>Chemical Name</b>	<b>CAS No.</b>	<b>Group No.</b>
Monograph 71; 1998	126-99-8	Group 2B

**12. ECOLOGICAL INFORMATION**

<b>Overview:</b>	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
<b>Mobility:</b>	No data
<b>Persistence:</b>	No data
<b>Bioaccumulation:</b>	No data
<b>Degradability:</b>	Biodegrades slowly.
<b>Ecological Toxicity Data:</b>	No data available

**13. DISPOSAL CONSIDERATIONS**

<b>Waste Description of Spent Product:</b>	Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.
<b>Disposal Methods:</b>	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
<b>Waste Disposal of Packaging:</b>	Comply with all Local, State, Federal, and Provincial Environmental Regulations.

**14. TRANSPORTATION INFORMATION**

<b>United States:</b>	
<b>DOT Proper Shipping Name:</b>	Methanol
<b>UN Number:</b>	UN1230
<b>Hazard Class:</b>	3
<b>Packing Group:</b>	II

<b>International:</b>	
<b>IATA Proper Shipping Name:</b>	Methanol
<b>UN Number:</b>	UN1230
<b>Hazard Class:</b>	3(6.1)
<b>Packing Group:</b>	II

**Marine Pollutant:** No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

**15. REGULATORY INFORMATION****United States:**

<b>Chemical Name</b>	<b>CAS#</b>	<b>CERCLA</b>	<b>SARA 313</b>	<b>SARA EHS 313</b>	<b>TSCA</b>
methanol	67-56-1	X	X	-	X

2-Chloro-1,3-butadiene 126-99-8 X X - X

**The following chemicals are listed on CA Prop 65:**

Chemical Name	CAS #	Regulation
Chloroprene	126-99-8	Prop 65 Cancer
Methanol	67-56-1	Prop 65 Develop Tox

**State Right To Know Listing:**

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
2-Chloro-1,3-butadiene	126-99-8	X	X	X	X

**16. OTHER INFORMATION**

---

**Prior Version Date:** 07/08/16

**Other Information:** Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

**References:** No data available

**Disclaimer:** Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.