

FULL HEIGHT JAMB STUDS.
ATTACHED BACK-TO-BACK W/
(2) #10-16 SCREWS @ 16"o.c.

SEE DETAIL BELOW
FOR HEADER TO JAMB
CONNECTION

CAP OPENING SIDE OF JAMB
W/ TRACK ATTACHED W/ (1)
#10-16 SCREW @ 16"o.c. IN
EACH LEG.

(2) UNPUNCHED STUDS.
MEMBER SIZES AS REQ'D
PER DESIGN.

CRIPPLE STUDS

(1) #10-16 SCREW
TYP. EACH FLANGE

(2) #10-16
SCREWS @ 16"o.c.

W/(2) H-SERIES UNIVERSAL HEADER
HANGERS ON BOTH SIDES OF
HEADER. USE (6) #10-16 SCREWS
INTO JAMB & (6) #10-16 SCREWS
INTO HEADER. TYP. AT EACH END
OF HEADER.

BOXED HEADER CONNECTION

HEADER TO BACK-TO-BACK JAMB



Engineering Services: (877) 832-3206

Technical Services: (888) 437-3244

The CAD detail library is intended to provide general framing details only and does not replace the judgments and designs of a qualified architect and/or engineer. The details are provided as a starting tool to assist the user in creating and detailing cold-formed steel framing construction details. Each detail including accompanying text must be thoroughly evaluated and approved by a qualified architect or engineer. | Find over 500 CAD details at cad.clarkdietrich.com | © Copyright 2020 ClarkDietrich