

TECHNICLE SPECIFICATION

CHARACTERISITICS	EURO STANDARD	OUR VALUE	
DIMENSION & SURFACE QUALITY			
DIMENSION & SURFACE QUALITY DEVIATION IN THICKNESS STRAIGHTNESS OF SIDES RECTANGULARITY SURFACE FLATNESS SURFACE QUALITY	+ 0.5% + 0.6mm + 0.3% + 0.5% + 0.5% MIN 95%	+ 0.2% + 0.2mm + 0.2% + 0.3% + 0.3% MIN 96%	
PHYSICAL PROPERTIES			
WATER ABSORPTION BEND STRENGTH SCRATCH HARDNESS (MOHS) CRAZING	> 10% > 150Kg./cm2 MIN 3 1 CYCLE	> 14 - 17 % > 200-250kg./cm2 MIN 3 NO CRAZING AT 2 CYCLE	
CHEMICAL PROPERTIES			
STAINING RESISTANCE HOUSEHOLD CHEMICAL	MIN CLASS 2 MIN CLASS B	RESISTANCE TO ALL ACIDS AND ALKALIES & HOUSEHOLD CHEMICALS EXCEPT HYDRO FLURIC ACID	
THERMAL PROPERTIES			
THERMAL SHOKE THERMAL EXPANSION	RESISTANT TO 10 CYCLE MAX-9E-06	CONFORMS CONFORMS	

Packing Detail

Dimension (mm)	Tile Per Box (pcs)	Area Coverage per Box (Sq. ft.)Approx	Area Coverage per Box (Sq. m.)Approx	Weight per Box (Kg.)Approx	Thickness (mm)Approx
108 x 108 mm	80	10.04	0.933	9.600	5.80
150 x 150 mm	44	10.65	0.99	10.500	6.00
100 x 200 mm	50	10.76	1.00	12.500	7.50
200 x 200 mm	25	10.76	1.00	10.500	6.00
75x 300 mm	44	10.65	0.99	13.500	7.50
100 x 300 mm	33	10.65	0.99	13.500	7.50
100 x 400 mm	25	10.76	1.00	14.00	8.00
76 x 152 mm	86	10.66	0.99	12.5	7.30
75 x 200 mm	90	14.53	1.35	14.1	6.00

Note: Size / shade variation is inherent in ceramic tiles, in case of any complain its should be brought to our dealer's notice before laying the tiles.

- colour shown are indicative only. Check actual tiles for exact colour.
- The information contained in this catalogue are accurate as possible, but cannot be considered as legally binding.
- Customers are advised to inspect a sample of the tile before ordering.
- The company reserves the right to change the specifications without prior notice.

Exterior Elevation or interior Walls



















