



**MUTUAL INDUSTRIES, INC.**  
**707 W. GRANGE**  
**PHILADELPHIA, PA 19120**  
**215-927-6000 \* 800-523-0888**  
**215-927-3388 FAX**  
**www.mutualindustries.com**

#3200-8-60  
**5' X 50' TURBIDITY CURTAIN**  
**TYPE 2 DOT SPECIFICATION**

**22oz. Laminated vinyl/polyester fabric meets the following specification:**

<b>CONSTRUCTION</b>	Vinyl Laminate on 1500 Denier 16x16 scrim	
<b>WEIGHT</b>	22oz. / sq.yd	ASTM D-3776
<b>ADHESION</b>	28 lb / 2 inch	ASTM D-751-95 Sec. 43.1.2
<b>GRAB TENSILE</b>	500 x 500 lb / inch	ASTM D-5034
<b>TOUNG TEAR</b>	132 x 143 lb / inch	ASTM D-2261
<b>HYDROSTATIC</b>	881 psi	ASTM D-751-95 Sec 34.2

\*\*\*\*\*

**ADDITIONAL PRODUCT SPECIFICATIONS**

- Heat sealed seams
- 5/8" polypropylene twisted rope edge reinforcement
- 8"x8"x48" EPS foam blocks providing 26.7 lbs / ft buoyancy
- Standard depth = 5 feet
- #5 brass grommets approximately 12" o.c. in edges for laced connection
- Aluminum stress plates at top and bottom corners
- 5/16" galvanized steel ballast chain (100lbs/100ft)
- Galvanized steel safety snap top connection