

The Unicode® Standard

Version 15.0 – Core Specification

To learn about the latest version of the Unicode Standard, see <https://www.unicode.org/versions/latest/>.

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and the publisher was aware of a trademark claim, the designations have been printed with initial capital letters or in all capitals.

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc., in the United States and other countries.

The authors and publisher have taken care in the preparation of this specification, but make no expressed or implied warranty of any kind and assume no responsibility for errors or omissions. No liability is assumed for incidental or consequential damages in connection with or arising out of the use of the information or programs contained herein.

The *Unicode Character Database* and other files are provided as-is by Unicode, Inc. No claims are made as to fitness for any particular purpose. No warranties of any kind are expressed or implied. The recipient agrees to determine applicability of information provided.

© 2022 Unicode, Inc.

All rights reserved. This publication is protected by copyright, and permission must be obtained from the publisher prior to any prohibited reproduction. For information regarding permissions, inquire at <https://www.unicode.org/reporting.html>. For information about the Unicode terms of use, please see <https://www.unicode.org/copyright.html>.

The Unicode Standard / the Unicode Consortium; edited by the Unicode Consortium. — Version 15.0.

Includes index.

ISBN 978-1-936213-32-0 (<https://www.unicode.org/versions/Unicode15.0.0/>)

1. Unicode (Computer character set) I. Unicode Consortium.

QA268.U545 2022

ISBN 978-1-936213-32-0

Published in Mountain View, CA

September 2022

Appendix A

Notational Conventions

This appendix describes the typographic conventions, the extended BNF, and the conventions for describing rendering rules that are used throughout this core specification.

A.1 Typographic Conventions

Code Points

In running text, an individual Unicode code point is expressed as U+n, where *n* is four to six hexadecimal digits, using the digits 0–9 and uppercase letters A–F (for 10 through 15, respectively). Leading zeros are omitted, unless the code point would have fewer than four hexadecimal digits—for example, U+0001, U+0012, U+0123, U+1234, U+12345, U+102345.

- U+0416 is the Unicode code point for the character named CYRILLIC CAPITAL LETTER ZHE.

The *U+* may be omitted for brevity in tables or when denoting ranges. The *U+* is obligatorily omitted when this code point convention is used in rule NR2, for cases where characters have names algorithmically derived from their code points. See “Unicode Name Property” in *Section 4.8, Name*.

A range of Unicode code points is expressed as U+xxxx–U+yyyy or U+xxxx..U+yyyy, where *xxxx* and *yyyy* are the first and last Unicode values in the range, and the en dash or two dots indicate a contiguous range inclusive of the endpoints. For ranges involving supplementary characters, the code points in the ranges are expressed with five or six hexadecimal digits.

- The range U+0900–U+097F contains 128 Unicode code points.
- The Plane 16 private-use characters are in the range U+10000..U+10FFFD.

Character Names

In running text, a formal Unicode name is shown in small capitals (for example, GREEK SMALL LETTER MU), and alternative names (aliases) appear in italics (for example, *umlaut*). Italics are also used to refer to a text element that is not explicitly encoded (for example, *pasekh alef*) or to set off a non-English word (for example, the Welsh word *ynghyd*).

For more information on Unicode character names, see *Section 4.8, Name*.

For notational conventions used in the code charts, see *Section 24.1, Character Names List*.

Character Blocks

When referring to the normative names of character blocks in the text of the standard, the character block name is titlecased and is used with the term “block.” For example:

the Latin Extended-B block

Optionally, an exact range for the character block may also be cited:

the Alphabetic Presentation Forms block (U+FB00..U+FB4F)

These references to normative character block names should not be confused with the headers used throughout the text of the standard, particularly in the block description chapters, to refer to particular ranges of characters. Such headers may be abbreviated in various ways and may refer to subranges within character blocks or ranges that cross character block boundaries. For example:

Latin Ligatures: U+FB00–U+FB06

The definitive list of normative character block names is `Blocks.txt` in the Unicode Character Database.

Sequences

A sequence of two or more code points may be represented by a comma-delimited list, set off by angle brackets. For this purpose, angle brackets consist of U+003C LESS-THAN SIGN and U+003E GREATER-THAN SIGN. Spaces are optional after the comma, and U+ notation for the code point is also optional—for example, “<U+0061, U+0300>”.

When the usage is clear from the context, a sequence of characters may be represented with generic short names, as in “<a, grave>”, or the angle brackets may be omitted.

In contrast to sequences of code points, a sequence of one or more code *units* may be represented by a list set off by angle brackets, but without comma delimitation or U+ notation. For example, the notation “<nn nn nn nn>” represents a sequence of bytes, as for the UTF-8 encoding form of a Unicode character. The notation “<nnnn nnnn>” represents a sequence of 16-bit code units, as for the UTF-16 encoding form of a Unicode character.

Properties and Property Values

The names of properties and property values appear in titlecase, with words connected by an underscore—for example, `General_Category` or `Uppercase_Letter`. In some instances, short names are used, such as `gc = Lu`, which is equivalent to `General_Category = Uppercase_Letter`. Long and short names for all properties and property values are defined in the Unicode Character Database; see also *Section 3.5, Properties*.

Occasionally, and especially when discussing character properties that have single words as names, such as *age* and *block*, the names appear in lowercase italics.

Miscellaneous

Phonemic transcriptions are shown between slashes, as in Khmer /khnyom/.

Phonetic transcriptions are shown between square brackets, using the International Phonetic Alphabet. (Full details on the IPA can be found on the International Phonetic Association’s website, <https://www.internationalphoneticassociation.org/>.)

A leading asterisk is used to represent an incorrect or nonoccurring linguistic form.

In this specification, the word “Unicode” when used alone as a noun refers to the Unicode Standard.

Unambiguous dates of the current common era, such as 1999, are unlabeled. In cases of ambiguity, CE is used. Dates before the common era are labeled with BCE.

The term *byte*, as used in this standard, always refers to a unit of eight bits. This corresponds to the use of the term *octet* in some other standards.

Operators

Operators used in this standard are listed in *Table A-1*.

Table A-1. Operators

Symbol	Meaning
→	is transformed to, or behaves like
↯	is not transformed to
¬	logical not

A.2 Extended BNF

The Unicode Standard and technical reports use an extended BNF format for describing syntax. This format uses elements from the regular expression syntax specified in Unicode Technical Standard #18, “Unicode Regular Expressions”; however, a BNF is not a regular expression, and may be interpreted differently even when looking like one. As different conventions are used for BNF, *Table A-2* lists the notation used here.

Table A-2. Extended BNF

Symbols	Meaning
$x := \dots$	production rule
$x y$	the sequence consisting of x then y
x^*	zero or more occurrences of x
$x?$	zero or one occurrence of x
x^+	one or more occurrences of x
$x \mid y$	either x or y
(x)	for grouping
$\{ x \}$	equivalent to $(x) ?$
"abc"	string literals (“_” is sometimes used to denote space for clarity)
'abc'	string literals (alternative form)
sot	start of text
eot	end of text
$\backslash u\{HHHHHH\}$	Unicode code points within string literals or character classes. Between one and six hexadecimal digits; maximum $\backslash u\{10FFFF\}$.
$\backslash uHHHH$	Unicode BMP code points within string literals or character classes. Exactly four hexadecimal digits.
$U+HHHHHH$	Unicode code point literal: equivalent to “ $\backslash u\{HHHHHH\}$ ”. Between four and six hexadecimal digits; maximum $U+10FFFF$.
$U-00HHHHHH$	Unicode code point literal: equivalent to “ $\backslash u\{HHHHHH\}$ ”. Exactly six hexadecimal digits after the initial two zeroes; maximum $U+10FFFF$. This format was used in ISO 10646 but is now obsolete.
H	Hexadecimal digit, 0-9 or A-F
$[...] , \backslash p\{...\}$	code point or character class (syntax below)

In other environments, such as programming languages or markup, alternative notation for sequences of code points or code units may be used.

Character Classes

A *code point class* is a set of code points. When the code points are all assigned characters, it can also be referred to as a *character class*. Its specification can be based on any of the following:

- A literal code point or a range of literal code points.

- A set of code points having a given value for a given Unicode character property, as defined in the Unicode Character Database (see PropertyAliases.txt and PropertyValueAliases.txt).
- Set operations on character classes.

Further extensions to this specification of character classes are used in some Unicode Standard Annexes and Unicode Technical Reports. Such extensions are described in those documents, as appropriate.

A partial formal BNF syntax for character classes as used in this standard is given by the following:

```

CHARACTER_CLASS := '[' COMPLEMENT? SET ']' | '\p{'
PROP_SPEC '}'
COMPLEMENT := '^'
SET := ITEM (SET_EXTEND)*
ITEM := LITERAL (RANGE_OPERATOR LITERAL)? | CHARACTER_CLASS
RANGE_OPERATOR := '-' | '..'
SET_EXTEND := SET_OPERATOR CHARACTER_CLASS | ',?' ITEM
SET_OPERATOR := '--'
PROP_SPEC := PROP_NAME (RELATION PROP_VALUE)?
RELATION := '=' | '≠'

```

If `COMPLEMENT` is specified, the resulting code point set is the set of all Unicode code points (U+0000..U+10FFFF) except the code points given by `SET`. A `LITERAL` can be a Unicode code point escape sequence, a Unicode code point literal, or a character itself. The operator “--” indicates set difference (older documents may use “-”). A `PROP_NAME` must be a valid Unicode property name or alias. A `PROP_VALUE` must be a valid property value for the `PROP_NAME` it is used with. If a `PROP_NAME` is used by itself, without a `RELATION` and `PROP_VALUE`, the property must be a Boolean property, the relation is assumed to be “=” and the value to be `True`.

In prose where the context makes clear that a property-based character class is being discussed, `\p{PROP_NAME=PROP_VALUE}` may be simplified to `PROP_NAME=PROP_VALUE`.

Whenever any character could be interpreted as a syntax character, it must be escaped. If a space character is used as a literal, it is escaped. The interpretation of spaces differs from

that in regular expressions, so that in the examples below spaces have to be removed in order to obtain equivalent regular expressions. Examples are found in *Table A-3*.

Table A-3. Character Class Examples

Syntax	Matches
[a-z]	English lowercase letters
[a-z -- c]	English lowercase letters except for c
[0-9]	European decimal digits
[\u0030-\u0039]	(same as above, using Unicode escapes)
[0-9 A-F a-f]	hexadecimal digits
[\p{gc=Letter} \p{gc=Nonspacing_Mark}]	all letters and nonspacing marks
[\p{gc=L} \p{gc=Mn}]	(same as above, using abbreviated notation)
[^\p{gc=Unassigned}]	all assigned Unicode characters
[\u{A980}-\u{A9DF} -- \p{gc=Unassigned}]	all assigned characters in the main Javanese range
[\p{Alphabetic}]	all alphabetic characters
[^\p{Line_Break=Infix_Numeric}]	all code points that do not have the line break property of Infix_Numeric

For more information about character classes, see Unicode Technical Standard #18, “Unicode Regular Expressions.”

A.3 Rendering

A figure such as *Figure A-1* depicts how a sequence of characters is typically rendered.

Figure A-1. Example of Rendering

$$\begin{array}{c} \text{A} + \text{ö} \rightarrow \text{Ä} \\ 0041 \quad 0308 \end{array}$$

The sequence under discussion is depicted on the left of the arrow, using representative glyphs and code points below them. A possible rendering of that sequence is depicted on the right side of the arrow.